



FCC DoC TEST REPORT

REPORT NO.: FD990501C03

MODEL NO.: PA3844D

FCC ID: CJ6UPA3844RD

RECEIVED: May 01, 2010

TESTED: May 03 ~ May 05, 2010

ISSUED: May 10, 2010

APPLICANT: Toshiba Corporation

ADDRESS: Digital Media Network Company Ome Complex,
2-9, Suehiro-cho, Tokyo 198-8710k, Japan

ISSUED BY: Bureau Veritas Consumer Products Services (H.K.)
Ltd., Taoyuan Branch

LAB ADDRESS: No. 19, Hwa Ya 2nd Rd., Wen Hwa Tsuen, Kwei
Shan Hsiang, Taoyuan Hsien 333, Taiwan

This test report consists of 26 pages in total. It may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval or endorsement by TAF, NVLAP, NIST or any government agency. The test results in the report only apply to the tested sample. The test results in this report are traceable to the national or international standards.





Table of Contents

1	CERTIFICATION	3
2	SUMMARY OF TEST RESULTS	4
2.1	MEASUREMENT UNCERTAINTY	4
3	GENERAL INFORMATION	5
3.1	GENERAL DESCRIPTION OF EUT	5
3.2	DESCRIPTION OF TEST MODES	5
3.3	DESCRIPTION OF SUPPORT UNITS	6
3.4	CONFIGURATION OF SYSTEM UNDER TEST	7
4	TEST TYPES AND RESULTS	8
4.1	CONDUCTED EMISSION MEASUREMENT	8
4.1.1	LIMITS OF CONDUCTED EMISSION MEASUREMENT	8
4.1.2	TEST INSTRUMENTS	8
4.1.3	TEST PROCEDURES	9
4.1.4	DEVIATION FROM TEST STANDARD	9
4.1.5	TEST SETUP	9
4.1.6	EUT OPERATING CONDITIONS	10
4.1.7	TEST RESULTS	11
4.2	RADIATED EMISSION MEASUREMENT	13
4.2.1	LIMITS OF RADIATED EMISSION MEASUREMENT	13
4.2.2	TEST INSTRUMENTS	14
4.2.3	TEST PROCEDURES	16
4.2.4	DEVIATION FROM TEST STANDARD	16
4.2.5	TEST SETUP	17
4.2.6	EUT OPERATING CONDITIONS	17
4.2.7	TEST RESULTS	18
5	PHOTOGRAPHS OF THE TEST CONFIGURATION	22
6	INFORMATION ON THE TESTING LABORATORIES	25
7	APPENDIX A – MODIFICATION RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB	26



1 CERTIFICATION

PRODUCT: Nano receiver
BRAND: TOSHIBA
MODEL NO.: PA3844D
APPLICANT: Toshiba Corporation
TESTED: May 03 ~ May 05, 2010
TEST SAMPLE: ENGINEERING SAMPLE
STANDARD: FCC Part 15, Subpart B, Class B
CISPR 22: 1997, Class B
ICES-003: 2004, Class B
ANSI C63.4: 2003

The above equipment (model: PA3844D) has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY : Suntee Liu, **DATE :** May 10, 2010
Suntee Liu / Specialist

**TECHNICAL
ACCEPTANCE :** Ban Hsieh, **DATE :** May 10, 2010
Responsible for EMI
Ban Hsieh / Supervisor

APPROVED BY : David Liu, **DATE :** May 10, 2010
David Liu / Senior Engineer



2 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications.

EMISSION			
Standard	Test Type	Result	Remarks
FCC Part 15, Subpart B, Class B CISPR 22: 1997, Class B ICES-003: 2004, Class B	Conducted emission test	PASS	Meet the requirement of limit Minimum passing margin is -6.90 dB at 1.892 MHz
	Radiated emission test	PASS	Meet the requirement of limit Minimum passing margin is -10.23 dB at 780.34 MHz

Note: The limit for radiated test for 30-1000 MHz was performed according to CISPR 22: 1997, which was specified in FCC PART 15 Subpart B 15.109(g). Also the limits of ICES-003: 2004 and CISPR 22: 1997 are same.

2.1 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Uncertainty
Conducted emissions	150kHz ~ 30MHz	2.44 dB
Radiated emissions	30MHz ~ 1GHz	3.84 dB
	Above 1GHz	2.26 dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



A D T

3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Nano receiver
MODEL NO.	PA3844D
POWER SUPPLY	5 Vdc from host equipment
DATA CABLE	NA
ACCESSORY DEVICE	NA

NOTE:

1. The EUT's highest operating frequency is 2480 MHz.
2. The above EUT information was declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

3.2 DESCRIPTION OF TEST MODES

Typical test configuration.



A D T

3.3 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	NOTEBOOK	DELL	PP18L	D1T5W1S 28407620224	QDS-BRCM1019
2	24" LCD MONITOR	DELL	2407WFPb	CN-0FC255-46633 -665-07US	FCC DoC Approved
3	PRINTER	EPSON	B241A	FAPY139300	FCC DoC Approved
4	MODEM	ACEEX	1414V/3	0401008252	IFAXDM1414
5	2.4GHZ WIRELESS OPTICAL MOUSE	TOSHIBA	PA3844	NA	NA

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	NA
2	1.8 m braid shielded wire, VGA connector, with two cores
3	1.8 m shielded cable, terminated with USB connector, w/o core
4	1.2 m braid shielded wire, DB25 & DB9 connector , w/o core
5	NA

NOTE:

1. All power cords of the above support units are non-shielded (1.8 m).
2. Item 5 is provided by the client.

3.4 CONFIGURATION OF SYSTEM UNDER TEST





A D T

4 TEST TYPES AND RESULTS

4.1 CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

TEST STANDARD:

FCC Part 15, Subpart B (section: 15.107)

CISPR 22: 1997 (section 5)

ICES-003: 2004 (Class A: section 5.2)

(Class B: section 5.3)

Frequency (MHz)	Class A (dBuV)		Class B (dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15-0.5	79	66	66-56	56-46
0.5-5	73	60	56	46
5-30	73	60	60	50

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50 MHz.
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESCS30	100291	Dec. 16, 2009	Dec. 15, 2010
RF signal cable Woken	5D-FB	Cable-HYC01-01	Nov. 12, 2009	Nov. 11, 2010
LISN ROHDE & SCHWARZ	ESH3-Z5	100312	Jun. 18, 2009	Jun. 17, 2010
LISN SCHWARZBECK	NNBL 8226-2	8226-142	Jun. 03, 2009	Jun. 02, 2010
Software ADT	ADT_Cond_V7.3.7	NA	NA	NA

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Shielded Room 1.
3. The VCCI Site Registration No. is C-2040.

4.1.3 TEST PROCEDURES


The basic test procedure was in accordance with ANSI C63.4: 2003 (section 7) and CISPR 22 (section 9).

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150 kHz to 30 MHz was searched. Emission levels under Limit - 20dB was not recorded.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.

4.1.5 TEST SETUP



Note:
1. Support units were connected to second LISN.
2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 cm from other units and other metal planes

For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.



A D T

4.1.6 EUT OPERATING CONDITIONS

- a. The notebook ran a test program to enable all functions.
- b. The notebook sent "H" patterns to the monitor, and the monitor displayed them.
- c. The notebook sent "H" patterns to the printer, and the printer printed them.
- d. The notebook sent "H" patterns to the modem.
- e. The EUT linked with the wireless mouse.
- f. Steps b~d were repeated.


4.1.7 TEST RESULTS

INPUT POWER (SYSTEM)	120 Vac, 60 Hz	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	24 deg. C, 57% RH, 981 hPa	PHASE	Line 1
TESTED BY	Ariel Lin		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.12	47.76	18.38	47.88	18.50	66.00	56.00	-18.12	-37.50
2	0.183	0.11	47.23	38.75	47.34	38.86	64.37	54.37	-17.03	-15.51
3	0.244	0.11	44.27	33.83	44.38	33.94	61.97	51.97	-17.58	-18.02
4	0.910	0.17	39.12	33.60	39.29	33.77	56.00	46.00	-16.71	-12.23
5	1.457	0.21	40.74	35.62	40.95	35.83	56.00	46.00	-15.05	-10.17
6	1.762	0.23	42.12	37.39	42.35	37.62	56.00	46.00	-13.65	-8.38
7	3.094	0.30	40.55	28.19	40.85	28.49	56.00	46.00	-15.15	-17.51
8	3.462	0.32	45.43	30.95	45.75	31.27	56.00	46.00	-10.25	-14.73
9	3.764	0.34	44.78	31.16	45.12	31.50	56.00	46.00	-10.88	-14.50

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.




INPUT POWER (SYSTEM)	120 Vac, 60 Hz	6dB BANDWIDTH	9 kHz
ENVIRONMENTAL CONDITIONS	24 deg. C, 57% RH, 981 hPa	PHASE	Line 2
TESTED BY	Ariel Lin		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.150	0.10	47.36	18.22	47.46	18.32	66.00	56.00	-18.54	-37.68
2	0.184	0.10	47.52	39.52	47.62	39.62	64.31	54.31	-16.69	-14.69
3	0.244	0.10	40.88	31.65	40.98	31.75	61.97	51.97	-20.98	-20.21
4	1.341	0.19	41.38	36.10	41.57	36.29	56.00	46.00	-14.43	-9.71
5	1.583	0.21	41.70	37.49	41.91	37.70	56.00	46.00	-14.09	-8.30
6	1.645	0.22	41.90	38.10	42.12	38.32	56.00	46.00	-13.88	-7.68
7	1.892	0.23	43.02	38.87	43.25	39.10	56.00	46.00	-12.75	-6.90
8	3.052	0.28	41.23	28.18	41.51	28.46	56.00	46.00	-14.49	-17.54
9	3.664	0.31	44.70	30.06	45.01	30.37	56.00	46.00	-10.99	-15.63

REMARKS: 1. Q.P. and AV. are abbreviations of quasi-peak and average individually.

2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
3. The emission levels of other frequencies were very low against the limit.
4. Margin value = Emission level - Limit value
5. Correction factor = Insertion loss + Cable loss
6. Emission Level = Correction Factor + Reading Value.





A D T

4.2 RADIATED EMISSION MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION MEASUREMENT

TEST STANDARD:

FCC Part 15, Subpart B (section: 15.109)

CISPR 22: 1997 (section 6)

ICES-003: 2004 (Class A: section 5.4)

(Class B: section 5.5)

Frequency (MHz)	Class A (at 10m)		Class B (at 10m)	
	Quasi-peak (dB _u V/m)		Quasi-peak (dB _u V/m)	
30-230	40		30	
230-1000	47		37	

NOTE: The limit for radiated test was performed according to CISPR 22:1997, which was specified in FCC PART 15B 15.109(g). Also the limits of CISPR 22:1997 is same.

Frequency (MHz)	Class A (at 3m)		Class B (at 3m)	
	Peak (dB _u V/m)	Average (dB _u V/m)	Peak (dB _u V/m)	Average (dB _u V/m)
Above 1000	80	60	74	54

NOTE: 1. The lower limit shall apply at the transition frequencies.
2. Emission level (dB_uV/m) = 20 log Emission level (uV/m).
3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

FREQUENCY RANGE OF RADIATED MEASUREMENT (For unintentional radiators)

Highest frequency generated or used in the device or on which the device operates or tunes (MHz)	Upper frequency of measurement range (MHz)
Below 1.705	30
1.705-108	1000
108-500	2000
500-1000	5000
Above 1000	5th harmonic of the highest frequency or 40 GHz, whichever is lower



A D T

4.2.2 TEST INSTRUMENTS

For frequency below 1 GHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESIB7	100186	Dec. 11, 2009	Dec. 10, 2010
Test Receiver ROHDE & SCHWARZ	ESIB7	100187	Sep. 18, 2009	Sep. 17, 2010
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100076	May 26, 2009	May 25, 2010
BILOG Antenna SCHWARZBECK	VULB9168	9168-148	Apr. 27, 2010	Apr. 26, 2011
BILOG Antenna SCHWARZBECK	VULB9168	9168-149	Apr. 27, 2010	Apr. 26, 2011
HORN Antenna EMCO	3115	5623	Jul. 29, 2009	Jul. 28, 2010
Preamplifier Agilent	8447D	2944A10636	Dec. 10, 2009	Dec. 09, 2010
Preamplifier Agilent	8447D	2944A10637	Dec. 10, 2009	Dec. 09, 2010
Preamplifier Agilent	8449B	3008A01959	Dec. 10, 2009	Dec. 09, 2010
RF signal cable Woken	8D-FB	Cable-Hych1-01	Oct. 24, 2009	Oct. 23, 2010
RF signal cable Woken	8D-FB	Cable-Hych1-02	Oct. 24, 2009	Oct. 23, 2010
Software ADT	ADT_Radiated_V 7.7.03.6	NA	NA	NA
Antenna Tower(V)	MFA-440	9707	NA	NA
Antenna Tower(H)	MFA-440	970705	NA	NA
Turn Table	DS430	50303	NA	NA
Controller	MF7802	074	NA	NA
Controller	MF7802	08093	NA	NA
RF signal cable EAST COST Microwave	HP 160S-29	NA	Feb. 12, 2010	Feb. 11, 2011

NOTE:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 1.
3. The FCC Site Registration No. is 477732.
4. The IC Site Registration No. is IC 7450F-1.
5. The VCCI Site Registration No. is R-1893, G-113.



A D T

For frequency above 1 GHz

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	DATE OF CALIBRATION	DUE DATE OF CALIBRATION
Test Receiver ROHDE & SCHWARZ	ESIB7	100212	May 25, 2009	May 24, 2010
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100076	May 26, 2009	May 25, 2010
HORN Antenna SCHWARZBECK	BBHA 9120 D	9120D-405	Feb. 03, 2010	Feb. 02, 2011
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170148	Jul. 06, 2009	Jul. 05, 2010
Loop Antenna	HFH2-Z2	100070	Jan. 14, 2008	Jan. 13, 2010
Preamplifier Agilent	8447D	2944A10629	Nov. 04, 2009	Nov. 03, 2010
Preamplifier Agilent	8449B	3008A01959	Dec. 10, 2009	Dec. 09, 2010
RF signal cable HUBER+SUHNER	SUCOFLEX 104	23636/6	Aug. 28, 2009	Aug. 27, 2010
RF signal cable HUBER+SUHNER	SUCOFLEX 104	283402/4	Aug. 28, 2009	Aug. 27, 2010
Software ADT.	ADT_Radiated_V7.6.15.9.2	NA	NA	NA
Antenna Tower ADT.	AT100	AT93021702	NA	NA
Turn Table ADT.	TT100.	TT93021702	NA	NA
Controller ADT.	SC100.	SC93021702	NA	NA

NOTE: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Chamber 2.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 686814.
5. The IC Site Registration No. is IC 7450F-2.
6. The VCCI Site Registration No. is G-18.

4.2.3 TEST PROCEDURES

The basic test procedure was in accordance with ANSI C63.4: 2003 (section 8) and CISPR 22 (section 10).

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. **<Frequency Range below 1GHz>**
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. **<Frequency Range above 1GHz>**
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz.

NOTE:


1. The resolution bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasi-peak detection (QP) at frequency below 1 GHz.
2. The resolution bandwidth is 1MHz and video bandwidth of test receiver/spectrum analyzer is 3 MHz for Peak (PK) detection at frequency above 1 GHz. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz for Average (AV) detection at frequency above 1 GHz.
3. For measurement of frequency above 1000 MHz, the EUT was set 3 meters away from the receiver antenna.

4.2.4 DEVIATION FROM TEST STANDARD


No deviation.

4.2.5 TEST SETUP

For frequency below 1 GHz



For frequency above 1 GHz



For the actual test configuration, please refer to the related item – Photographs of the Test Configuration.

4.2.6 EUT OPERATING CONDITIONS


Same as item 4.1.6.

4.2.7 TEST RESULTS

INPUT POWER (SYSTEM)	120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23 deg. C, 65% RH, 981 hPa	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak , 120 kHz
TESTED BY	Whisky Chang		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 10 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	109.70	15.26 QP	30.00	-14.74	4.00 H	143	4.34	10.91
2	117.47	16.04 QP	30.00	-13.96	4.00 H	324	4.21	11.83
3	191.34	13.25 QP	30.00	-16.75	4.00 H	30	1.70	11.55
4	228.28	15.33 QP	30.00	-14.67	4.00 H	192	3.07	12.26
5	239.94	15.05 QP	37.00	-21.95	3.00 H	178	2.28	12.77
6	786.17	25.59 QP	37.00	-11.41	3.00 H	213	0.18	25.41

REMARKS: 1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
 2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
 3. The other emission levels were very low against the limit.
 4. Margin value = Emission level – Limit value.






A D T

INPUT POWER (SYSTEM)	120 Vac, 60 Hz	FREQUENCY RANGE	30-1000 MHz
ENVIRONMENTAL CONDITIONS	23 deg. C, 65% RH, 981 hPa	DETECTOR FUNCTION & BANDWIDTH	Quasi-Peak, 120 kHz
TESTED BY	Whisky Chang		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 10 m								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	119.42	17.04 QP	30.00	-12.96	4.00 V	223	4.58	12.45
2	191.34	17.87 QP	30.00	-12.13	1.00 V	249	5.72	12.15
3	210.78	19.07 QP	30.00	-10.93	1.00 V	18	6.94	12.13
4	243.83	24.89 QP	37.00	-12.11	1.00 V	146	11.28	13.60
5	492.65	20.78 QP	37.00	-16.22	3.00 V	359	0.10	20.69
6	780.34	26.77 QP	37.00	-10.23	2.00 V	306	0.14	26.63

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






A D T

INPUT POWER (SYSTEM)	120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23 deg. C, 65% RH, 981 hPa	DETECTOR FUNCTION & BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Peter Lin		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1163.17	43.69 PK	74.00	-30.31	1.11 H	13	15.45	28.24
2	1163.17	28.65 AV	54.00	-25.35	1.11 H	13	0.41	28.24
3	1497.35	37.41 PK	74.00	-36.59	1.08 H	191	8.26	29.15
4	1497.35	30.71 AV	54.00	-23.29	1.08 H	191	1.56	29.15
5	1662.65	51.99 PK	74.00	-22.01	1.00 H	192	22.38	29.61
6	1662.65	29.66 AV	54.00	-24.34	1.00 H	192	0.05	29.61

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






A D T

INPUT POWER (SYSTEM)	120 Vac, 60 Hz	FREQUENCY RANGE	1-18 GHz
ENVIRONMENTAL CONDITIONS	23 deg. C, 65% RH, 981 hPa	DETECTOR FUNCTION & BANDWIDTH	Peak/Average, 1 MHz
TESTED BY	Peter Lin		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
No.	Freq. (MHz)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Antenna Height (m)	Table Angle (Degree)	Raw Value (dBuV)	Correction Factor (dB/m)
1	1198.02	39.75 PK	74.00	-34.25	1.00 V	166	11.41	28.34
2	1198.02	28.48 AV	54.00	-25.52	1.00 V	166	0.14	28.34
3	1497.30	41.29 PK	74.00	-32.71	1.00 V	6	12.14	29.15
4	1497.30	34.56 AV	54.00	-19.44	1.00 V	6	5.41	29.15
5	2494.08	46.71 PK	74.00	-27.29	1.00 V	195	14.37	32.34
6	2494.08	33.75 AV	54.00	-20.25	1.00 V	195	1.41	32.34

REMARKS:

1. Emission level(dBuV/m)=Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.



5 PHOTOGRAPHS OF THE TEST CONFIGURATION


Conducted Emission Test



Radiated Emission Test
(Frequency below 1 GHz)



Radiated Emission Test (Frequency above 1 GHz)





6 INFORMATION ON THE TESTING LABORATORIES

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

Copies of accreditation certificates of our laboratories obtained from approval agencies can be downloaded from our web site: www.adt.com.tw/index.5/phtml. If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180
Fax: 886-2-26051924

Hsin Chu EMC/RF Lab

Tel: 886-3-5935343
Fax: 886-3-5935342

Hwa Ya EMC/RF/Safety/Telecom Lab

Tel: 886-3-3183232
Fax: 886-3-3185050

Email: service@adt.com.tw

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



A D T

7 APPENDIX A – MODIFICATION RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

--- END ---