



FCC Part 1 Subpart I
FCC Part 2 Subpart J

RF EXPOSURE REPORT

FOR

NETBOOK

MODEL NUMBER: TOSHIBA NB300/ NB305

FCC ID: CJ6UPLL3APC

REPORT NUMBER: 09U12936-1

ISSUE DATE: DECEMBER 02, 2009

Prepared for
TOSHIBA CORPORATION
DIGITAL MEDIA NETWORK COMPANY
OME COMPLEX, 2-9, SUEHIRO-CHO
TOKYO, 198-8710, JAPAN

Prepared by
COMPLIANCE CERTIFICATION SERVICES
47173 BENICIA STREET
FREMONT, CA 94538, U.S.A.
TEL: (510) 771-1000
FAX: (510) 661-0888

NVLAP[®]

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
--	12/02/2009	Initial Issue	T. Chan

TABLE OF CONTENTS

1. ATTESTATION OF TEST RESULTS.....	4
2. METHODOLOGY	5
3. REFERENCES	5
4. FACILITIES AND ACCREDITATION.....	5
5. EUT DESCRIPTION	5
5.1. DESCRIPTION OF EUT.....	5
5.2. DESCRIPTION OF EUT MODULES.....	5
6. REQUIREMENTS - LIMITATION OF EXPOSURE	6
6.1. LIMITS.....	6
6.1.1. FCC RULES.....	6
6.1.2. LIMITS APPLICABLE TO THE EUT.....	6
6.2. EQUATIONS	7
6.3. RESULTS.....	8
6.3.1. CO-LOCATED RESULTS FOR SIMULTANEOUS OPERATION IN THE CELLULAR BAND AND 2.4 GHz BAND	8
6.3.2. CO-LOCATED RESULTS FOR SIMULTANEOUS OPERATION IN THE PCS BAND AND 2.4 GHz BAND	8
6.3.3. CO-LOCATED RESULTS FOR SIMULTANEOUS OPERATION IN THE CELLULAR BAND AND 2.4 GHz BAND	9
6.3.4. CO-LOCATED RESULTS FOR SIMULTANEOUS OPERATION IN THE PCS BAND AND 2.4 GHz BAND	9

1. ATTESTATION OF TEST RESULTS

COMPANY NAME: TOSHIBA CORPORATION
DIGITAL MEDIA NETWORK COMPANY
OME COMPLEX, 2-9, SUEHIRO-CHO
TOKYO, 198-8710, JAPAN

EUT DESCRIPTION: NETBOOK

MODEL: TOSHIBA NB300/ NB305

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC PART 1 SUBPART I & PART 2 SUBPART J	Pass

Compliance Certification Services, Inc. (CCS) calculated the RF Exposure of the above equipment in accordance with the requirements set forth in the above standards, using test results reported in the test report documents referenced below and/or documentation furnished by the applicant. All indications of Pass/Fail in this report are opinions expressed by CCS based on interpretations of these calculations. The results show that the equipment is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation, as described by the referenced documents. This document may not be altered or revised in any way unless done so by CCS and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by CCS will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For CCS By:



THU CHAN
EMC MANAGER
COMPLIANCE CERTIFICATION SERVICES

Calculated By:



CHIN PANG
EMC ENGINEER
COMPLIANCE CERTIFICATION SERVICES

2. METHODOLOGY

All calculations were made in accordance with FCC OET Bulletin 65 Edition 97-01.

3. REFERENCES

Worst-case power, antenna gain and duty cycle data is excerpted from the Qualcomm RF Exposure report applicable to model Gobi2000 for the WWAN module operating in the 850 and 1900 MHz bands.

Worst-case power and antenna gain data is excerpted from Taiwan CCS report number 81029005 for the WLAN module operating in the 2.4 GHz band.

Worst-case power and antenna gain data is excerpted from ADT report number RF971217L11 for the BT module operating in the 2.4 GHz band.

4. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 Benicia Street, Fremont, California, USA.

CCS is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <http://www.ccsemc.com>.

5. EUT DESCRIPTION

5.1. DESCRIPTION OF EUT

The EUT is a Netbook.

5.2. DESCRIPTION OF EUT MODULES

The EUT will be co-located with a WLAN radio module, Toshiba Corporation model number: PA3722U-1MPC, FCC ID: CJ6UPA3722WL, operating in the 2.4 GHz band.

The EUT will be co-located with a BT radio module, Taiyo Yuden Co., Ltd. model number: EYTMECS, FCC ID: RYYEYTMECS, operating in the 2.4 GHz band.

The EUT is a fixed or mobile device, thus a separation distance of at least 20 cm from all persons is applicable.

Other details regarding the EUT are documented in the applicable test reports and product documentation.

6. REQUIREMENTS - LIMITATION OF EXPOSURE

6.1. LIMITS

6.1.1. FCC RULES

§1.1310 The criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093 of this chapter.

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3–3.0	614	1.63	*(100)	6
3.0–30	1842/f	4.89/f	*(900/f ²)	6
30–300	61.4	0.163	1.0	6
300–1500	f/300	6
1500–100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30

TABLE 1—LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)—Continued

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
30–300	27.5	0.073	0.2	30
300–1500	f/1500	30
1500–100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

NOTE 1 TO TABLE 1: Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided he or she is made aware of the potential for exposure.

NOTE 2 TO TABLE 1: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

6.1.2. LIMITS APPLICABLE TO THE EUT

For mobile radio equipment operating in the cellular phone band, the lowest power density limit is calculated using the lowest frequency, as 824 MHz / 1500 = 0.55 mW/cm² (FCC).

For operation in the PCS band and the 2.4 GHz band, from FCC §1.1310 Table 1 (B), the maximum value of S = 1.0 mW/cm².

6.2. EQUATIONS

Power density is given by:

$$S = \text{EIRP} / (4 * \pi * D^2)$$

where

S = Power density in W/m²

EIRP = Equivalent Isotropic Radiated Power in W

D = Separation distance in m

Where applicable (for example, multi-slot cell phone applications) a duty cycle factor may be applied.

$$\text{Source-based time-averaged EIRP} = (\text{DC} / 100) * \text{EIRP}$$

where

DC = Duty Cycle in %, as applicable

EIRP = Equivalent Isotropic Radiated Power in W

For multiple colocated transmitters operating simultaneously in frequency bands where the limit is identical, the total power density is calculated using the total EIRP obtained by summing the Power * Gain product (in linear units) of each transmitter.

$$\text{Total EIRP} = (P1 * G1) + (P2 * G2) + \dots + (Pn * Gn)$$

where

P_x = Power of transmitter x

G_x = Numeric gain of antenna x

For multiple colocated transmitters operating simultaneously in frequency bands where different limits apply, either the lowest limit applicable to the co-located transmitters can be applied or a fraction of the exposure limit is established for each band, such that the sum of the fractions is less than or equal to one.

In the table(s) below, Power and Gain are entered in units of dBm and dBi respectively and conversions to linear forms are used for the calculations.

6.3. RESULTS

6.3.1. CO-LOCATED RESULTS FOR SIMULTANEOUS OPERATION IN THE CELLULAR BAND AND 2.4 GHz BAND

The co-located Power Density is less than .55 W/m², which is the most stringent of the limits for each separate transmitter (.55 W/m² and 1 W/m² for the WWAN and WLAN respectively).

Band	Mode	Separation Distance (m)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	FCC Power Density (mW/cm ²)
850 MHz	WWAN		32.83	-0.60	100	
2.4 GHz	WLAN		25.28	-1.50	100	
Combined		0.20				0.380

6.3.2. CO-LOCATED RESULTS FOR SIMULTANEOUS OPERATION IN THE PCS BAND AND 2.4 GHz BAND

The co-located Power Density is less than 1 W/m², which is the limit for each separate transmitter.

Band	Mode	Separation Distance (m)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	FCC Power Density (mW/cm ²)
1900 MHz	WWAN		29.42	-1.60	100	
2.4 GHz	WLAN		25.28	-1.50	100	
Combined		0.20				0.168

6.3.3. CO-LOCATED RESULTS FOR SIMULTANEOUS OPERATION IN THE CELLULAR BAND AND 2.4 GHz BAND

The co-located Power Density is less than .55 W/m², which is the most stringent of the limits for each separate transmitter (.55 W/m² and 1 W/m² for the WWAN and WLAN respectively).

Band	Mode	Separation Distance (m)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	FCC Power Density (mW/cm ²)
850 MHz	WWAN		32.83	-0.60	100	
2.4 GHz	BT		3.40	1.20	100	
Combined		0.20				0.333

6.3.4. CO-LOCATED RESULTS FOR SIMULTANEOUS OPERATION IN THE PCS BAND AND 2.4 GHz BAND

The co-located Power Density is less than 1 W/m², which is the limit for each separate transmitter.

Band	Mode	Separation Distance (m)	Output Power (dBm)	Antenna Gain (dBi)	Duty Cycle (%)	FCC Power Density (mW/cm ²)
1900 MHz	WWAN		29.42	-1.60	100	
2.4 GHz	BT		3.40	1.20	100	
Combined		0.20				0.121

END OF REPORT