

ATTACHMENT A.
ID LABEL INFORMATION AND LOCATION PHOTOS

1.1 ID Label Information

Following is a copy of the label that will be placed on the rear side of the cabinet.

Figure 3.1 PRODUCT LABEL

Both the FCC ID and compliance statement are included in the product label

•HYUNDAI Model NO : P210 POWER : AC 100-240VAC 3 A FCC ID : CKLP210 Serial No : This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) This device must accept any interference received, including interference that may cause undesired operation. Product complies with DHHS Rules-21 CFR subchapter J-applicable at date of manufacture" HYUNDAI ELECTRONICS AMERICA 166 Baypoint Parkway, San Jose , CA 95134 MANUFACTURED BY HYUNDAI ELECTRONICS IND. CO., LTD. MADE IN KOREA

HYUNDAI

See installation instructions before connecting to the supply.

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions:
 (1) This device may not cause harmful interference, and
 (2) This device must accept any interference received, including interference that may cause undesired operation.

"Product complies with DHHS Rules-21 CFR subchapter J-applicable at date of manufacture"

WARNUNG: Vor öffnen des Gerätes Netzstecker ziehen.
 Disconnect power before opening.

HYUNDAI ELECTRONICS AMERICA
 3101 North 1st Street, San Jose, CA95134
 MANUFACTURED BY
 HYUNDAI ELECTRONICS IND. CO., LTD.
 631 6345 200

MADE IN KOREA



E142408
LISTED
I.T.E.
6K83







ISO
9241-3





LR 65701









This Class B digital apparatus meets all requirements of the Canadian Interference-Causing Equipment Regulations. Cet appareil num.rique de la classe B respecte toutes les exigences du Règlement sur le matériel brouilleur du Canada.

Apparaten skall anslutas till jordat n tuffrag.
 Connect only to a properly grounded outlet.



Model No. :	P210
POWER :	100-240V~
FCC ID :	3.0A 60/50Hz
Serial No. :	CKLP210
Manufactured	MARCH 1999

Die in diesem Ger l entstehende R ngenstrahlung ist durch eine eigensichere Kathodenstrahl hre nach Anlage III R ngenverordnung ausreichend abgeschirmt.
 Beschleunigungsspannung : Max. 27.5kV

TP27

1.2 Label Location Photos

The label shown shall be permanently affixed at a conspicuous location on the device and be readily visible to the user at the time purchase.(Labeling requirements per 2.925)



