

FCC PART 27
FCC PART 22H, PART 24E
MEASUREMENT AND TEST REPORT

For

MFOURTEL MEXICO S.A. DE C.V.

Av. Ejército Nacional 436 Piso 3 Chapultepec Morales Miguel Hidalgo D.F 11570

FCC ID: CLNSS4453

Report Type: Original Report	Product Type: Smart Phone
Test Engineer: Vincent Zheng <i>Vincent zheng</i>	
Report Number: RSZ160809003-00D	
Report Date: 2016-08-25	
Reviewed By: RF Engineer	Rocky Kang <i>Rocky Kang</i>
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
JUSTIFICATION	6
EQUIPMENT MODIFICATIONS	6
SUPPORT EQUIPMENT LIST AND DETAILS	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §1.1307(B) & §2.1093 - RF EXPOSURE INFORMATION.....	8
APPLICABLE STANDARD	8
TEST RESULT	8
FCC §2.1047 - MODULATION CHARACTERISTIC	9
§2.1046; § 22.913 (A); § 24.232 (C); §27.50 (D) (H) - RF OUTPUT POWER.....	10
APPLICABLE STANDARDS.....	10
TEST PROCEDURE	10
TEST EQUIPMENT LIST AND DETAILS.....	11
TEST DATA	11
FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH.....	33
APPLICABLE STANDARDS.....	33
TEST PROCEDURE	33
TEST EQUIPMENT LIST AND DETAILS.....	33
TEST DATA	34
§ 2.1051; § 22.917 (A); § 24.238 (A); §27.53 (H)(M)	62
SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	62
APPLICABLE STANDARDS.....	62
TEST PROCEDURE	62
TEST EQUIPMENT LIST AND DETAILS.....	62
TEST DATA	63
FCC § 2.1053; § 22.917 (A); § 24.238 (A); §27.53 (H)(M) SPURIOUS RADIATED EMISSIONS.....	95
APPLICABLE STANDARDS.....	95
TEST PROCEDURE	95
TEST EQUIPMENT LIST AND DETAILS.....	96
TEST DATA	96
FCC § 22.917 (A); § 24.238 (A); §27.53 (H)(M) - BAND EDGES	99
APPLICABLE STANDARDS.....	99
TEST PROCEDURE	99
TEST EQUIPMENT LIST AND DETAILS.....	100
TEST DATA	100

FCC § 2.1055; § 22.355; § 24.235; §27.54; - FREQUENCY STABILITY147
 APPLICABLE STANDARDS.....147
 TEST PROCEDURE147
 TEST EQUIPMENT LIST AND DETAILS.....148
 TEST DATA148

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *MFOURTEL MEXICO S.A. DE C.V.*'s product, model number: *M4 SS4453(FCC ID: CLNSS4453)* or the "EUT" in this report was a *Smart Phone*, which was measured approximately: 143 mm (L) × 72.2 mm (W) × 8.7 mm (H), rated with input voltage: DC 3.85 V battery or DC 5.0 V from adapter.

Adapter Information:

Model: M4

Input: AC 100-240V, 50/60Hz, 150 mA

Output: DC 5.0V, 1000mA

**All measurement and test data in this report was gathered from production sample serial number: 1602932 (Assigned by applicant). The EUT supplied by the applicant was received on 2016-08-09.*

Objective

This type approval report is prepared on behalf of *MFOURTEL MEXICO S.A. DE C.V.* in accordance with Part 2, Part 22-Subpart H, Part 24-Subpart E and Part 27 of the Federal Communication Commission's rules.

The objective is to determine the compliance of EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, and spurious emission at antenna terminal, spurious radiated emission, frequency stability, and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15B JBP, Part 15.247 DSS & DTS submissions with FCC ID: CLNSS4453.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2, Sub-Part J as well as the following parts:

Part 22 Subpart H - Public Mobile Services

Part 24 Subpart E - Personal Communication Services

Part 27 – Miscellaneous wireless communications services

Applicable Standards: TIA/EIA 603-D.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.81 dB for 30MHz-1GHz and 4.88 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located in the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on October 31, 2103. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2014.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Justification

The EUT was configured for testing according to TIA/EIA-603-D.
The final qualification test was performed with the EUT operating at normal mode.


Equipment Modifications

No modifications were made to the EUT.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Rohde & Schwarz	Wideband Radio Communication Tester	CMW500	1201.002K50
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307 (b)(1), §2.1093	RF Exposure Information	Compliance*
§2.1046; § 22.913 (a); § 24.232 (c); §27.50 (d) (h)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905; § 22.917; § 24.238; §27.53	Occupied Bandwidth	Compliance
§ 2.1051; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053; § 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Spurious Radiated Emissions	Compliance
§ 22.917 (a); § 24.238 (a); §27.53 (h)(m)	Band Edge	Compliance
§ 2.1055; § 22.355; § 24.235; §27.54;	Frequency stability	Compliance

Compliance*: Please refer to SAR report released by BACL, report number: RSZ160809003-20.

FCC §1.1307(b) & §2.1093 - RF EXPOSURE INFORMATION

Applicable Standard

FCC§1.1307, §2.1093.

Test Result

Compliance, please refer to the SAR report: RSZ160809003-20.

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d) , Part 22H & 24E, Part 27 there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

§2.1046; § 22.913 (a); § 24.232 (c); §27.50 (d) (h) - RF OUTPUT POWER**Applicable Standards**

According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (c), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..


According to §27.50(d), the maximum EIRP must not exceed 1Watts (30dBm) for 1710-1755MHz. The peak-to-average power ratio (PAPR) of the transmitter output power must not exceed 13 dB.

According to §27.50(h), the maximum EIRP must not exceed 2Watts (33dBm) for 2500-2570MHz.

According to §27.50(b)(10), the maximum ERP must not exceed 3Watts (34.77dBm) for 746-757 MHz, 776-788 MHz, and 805-806 MHz bands .

Test Procedure*Conducted method:*

The RF output of the transmitter was connected to the CMW500/CMU200 through sufficient attenuation.

*Radiated method:*

TIA603-D section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2015-12-15	2016-12-14
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-07	2017-12-06
HP	Synthesized Sweeper	HP 8341B	2624A00116	2016-07-02	2017-07-01
COM POWER	Dipole Antenna	AD-100	041000	2016-08-18	2017-08-18
A.H. System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2016-04-14	2017-04-14
Sunol Sciences	Horn Antenna	DRH-118	A052604	2014-12-29	2017-12-28
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2015-11-23	2016-11-23
R&S	Wideband Radio Communication tester	CMW500	1201.002K50-146520-wh	2016-04-14	2017-04-14
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2015-10-22	2016-10-22
Ducommun technologies	RF Cable	104PEA	218124002	2015-10-22	2016-10-22
Ducommun technologies	RF Cable	RG-214	1	2016-05-06	2017-05-06
Ducommun technologies	RF Cable	RG-214	2	2016-05-06	2017-05-06
Ducommun technologies	RF Cable	RG-214	3	2016-05-06	2017-05-06
WEINSCHL	10dB Attenuator	5324	AU0709	2016-06-18	2017-06-18

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0kPa

The testing was performed by Vincent Zheng on 2016-08-18.

Conducted Power**Cellular Band (Part 22H)**

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	128	824.2	31.63	38.45
	190	836.6	31.79	38.45
	251	848.8	31.90	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	128	824.2	31.67	29.91	28.09	26.46	38.45
	190	836.6	31.84	30.14	28.46	26.69	38.45
	251	848.8	31.92	30.33	28.61	26.88	38.45

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	128	824.2	27.28	26.70	24.58	22.45	38.45
	190	836.6	27.44	26.85	24.68	22.58	38.45
	251	848.8	27.49	26.95	24.80	22.72	38.45

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band V)	Normal	RMC12.2k		22.47	22.59	22.61
		Rel 6 HSDPA	1	21.50	21.48	21.78
			2	21.45	21.46	21.68
			3	21.43	21.38	21.51
			4	21.40	21.32	21.74
		Rel 6 HSUPA	1	21.79	21.93	21.82
			2	21.48	21.47	21.66
			3	21.36	21.36	21.57
			4	21.41	21.52	21.49
			5	21.42	21.51	21.51

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	28.68	33
	661	1880.0	28.64	33
	810	1909.8	28.46	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
GPRS	512	1850.2	29.07	27.48	26.08	24.69	33
	661	1880.0	28.84	27.53	26.12	24.47	33
	810	1909.8	28.57	27.14	25.86	24.48	33

Mode	Channel	Frequency (MHz)	Average Output Power (dBm)				Limit (dBm)
			1 slot	2 slots	3 slots	4 slots	
EGPRS	512	1850.2	26.99	26.45	25.49	23.36	33
	661	1880.0	26.81	26.33	25.32	22.14	33
	810	1909.8	26.67	26.21	25.12	21.93	33

Mode	Test Condition	Test Mode	3GPP Sub Test	Average Output Power (dBm)		
				Low Frequency	Middle Frequency	High Frequency
WCDMA (Band II)	Normal	RMC12.2k		22.46	22.18	22.11
		Rel 6 HSDPA	1	21.65	21.33	21.27
			2	21.66	21.33	21.27
			3	21.63	21.35	21.24
			4	21.60	21.31	21.27
		Rel 6 HSUPA	1	21.62	21.35	21.31
			2	21.64	21.31	21.27
			3	21.64	21.33	21.28
			4	21.60	21.30	21.26
			5	21.62	21.35	21.31

Peak-to-average ratio (PAR)**Cellular Band**

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.14	13
	Middle	0.17	13
	High	0.16	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	0.19	13
	Middle	0.22	13
	High	0.24	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	1.82	13
	Middle	2.02	13
	High	2.89	13
HSDPA (16QAM)	Low	1.69	13
	Middle	1.88	13
	High	2.12	13
HSUPA (BPSK)	Low	1.97	13
	Middle	1.98	13
	High	2.31	13

PCS Band

Mode	Channel	PAR (dB)	Limit (dB)
GSM	Low	0.13	13
	Middle	0.16	13
	High	0.18	13

Mode	Channel	PAR (dB)	Limit (dB)
EGPRS	Low	0.23	13
	Middle	0.25	13
	High	0.28	13

Mode	Channel	PAR (dB)	Limit (dB)
RMC (BPSK)	Low	2.48	13
	Middle	2.43	13
	High	2.67	13
HSDPA (16QAM)	Low	2.56	13
	Middle	2.38	13
	High	2.26	13
HSUPA (BPSK)	Low	2.47	13
	Middle	2.35	13
	High	2.51	13

Radiated Power**GSM Mode:**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)			
ERP, Cellular Band (Part 22H), Middle Channel										
836.6	95.89	72	1.7	H	29.2	0.30	0.0	28.88	38.45	9.57
836.6	93.76	67	1.8	V	27.0	0.30	0.0	26.72	38.45	11.73
EIRP, PCS Band (Part 24E), Middle Channel										
1880.0	90.68	355	1.3	H	22.0	1.40	7.30	27.90	33	5.10
1880.0	89.76	324	1.9	V	20.5	1.40	7.30	26.40	33	6.60

EDGE Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)			
ERP, Cellular Band (Part 22H), Middle Channel										
836.6	91.29	240	1.2	H	24.6	0.30	0.0	24.28	38.45	14.17
836.6	90.46	309	2.1	V	23.7	0.30	0.0	23.42	38.45	15.03
EIRP, PCS Band (Part 24E), Middle Channel										
1880.0	87.95	344	1.1	H	19.3	1.40	7.30	25.20	33	7.80
1880.0	86.76	322	2.0	V	17.5	1.40	7.30	23.40	33	9.60

WCDMA Mode:

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	S.G. Level (dBm)	Cable loss (dB)	Antenna Gain (dB)			
ERP, WCDMA Band V (Part 22H), Middle Channel										
836.6	87.32	248	1.6	H	20.6	0.30	0.0	20.31	38.45	18.12
836.6	87.86	189	1.1	V	21.1	0.30	0.0	20.82	38.45	17.63
EIRP, WCDMA Band II (Part 24E), Middle Channel										
1880.0	82.43	320	1.2	H	13.8	1.40	7.30	19.70	33	13.3
1880.0	83.64	225	1.6	V	14.4	1.40	7.30	20.30	33	12.7

Note:

All above data were tested with no amplifier.

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

LTE Band 2:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	23.76	23.10	23.71
		RB Size=1, RB Offset=2	23.16	23.02	22.32
		RB Size=1, RB Offset=5	22.81	22.87	22.87
		RB Size=3, RB Offset=0	22.90	22.99	23.12
		RB Size=3, RB Offset=1	23.40	23.35	23.31
		RB Size=3, RB Offset=2	23.55	23.45	22.63
		RB Size=6, RB Offset=0	22.01	22.89	22.29
	16QAM	RB Size=1, RB Offset=0	22.72	22.11	22.55
		RB Size=1, RB Offset=2	22.42	22.79	22.72
		RB Size=1, RB Offset=5	23.14	21.83	23.05
		RB Size=3, RB Offset=0	22.63	22.30	21.57
		RB Size=3, RB Offset=1	22.80	21.97	22.97
		RB Size=3, RB Offset=2	22.27	21.66	21.39
		RB Size=6, RB Offset=0	21.80	21.44	22.31
3.0	QPSK	RB Size=1, RB Offset=0	23.89	23.15	23.07
		RB Size=1, RB Offset=7	23.27	23.41	22.36
		RB Size=1, RB Offset=14	22.39	23.41	22.60
		RB Size=8, RB Offset=0	22.03	22.67	23.04
		RB Size=8, RB Offset=4	22.28	22.40	22.19
		RB Size=8, RB Offset=7	21.59	22.55	22.08
		RB Size=15, RB Offset=0	23.08	22.08	22.41
	16QAM	RB Size=1, RB Offset=0	22.04	22.76	22.87
		RB Size=1, RB Offset=7	21.51	22.08	22.45
		RB Size=1, RB Offset=14	21.85	22.48	22.08
		RB Size=8, RB Offset=0	21.21	21.38	20.92
		RB Size=8, RB Offset=4	21.88	21.09	22.03
		RB Size=8, RB Offset=7	21.22	21.58	20.61
		RB Size=15, RB Offset=0	20.99	20.46	21.50

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	22.68	23.63	23.27
		RB Size=1, RB Offset=12	21.94	23.20	23.30
		RB Size=1, RB Offset=24	23.54	22.50	22.81
		RB Size=12, RB Offset=0	22.08	21.90	22.22
		RB Size=12, RB Offset=6	21.59	22.02	22.24
		RB Size=12, RB Offset=11	21.45	22.15	21.66
		RB Size=25, RB Offset=0	21.36	22.25	21.25
	16QAM	RB Size=1, RB Offset=0	23.62	22.35	22.53
		RB Size=1, RB Offset=12	22.67	22.62	21.52
		RB Size=1, RB Offset=24	22.71	22.13	22.27
		RB Size=12, RB Offset=0	21.23	21.65	20.82
		RB Size=12, RB Offset=6	21.34	20.76	20.38
		RB Size=12, RB Offset=11	20.45	20.81	21.29
		RB Size=25, RB Offset=0	21.90	20.50	21.35
10.0	QPSK	RB Size=1, RB Offset=0	22.67	22.78	23.19
		RB Size=1, RB Offset=24	23.46	22.31	22.69
		RB Size=1, RB Offset=49	22.74	22.17	22.43
		RB Size=25, RB Offset=0	21.72	21.93	22.34
		RB Size=25, RB Offset=12	22.25	21.67	21.97
		RB Size=25, RB Offset=24	22.43	21.68	21.67
		RB Size=50, RB Offset=0	22.32	22.16	22.95
	16QAM	RB Size=1, RB Offset=0	21.40	22.08	21.39
		RB Size=1, RB Offset=24	22.69	22.01	21.76
		RB Size=1, RB Offset=49	22.07	21.92	22.16
		RB Size=25, RB Offset=0	21.04	20.85	21.79
		RB Size=25, RB Offset=12	20.83	20.99	21.76
		RB Size=25, RB Offset=24	21.42	20.83	20.84
		RB Size=50, RB Offset=0	20.77	21.40	21.28

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	22.72	23.14	23.20
		RB Size=1, RB Offset=37	22.94	23.65	23.20
		RB Size=1, RB Offset=74	22.87	22.92	22.99
		RB Size=36, RB Offset=0	22.20	22.40	23.10
		RB Size=36, RB Offset=18	22.39	22.23	22.30
		RB Size=36, RB Offset=37	21.85	21.75	22.14
		RB Size=75, RB Offset=0	21.80	22.54	22.05
	16QAM	RB Size=1, RB Offset=0	21.74	21.88	22.47
		RB Size=1, RB Offset=37	22.94	21.53	22.42
		RB Size=1, RB Offset=74	23.35	21.55	21.11
		RB Size=36, RB Offset=0	21.45	21.70	20.87
		RB Size=36, RB Offset=18	20.49	20.69	21.95
		RB Size=36, RB Offset=37	21.40	20.82	21.13
		RB Size=75, RB Offset=0	21.62	21.01	21.48
20.0	QPSK	RB Size=1, RB Offset=0	23.11	22.45	23.72
		RB Size=1, RB Offset=49	22.81	22.90	23.13
		RB Size=1, RB Offset=99	23.79	23.77	23.52
		RB Size=50, RB Offset=0	22.81	22.61	21.88
		RB Size=50, RB Offset=24	22.03	22.35	22.24
		RB Size=50, RB Offset=49	23.11	23.22	23.77
		RB Size=100, RB Offset=0	22.68	22.74	21.69
	16QAM	RB Size=1, RB Offset=0	22.23	22.99	22.19
		RB Size=1, RB Offset=49	22.93	21.68	22.44
		RB Size=1, RB Offset=99	22.79	22.53	23.11
		RB Size=50, RB Offset=0	21.82	21.34	21.32
		RB Size=50, RB Offset=24	21.47	21.73	20.95
		RB Size=50, RB Offset=49	21.61	21.45	20.64
		RB Size=100, RB Offset=0	21.62	21.05	21.40

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK(1RB Size)	4.32	13	Pass
QPSK (100%RB Size)	6.58	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1880.00	83.74	302	1.2	H	15.1	1.40	7.30	21.00	33
1880.00	83.10	290	2.5	V	13.9	1.40	7.30	19.80	33
3 MHz Bandwidth									
1880.00	83.99	343	1.9	H	15.3	1.40	7.30	21.20	33
1880.00	83.45	171	1.7	V	14.2	1.40	7.30	20.10	33
5 MHz Bandwidth									
1880.00	83.89	132	1.5	H	15.2	1.40	7.30	21.10	33
1880.00	83.38	168	2.0	V	14.1	1.40	7.30	20.00	33
10 MHz Bandwidth									
1880.00	84.38	140	2.1	H	15.7	1.40	7.30	21.60	33
1880.00	82.99	254	1.4	V	13.8	1.40	7.30	19.70	33
15 MHz Bandwidth									
1880.00	83.47	257	1.4	H	14.8	1.40	7.30	20.70	33
1880.00	82.58	86	1.2	V	13.3	1.40	7.30	19.20	33
20 MHz Bandwidth									
1880.00	83.54	249	2.0	H	14.9	1.40	7.30	20.80	33
1880.00	82.92	310	1.5	V	13.7	1.40	7.30	19.60	33

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1880.00	84.22	247	1.1	H	15.5	1.40	7.30	21.40	33
1880.00	83.34	21	1.3	V	14.1	1.40	7.30	20.00	33
3 MHz Bandwidth									
1880.00	83.97	322	1.8	H	15.3	1.40	7.30	21.20	33
1880.00	83.89	121	1.9	V	14.7	1.40	7.30	20.60	33
5 MHz Bandwidth									
1880.00	84.30	2	1.3	H	15.6	1.40	7.30	21.50	33
1880.00	83.99	291	2.2	V	14.7	1.40	7.30	20.60	33
10 MHz Bandwidth									
1880.00	84.10	262	1.5	H	15.4	1.40	7.30	21.30	33
1880.00	83.63	173	1.8	V	14.4	1.40	7.30	20.30	33
15 MHz Bandwidth									
1880.00	83.87	267	1.1	H	15.2	1.40	7.30	21.10	33
1880.00	83.73	238	1.5	V	14.5	1.40	7.30	20.40	33
20 MHz Bandwidth									
1880.00	83.83	48	2.0	H	15.2	1.40	7.30	21.10	33
1880.00	83.01	357	2.4	V	13.8	1.40	7.30	19.70	33

LTE Band 4:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
1.4	QPSK	RB Size=1, RB Offset=0	22.93	22.91	23.01
		RB Size=1, RB Offset=2	22.93	22.64	23.40
		RB Size=1, RB Offset=5	23.12	22.43	23.92
		RB Size=3, RB Offset=0	23.65	23.53	23.37
		RB Size=3, RB Offset=1	22.55	23.47	23.11
		RB Size=3, RB Offset=2	23.17	22.81	23.75
		RB Size=6, RB Offset=0	21.62	21.59	22.10
	16QAM	RB Size=1, RB Offset=0	22.60	22.52	22.25
		RB Size=1, RB Offset=2	22.20	22.53	22.37
		RB Size=1, RB Offset=5	22.15	21.85	22.72
		RB Size=3, RB Offset=0	21.83	23.01	21.86
		RB Size=3, RB Offset=1	21.36	22.48	22.13
		RB Size=3, RB Offset=2	22.02	21.84	22.01
		RB Size=6, RB Offset=0	20.62	21.42	20.28
3.0	QPSK	RB Size=1, RB Offset=0	22.50	23.13	23.36
		RB Size=1, RB Offset=7	23.23	22.43	22.57
		RB Size=1, RB Offset=14	23.10	22.71	23.67
		RB Size=8, RB Offset=0	22.18	21.65	22.16
		RB Size=8, RB Offset=4	22.28	21.59	22.87
		RB Size=8, RB Offset=7	22.00	22.21	21.95
		RB Size=15, RB Offset=0	21.65	22.42	21.66
	16QAM	RB Size=1, RB Offset=0	22.02	21.45	22.47
		RB Size=1, RB Offset=7	21.81	22.33	21.29
		RB Size=1, RB Offset=14	22.39	21.99	22.31
		RB Size=8, RB Offset=0	21.18	20.78	20.86
		RB Size=8, RB Offset=4	20.40	20.52	21.69
		RB Size=8, RB Offset=7	20.40	21.08	20.98
		RB Size=15, RB Offset=0	21.26	20.96	20.44

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	22.64	22.83	23.34
		RB Size=1, RB Offset=12	23.96	23.19	23.26
		RB Size=1, RB Offset=24	23.44	23.47	23.26
		RB Size=12, RB Offset=0	22.10	21.72	22.60
		RB Size=12, RB Offset=6	22.34	22.24	22.18
		RB Size=12, RB Offset=11	22.00	21.34	21.81
		RB Size=25, RB Offset=0	21.88	22.16	22.58
	16QAM	RB Size=1, RB Offset=0	22.53	22.16	22.57
		RB Size=1, RB Offset=12	21.57	21.90	22.92
		RB Size=1, RB Offset=24	21.98	22.32	22.64
		RB Size=12, RB Offset=0	20.70	21.01	21.91
		RB Size=12, RB Offset=6	21.47	20.81	21.45
		RB Size=12, RB Offset=11	21.32	21.46	21.54
		RB Size=25, RB Offset=0	21.51	20.50	21.84
10.0	QPSK	RB Size=1, RB Offset=0	22.83	23.02	23.30
		RB Size=1, RB Offset=24	23.21	22.85	23.10
		RB Size=1, RB Offset=49	24.08	22.91	22.48
		RB Size=25, RB Offset=0	22.34	21.96	22.41
		RB Size=25, RB Offset=12	22.12	21.84	22.70
		RB Size=25, RB Offset=24	21.71	22.25	21.95
		RB Size=50, RB Offset=0	21.54	21.95	22.02
	16QAM	RB Size=1, RB Offset=0	21.74	22.70	21.83
		RB Size=1, RB Offset=24	21.55	21.63	21.69
		RB Size=1, RB Offset=49	22.89	22.25	22.10
		RB Size=25, RB Offset=0	21.38	20.99	21.86
		RB Size=25, RB Offset=12	21.53	21.45	20.46
		RB Size=25, RB Offset=24	20.91	21.24	20.73
		RB Size=50, RB Offset=0	21.28	20.84	20.99

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	22.61	23.20	23.56
		RB Size=1, RB Offset=37	22.97	23.37	22.84
		RB Size=1, RB Offset=74	23.33	23.19	23.18
		RB Size=36, RB Offset=0	21.90	22.73	22.33
		RB Size=36, RB Offset=18	22.39	21.90	22.83
		RB Size=36, RB Offset=37	21.94	21.60	22.29
		RB Size=75, RB Offset=0	22.25	21.90	22.59
	16QAM	RB Size=1, RB Offset=0	22.16	21.81	23.28
		RB Size=1, RB Offset=37	21.71	21.58	23.27
		RB Size=1, RB Offset=74	22.26	22.52	22.33
		RB Size=36, RB Offset=0	20.45	21.05	21.46
		RB Size=36, RB Offset=18	21.57	21.36	21.78
		RB Size=36, RB Offset=37	20.53	20.74	21.25
		RB Size=75, RB Offset=0	20.87	21.14	21.22
20.0	QPSK	RB Size=1, RB Offset=0	23.99	24.10	23.92
		RB Size=1, RB Offset=49	21.78	22.39	23.14
		RB Size=1, RB Offset=99	22.86	22.40	22.11
		RB Size=50, RB Offset=0	22.36	22.29	21.83
		RB Size=50, RB Offset=24	21.98	21.84	21.97
		RB Size=50, RB Offset=49	23.86	23.95	23.81
		RB Size=100, RB Offset=0	21.69	21.37	21.69
	16QAM	RB Size=1, RB Offset=0	21.58	22.90	22.67
		RB Size=1, RB Offset=49	22.82	22.57	21.83
		RB Size=1, RB Offset=99	22.98	22.44	22.01
		RB Size=50, RB Offset=0	20.44	21.10	21.74
		RB Size=50, RB Offset=24	21.53	20.78	21.77
		RB Size=50, RB Offset=49	21.66	21.10	21.13
		RB Size=100, RB Offset=0	21.58	20.97	20.73

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK(1RB Size)	4.43	13	Pass
QPSK (100%RB Size)	6.51	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	84.02	253	1.6	H	15.2	1.60	6.90	20.50	30
1732.50	83.62	99	2.1	V	14.4	1.60	6.90	19.70	30
3 MHz Bandwidth									
1732.50	84.22	169	1.9	H	15.4	1.60	6.90	20.70	30
1732.50	83.30	178	2.4	V	14.1	1.60	6.90	19.40	30
5 MHz Bandwidth									
1732.50	84.03	82	1.1	H	15.2	1.60	6.90	20.50	30
1732.50	82.73	88	1.3	V	13.5	1.60	6.90	18.80	30
10 MHz Bandwidth									
1732.50	83.82	281	1.1	H	15.0	1.60	6.90	20.30	30
1732.50	83.88	200	2.1	V	14.7	1.60	6.90	20.00	30
15 MHz Bandwidth									
1732.50	83.77	150	2.1	H	15.0	1.60	6.90	20.30	30
1732.50	82.76	23	1.8	V	13.5	1.60	6.90	18.80	30
20 MHz Bandwidth									
1732.50	83.50	257	1.3	H	14.7	1.60	6.90	20.00	30
1732.50	82.46	335	2.4	V	13.2	1.60	6.90	18.50	30

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
1.4 MHz Bandwidth									
1732.50	83.78	112	1.6	H	15.0	1.60	6.90	20.30	30
1732.50	83.71	286	1.4	V	14.5	1.60	6.90	19.80	30
3 MHz Bandwidth									
1732.50	83.88	233	2.3	H	15.1	1.60	6.90	20.40	30
1732.50	82.99	260	2.0	V	13.8	1.60	6.90	19.10	30
5 MHz Bandwidth									
1732.50	84.48	302	2.0	H	15.7	1.60	6.90	21.00	30
1732.50	83.78	140	2.0	V	14.6	1.60	6.90	19.90	30
10 MHz Bandwidth									
1732.50	83.57	173	2.5	H	14.8	1.60	6.90	20.10	30
1732.50	83.87	282	1.1	V	14.7	1.60	6.90	20.00	30
15 MHz Bandwidth									
1732.50	84.34	203	1.4	H	15.5	1.60	6.90	20.80	30
1732.50	84.06	100	1.8	V	14.8	1.60	6.90	20.10	30
20 MHz Bandwidth									
1732.50	83.93	67	1.3	H	15.1	1.60	6.90	20.40	30
1732.50	84.75	350	1.8	V	15.5	1.60	6.90	20.80	30

LTE Band 7:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	23.48	23.24	23.10
		RB Size=1, RB Offset=12	23.59	23.13	22.02
		RB Size=1, RB Offset=24	23.87	23.89	23.02
		RB Size=12, RB Offset=0	22.53	22.48	22.84
		RB Size=12, RB Offset=6	22.33	22.66	21.49
		RB Size=12, RB Offset=11	22.29	22.72	21.94
		RB Size=25, RB Offset=0	22.35	22.28	22.32
	16QAM	RB Size=1, RB Offset=0	22.16	23.14	22.51
		RB Size=1, RB Offset=12	22.65	23.14	21.71
		RB Size=1, RB Offset=24	23.13	23.13	22.42
		RB Size=12, RB Offset=0	22.01	21.40	21.60
		RB Size=12, RB Offset=6	21.29	21.60	22.00
		RB Size=12, RB Offset=11	21.74	22.07	20.98
		RB Size=25, RB Offset=0	21.24	22.21	21.95
10.0	QPSK	RB Size=1, RB Offset=0	23.04	22.90	22.44
		RB Size=1, RB Offset=24	22.97	23.43	22.93
		RB Size=1, RB Offset=49	22.47	22.91	22.09
		RB Size=25, RB Offset=0	22.23	22.66	22.59
		RB Size=25, RB Offset=12	22.82	22.54	21.92
		RB Size=25, RB Offset=24	22.57	22.68	22.02
		RB Size=50, RB Offset=0	22.48	22.29	21.83
	16QAM	RB Size=1, RB Offset=0	22.98	22.36	21.15
		RB Size=1, RB Offset=24	23.22	21.71	21.25
		RB Size=1, RB Offset=49	22.71	22.56	21.45
		RB Size=25, RB Offset=0	22.03	22.03	20.14
		RB Size=25, RB Offset=12	21.53	21.15	21.20
		RB Size=25, RB Offset=24	21.73	22.29	20.46
		RB Size=50, RB Offset=0	20.67	21.52	21.27

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
15.0	QPSK	RB Size=1, RB Offset=0	23.29	22.85	22.46
		RB Size=1, RB Offset=37	23.28	22.56	22.70
		RB Size=1, RB Offset=74	22.54	23.41	22.55
		RB Size=36, RB Offset=0	22.72	22.53	22.27
		RB Size=36, RB Offset=18	23.10	23.14	21.57
		RB Size=36, RB Offset=37	22.91	22.29	21.87
		RB Size=75, RB Offset=0	22.65	23.24	21.74
	16QAM	RB Size=1, RB Offset=0	22.42	22.63	22.64
		RB Size=1, RB Offset=37	21.79	22.19	22.06
		RB Size=1, RB Offset=74	22.84	22.75	21.94
		RB Size=36, RB Offset=0	21.18	21.08	21.64
		RB Size=36, RB Offset=18	21.53	20.88	21.30
		RB Size=36, RB Offset=37	21.07	21.53	20.50
		RB Size=75, RB Offset=0	22.37	21.29	21.58
20.0	QPSK	RB Size=1, RB Offset=0	23.38	22.71	22.53
		RB Size=1, RB Offset=49	23.83	23.99	23.81
		RB Size=1, RB Offset=99	22.09	23.73	22.72
		RB Size=50, RB Offset=0	23.23	21.87	21.92
		RB Size=50, RB Offset=24	21.83	23.25	21.65
		RB Size=50, RB Offset=49	22.63	23.93	22.15
		RB Size=100, RB Offset=0	22.42	22.80	22.60
	16QAM	RB Size=1, RB Offset=0	22.75	22.91	23.18
		RB Size=1, RB Offset=49	22.48	23.34	22.25
		RB Size=1, RB Offset=99	21.50	22.51	21.63
		RB Size=50, RB Offset=0	21.86	21.24	21.25
		RB Size=50, RB Offset=24	21.44	21.11	20.96
		RB Size=50, RB Offset=49	21.98	22.58	21.72
		RB Size=100, RB Offset=0	21.45	21.83	20.85

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK(1RB Size)	4.62	13	Pass
QPSK (100%RB Size)	7.03	13	Pass

EIRP:**QPSK:**

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
2535.00	80.34	195	2.1	H	14.0	1.70	8.60	20.90	33
2535.00	81.30	296	2.4	V	14.6	1.70	8.60	21.50	33
10 MHz Bandwidth									
2535.00	79.70	294	2.5	H	13.3	1.70	8.60	20.20	33
2535.00	80.68	228	2.1	V	14.0	1.70	8.60	20.90	33
15 MHz Bandwidth									
2535.00	79.95	270	2.1	H	13.6	1.70	8.60	20.50	33
2535.00	81.02	270	1.2	V	14.3	1.70	8.60	21.20	33
20 MHz Bandwidth									
2535.00	79.70	286	1.0	H	13.3	1.70	8.60	20.20	33
2535.00	80.52	3	1.5	V	13.8	1.70	8.60	20.70	33

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
2535.00	79.16	171	1.6	H	12.8	1.70	8.60	19.70	33
2535.00	80.96	279	1.5	V	14.3	1.70	8.60	21.20	33
10 MHz Bandwidth									
2535.00	79.86	120	1.5	H	13.5	1.70	8.60	20.40	33
2535.00	80.56	331	2.4	V	13.8	1.70	8.60	20.70	33
15 MHz Bandwidth									
2535.00	79.88	112	1.0	H	13.5	1.70	8.60	20.40	33
2535.00	81.28	98	2.2	V	14.6	1.70	8.60	21.50	33
20 MHz Bandwidth									
2535.00	80.14	53	2.3	H	13.7	1.70	8.60	20.60	33
2535.00	81.26	18	1.2	V	14.6	1.70	8.60	21.50	33

LTE Band 13:**Maximum Output Power**

Bandwidth (MHz)	Modulation	RB size/RB Offset	Low Channel (dBm)	Middle Channel (dBm)	High Channel (dBm)
5.0	QPSK	RB Size=1, RB Offset=0	24.01	24.34	24.49
		RB Size=1, RB Offset=12	25.39	24.68	24.44
		RB Size=1, RB Offset=24	24.48	25.09	24.31
		RB Size=12, RB Offset=0	23.42	23.20	23.50
		RB Size=12, RB Offset=6	23.00	23.06	22.73
		RB Size=12, RB Offset=11	24.06	22.94	23.20
		RB Size=25, RB Offset=0	23.10	23.59	24.05
	16QAM	RB Size=1, RB Offset=0	24.23	23.78	23.80
		RB Size=1, RB Offset=12	23.94	24.06	24.30
		RB Size=1, RB Offset=24	23.27	24.11	23.80
		RB Size=12, RB Offset=0	23.31	22.28	22.44
		RB Size=12, RB Offset=6	22.84	22.68	22.85
		RB Size=12, RB Offset=11	22.38	23.14	22.42
		RB Size=25, RB Offset=0	22.54	22.72	22.28
10.0	QPSK	RB Size=1, RB Offset=0	/	24.93	/
		RB Size=1, RB Offset=24	/	23.69	/
		RB Size=1, RB Offset=49	/	23.38	/
		RB Size=25, RB Offset=0	/	23.08	/
		RB Size=25, RB Offset=12	/	22.89	/
		RB Size=25, RB Offset=24	/	24.90	/
		RB Size=50, RB Offset=0	/	23.32	/
	16QAM	RB Size=1, RB Offset=0	/	23.40	/
		RB Size=1, RB Offset=24	/	22.94	/
		RB Size=1, RB Offset=49	/	22.67	/
		RB Size=25, RB Offset=0	/	22.84	/
		RB Size=25, RB Offset=12	/	22.20	/
		RB Size=25, RB Offset=24	/	22.62	/
		RB Size=50, RB Offset=0	/	21.99	/

Peak-to-average ratio (PAR)

Modulation	Middle Channel (dB)	PAR Limit (dB)	Result
QPSK(1RB Size)	4.81	13	Pass
QPSK (100%RB Size)	7.04	13	Pass

QPSK:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
Middle Channel									
5 MHz Bandwidth									
782	87.35	94	2.2	H	20.6	0.30	0.0	20.34	34.77
782	88.41	31	1.4	V	21.7	0.30	0.0	21.37	34.77
10 MHz Bandwidth									
782	87.68	255	1.1	H	21.0	0.30	0.0	20.67	34.77
782	88.27	339	1.1	V	21.5	0.30	0.0	21.23	34.77

16QAM:

Frequency (MHz)	Receiver Reading (dBμV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		
5 MHz Bandwidth									
782	88.49	266	1.4	H	21.8	0.30	0.0	21.48	34.77
782	87.76	146	1.7	V	21.0	0.30	0.0	20.72	34.77
10 MHz Bandwidth									
782	88.22	267	2.5	H	21.5	0.30	0.0	21.21	34.77
782	87.94	112	2.4	V	21.2	0.30	0.0	20.90	34.77

Note:

All above data were tested with no amplifier

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §2.1049, §22.917, §22.905 & §24.238 & §27.53 - OCCUPIED BANDWIDTH


Applicable Standards

FCC 47 §2.1049, §22.917, §22.905, §24.238 and §27.53.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 5 kHz (Cellular /PCS) & 100 kHz (WCDMA) and the 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2016-04-14	2017-04-14
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2015-11-23	2016-11-23
R&S	Wideband Radio Communication tester	CMW500	1201.002K50-146520-wh	2016-04-14	2017-04-14
HONOVA	Power Splitter	HPDL-2W-B-NF	N/A	2016-06-12	2017-06-12
Ducommun technologies	RF Cable	RG-214	4	2016-05-06	2017-05-06
WEINSCHTEL	10dB Attenuator	5324	AU0709	2016-06-18	2017-06-18

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	24~27℃
Relative Humidity:	50~53 %
ATM Pressure:	100.0~101.0kPa

The testing was performed by Vincent Zheng from 2016-08-17 to 2016-08-25.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	836.6	244.5	318.6
EGPRS(8PSK)	836.6	244.5	314.6

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	836.6	4.15	4.73
HSUPA (BPSK)	836.6	4.15	4.73
HSDPA (16QAM)	836.6	4.15	4.73


PCS Band (Part 24E)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Emission Bandwidth (kHz)
GSM(GMSK)	1880.0	242.5	312.6
EGPRS(8PSK)	1880.0	244.5	314.6


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
RMC (BPSK)	1880.0	4.15	4.73
HSUPA (BPSK)	1880.0	4.13	4.73
HSDPA (16QAM)	1880.0	4.15	4.73

Cellular Band (Part 22H)


99% Occupied & 26 dB Emissions Bandwidth for GSM (GMSK) Mode




99% Occupied & 26 dB Emissions Bandwidth for EDGE Mode



99% Occupied & 26 dB Emissions Bandwidth for WCDMA (BPSK) Mode



99% Occupied & 26 dB Emissions Bandwidth for HSUPA (BPSK) Mode



Delta 1 [T1] RBW 100 kHz RF Att 40 dB
 Ref Lvl -0.01 dB VBW 300 kHz
 34.5 dBm 4.72945892 MHz SWT 5 ms Unit dBm

4.5 dB Offset
 D1 17.38 dBm
 D2 -8.62 dBm
 1MAX
 1

1 [T1] -8.28 dBm
 1 [T1] -6.01 dBm
 4.72945892 MHz
 4.14829659 MHz
 834.22529050 MHz
 834.50581162 MHz
 838.65410822 MHz
 5.56 dBm
 5.40 dBm
 OP8
 12 [T1]
 1

Center 836.6 MHz 1 MHz/ Span 10 MHz

Date: 23.AUG.2016 17:54:35

Ref Lvl -3.14 dBm RBW 5 kHz RF Att 40 dB

33.5 dBm 1.87984469 GHz SWT 100 ms Unit dBm

4.5 dB Offset

D1 22.68 dBm

D2 -3.32 dBm

1MAX

1MA

Marker 1 [T1]

1.87984469 GHz

7.58 dBm

1.87988076 GHz

7.29 dBm

1.88012325 GHz


6.15 dB

312.62525050 kHz


Center 1.88 GHz 100 kHz/ Span 1 MHz



Date: 20.AUG.2016 15:14:02

99% Occupied & 26 dB Emissions Bandwidth for EGPRS Mode





99% Occupied & 26 dB Emissions Bandwidth for WCDMA (BPSK) Mode







99% Occupied & 26 dB Emissions Bandwidth for HSUPA (BPSK) Mode**99% Occupied & 26 dB Emissions Bandwidth for HSDPA (16QAM) Mode**



LTE Band 2: (Middle Channel)

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.111	1.313
	16QAM	1.105	1.330
3.0	QPSK	2.705	2.958
	16QAM	2.693	2.933
5.0	QPSK	4.529	5.010
	16QAM	4.529	4.990
10.0	QPSK	8.938	9.739
	16QAM	8.938	9.659
15.0	QPSK	13.527	14.910
	16QAM	13.527	14.790
20.0	QPSK	17.956	19.319
	16QAM	17.956	19.479


QPSK (1.4 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (1.4 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**

QPSK (3.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (3.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**


QPSK (5.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (5.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**



QPSK (10.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (10.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**

QPSK (15.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel





16-QAM (15.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel







QPSK (20.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (20.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**



LTE Band 4: (Middle Channel)



Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
1.4	QPSK	1.105	1.296
	16QAM	1.105	1.319
3.0	QPSK	2.705	2.934
	16QAM	2.705	2.946
5.0	QPSK	4.509	5.010
	16QAM	4.529	5.030
10.0	QPSK	8.978	9.780
	16QAM	8.978	9.459
15.0	QPSK	13.587	14.970
	16QAM	13.587	14.910
20.0	QPSK	17.956	19.399
	16QAM	18.036	19.479



QPSK (1.4 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (1.4 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**

QPSK (3.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (3.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**

QPSK (5.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (5.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**



QPSK (10.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (10.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**



QPSK (15.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (15.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**



QPSK (20.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (20.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**



LTE Band 7: (Middle Channel)

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
5.0	QPSK	4.529	5.010
	16QAM	4.529	5.010
10.0	QPSK	8.978	9.780
	16QAM	8.978	9.739
15.0	QPSK	13.467	15.429
	16QAM	13.467	14.429
20.0	QPSK	18.036	19.559
	16QAM	17.956	19.399

QPSK (5.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (5.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**



QPSK (10.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (10.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**



QPSK (15.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (15.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**

QPSK (20.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (20.0 MHz) -99% Occupied & 26 dB Bandwidth, Middle channel**

LTE Band 13: (Middle Channel)

Bandwidth (MHz)	Modulation	99% Occupied Bandwidth (MHz)	26 dB Emission Bandwidth (MHz)
5.0	QPSK	4.529	5.030
	16QAM	4.569	5.050
10.0	QPSK	9.018	9.780
	16QAM	9.018	9.860

QPSK (5.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (5.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**

QPSK (10.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**16-QAM (10.0 MHz) - 99% Occupied & 26 dB Bandwidth, Middle channel**

§ 2.1051; § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standards

FCC §2.1051, §22.917(a) and §24.238(a) and §27.53(h)(m).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2016-04-14	2017-04-14
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2015-11-23	2016-11-23
R&S	Wideband Radio Communication tester	CMW500	1201.002K50-146520-wh	2016-04-14	2017-04-14
HONOVA	Power Splitter	HPDL-2W-B-NF	N/A	2016-06-12	2017-06-12
Ducommun technologies	RF Cable	RG-214	4	2016-05-06	2017-05-06
WEINSCHL	10dB Attenuator	5324	AU0709	2016-06-18	2017-06-18

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	24~27℃
Relative Humidity:	50~53 %
ATM Pressure:	100.0~101.0kPa

The testing was performed by Vincent Zheng from 2016-08-17 to 2016-08-23.


Please refer to the following plots.



Cellular Band (Part 22H)

30 MHz – 1 GHz (GSM Mode)




1 GHz – 10 GHz (GSM Mode)




30 MHz – 1 GHz (WCDMA Mode)**1 GHz – 10 GHz (WCDMA Mode)**



PCS Band (Part 24E)

30 MHz – 1 GHz (GSM Mode)




1 GHz – 2 GHz (GSM Mode)




2 GHz – 20 GHz (GSM Mode)**30 MHz – 1 GHz (WCDMA Mode)**

1 GHz – 2 GHz (WCDMA Mode)




Fundamental test

2 GHz – 20 GHz (WCDMA Mode)




LTE Band 2:


30 MHz - 1 GHz (1.4 MHz, Middle Channel)




1 GHz - 2 GHz (1.4 MHz, Middle Channel)




2 GHz – 20 GHz (1.4 MHz, Middle Channel)




30 MHz - 1 GHz (3.0 MHz, Middle Channel)




1 GHz – 2 GHz (3.0 MHz, Middle Channel)




2 GHz – 20 GHz (3.0 MHz, Middle Channel)




30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz - 2 GHz (5.0 MHz, Middle Channel)




2 GHz – 20 GHz (5.0 MHz, Middle Channel)




30 MHz - 1 GHz (10.0 MHz, Middle Channel)




1 GHz – 2 GHz (10.0 MHz, Middle Channel)


Fundamental test



2 GHz – 20 GHz (10.0 MHz, Middle Channel)

30 MHz - 1 GHz (15.0 MHz, Middle Channel)




1 GHz - 2 GHz (15.0 MHz, Middle Channel)




2 GHz – 20 GHz (15.0 MHz, Middle Channel)**30 MHz - 1 GHz (20.0 MHz, Middle Channel)**

1 GHz – 2 GHz (20.0 MHz, Middle Channel)




2 GHz –20 GHz (20.0 MHz, Middle Channel)




LTE Band 4:


30 MHz - 1 GHz (1.4 MHz, Middle Channel)




1 GHz - 2 GHz (1.4 MHz, Middle Channel)




2 GHz – 20 GHz (1.4 MHz, Middle Channel)




30 MHz - 1 GHz (3.0 MHz, Middle Channel)




1 GHz – 2 GHz (3.0 MHz, Middle Channel)




2 GHz – 20 GHz (3.0 MHz, Middle Channel)




30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz - 2 GHz (5.0 MHz, Middle Channel)




2 GHz – 20 GHz (5.0 MHz, Middle Channel)




30 MHz - 1 GHz (10.0 MHz, Middle Channel)




1 GHz – 2 GHz (10.0 MHz, Middle Channel)




2 GHz – 20 GHz (10.0 MHz, Middle Channel)





30 MHz - 1 GHz (15.0 MHz, Middle Channel)




1 GHz - 2 GHz (15.0 MHz, Middle Channel)




2 GHz – 20 GHz (15.0 MHz, Middle Channel)**30 MHz - 1 GHz (20.0 MHz, Middle Channel)**

1 GHz – 2 GHz (20.0 MHz, Middle Channel)




2 GHz –20 GHz (20.0 MHz, Middle Channel)






LTE Band 7:

30 MHz - 1 GHz (5.0 MHz, Middle Channel)




1 GHz - 3 GHz (5.0 MHz, Middle Channel)




3 GHz – 26 GHz (5.0 MHz, Middle Channel)**30 MHz - 1 GHz (10.0 MHz, Middle Channel)**


1 GHz – 3 GHz (10.0 MHz, Middle Channel)




3 GHz – 26 GHz (10.0 MHz, Middle Channel)




30 MHz - 1 GHz (15.0 MHz, Middle Channel)




1 GHz - 3 GHz (15.0 MHz, Middle Channel)




3 GHz –26 GHz (15.0 MHz, Middle Channel)




30 MHz - 1 GHz (20.0 MHz, Middle Channel)





1 GHz – 3 GHz (20.0 MHz, Middle Channel)




3 GHz – 26 GHz (20.0 MHz, Middle Channel)




LTE Band 13:**30 MHz - 1 GHz (5.0 MHz, Middle Channel)****1 GHz – 10 GHz (5.0 MHz, Middle Channel)**

30 MHz - 1 GHz (10.0 MHz, Middle Channel)



1 GHz – 10 GHz (10.0 MHz, Middle Channel)



FCC § 2.1053; § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) SPURIOUS RADIATED EMISSIONS

Applicable Standards

FCC § 2.1053, § 22.917(a) and § 24.238(a) and § 27.53(h)(m)

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = $10 \lg (\text{TX pwr in Watts}/0.001)$ – the absolute level

Spurious attenuation limit in dB = $43 + 10 \log_{10} (\text{power out in Watts})$

Spurious attenuation limit in dB = $55 + 10 \log_{10} (\text{power out in Watts})$

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052604	2014-12-29	2017-12-28
Sunol Sciences	Bi-log Antenna	JB1	A040904-2	2014-12-07	2017-12-06
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2016-04-14	2017-04-14
Mini	Pre-amplifier	ZVA-183-S+	5969001149	2016-04-23	2017-04-23
HP	Amplifier	HP8447E	1937A01046	2016-05-06	2017-05-06
HP	Signal Generator	HP 8341B	2624A00116	2016-07-02	2017-07-01
COM POWER	Dipole Antenna	AD-100	041000	2016-08-18	2017-08-18
A.H. System	Horn Antenna	SAS-200/571	135	2015-08-18	2018-08-17
Rohde & Schwarz	EMI Test Receiver	ESCI	101120	2015-12-15	2016-12-14
Electro-Mechanics	Horn Antenna	3116	9510-2270	2013-10-14	2016-10-13
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2015-11-23	2016-11-23
R&S	Wideband Radio Communication tester	CMW500	1201.002K50-146520-wh	2016-04-14	2017-04-14
Ducommun technologies	RF Cable	UFA210A-1-4724-30050U	MFR64369 223410-001	2015-10-22	2016-10-22
Ducommun technologies	RF Cable	104PEA	218124002	2015-10-22	2016-10-22
Ducommun technologies	RF Cable	RG-214	1	2016-05-06	2017-05-06
Ducommun technologies	RF Cable	RG-214	2	2016-05-06	2017-05-06

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0kPa

The testing was performed by Vincent Zheng on 2016-08-18.

Test mode: Transmitting

Test mode: Transmitting (Pre-scan with Low, Middle, High channel, and the worse case data as below)

30 MHz ~ 10 GHz:

Cellular Band (Part 22H)

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GSM Mode										
481.36	30.58	147	1.0	H	-66.4	0.47	0	-66.87	-13	53.87
481.36	30.95	315	1.5	V	-66.0	0.47	0	-66.47	-13	53.47
1673.20	49.96	333	1.4	H	-45.7	1.60	6.90	-40.40	-13	27.40
1673.20	47.01	189	1.0	V	-49.1	1.60	6.90	-43.80	-13	30.80
2509.80	49.32	200	1.2	H	-44.2	1.70	8.60	-37.30	-13	24.30
2509.80	54.25	274	1.9	V	-39.6	1.70	8.60	-32.70	-13	19.70
WCDMA Mode										
481.36	31.78	146	1.1	H	-65.2	0.47	0	-65.67	-13	52.67
481.36	31.86	321	2.4	V	-65.1	0.47	0	-65.57	-13	52.57
1673.20	44.19	294	2.3	H	-51.5	1.60	6.90	-46.20	-13	33.20
1673.20	44.37	196	2.1	V	-51.8	1.60	6.90	-46.50	-13	33.50

30 MHz ~ 20 GHz:

PCS Band (Part 24E)

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
GSM Mode										
481.36	31.63	266	2.1	H	-65.4	0.47	0	-65.87	-13	52.87
481.36	30.84	148	1.1	V	-66.2	0.47	0	-66.67	-13	53.67
3760.00	35.02	351	1.1	H	-52.0	1.90	9.90	-44.00	-13	31.00
3760.00	35.47	282	2.2	V	-51.2	1.90	9.90	-43.20	-13	30.20
WCDMA Mode										
481.36	31.84	111	1.9	H	-65.2	0.47	0	-65.67	-13	52.67
481.36	30.86	320	1.4	V	-66.1	0.47	0	-66.57	-13	53.57
3760.00	34.17	64	1.4	H	-52.9	1.90	9.90	-44.90	-13	31.90
3760.00	33.88	238	1.9	V	-52.8	1.90	9.90	-44.80	-13	31.80

Test mode: Transmitting (Pre-scan with all the bandwidth, and worse case as below)

Frequency	Receiver	Turntable	Rx Antenna		Substituted			Absolute Level (dBm)	Limit (dBm)	Margin (dB)
(MHz)	Reading (dBμV)	Angle Degree	Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)			
LTE Band 2										
Test frequency range: 30 MHz ~ 20 GHz										
481.36	30.52	200	1.8	H	-66.5	0.47	0	-66.97	-13	53.97
481.36	30.90	305	1.7	V	-66.1	0.47	0	-66.57	-13	53.57
3760.00	44.29	161	1.6	H	-42.8	1.90	9.90	-34.80	-13	21.80
3760.00	45.67	186	2.1	V	-41.0	1.90	9.90	-33.00	-13	20.00
5640.00	35.38	221	2.3	H	-47.2	2.10	10.30	-39.00	-13	26.00
5640.00	36.11	255	1.4	V	-47.3	2.10	10.30	-39.10	-13	26.10
LTE Band 4										
Test frequency range: 30 MHz ~ 18 GHz										
481.36	30.47	181	2.4	H	-66.5	0.47	0	-66.97	-13	53.97
481.36	31.32	39	1.6	V	-65.7	0.47	0	-66.17	-13	53.17
3465.00	43.58	193	2.3	H	-40.3	1.90	10.00	-32.20	-13	19.20
3465.00	33.21	258	1.7	V	-50.8	1.90	10.00	-42.70	-13	29.70
LTE Band 7										
Test frequency range: 30 MHz ~ 26 GHz										
481.36	30.08	86	1.2	H	-66.9	0.47	0	-67.37	-25	42.37
481.36	31.63	1	2.1	V	-65.4	0.47	0	-65.87	-25	40.87
5070.00	32.64	89	1.8	H	-51.4	2.30	10.10	-43.60	-25	18.60
5070.00	32.56	272	2.3	V	-50.7	2.30	10.10	-42.90	-25	17.90
7605.00	33.78	197	2.2	H	-46.0	4.70	10.80	-39.90	-25	14.90
7605.00	37.05	128	2.3	V	-43.6	4.70	10.80	-37.50	-25	12.50
LTE Band 13										
Test frequency range: 30 MHz ~ 10 GHz										
481.36	30.50	265	1.6	H	-66.5	0.47	0	-66.97	-13	53.97
481.36	30.13	306	2.5	V	-66.9	0.47	0	-67.37	-13	54.37
1564.00	42.39	65	1.8	H	-55.7	1.30	6.70	-50.30	-13	37.30
1564.00	44.67	309	2.4	V	-54.1	1.30	6.70	-48.70	-13	35.70
2346.00	35.24	314	1.4	H	-56.9	1.30	8.30	-49.90	-13	36.90
2346.00	35.39	218	2.4	V	-56.9	1.30	8.30	-49.90	-13	36.90

Note:

- 1) Absolute Level = SG Level - Cable loss + Antenna Gain
- 2) Margin = Limit- Absolute Level

FCC § 22.917 (a); § 24.238 (a); § 27.53 (h)(m) - BAND EDGES**Applicable Standards**

According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to § 24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.


According to FCC § 27.53 (h)(m), the power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log(P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log(P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log(P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log(P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log(P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2016-04-14	2017-04-14
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2015-11-23	2016-11-23
R&S	Wideband Radio Communication tester	CMW500	1201.002K50-146520-wh	2016-04-14	2017-04-14
HONOVA	Power Splitter	HPDL-2W-B-NF	N/A	2016-06-12	2017-06-12
Ducommun technologies	RF Cable	RG-214	4	2016-05-06	2017-05-06
WEINSCHL	10dB Attenuator	5324	AU0709	2016-06-18	2017-06-18

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	24~27°C
Relative Humidity:	50~53 %
ATM Pressure:	100.0~101.0kPa

The testing was performed by Vincent Zheng from 2016-08-17 to 2016-08-23.


EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following plots.


Cellular Band, Left Band Edge for GSM (GMSK) Mode




Cellular Band, Right Band Edge for GSM (GMSK) Mode




Cellular Band, Left Band Edge for EGPRS Mode




Cellular Band, Right Band Edge for EGPRS Mode




Cellular Band, Left Band Edge for RMC (BPSK) Mode




Cellular Band, Right Band Edge for RMC (BPSK) Mode




Cellular Band, Left Band Edge for HSDPA (16QAM) Mode




Cellular Band, Right Band Edge for HSDPA (16QAM) Mode




Cellular Band, Left Band Edge for HSUPA (BPSK) Mode




Cellular Band, Right Band Edge for HSUPA (BPSK) Mode




PCS Band, Left Band Edge for GSM (GMSK) Mode




PCS Band, Right Band Edge for GSM (GMSK) Mode




PCS Band, Left Band Edge for EGPRS Mode




PCS Band, Right Band Edge for EGPRS Mode




PCS Band, Left Band Edge for RMC (BPSK) Mode




PCS Band, Right Band Edge for RMC (BPSK) Mode




PCS Band, Left Band Edge for HSDPA (16QAM) Mode




PCS Band, Right Band Edge for HSDPA (16QAM) Mode



PCS Band, Left Band Edge for HSUPA (BPSK) Mode




PCS Band, Right Band Edge for HSUPA (BPSK) Mode






Band 2:

QPSK (1.4 MHz, FULL RB) - Left Band Edge




QPSK (1.4 MHz, FULL RB) - Right Band Edge






16-QAM (1.4 MHz, FULL RB) - Left Band Edge**16-QAM (1.4 MHz, FULL RB) - Right Band Edge**



QPSK (3.0 MHz, FULL RB) - Left Band Edge





QPSK (3.0 MHz, FULL RB) - Right Band Edge




16-QAM (3.0 MHz, FULL RB) - Left Band Edge**16-QAM (3.0 MHz, FULL RB) - Right Band Edge**


QPSK (5.0 MHz, FULL RB) - Left Band Edge**QPSK (5.0 MHz, FULL RB) - Right Band Edge**

16-QAM (5.0 MHz, FULL RB) - Left Band Edge**16-QAM (5.0 MHz, FULL RB) - Right Band Edge**


QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge




16-QAM (10.0 MHz, FULL RB) - Left Band Edge




16-QAM (10.0 MHz, FULL RB) - Right Band Edge




QPSK (15.0 MHz, FULL RB) - Left Band Edge




QPSK (15.0 MHz, FULL RB) - Right Band Edge




16-QAM (15.0 MHz, FULL RB) - Left Band Edge




16-QAM (15.0 MHz, FULL RB) - Right Band Edge





QPSK (20.0 MHz, FULL RB) - Left Band Edge




QPSK (20.0 MHz, FULL RB) - Right Band Edge




16-QAM (20.0 MHz, FULL RB) - Left Band Edge**16-QAM (20.0 MHz, FULL RB) - Right Band Edge**



Band 4:

QPSK (1.4 MHz, FULL RB) - Left Band Edge




QPSK (1.4 MHz, FULL RB) - Right Band Edge






16-QAM (1.4 MHz, FULL RB) - Left Band Edge**16-QAM (1.4 MHz, FULL RB) - Right Band Edge**

QPSK (3.0 MHz, FULL RB) - Left Band Edge




QPSK (3.0 MHz, FULL RB) - Right Band Edge



16-QAM (3.0 MHz, FULL RB) - Left Band Edge**16-QAM (3.0 MHz, FULL RB) - Right Band Edge**


QPSK (5.0 MHz, FULL RB) - Left Band Edge




QPSK (5.0 MHz, FULL RB) - Right Band Edge





16-QAM (5.0 MHz, FULL RB) - Left Band Edge




16-QAM (5.0 MHz, FULL RB) - Right Band Edge




QPSK (10.0 MHz, FULL RB) - Left Band Edge**QPSK (10.0 MHz, FULL RB) - Right Band Edge**


16-QAM (10.0 MHz, FULL RB) - Left Band Edge




16-QAM (10.0 MHz, FULL RB) - Right Band Edge




QPSK (15.0 MHz, FULL RB) - Left Band Edge




QPSK (15.0 MHz, FULL RB) - Right Band Edge




16-QAM (15.0 MHz, FULL RB) - Left Band Edge




16-QAM (15.0 MHz, FULL RB) - Right Band Edge







QPSK (20.0 MHz, FULL RB) - Left Band Edge





QPSK (20.0 MHz, FULL RB) - Right Band Edge




16-QAM (20.0 MHz, FULL RB) - Left Band Edge**16-QAM (20.0 MHz, FULL RB) - Right Band Edge**


Band 7:**QPSK (5.0 MHz, FULL RB) - Left Band Edge****QPSK (5.0 MHz, FULL RB) - Right Band Edge**



16-QAM (5.0 MHz, FULL RB) - Left Band Edge**16-QAM (5.0 MHz, FULL RB) - Right Band Edge**

QPSK (10.0 MHz, FULL RB) - Left Band Edge




QPSK (10.0 MHz, FULL RB) - Right Band Edge






16-QAM (10.0 MHz, FULL RB) - Left Band Edge**16-QAM (10.0 MHz, FULL RB) - Right Band Edge**

QPSK (15 MHz, FULL RB) - Left Band Edge




QPSK (15 MHz, FULL RB) - Right Band Edge






16-QAM (15 MHz, FULL RB) - Left Band Edge**16-QAM (15 MHz, FULL RB) - Right Band Edge**



QPSK (20 MHz, FULL RB) - Left Band Edge





QPSK (20 MHz, FULL RB) - Right Band Edge




16-QAM (20 MHz, FULL RB) - Left Band Edge**16-QAM (20 MHz, FULL RB) - Right Band Edge**


Band 13:**QPSK (5.0 MHz, FULL RB) - Left Band Edge****QPSK (5.0 MHz, FULL RB) - Right Band Edge**



16-QAM (5.0 MHz, FULL RB) - Left Band Edge**16-QAM (5.0 MHz, FULL RB) - Right Band Edge**

QPSK (10.0 MHz, FULL RB) - Left Band Edge



QPSK (10.0 MHz, FULL RB) - Right Band Edge



16-QAM (10.0 MHz, FULL RB) - Left Band Edge**16-QAM (10.0 MHz, FULL RB) - Right Band Edge**

FCC § 2.1055; § 22.355; § 24.235; §27.54; - FREQUENCY STABILITY**Applicable Standards**

FCC § 2.1055, §22.355, §24.235 and & §27.54.

According to FCC §2.1055, the frequency stability shall be sufficient to ensure that the fundamental emissions stay within the authorized bands of operation.

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile > 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2015-11-01	2016-10-31
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2015-11-23	2016-11-23
R&S	Wideband Radio Communication tester	CMW500	1201.002K50-146520-wh	2016-04-14	2017-04-14
Ducommun technologies	RF Cable	RG-214	4	2016-05-06	2017-05-06
WEINSCHTEL	10dB Attenuator	5324	AU0709	2016-06-18	2017-06-18
Long Wei	DC Power Supply	TPR-6420D	398363	NCR	NCR

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	52 %
ATM Pressure:	101.0kPa

The testing was performed by Vincent Zheng on 2016-08-18.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

Cellular Band (Part 22H)**GSM Mode**

Middle Channel, $f_0=836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.85	-2	-0.002391	2.5
-20		-1	-0.001195	2.5
-10		0	0.000000	2.5
0		-1	-0.001195	2.5
10		-3	-0.003586	2.5
20		-1	-0.001195	2.5
30		0	0.000000	2.5
40		1	0.001195	2.5
50		-1	-0.001195	2.5
25	V min.= 3.66	2	0.002391	2.5
25	V max.= 4.24	-3	-0.003586	2.5

EDGE Mode

Middle Channel, $f_0=836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.85	1	0.001195	2.5
-20		1	0.001195	2.5
-10		0	0.000000	2.5
0		-1	-0.001195	2.5
10		2	0.002391	2.5
20		3	0.003586	2.5
30		1	0.001195	2.5
40		-1	-0.001195	2.5
50		-2	-0.002391	2.5
25	V min.= 3.66	3	0.003586	2.5
25	V max.= 4.24	-2	-0.002391	2.5

WCDMA Mode

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.85	-1	-0.001195	2.5
-20		-1	-0.001195	2.5
-10		-2	-0.002391	2.5
0		0	0.000000	2.5
10		1	0.001195	2.5
20		-1	-0.001195	2.5
30		2	0.002391	2.5
40		3	0.003586	2.5
50		-1	-0.001195	2.5
25	V min.= 3.66	0	0.000000	2.5
25	V max.= 4.24	1	0.001195	2.5

PCS Band (Part 24E)**GSM Mode**

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V_{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.85	1	0.000532	pass
-20		2	0.001064	pass
-10		1	0.000532	pass
0		-1	-0.000532	pass
10		0	0.000000	pass
20		3	0.001596	pass
30		-1	-0.000532	pass
40		2	0.001064	pass
50		3	0.001596	pass
25	V min.= 3.66	0	0.000000	pass
25	V max.= 4.24	3	0.001596	pass

EDGE Mode

Middle Channel, $f_0=1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.85	2	0.001064	pass
-20		3	0.001596	pass
-10		3	0.001596	pass
0		1	0.000532	pass
10		1	0.000532	pass
20		4	0.002128	pass
30		0	0.000000	pass
40		2	0.001064	pass
50		4	0.002128	pass
25	V min.= 3.66	0	0.000000	pass
25	V max.= 4.24	3	0.001596	pass

WCDMA Mode

Middle Channel, $f_0=1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.85	1	0.000532	pass
-20		0	0.000000	pass
-10		1	0.000532	pass
0		-2	-0.001064	pass
10		0	0.000000	pass
20		2	0.001064	pass
30		-1	-0.000532	pass
40		2	0.001064	pass
50		1	0.000532	pass
25	V min.= 3.66	-1	-0.000532	pass
25	V max.= 4.24	2	0.001064	pass

Band 2:

20.0 MHz Middle Channel, $f_o=1880\text{MHz}$ (QPSK)				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.85	1	0.000532	pass
-20		-1	-0.000532	pass
-10		-2	-0.001064	pass
0		-3	-0.001596	pass
10		-1	-0.000532	pass
20		-2	-0.001064	pass
30		1	0.000532	pass
40		-1	-0.000532	pass
50		2	0.001064	pass
25	V min.= 3.66	-1	-0.000532	pass
25	V max.= 4.24	-2	-0.001064	pass

20.0 MHz Middle Channel, $f_o=1880\text{MHz}$ (16QAM)				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.85	1	0.000532	pass
-20		-2	-0.001064	pass
-10		2	0.001064	pass
0		1	0.000532	pass
10		-2	-0.001064	pass
20		1	0.000532	pass
30		2	0.001064	pass
40		-2	-0.001064	pass
50		1	0.000532	pass
25	V min.= 3.66	1	0.000532	pass
25	V max.= 4.24	-1	-0.000532	pass

Band 4:

20.0 MHz Middle Channel, $f_0 = 1732.5$ MHz (QPSK)				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.85	2	0.001154	pass
-20		-3	-0.001732	pass
-10		-1	-0.000577	pass
0		-2	-0.001154	pass
10		-1	-0.000577	pass
20		2	0.001154	pass
30		-3	-0.001732	pass
40		-1	-0.000577	pass
50		1	0.000577	pass
25	V min.= 3.66	-3	-0.001732	pass
25	V max.= 4.24	-2	-0.001154	pass

20.0 MHz Middle Channel, $f_0 = 1732.5$ MHz (16QAM)				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.85	1	0.000577	pass
-20		-1	-0.000577	pass
-10		2	0.001154	pass
0		-1	-0.000577	pass
10		-2	-0.001154	pass
20		1	0.000577	pass
30		-1	-0.000577	pass
40		2	0.001154	pass
50		2	0.001154	pass
25	V min.= 3.66	2	0.001154	pass
25	V max.= 4.24	2	0.001154	pass

Band 7:

20.0 MHz Middle Channel, $f_o=2535$ MHz (QPSK)				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.85	-1	-0.000394	pass
-20		1	0.000394	pass
-10		2	0.000789	pass
0		3	0.001183	pass
10		1	0.000394	pass
20		-1	-0.000394	pass
30		3	0.001183	pass
40		1	0.000394	pass
50		-2	-0.000789	pass
25	V min.= 3.66	-1	-0.000394	pass
25	V max.= 4.24	-2	-0.000789	pass

20.0 MHz Middle Channel, $f_o=2535$ MHz (16QAM)				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.85	1	0.000394	pass
-20		3	0.001183	pass
-10		-1	-0.000394	pass
0		1	0.000394	pass
10		2	0.000789	pass
20		-3	-0.001183	pass
30		-2	-0.000789	pass
40		-1	-0.000394	pass
50		2	0.000789	pass
25	V min.= 3.66	1	0.000394	pass
25	V max.= 4.24	2	0.000789	pass

Band 13:

10.0 MHz Middle Channel, $f_o = 782$ MHz (QPSK)				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.85	-3	-0.003836	pass
-20		1	0.001279	pass
-10		-2	-0.002558	pass
0		-1	-0.001279	pass
10		1	0.001279	pass
20		-3	-0.003836	pass
30		-2	-0.002558	pass
40		-1	-0.001279	pass
50		1	0.001279	pass
25	V min.= 3.66	2	0.002558	pass
25	V max.= 4.24	-2	-0.002558	pass

10.0 MHz Middle Channel, $f_o = 782$ MHz (16QAM)				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Result
-30	3.85	-3	-0.003836	pass
-20		1	0.001279	pass
-10		2	0.002558	pass
0		-1	-0.001279	pass
10		1	0.001279	pass
20		2	0.002558	pass
30		-2	-0.002558	pass
40		1	0.001279	pass
50		-3	-0.003836	pass
25	V min.= 3.66	1	0.001279	pass
25	V max.= 4.24	1	0.001279	pass

***** END OF REPORT *****