

Compliance with 47 CFR 2.1091, 1.1310, 15.247, 15.407

The EUT contains a 802.11 a/b/g radio transceiver operating under FCC Part 15.247 and FCC 15.407. The EUT will only be used with a separation distance of 20 centimeters or greater between the antenna and the body of the user or nearby persons and can therefore be considered a mobile transmitter per 47 CFR 2.1091(b).

Since the transmit frequency is greater than 1.5 GHz, and the output power is less than 3 W ERP, the EUT is categorically excluded from routine environmental evaluation per 47 CFR 2.1091(c).

The MPE estimates are as follows:

Table 1 in 47 CFR 1.1310 defines the maximum permissible exposure (MPE) for the general population as 1 mW/cm^2 . The exposure level at a 20 cm distance from the EUT's transmitting antenna is calculated using the general equation:

$$S = (PG)/4\pi R^2$$

Where: S = power density (mW/cm^2)

P = power input to the antenna (mW)

G = numeric power gain relative to an isotropic radiator

R = distance to the center of the radiation of the antenna (20 cm = limit for MPE estimates)

PG = EIRP

Solving for S, the maximum power density 20 cm from the transmitting antenna is summarized in the following table:

MPE Estimate

FCC ID: CM6010-1471ABG

Antenna Type	Antenna Manufacturer	Antenna Part No.	Transmit Frequency (MHz)	Max Peak Conducted Output Power (mW)	Antenna Gain (dBi)	Minimum Antenna Cable Loss (dB)	Power Density @ 20 cm (mW/cm^2)	General Population Exposure Limit from 1.1310 (mW/cm^2)
Omni	Nearson	TPCB04653L	2400	186	2	0	0.059	1
			5500	56.62	2	0	0.018	1
Omni	Nearson	TPCB04653R	2400	186	2	0	0.059	1
			5500	56.62	2	0	0.018	1

The power density does not exceed 0.059 mW/cm^2 at 20 cm; therefore, the exposure condition is compliant with FCC rules. Per FCC 15.407(f), both the fundamental emissions and unwanted emissions are compliant with FCC rules for RF exposure.