



Test Report - FCC Part 90

Applicant: Cattron North America Inc.

Signature:

A handwritten signature in black ink, appearing to read "Tim Royer", is written over a horizontal line.

Sr. EMC Engineer
EMC-003838-NE



Name & Title: Tim Royer, EMC Engineer

Date of Signature 7/17/2024

This test report relates only to the items tested as identified and is not valid for any subsequent changes or modifications made to the equipment under test.

Table of Contents

1.	APPLICANT INFORMATION.....	4
1.1	PART 90 TEST RESULT SUMMARY	4
2.	LOCATION OF TESTING	5
2.1	TEST LABORATORY	5
3.	TEST SAMPLE(S) (EUT/DUT).....	5
3.1	DESCRIPTION OF THE EUT.....	6
3.2	CONFIGURATION OF EUT.....	7
3.3	TEST SETUP OF EUT.....	7
4.	TEST METHODS & APPLICABLE REGULATORY LIMITS.....	8
4.1	TEST METHODS/STANDARDS/GUIDANCE:	8
4.2	APPLIED LIMITS AND REGULATORY LIMITS:.....	8
5.	MEASUREMENT UNCERTAINTY.....	8
6.	ENVIRONMENTAL CONDITIONS	8
6.1	TEMPERATURE & HUMIDITY.....	8
7.	LIST OF TEST EQUIPMENT AND TEST FACILITY.....	9
7.1	LIST OF TEST EQUIPMENT	9
8.	TEST RESULTS	11
8.1	POWER AT THE FINAL AMPLIFIER.....	12
8.2	RF OUTPUT POWER.....	13
8.2.1	RF Output Power Plot, 217 MHz, Mode 1.....	14
8.2.2	RF Power Output Plot, 220 MHz, Mode 1.....	15
8.2.3	RF Power Output Plot, 222 MHz, Mode 1.....	16
8.2.4	RF Output Power Plot, 217 MHz, Mode 2.....	17
8.2.5	RF Power Output Plot, 220 MHz, Mode 2.....	18
8.2.6	RF Power Output Plot, 222 MHz, Mode 2.....	19
8.3	BANDWIDTH & EMISSION.....	20
8.3.1	99% Bandwidth Plot, 217 MHz.....	22
8.3.2	99% Bandwidth Plot, 220 MHz.....	23
8.3.3	99% Bandwidth Plot, 222 MHz.....	24
8.4	EMISSION LIMITATIONS, IN-BAND.....	25
8.4.1	Emission Mask, 217 MHz.....	26
8.4.2	Emission Mask, 220 MHz.....	27
8.4.3	Emission Mask, 222 MHz.....	28
8.5	EMISSION LIMITATIONS, OUT-OF-BAND.....	29
8.5.1	Conducted Emissions, Below 1GHz, 217 MHz.....	30
8.5.2	Conducted Emissions Above 1GHz, 217 MHz.....	31
8.5.1	Conducted Emissions, Below 1GHz, 220 MHz.....	32
8.5.2	Conducted Emissions Above 1GHz, 220 MHz.....	33
8.5.3	Conducted Emissions Below 1GHz, 222 MHz.....	34
8.5.4	Conducted Emissions Above 1GHz, 222 MHz.....	35
8.6	RADIATED EMISSIONS.....	36
8.6.1	Radiated Emissions, 217 MHz.....	37
8.6.2	Radiated Emissions, 220 MHz.....	38
8.6.3	Radiated Emissions, 222 MHz.....	39

8.7	MODULATION CHARACTERISTICS.....	40
8.8	FREQUENCY STABILITY.....	41
8.8.1	<i>Frequency Stability Data</i>	42
8.8.2	<i>Frequency Stability Plot</i>	43
8.9	TRANSIENT FREQUENCY BEHAVIOR.....	44
8.10	ADJACENT CHANNEL POWER LIMITS.....	45
9.	ANNEX-B – TEST SETUP PHOTOGRAPHS.....	46
10.	HISTORY OF TEST REPORT CHANGES.....	46

1. Applicant Information

Applicant: Cattron North America Inc.
Address: 655 N. River Road NW
Suite A
Warren, OH 44483-2254, United States

1.1 Part 90 Test Result Summary

The following test procedure and guidance were used for measuring FCC PART 90 (PRIVATE LAND MOBILE RADIO SERVICES) known as Licensed Land Mobile; ANSI C63.26-2015. Full test results are available in this report.

Applicable Clauses from Part 2		
FCC Clauses	Description of the requirements	Result: (Pass, Fail, N/A)
2.202	Bandwidth & Emission	Pass
2.1033 (c)(8)	Power at the Final Amplifier	Reported
2.1046 (a)	RF Output Power	Pass
2.1047	Modulation characteristics	n/a
2.1049	Occupied Bandwidth	Pass
2.1051	Spurious emissions at antenna terminals	Pass
2.1053	Field strength of spurious radiation	Pass
2.1055	Frequency stability	Pass

Applicable Clauses from Part 90		
FCC Clauses	Description of the requirements	Result: (Pass, Fail, N/A)
90.205 (r)	Transmitter Power	Pass
90.207 (n)	Emission designator	Reported
90.209 (b) (5) footnote 2	Bandwidth limitations	Pass
90.210 (n)	Emission masks, In-band	Pass
90.210 (n)	Emission masks, Out-of-band	Pass
90.213 (a) footnote 10	Frequency stability	Pass
90.214	Transient Frequency Behavior	n/a
90.221	Adjacent channel power limits	n/a

No additions to the test methods were needed. There were no deviations, or exclusions from the test methods. No test results are from external providers or from the customer. The test results relate only to the items tested. Timco does not offer opinions and interpretations, only a pass/fail statement.

2. Location of Testing

2.1 Test Laboratory

Timco Engineering Inc. is a subsidiary of Industrial Inspection & Analysis, Inc. ("IIA"). Testing was performed at IIA's permanent laboratory located at 13146 NW 86th Drive, Suite 400, Alachua, Florida 32615.

FCC test firm # 578780

FCC Designation # US1070

FCC site registration is under A2LA certificate # 0955.01

ISED Canada test site registration # 2056A

EU Notified Body # 1177

For all designations see A2LA scope # 0955.01

3. Test Sample(s) (EUT/DUT)

The test sample was received: 6/17/2024

Dates of Testing: 6/21 – 7/11/2024

3.1 Description of the EUT

A description as well as unambiguous identification of the EUT(s) tested. Where more than one sample is required for technical reasons (such as the use of connected units for the purpose of conducted output power testing where the product units will have integral antennas), each specific test shall identify which unit was tested.

Identification	
FCC ID:	CN289696-91071
Brief Description	220 MHz transceiver module for data delivery in Cattron applications.
Model(s) #	89696+91071 TRX
Firmware version	N/A
Software version	N/A
Serial Number	N/A

Technical Characteristics	
Frequency Range	217 – 225 MHz
RF O/P Power (Max.)	30 dBm
Modulation	Digital
Bandwidth & Emission Class	F1X,F1D,F1W
Antenna Connector	UFL
Voltage Rating (AC or Batt.)	5v DC

Antenna Characteristics			
Antenna	Frequency Range	Mode / BW	Antenna Gain
1	217 - 225	n/a	5.15 dBi

- Note: Information such as antenna gain, firmware/software numbers are provided by manufacturer and cannot be validated by the test lab.

3.2 Configuration of EUT

Test Modes					
Mode (#)	Mode (Type)	Test Frequencies (MHz)	BW (nominal) (kHz)	Emission Designator	Software Setting
1	0dBm	217 - 222	6.41	F1X,F1D,F1W	-p 1
2	30dBm	217 - 222	6.41	F1X,F1D,F1W	-p 31

Operating conditions during Testing:

The device was operated without the provided antenna(s).

No other modifications of the device under test (including firmware, specific software settings, and input/output signal levels to the EUT) were made.

Peripherals used during Testing:

A laptop provided by the manufacturer was used to program the EUT.

3.3 Test Setup of EUT

Equipment, antenna, and cable arrangement. The setup of the equipment and cable or wire placement on the test site that produces the highest radiated and the highest ac power line conducted emissions shall be shown clearly and described. Information on the orientation of portable equipment during testing shall be included. Drawings or photographs may be used for this purpose.

Test Setups are included in the test report.

4. Test methods & Applicable Regulatory Limits

4.1 Test methods/Standards/Guidance:

Test procedures and guidance for measuring Licensed Part 90 Licensed device:

- 1) ANSI C63.26-2015

4.2 Applied Limits and Regulatory Limits:

- 1) FCC CFR 47 Part 90 (2007)

5. Measurement Uncertainty

Parameter	Uncertainty (dB)
Conducted Emissions	± 3.14 dB
Radiated Emissions (9kHz – 30 MHz)	± 3.08 dB
Radiated Emissions (30 – 200 MHz)	± 2.16 dB
Radiated Emissions (200 – 1000 MHz)	± 2.15 dB
Radiated Emissions (1 GHz – 18 GHz)	± 2.14 dB
Radiated Emissions (18 GHz – 40 GHz)	± 2.31 dB
Note: The uncertainties provided in this table represent an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of K=2.	

6. Environmental Conditions

6.1 Temperature & Humidity

Measurements performed at the test site did not exceed the following:

Parameter	Measurement
Temperature	23 C +/- 5%
Humidity	55% +/- 5%
Barometric Pressure	30.05 in Hg
Note: Specific environmental conditions that are applicable to a specific test are available in the test result section.	

7. List of Test Equipment and Test Facility

The test equipment used identified by type, manufacturer, serial number, or other identification and the date on which the next calibration or service check is due.

Description of the firmware or software used to operate EUT for testing purposes.

A complete list of all test equipment used shall be included with the test report. The manufacturer's model and serial numbers, and date of last calibration, and calibration interval shall be included. Measurement cable loss, measuring instrument bandwidth and detector function, video bandwidth, if appropriate, and antenna factors shall also be included where applicable.

7.1 List of Test Equipment

Test Equipment						
Type	Device	Manufacturer	Model	SN#	Current Cal	Cal Due
Antenna, NSA	Log-Periodic 1243	Eaton	96005	1243	5/4/21	5/3/2024
Antenna	Double-Ridged Horn/ETS Horn 1	ETS-Lindgren	3117	00035923	5/31/23	5/30/2026
CHAMBER	CHAMBER	Panashield	3M	N/A	12/29/23	12/18/2025
Pre-amp	Pre-amp	RF-LAMBDA	RLNA00M45GA	NA	2/27/22	7/26/2025
Receiver	EMI Test Receiver R&S ESU 40	Rohde & Schwarz	ESU 40	100320	5/27/21	5/26/2024
Receiver	EMI Test Receiver R&S ESW44	Rohde & Schwarz	ESW44	103049	10/13/21	10/12/2024
Signal Generator	Signal Generator HP 8648C	HP	8648C	35537A01679	8/4/22	8/03/2025

Software			
Software	Author	Version	Validation on
ESU Firmware	Rohde & Schwarz	4.43 SP3; BIOS v5.1-24-3	2018
RSCCommander	Rohde & Schwarz	1.6.4	2014
ScopeExplorer	LeCroy	v2.25.0.0	2009
Field Strength	Timco	v4.10.7.0	2016

8. Test Results

The results of the test are usually indicated in the form of tables, spectrum analyzer plots, charts, sample calculations, as appropriate for each test procedure.

A description and/or a block diagram of the test setup is usually provided.

The measurement results, along with the appropriate limits for comparison, may be presented in tabular or graphical form. In addition, any variation in the measurement environment may be reported if applicable (e.g., a significant change of temperature that could affect the cable loss and amplifier response).

Unless noted otherwise in the referenced standard, the measurements of **ac power-line conducted emissions and conducted power output** will be reported in units of dB μ V. Unless noted otherwise in the referenced standard, the measurements of **radiated emissions** will be reported in units of decibels, referenced to one microvolt per meter (dB μ V/m) for electric fields, or to one ampere per meter (dBA/m) for magnetic fields, at the distance specified in the appropriate standards or requirements. The measurements of antenna-conducted power for receivers may be reported in units of dB μ V if the impedance of the measuring instrument is also reported. Otherwise, antenna-conducted power will be reported in units of decibels referenced to one milliwatt (dBm). All formulas for data conversions and conversion factors, if used, will be included in this measurement report.

Example:

Freq (MHz)	Meter Reading	+ ACF	+CL	= FS
33	20 dB μ V	+ 10.36 dB/m	+0.40 dB	=30.36 dB μ V/m @ 3m

$EIRP = P_{cond} \text{ (dBm)} + dBi$


8.1 Power at the Final Amplifier

Limits from FCC Part 2.1033 (c)(8). No method of measurement is specified.

Test Results		
EUT Operating Voltage (V)	EUT Current (A)	Power at the Final Amplifier (W)
5	3.6	18

8.2 RF Output Power

Limits from FCC Parts 2.1046(a), and 90.205 (r); and test procedure from ANSI C63.26-2015.



Test Results, Mode 1			
Tuned Frequency (MHz)	Power Setting	Power Output (dBm)	Power Output (mW)
217	0 dBm	-0.19	0.96
220	0 dBm	-0.09	0.97
222	0 dBm	0.02	1

Test Results, Mode 2			
Tuned Frequency (MHz)	Power Setting	Power Output (dBm)	Power Output (W)
217	30 dBm	29.54	0.89
220	30 dBm	30.23	1.05
222	30 dBm	30.5	1.12

8.2.1 RF Output Power Plot, 217 MHz, Mode 1



* RBW 1 MHz Marker 1 [T1]
 VBW 3 MHz -0.19 dBm
 SWT 2.5 ms 216.996794872 MHz


Ref 21.1 dBm

* Att 10 dB

SWT 2.5 ms

216.996794872 MHz

1 PK
VIEW




Date: 11.JUL.2024 14:58:01

8.2.2 RF Power Output Plot, 220 MHz, Mode 1



* RBW 1 MHz Marker 1 [T1]
VBW 3 MHz -0.09 dBm
SWT 2.5 ms 220.006410256 MHz



Date: 11.JUL.2024 14:56:37

8.2.3 RF Power Output Plot, 222 MHz, Mode 1



* RBW 1 MHz Marker 1 [T1]
VBW 3 MHz 0.02 dBm
SWT 2.5 ms 221.983974359 MHz


Ref 21.1 dBm

* Att 10 dB

SWT 2.5 ms


221.983974359 MHz

1 PK
VIEW




Date: 11.JUL.2024 14:54:58

8.2.4 RF Output Power Plot, 217 MHz, Mode 2




19:21:54 21.06.2024

8.2.5 RF Power Output Plot, 220 MHz, Mode 2



19:21:08 21.06.2024


8.2.6 RF Power Output Plot, 222 MHz, Mode 2



14:57:07 22.06.2024

8.3 Bandwidth & Emission

Limits from FCC Parts 2.1049, and 90.207 & 90.209, and test procedure from ANSI C63.26-2015.



Test Results, Authorized Bandwidth		
Rule Part	Operating Range (MHz)	Authorized Bandwidth (kHz)
Part 90	217 - 222	6

Test Results, Occupied Bandwidth				
Tuned Frequency (MHz)	Mode	Emission Designator	Occupied Bandwidth (kHz)	Bandwidth Type
217	2	F1X,F1D,F1W	6.39	99%
220	2	F1X,F1D,F1W	6.38	99%
222	2	F1X,F1D,F1W	6.41	99%

Tuned Frequency (MHz)	Emission Designator	Occupied Bandwidth (kHz)	Bandwidth Type
220	F1X,F1D,F1W	6.38	99%
222	F1X,F1D,F1W	6.41	99%


Occupied Bandwidth, Spectrum Plots

8.3.1 99% Bandwidth Plot, 217 MHz




19:25:15 21.06.2024

8.3.2 99% Bandwidth Plot, 220 MHz



19:26:10 21.06.2024

8.3.3 99% Bandwidth Plot, 222 MHz




14:58:04 22.06.2024


8.4 Emission Limitations, In-Band

Limits from FCC Part 90.210; and test procedure from ANSI C63.26-2015.

Conducted Test Setup



8.4.1 Emission Mask, 217 MHz



Date: 26.JUN.2024 14:34:21

Conducted Emissions Mask, Spectrum Plots

8.4.2 Emission Mask, 220 MHz




Date: 11.JUL.2024 13:18:27

8.4.3 Emission Mask, 222 MHz



1 SA
VIEW




Date: 11.JUL.2024 13:19:55

8.5 Emission Limitations, Out-of-Band

Limits from FCC Parts 2.1051, and 90.210; and test procedure from ANSI C63.26-2015.

Conducted Test Setup




Conducted Emissions Spectrum Plots

8.5.1 Conducted Emissions, Below 1GHz, 217 MHz




8.5.2 Conducted Emissions Above 1GHz, 217 MHz



21:00:35 21.06.2024

8.5.1 Conducted Emissions, Below 1GHz, 220 MHz




21:03:02 21.06.2024

8.5.2 Conducted Emissions Above 1GHz, 220 MHz




20:58:42 21.06.2024

8.5.3 Conducted Emissions Below 1GHz, 222 MHz



21:04:05 21.06.2024

8.5.4 Conducted Emissions Above 1GHz, 222 MHz




20:59:58 21.06.2024


8.6 Radiated Emissions

Limits from FCC Parts 2.1053 and 90.210 (n); and test procedure from ANSI C63.26-2015.

Radiated Test Setup, 30 – 1000 MHz



Radiated Test Setup, Above 1000 MHz



8.6.1 Radiated Emissions, 217 MHz

Tuned Frequency (MHz)	Emission Frequency (MHz)	Detector	Meter Reading (dBuV)	Antenna Polarity	Coax Loss (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dBuV/m)	ERP (dBm)	Spurious Limit (dBm)	Margin (dB)
217.00	434.00	PK	39.94	H	-2.39	16.31	3.00	53.86	-43.52	-20.00	23.52
217.00	434.00	PK	41.57	V	-2.39	16.31	3.00	55.49	-41.89	-20.00	21.89
217.00	651.00	PK	36.30	H	-2.96	19.52	3.00	52.85	-44.53	-20.00	24.53
217.00	651.00	PK	32.17	V	-2.96	19.52	3.00	48.72	-48.66	-20.00	28.66
217.00	868.00	PK	23.65	H	-3.51	22.47	3.00	42.61	-54.77	-20.00	34.77
217.00	868.00	PK	19.81	V	-3.51	22.47	3.00	38.77	-58.61	-20.00	38.61
217.00	1085.00	PK	19.06	H	-3.91	27.14	3.00	42.29	-55.09	-20.00	35.09
217.00	1085.00	PK	19.94	V	-3.91	27.14	3.00	43.17	-54.21	-20.00	34.21
217.00	1302.00	PK	14.36	H	-4.28	29.13	3.00	39.20	-58.17	-20.00	38.17
217.00	1302.00	PK	14.87	V	-4.28	29.13	3.00	39.71	-57.66	-20.00	37.66
217.00	1519.00	PK	15.61	H	-4.57	27.70	3.00	38.74	-58.64	-20.00	38.64
217.00	1519.00	PK	16.52	V	-4.57	27.70	3.00	39.65	-57.73	-20.00	37.73
217.00	1736.00	PK	11.10	H	-4.85	29.67	3.00	35.92	-61.46	-20.00	41.46
217.00	1736.00	PK	13.77	V	-4.85	29.67	3.00	38.59	-58.79	-20.00	38.79
217.00	1953.00	PK	11.08	H	-5.26	31.63	3.00	37.44	-59.93	-20.00	39.93
217.00	1953.00	PK	11.88	V	-5.26	31.63	3.00	38.24	-59.13	-20.00	39.13
217.00	2170.00	PK	12.27	H	-5.60	31.46	3.00	38.13	-59.25	-20.00	39.25
217.00	2170.00	PK	12.62	V	-5.60	31.46	3.00	38.48	-58.90	-20.00	38.90

Radiated Emissions, Tabular Data

8.6.2 Radiated Emissions, 220 MHz


Tuned Frequency (MHz)	Emission Frequency (MHz)	Detector	Meter Reading (dBuV)	Antenna Polarity	Coax Loss (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dBuV/m)	ERP (dBm)	Spurious Limit (dBm)	Margin (dB)
220.00	440.00	PK	42.17	H	-2.40	16.44	3.00	56.21	-41.17	-25.00	16.17
220.00	440.00	PK	44.06	V	-2.40	16.44	3.00	58.10	-39.28	-25.00	14.28
220.00	660.00	PK	37.68	H	-3.00	19.90	3.00	54.58	-42.80	-25.00	17.80
220.00	660.00	PK	34.08	V	-3.00	19.90	3.00	50.98	-46.40	-25.00	21.40
220.00	880.00	PK	20.97	H	-3.54	22.51	3.00	39.94	-57.43	-25.00	32.43
220.00	880.00	PK	25.11	V	-3.54	22.51	3.00	44.08	-53.29	-25.00	28.29
220.00	1100.00	PK	14.00	H	-3.94	27.43	3.00	37.49	-59.89	-25.00	34.89
220.00	1100.00	PK	16.60	V	-3.94	27.43	3.00	40.09	-57.29	-25.00	32.29
220.00	1320.00	PK	12.61	H	-4.30	29.04	3.00	37.36	-60.02	-25.00	35.02
220.00	1320.00	PK	10.59	V	-4.30	29.04	3.00	35.34	-62.04	-25.00	37.04
220.00	1540.00	PK	11.82	H	-4.62	27.69	3.00	34.90	-62.48	-25.00	37.48
220.00	1540.00	PK	14.58	V	-4.62	27.69	3.00	37.66	-59.72	-25.00	34.72
220.00	1760.00	PK	12.78	H	-4.95	30.08	3.00	37.91	-59.47	-25.00	34.47
220.00	1760.00	PK	13.45	V	-4.95	30.08	3.00	38.58	-58.80	-25.00	33.80
220.00	1980.00	PK	12.53	H	-5.34	31.64	3.00	38.83	-58.55	-25.00	33.55
220.00	1980.00	PK	12.06	V	-5.34	31.64	3.00	38.36	-59.02	-25.00	34.02
220.00	2200.00	PK	12.71	H	-5.63	31.38	3.00	38.46	-58.91	-25.00	33.91
220.00	2200.00	PK	11.28	V	-5.63	31.38	3.00	37.03	-60.34	-25.00	35.34

8.6.3 Radiated Emissions, 222 MHz

Tuned Frequency (MHz)	Emission Frequency (MHz)	Detector	Meter Reading (dBuV)	Antenna Polarity	Coax Loss (dB)	Antenna Correction Factor (dB/m)	Distance (m)	Field Strength (dBμV/m)	ERP (dBm)	Spurious Limit (dBm)	Margin (dB)
222.00	444.00	PK	41.55	H	-2.42	16.55	3.00	55.67	-41.70	-25.00	16.70
222.00	444.00	PK	44.25	V	-2.42	16.55	3.00	58.37	-39.00	-25.00	14.00
222.00	666.00	PK	31.49	H	-3.02	20.31	3.00	48.78	-48.60	-25.00	23.60
222.00	666.00	PK	29.11	V	-3.02	20.31	3.00	46.40	-50.98	-25.00	25.98
222.00	888.00	PK	22.51	H	-3.56	22.58	3.00	41.54	-55.84	-25.00	30.84
222.00	888.00	PK	20.42	V	-3.56	22.58	3.00	39.45	-57.93	-25.00	32.93
222.00	1110.00	PK	13.87	H	-3.95	27.50	3.00	37.42	-59.96	-25.00	34.96
222.00	1110.00	PK	14.62	V	-3.95	27.50	3.00	38.17	-59.21	-25.00	34.21
222.00	1332.00	PK	15.46	H	-4.31	28.92	3.00	40.08	-57.30	-25.00	32.30
222.00	1332.00	PK	12.80	V	-4.31	28.92	3.00	37.42	-59.96	-25.00	34.96
222.00	1554.00	PK	13.23	H	-4.65	27.70	3.00	36.28	-61.09	-25.00	36.09
222.00	1554.00	PK	14.03	V	-4.65	27.70	3.00	37.08	-60.29	-25.00	35.29
222.00	1776.00	PK	12.20	H	-5.01	30.28	3.00	37.46	-59.91	-25.00	34.91
222.00	1776.00	PK	13.60	V	-5.01	30.28	3.00	38.86	-58.51	-25.00	33.51
222.00	1998.00	PK	11.21	H	-5.39	31.60	3.00	37.42	-59.96	-25.00	34.96
222.00	1998.00	PK	10.34	V	-5.39	31.60	3.00	36.55	-60.83	-25.00	35.83
222.00	2220.00	PK	11.65	H	-5.65	31.54	3.00	37.54	-59.84	-25.00	34.84
222.00	2220.00	PK	11.08	V	-5.65	31.54	3.00	36.96	-60.41	-25.00	35.41

8.7 Modulation Characteristics


Limits from FCC Parts 2.1047 and test procedure from ANSI C63.26-2015



N/A

8.8 Frequency Stability

Limits from FCC Parts 2.1055, and 90.213; and test procedure from ANSI C63.26-2015.




Test Results, Mode 1		
Tuned Frequency (MHz)	Max Deviation (kHz)	Limit (ppm)

8.8.1 Frequency Stability Data


FCC Part 90 Limit	1.5	ppm	
FCC Part 90 Limit, as ppb	1500	ppb (Parts per Billion)	
FCC Part 90 Limit, as %	0.00015	%	
Strictest Combined Limit, as Hz	330.000	Hz	
Combined Lower Limit	219.999440	MHz	
Combined Upper Limit	220.000100	MHz	
Rated Supply Voltage	5.0	☐ AC ☒ DC	
Temperature / Voltage Variation			
Temperature (°C)	Supplied Voltage (V)	Frequency (MHz)	Deviation (kHz)
-30	5.0	220.000040	-0.270
-20	5.0	220.000010	-0.240
-10	5.0	219.999900	-0.130
0	5.0	219.999650	0.120
+10	5.0	219.999680	0.090
+20 (reference)	5.0	219.999770	0.000
+20	4.3	219.999770	0.000
+20	5.8	219.999770	0.000
+30	5.0	219.999910	-0.140
+40	5.0	219.999910	-0.140
+50	5.0	219.999890	-0.120

8.8.2 Frequency Stability Plot



8.9 Transient Frequency Behavior

Limits from FCC Part 90.214; and test procedure from ANSI C63.26-2015.




N/A

8.10 Adjacent channel power limits

Limits from FCC Part 90.221, and test procedure from ANSI C63.26-2015.

Conducted Test Setup



n/a. The EUT does not operate in a band requiring ACP.

9. ANNEX-B – Test Setup Photographs

Test setup photographs are located in a separate supplementary ANNEX-B document.

10. History of Test Report Changes

Test Report #	Revision #	Description	Date of Issue
TR_14337-24_FCC 90_	1	Initial release	7/17/2024
	2	Updated Page 6	9/23/2024

END OF TEST REPORT
