



Electromagnetic Compatibility Test Report

Tests Performed on a Hewlett-Packard

Dual Frequency Card Reader, Model BOISB-1106-00

Radiometrics Document RP-7278



Product Detail:

FCC ID: CNTBOISB110600

IC ID: 466I-BOISB110600

Equipment type: Dual Frequency Card Reader

Test Standards:

US CFR Title 47, Chapter I, FCC Part 15 Subpart C

FCC Part 15 CFR Title 47: 2009

Industry Canada RSS-210, Issue 8: 2010 as required for Category I Equipment

This report concerns: Class II Permissive Change

FCC Part 15.209

Tests Performed For:

Hewlett-Packard

3000 Hanover St.

Palo Alto, CA 94304

Test Facility:

Radiometrics Midwest Corporation

12 East Devonwood

Romeoville, IL 60446

Test Date(s): (Month-Day-Year)

December 1 thru 9, 2011

Document RP-7278 Revisions:

Rev.	Issue Date	Affected Sections	Revised By
0	April 12, 2012		
1	April 20, 2012	10.3.1	Joseph Strzelecki
2	April 23, 2012	4.1	Joseph Strzelecki

Table of Contents

1 ADMINISTRATIVE DATA	3
2 TEST SUMMARY AND RESULTS	3
2.1 RF Exposure Compliance Requirements	3
3 EQUIPMENT UNDER TEST (EUT) DETAILS	4
3.1 EUT Description	4
3.1.1 FCC Section 15.203 & RSS-GEN Antenna Requirements	4
3.2 Related Submittals	4
4 TESTED SYSTEM DETAILS	4
4.1 Tested System Configuration	4
4.2 Special Accessories	5
4.3 Equipment Modifications	5
5 TEST SPECIFICATIONS AND RELATED DOCUMENTS	5
6 RADIOMETRICS' TEST FACILITIES	6
7 DEVIATIONS AND EXCLUSIONS FROM THE TEST SPECIFICATIONS	6
8 CERTIFICATION	6
9 TEST EQUIPMENT TABLE	6
10 TEST SECTIONS	7
10.1 AC Conducted Emissions	7
10.2 Radiated RF Emissions	10
10.2.1 Field Strength Calculation	11
10.2.2 Radiated Emissions Test Results	11
10.3 Magnetic Field Measurements and Decay Factor Calculations	15
10.3.1 Magnetic Field Radiated Emissions Results (0.009 to 30 MHz)	15
10.4 Occupied Bandwidth Data	16

Notice: This report must not be reproduced (except in full) without the written approval of Radiometrics Midwest Corporation.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report

Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader

1 ADMINISTRATIVE DATA


Equipment Under Test:

A Hewlett-Packard, Dual Frequency Card Reader

Model: BOISB-1106-00

Product Numbers: BOD40A and CZ208A

These will be referred to as the EUT in this Report

<i>Date EUT Received at Radiometrics: (Month-Day-Year)</i> December 1, 2011	<i>Test Date(s): (Month-Day-Year)</i> December 1 thru 9, 2011
<i>Test Report Written By:</i> Joseph Strzelecki Senior EMC Engineer	<i>Test Witnessed By:</i> The tests were not witnessed by Hewlett-Packard
<i>Radiometrics' Personnel Responsible for Test:</i>  Joseph Strzelecki Senior EMC Engineer NARTE EMC-000877-NE	<i>Test Report Approved By</i>  Chris W. Carlson Director of Engineering NARTE EMC-000921-NE

2 TEST SUMMARY AND RESULTS

The EUT (Equipment Under Test) is a Dual Frequency Card Reader, Model BOISB-1106-00, manufactured by Hewlett-Packard. The detailed test results are presented in a separate section. The following is a summary of the test results.

Emissions Tests Results

Environmental Phenomena	Frequency Range	Basic Standard	Test Result
RF Radiated Emissions	30-1000 MHz	RSS-210 & FCC Part 15	Pass
Conducted Emissions, AC Mains	0.15 - 30 MHz	RSS-210 & FCC Part 15	Pass
RF Radiated Emissions H-Field	0.009 – 30 MHz	RSS-210 & FCC Part 15	Pass

2.1 RF Exposure Compliance Requirements

Since the effective power output is less than 1 mW, the EUT meets the FCC requirement for RF exposure and is exempt from RSS-102. There are no power level adjustments and the antenna is permanently attached. The detailed calculations for RF Exposure are presented in a separate document.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report

Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader

3 EQUIPMENT UNDER TEST (EUT) DETAILS

3.1 EUT Description

The EUT is a dual frequency card reader, Model BOISB-1106-00, manufactured by Hewlett-Packard. The difference between the two part numbers being that the BOD40A has an RS-232 interface and the model CZ208A has a USB interface. Both products have the same PCB, with either the USB or the serial port populated. The EUT was in good working condition during the tests, with no known defects.

3.1.1 FCC Section 15.203 & RSS-GEN Antenna Requirements

The antenna is permanently attached to the PCB. The antenna is internal to the EUT and it is not readily available to be modified by the end user.

3.2 Related Submittals

Hewlett-Packard is not submitting any other products simultaneously for equipment authorization related to the EUT.

4 TESTED SYSTEM DETAILS

4.1 Tested System Configuration

The system was configured for testing in a typical fashion. The EUT was placed on an 80-cm high, nonconductive test stand. The testing was performed in conditions as close as possible to installed conditions. Wiring was consistent with manufacturer's recommendations. Power was supplied at 115 VAC, 60 Hz single-phase to the host computer. The EUT was powered from either the USB or PS/2 port.

The identification for all equipment, plus descriptions of all cables used in the tested system, are:

Tested System Configuration List

Item	Description	Type*	Manufacturer	Model Number	Serial Number
1	Card Reader: serial version	E	RF IDeas	BOISB-1106-00 Product Number BOD40A	Sample 1
2	Card Reader: USB version	E	RF IDeas	BOISB-1106-00 Product Number CZ208A	Sample 2
3	IBM Desktop	H	IBM	31U	KCHR8AA (COMP2)
4	LCD Monitor	P	HP	P9621D	CNC5272RNC
5	Modem MDM-01	P	US Robotics	0701	22SBBAC9FPMN
6	Mouse MS-01	P	IBM	MO09KZ	23-001330

* Type: E = EUT, P = Peripheral, S = Support Equipment; H = Host Computer

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report	
Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader	

List of Cables

QTY	Length (m)	Cable Description	Connected to (Item #)	Shielded?
1	1.85	USB Cable to Card Reader	#2 and #3	Yes
	1.8	Serial Cable to Card Reader	#1 and #3	Yes
1	1.1	Serial Cable from modem to computer	#3 and #5	Yes
1	1.8	AC Cord to Computer	#3 Power input	No
1	1.5	Video Cable	#3 to #4	Yes

See previous table for Item #'s.

4.2 Special Accessories

No special accessories were used during the tests in order to achieve compliance.

4.3 Equipment Modifications

No modifications were made at Radiometrics in order to meet the requirements listed in this report.

4.4 Description of Permissive Change

Summary of changes for this version of the product (PCB-1038-04):

1. Introduced Serial interface option 3.3V circuit. No PCB rework. No jumpers are needed. The traces were already in place.
2. A negative 5V RF switch was introduced. This must be on to enable 13.56 MHz operation. It is disabled for sleep mode when current is less than 1mA.

5 TEST SPECIFICATIONS AND RELATED DOCUMENTS

Document	Date	Title
FCC CFR Title 47	2009	Code of Federal Regulations Title 47, Chapter 1, Federal Communications Commission, Part 15 - Radio Frequency Devices
ANSI C63.4-2003	2003	Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz
IC RSS-210 Issue 8	2010	Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands) Category I Equipment
IC RSS-Gen Issue 3	2010	General Requirements and Information for the Certification of Radiocommunication Equipment (RSS-Gen)

The test procedures used are in accordance with the Industry Canada RSS-Gen and ANSI document C63.4-2003, "Methods of Measurement of Radio Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The specific procedures are described herein. Radiated testing was performed at an antenna to EUT distance of 3 meters. The antenna was raised and lowered from 1 to 4 meters.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report

Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader

6 RADIOMETRICS' TEST FACILITIES

The results of these tests were obtained at Radiometrics Midwest Corp. in Romeoville, Illinois, USA. Radiometrics is accredited by A2LA (American Association for Laboratory Accreditation) to conform to ISO/IEC 17025: 2005 "General Requirements for the Competence of Calibration and Testing Laboratories". Radiometrics' Lab Code is 121191 and Certification Number is 1495.01. Radiometrics' scope of accreditation includes all of the test methods listed herein. A copy of the accreditation can be accessed on our web site (www.radiomet.com). Radiometrics accreditation status can be verified at A2LA's web site (www.a2la2.org).

The following is a list of shielded enclosures located in Romeoville, Illinois used during the tests:

Chamber A: Is an anechoic chamber that measures 24' L X 12' W X 12' H. The walls and ceiling are fully lined with ferrite absorber tiles. The floor has a 10' x 10' section of ferrite absorber tiles located in the center. Panashield of Rowayton, Connecticut manufactured the chamber. The enclosure is NAMAS certified.

Chamber E: Is a custom made anechoic chamber that measures 52' L X 30' W X 18' H. The walls and ceiling are fully lined with RF absorber. Pro-shield of Collinsville, Oklahoma manufactured the chamber.

Test Station F: Is an area that measures 10' D X 12' W X 10' H. The floor and back wall are metal shielded. This area is used for conducted emissions measurements.

A separate ten-foot long, brass plated, steel ground rod attached via a 6 inch copper braid grounds each of the above chambers. Each enclosure is also equipped with low-pass power line filters.

The FCC has accepted these sites as test site number US1065. The FCC test site Registration Number is 732175. Details of the site characteristics are on file with the Industry Canada as site number IC3124A-1.

A complete list of the test equipment is provided herein. The calibration due dates are indicated on the equipment list. The equipment is calibrated in accordance to ANSI/NCSL Z540-1 with traceability to the National Institute of Standards and Technology (NIST).

7 DEVIATIONS AND EXCLUSIONS FROM THE TEST SPECIFICATIONS

There were no deviations or exclusions from the test specifications.

8 CERTIFICATION

Radiometrics Midwest Corporation certifies that the data contained herein was taken under conditions that meet or exceed the requirements of the test specification. The results relate only to the EUT listed herein. Any modifications made to the EUT subsequent to the indicated test date will invalidate the data and void this certification.

9 TEST EQUIPMENT TABLE

RMC ID	Manufacturer	Description	Model No.	Serial No.	Frequency Range	Cal Period	Cal Date
AMP-22	Anritsu	Pre-amplifier	MH648A	M23969	0.1-1200MHz	12 Mo.	01/18/11
ANT-04	Tensor	Biconical Antenna	4104	2246	20-250MHz	24 Mo.	07/06/10

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report							
Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader							

RMC ID	Manufacturer	Description	Model No.	Serial No.	Frequency Range	Cal Period	Cal Date
ANT-06	EMCO	Log-Periodic Ant.	3146	1248	200-1000MHz	24 Mo.	12/14/09
ANT-44	Impossible Machine	Super Log Antenna	SL-20M2G	1002	20-2000MHz	24 Mo.	11/25/09 12/14/11
ANT-53	EMCO	Loop Antenna	6507	1453	1 kHz-30 MHz	24 Mo	10/26/11
HPF-01	Solar	High Pass Filter	7930-100	HPF-1	0.15-30MHz	24 Mo.	02/18/11
LSN-01	Electrometrics	50 uH LISN	FCC/VDE 50/2	1001	0.01-30MHz	12 Mo.	06/14/11
LSN-03	Farnell	50 uH LISN	1EXLSN30B	000314	0.01-30MHz	12 Mo.	06/14/11
REC-03	Anritsu	Spectrum Analyzer	MS2601B	MT94589	0.01-2200MHz	12 Mo.	03/18/11
REC-07	Anritsu	Spectrum Analyzer	MS2601A	MT53067	0.01-2200MHz	12 Mo.	01/21/11
THM-02	Fluke	Temp/Humid Meter	971	93490471	N/A	24 Mo.	04/01/10

Note: All calibrated equipment is subject to periodic checks.

10 TEST SECTIONS

10.1 AC Conducted Emissions

The tests and limits are in accordance with FCC section 15.207 and RSS Gen section 7.2.2.

A computer-controlled analyzer was used to perform the conducted emissions measurements. The frequency range was divided into 500 subranges equally spaced on a logarithmic scale. The computer recorded the peak of each subrange. This data was then plotted on semi-log graph paper generated by the computer and plotter. Adjusting the positions of the cables and orientation of the test system then maximizes the highest emissions.

Mains Conducted emission measurements were performed using a 50 Ohm/50 uH Line Impedance Stabilization Network (LISN) as the pick-up device. Measurements were repeated on both leads within the power cord. If the EUT power cord exceeded 80 cm in length, the excess length of the power cord was made into a 30 to 40 cm bundle near the center of the cord. The LISN was placed on the floor at the base of the test platform and electrically bonded to the ground plane.

FCC/IC Limits of Conducted Emissions at the AC Mains Ports

Frequency Range (MHz)	Class B Limits (dBuV)	
	Quasi-Peak	Average
0.150 - 0.50*	66 - 56	56 - 46
0.5 - 5.0	56	46
5.0 - 30	60	50

* The limit decreases linearly with the logarithm of the frequency in this range.

The initial step in collecting conducted data is a peak detector scan and the plotting of the measurement range. Significant peaks are then marked as shown on the following table, and these signals are then measured with the quasi-peak detector. The following represents the worst case emissions from the host computer (with the EUT connected) power cord, after testing all modes of operation.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report


Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader

Serial	Lead Tested	Freq. MHz	Quasi Peak		Average		Margin dB
			Amplitude dBuV	Limit dBuV	Amplitude dBuV	Limit dBuV	
BOD40A	AC Hot	0.150	51.7	66.0	40.2	56.0	14.3
BOD40A	AC Hot	0.179	52.7	64.6	35.5	54.6	11.9
BOD40A	AC Hot	0.188	50.5	64.1	34.3	54.1	13.6
BOD40A	AC Hot	0.256	49.9	61.6	27.2	51.6	11.7
BOD40A	AC Hot	1.068	44.7	56.0	29.1	46.0	11.3
BOD40A	AC Hot	1.442	44.4	56.0	32.4	46.0	11.6
BOD40A	AC Hot	1.921	45.3	56.0	29.1	46.0	10.7
BOD40A	AC Hot	2.476	45.6	56.0	25.9	46.0	10.4
BOD40A	AC Hot	2.738	45.1	56.0	23.7	46.0	10.9
BOD40A	AC Hot	3.235	45.0	56.0	28.4	46.0	11
BOD40A	AC Hot	3.754	46.1	56.0	20.8	46.0	9.9
BOD40A	AC Hot	13.566	50.1	60.0	47.6	50.0	2.4
BOD40A	AC Neutral	0.156	52.9	65.7	38.7	55.7	12.8
BOD40A	AC Neutral	0.203	52.0	63.5	29.8	53.5	11.5
BOD40A	AC Neutral	0.285	49.6	60.7	31.4	50.7	11.1
BOD40A	AC Neutral	0.317	48.8	59.8	35.8	49.8	11
BOD40A	AC Neutral	0.447	45.7	56.9	38.9	46.9	8
BOD40A	AC Neutral	0.550	45.8	56.0	31.1	46.0	10.2
BOD40A	AC Neutral	2.194	46.2	56.0	33.3	46.0	9.8
BOD40A	AC Neutral	2.416	44.8	56.0	25.9	46.0	11.2
BOD40A	AC Neutral	3.289	37.1	56.0	27.7	46.0	18.3
BOD40A	AC Neutral	5.256	45.8	60.0	25.0	50.0	14.2
CZ208A	AC Hot	0.169	52.2	65.0	36.2	55.0	12.8
CZ208A	AC Hot	0.197	53.4	63.7	32.6	53.7	10.3
CZ208A	AC Hot	0.221	53.6	62.8	26.4	52.8	9.2
CZ208A	AC Hot	1.421	44.5	56.0	22.4	46.0	11.5
CZ208A	AC Hot	1.628	40.3	56.0	25.9	46.0	15.7
CZ208A	AC Hot	1.902	42.6	56.0	26.8	46.0	13.4
CZ208A	AC Hot	2.381	47.5	56.0	22.4	46.0	8.5
CZ208A	AC Hot	2.687	44.9	56.0	23.7	46.0	11.1
CZ208A	AC Hot	3.167	45.7	56.0	23.7	46.0	10.3
CZ208A	AC Hot	3.633	45.4	56.0	26.8	46.0	10.6
CZ208A	AC Hot	4.321	43.0	56.0	20.8	46.0	13
CZ208A	AC Hot	5.439	47.7	60.0	20.9	50.0	12.3
CZ208A	AC Hot	6.453	47.6	60.0	26.0	50.0	12.4
CZ208A	AC Hot	6.963	45.3	60.0	26.0	50.0	14.7
CZ208A	AC Hot	10.180	45.6	60.0	29.1	50.0	14.4
CZ208A	AC Hot	18.369	45.8	60.0	26.8	50.0	14.2
CZ208A	AC Hot	24.231	34.8	60.0	20.0	50.0	25.2
CZ208A	AC Neutral	0.157	53.0	65.6	39.1	55.6	12.6
CZ208A	AC Neutral	0.226	51.1	62.6	27.4	52.6	11.5
CZ208A	AC Neutral	0.250	51.2	61.7	30.2	51.7	10.5
CZ208A	AC Neutral	2.136	45.8	56.0	25.9	46.0	10.2
CZ208A	AC Neutral	4.343	44.3	56.0	23.8	46.0	11.7

Test Date : December 1, 2011


QP readings are quasi-peak with a 9 kHz bandwidth and no video filter.

Judgment: Passed by 2.4 dB

Figure 1. Conducted Emissions Test Setup (USB Reader)**Notes:**

- LISN's at least 80 cm from EUT chassis
- Vertical conductive plane 40 cm from rear of table top
- EUT power cord bundled

1x1.5m surface

Figure 2. Conducted Emissions Test Setup (Serial Reader)

10.2 Radiated RF Emissions

Radiated emission measurements were performed with linearly polarized broadband antennas. The results obtained with these antennas can be correlated with results obtained with a tuned dipole antenna. The radiated emission measurements were performed with a spectrum analyzer. The bandwidth used from 150 kHz to 30 MHz is 9 or 10 kHz and the bandwidth from 30 MHz to 1000 MHz is 100 or 120 kHz. Above 1 GHz, a 1 MHz bandwidth is used. A 10 dB linearity check is performed prior to start of testing in order to determine if an overload condition exists.

From 30 to 1000 MHz, an Anritsu spectrum analyzer was used. For tests from 1 to 25 GHz, an HP 8566 spectrum analyzer was used. Figure 4 herein lists the details of the test equipment used during radiated emissions tests.

Final radiated emissions measurements were performed inside of an anechoic chamber at a test distance of 3 meters. The anechoic chamber is designated as Chamber E. This Chamber meets the Site Attenuation requirements of ANSI C63.4 and CISPR 16-1. Chamber E is located at 12 East Devonwood Ave. Romeoville, Illinois EMI test lab.

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report

Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader

The entire frequency range from 30 to 1000 MHz was slowly scanned with particular attention paid to those frequency ranges which appeared high. Measurements were performed using two antenna polarizations, (vertical and horizontal). The worst case emissions were recorded. All measurements may be performed using either the peak, average or quasi-peak detector functions. If the peak detector data exceeds or is marginally close to the limits, the measurements are repeated using a quasi-peak detector or average function as required by the specification for final determination of compliance.

The detected emission levels were maximized by rotating the EUT, adjusting the positions of all cables, and by scanning the measurement antenna from 1 to 4 meters above the ground.

10.2.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Loss, and by subtracting the Amplifier Gain from the measured reading. The basic equation is as follows:

$$FS = RA + AF + CF - AG$$

Where: FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

10.2.2 Radiated Emissions Test Results

Test Date	12/01/2011						
Test Distance	3 Meters						
Specification	FCC Part 15 Subpart C & RSS-210						
Abbreviations	P = peak; Q = QP Pol = Antenna Polarization; V = Vertical; H = Horizontal; For Antenna Type Biconical = (ANT-03) Log periodic (ANT-06); Horn = (ANT-13)						
EUT	BOD40A						

Freq. MHz	Meter Reading dBuV	Dect. Type	Antenna		Corr. Factors dB	Field Strength dBuV/m		Margin Under Limit dB
			Factor dB	Pol/ ID#		EUT	Limit	
61.6	40.0	P	10.3	H/03	-27.7	22.6	40.0	17.4
110.4	50.4	P	14.6	H/03	-27.0	38.0	43.5	5.5
110.6	48.9	Q	14.7	H/03	-27.0	36.6	43.5	6.9
132.8	45.2	P	11.5	H/03	-26.9	29.8	43.5	13.7
168.8	42.6	P	16.0	H/03	-26.6	32.0	43.5	11.5
220.7	32.5	Q	10.6	H/06	-26.2	16.9	46.0	29.1
247.4	42.9	P	11.5	H/06	-26.0	28.4	46.0	17.6
263.6	44.9	P	12.1	H/06	-26.0	31.0	46.0	15.0
300.6	38.6	P	13.5	H/06	-25.8	26.3	46.0	19.7
321.9	36.2	P	14.2	H/06	-25.7	24.7	46.0	21.3
347.1	35.0	P	14.1	H/06	-25.6	23.5	46.0	22.5
363.3	37.3	P	14.4	H/06	-25.6	26.1	46.0	19.9
400.3	41.2	P	14.9	H/06	-25.4	30.7	46.0	15.3
433.9	38.5	P	15.9	H/06	-25.3	29.1	46.0	16.9
451.2	35.1	P	15.8	H/06	-25.2	25.7	46.0	20.3
479.2	32.6	P	17.2	H/06	-25.0	24.8	46.0	21.2
530.0	32.9	P	17.3	H/06	-24.5	25.7	46.0	20.3

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report

Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader

Freq. MHz	Meter Reading dBuV	Dect. Type	Antenna		Corr. Factors dB	Field Strength dBuV/m		Margin Under Limit dB
			Factor dB	Pol/ ID#		EUT	Limit	
582.0	30.6	P	18.5	H/06	-24.0	25.1	46.0	20.9
701.0	32.2	P	21.0	H/06	-23.6	29.6	46.0	16.4
731.0	30.5	P	19.9	H/06	-23.4	27.0	46.0	19.0
801.0	33.6	P	20.3	H/06	-22.6	31.3	46.0	14.7
868.0	29.7	P	22.6	H/06	-21.9	30.4	46.0	15.6
931.0	31.8	P	22.4	H/06	-21.3	32.9	46.0	13.1
33.2	52.6	P	11.0	V/03	-28.1	35.5	40.0	4.5
61.4	48.3	Q	10.4	V/03	-27.7	31.0	40.0	9.0
67.2	52.4	P	8.5	V/03	-27.5	33.4	40.0	6.6
108.5	50.1	Q	14.0	V/03	-27.1	37.0	43.5	6.5
109.0	50.5	Q	14.1	V/03	-27.1	37.5	43.5	6.0
146.5	35.4	Q	12.8	V/03	-26.8	21.4	43.5	22.1
150.2	32.6	Q	13.4	V/03	-26.8	19.2	43.5	24.3
169.4	33.6	Q	16.0	V/03	-26.6	23.0	43.5	20.5
171.4	39.8	Q	16.3	V/03	-26.6	29.5	43.5	14.0
184.8	32.0	Q	17.2	V/03	-26.4	22.8	43.5	20.7
219.5	30.9	Q	10.6	V/06	-26.2	15.3	46.0	30.7
249.1	46.1	P	11.6	V/06	-26.0	31.7	46.0	14.3
293.3	40.1	P	13.1	V/06	-25.8	27.4	46.0	18.6
328.0	40.2	P	13.9	V/06	-25.7	28.4	46.0	17.6
366.1	37.7	P	14.3	V/06	-25.6	26.4	46.0	19.6
408.1	40.4	P	14.8	V/06	-25.4	29.8	46.0	16.2
432.8	39.7	P	15.9	V/06	-25.3	30.3	46.0	15.7
456.3	36.6	P	15.7	V/06	-25.1	27.2	46.0	18.8
492.1	36.2	P	17.4	V/06	-24.9	28.7	46.0	17.3
506.0	34.3	P	17.3	V/06	-24.8	26.8	46.0	19.2
601.0	32.8	P	18.1	V/06	-23.8	27.1	46.0	18.9
665.0	33.4	P	19.7	V/06	-23.5	29.6	46.0	16.4
731.0	32.3	P	19.9	V/06	-23.4	28.8	46.0	17.2
798.0	29.3	P	20.4	V/06	-22.7	27.0	46.0	19.0
864.0	28.4	P	22.9	V/06	-21.9	29.4	46.0	16.6
979.0	27.2	P	22.2	V/06	-20.8	28.6	54.0	25.4
Product Number			CZ208A					
60.4	47.2	P	10.6	H/03	-27.6	30.2	40.0	9.8
76.8	39.5	P	6.5	H/03	-27.3	18.7	40.0	21.3
109.6	51.2	P	14.3	H/03	-27.1	38.4	43.5	5.1
110.0	45.7	Q	14.5	H/03	-27.1	33.1	43.5	10.4
138.0	38.6	P	11.7	H/03	-26.8	23.5	43.5	20.0
184.3	32.7	Q	17.1	H/03	-26.4	23.4	43.5	20.1
199.2	47.1	P	16.4	H/03	-26.3	37.2	43.5	6.3
93.2	43.2	P	11.8	H/04	-27.1	27.9	43.5	15.6
107.6	51.7	P	13.8	H/04	-27.1	38.4	43.5	5.1
110.6	43.7	Q	14.7	H/04	-27.0	31.4	43.5	12.1
137.2	41.6	P	11.6	H/04	-26.8	26.4	43.5	17.1
151.2	44.5	P	13.6	H/04	-26.8	31.3	43.5	12.2
199.2	45.3	P	16.4	H/04	-26.3	35.4	43.5	8.1
200.1	33.7	Q	10.8	H/06	-26.3	18.2	43.5	25.3
200.1	38.5	Q	10.8	H/06	-26.3	23.0	43.5	20.5
200.3	46.3	Q	10.8	H/06	-26.3	30.8	43.5	12.7
231.2	44.9	P	10.4	H/06	-26.1	29.2	46.0	16.8

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report							
Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader							

Freq. MHz	Meter Reading dBuV	Dect. Type	Antenna		Corr. Factors dB	Field Strength dBuV/m		Margin Under Limit dB
			Factor dB	Pol/ ID#		EUT	Limit	
250.8	45.1	P	11.8	H/06	-26.0	30.9	46.0	15.1
276.5	44.4	P	12.8	H/06	-25.9	31.3	46.0	14.7
277.1	43.4	P	12.9	H/06	-25.9	30.4	46.0	15.6
305.6	39.4	P	14.2	H/06	-25.8	27.8	46.0	18.2
322.4	44.4	P	14.2	H/06	-25.7	32.9	46.0	13.1
368.4	45.5	P	14.3	H/06	-25.6	34.2	46.0	11.8
399.7	42.5	P	14.9	H/06	-25.4	32.0	46.0	14.0
414.3	42.1	P	15.1	H/06	-25.3	31.9	46.0	14.1
460.6	46.3	Q	15.9	H/06	-25.0	37.2	46.0	8.8
487.1	36.7	P	17.2	H/06	-25.0	28.9	46.0	17.1
507.0	39.6	P	17.3	H/06	-24.8	32.1	46.0	13.9
553.0	35.9	P	17.9	H/06	-24.3	29.5	46.0	16.5
599.0	37.7	P	18.1	H/06	-23.8	32.0	46.0	14.0
645.0	34.9	P	19.9	H/06	-23.5	31.3	46.0	14.7
691.0	41.4	P	20.3	H/06	-23.6	38.1	46.0	7.9
784.0	40.2	P	21.4	H/06	-22.9	38.7	46.0	7.3
876.0	39.1	P	21.8	H/06	-21.8	39.1	46.0	6.9
923.0	33.8	P	22.5	H/06	-21.4	34.9	46.0	11.1
968.0	35.2	P	22.7	H/06	-20.9	37.0	54.0	17.0
58.9	43.6	Q	10.9	V/03	-27.6	26.9	40.0	13.1
80.4	55.0	P	6.9	V/03	-27.4	34.5	40.0	5.5
94.2	46.4	Q	11.6	V/03	-27.2	30.8	43.5	12.7
94.4	52.5	P	11.6	V/03	-27.2	36.9	43.5	6.6
108.5	53.5	Q	14.0	V/03	-27.1	40.4	43.5	3.1
143.6	48.7	P	12.3	V/03	-26.8	34.2	43.5	9.3
163.2	49.0	P	15.4	V/03	-26.7	37.7	43.5	5.8
163.7	35.5	Q	15.4	V/03	-26.7	24.2	43.5	19.3
175.1	38.2	Q	16.7	V/03	-26.6	28.3	43.5	15.2
58.0	51.8	P	10.9	V/04	-27.7	35.0	40.0	5.0
58.9	43.2	Q	10.9	V/04	-27.6	26.5	40.0	13.5
108.8	52.4	Q	14.1	V/04	-27.1	39.4	43.5	4.1
153.4	35.9	Q	14.1	V/04	-26.8	23.2	43.5	20.3
199.2	46.6	P	16.4	V/04	-26.3	36.7	43.5	6.8
200.2	33.9	Q	10.8	V/06	-26.3	18.4	43.5	25.1
217.6	49.5	P	10.7	V/06	-26.2	34.0	46.0	12.0
226.7	43.3	P	10.5	V/06	-26.2	27.6	46.0	18.4
249.6	41.6	P	11.7	V/06	-26.0	27.3	46.0	18.7
267.0	45.0	P	12.1	V/06	-26.0	31.1	46.0	14.9
277.1	40.3	P	12.9	V/06	-25.9	27.3	46.0	18.7
283.2	50.0	P	13.0	V/06	-25.9	37.1	46.0	8.9
310.1	42.9	P	14.6	V/06	-25.8	31.7	46.0	14.3
320.8	41.9	P	14.3	V/06	-25.7	30.5	46.0	15.5
340.9	41.5	P	13.9	V/06	-25.6	29.8	46.0	16.2
357.2	43.6	P	14.7	V/06	-25.6	32.7	46.0	13.3
368.9	44.3	P	14.3	V/06	-25.6	33.0	46.0	13.0
377.3	46.7	P	14.4	V/06	-25.6	35.5	46.0	10.5
413.7	39.5	P	15.1	V/06	-25.3	29.3	46.0	16.7
416.0	39.8	P	15.3	V/06	-25.3	29.8	46.0	16.2
460.8	45.9	P	15.9	V/06	-25.0	36.8	46.0	9.2
472.5	46.6	P	16.9	V/06	-25.0	38.5	46.0	7.5

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report


Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader

Freq. MHz	Meter Reading dBuV	Dect. Type	Antenna		Corr. Factors dB	Field Strength dBuV/m		Margin Under Limit dB
			Factor dB	Pol/ ID#		EUT	Limit	
493.2	39.1	P	17.4	V/06	-24.9	31.6	46.0	14.4
495.5	39.5	P	17.5	V/06	-24.9	32.1	46.0	13.9
507.0	40.9	P	17.3	V/06	-24.8	33.4	46.0	12.6
553.0	39.0	P	17.9	V/06	-24.3	32.6	46.0	13.4
599.0	40.5	P	18.1	V/06	-23.8	34.8	46.0	11.2
645.0	37.1	P	19.9	V/06	-23.5	33.5	46.0	12.5
691.0	38.4	P	20.3	V/06	-23.6	35.1	46.0	10.9
784.0	35.1	P	21.4	V/06	-22.9	33.6	46.0	12.4
875.0	32.4	P	21.8	V/06	-21.8	32.4	46.0	13.6
921.0	30.2	P	22.4	V/06	-21.4	31.2	46.0	14.8
968.0	30.1	P	22.7	V/06	-20.9	31.9	54.0	22.1

Judgment: Passed by 3.1 dB

Figure 3. Drawing of Radiated Emissions Test Setup

Chamber E, anechoic



Notes:

- Not to Scale
- Antenna height varied 1-4 meters
- Distance from antenna to tested system is 3 meters
- AC cords not shown. They are connected to AC outlet with low-pass filter on turntable

Frequency Range	Receive Antenna	Pre-Amplifier	Spectrum Analyzer
0.01 to 30 MHz	ANT-53	None	REC-07
30 to 1000 MHz	ANT-44	AMP-22	REC-07

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report

Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader

10.3 Magnetic Field Measurements and Decay Factor Calculations

Radiated emission measurements are performed with shielded loop antennas. An EMCO Loop antenna was used. The antenna was rotated in order to find the maximize readings.

The distance factor in (dB) = DE*20*Log(TD/SD)
 Where: DE = Decay Exponent (2.0 is used for this)
 TD = Test distance in meters. This is usually 3 meters
 SD = Specification Distance in meters

For frequencies below 490 kHz, the specification distance is 300 meters below 490 kHz. The Distance correction factor at 3 meters is -80 dB for frequencies below 490 kHz.

For frequencies above 490 kHz, the specification distance is 30. The Distance correction factor at 3 meters is -40 dB.

10.3.1 Magnetic Field Radiated Emissions Results (0.009 to 30 MHz)

Test Date	December 1, 2011								
Test Distance	3 Meters								
Specification	FCC 15 & RSS-210								
Notes	Corr. Factors = cable loss - preamp gain - distance factor. Shielded Loop Antennas were used for this test.								
Configuration									

125 kHz Frequencies

Freq (kHz)	meter reading dBuV	Loop Ant Factor	Dist (m)	Decay exp	Cable Loss dB	FCC Distance factor dB	Field Strength dBuV/m	FCC 15.209 Limit dBuV/m	Margin under limit	Model
125.0	65.1	20.0	3.0	2.0	0.0	-80.0	5.1	25.7	20.6	USB
250.0	47.0	19.8	3.0	2.0	0.0	-80.0	-13.2	19.6	32.8	USB
375.0	33.9	19.5	3.0	2.0	0.0	-80.0	-26.6	16.1	42.7	USB
125.0	64.6	20.0	3.0	2.0	0.0	-80.0	4.6	25.7	21.1	Serial
250.0	48.2	19.8	3.0	2.0	0.0	-80.0	-12.0	19.6	31.6	Serial
375.0	34.1	19.5	3.0	2.0	0.0	-80.0	-26.4	16.1	42.5	Serial

13.56 MHz Frequencies

Freq (MHz)	meter reading dBuV	Loop Ant Factor	Dist (m)	Decay exp	Cable Loss dB	FCC Distance factor dB	Field Strength dBuV/m	FCC 15.209 Limit dBuV/m	Margin under limit	Model
13.560	46.1	17.5	3.0	2.0	0.4	-40.0	24.0	29.5	5.5	USB
27.120	22.9	16.9	3.0	2.0	0.5	-40.0	0.3	29.5	29.2	USB
13560	45.8	17.5	3.0	2.0	0.4	-40.0	23.7	29.5	5.8	Serial
27120	23.8	16.9	3.0	2.0	0.5	-40.0	1.2	29.5	28.3	Serial

Judgement: Passed by 6.4 dB.


No other emissions were detected from 9 kHz to 30 MHz.

10.4 Occupied Bandwidth Data

The occupied bandwidth of the RF output was measured using a spectrum analyzer. The bandwidth was measured using the peak detector function and a narrow resolution bandwidth.

A broadband antenna was used to receive the modulated signal. The spectrum analyzer was set to the MAX HOLD mode to record the worst case of the modulation. The spectrum analyzer display was digitized and plotted. A limit was drawn on the plots based on the level of the modulated carrier. The plots of the occupied bandwidth for the EUT are supplied on the following page.


Figure 4. Occupied Bandwidth Plots 125 kHz



USB

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report

Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader



Company: Hewlett-Packard

CENTER 125.0 kHz

RES BW 1 kHz

10 dB/

Notes: 20 dB Bandwidth, 125 kHz

ITEM : BOD40A

REF 0.0 dBm

VBW 10 kHz

Time: 16:59

Date : 12-08-2011

SPAN 10.0 kHz

ATTEN 10 dB

SWP 480 msec

File: BW2-S


Serial

Bandwidth = 4.02 kHz

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report

Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader


Figure 5. Occupied Bandwidth Plots 13.56 MHz



USB

RADIOMETRICS MIDWEST CORPORATION - EMC Test Report

Testing of a Hewlett-Packard, Model BOISB-1106-00, Dual Frequency Card Reader



Serial

Bandwidth = 3.98 kHz