

## FCC Test Report (BT-EDR)

**Report No.:** RF160819E01A-1

**FCC ID:** COF-WMBNBM26A

**Test Model:** WM-BN-BM-26\_A

**Received Date:** June 28, 2017

**Test Date:** July 11 to 13, 2017

**Issued Date:** Aug. 04, 2017

**Applicant:** UNIVERSAL GLOBAL SCIENTIFIC INDUSTRIAL CO., LTD.

**Address:** 141, Lane 351, Sec. 1, Taiping Road., Tsaoctuen, Nantou 54261, Taiwan

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

**Test Location (1):** E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,  
Taiwan R.O.C.

**Test Location (2):** No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin  
Chu Hsien 307, Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

<b>Release Control Record .....</b>	<b>3</b>
<b>1      Certificate of Conformity.....</b>	<b>4</b>
<b>2      Summary of Test Results.....</b>	<b>5</b>
2.1    Measurement Uncertainty .....	5
2.2    Modification Record .....	5
<b>3      General Information.....</b>	<b>6</b>
3.1    General Description of EUT (BT-EDR).....	6
3.2    Description of Test Modes .....	7
3.2.1 Test Mode Applicability and Tested Channel Detail.....	8
3.3    Description of Support Units .....	10
3.3.1 Configuration of System under Test .....	11
3.4    General Description of Applied Standards .....	12
<b>4      Test Types and Results .....</b>	<b>13</b>
4.1    Radiated Emission and Bandedge Measurement.....	13
4.1.1 Limits of Radiated Emission and Bandedge Measurement .....	13
4.1.2 Test Instruments .....	14
4.1.3 Test Procedures.....	16
4.1.4 Deviation from Test Standard .....	16
4.1.5 Test Setup.....	17
4.1.6 EUT Operating Conditions.....	18
4.1.7 Test Results .....	19
4.2    Maximum Output Power.....	26
4.2.1 Limits of Maximum Output Power Measurement .....	26
4.2.2 Test Setup.....	26
4.2.3 Test Instruments .....	26
4.2.4 Test Procedure .....	26
4.2.5 Deviation from Test Standard .....	26
4.2.6 EUT Operating Condition .....	26
4.2.7 Test Results .....	27
<b>5      Pictures of Test Arrangements.....</b>	<b>28</b>
<b>Appendix – Information on the Testing Laboratories .....</b>	<b>29</b>

### Release Control Record

Issue No.	Description	Date Issued
RF160819E01A-1	Original release.	Aug. 04, 2017

## 1 Certificate of Conformity

**Product:** 802.11b/g/n + BT Wireless LAN Module

**Brand:** USI

**Test Model:** WM-BN-BM-26\_A

**Sample Status:** ENGINEERING SAMPLE

**Applicant:** UNIVERSAL GLOBAL SCIENTIFIC INDUSTRIAL CO., LTD.


**Test Date:** July 11 to 13, 2017

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)

ANSI C63.10: 2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

  
**Prepared by :** \_\_\_\_\_, **Date:** \_\_\_\_\_ Aug. 04, 2017  
Wendy Wu / Specialist

  
**Approved by :** \_\_\_\_\_, **Date:** \_\_\_\_\_ Aug. 04, 2017  
May Chen / Manager

## 2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (SECTION 15.247)			
FCC Clause	Test Item	Result	Remarks
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.205 & 209 & 15.247(d)	Radiated Emissions & Band Edge Measurement	PASS	Meet the requirement of limit. Minimum passing margin is -3.2dB at 343.5MHz.

**NOTE:** If The Frequency Hopping System operating in 2400-2483.5MHz band and the output power less than 125mW. The hopping channel carrier frequencies separated by a minimum of 25kHz or two-thirds of the 20dB bandwidth of hopping channel whichever is greater.

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) (±)
Radiated Emissions up to 1 GHz	30MHz ~ 1GHz	5.32 dB
Radiated Emissions above 1 GHz	1GHz ~ 6GHz	5.14 dB
	6GHz ~ 18GHz	5.04 dB
	18GHz ~ 40GHz	5.25 dB

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT (BT-EDR)

Product	802.11b/g/n + BT Wireless LAN Module
Brand	USI
Test Model	WM-BN-BM-26_A
Status of EUT	ENGINEERING SAMPLE
Power Supply Rating	3.6Vdc from host equipment
Modulation Type	GFSK, $\pi/4$ -DQPSK, 8DPSK
Modulation Technology	FHSS
Transfer Rate	Up to 3Mbps
Operating Frequency	2402MHz ~ 2480MHz
Number of Channel	79
Output Power	3.819mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	NA
Data Cable Supplied	NA

Note:

1. This report is prepared for FCC Class II change. The difference compared with the Report No.: RF160819E01-1 design is as the following:
  - ◆ Changed R30, C46 components.
2. According to above conditions only Output Power and Radiated Emissions test items need to be performed. And all data was verified to meet the requirements.
3. There are WLAN, BT technology used for the EUT.
4. The antenna provided to the EUT, please refer to the following table:

Brand	Model	Antenna Net Gain(dBi)	Frequency range (GHz to GHz)	Antenna Type	Connector Type
YAGEO	ANT3216LL11R2400A	3.68	2.4~2.4835	Chip	NA

5. WLAN and BT technology cannot transmit at same time.
6. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or User's Manual.

### 3.2 Description of Test Modes

79 channels are provided for BT-EDR mode:

Channel	Freq. (MHz)						
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		

### 3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO			DESCRIPTION
	RE≥1G	RE<1G	APCM	
-	√	√	√	-

Where RE≥1G: Radiated Emission above 1GHz RE<1G: Radiated Emission below 1GHz

APCM: Antenna Port Conducted Measurement

**NOTE:**

1. In the original report, the EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.

#### Radiated Emission Test (Above 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

#### Radiated Emission Test (Below 1GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	78	FHSS	8DPSK	3DH5

#### Antenna Port Conducted Measurement:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	3DH5

**Test Condition:**

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE≥1G	22deg. C, 64%RH	120Vac, 60Hz	Rey Chen
RE<1G	25deg. C, 67%RH	120Vac, 60Hz	Weiwei Lo
APCM	25deg. C, 60%RH	120Vac, 60Hz	Anderson Chen

### 3.3 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Test Tool	WM-BN-BM-26_A_EVB TDK V1.1	NA	NA	NA	Supplied by client
B.	DC Power Supply	GOOD WILL INSTRUMENT CO., LTD.	GPC-3030D	7700087	NA	Provided by Lab

Note:

1. All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	DC Cable	1	3	No	0	Provided by Lab

### 3.3.1 Configuration of System under Test



### 3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

**NOTE:**

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

## 4.1.2 Test Instruments

DESCRIPTION & MANUFACTURER	MODEL NO.	SERIAL NO.	CALIBRATED DATE	CALIBRATED UNTIL
Test Receiver Agilent	N9038A	MY50010156	Aug. 18, 2016	Aug. 17, 2017
Pre-Amplifier(*) EMCI	EMC001340	980142	Jan. 20, 2016	Jan. 19, 2018
Loop Antenna(*) Electro-Metrics	EM-6879	264	Dec. 16, 2016	Dec. 15, 2018
RF Cable	NA	LOOPCAB-001 LOOPCAB-002	Jan. 17, 2017	Jan. 16, 2018
Pre-Amplifier Mini-Circuits	ZFL-1000VH2B	AMP-ZFL-05	May 06, 2017	May 05, 2018
Trilog Broadband Antenna SCHWARZBECK	VULB 9168	9168-361	Dec. 29, 2016	Dec. 28, 2017
RF Cable	8D	966-3-1 966-3-2 966-3-3	Apr. 01, 2017	Mar. 31, 2018
Fixed attenuator Mini-Circuits	UNAT-5+	PAD-3m-3-01	Oct. 05, 2016	Oct. 04, 2017
Horn_Antenna SCHWARZBECK	BBHA9120-D	9120D-406	Dec. 28, 2016	Dec. 27, 2017
Pre-Amplifier EMCI	EMC12630SE	980384	Feb. 02, 2017	Feb. 01, 2018
RF Cable	EMC104-SM-SM-1200 EMC104-SM-SM-2000 EMC104-SM-SM-5000	160922 150317 150322	Feb. 02, 2017 Mar. 29, 2017 Mar. 29, 2017	Feb. 01, 2018 Mar. 28, 2018 Mar. 28, 2018
Spectrum Analyzer Keysight	N9030A	MY54490520	July 29, 2016	July 28, 2017
Pre-Amplifier EMCI	EMC184045SE	980386	Feb. 02, 2017	Feb. 01, 2018
Horn_Antenna SCHWARZBECK	BBHA 9170	BBHA9170608	Dec. 15, 2016	Dec. 14, 2017
RF Cable	SUCOFLEX 102	36432/2 36433/2	Jan. 15, 2017	Jan. 14, 2018
Software	ADT_Radiated_V8.7.08	NA	NA	NA
Antenna Tower & Turn Table Max-Full	MF-7802	MF780208406	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Spectrum Analyzer R&S	FSv40	100964	July 1, 2017	June 30, 2018
Power meter Anritsu	ML2495A	1014008	May 11, 2017	May 10, 2018
Power sensor Anritsu	MA2411B	0917122	May 11, 2017	May 10, 2018

**NOTE:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. \*The calibration interval of the above test instruments is 24 months and the calibrations are traceable to NML/ROC and NIST/USA.
3. The test was performed in 966 Chamber No. 3.
4. The CANADA Site Registration No. is 20331-1
5. Loop antenna was used for all emissions below 30 MHz.
6. Tested Date: July 11 to 12, 2017.

#### 4.1.3 Test Procedures

##### For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Both X and Y axes of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

##### NOTE:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

##### For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

##### Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup


##### For Radiated emission below 30MHz



##### For Radiated emission 30MHz to 1GHz



**For Radiated emission above 1GHz**



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Connected the EUT with the Laptop.
- Controlling software (Broadcom BlueTool V1.4.2) has been activated to set the EUT on specific status.

## 4.1.7 Test Results

## Above 1GHz Data:

## BT\_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.6 PK	74.0	-18.4	1.01 H	264	57.2	-1.6
2	2390.00	41.5 AV	54.0	-12.5	1.01 H	264	43.1	-1.6
3	*2402.00	103.0 PK			1.01 H	264	104.5	-1.5
4	*2402.00	72.9 AV			1.01 H	264	74.4	-1.5
5	4804.00	38.4 PK	74.0	-35.6	1.84 H	195	35.4	3.0
6	4804.00	8.3 AV	54.0	-45.7	1.84 H	195	5.3	3.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	55.1 PK	74.0	-18.9	3.85 V	251	56.7	-1.6
2	2390.00	41.0 AV	54.0	-13.0	3.85 V	251	42.6	-1.6
3	*2402.00	90.1 PK			3.85 V	251	91.6	-1.5
4	*2402.00	60.0 AV			3.85 V	251	61.5	-1.5
5	4804.00	37.5 PK	74.0	-36.5	1.67 V	204	34.5	3.0
6	4804.00	7.4 AV	54.0	-46.6	1.67 V	204	4.4	3.0

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on  $0.625 * 5$  per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1$  dB
7. The average value of fundamental and harmonic frequency is: Average = Peak value +  $20 \log(\text{Duty cycle})$

<b>CHANNEL</b>		TX Channel 39		<b>DETECTOR FUNCTION</b>		Peak (PK)			
<b>FREQUENCY RANGE</b>		1GHz ~ 25GHz				Average (AV)			
<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2441.00	103.2 PK			1.02 H	281	104.7	-1.5	
2	*2441.00	73.1 AV			1.02 H	281	74.6	-1.5	
3	4882.00	38.3 PK	74.0	-35.7	1.75 H	185	35.1	3.2	
4	4882.00	8.2 AV	54.0	-45.8	1.75 H	185	5.0	3.2	
5	7323.00	42.8 PK	74.0	-31.2	2.04 H	143	33.9	8.9	
6	7323.00	12.7 AV	54.0	-41.3	2.04 H	143	3.8	8.9	
<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2441.00	90.3 PK			3.78 V	271	91.8	-1.5	
2	*2441.00	60.2 AV			3.78 V	271	61.7	-1.5	
3	4882.00	37.8 PK	74.0	-36.2	1.72 V	193	34.6	3.2	
4	4882.00	7.7 AV	54.0	-46.3	1.72 V	193	4.5	3.2	
5	7323.00	42.4 PK	74.0	-31.6	2.13 V	299	33.5	8.9	
6	7323.00	12.3 AV	54.0	-41.7	2.13 V	299	3.4	8.9	
<b>REMARKS:</b>									
<ol style="list-style-type: none"> <li>1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)</li> <li>2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)</li> <li>3. The other emission levels were very low against the limit.</li> <li>4. Margin value = Emission Level – Limit value</li> <li>5. " * ": Fundamental frequency.</li> <li>6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: <math>20\log(3.125 / 100) = -30.1</math> dB</li> <li>7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)</li> </ol>									

<b>CHANNEL</b>		TX Channel 78		<b>DETECTOR FUNCTION</b>		Peak (PK)			
<b>FREQUENCY RANGE</b>		1GHz ~ 25GHz				Average (AV)			
<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2480.00	103.4 PK			1.00 H	275	104.8	-1.4	
2	*2480.00	73.3 AV			1.00 H	275	74.7	-1.4	
3	2483.50	55.9 PK	74.0	-18.1	1.00 H	275	57.3	-1.4	
4	2483.50	25.8 AV	54.0	-28.2	1.00 H	275	27.2	-1.4	
5	4960.00	37.9 PK	74.0	-36.1	1.78 H	201	34.7	3.2	
6	4960.00	7.8 AV	54.0	-46.2	1.78 H	201	4.6	3.2	
7	7440.00	43.0 PK	74.0	-31.0	2.01 H	158	33.8	9.2	
8	7440.00	12.9 AV	54.0	-41.1	2.01 H	158	3.7	9.2	
<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2480.00	90.5 PK			3.82 V	256	91.9	-1.4	
2	*2480.00	60.4 AV			3.82 V	256	61.8	-1.4	
3	2483.50	54.7 PK	74.0	-19.3	3.82 V	256	56.1	-1.4	
4	2483.50	24.6 AV	54.0	-29.4	3.82 V	256	26.0	-1.4	
5	4960.00	37.8 PK	74.0	-36.2	1.68 V	198	34.6	3.2	
6	4960.00	7.7 AV	54.0	-46.3	1.68 V	198	4.5	3.2	
7	7440.00	42.8 PK	74.0	-31.2	2.11 V	302	33.6	9.2	
8	7440.00	12.7 AV	54.0	-41.3	2.11 V	302	3.5	9.2	
<b>REMARKS:</b>									
<ol style="list-style-type: none"> <li>1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)</li> <li>2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)</li> <li>3. The other emission levels were very low against the limit.</li> <li>4. Margin value = Emission Level – Limit value</li> <li>5. " * ": Fundamental frequency.</li> <li>6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: <math>20\log(3.125 / 100) = -30.1</math> dB</li> <li>7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)</li> </ol>									

**BT\_8DPSK**

<b>CHANNEL</b>	TX Channel 0	<b>DETECTOR FUNCTION</b>	Peak (PK)
<b>FREQUENCY RANGE</b>	1GHz ~ 25GHz		Average (AV)

<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.8 PK	74.0	-19.2	1.00 H	274	56.4	-1.6
2	2390.00	41.8 AV	54.0	-12.2	1.00 H	274	43.4	-1.6
3	*2402.00	101.0 PK			1.00 H	274	102.5	-1.5
4	*2402.00	70.9 AV			1.00 H	274	72.4	-1.5
5	4804.00	38.2 PK	74.0	-35.8	1.82 H	206	35.2	3.0
6	4804.00	8.1 AV	54.0	-45.9	1.82 H	206	5.1	3.0

<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	54.3 PK	74.0	-19.7	3.41 V	273	55.9	-1.6
2	2390.00	41.0 AV	54.0	-13.0	3.41 V	273	42.6	-1.6
3	*2402.00	87.6 PK			3.41 V	273	89.1	-1.5
4	*2402.00	57.5 AV			3.41 V	273	59.0	-1.5
5	4804.00	37.6 PK	74.0	-36.4	1.72 V	186	34.6	3.0
6	4804.00	7.5 AV	54.0	-46.5	1.72 V	186	4.5	3.0

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 \* 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to:  $20\log(3.125 / 100) = -30.1 \text{ dB}$
7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)

<b>CHANNEL</b>		TX Channel 39		<b>DETECTOR FUNCTION</b>		Peak (PK)			
<b>FREQUENCY RANGE</b>		1GHz ~ 25GHz				Average (AV)			
<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2441.00	101.4 PK			1.02 H	283	102.9	-1.5	
2	*2441.00	71.3 AV			1.02 H	283	72.8	-1.5	
3	4882.00	37.8 PK	74.0	-36.2	1.75 H	188	34.6	3.2	
4	4882.00	7.7 AV	54.0	-46.3	1.75 H	188	4.5	3.2	
5	7323.00	43.4 PK	74.0	-30.6	2.03 H	161	34.5	8.9	
6	7323.00	13.3 AV	54.0	-40.7	2.03 H	161	4.4	8.9	
<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2441.00	87.8 PK			3.49 V	267	89.3	-1.5	
2	*2441.00	57.7 AV			3.49 V	267	59.2	-1.5	
3	4882.00	37.5 PK	74.0	-36.5	1.71 V	205	34.3	3.2	
4	4882.00	7.4 AV	54.0	-46.6	1.71 V	205	4.2	3.2	
5	7323.00	42.9 PK	74.0	-31.1	2.07 V	308	34.0	8.9	
6	7323.00	12.8 AV	54.0	-41.2	2.07 V	308	3.9	8.9	
<b>REMARKS:</b>									
<ol style="list-style-type: none"> <li>1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)</li> <li>2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)</li> <li>3. The other emission levels were very low against the limit.</li> <li>4. Margin value = Emission Level – Limit value</li> <li>5. " * ": Fundamental frequency.</li> <li>6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: <math>20\log(3.125 / 100) = -30.1</math> dB</li> <li>7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)</li> </ol>									

<b>CHANNEL</b>		TX Channel 78		<b>DETECTOR FUNCTION</b>		Peak (PK)			
<b>FREQUENCY RANGE</b>		1GHz ~ 25GHz				Average (AV)			
<b>ANTENNA POLARITY &amp; TEST DISTANCE: HORIZONTAL AT 3 M</b>									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2480.00	101.5 PK			1.01 H	277	102.9	-1.4	
2	*2480.00	71.4 AV			1.01 H	277	72.8	-1.4	
3	2483.50	54.6 PK	74.0	-19.4	1.01 H	277	56.0	-1.4	
4	2483.50	24.5 AV	54.0	-29.5	1.01 H	277	25.9	-1.4	
5	4960.00	38.2 PK	74.0	-35.8	1.79 H	207	35.0	3.2	
6	4960.00	8.1 AV	54.0	-45.9	1.79 H	207	4.9	3.2	
7	7440.00	43.4 PK	74.0	-30.6	2.03 H	159	34.2	9.2	
8	7440.00	13.3 AV	54.0	-40.7	2.03 H	159	4.1	9.2	
<b>ANTENNA POLARITY &amp; TEST DISTANCE: VERTICAL AT 3 M</b>									
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)	
1	*2480.00	88.1 PK			3.44 V	264	89.5	-1.4	
2	*2480.00	58.0 AV			3.44 V	264	59.4	-1.4	
3	2483.50	54.3 PK	74.0	-19.7	3.44 V	264	55.7	-1.4	
4	2483.50	24.2 AV	54.0	-29.8	3.44 V	264	25.6	-1.4	
5	4960.00	37.9 PK	74.0	-36.1	1.69 V	186	34.7	3.2	
6	4960.00	7.8 AV	54.0	-46.2	1.69 V	186	4.6	3.2	
7	7440.00	43.2 PK	74.0	-30.8	2.08 V	309	34.0	9.2	
8	7440.00	13.1 AV	54.0	-40.9	2.08 V	309	3.9	9.2	
<b>REMARKS:</b>									
<ol style="list-style-type: none"> <li>1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)</li> <li>2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)</li> <li>3. The other emission levels were very low against the limit.</li> <li>4. Margin value = Emission Level – Limit value</li> <li>5. " * ": Fundamental frequency.</li> <li>6. The DH5 packet was the worse case duty cycle for a transmit dwell time on a channel, based upon bluetooth theory the transmitter is on 0.625 * 5 per 296.25 ms per channel. Therefore, the duty cycle correlation factor be equal to: <math>20\log(3.125 / 100) = -30.1</math> dB</li> <li>7. The average value of fundamental and harmonic frequency is: Average = Peak value + 20 log(Duty cycle)</li> </ol>									

## Below 1GHz Data:

## BT\_GFSK

CHANNEL	TX Channel 78	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	96.01	36.1 QP	43.5	-7.4	1.70 H	360	49.2	-13.1
2	<b>343.50</b>	<b>42.8 QP</b>	<b>46.0</b>	<b>-3.2</b>	<b>1.50 H</b>	<b>319</b>	<b>49.3</b>	<b>-6.5</b>
3	406.51	40.9 QP	46.0	-5.1	1.70 H	240	46.1	-5.2
4	509.98	32.2 QP	46.0	-13.8	1.70 H	196	35.0	-2.8
5	687.01	41.9 QP	46.0	-4.1	3.00 H	20	41.6	0.3
6	768.02	37.6 QP	46.0	-8.4	1.00 H	313	35.9	1.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	94.01	33.7 QP	43.5	-9.8	1.50 V	184	47.3	-13.6
2	303.41	42.3 QP	46.0	-3.7	2.00 V	88	49.7	-7.4
3	336.01	40.2 QP	46.0	-5.8	1.70 V	104	46.7	-6.5
4	398.98	41.6 QP	46.0	-4.4	3.00 V	360	46.9	-5.3
5	494.99	41.0 QP	46.0	-5.0	1.20 V	213	44.1	-3.1
6	745.32	42.4 QP	46.0	-3.6	1.30 V	326	40.9	1.5

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 4.2 Maximum Output Power

### 4.2.1 Limits of Maximum Output Power Measurement

The Maximum Output Power Measurement is 125mW.

### 4.2.2 Test Setup



### 4.2.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.2.4 Test Procedure

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. The center frequency of the spectrum analyzer is set to the fundamental frequency and using 3MHz RBW and 10 MHz VBW.
- d. Measure the captured power within the band and recording the plot.
- e. Repeat above procedures until all frequencies required were complete.

### 4.2.5 Deviation from Test Standard


No deviation.

### 4.2.6 EUT Operating Condition

The software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel frequencies individually.

#### 4.2.7 Test Results

Channel	Frequency (MHz)	Output Power (mW)		Output Power (dBm)		Power Limit (mW)	Pass / Fail
		GFSK	8DPSK	GFSK	8DPSK		
0	2402	3.097	2.291	4.91	3.60	125	Pass
39	2441	3.499	2.547	5.44	4.06	125	Pass
78	2480	3.819	2.805	5.82	4.48	125	Pass



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

### **Linko EMC/RF Lab**

Tel: 886-2-26052180  
Fax: 886-2-26051924

### **Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-6668565  
Fax: 886-3-6668323

### **Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232  
Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---