

Maximum Permissible Exposure(MPE) Estimation

1. Introduction

810-00012-00 is Beats wireless, which contain Bluetooth function inside.

2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v03r03, no SAR required if power is lower than the flowing threshold:

When routine evaluation is required for SAR and the output power is $\leq 60/f(\text{GHz})$ mW, the test reduction and test exclusion procedures given herein, or in KDB 616217 or KDB 648474, are applicable.

A device may be used in portable exposure conditions with no restrictions on host platforms when either the source-based time-averaged output power is $\leq 60/f(\text{GHz})$ mW or all measured 1-g SAR are $< 0.4 \text{ W/kg}$. When SAR evaluation is required, the most conservative exposure conditions for all expected operating configurations must be tested.

3. Calculation method

Max Peak output power: GFSK mode 2402 MHz: $4.48\text{dBm}=2.8054\text{mW}$

$60/\text{fGHz} = 60/2.402 = 24.98\text{mW}$

Max Peak output power $< 60/\text{fGHz}$

810-00012-00 is a portable device and the Max Peak output power is less than 24.98 mW, so SAR evaluation is not necessary.

The two models 810-00012-00 and 810-00012-01 are identical only except the enclosure color, 810-00012-00 is black color, 810-00012-01 is white color, so SAR evaluation for 810-00012-00 is also not necessary

Jiangsu TUV Product Service Ltd. Shenzhen Branch

Reviewed by:



Prepared By:



Paul Yu/Assistant EMC Project Manager
Date: 2012-03-23

Cookies Bu// EMC Project Engineer
Date: 2012-03-23