| | | | REVISIONS | | | |
|-------------------------------------|--|--|---|------------------------|-------------------------|-----------------------|
| | | LTR | DESCRIPTION | | | APPROVED |
| | | А | | R PROD., ECO 3 | | JCR 1-83 |
| | | В | CHG TEXT AND S | IZE OF LABEL, E | ECO 5179 G.T. | |
| .62 —— | "This device complies Operation is subject t (1) This device may no (2) This device must of including interferent operations." | o the following ot cause harmfo accept any inter | two conditions ul interference rference receive | : | | |
| | | | | 2.25 - | | |
| 3. ALL LETTERING | AND BORDER IS BLACK. | | | | | |
| _ · | D BE TYPE SET FOR BEST BY LABEL MANUFACTURER. | FRA | TRANCE: CT ± 1/32 ± .030, .xxx ± .010, | Moseley | 111 CASTIL GOLETA, C | IAN DR. ALIF 93117 |
| 1. MAT'L: .003 AL SENSITIVE ADHE | UMINUM WITH PRESSURE SIVE BACKING. | | ± 1/2° ROVALS DATE JCR 12-30-82 | LABEL, | FCC (Te | sted) |
| NOTES: UNLESS OTHER | WISE SPECIFIED DO NO | CHK T SCALE DWG ENG | JCR 12-30-82 DLB 1-4-83 | SHEET 1 OF SCALE 2X | 10A10 | 78 B |