

# RADIO TEST REPORT – 409404-1TRFWL

Type of assessment:

**Final product testing**

Applicant:

**Zimmer CAS**

Model:

**Pod V2 Reference**

FCC ID:

**CVO50001**

Specifications:

- ◆ FCC 47 CFR Part 15 Subpart C, §15.247
- ◆ RSS-247, Issue 2, Feb 2017, Section 5

Date of issue: January 31, 2021

---

**Yong Huang, EMC/RF Specialist**

Tested by



Signature

---

**David Duchesne, EMC/RF Lab Manager**

Reviewed by



Signature

Nemko Canada Inc., a testing laboratory, is accredited by the Standards Council of Canada.  
The tests included in this report are within the scope of this accreditation

---

**Lab locations**

---

<b>Company name</b>	Nemko Canada Inc.			
<b>Facilities</b>	<i>Ottawa site:</i> 303 River Road Ottawa, Ontario Canada K1V 1H2	<i>Montréal site:</i> 292 Labrosse Avenue Pointe-Claire, Québec Canada H9R 5L8	<i>Cambridge site:</i> 1-130 Saltsman Drive Cambridge, Ontario Canada N3E 0B2	<i>Almonte site:</i> 1500 Peter Robinson Road West Carleton, Ontario Canada K0A 1L0
	Tel: +1 613 737 9680 Fax: +1 613 737 9691	Tel: +1 514 694 2684 Fax: +1 514 694 3528	Tel: +1 519 650 4811	Tel: +1 613 256-9117 Fax: +1 613 256-8848
<b>Test site registration</b>	<b>Organization</b>	<b>Recognition numbers and location</b>		
	FCC/ISED	FCC: CA2040; IC: 2040A-4 (Ottawa/Almonte); FCC: CA2041; IC: 2040G-5 (Montreal); CA0101 (Cambridge)		
<b>Website</b>	<a href="http://www.nemko.com">www.nemko.com</a>			

---

**Limits of responsibility**

---

Note that the results contained in this report relate only to the items tested and were obtained in the period between the date of initial receipt of samples and the date of issue of the report.

This test report has been completed in accordance with the requirements of ISO/IEC 17025. All results contained in this report are within Nemko Canada's ISO/IEC 17025 accreditation.

---

**Copyright notification**

---

Nemko Canada Inc. authorizes the applicant to reproduce this report provided it is reproduced in its entirety and for use by the company's employees only. Any use which a third party makes of this report, or any reliance on or decisions to be made based on it, are the responsibility of such third parties.

Nemko Canada Inc. accepts no responsibility for damages, if any, suffered by any third party as a result of decisions made or actions based on this report.

© Nemko Canada Inc.

## Table of Contents

<b>Table of Contents .....</b>	<b>3</b>
<b>Section 1      Report summary .....</b>	<b>4</b>
1.1    Test specifications .....	4
1.2    Test methods .....	4
1.3    Exclusions .....	4
1.4    Statement of compliance .....	4
1.5    Test report revision history .....	4
<b>Section 2      Engineering considerations .....</b>	<b>5</b>
2.1    Modifications incorporated in the EUT for compliance .....	5
2.2    Technical judgment .....	5
2.3    Deviations from laboratory tests procedures .....	5
<b>Section 3      Test conditions .....</b>	<b>6</b>
3.1    Atmospheric conditions .....	6
3.2    Power supply range .....	6
<b>Section 4      Measurement uncertainty .....</b>	<b>7</b>
4.1    Uncertainty of measurement .....	7
<b>Section 5      Information provided by the applicant .....</b>	<b>8</b>
5.1    Disclaimer .....	8
5.2    Applicant/Manufacture .....	8
5.3    EUT information .....	8
5.4    Technical information .....	9
5.5    EUT setup details .....	9
<b>Section 6      Summary of test results .....</b>	<b>11</b>
6.1    Testing location .....	11
6.2    Testing period .....	11
6.3    Sample information .....	11
6.4    FCC Part 15 Subpart C, general requirements test results .....	11
6.5    FCC Part 15 Subpart C, intentional radiators test results for digital transmission systems (DTS) .....	11
6.6    ISED RSS-Gen, Issue 5, test results .....	12
6.7    ISED RSS-247, Issue 2, test results for digital transmission systems (DTS) .....	12
<b>Section 7      Test equipment .....</b>	<b>13</b>
7.1    Test equipment list .....	13
<b>Section 8      Testing data .....</b>	<b>14</b>
8.1    FCC 15.31(e) Variation of power source .....	14
8.2    FCC 15.31(m) and RSS-Gen 6.9 Number of frequencies .....	15
8.3    FCC 15.203 and RSS-Gen, section 6.8 Antenna requirement .....	16
8.4    FCC 15.247(a)(2) and RSS-247 5.2(a) Minimum 6 dB bandwidth for DTS systems .....	17
8.5    FCC 15.247(b) and RSS-247 5.4(d) Transmitter output power and e.i.r.p. requirements for DTS in 2.4 GHz .....	20
8.6    FCC 15.247(d) and RSS-247 5.5 Spurious (out-of-band) unwanted emissions .....	23
8.7    FCC 15.247(e) and RSS-247 5.2(b) Power spectral density for digitally modulated devices .....	30
<b>Section 9      EUT photos .....</b>	<b>32</b>
9.1    External photos .....	32

## Section 1 Report summary

---

### 1.1 Test specifications

---

FCC 47 CFR Part 15, Subpart C, Clause 15.247 RSS-247, Issue 2, Feb 2017, Section 5	Operation in the 902–928 MHz, 2400–2483.5 MHz, and 5725–585 MHz Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
---	---

### 1.2 Test methods

---

558074 D01 15.247 Meas Guidance v05r02 (April 2, 2019)	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules.
ANSI C63.10 v2013	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
RSS-102, Issue 5, March 19, 2015	Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands)

### 1.3 Exclusions

---

None

### 1.4 Statement of compliance

---

In the configuration tested, the EUT was found compliant.

Testing was performed against all relevant requirements of the test standard except as noted in section 1.3 above. Results obtained indicate that the product under test complies in full with the requirements tested. The test results relate only to the items tested.

See "Summary of test results" for full details.

### 1.5 Test report revision history

---

**Table 1.5-1: Test report revision history**

Revision #	Date of issue	Details of changes made to test report
TRF	January 31, 2021	Original report issued

## Section 2 Engineering considerations

---

### 2.1 Modifications incorporated in the EUT for compliance

---

There were no modifications performed to the EUT during this assessment.

### 2.2 Technical judgment

---

- EUT has 2 model variants, between each the difference is user interface, including: LEDs and graphic overlay
- Both variants have been fully tested, worst-case scenario data was presented in this report.

### 2.3 Deviations from laboratory tests procedures

---

No deviations were made from laboratory procedures.

## Section 3 Test conditions

---

### 3.1 Atmospheric conditions

---

Temperature	15 °C – 35 °C
Relative humidity	20 % – 75 %
Air pressure	86 kPa (860 mbar) – 106 kPa (1060 mbar)

When it is impracticable to carry out tests under these conditions, a note to this effect stating the ambient temperature and relative humidity during the tests shall be recorded and stated.

### 3.2 Power supply range

---

The normal test voltage for equipment to be connected to the mains shall be the nominal mains voltage. For the purpose of the present document, the nominal voltage shall be the declared voltage, or any of the declared voltages  $\pm 5\%$ , for which the equipment was designed.

## Section 4 Measurement uncertainty

---

### 4.1 Uncertainty of measurement

---

UKAS Lab 34 and TIA-603-B have been used as guidance for measurement uncertainty reasonable estimations with regards to previous experience and validation of data. Nemko Canada, Inc. follows these test methods in order to satisfy ISO/IEC 17025 requirements for estimation of uncertainty of measurement for wireless products.

Measurement uncertainty budgets for the tests are detailed below. Measurement uncertainty calculations assume a coverage factor of  $K = 2$  with 95% certainty.

**Table 4.1-1: Measurement uncertainty calculations for Radio**

Test name	Measurement uncertainty, $\pm$ dB
All antenna port measurements	0.55
Occupied bandwidth	4.45
Conducted spurious emissions	1.13
Radiated spurious emissions	3.78

## Section 5 Information provided by the applicant

---

### 5.1 Disclaimer

---

This section contains information provided by the applicant and has been utilized to support the test plan. Inaccurate information provided by the applicant can affect the validity of the results contained within this test report. Nemko accepts no responsibility for the information contained within this section and the impact it may have on the test plan and resulting measurements.

### 5.2 Applicant/Manufacture

---

Company name	Zimmer CAS
Address	75 Queen St, suite 3300, Montreal QC, Canada, H3C 2N6

### 5.3 EUT information

---

Product name	iASSIST Knee V2 Pod kit
Model	Pod V2 Reference
Model variant	Pod V2 Cut Guide
Serial number	Pod V2 Reference S/N: E0957900000B0083 for conducted measurements and S/N: E0957900000B0085 for radiated measurements Pod V2 Cut Guide S/N: E0957900000B0084 for conducted measurements and S/N: E0957900000B0086 for radiated measurements
Part number	20-8011-500-01(Pod V2 Reference) 20-8011-500-02 (Pod V2 Cut Guide)
Operating conditions	Both EUT variants are operated with primary battery 1.5V alkaline type. Both EUT variants are using firmware version 2.0.0.83. EUT is connected to computer via USB debug port to send test commands such as continuous transmit on a specific channel. EUT is also connected via wireless network to iAssist V2 Tablet to monitor wireless link.
Product description and theory of operation	Both EUT variants are part of the iASSIST Knee V2 Pod kit which is used in the iASSIST™ Knee System. This system is a computer assisted stereotaxic surgical instrument system to assist the surgeon in preparing the bone surfaces for positioning orthopedic implant system components intra-operatively. It involves surgical instruments and the wireless Pod V2 inertial sensors to determine alignment axes in relation to anatomical landmarks and to precisely position alignment instruments and cut guides relative to these axes.

## 5.4 Technical information

---

Applicant IC company number	10254A
IC UPN number	50001
All used IC test site(s) Reg. number	2040G-5
RSS number and Issue number	RSS-247 Issue 2, Feb 2017
Category of Wideband Data Transmission equipment	Other types of Wideband Data Transmission equipment (e.g. DSSS, OFDM, etc.)
Frequency band	2400–2483.5 MHz
Frequency Min (MHz)	2405
Frequency Max (MHz)	2480
Channel numbers	11–26
RF power Max (W), Conducted	0.001 W and (0.1 dBm)
Field strength, dB $\mu$ V/m @ 3 m	N/A
Measured BW (kHz), 99% OBW	2564
Type of modulation	OQPSK
Emission classification	F1D
Transmitter spurious, dB $\mu$ V/m @ 3 m	45.3, Average, @2483.5 MHz
Power supply requirements	Battery: 1.5 V <sub>DC</sub>
Antenna information	Integrated chip antenna with Max peak of 0.5 dBi

## 5.5 EUT setup details

---

### 5.5.1 EUT Exercise mode

---

#### Methods used to exercise the EUT

The device was configured in forced transmit mode using special port commands. Tx continuously at 100% duty cycle

## 5.5 EUT setup details, continued


### 5.5.2 EUT test configuration

**Table 5.5-1: EUT sub assemblies**


Description	Brand name	Model, Part number, Serial number, Revision level
Pod V2 Reference	iASSIST Knee V2 Pod kit	MN: Pod V2 Reference, PN: 20-8011-500-01, SN: E0957900000B0083, Rev: A5
Pod V2 Reference	iASSIST Knee V2 Pod kit	MN: Pod V2 Reference, PN: 20-8011-500-01, SN: E0957900000B0085, Rev: A5
Pod V2 Cut Guide	iASSIST Knee V2 Pod kit	MN: Pod V2 Cut Guide, PN: 20-8011-500-02, SN: E0957900000B0084, Rev: A5
Pod V2 Cut Guide	iASSIST Knee V2 Pod kit	MN: Pod V2 Cut Guide, PN: 20-8011-500-02, SN: E0957900000B0086, Rev: A5

**Table 5.5-2: Support equipment**

Description	Brand name	Model, Part number, Serial number, Revision level
Laptop	Dell	MN: P02T, SN: 00186-071-540-861
AC Adapter for laptop	Dell	PA-1650-05D2, SN: CN-0F7970-71615-57I-2617



**Figure 5.5-1: Radiated testing block diagram**



**Figure 5.5-2: Antenna port testing block diagram**

## Section 6 Summary of test results

---

### 6.1 Testing location

---

Test location (s)	Montreal
-------------------	----------

### 6.2 Testing period

---

Test start date	December 1, 2020	Test end date	January 6, 2021
-----------------	------------------	---------------	-----------------

### 6.3 Sample information

---

Receipt date	December 1, 2020	Nemko sample ID number(s)	1,2,3,4
--------------	------------------	---------------------------	---------

### 6.4 FCC Part 15 Subpart C, general requirements test results

---

**Table 6.4-1: FCC general requirements results**

Part	Test description	Verdict
§15.31	Variation of power source	Pass
§15.31(m)	Number of tested frequencies	Pass
§15.203	Antenna requirement	Pass

### 6.5 FCC Part 15 Subpart C, intentional radiators test results for digital transmission systems (DTS)

---

**Table 6.5-1: FCC 15.247 results for DTS**

Part	Test description	Verdict
§15.247(a)(2)	Minimum 6 dB bandwidth	Pass
§15.247(b)(3)	Maximum peak output power in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands	Pass
§15.247(1)	Fixed point-to-point operation with directional antenna gains greater than 6 dBi	Pass
§15.247(d)	Spurious emissions	Pass
§15.247I	Power spectral density	Pass

Notes: Only test applicable to the EUT have been included in this table.

## 6.6 ISED RSS-Gen, Issue 5, test results

---

**Table 6.6-1: RSS-Gen results**

Part	Test description	Verdict
6.9	Operating bands and selection of test frequencies	Pass

## 6.7 ISED RSS-247, Issue 2, test results for digital transmission systems (DTS)

---

**Table 6.7-1: RSS-247 results for DTS**

Part	Test description	Verdict
5.2 (a)	Minimum 6 dB bandwidth	Pass
5.2 (b)	Maximum power spectral density	Pass
5.4	Transmitter output power and e.i.r.p. requirements	
5.4 (d)	Systems employing digital modulation techniques	Pass
5.5	Unwanted emissions	Pass

Notes: Only test applicable to the EUT have been included in this table.

## Section 7 Test equipment

---

### 7.1 Test equipment list

---

**Table 7.1-1: Equipment list**

Equipment	Manufacturer	Model no.	Asset no.	Cal cycle	Next cal.
3 m EMI test chamber (Emissions)	TDK	SAC-3	FA002532e	2 year	February 25, 2022
Flush mount turntable	Sunol	FM2022	FA002550	—	NCR
Controller	Sunol	SC104V	FA002551	—	NCR
Antenna mast	Sunol	TLT2	FA002552	—	NCR
Receiver/spectrum analyzer	Rohde & Schwarz	ESU 40	FA002071	1 year	June 1, 2021
Bilog antenna (20–2000 MHz)	Sunol	JB1	FA002517	1 year	January 28, 2021
Horn antenna (1–18 GHz)	EMCO	3115	FA001452	1 year	June 16, 2021
Horn antenna (18–40 GHz)	EMCO	3116	FA002487	2 year	March 11, 2021
Pre-amplifier (0.5–18 GHz)	Com-Power	PAM-118A	FA002561	1 year	September 22, 2021
Pre-amplifier (18–40 GHz)	Com-Power	PAM-840	FA002508	1 year	September 24, 2021
2.4 GHz band Notch Filter	Microwave Circuits	N0324413	FA002693	—	VOU
Spectrum analyzer	Rohde & Schwarz	FSV 40	FA002731	1 year	March 23, 2021

Notes: NCR - no calibration required, VOU - verify on use

## Section 8 Testing data

---

### 8.1 FCC 15.31(e) Variation of power source

---

#### 8.1.1 References, definitions and limits

---

For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

#### 8.1.2 Observations, settings and special notes

---

The testing was performed as per ANSI C63.10 Section 5.13.

- a) Where the device is intended to be powered from an external power adapter, the voltage variations shall be applied to the input of the adapter provided with the device at the time of sale. If the device is not marketed or sold with a specific adapter, then a typical power adapter shall be used.
- b) For devices, where operating at a supply voltage deviating  $\pm 15\%$  from the nominal rated value may cause damages or loss of intended function, test to minimum and maximum allowable voltage per manufacturer's specification and document in the report.
- c) For devices with wide range of rated supply voltage, test at 15% below the lowest and 15% above the highest declared nominal rated supply voltage.
- d) For devices obtaining power from an input/output (I/O) port (USB, firewire, etc.), a test jig is necessary to apply voltage variation to the device from a support power supply, while maintaining the functionalities of the device.

For battery-operated equipment, the equipment tests shall be performed using a variable power supply.

#### 8.1.3 Summary

---

The EUT is battery powered. Testing performed using fresh batteries

## 8.2 FCC 15.31(m) and RSS-Gen 6.9 Number of frequencies

### 8.2.1 References, definitions and limits

**FCC:**

Measurements on intentional radiators or receivers shall be performed and, if required, reported for each band in which the device can be operated with the device operating at the number of frequencies in each band specified in the following table.

**ISED:**

Except where otherwise specified, measurements shall be performed for each frequency band of operation for which the radio apparatus is to be certified, with the device operating at the frequencies in each band of operation shown in table below. The frequencies selected for measurements shall be reported in the test report.

*Table 8.2-1: Frequency Range of Operation*

Frequency range over which the device operates (in each band)	Number of test frequencies required	Location of measurement frequency inside the operating frequency range
1 MHz or less	1	Center (middle of the band)
1–10 MHz	2	1 near high end, 1 near low end
Greater than 10 MHz	3	1 near high end, 1 near center and 1 near low end

Note: "near" means as close as possible to or at the centre / low end / high end of the frequency range over which the device operates.

### 8.2.2 Observations, settings and special notes

Per ANSI C63.10 Subclause 5.6.2.1:

The number of channels tested can be reduced by measuring the center channel bandwidth first and then applying the following relaxations as appropriate:

- a) For each operating mode, if the measured channel bandwidth on the middle channel is at least 150% of the minimum permitted bandwidth, then it is not necessary to measure the bandwidth on the high and low channels.
- b) For multiple-input multiple-output (MIMO) systems, if the measured channel bandwidth on testing the middle channel exceeds the minimum permitted bandwidth by more than 50% on one transmit chain, then it is not necessary to repeat testing on the other chains.
- c) If the measured channel bandwidth on the middle channel is less than 50% of the maximum permitted bandwidth, then it is not necessary to measure the bandwidth on the high and low channels.

Per ANSI C63.10 Subclause 5.6.2.2:

For devices with multiple operating modes, measurements on the middle channel can be used to determine the worst-case mode(s). The worst-case modes are as follows:

- a) Band edge requirements—Measurements on the mode with the widest bandwidth can be used to cover the same channel (center frequency) on modes with narrower bandwidth that have the same or lower output power for each modulation family (e.g., OFDM and direct sequence spread spectrum).
- b) Spurious emissions—Measure the mode with the highest output power and the mode with the highest output power spectral density for each modulation family (e.g., OFDM and direct sequence spread spectrum).
- c) In-band PSD—Measurements on the mode with the narrowest bandwidth can be used to cover all modes within the same modulation family of an equal or lower output power provided the result is less than 50% of the limit.

### 8.2.3 Summary

*Table 8.2-2: Test channels selection*

Start of Frequency range, MHz	End of Frequency range, MHz	Frequency range bandwidth, MHz	Low channel, MHz	Mid channel, MHz	High channel, MHz
2400	2483.5	83.5	2405	2440	2480

## 8.3 FCC 15.203 and RSS-Gen, section 6.8 Antenna requirement

---

### 8.3.1 References, definitions and limits

---

#### FCC:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

#### FCC 15.247(b)(4)

The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

#### ISED:

The applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report.

### 8.3.2 Observations, settings and special notes

---

None

### 8.3.1 Summary

---

**Table 8.3-1: Antenna information**

Antenna type	Manufacturer	Model number	Maximum gain	Connector type
Integrated chip antenna	Johanson Technology Inc	2450AT18A100E	0.5 dBi	N/A

Notes: EUT is not professionally installed and does not have a detachable antenna.

## 8.4 FCC 15.247(a)(2) and RSS-247 5.2(a) Minimum 6 dB bandwidth for DTS systems

---

### 8.4.1 References, definitions and limits

---

**FCC:**

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

**ISED:**

The minimum 6 dB bandwidth shall be 500 kHz.

**RSS-GEN, Section 6.7:**

6 dB bandwidth is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated 6 dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

### 8.4.2 Test summary

---

Verdict	Pass
Tested by	Yong Huang

Test date

January 4, 2021

### 8.4.3 Observations, settings and special notes

---

The test was performed as per KDB 558074, section 8.2 with reference to ANSI C63.10 subclause 11.8.


Spectrum analyser settings:

Resolution bandwidth	6 dB BW: 100 kHz; 99% OBW: 1–5% of OBW
Video bandwidth	$\geq 3 \times$ RBW
Frequency span	5 MHz
Detector mode	Peak
Trace mode	Max Hold


#### 8.4.4 Test data

**Table 8.4-1: 6 dB bandwidth results**


Frequency, MHz	6 dB bandwidth, MHz	Minimum limit, MHz	Margin, MHz
2405	1.598	0.500	1.098
2440	1.603	0.500	1.103
2480	1.601	0.500	1.101



**Figure 8.4-1: 6 dB bandwidth, Tx on low channel**



**Figure 8.4-2: 6 dB bandwidth, Tx on mid channel**






**Figure 8.4-3: 6 dB bandwidth, Tx on high channel**

Test data, continued

**Table 8.4-2: 99% occupied bandwidth results**

Frequency, MHz	99% occupied bandwidth, kHz
2405	2564
2440	2562
2480	2561

Note: there is no 99% occupied bandwidth limit in the standard's requirements, the measurement results provided for information purposes only.


**Figure 8.4-4: 99% occupied bandwidth, Tx on low channel**

**Figure 8.4-5: 99% occupied bandwidth, Tx on mid channel**

**Figure 8.4-6: 99% occupied bandwidth, Tx on high channel**

## 8.5 FCC 15.247(b) and RSS-247 5.4(d) Transmitter output power and e.i.r.p. requirements for DTS in 2.4 GHz

---

### 8.5.1 References, definitions and limits

---

#### FCC:

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

- (3) For systems using digital modulation in the 2400–2483.5 MHz band: 1 W (30 dBm). As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
- (4) The conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

(c) Operation with directional antenna gains greater than 6 dBi.

(1) Fixed point-to-point operation:

- (i) Systems operating in the 2400–2483.5 MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6 dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.
- (ii) Fixed, point-to-point operation, as used in paragraphs (c)(1)(i) and (c)(1)(ii) of this section, excludes the use of point-to-multipoint systems, omnidirectional applications, and multiple co-located intentional radiators transmitting the same information. The operator of the spread spectrum or digitally modulated intentional radiator or, if the equipment is professionally installed, the installer is responsible for ensuring that the system is used exclusively for fixed, point-to-point operations. The instruction manual furnished with the intentional radiator shall contain language in the installation instructions informing the operator and the installer of this responsibility.

(2) In addition to the provisions in paragraphs (b)(1), (b)(3), (b)(4) and (c)(1)(i) of this section, transmitters operating in the 2400–2483.5 MHz band that emit multiple directional beams, simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers provided the emissions comply with the following:

- (i) Different information must be transmitted to each receiver.
- (ii) If the transmitter employs an antenna system that emits multiple directional beams but does not do emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device, i.e., the sum of the power supplied to all antennas, antenna elements, staves, etc. and summed across all carriers or frequency channels, shall not exceed the limit specified in paragraph (b)(1) or (b)(3) of this section, as applicable. However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as follows:
  - (A) The directional gain shall be calculated as the sum of  $10 \log$  (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.
  - (B) A lower value for the directional gain than that calculated in paragraph (c)(2)(ii)(A) of this section will be accepted if sufficient evidence is presented, e.g., due to shading of the array or coherence loss in the beamforming.
- (iii) If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the power limit specified in paragraph (c)(2)(ii) of this section. If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the limit specified in paragraph (c)(2)(ii) of this section. In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the limit specified in paragraph (c)(2)(ii) of this section by more than 8 dB.
- (iv) Transmitters that emit a single directional beam shall operate under the provisions of paragraph (c)(1) of this section.

## References, definitions and limits, continued

### ISED:

d. For DTSs employing digital modulation techniques operating in the 2400–2483.5 MHz band, the maximum peak conducted output power shall not exceed 1 W. The e.i.r.p. shall not exceed 4 W, except as provided in section 5.4(e).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power. The maximum conducted output power is the total transmit power delivered to all antennas and antenna elements, averaged across all symbols in the signalling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or transmitting at a reduced power level. If multiple modes of operation are implemented, the maximum conducted output power is the highest total transmit power occurring in any mode.

e. Fixed point-to-point systems in the 2400–2483.5 MHz band are permitted to have an e.i.r.p. higher than 4 W provided that the higher e.i.r.p. is achieved by employing higher gain directional antennas and not higher transmitter output powers. Point-to-multipoint systems, omnidirectional applications and multiple co-located transmitters transmitting the same information are prohibited from exceeding an e.i.r.p. of 4 W.

f. Transmitters operating in the band 2400–2483.5 MHz, may employ antenna systems that emit multiple directional beams simultaneously or sequentially, for the purpose of directing signals to individual receivers or to groups of receivers, provided that the emissions comply with the following:

i Different information must be transmitted to each receiver.

ii If the transmitter employs an antenna system that emits multiple directional beams, but does not emit multiple directional beams simultaneously, the total output power conducted to the array or arrays that comprise the device (i.e. the sum of the power supplied to all antennas, antenna elements, staves, etc., and summed across all carriers or frequency channels) shall not exceed the applicable output power limit specified in sections 5.4(b) and 5.4(d). However, the total conducted output power shall be reduced by 1 dB below the specified limits for each 3 dB that the directional gain of the antenna/antenna array exceeds 6 dBi. The directional antenna gain shall be computed as the sum of  $10 \log$  (number of array elements or staves) plus the directional gain of the element or stave having the highest gain.

iii If a transmitter employs an antenna that operates simultaneously on multiple directional beams using the same or different frequency channels, the power supplied to each emission beam is subject to the applicable power limit specified in sections 5.4(b) and 5.4(d). If transmitted beams overlap, the power shall be reduced to ensure that their aggregate power does not exceed the applicable limit specified in sections 5.4(b) and 5.4(d). In addition, the aggregate power transmitted simultaneously on all beams shall not exceed the applicable limit specified in sections 5.4(b) and 5.4(d) by more than 8 dB.

iv Transmitters that transmit a single directional beam shall operate under the provisions of sections 5.4(b), 5.4(d) and 5.4(e).

### 8.5.2 Test summary

Verdict	Pass		
Tested by	Yong Huang	Test date	January 4, 2021

### 8.5.3 Observations, settings and special notes

- The test was performed as per KDB 558074, section 8.3 with reference to ANSI C63.10 subclause 11.9.1 (peak power) using method  $RBW \geq DTS$  bandwidth (Maximum peak conducted output power)
- Conducted measurement was performed at the coupling test port of EUT, path loss was included in the offset of reference level.


#### Spectrum analyser settings:

Resolution bandwidth	3 MHz
Video bandwidth	$\geq 3 \times RBW$
Frequency span	10 MHz
Detector mode	Peak
Trace mode	Max Hold

#### 8.5.4 Test data


**Table 8.5-1: Output power measurements results**

Frequency, MHz	Conducted output power, dBm		Margin, dB	Antenna gain, dBi	EIRP, dBm	EIRP limit, dBm	EIRP margin, dB
	Measured	Limit					
2405	0.1	30.0	29.9	0.5	0.6	36.0	35.4
2440	0.0	30.0	30.0	0.5	0.5	36.0	35.5
2480	-0.6	30.0	30.6	0.5	-0.1	36.0	36.1




Date: 4.JAN.2021 13:43:21

**Figure 8.5-1: Output power on low channel**



Date: 4.JAN.2021 14:37:04

**Figure 8.5-2: Output power on mid channel**



Date: 4.JAN.2021 14:38:18

**Figure 8.5-3: Output power on high channel**

## 8.6 FCC 15.247(d) and RSS-247 5.5 Spurious (out-of-band) unwanted emissions

### 8.6.1 References, definitions and limits

#### FCC:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

#### ISED:

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 5.4(d), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

**Table 8.6-1: FCC §15.209 and RSS-Gen – Radiated emission limits**

Frequency, MHz	Field strength of emissions		Measurement distance, m
	µV/m	dBµV/m	
0.009–0.490	2400/F	67.6 – 20 × log <sub>10</sub> (F)	300
0.490–1.705	24000/F	87.6 – 20 × log <sub>10</sub> (F)	30
1.705–30.0	30	29.5	30
30–88	100	40.0	3
88–216	150	43.5	3
216–960	200	46.0	3
above 960	500	54.0	3

Notes: In the emission table above, the tighter limit applies at the band edges.

For frequencies above 1 GHz the limit on peak RF emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test



**Section 8**  
**Test name**  
**Specification**

*Testing data*  
*FCC 15.247(d) and RSS-247 5.5 Spurious (out-of-band) unwanted emissions*  
*FCC Part 15 Subpart C and RSS-247, Issue 2*

## References, definitions and limits, continued

**Table 8.6-2: ISED restricted frequency bands**

MHz	MHz	MHz	GHz
0.090–0.110	12.57675–12.57725	399.9–410	7.25–7.75
0.495–0.505	13.36–13.41	608–614	8.025–8.5
2.1735–2.1905	16.42–16.423	960–1427	9.0–9.2
3.020–3.026	16.69475–16.69525	1435–1626.5	9.3–9.5
4.125–4.128	16.80425–16.80475	1645.5–1646.5	10.6–12.7
4.17725–4.17775	25.5–25.67	1660–1710	13.25–13.4
4.20725–4.20775	37.5–38.25	1718.8–1722.2	14.47–14.5
5.677–5.683	73–74.6	2200–2300	15.35–16.2
6.215–6.218	74.8–75.2	2310–2390	17.7–21.4
6.26775–6.26825	108–138	2483.5–2500	22.01–23.12
6.31175–6.31225	149.9–150.05	2655–2900	23.6–24.0
8.291–8.294	156.52475–156.52525	3260–3267	31.2–31.8
8.362–8.366	156.7–156.9	3332–3339	36.43–36.5
8.37625–8.38675	162.0125–167.17	3345.8–3358	
8.41425–8.41475	167.72–173.2	3500–4400	
12.29–12.293	240–285	4500–5150	Above 38.6
12.51975–12.52025	322–335.4	5350–5460	

Note: Certain frequency bands listed in Table 8.6-2 and above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

**Table 8.6-3: FCC restricted frequency bands**

MHz	MHz	MHz	GHz
0.090–0.110	16.42–16.423	399.9–410	4.5–5.15
0.495–0.505	16.69475–16.69525	608–614	5.35–5.46
2.1735–2.1905	16.80425–16.80475	960–1240	7.25–7.75
4.125–4.128	25.5–25.67	1300–1427	8.025–8.5
4.17725–4.17775	37.5–38.25	1435–1626.5	9.0–9.2
4.20725–4.20775	73–74.6	1645.5–1646.5	9.3–9.5
6.215–6.218	74.8–75.2	1660–1710	10.6–12.7
6.26775–6.26825	108–121.94	1718.8–1722.2	13.25–13.4
6.31175–6.31225	123–138	2200–2300	14.47–14.5
8.291–8.294	149.9–150.05	2310–2390	15.35–16.2
8.362–8.366	156.52475–156.52525	2483.5–2500	17.7–21.4
8.37625–8.38675	156.7–156.9	2690–2900	22.01–23.12
8.41425–8.41475	162.0125–167.17	3260–3267	23.6–24.0
12.29–12.293	167.72–173.2	3332–3339	31.2–31.8
12.51975–12.52025	240–285	3345.8–3358	36.43–36.5
12.57675–12.57725	322–335.4	3600–4400	Above 38.6
13.36–13.41			

## 8.6.2 Test summary

Verdict	Pass		
Tested by	Yong Huang	Test date	January 4, 2021

### 8.6.3 Observations, settings and special notes

- As part of the current assessment, the test range of 9 kHz to 10<sup>th</sup> harmonic has been fully considered and compared to the actual frequencies utilized within the EUT. Since the EUT contains a transmitter in the GHz range, the EUT has been deemed compliant without formal testing in the 9 kHz to 30 MHz test range, therefore formal test results (tabular data and/or plots) are not provided within this test report.
- EUT was set to transmit with 100 % duty cycle.
- Radiated measurements were performed at a distance of 3 m below 18 GHz and 1 m above 18 GHz. The level of spurious emissions were measured as their effective radiated power when radiated by cabinet and antenna in case of integral antenna equipment with no antenna connectors.
- DTS emissions in non-restricted frequency bands test was performed as per KDB 558074, section 8.5 with reference to ANSI C63.10 subclause 11.11.
- Since fundamental power was tested using the maximum peak conducted output power procedure to demonstrate compliance, the spurious emissions limit is -20 dBc/100 kHz.
- DTS emissions in restricted frequency bands test was performed as per KDB 558074, section 8.6 with reference to ANSI C63.10 subclause 11.12.
- DTS band-edge emission measurements test was performed as per KDB 558074, section 8.7 with reference to ANSI C63.10 subclause 11.13.
- The radiated measurements of both model variants have been tested, only the representative worst-case are recorded in this report

Spectrum analyser settings for radiated measurements within restricted bands below 1 GHz:

Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for peak radiated measurements within restricted bands above 1 GHz:

Resolution bandwidth:	1 MHz
Video bandwidth:	3 MHz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for average radiated measurements within restricted bands above 1 GHz:

Resolution bandwidth:	1 MHz
Video bandwidth:	10 Hz
Detector mode:	Peak
Trace mode:	Max Hold

Spectrum analyser settings for conducted spurious emissions measurements:


Resolution bandwidth:	100 kHz
Video bandwidth:	300 kHz
Detector mode:	Peak
Trace mode:	Max Hold

#### 8.6.4 Test data

**Table 8.6-4: Radiated field strength measurement results above 1 GHz**


Channel	Frequency, MHz	Peak Field strength, dB $\mu$ V/m		Margin, dB	Average Field strength, dB $\mu$ V/m		Margin, dB
		Measured	Limit		Measured	Limit	
Low	2390.0	52.4	74.0	21.6	43.5	54.0	10.5
High	2483.5	52.3	74.0	21.7	45.3	54.0	8.7

Notes: Field strength includes correction factor of antenna, cable loss, amplifier, and attenuators where applicable.




Date: 4.JAN.2021 14:00:20

**Figure 8.6-1: Conducted spurious emission at band edge outside restricted band, low channel**




Date: 4.JAN.2021 14:39:25

**Figure 8.6-2: Conducted spurious emissions at band edge outside restricted band, High channel**

**Test data, continued**



Date: 4.JAN.2021 13:58:54

**Figure 8.6-3: Conducted spurious emissions outside restricted band, Low channel**



Date: 4.JAN.2021 14:34:49


**Figure 8.6-4: Conducted spurious emissions outside restricted band, Mid channel**




Date: 4.JAN.2021 14:41:38

**Figure 8.6-5: Conducted spurious emissions outside restricted band, High channel**


Test data, continued



**Figure 8.6-6: Radiated spurious emissions 30 MHz to 1 GHz, Low channel**






**Figure 8.6-7: Radiated spurious emissions 30 MHz to 1 GHz, mid channel**



**Figure 8.6-8: Radiated spurious emissions 30 MHz to 1 GHz, High channel**

Test data, continued



Note: Spectrum was investigated from 30 MHz to 25 GHz. Above 18 GHz, no emission related to RF portion were detected within 6 dB below the limit  
 Average curves in plots above are for information purpose only

## 8.7 FCC 15.247(e) and RSS-247 5.2(b) Power spectral density for digitally modulated devices

---

### 8.7.1 References, definitions and limits

---

#### FCC:

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

(f) For the purposes of this section, hybrid systems are those that employ a combination of both frequency hopping and digital modulation techniques. The frequency hopping operation of the hybrid system, with the direct sequence or digital modulation operation turned-off, shall have an average time of occupancy on any frequency not to exceed 0.4 seconds within a time period in seconds equal to the number of hopping frequencies employed multiplied by 0.4. The power spectral density conducted from the intentional radiator to the antenna due to the digital modulation operation of the hybrid system, with the frequency hopping operation turned off, shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

#### ISED:

The transmitter power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 5.4(d), (i.e. the power spectral density shall be determined using the same method as is used to determine the conducted output power).

### 5.3 Hybrid systems

Hybrid systems employ a combination of both frequency hopping and digital transmission techniques and shall comply with the following:  
With the frequency hopping turned off, the digital transmission operation shall comply with the power spectral density requirements for digital modulation systems set out in of section 5.2(b) or section 6.2.4 for hybrid devices operating in the band 5725–5850 MHz.

### 8.7.2 Test summary

---

Verdict	Pass		
Tested by	Yong Huang	Test date	January 4, 2021

### 8.7.3 Observations, settings and special notes

---

- Power spectral density test was performed as per KDB 558074, section 8.4 with reference to ANSI C63.10 subclause 11.10.
- The test was performed using method PKPSD (peak PSD).


#### Spectrum analyser settings:

Resolution bandwidth:	100 kHz
Video bandwidth:	$\geq 3 \times$ RBW
Frequency span:	5 MHz.
Detector mode:	Peak
Trace mode:	Maxhold

#### 8.7.4 Test data


**Table 8.7-1: PSD results (antenna port measurement)**

Frequency, MHz	PSD, dBm/3 kHz	PSD limit, dBm/3 kHz	Margin, dB
2405	-15.4	8.0	23.4
2440	-16.1	8.0	24.1
2480	-16.0	8.0	24.0




Date: 4.JAN.2021 13:44:20

**Figure 8.7-1: PSD on low channel**



Date: 4.JAN.2021 14:36:41

**Figure 8.7-2: PSD on mid channel**



Date: 4.JAN.2021 14:42:39

**Figure 8.7-3: PSD on high channel**

## Section 9 EUT photos

### 9.1 External photos

---



Figure 9.1-1: Front view photo



Figure 9.1-2: Rear view photo



Figure 9.1-3: Side view photo



**Figure 9.1-4: Side view photo**



**Figure 9.1-5: Side view photo**



**Figure 9.1-6: Side view photo**

**End of the test report**