



**CMA Testing
and Certification
Laboratories**
廠商會檢定中心

TEST REPORT

Report No. : AG016253-001 Date : 2006 July 12

Application No. : LG213729(2)

Applicant : Nikko (NICS Engineering Ltd.)
Unit 2701 & 2710-19, 27/F.,
The Metropolis Tower, The Metropolis Drive,
Hung Hom, Kowloon, Hong Kong

Sample Description : One(1) submitted sample(s) stated to be:

<u>Model name</u>	<u>Model No</u>
Wild Cat	60-4455
Twin Truck	60-4456

Rating : 1 x 9V size battery
No. of submitted sample : One(1) piece(s) ***

Date Received : 2006 July 07

Test Period : 2006 July 10 – 2006 July 11

Test Requested : FCC Part 15 Certification.

Test Method : 47 CFR Part 15 (10-1-05 Edition)
ANSI C63.4 – 2003

Test Result : See attached sheet(s) from page 2 to 11.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15 Subpart C.

Remark : All two models are the same in circuitry and components; and therefore model 60-4455 was chosen to be the representative of the test sample.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature :

Danny Chui
Deputy Manager - EL. Division

FCC ID: CTV41TX-27-1

Page 1 of 11

This document shall not be reproduced except in full or with written approval by the laboratory.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AG016253-001

Date : 2006 July 12

Table of Contents

1	General Information.....	3
1.1	General Description	3
1.2	Location of the test site	4
1.3	List of measuring equipment.....	5
2	Description of the radiated emission test	6
2.1	Test Procedure	6
2.2	Test Result	6
2.3	Radiated Emission Measurement Data	7
3	Description of the Line-conducted Test.....	8
3.1	Test Procedure	8
3.2	Test Result	8
3.3	Graph and Table of Conducted Emission Measurement Data	8
4	Photograph	9
4.1	Photographs of the Test Setup for Radiated Emission and Conduction Emission.....	9
4.2	Photographs of the External and Internal Configurations of the EUT.....	9
5	Supplementary document.....	10
5.1	Bandwidth.....	10
5.2	Duty cycle	10
5.3	Transmission time	10
6	Appendices.....	11

FCC ID: CTV41TX-27-1

Page 2 of 11

This document shall not be reproduced except in full or with written approval by the laboratory.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AG016253-001

Date : 2006 July 12

1 General Information

1.1 General Description

The equipment under test (EUT) is a transmitter for Wild Cat. It is operating at 27.145MHz which is controlled by a crystal. The EUT is powered by 1 x 9V size battery and it has two control trigger in the EUT. When the forward, backward, turn left and turn right trigger is pressed once, it will transmit a difference radio signal to receiver.

The brief circuit description is listed as follows:

- X1, Q1 and associated circuit act as oscillator.
- Q2 and associated circuit act as RF amplify.
- TX2 and associated circuit act as encoder.

FCC ID: CTV41TX-27-1

Page 3 of 11

This document shall not be reproduced except in full or with written approval by the laboratory.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AG016253-001

Date : 2006 July 12

1.2 Location of the test site

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. A shielded room is located at :

Ground Floor, Yan Hing Centre,
9 – 13 Wong Chuk Yeung Street,
Fo Tan, Shatin,
New Territories,
Hong Kong.

FCC ID: CTV41TX-27-1

Page 4 of 11

This document shall not be reproduced except in full or with written approval by the laboratory.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AG016253-001

Date : 2006 July 12

1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.
Spectrum Analyzer	R&S	FSP30	100628
Broadband Antenna	Schaffner	CBL6112B	2692
Loop Antenna	EMCO	6502	0056620

FCC ID: CVT41TX-27-1

Page 5 of 11

This document shall not be reproduced except in full or with written approval by the laboratory.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AG016253-001

Date : 2006 July 12

2 Description of the radiated emission test

2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2003.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

The device was rotated through three orthogonal axes to determine which attitude and configuration produce the highest emission during measurement.

2.2 Test Result

All other measurements are well below the limit. Thus, those highest emissions were presented in next page.

Peak Detector data was measured unless otherwise stated.

* Emissions appearing within the restricted bands shall follow the requirement of section 15.205.

The harmonic emissions meeting the requirement of section 15.209 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

It was found that the EUT meet the FCC requirement.

FCC ID: CTV41TX-27-1

Page 6 of 11

This document shall not be reproduced except in full or with written approval by the laboratory.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AG016253-001

Date : 2006 July 12

2.3 Radiated Emission Measurement Data

Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dB μ V/m)	Antenna and Cable factor (dB)	Average Factor (dB)	Field Strength (dB μ V/m)	Limit at 3m (dB μ V/m)	Margin (dB)
27.145	H	73.8	9.0	-4.3	78.5	80.0	-1.5
54.290	H	14.7	8.1	-	22.8	40.0	-17.2
81.435	H	15.9	7.2	-	23.1	40.0	-16.9
*108.576	H	11.9	11.0	-	22.9	43.5	-20.6
*135.721	H	10.8	12.4	-	23.2	43.5	-20.3
*162.866	H	16.3	10.4	-	26.7	43.5	-16.8
190.011	H	13.7	9.2	-	22.9	43.5	-20.6
217.112	H	13.4	9.7	-	23.1	46.0	-22.9
*244.257	H	13.5	9.7	-	23.2	46.0	-22.8
*271.059	H	13.9	13.9	-	22.8	46.0	-23.2

FCC ID: CTV41TX-27-1

Page 7 of 11

This document shall not be reproduced except in full or with written approval by the laboratory.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>



TEST REPORT

Report No. : AG016253-001

Date : 2006 July 12

3 Description of the Line-conducted Test

3.1 Test Procedure

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2003. The EUT was setup as described in the procedures, and both lines were measured.

3.2 Test Result

No measurement is required as the EUT is a battery-operated product.

3.3 Graph and Table of Conducted Emission Measurement Data

Not Applicable



TEST REPORT

Report No. : AG016253-001

Date : 2006 July 12

4 Photograph

4.1 Photographs of the Test Setup for Radiated Emission and Conduction Emission

The appendices A1 is show the photo of emission test setup configuration.

4.2 Photographs of the External and Internal Configurations of the EUT

The appendices A2 and A3 are show the photos of external and internal configuration.



TEST REPORT

Report No. : AG016253-001

Date : 2006 July 12

5 Supplementary document

The following document were submitted by applicant, and filing in the appendices as below:

Appendices	Document
A4	ID Label/Location
A7	Block Diagram
A8	Schematic Diagram
A9	Users Manual
A10	Operational Description

5.1 Bandwidth

The appendices A5 shows the fundamental emission is confined in the specified band. It also shows that the band edge met the 15.209 requirement at 26.9599 and 27.2801 MHz.

5.2 Duty cycle

The duty cycle is simply the on-time divided by the period, and the appendices A6 shows the graph of following duty cycle.

The duration of one cycle = 23.4ms

Effective period of the cycle = $(1.96\text{ms} \times 4) + (0.64\text{ms} \times 10)$
= 14.24ms

Duty Cycle = $(14.24 / 23.4)\text{ms}$
= 0.61

Therefore, the average factor is found by $20 \log_{10} 0.61 = -4.3\text{dB}$

5.3 Transmission time

N/A



TEST REPORT

Report No. : AG016253-001

Date : 2006 July 12

6 Appendices

A1.	Photos of the set-up of Radiated Emissions	1	page
A2.	Photos of External Configurations	1	page
A3.	Photos of Internal Configurations	1	page
A4.	ID Label/Location	1	page
A5.	Bandwidth Plot	1	page
A6.	Average Factor	2	pages
A7.	Block Diagram	1	page
A8.	Schematics Diagram	1	page
A9.	User Manual	4	pages
A10.	Operation Description	1	page

***** End of Report *****

FCC ID: CTV41TX-27-1

Page 11 of 11

This document shall not be reproduced except in full or with written approval by the laboratory.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: <http://www.cmatcl.com>