



**JAPAN QUALITY ASSURANCE ORGANIZATION**  
21-25, KINUTA 1-CHOME, SETAGAYA-KU, TOKYO 157-8573 JAPAN  
PHONE (03) 3416-0111, TELEX 242-2531 JQA J FAX (03) 3416-9691

JQA APPLICATION NO.: 80-90114  
Issue Date : June 3, 1999  
Page 1 of 16

### **EMI TEST REPORT**

JQA APPLICATION NO. : 80-90114  
Model No. : RN7110  
Type of Equipment : Radio Controlled Toy  
(Superregenerative Type)  
Regulations Applied : CFR 47 FCC Rules and Regulations Part 15  
FCC ID : CVTRN7110  
Applicant : NIKKO CO., LTD.  
Address : 1-7-14, Mizumoto, Katsushika-ku,  
Tokyo 125-0032, Japan  
Manufacture : NIKKO TEC INTERNATIONAL LTD.  
Address : Room 812, Houston Center, 63 Mody Road,  
Tsimshatsui, Kowloon, Hong Kong  
**Final Judgment** : **Passed**

**TEST RESULTS IN THIS REPORT** are obtained in use of equipment that is traceable to  
Electrotechnical Lab. of MITI Japan and Communications Research Lab. of MPT Japan.

The **test results** only respond to the tested sample. It is not allowed to copy this  
report even partly without the allowance of the JQA EMC Engineering Dept. Testing Div.



JQA Application No. :80-90114

FCC ID :CVTRN7110

Model No.

:RN7110

Issue Date :June 3, 1999

Standard

:CFR 47 FCC Rules Part 15

Page 2 of 16

## TABLE OF CONTENTS

	Page
<b>1 Documentation</b>	
1.1 Test Regulation	<u>3</u>
1.2 General Information	<u>3</u>
1.3 Test Condition	<u>4 - 6</u>
1.4 EUT Modifications	<u>7</u>
1.5 Test results / Uncertainty	<u>8</u>
1.6 Summary	<u>9</u>
1.7 Test Configuration / Operation of EUT	<u>10</u>
1.8 Preliminary Test and Test-setup (Drawings)	<u>11 - 13</u>
1.9 EUT Arrangement (Photographs)	<u>14</u>
<b>2 Test Data</b>	
2.1 AC Power Line Conducted Emission 0.45 MHz - 30 MHz	<u>N/A</u>
2.2 Radiated Emission (Electric Field) 30 MHz - 1000 MHz	<u>15 - 16</u>



JQA Application No. :80-90114

FCC ID :CVTRN7110

Model No.

:RN7110

Issue Date :June 3, 1999

Standard

:CFR 47 FCC Rules Part 15

Page 3 of 16

## **1 DOCUMENTATION**

### **1.1 TEST REGULATION**

FCC Rules and Regulations Part 15 Subpart A and B (June 23, 1989) Superregenerative Receiver

#### **Test procedure :**

AC power line conducted emission and radiated emission tests were performed according to the procedures in ANSI C63.4-1992.

### **1.2 GENERAL INFORMATION**

#### **1.2.1 Test facility :**

1) Test Facility located at EMC Engineering Dept. Testing Div. : No.2 and 3 Anechoic Chambers( 3 meters Site )  
FCC filing No. : 31040/SIT 1300F2

2) EMC Engineering Dept. Testing Div. is recognized under the National Voluntary Laboratory accreditation Program for satisfactory compliance established in title 15, Part 285 Code of Federal Regulations.

NVLAP Lab Code : 200189-0 (Effective through : June 30, 1999)

#### **1.2.2 Description of the Equipment Under Test (EUT) :**

1) Type of Equipment	: Radio Controlled Toy
2) Product Type	: Production
3) Category	: Superregenerative receiver
4) EUT Authorization	: Certification
5) FCC ID	: CVTRN7110
6) Trade Name	: NIKKO
7) Model No.	: RN7110
8) Tuning Frequency Range	: 49.830 MHz - 49.890 MHz
9) Highest Frequency Used in the EUT	: -
10) Serial No.	: None
11) Date of Manufacture	: -
12) Power Rating	: DC 4.8V(Battery)
13) EUT Grounding	: None

#### **1.2.3 Definitions for symbols used in this test report :**

x - indicates that the listed condition, standard or equipment is applicable for this report.

— - indicates that the listed condition, standard or equipment is not applicable for this report.

**1.3 TEST CONDITION****1.3.1 The measurement of the AC Power Line Conducted Emission**

   - was performed in the following test site.  
   - was not applicable.

**Test location :**

Safety Testing Center EMC Engineering Dept. Testing Div.  
21-25, Kinuta 1-chome, Setagaya-ku, Tokyo 157-8573, Japan

   - Shielded Enclosure  
   - Anechoic Chamber No. 2 (portable Type)

**Used test instruments :**

Type	Model No.	Manufacturer	Serial No.	Last Cal.	Interval
<u>  </u> - Field Strength Meter	ESH-2	Rohde & Schwarz	872280/011	Sep. 1998	1 Year
<u>  </u> - Field Strength Meter	ESH-2	Rohde & Schwarz	880370/016	May 1999	1 Year
<u>  </u> - Field Strength Meter	ESH-3	Rohde & Schwarz	881460/016	May 1999	1 Year
<u>  </u> - Field Strength Meter	ESH-3	Rohde & Schwarz	881460/030	Nov 1999	1 Year
<u>  </u> - LISN	KNW-407	Kyoritsu Electrical	8-833-6	Apr. 1999	1 Year
<u>  </u> - LISN	KNW-407	Kyoritsu Electrical	8-855-2	Apr. 1999	1 Year
<u>  </u> - LISN	KNW-407	Kyoritsu Electrical	8-757-1	Apr. 1999	1 Year
<u>  </u> - RF Cable	3D-2W	Fujikura	155-21-005	Apr. 1999	1 Year
<u>  </u> - RF Cable	3D-2W	Fujikura	155-21-006	Apr. 1999	1 Year

**1.3.2 The measurement of the Radiated Emission(30 MHz - 1000 MHz)**

x - was performed in the following test site.  
  - was not applicable.

**Test location :**

Safety Testing Center EMC Engineering Dept. Testing Div.  
21-25, Kinuta 1-chome, Setagaya-ku, Tokyo 157-8573, Japan

x - Anechoic Chamber No. 2 (3 meters)  
  - Anechoic Chamber No. 3 (3 meters)

**Validation of Site Attenuation :**

1) Last Confirmed Date :March, 1999  
2) Interval :1 year

**Used test instruments :**

Type	Model No.	Manufacturer	Serial No.	Last Cal.	Interval
<u> </u> - Field Strength Meter	ESV	Rohde & Schwarz	872148/039	May 1999	1 Year
<u> </u> - Field Strength Meter	ESVP	Rohde & Schwarz	879783/030	May 1999	1 Year
<u>x</u> - Field Strength Meter	ESVP	Rohde & Schwarz	881478/004	May 1999	1 Year
<u> </u> - Field Strength Meter	ESVP	Rohde & Schwarz	881478/005	May 1999	1 Year
<u> </u> - Antenna	KBA-511A	Kyoritsu Electrical	0-201-13	Nov. 1998	1 Year
<u>x</u> - Antenna	KBA-511A	Kyoritsu Electrical	0-170-1	Nov. 1998	1 Year
<u> </u> - Antenna	KBA-611	Kyoritsu Electrical	0-210-5	Nov. 1998	1 Year
<u>x</u> - Antenna	KBA-611	Kyoritsu Electrical	0-147-14	Nov. 1998	1 Year
<u>x</u> - RF Cable	5D-2W	Fujikura	155-21-001	Feb. 1999	1 Year
<u> </u> - RF Cable	5D-2W	Fujikura	155-21-002	Feb. 1999	1 Year

**1.3.3 The measurement of the Radiated Emission(Above 1000 MHz)**

       - was performed in the following test site.  
x - was not applicable.

**Test location :**

Safety Testing Center EMC Engineering Dept. Testing Div.  
21-25, Kinuta 1-chome, Setagaya-ku, Tokyo 157-8573, Japan

       - No. 2 site (3 meters)  
       - No. 3 site (3 meters)

**Validation of Site Attenuation :**

- 1) Last Confirmed Date :March, 1999
- 2) Interval :1 year

**Used test instruments :**

Type	Model No.	Manufacturer	Serial No.	Last Cal.	Interval
<u>      </u> - Spectrum Analyzer	8560E	Hewlett Packard	3240A00189	May 1999	1 Year
<u>      </u> - Spectrum Analyzer	8563E	Hewlett Packard	3221A00201	May 1999	1 Year
<u>      </u> - Spectrum Analyzer	8566B	Hewlett Packard	2140A01091	Apr. 1999	1 Year
<u>      </u> - Spectrum Analyzer	8566B	Hewlett Packard	2747A05855	Jul. 1998	1 Year
<u>      </u> - Log-Periodic Antenna	HL 025	Rohde & Schwarz	340182/015	Nov. 1998	1 Year
<u>      </u> - RF Cable	S 04272B	Suhner	155-21-011	May 1999	1 Year



JQA Application No. :80-90114

Model No.

:RN7110

Standard

:CFR 47 FCC Rules Part 15

FCC ID :CVTRN7110

Issue Date :June 3, 1999

Page 7 of 16

#### 1.4 EUT MODIFICATION

-No modifications were conducted by JQA to achieve compliance to Class B levels.  
 -To achieve compliance to Class B levels, the following changes were made by JQA during the compliance test.

**The modifications will be implemented in all production models of this equipment.**

Applicant :

Date :

Typed Name :

Position :



JQA Application No. :80-90114

FCC ID :CVTRN7110

Model No.

:RN7110

Issue Date :June 3, 1999

Standard

:CFR 47 FCC Rules Part 15

Page 8 of 16

**1.5 TEST RESULTS / UNCERTAINTY****AC Power Line Conducted Emission**  - Applicable  - NOT ApplicableThe requirements are  - PASSED  - NOT PASSED

Min. Limit Margin dB at MHz

Max. Limit Exceeding dB at MHz

Uncertainty of Measurement Results + 2.3 dB - 2.3 dB

**Remarks :****Radiated Emission [§15.109(a)]**  - Applicable  - NOT ApplicableThe requirements are  - PASSED  - NOT PASSED

Min. Limit Margin 22.4 dB at 224.240 MHz

Max. Limit Exceeding dB at MHz

Uncertainty of Measurement Results + 3.2 dB - 3.2 dB

**Remarks:**

**1.6 SUMMARY****General Remarks :**

The EUT was tested according to the requirements of FCC Rules and Regulations Part 15 Subpart A and B (June 23, 1989) under the test configuration, as shown in clause 1.7 to 1.9.

The conclusion for the test items of which are required by the applied regulation is indicated under the final judgment.

**Final Judgment :**

The "as received" sample;

- x - fulfill the test requirements of the regulation mentioned on clause 1.1.
- fulfill the test requirements of the regulation mentioned on clause 1.1, but with certain qualifications.
- doesn't fulfill the test regulation mentioned on clause 1.1.

Begin of testing : May 21, 1999

End of testing : May 21, 1999

- JAPAN QUALITY ASSURANCE ORGANIZATION -

Signatories:



Masaaki Takahashi  
Manager  
JQA EMC Engineering Dept.



Shigeru Osawa  
Assistant Manager  
JQA EMC Engineering Dept.



JQA Application No. :80-90114

FCC ID :CVTRN7110

Model No.

:RN7110

Issue Date :June 3, 1999

Standard

:CFR 47 FCC Rules Part 15

Page 10 of 16

---

## 1.7 TEST CONFIGURATION / OPERATION OF EUT

### 1.7.1 Test Configuration

**The equipment under test (EUT) consists of :**

Item	Manufacturer	Model No.	FCC ID	Serial No.
Radio Controlled Toy	NIKKO TEC INTERNATIONAL LTD.	RN7110	CVTRN7110	-

### 1.7.2 Operating condition

Power supply Voltage : 4.8 VDC(Battery)

The tests have been carried out under the receiving condition.

## 1.8 PRELIMINARY TEST AND TEST-SETUP (DRAWINGS)

### 1.8.1 AC Power Line Conducted Emission ( 450 kHz - 30 MHz) :

According to description of ANSI C63.4-1992 sec.7.2.3, the AC power line preliminary conducted emissions measurements were carried out.

The preliminary conducted measurements were performed using the spectrum analyzer to observe the emission characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions. These configurations were used for final AC power line conducted emissions measurements.


#### Shielded Enclosure

##### - Side View -

Vertical

Ground


Plane



**1.8.2 Radiated Emission ( 30 MHz - 1000 MHz) :**

According to description of ANSI C63.4-1992 sec.8.3.1.1, the preliminary radiated emissions measurements were carried out. The preliminary radiated measurements were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.


The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions. These configurations were used for the final radiated emissions measurements.

**Anechoic Chamber****- Side View -**

**1.8.3 Radiated Emission (Above 1 GHz) :**

According to description of ANSI C63.4-1992 sec.8.3.1.1, the preliminary radiated emissions measurements were carried out. The preliminary radiated measurements were performed at the measurement distance that specified for compliance to determine the emission characteristics of the EUT.

The EUT configuration, cable configuration and mode of operation were determined for producing the maximum level of emissions. These configurations were used for the final radiated emissions measurements.

**Anechoic Chamber****- Side View -**

**1.9 TEST ARRANGEMENT (PHOTOGRAPHS)**

PHOTOGRAPHS OF EUT CONFIGURATION FOR RADIATED EMISSIONS MEASUREMENT

Photograph present configuration with maximum emission





JQA Application No. :80-90114

FCC ID :CVTRN7110

Model No.

:RN7110

Issue Date :June 3, 1999

Standard

:CFR 47 FCC Rules Part 15

Page 15 of 16

---

**TEST DATA****2.2 Radiated Emissions Measurement( 30 MHz - 1000 MHz )**Date : May 21, 1999Temp.: 24 °C Humi.: 58 %

Tuning Frequency : 49.860 MHz

Distance of Measurement : 3.0 meters

Frequency (MHz)	Antenna Factor (dB/m)	Meter Reading		Limits (dBµV/m)	Field Strength at 3 m		Margins	
		Horiz. (dBµV)	Vert. (dBµV)		Horiz. (dBµV/m)	Vert. (dBµV/m)	Horiz. (dB)	Vert. (dB)
47.100	3.0	3.8	9.6	40.0	6.8	12.6	33.2	27.4
50.500	3.7	5.5	11.2	40.0	9.2	14.9	30.8	25.1
90.370	9.0	< 0.0	6.1	43.5	< 9.0	15.1	> 34.5	28.4
224.240	17.5	< 0.0	6.1	46.0	< 17.5	23.6	> 28.5	22.4
266.800	19.2	< 0.0	4.5	46.0	< 19.2	23.7	> 26.8	22.3

Note: 1. The spectrum was checked from 30 MHz to 1000 MHz.

All emissions not listed were found to be more than 20 dB below  
the limits.

2. The symbol of "<" means "or less".
3. The cable loss was included in the antenna factor.
4. Sample calculation :  
at 47.100 MHz  
$$Af + Mr = 3.0 + 9.6 = 12.6 \text{ dB}\mu\text{V/m}$$
Where,  
Af = Antenna Factor including the cable loss.  
Mr = Meter Reading
5. Measuring Instrument Setting:  
Detector function : CISPR quasi-peak  
IF Bandwidth : 120 kHz

Tested by :

Shigeru Osawa  
Testing Engineer

**Radiated Spurious Emissions**

FCC ID : CVTRN7110  
Tuning Frequency : 49.860 MHz  
Test Condition :

