

Applicant: LICC Manufacturing Co (Far East) Limited

Product Description: i-Lasso Presenter

Model No.: G202, R201

FCC ID: CWHPTT200M

Frequency range: 2409.65 MHz – 2465.68 MHz

Maximum Antenna Gain: 7.9 dBi

Maximum RF Output Power: 0.2mW

Following KDB 447498 D01, clause 4.3.1:

#### **4.3.1 Exemption from Routine Evaluation Limits – RF Exposure Evaluation**

RF Exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is less than 20 cm, except when the device operates as follows

For 100 MHz to 6 GHz and *test separation distances*  $\leq$  50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0$  for 1-g SAR, and  $\leq 7.5$  for 10-g extremity SAR, where

$f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz

$$0.2/(5) * \sqrt{2.46568} = 0.0628 < 3$$

Thus for <20cm portable usage, the SAR exclusion condition is fulfilled and SAR evaluation is not required for a separation distance of 5mm or more.