

Document No. 5AX000XX00	Title Product Specification	Page 1/13
Background	Passive Entry System	

Product Specification

Passive Entry System

ALPS

Document No. 5AX000XX00	Title Product Specification	Page 2/13
Background	Passive Entry System	

Ver.	Date	Background	Changing point	Page	Appd.	Chkd.	Dsgd.
DRAFT	00/02/18	-	Create	-	-	-	MRK
CHG1	02/08/27		All	-			NKH

Document No. 5AX000XX00	Title Product Specification	Page 3/13
Background	Passive Entry System	

CONTENTS

1. PREFACE	4
2. PASSIVE ACCESS ENTRY FUNCTIONALITY	5
2.1. Door Unlocking.....	5
2.2. Engine Start.....	6
2.3. Engine Stop.....	6
2.4. Door Locking (Push switch)	7
3. ACTIVE ACCESS ENTRY FUNCTIONALITY	8
3.1. Door Unlocking.....	8
3.2. Engine Start.....	8
3.3. Engine Stop.....	8
3.4. Door Locking	8
4. ENTRY SYSTEM OPTIONS.....	9
4.1. System Schematic	9
4.2. Modules	9
4.2.1. FOB ECU	9
4.2.2. Entry System ECU	9
5. SYSTEM CHARACTERISTICS.....	10
5.1. Antenna Areas	10
5.2. Exciter Locations.....	11
5.3. Switch Input Locations (Door handle, Touch sensor)	12
6. ELECTRICAL CHARACTERISTICS	13
6.1. FOB	13
6.2. Entry System ECU	13

Document No. 5AX000XX00	Title Product Specification	Page 4/13
Background	Passive Entry System	

1.Preface

This document describes the requirements and operation of the Passive Entry System. However, this document is especially for the Entry system ECU (acronym for Electric Control Unit) and the FOB.

The FOB consists the following functionality for passive access and active access:

- Door unlocking / locking (however, only for request by means of switch operation)
- Trunk unlocking / locking (however, only for request by means of switch operation)
- LF decoding
- RF encoding
- Communication data encryption (cryptograph, anti-collision, rolling code and stuff)

And the entry system ECU consists of the following functionality:

- Door unlocking / locking
- Trunk unlocking / locking
- Engine start (/ stop)
- LF encoding
- RF encoding
- Communication data encryption (cryptograph, anti-collision, rolling code and stuff)
- LF antenna unit control
- Communication with the node ECUs connected to the body bus (e.g. CAN, J1850, customer dependent bus)

As a further function, both the FOB and the entry system ECU provides the following function:

- Learning mode for programming the manufacturing data and stuff
- Data locking and password protection
- Diagnostic (based upon ISO9141 if required)

Document No. 5AX000XX00	Title Product Specification	Page 5/13
Background	Passive Entry System	

2. Passive Access Entry Functionality

A proximity sensor located on, for example the door handles, mirrors and trunk lid will be used for proximity check if user is in neighborhood of the vehicle. The switch input will trigger for unlocking and open the doors and trunk.



Figure 1

2.1. Door Unlocking

- User pull / touch the door handle (sensing of door handle switch).
- ECU sends LF-challenge via exterior antenna.
- FOB sends RF-response to the ECU.
- Door unlocking status is engaged.
- Doors are opened.




Figure 2

Document No. 5AX000XX00	Title Product Specification	Page 6/13
Background	Passive Entry System	

2.2.Engine Start

- User pushes / operate the engine start button / knob.
- ECU sends LF-challenge via interior antenna.
- FOB sends RF-response to the ECU.
- Immobilizer ECU receives and authorize the response.
- Engine controller ECU receives the authorization for engine start.
- Start the engine.




Figure 3

2.3.Engine Stop

- User pushes / operate the engine stop button / knob.
- ECU communicates with the other ECU for engine start request.
- Engine controller ECU receives the request.
- Stop the engine



Figure 4

Document No. 5AX000XX00	Title Product Specification	Page 7/13
Background	Passive Entry System	

2.4.Door Locking (Push switch)

- User closes the door and pushes the switch (sensing of door locking switch).
- ECU sends LF-challenge via exterior antenna.
- FOB sends RF-response to the ECU.
- Door locking status is engaged.
- Doors are locked.
- (Indicates the door locking status by means of Flasher / Buzzer or stuff)



Figure 5

Document No. 5AX000XX00	Title Product Specification	Page 8/13
Background	Passive Entry System	

3.Active Access Entry Functionality

3.1.Door Unlocking

Same functionality as the current one.

3.2.Engine Start

This function does not effect on the active entry system.

3.3.Engine Stop

This function does not have influencei on the active entry system.


3.4.Door Locking

Same functionality as the current one.

Document No. 5AX000XX00	Title Product Specification	Page 9/13
Background	Passive Entry System	


4. Entry System Options

4.1. System Schematic




4.2. Modules

4.2.1. FOB ECU



4.2.2. Entry System ECU



Document No. 5AX000XX00	Title Product Specification	Page 10/13
Background	Passive Entry System	

5. System Characteristics

5.1. Antenna Areas

Exterior operating range: 0.8m to 1.5m
Interior operating range: Only inside the car

Number of the exterior excitors : max. 5 (min. 2), however, it is depending on the type of the vehicle.
Number of the interior excitors: 1 (1-Dimension) or 2 (2-Dimension required)




Figure 6

Exterior antenna functionality:

- Unlock / lock doors and trunk.
- Activate / deactivate alarm system.
- Activate immobilizer

Interior antenna functionality:

- Deactivate immobilizer
- Engine start

Document No. 5AX000XX00	Title Product Specification	Page 11/13
Background	Passive Entry System	

5.2.Exciter Locations

Exterior excitors: 2 doors and 1 trunk

Interior excitors: 1 driver's sheet

2 column / shift lever (X-Y 2-Dimension)




Figure 7

Antenna location can be different among of type of the vehicle (e.g. coupe, sedan, mini and stuff).

Document No. 5AX000XX00	Title Product Specification	Page 12/13
Background	Passive Entry System	

5.3.Switch Input Locations (Door handle, Touch sensor)

There are some kind of sensors, for instance the door handle contact switch and touch sensor, will be used as a triggering for unlocking and open the door.

Switch inputs: 2 doors and 1 trunk




Figure 8

Switch inputs can be different among of type of the vehicle (e.g. coupe, sedan, mini and stuff).

Document No. 5AX000XX00	Title Product Specification	Page 13/13
Background	Passive Entry System	

6.Electrical Characteristics

6.1.FOB

- ASK / FSK modulation
- Operating supply voltage 2.1V to 3.3V (3.0V Battery)
- Operating supply current < 30mA
- Stand-by current < 10.0uA
- Operating ambient temperature -20°C to +60°C
- Antenna direction 3-Dimension (X, Y, Z), to be considered
- Battery life 2 Years (Low battery indication is considered)

6.2.Entry System ECU

- Operating supply voltage 10.5V to 16.0V
- Operating supply current < 15mA (20mA to 30mA)
- Stand-by current < 2mA
- Operating ambient temperature -40°C to +85°C
-