

FCC Test Report

Report No.: RF150907C14B

FCC ID: D87-UZB3-HMY

Test Model: ACC-UZB3-HMY

Received Date: May 26, 2016

Test Date: Jun. 02 ~ Jun. 04, 2016

Issued Date: Jun. 06, 2016

Applicant: Sigma Designs, Inc.

Address: 47467 Fremont Blvd., Fremont, CA 94538 USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan (R.O.C.)

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 Summary of Test Results	5
2.1 Measurement Uncertainty	5
2.2 Modification Record	5
3 General Information.....	6
3.1 General Description of EUT	6
3.2 Description of Test Modes	6
3.2.1 Test Mode Applicability and Tested Channel Detail.....	7
3.3 Description of Support Units	8
3.3.1 Configuration of System under Test	8
3.4 General Description of Applied Standards	8
4 Test Types and Results	9
4.1 Radiated Emission Measurement	9
4.1.1 Limits of Radiated Emission Measurement	9
4.1.2 Test Instruments	10
4.1.3 Test Procedures.....	11
4.1.4 Deviation from Test Standard	11
4.1.5 Test Set Up	12
4.1.6 EUT Operating Conditions.....	12
4.1.7 Test Results	13
4.2 Conducted Emission Measurement	22
4.2.1 Limits of Conducted Emission Measurement	22
4.2.2 Test Instruments	22
4.2.3 Test Procedures.....	23
4.2.4 Deviation from Test Standard	23
4.2.5 Test Setup.....	23
4.2.6 EUT Operating Conditions.....	23
4.2.7 Test Results	24
4.3 Band Edge Measurement	30
4.3.1 Limits of Band Edge Measurement	30
4.3.2 Test Instruments	31
4.3.3 Test Procedures.....	32
4.3.4 Deviation from Test Standard	32
4.3.5 Test Set Up	33
4.3.6 EUT Operating Conditions.....	33
4.3.7 Test Results	34
5 Pictures of Test Arrangements.....	40
Appendix – Information on the Testing Laboratories	41

Release Control Record

Issue No.	Description	Date Issued
RF150907C14B	Original release.	Jun. 06, 2016

1 Certificate of Conformity

Product: Z-Wave USB Stick

Brand: Sigma Designs

Test Model: ACC-UZB3-HMY

Sample Status: Engineering sample

Applicant: Sigma Designs, Inc.

Test Date: Jun. 02 ~ Jun. 04, 2016

Standards: 47 CFR FCC Part 15, Subpart C (Section 15.249)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Celine Chou , **Date:** Jun. 06, 2016
Celine Chou / Specialist

Approved by : Ken Liu , **Date:** Jun. 06, 2016
Ken Liu / Senior Manager

2 Summary of Test Results

47 CFR FCC Part 15, Subpart C (Section 15.249)			
FCC Clause	Test Item	Result	Remarks
15.207	AC Power Conducted Emission	Pass	Meet the requirement of limit. Minimum passing margin is -12.89dB at 0.36094MHz.
15.209 15.249 15.249 (d)	Radiated Emission Test Band Edge Measurement Limit: 50dB less than the peak value of fundamental frequency or meet radiated emission limit in section 15.209	Pass	Meet the requirement of limit. Minimum passing margin is -1.1dB at 921.42MHz.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.44 dB
Radiated Emissions up to 1 GHz	30MHz ~ 200MHz	3.86 dB
	200MHz ~ 1000MHz	3.87 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	Z-Wave USB Stick
Brand	Sigma Designs
Test Model	ACC-UZB3-HMY
Status of EUT	Engineering sample
Power Supply Rating	5Vdc (Host equipment)
Modulation Type	2FSK (9.6kbps, 40kbps) / 2GFSK (100kbps)
Transfer Rate	9.6kbps, 40kbps, 100kbps
Operating Frequency	921.42MHz, 921.40MHz, 919.80MHz
Number of Channel	3
Antenna Type	Helical antenna with -1.13dBi gain
Accessory Device	N/A
Data Cable Supplied	N/A

Note: The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

3.2 Description of Test Modes

3 channels are provided for EUT:

Channel	Frequency (MHz)	Transfer Rate (kbps)
1	921.42	9.6
2	921.40	40
3	919.80	100

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT CONFIGURE MODE	APPLICABLE TO			DESCRIPTION
	RE $\geq$ 1G	RE<1G	PLC	
-	√	√	√	-

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz & Bandedge Measurement
RE<1G: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission

NOTE: The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **X-plane**.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
1	921.42MHz	2FSK
2	921.40MHz	2FSK
3	919.80MHz	2GFSK

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
1	921.42MHz	2FSK
2	921.40MHz	2FSK
3	919.80MHz	2GFSK

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE
1	921.42MHz	2FSK
2	921.40MHz	2FSK
3	919.80MHz	2GFSK

Test Condition:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	INPUT POWER (SYSTEM)	TESTED BY
RE $\geq$ 1G	16deg. C, 70%RH	120Vac, 60Hz	Nick Hsu
RE<1G	16deg. C, 70%RH	120Vac, 60Hz	Nick Hsu
PLC	16deg. C, 70%RH	120Vac, 60Hz	Alan Wu

3.3 Description of Support Units


The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	ASUS	P2420L	FCNXCV16385351D	FCC DoC Approved	-

Note: All power cords of the above support units are non-shielded (1.8m).

ID	Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	USB cable	1	1.8	Y	0	-

3.3.1 Configuration of System under Test



3.4 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C (15.249)

ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

Note: The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

4 Test Types and Results

4.1 Radiated Emission Measurement

4.1.1 Limits of Radiated Emission Measurement

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902 ~ 928 MHz	50	500
2400 ~ 2483.5 MHz	50	500
5725 ~ 5875 MHz	50	500
24 ~ 24.25 GHz	250	2500

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits as below table, whichever is the lesser attenuation

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	$2400/F(\text{kHz})$	300
0.490 ~ 1.705	$24000/F(\text{kHz})$	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = $20 \log$ Emission level ($\mu\text{V}/\text{m}$).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESIB7	100187	Apr. 18, 2016	Apr. 17, 2017
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Sep. 02, 2015	Sep. 01, 2016
BILOG Antenna SCHWARZBECK	VULB9168	9168-171	Jan. 07, 2016	Jan. 06, 2017
HORN Antenna SCHWARZBECK	9120D	209	Jan. 20, 2016	Jan. 19, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Jan. 18, 2016	Jan. 17, 2017
Preamplifier Agilent	8447D	2944A10738	Oct. 18, 2015	Oct. 17, 2016
Preamplifier Agilent	8449B	3008A01964	Aug. 22, 2015	Aug. 21, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH3-03 (214378)	Aug. 22, 2015	Aug. 21, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 106	Cable-CH3-03 (309224+12738)	Aug. 22, 2015	Aug. 21, 2016
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021702	NA	NA
Turn Table BV ADT	TT100	TT93021702	NA	NA
Turn Table Controller BV ADT	SC100	SC93021702	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 3.
 3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 988962.
 5. The IC Site Registration No. is IC 7450F-3.

4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters (for below 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Set Up

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

Set the EUT under transmission condition continuously at specific channel frequency.

4.1.7 Test Results

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1 (921.42MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*921.42	93.3 PK	114.0	-20.7	1.39 H	194	64.8	28.5
2	*921.42	92.9 AV	94.0	-1.1	1.39 H	194	64.4	28.5
3	928.00	35.3 PK	43.3	-8.0	1.39 H	194	6.6	28.7
4	928.00	32.5 AV	42.9	-10.4	1.39 H	194	3.8	28.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*921.42	86.6 PK	114.0	-27.4	1.55 V	156	58.1	28.5
2	*921.42	86.1 AV	94.0	-7.9	1.55 V	156	57.6	28.5
3	928.00	30.1 PK	36.6	-6.5	1.55 V	156	1.4	28.7
4	928.00	27.0 AV	36.1	-9.1	1.55 V	156	-1.7	28.7

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * “ : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 2 (921.40MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*921.40	92.8 PK	114.0	-21.2	1.45 H	191	64.3	28.5
2	*921.40	92.6 AV	94.0	-1.4	1.45 H	191	64.1	28.5
3	928.00	33.3 PK	42.8	-9.5	1.45 H	194	4.6	28.7
4	928.00	31.6 AV	42.6	-11.0	1.45 H	194	2.9	28.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*921.40	86.5 PK	114.0	-27.5	1.50 V	157	58.0	28.5
2	*921.40	86.3 AV	94.0	-7.7	1.50 V	157	57.8	28.5
3	928.00	33.2 PK	36.5	-3.3	1.50 V	157	4.5	28.7
4	928.00	30.3 AV	36.3	-6.0	1.50 V	157	1.6	28.7

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3 (919.80MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*919.80	92.6 PK	114.0	-21.4	1.38 H	194	64.1	28.5
2	*919.80	92.4 AV	94.0	-1.6	1.38 H	194	63.9	28.5
3	928.00	37.1 PK	42.6	-5.5	1.38 H	194	8.4	28.7
4	928.00	33.7 AV	42.4	-8.7	1.38 H	194	5.0	28.7
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*919.80	86.0 PK	114.0	-28.0	1.51 V	159	57.5	28.5
2	*919.80	85.7 AV	94.0	-8.3	1.51 V	159	57.2	28.5
3	928.00	33.2 PK	36.0	-2.8	1.51 V	159	4.5	28.7
4	928.00	30.8 AV	35.7	-4.9	1.51 V	159	2.1	28.7

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency

Above 1GHz Worst-Case Data:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1 (921.42MHz)	FREQUENCY RANGE	1 ~ 10GHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1842.84	38.5 PK	74.0	-35.5	1.56 H	304	42.1	-3.6
2	1842.84	25.2 AV	54.0	-28.8	1.56 H	304	28.8	-3.6
3	2764.26	49.8 PK	74.0	-24.2	1.50 H	259	50.0	-0.2
4	2764.26	47.4 AV	54.0	-6.6	1.50 H	259	47.6	-0.2
5	4607.10	49.3 PK	74.0	-24.7	1.18 H	233	44.6	4.7
6	4607.10	43.8 AV	54.0	-10.2	1.18 H	233	39.1	4.7
7	8292.78	56.8 PK	74.0	-17.2	1.29 H	204	43.2	13.6
8	8292.78	47.5 AV	54.0	-6.5	1.29 H	204	33.9	13.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1842.84	38.2 PK	74.0	-35.8	1.51 V	79	41.8	-3.6
2	1842.84	26.7 AV	54.0	-27.3	1.51 V	79	30.3	-3.6
3	2764.26	49.1 PK	74.0	-24.9	1.46 V	181	49.3	-0.2
4	2764.26	45.9 AV	54.0	-8.1	1.46 V	181	46.1	-0.2
5	4607.10	47.8 PK	74.0	-26.2	1.44 V	171	43.1	4.7
6	4607.10	40.3 AV	54.0	-13.7	1.44 V	171	35.6	4.7
7	8292.78	57.6 PK	74.0	-16.4	1.01 V	182	44.0	13.6
8	8292.78	48.8 AV	54.0	-5.2	1.01 V	182	35.2	13.6

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 2 (921.40MHz)	FREQUENCY RANGE	1 ~ 10GHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1842.80	38.7 PK	74.0	-35.3	1.57 H	301	42.3	-3.6
2	1842.80	26.7 AV	54.0	-27.3	1.57 H	301	30.3	-3.6
3	2764.20	49.7 PK	74.0	-24.3	1.08 H	240	49.9	-0.2
4	2764.20	47.5 AV	54.0	-6.5	1.08 H	240	47.7	-0.2
5	4607.00	49.3 PK	74.0	-24.7	1.15 H	231	44.6	4.7
6	4607.00	42.4 AV	54.0	-11.6	1.15 H	231	37.7	4.7
7	8292.60	56.9 PK	74.0	-17.1	1.22 H	204	43.3	13.6
8	8292.60	48.2 AV	54.0	-5.8	1.22 H	204	34.6	13.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1842.80	37.2 PK	74.0	-36.8	1.50 V	79	40.8	-3.6
2	1842.80	26.8 AV	54.0	-27.2	1.50 V	79	30.4	-3.6
3	2764.20	49.0 PK	74.0	-25.0	1.55 V	180	49.2	-0.2
4	2764.20	46.3 AV	54.0	-7.7	1.55 V	180	46.5	-0.2
5	4607.00	47.8 PK	74.0	-26.2	1.41 V	159	43.1	4.7
6	4607.00	40.2 AV	54.0	-13.8	1.41 V	159	35.5	4.7
7	8292.60	57.6 PK	74.0	-16.4	1.02 V	179	44.0	13.6
8	8292.60	50.5 AV	54.0	-3.5	1.02 V	179	36.9	13.6

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3 (919.80MHz)	FREQUENCY RANGE	1 ~ 10GHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK) Average (AV)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1839.60	38.4 PK	74.0	-35.6	1.00 H	296	42.0	-3.6
2	1839.60	25.8 AV	54.0	-28.2	1.00 H	296	29.4	-3.6
3	2759.40	48.5 PK	74.0	-25.5	1.14 H	237	48.8	-0.3
4	2759.40	45.6 AV	54.0	-8.4	1.14 H	237	45.9	-0.3
5	4599.00	48.3 PK	74.0	-25.7	1.05 H	230	43.6	4.7
6	4599.00	41.0 AV	54.0	-13.0	1.05 H	230	36.3	4.7
7	8278.20	56.1 PK	74.0	-17.9	1.24 H	203	42.5	13.6
8	8278.20	46.1 AV	54.0	-7.9	1.24 H	203	32.5	13.6
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	1839.60	38.4 PK	74.0	-35.6	1.00 V	296	42.0	-3.6
2	1839.60	26.1 AV	54.0	-27.9	1.00 V	296	29.7	-3.6
3	2759.40	46.0 PK	74.0	-28.0	1.14 V	237	46.3	-0.3
4	2759.40	42.3 AV	54.0	-11.7	1.14 V	237	42.6	-0.3
5	4599.00	47.4 PK	74.0	-26.6	1.05 V	230	42.7	4.7
6	4599.00	37.4 AV	54.0	-16.6	1.05 V	230	32.7	4.7
7	8278.20	56.3 PK	74.0	-17.7	1.24 V	203	42.7	13.6
8	8278.20	47.4 AV	54.0	-6.6	1.24 V	203	33.8	13.6

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

Below 1GHz Worst-Case Data:

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1 (921.42MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	86.37	27.0 QP	40.0	-13.0	2.00 H	165	46.7	-19.7
2	148.58	27.4 QP	43.5	-16.1	2.00 H	208	41.3	-13.9
3	228.28	19.3 QP	46.0	-26.7	1.50 H	45	35.3	-16.0
4	306.03	22.7 QP	46.0	-23.3	1.01 H	225	34.6	-11.9
5	473.21	22.7 QP	46.0	-23.3	1.50 H	261	31.4	-8.7
6	714.25	31.7 QP	46.0	-14.3	1.50 H	171	35.6	-3.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	33.89	21.6 QP	40.0	-18.4	1.00 V	141	37.3	-15.7
2	80.54	25.3 QP	40.0	-14.7	1.49 V	159	44.0	-18.7
3	148.58	22.8 QP	43.5	-20.7	1.99 V	195	36.7	-13.9
4	239.94	20.0 QP	46.0	-26.0	1.00 V	199	34.6	-14.6
5	300.20	22.1 QP	46.0	-23.9	1.00 V	296	34.3	-12.2
6	416.83	19.8 QP	46.0	-26.2	1.49 V	135	29.7	-9.9

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB)
– Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 2 (921.40MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	86.37	24.9 QP	40.0	-15.1	1.99 H	163	44.6	-19.7
2	148.58	27.2 QP	43.5	-16.3	1.99 H	24	41.1	-13.9
3	236.05	18.9 QP	46.0	-27.1	1.49 H	67	34.1	-15.2
4	286.59	22.2 QP	46.0	-23.8	1.00 H	219	34.7	-12.5
5	473.21	22.4 QP	46.0	-23.6	1.49 H	234	31.1	-8.7
6	714.25	35.0 QP	46.0	-11.0	1.49 H	354	38.9	-3.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	80.54	25.5 QP	40.0	-14.5	1.50 V	198	44.2	-18.7
2	148.58	20.3 QP	43.5	-23.2	2.00 V	213	34.2	-13.9
3	247.72	20.2 QP	46.0	-25.8	1.01 V	206	34.5	-14.3
4	300.20	22.4 QP	46.0	-23.6	1.01 V	265	34.6	-12.2
5	414.89	20.0 QP	46.0	-26.0	1.01 V	156	30.0	-10.0
6	480.98	20.5 QP	46.0	-25.5	1.50 V	308	29.1	-8.6

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3 (919.80MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Quasi-Peak
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	86.37	26.0 QP	40.0	-14.0	2.00 H	179	45.7	-19.7
2	148.58	26.9 QP	43.5	-16.6	2.00 H	198	40.8	-13.9
3	238.00	20.3 QP	46.0	-25.7	1.50 H	66	35.1	-14.8
4	304.09	21.7 QP	46.0	-24.3	1.01 H	224	33.8	-12.1
5	482.93	22.6 QP	46.0	-23.4	1.50 H	254	31.2	-8.6
6	714.25	32.5 QP	46.0	-13.5	1.50 H	79	36.4	-3.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	33.89	21.8 QP	40.0	-18.2	1.00 V	276	37.5	-15.7
2	80.54	24.8 QP	40.0	-15.2	1.00 V	149	43.5	-18.7
3	148.58	20.5 QP	43.5	-23.0	1.00 V	259	34.4	-13.9
4	238.00	22.4 QP	46.0	-23.6	1.00 V	312	37.2	-14.8
5	307.98	23.4 QP	46.0	-22.6	1.00 V	253	35.3	-11.9
6	714.25	31.8 QP	46.0	-14.2	2.00 V	310	35.7	-3.9

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.

4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Oct. 12, 2015	Oct. 11, 2016
RF signal cable (with 10dB PAD) Woken	5D-FB	Cable-cond2-01	Dec. 26, 2015	Dec. 25, 2016
LISN ROHDE & SCHWARZ (EUT)	ESH2-Z5	100100	Jan. 11, 2016	Jan. 10, 2017
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100312	Jul. 21, 2015	Jul. 20, 2016
Software ADT	BV ADT_Cond_ V7.3.7.3	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 2.

3. The VCCI Site Registration No. is C-2047.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

Note: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.


4.2.7 Test Results

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	Channel 1 (921.42MHz)		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15781	10.13	31.88	21.54	42.01	31.67	65.58	55.58	-23.57	-23.91
2	0.20469	10.16	24.58	20.10	34.74	30.26	63.42	53.42	-28.68	-23.16
3	0.36484	10.18	29.50	21.90	39.68	32.08	58.62	48.62	-18.94	-16.54
4	1.18750	10.23	26.20	19.86	36.43	30.09	56.00	46.00	-19.57	-15.91
5	3.87891	10.35	18.28	10.74	28.63	21.09	56.00	46.00	-27.37	-24.91
6	11.58594	10.50	16.48	9.90	26.98	20.40	60.00	50.00	-33.02	-29.60

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	Channel 1 (921.42MHz)		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15391	10.13	35.18	21.12	45.31	31.25	65.79	55.79	-20.48	-24.54
2	0.19297	10.16	28.46	14.90	38.62	25.06	63.91	53.91	-25.29	-28.85
3	0.34922	10.18	31.38	24.22	41.56	34.40	58.98	48.98	-17.42	-14.58
4	1.21484	10.23	22.18	15.94	32.41	26.17	56.00	46.00	-23.59	-19.83
5	3.92578	10.39	16.70	8.24	27.09	18.63	56.00	46.00	-28.91	-27.37
6	11.81250	10.59	16.20	11.90	26.79	22.49	60.00	50.00	-33.21	-27.51

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	Channel 2 (921.40MHz)		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.12	36.42	22.14	46.54	32.26	66.00	56.00	-19.46	-23.74
2	0.18906	10.15	28.28	16.86	38.43	27.01	64.08	54.08	-25.65	-27.07
3	0.35313	10.18	29.42	22.00	39.60	32.18	58.89	48.89	-19.29	-16.71
4	1.15234	10.23	26.76	19.56	36.99	29.79	56.00	46.00	-19.01	-16.21
5	3.91797	10.35	19.56	11.32	29.91	21.67	56.00	46.00	-26.09	-24.33
6	12.09375	10.51	17.56	11.32	28.07	21.83	60.00	50.00	-31.93	-28.17

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	Channel 2 (921.40MHz)		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.13	35.30	21.40	45.43	31.53	66.00	56.00	-20.57	-24.47
2	0.18125	10.15	30.14	16.30	40.29	26.45	64.43	54.43	-24.14	-27.98
3	0.35703	10.18	32.20	24.40	42.38	34.58	58.80	48.80	-16.42	-14.22
4	1.25781	10.23	21.78	15.38	32.01	25.61	56.00	46.00	-23.99	-20.39
5	4.07813	10.39	16.24	6.58	26.63	16.97	56.00	46.00	-29.37	-29.03
6	11.35547	10.58	12.96	4.66	23.54	15.24	60.00	50.00	-36.46	-34.76

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	Channel 3 (919.80MHz)		

No	Freq.	Corr. Factor	Reading Value		Emission Level		Limit		Margin	
	[MHz]		[dB (uV)]		[dB (uV)]		[dB (uV)]		(dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.12	38.06	23.12	48.18	33.24	66.00	56.00	-17.82	-22.76
2	0.17734	10.14	32.42	18.48	42.56	28.62	64.61	54.61	-22.05	-25.99
3	0.36094	10.18	32.36	25.64	42.54	35.82	58.71	48.71	-16.17	-12.89
4	1.19141	10.23	27.60	21.20	37.83	31.43	56.00	46.00	-18.17	-14.57
5	4.07031	10.35	18.34	10.90	28.69	21.25	56.00	46.00	-27.31	-24.75
6	11.68359	10.50	18.02	10.48	28.52	20.98	60.00	50.00	-31.48	-29.02

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	Channel 3 (919.80MHz)		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	10.13	35.02	21.46	45.15	31.59	66.00	56.00	-20.85	-24.41
2	0.17344	10.14	31.00	17.72	41.14	27.86	64.79	54.79	-23.65	-26.93
3	0.34922	10.18	32.32	24.84	42.50	35.02	58.98	48.98	-16.48	-13.96
4	1.17578	10.23	21.14	14.40	31.37	24.63	56.00	46.00	-24.63	-21.37
5	4.12109	10.39	18.38	6.76	28.77	17.15	56.00	46.00	-27.23	-28.85
6	11.84375	10.59	14.76	7.76	25.35	18.35	60.00	50.00	-34.65	-31.65

Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 Band Edge Measurement

4.3.1 Limits of Band Edge Measurement

The field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following

Fundamental Frequency	Field Strength of Fundamental (millivolts/meter)	Field Strength of Harmonics (microvolts/meter)
902 ~ 928 MHz	50	500
2400 ~ 2483.5 MHz	50	500
5725 ~ 5875 MHz	50	500
24 ~ 24.25 GHz	250	2500

Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits as below table, whichever is the lesser attenuation

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	$2400/F(\text{kHz})$	300
0.490 ~ 1.705	$24000/F(\text{kHz})$	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = $20 \log$ Emission level ($\mu\text{V}/\text{m}$).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

4.3.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESIB7	100187	Apr. 18, 2016	Apr. 17, 2017
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100041	Sep. 02, 2015	Sep. 01, 2016
BILOG Antenna SCHWARZBECK	VULB9168	9168-171	Jan. 07, 2016	Jan. 06, 2017
HORN Antenna SCHWARZBECK	9120D	209	Jan. 20, 2016	Jan. 19, 2017
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Jan. 18, 2016	Jan. 17, 2017
Preamplifier Agilent	8447D	2944A10738	Oct. 18, 2015	Oct. 17, 2016
Preamplifier Agilent	8449B	3008A01964	Aug. 22, 2015	Aug. 21, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH3-03 (214378)	Aug. 22, 2015	Aug. 21, 2016
RF signal cable HUBER+SUHNER	SUCOFLEX 106	Cable-CH3-03 (309224+12738)	Aug. 22, 2015	Aug. 21, 2016
Software BV ADT	ADT_Radiated_ V7.6.15.9.4	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	013303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021702	NA	NA
Turn Table BV ADT	TT100	TT93021702	NA	NA
Turn Table Controller BV ADT	SC100	SC93021702	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 3.
 3. The horn antenna and preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
 4. The FCC Site Registration No. is 988962.
 5. The IC Site Registration No. is IC 7450F-3.

4.3.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.


Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz(Duty cycle > 98%) for Average detection (AV) at frequency above 1GHz.
4. All modes of operation were investigated and the worst-case emissions are reported.

4.3.4 Deviation from Test Standard

No deviation.

4.3.5 Test Set Up



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.3.6 EUT Operating Conditions

Same as 4.1.6.


4.3.7 Test Results

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1 (921.42MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	914.82	33.72 PK	41.4	-7.68	1.39 H	194	5.32	28.4
2	*921.42	91.40 PK			-	-	62.90	28.5
3	928.02	33.79 PK	41.4	-7.61	1.39 H	194	5.09	28.7

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency




Date: 3.JUN.2016 14:31:01

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 1 (921.42MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	916.62	31.72 PK	35.2	-3.48	1.55 V	156	3.32	28.4
2	*921.42	85.15 PK			-	-	56.65	28.5
3	926.02	31.49 PK	35.2	-3.71	1.55 V	156	2.89	28.6

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency




Date: 3.JUN.2016 14:33:14

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 2 (921.40MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	917.00	36.81 PK	41.8	-4.99	1.45 H	191	8.41	28.4
2	*921.40	91.82 PK			-	-	63.32	28.5
3	926.40	33.88 PK	41.8	-7.92	1.45 H	191	5.28	28.6

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency




Date: 3.JUN.2016 14:17:40

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 2 (921.40MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	908.60	30.22 PK	34.9	-4.68	1.50 V	157	1.92	28.3
2	*921.40	84.92 PK			-	-	56.42	28.5
3	967.40	31.52 PK	34.9	-3.38	1.50 V	157	2.62	28.9

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency




Date: 3.JUN.2016 14:23:44

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3 (919.80MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	907.80	29.55 PK	41.2	-11.65	1.38 H	194	1.25	28.3
2	*919.80	91.22 PK			-	-	62.72	28.5
3	923.80	30.65 PK	41.2	-10.55	1.38 H	194	2.15	28.5

Remarks:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “*”: Fundamental frequency




Date: 3.JUN.2016 14:46:27

EUT TEST CONDITION		MEASUREMENT DETAIL	
CHANNEL	Channel 3 (919.80MHz)	FREQUENCY RANGE	Below 1000MHz
INPUT POWER	120Vac, 60 Hz (System)	DETECTOR FUNCTION	Peak (PK)
ENVIRONMENTAL CONDITIONS	16deg. C, 70%RH	TESTED BY	Nick Hsu

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	910.80	29.94 PK	35.2	-5.26	1.51 V	159	1.64	28.3
2	*919.80	85.18 PK			-	-	56.68	28.5
3	949.40	30.72 PK	35.2	-4.48	1.51 V	159	2.02	28.7

- REMARKS: 1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Pre-Amplifier Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. “ * ” : Fundamental frequency



Date: 3.JUN.2016 14:51:02

5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Linko EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---