



RF MEASUREMENT REPORT

FCC ID: DD4ADTQG57

Applicant: Shure Incorporated

Product: Wireless Quad Transmitter

Model No.: ADTQ G57, ADTQ DC G57

Trade Mark: 

FCC Classification: Part 15 Wireless Microphone (DWM)

FCC Rule Part(s): Part 15 Subpart C (Section 15.236)

Application Type: Class II Permissive Change

Result: Complies

Received Date: 2025-05-16

Test Date: 2025-05-24 ~ 2025-06-16

Reviewed By:

Jame Yuan

Approved By:

Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.



Revision History

Report No.	Version	Description	Issue Date	Note
R25S1018044-U202	V01	Initial Report	2025-06-23	Valid

Note: This product has obtained FCC approval (FCC ID: DD4ADTQG57), original RF report no. is 2406RSU021-U2. The product has been modified via software to include additional test modes.

CONTENTS

Description	Page
1. General Information	5
1.1. Applicant	5
1.2. Manufacturer	5
1.3. Testing Facility	5
1.4. Product Information.....	6
1.5. Radio Specification under Test	6
1.6. Working Frequencies	7
1.7. Antenna Details.....	7
2. Test Configuration	8
2.1. Test Mode	8
2.2. Test Software	8
2.3. Applied Standards.....	8
2.4. Test Environment Condition.....	8
3. Measuring Instrument	9
4. Decision Rules and Measurement Uncertainty.....	10
4.1. Decision Rules	10
4.2. Measurement Uncertainty.....	10
5. Test Result	11
5.1. Summary	11
5.2. 99% Occupied Bandwidth Measurement.....	12
5.2.1. Test Limit	12
5.2.2. Test Procedure	12
5.2.3. Test Setting	12
5.2.4. Test Setup	12
5.2.5. Test Result	12
5.3. Emission Mask	13
5.3.1. Test Limit	13
5.3.2. Test Procedure	15
5.3.3. Test Setting	15
5.3.4. Test Setup	15
5.3.5. Test Result	15
5.4. Output Power Measurement	16
5.4.1. Test Limit	16
5.4.2. Test Procedure	16

5.4.3.	Test Setting	16
5.4.4.	Test Setup	16
5.4.5.	Test Result	16
5.5.	Radiated Spurious Emission Measurement.....	17
5.5.1.	Test Limit	17
5.5.2.	Test Procedure	18
5.5.3.	Test Setting	18
5.5.4.	Test Setup	19
5.5.5.	Test Result	20
Appendix A	- Test Result.....	21
A.1	99% Occupied Bandwidth Test Result	21
A.2	Emission Mask Test Result	22
A.3	Output Power Test Result	26
A.4	Radiated Spurious Emission Test Result	27
Appendix B	- Test Setup Photograph	28
Appendix C	- EUT Photograph	29

1. General Information

1.1. Applicant

Shure Incorporated

5800 West Touhy Avenue, Niles, IL 60714-4608, USA

1.2. Manufacturer

Shure Incorporated

5800 West Touhy Avenue, Niles, IL 60714-4608, USA

1.3. Testing Facility

☒	Test Site – MRT Suzhou Laboratory				
	Laboratory Location (Suzhou - Wuzhong)				
	D8 Building, No.2 Tian’edang Rd., Wuzhong Economic Development Zone, Suzhou, China				
	Laboratory Location (Suzhou - SIP)				
	4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China				
	Laboratory Location (Suzhou - Wujiang)				
	Building 1, No.1 Xingdong Road, Wujiang, Suzhou, Jiangsu, People’s Republic of China				
☒	Laboratory Accreditations				
	A2LA: 3628.01		CNAS: L10551		
	FCC: CN1166		ISED: CN0001		
	VCCI:	☐ R-20025	☐ G-20034	☐ C-20020	☐ T-20020
		☐ R-20141	☐ G-20134	☐ C-20103	☐ T-20104
☐	Test Site – MRT Shenzhen Laboratory				
	Laboratory Location (Shenzhen)				
	1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China				
	Laboratory Accreditations				
	A2LA: 3628.02		CNAS: L10551		
FCC: CN1284		ISED: CN0105			
☐	Test Site – MRT Taiwan Laboratory				
	Laboratory Location (Taiwan)				
	No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)				
	Laboratory Accreditations				
	TAF: 3261		FCC: 291082, TW3261		
		ISED: TW3261			

1.4. Product Information

Product Name	Wireless Quad Transmitter
Model No.	ADTQ G57, ADTQ DC G57
Serial No.	2DE31788237
Radio Specification	UHF Microphone Transmitter
Antenna Information	Refer to section 1.7
Operating Temperature	-18 ~ 50 °C
Network Interface	10/100/1000 Mbps, Dante Digital Audio
Power Type	ADTQ DC: AC Power Input (100~240V AC) & DC Power Input (12~48V) ADTQ: AC Power Output (100~240V AC)
Accessory	
8 Port Antenna Combiner	Model: AD8C, AD8C DC AC Ver.: 100-240V~, 50/60Hz, 0.76A max (5.76A max outlet loaded), DC Ver.: 12-48V DC, 4A max
Note 1: The information of the EUT (Equipment Under Test) was provided by the manufacturer. The accuracy, completeness, and validity of the information are solely the responsibility of the manufacturer. Note 2: ADTQ G57 and ADTQ DC G57 are completely same except power supply difference, ADTQ G57 supports AC power supply, while ADTQ DC G57 supports both AC and DC power supply. Note 3: AD8C and AD8C DC are completely same except power supply difference, AD8C supports AC power supply, while AD8C DC supports both AC and DC power supply.	

1.5. Radio Specification under Test

Transmission Mode	4-channel Wideband (WMAS)
Frequency Range	470 ~ 608 MHz
Declared Power Level	Low & Normal & High
Type of Modulation	4-channel Wideband: OFDM
Declared Occupied Bandwidth	4-channel Wideband (WMAS): 850 kHz
Channel Spacing	25 kHz
RF Connector Type	BNC

1.6. Working Frequencies

Bottom Channel (MHz)	Middle Channel (MHz)	Top Channel (MHz)
4-channel wideband		
470.400	539.000	607.600

1.7. Antenna Details

Antenna Type	Frequency Band (MHz)	Manufacturer	Peak Gain (dBi)
Dipole	470 ~ 608	Shure	1.10

2. Test Configuration

2.1. Test Mode

Mode 1: Transmit at G57 Band by 4-Channel wideband, spatial diversity, 2 frequencies (Power Level = 40mW)
Mode 2: Transmit at G57 Band by 4-Channel wideband, spatial diversity, 2 frequencies, combined
Mode 3: Transmit at G57 Band by 4-Channel wideband, 2 frequencies
Mode 4: Transmit at G57 Band by 4-Channel wideband, 2 frequencies, combined
Note: These newly added test modes 2 & 3 & 4 are the same type as modes 15 & 10 & 16 in the original report, respectively. Therefore, no additional testing was conducted.

2.2. Test Software

Power level and transmit frequency can be selected using the front panel controls.

2.3. Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC Part 15.236
- KDB 206256 D01v03
- ANSI C63.10-2013
- ETSI EN 300 422 - 1 V 2.2.1

2.4. Test Environment Condition

Ambient Temperature	15 ~ 35°C
Relative Humidity	20 ~ 75%RH

3. Measuring Instrument

Instrument	Manufacturer	Model No.	Asset No.	Cali. Interval	Cali. Due Date	Test Site
Thermohygrometer	testo	608-H1	MRTSUE06402	1 year	2026-04-24	WZ-SR5
Shielding Room	HUAMING	WZ-SR5	MRTSUE06442	N/A	N/A	WZ-SR5
Signal Analyzer	Keysight	N9010B	MRTSUE06457	1 year	2026-04-26	WZ-SR5
Signal Analyzer	Keysight	N9010B	MRTSUE06558	1 year	2026-05-17	WZ-SR5
USB Power Sensor	Keysight	U2021XA	MRTSUE06446	1 year	2026-04-26	WZ-SR5
Attenuator	MVE	MVE2213	MRTSUE11075	1 year	2025-06-03	WZ-SR5
				1 year	2026-06-02	WZ-SR5
Attenuator	MVE	MVE2213	MRTSUE11076	1 year	2025-06-03	WZ-SR5
				1 year	2026-06-02	WZ-SR5
Attenuator	MVE	MVE2213	MRTSUE11077	1 year	2025-06-03	WZ-SR5
				1 year	2026-06-02	WZ-SR5
Attenuator	MVE	MVE2213	MRTSUE11078	1 year	2025-06-03	WZ-SR5
				1 year	2026-06-02	WZ-SR5
Cable	UCwave	UCE500	24060015	Note	Note	WZ-SR5
TRILOG Antenna	Schwarzbeck	VULB 9162	MRTSUE06022	1 year	2026-03-22	WZ-AC2
EMI Test Receiver	Agilent	N9038A	MRTSUE06125	1 year	2026-04-26	WZ-AC2
Horn Antenna	Schwarzbeck	BBHA 9120D	MRTSUE06171	1 year	2025-09-23	WZ-AC2
Preamplifier	Schwarzbeck	BBV 9718	MRTSUE06176	1 year	2026-03-18	WZ-AC2
Anechoic Chamber	RIKEN	WZ-AC2	MRTSUE06213	1 year	2026-04-17	WZ-AC2
Thermohygrometer	testo	608-H1	MRTSUE11263	1 year	2025-10-16	WZ-AC2

Note: The loss of the RF cable will be measured before testing.

Software	Version	Function
e3	230711	RE & CE
Controller_MF 7802	1.02	RE Antenna & Turntable
BenchVue Power Meter	2018.1	Power

4. Decision Rules and Measurement Uncertainty

4.1. Decision Rules

The Decision Rule is based on Simple Acceptance in accordance with ISO Guide 98-4: 2012 Clause 8.2.

(Measurement uncertainty is not taken into account when stating conformity with a specified requirement.

4.2. Measurement Uncertainty

Where relevant, the following test uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k = 2$.

Radiated Emission Measurement	
The maximum measurement uncertainty is evaluated as:	
Coaxial:	9kHz~30MHz: 2.35dB
Coplanar:	9kHz~30MHz: 2.37dB
Horizontal:	30MHz~200MHz: 3.47dB
	200MHz~1GHz: 4.17dB
	1GHz~40GHz: 4.97dB
Vertical:	30MHz~200MHz: 4.07dB
	200MHz~1GHz: 5.28dB
	1GHz~40GHz: 4.84dB
Spurious Emissions, Conducted	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$):	
2.5dB	
Output Power	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$):	
1.5dB	
Occupied Bandwidth	
Measuring Uncertainty for a Level of Confidence of 95% ($U=2U_c(y)$):	
3.2%	

5. Test Result

5.1. Summary

FCC Part Section(s)	Test Description	Test Condition	Test Result
15.236(f) (1&2)	99% Occupied Bandwidth	Conducted	Pass
15.236(g) (1&2&3)	Emission Mask		Pass
15.236(d)(1)	RF Output Power		Pass
15.236(g)(4)	Radiated Spurious Emission	Radiated	Pass

Note: The analyzer plots shown in this section were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables and attenuators used as part of the system to connect the EUT to the analyzer at all frequencies of interest.

5.2. 99% Occupied Bandwidth Measurement

5.2.1. Test Limit

One or more adjacent 25 kHz segments within the assignable frequencies may be combined to form a channel whose maximum bandwidth shall not exceed 200 kHz. The operating bandwidth shall not exceed 200 kHz.

A wireless multichannel audio system may have an operating bandwidth not exceeding 6 megahertz and must have a mode of operation in which it is capable of operating with at least three audio channels per megahertz. For wireless multichannel audio systems operating in the TV bands (channels 2-36), the 6 megahertz (or less) channel must fall entirely within a single TV channel.


5.2.2. Test Procedure

ANSI C63.10-2013 - Section 6.9.3

5.2.3. Test Setting

1. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
2. Set RBW $\geq$ 1% to 5% of the OBW
3. VBW = Approximately three times RBW
4. Detector = Peak
5. Trace mode = Max hold
6. Sweep = Auto couple
7. Allow the trace to stabilize
8. Use the 99% power bandwidth function of the instrument and report the measured bandwidth.

5.2.4. Test Setup



5.2.5. Test Result

Refer to Appendix A.1.

5.3. Emission Mask

5.3.1. Test Limit

(1) Analog systems. Emissions within the band from $2.5 \times B$ below to $2.5 \times B$ above the carrier frequency, where B is the channel bandwidth, shall comply with the emission mask in Figure 1 of section 4.2.4.2.2 of ETSI EN 300 422-1 V2.2.1 (2021-11) (incorporated by reference, see § 15.38).

(2) Digital systems. Emissions within the band from $2.5 \times B$ below to $2.5 \times B$ above the carrier frequency, where B is the channel bandwidth, shall comply with the emission mask in Figure 2 of section 4.2.4.2.2 of ETSI EN 300 422-1 V2.2.1 (2021-11) (incorporated by reference, see § 15.38).

(3) Wireless Multichannel Audio Systems. Emissions within the band from $2.5 \times B$ below to $2.5 \times B$ above the carrier frequency, where B is the channel bandwidth, shall comply with the emission mask in Figure 3 of section 4.2.4.2.2 of ETSI EN 300 422-1 V2.2.1 (2021-11), (incorporated by reference, see § 15.38).

The mean Power Density, measured with 1 kHz measurement bandwidth and RMS detector, of the transmitter unwanted emissions shall not exceed the limits of the masks provided in figure 1 for equipment employing analogue modulation and figure 2 for equipment employing digital modulation, but excluding WMAS. B is the Declared Channel Bandwidth.




Figure 1: Transmit spectral power mask for equipment employing analogue modulation, RBW = 1 kHz



Figure 2: Transmit spectral power mask for equipment employing digital modulation, except WMAS, RBW = 1 kHz

The limits in figure 3 are applicable for WMAS, where B is the Declared Channel Bandwidth.

The mean Power Density, measured with 100 kHz measurement bandwidth and PEAK detector, of the transmitter unwanted emissions shall not exceed the limits of the mask provided in figure 3.




Figure 3: Transmit spectral power mask for WMAS, RBW = 100 kHz

The limits in figure 3 are provided with RBW = 100 kHz. The relevant measurements can also be performed with other RBW for certain ranges of B, accounting that the relevant limit given under RBW = 100 kHz needs to be converted appropriately by adding $c = 10 \times \log_{10} (\text{RBW}/100 \text{ kHz})$ for correction.

Correction Factor for different B and applicable RBW

B	RBW, VBW	c = correction factor
$B < 2 \text{ MHz}$	10 kHz	-10dB
$2 \text{ MHz} \leq B < 5 \text{ MHz}$	25 kHz	-7dB
$5 \text{ Hz} \leq B \leq 20\text{MHz}$	100 kHz	0dB

5.3.2. Test Procedure


EN 300 422-1 V2.2.1 clause 5.4.3.2.

5.3.3. Test Setting

The EUT was powered up and the transmit frequency & power output of the EUT were selected.

The spectrum analyzer center frequency is set to the nominal EUT channel frequency.

5.3.4. Test Setup



5.3.5. Test Result

Refer to Appendix A.2.

5.4. Output Power Measurement

5.4.1. Test Limit

1) In the bands allocated and assigned for broadcast television:

(i) Wireless microphones: 50 mW EIRP.

(ii) Wireless multichannel audio systems with a bandwidth up to 1 MHz: 50 mW EIRP.

(iii) Wireless multichannel audio systems with a bandwidth greater than 1 MHz: 100 mW EIRP.

(2) In the 600 MHz guard band and the 600 MHz duplex gap: 20 mW EIRP.


5.4.2. Test Procedure

ANSI C63.10 - 2013 - Section 11.9.2.3.2

5.4.3. Test Setting

Average power measurements were performed only when the EUT was transmitting at its maximum power control level using a broadband power meter with a pulse sensor. The power meter implemented triggering and gating capabilities which were set up such that power measurements were recorded only during the ON time of the transmitter.

5.4.4. Test Setup



5.4.5. Test Result

Refer to Appendix A.3.

5.5. Radiated Spurious Emission Measurement

5.5.1. Test Limit

Spurious emission limits. Emissions outside of the emission masks listed in paragraphs (g)(1) through (g)(3) shall comply with the limits specified in section 4.2.4.1.2 of ETSI EN 300 422-1 V2.2.1 (2021-11), (incorporated by reference, see § 15.38).

The level of transmitter unwanted emissions in the spurious domain shall not exceed the limits given in table Transmitter unwanted emission limits

Frequency Range	Maximum power	RBW
9kHz – 150kHz	-36dBm	1kHz
150kHz – 30MHz	-36dBm	10kHz
30MHz – 1GHz	-36dBm	$F_c + 2.5B \leq f \leq F_c + 4B$: 1kHz $F_c + 4B < f \leq F_c + 10B$: 10kHz $f > F_c + 10B$: 100kHz $f < F_c - 10B$: 100kHz $F_c - 10B \leq f < F_c - 4B$: 10kHz $F_c - 4B \leq f \leq F_c - 2.5B$: 1kHz
Except:		
47MHz to 74MHz 87.5MHz to 118MHz	-54dBm	100kHz
174MHz to 230MHz 470MHz to 862MHz	-36dBm	$F_c + 2.5B \leq f \leq F_c + 4B$: 1kHz $F_c + 4B < f \leq F_c + 10B$: 10kHz $f > F_c + 10B$: 100kHz $f < F_c - 10B$: 100kHz $F_c - 10B \leq f < F_c - 4B$: 10kHz $F_c - 4B \leq f \leq F_c - 2.5B$: 1kHz
$1\text{GHz} < f \leq F_{\text{upper}}$	-30dBm	$F_c + 2.5B \leq f \leq F_c + 10B$: 30kHz $F_c + 10B < f \leq F_c + 12B$: 300kHz $f > F_c + 12B$: 1MHz $f < F_c - 12B$: 1MHz $F_c - 12B \leq f < F_c - 10B$: 300kHz $F_c - 10B \leq f \leq F_c - 2.5B$: 30kHz
With B being the Declared Channel Bandwidth. F_{upper} is defined in table 5.		

Table 5: Frequency range for measurement of unwanted emissions

Applicable fundamental frequency range	Frequency range for measurements	
	Lower frequency	Upper frequency
9 kHz - 100 MHz	9 kHz	1GHz
100 MHz - 300 MHz	9 kHz	10th harmonic of the operating frequency
300 MHz - 600 MHz	30MHz	3GHz
600 MHz - 3 GHz	30MHz	5th harmonic of the operating frequency

5.5.2. Test Procedure

ETSI EN 300 422-1 V2.2.1 clause 5.4.4

5.5.3. Test Setting

Table 1 - RBW as a function of frequency

Frequency	RBW
30 ~ 1000 MHz	100 kHz
1000 ~ 7000 MHz	1 MHz

Emissions shall be investigated up to the 10th harmonic of the fundamental.


All the emissions shall be demonstrated using a QP detector below 1 GHz and an RMS Average detector above 1 GHz.

All significant broadband and narrowband signals found in the preliminary sweeps were measured using a peak detector at a test distance of 3 meters.


at each frequency at which a component is detected, the sample shall be rotated to obtain maximum response and the effective radiated power of that component determined by a substitution measurement.

5.5.4. Test Setup

Below 1GHz Test Setup:



Above 1GHz Test Setup:



5.5.5. Test Result


Refer to Appendix A.4.

Appendix A – Test Result

A.1 99% Occupied Bandwidth Test Result

Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2025-06-06	Test Mode	Mode 1

Frequency (MHz)	99% Bandwidth (kHz)	Limit (kHz)	Result
470.400	595.40	< 6000	Pass
539.000	595.95	< 6000	Pass
607.600	596.44	< 6000	Pass




A.2 Emission Mask Test Result


Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2025-06-15	Test Mode	Mode 1

Port A


Channel 470.400MHz



Channel 539.000MHz





Channel 607.600MHz




Port B



Channel 470.400MHz



Channel 539.000MHz





Channel 607.600MHz





Port C



Channel 470.400MHz



Channel 539.000MHz





Channel 607.600MHz





Port D



Channel 470.400MHz



Channel 539.000MHz



Channel 607.600MHz



A.3 Output Power Test Result

Test Site	WZ-SR5	Test Engineer	Lynn Yang
Test Date	2025-06-09 ~ 2025-06-16	Test Mode	Mode 1

Frequency (MHz)	Conducted Output Power (dBm)				Total Conducted Output Power (dBm)	Antenna Gain (dBi)	Total EIRP (dBm)	Limit (dBm)	Test Result
	Port A	Port B	Port C	Port D					
40mW Power Level									
470.400	9.51	8.51	10.52	10.59	15.88	1.10	16.98	≤ 16.99	Pass
539.000	8.30	7.35	9.33	8.81	14.53	1.10	15.63	≤ 16.99	Pass
607.600	9.13	8.87	9.16	9.46	15.18	1.10	16.28	≤ 16.99	Pass

Note 1: Limit = $10 \cdot \log(50\text{mW}) = 16.99 \text{ dBm}$.

Note 2: Total Conducted Output Power (dBm) = $10 \cdot \log(10^{(\text{Port A}/10)} + 10^{(\text{Port B}/10)} + 10^{(\text{Port C}/10)} + 10^{(\text{Port D}/10)})$ (dBm).

Note 3: Total EIRP (dBm) = Total Conducted Output Power dBm + Antenna Gain (dBi).

A.4 Radiated Spurious Emission Test Result

Test Site	WZ-AC2	Test Engineer	Lucas Wang & Dick Shen
Test Date	2025-05-24 ~ 2025-06-13	Test Mode	Mode 1

Test Channel (MHz)	Frequency (MHz)	Reading Level (dBm)	Substitution Factor (dB)	Measure Level (dBm)	Limit (dBm)	Margin (dB)	Detector	Polarization
470.400 + 471.400	485.420	-88.1	30.5	-57.6	-54.0	-3.6	QP	Horizontal
	528.970	-92.4	31.3	-61.1	-54.0	-7.1	QP	Horizontal
	507.050	-90.5	33.3	-57.2	-54.0	-3.2	QP	Vertical
	584.160	-93.6	34.4	-59.2	-54.0	-5.2	QP	Vertical
	1414.000	-64.2	8.0	-56.2	-30.0	-26.2	Peak	Horizontal
	6904.000	-71.8	20.9	-50.9	-30.0	-20.9	Peak	Horizontal
	1414.000	-65.8	7.9	-57.9	-30.0	-27.9	Peak	Vertical
	6661.000	-72.8	20.1	-52.7	-30.0	-22.7	Peak	Vertical
539.000 + 540.000	476.780	-88.5	30.5	-58.0	-54.0	-4.0	QP	Horizontal
	497.440	-89.6	31.0	-58.6	-54.0	-4.6	QP	Horizontal
	479.980	-88.6	33.3	-55.3	-54.0	-1.3	QP	Vertical
	520.530	-90.9	33.4	-57.5	-54.0	-3.5	QP	Vertical
	1080.400	-63.5	6.5	-57.0	-30.0	-27.0	Peak	Horizontal
	5176.600	-69.8	15.5	-54.3	-30.0	-24.3	Peak	Horizontal
	1633.000	-67.1	8.2	-58.9	-30.0	-28.9	Peak	Vertical
	5119.600	-70.2	15.0	-55.2	-30.0	-25.2	Peak	Vertical
607.600 + 606.600	481.630	-87.5	30.5	-57.0	-54.0	-3.0	QP	Horizontal
	528.190	-92.1	31.3	-60.8	-54.0	-6.8	QP	Horizontal
	517.230	-90.3	33.3	-57.0	-54.0	-3.0	QP	Vertical
	564.470	-93.0	34.2	-58.8	-54.0	-4.8	QP	Vertical
	1512.400	-68.3	8.8	-59.5	-30.0	-29.5	Peak	Horizontal
	5935.600	-70.3	17.4	-52.9	-30.0	-22.9	Peak	Horizontal
	1660.600	-68.8	8.9	-59.9	-30.0	-29.9	Peak	Vertical
	6526.000	-72.3	19.1	-53.2	-30.0	-23.2	Peak	Vertical

Note 1: Measure Level (dBm) = Reading Level (dBm) + Substitution Factor (dB)

Note 2: Substitution Factor (dB) = Cable Loss (dB) + Space Attenuation (dB) - Antenna Gain (dBi) - 2.15 (dB)

Note 3: RMS measurement was not performed when peak measure level was lower than the RMS limit.

Appendix B - Test Setup Photograph

Refer to "R25S1018044-UT" file.

Appendix C - EUT Photograph

Refer to "R25S1018044-UE" file.

_____ The End _____