

WT9650XE w/LI SHIN POWER ADAPTER MODEL: 0219B1280

WYSE TECHNOLOGY

25 Mar 2003 16:23:00

=====

2. CONDUCTED no Preselector

2.3 EN 55022 (1995)

Class B

LINE 1 (HOT SIDE)

=====

20 highest Avg Peaks above -15 dB of Limit Line #2
peak criteria = 6 dB

PEAK#	FREQ (MHz)	(dBUV)	DELTA
1	1.796	39.4	-6.6
2	4.3	39.4	-6.6
3	1.73	39	-7.0
4	4.369	39	-7.0
5	1.863	38.9	-7.1
6	2.315	38.9	-7.1
7	1.676	38.5	-7.5
8	2.243	38.4	-7.6
9	4.1	38.4	-7.6
10	4.232	38.4	-7.6
11	2.441	38.3	-7.7
12	4.036	38.3	-7.7
13	4.166	38.3	-7.7
14	2.39	38.2	-7.8
15	4.558	38.1	-7.9
16	4.755	38.1	-7.9
17	1.923	38	-8.0
18	1.607	37.8	-8.2
19	4.68	37.5	-8.5
20	4.935	37.2	-8.8

WT9650XE W/LI SHIN POWER ADAPTER MODEL: 0219B1280

WYSE TECHNOLOGY

25 Mar 2003 16:51:48

=====
2. CONDUCTED no Preselector

2.3 EN 55022 (1995)

Class B

LINE 2 (NEUTRAL SIDE)

=====
20 highest Avg Peaks above -15 dB of Limit Line #2

peak criteria = 6 dB

PEAK#	FREQ (MHz)	(dBuV)	DELTA
1	1.796	39.7	-6.3
2	4.3	39.5	-6.5
3	1.739	39.3	-6.7
4	4.68	39.1	-6.9
5	1.863	38.9	-7.1
6	4.346	38.8	-7.2
7	4.1	38.6	-7.4
8	1.667	38.5	-7.5
9	1.934	38.5	-7.5
10	4.232	38.5	-7.5
11	2.303	38.2	-7.8
12	4.036	38.1	-7.9
13	4.166	38.1	-7.9
14	4.606	38.1	-7.9
15	4.416	38	-8.0
16	2.364	37.8	-8.2
17	3.649	37.7	-8.3
18	1.607	37.4	-8.6
19	3.708	37.3	-8.7
20	2.441	37.1	-8.9

