

## FCC Test Report

**Report No.:** RF150513C20

**FCC ID:** E2K-APL290B7

**Test Model:** APL29-0B7

**Received Date:** May 13, 2015

**Test Date:** May 28 ~ Jun. 02, 2015

**Issued Date:** Jun. 05, 2015

**Applicant:** Dell Inc.

**Address:** One Dell Way, Round Rock, Texas 78682, USA

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch

**Lab Address:** No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan, R.O.C.

**Test Location:** No.19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City 33383, TAIWAN (R.O.C.)



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|                                                            |           |
|------------------------------------------------------------|-----------|
| <b>Release Control Record</b>                              | <b>4</b>  |
| <b>1 Certificate of Conformity</b>                         | <b>5</b>  |
| <b>2 Summary of Test Results</b>                           | <b>6</b>  |
| 2.1 Measurement Uncertainty                                | 6         |
| 2.2 Modification Record                                    | 6         |
| <b>3 General Information</b>                               | <b>7</b>  |
| 3.1 General Description of EUT                             | 7         |
| 3.2 Description of Test Modes                              | 9         |
| 3.2.1 Test Mode Applicability and Tested Channel Detail    | 10        |
| 3.3 Duty Cycle of Test Signal                              | 12        |
| 3.4 Description of Support Units                           | 13        |
| 3.4.1 Configuration of System under Test                   | 13        |
| 3.5 General Description of Applied Standards               | 14        |
| <b>4 Test Types and Results</b>                            | <b>14</b> |
| 4.1 Radiated Emission and Bandedge Measurement             | 15        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement | 15        |
| 4.1.2 Test Instruments                                     | 16        |
| 4.1.3 Test Procedures                                      | 17        |
| 4.1.4 Deviation from Test Standard                         | 17        |
| 4.1.5 Test Set Up                                          | 18        |
| 4.1.6 EUT Operating Conditions                             | 18        |
| 4.1.7 Test Results                                         | 19        |
| 4.2 Conducted Emission Measurement                         | 32        |
| 4.2.1 Limits of Conducted Emission Measurement             | 32        |
| 4.2.2 Test Instruments                                     | 32        |
| 4.2.3 Test Procedures                                      | 33        |
| 4.2.4 Deviation from Test Standard                         | 33        |
| 4.2.5 Test Setup                                           | 33        |
| 4.2.6 EUT Operating Conditions                             | 33        |
| 4.2.7 Test Results                                         | 34        |
| 4.3 6dB Bandwidth Measurement                              | 36        |
| 4.3.1 Limits of 6dB Bandwidth Measurement                  | 36        |
| 4.3.2 Test Setup                                           | 36        |
| 4.3.3 Test Instruments                                     | 36        |
| 4.3.4 Test Procedure                                       | 36        |
| 4.3.5 Deviation from Test Standard                         | 36        |
| 4.3.6 EUT Operating Conditions                             | 36        |
| 4.3.7 Test Result                                          | 37        |
| 4.4 Conducted Output Power Measurement                     | 39        |
| 4.4.1 Limits of Conducted Output Power Measurement         | 39        |
| 4.4.2 Test Setup                                           | 39        |
| 4.4.3 Test Instruments                                     | 39        |
| 4.4.4 Test Procedures                                      | 39        |
| 4.4.5 Deviation from Test Standard                         | 39        |
| 4.4.6 EUT Operating Conditions                             | 39        |
| 4.4.7 Test Results                                         | 40        |
| 4.5 Power Spectral Density Measurement                     | 42        |
| 4.5.1 Limits of Power Spectral Density Measurement         | 42        |
| 4.5.2 Test Setup                                           | 42        |
| 4.5.3 Test Instruments                                     | 42        |
| 4.5.4 Test Procedure                                       | 42        |
| 4.5.5 Deviation from Test Standard                         | 42        |
| 4.5.6 EUT Operating Condition                              | 42        |

|                                                                  |           |
|------------------------------------------------------------------|-----------|
| 4.5.7 Test Results .....                                         | 43        |
| 4.6 Conducted Out of Band Emission Measurement.....              | 46        |
| 4.6.1 Limits of Conducted Out of Band Emission Measurement ..... | 46        |
| 4.6.2 Test Setup.....                                            | 46        |
| 4.6.3 Test Instruments .....                                     | 46        |
| 4.6.4 Test Procedure .....                                       | 46        |
| 4.6.5 Deviation from Test Standard .....                         | 46        |
| 4.6.6 EUT Operating Condition .....                              | 46        |
| 4.6.7 Test Results .....                                         | 47        |
| <b>5 Pictures of Test Arrangements.....</b>                      | <b>59</b> |
| <b>Appendix – Information on the Testing Laboratories .....</b>  | <b>60</b> |



A D T

### Release Control Record

| Issue No.   | Description      | Date Issued   |
|-------------|------------------|---------------|
| RF150513C20 | Original release | Jun. 05, 2015 |

## 1 Certificate of Conformity

**Product:** Wireless Network Security Appliance

**Brand:** DELL, DELL SONICWALL, SONICWALL (Refer to item 3.1 for more details)

**Test Model:** APL29-0B7

**Sample Status:** Engineering sample

**Applicant:** Dell Inc.

**Test Date:** May 28 ~ Jun. 02, 2015

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10: 2009

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Polly Chien, **Date:** Jun. 05, 2015  
Polly Chien / Specialist

**Approved by :** Ken Liu, **Date:** Jun. 05, 2015  
Ken Liu / Senior Manager

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (Section 15.247) |                                              |        |                                                                                               |
|------------------------------------------------|----------------------------------------------|--------|-----------------------------------------------------------------------------------------------|
| FCC Clause                                     | Test Item                                    | Result | Remarks                                                                                       |
| 15.207                                         | AC Power Conducted Emission                  | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -17.34dB at 0.42370MHz            |
| 15.205 /<br>15.209 /<br>15.247(d)              | Radiated Emissions and Band Edge Measurement | Pass   | Meet the requirement of limit.<br>Minimum passing margin is -1.1dB at 2390.00MHz, 2483.50MHz. |
| 15.247(d)                                      | Antenna Port Emission                        | Pass   | Meet the requirement of limit.                                                                |
| 15.247(a)(2)                                   | 6dB bandwidth                                | Pass   | Meet the requirement of limit.                                                                |
| 15.247(b)                                      | Conducted power                              | Pass   | Meet the requirement of limit.                                                                |
| 15.247(e)                                      | Power Spectral Density                       | Pass   | Meet the requirement of limit.                                                                |
| 15.203                                         | Antenna Requirement                          | Pass   | Antenna connector is R-SMA & TNC not a standard connector.                                    |

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                        | Frequency        | Expended Uncertainty (k=2) (±) |
|------------------------------------|------------------|--------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz   | 2.44 dB                        |
| Radiated Emissions up to 1 GHz     | 30MHz ~ 200MHz   | 3.86 dB                        |
|                                    | 200MHz ~ 1000MHz | 3.87 dB                        |
| Radiated Emissions above 1 GHz     | 1GHz ~ 18GHz     | 2.29 dB                        |
|                                    | 18GHz ~ 40GHz    | 2.29 dB                        |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |                                                                                                                          |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------|
| Product               | Wireless Network Security Appliance                                                                                      |
| Brand                 | DELL, DELL SONICWALL, SONICWALL (Refer to note for more details)                                                         |
| Test Model            | APL29-0B7                                                                                                                |
| Status of EUT         | Engineering sample                                                                                                       |
| Power Supply Rating   | 12Vdc (Adapter)                                                                                                          |
| Modulation Type       | CCK, DQPSK, DBPSK for DSSS<br>64QAM, 16QAM, QPSK, BPSK for OFDM                                                          |
| Modulation Technology | DSSS, OFDM                                                                                                               |
| Transfer Rate         | 802.11b:11.0/ 5.5/ 2.0/ 1.0Mbps<br>802.11g: 54.0/ 48.0/ 36.0/ 24.0/ 18.0/ 12.0/ 9.0/ 6.0Mbps<br>802.11n: up to 300.0Mbps |
| Operating Frequency   | 2412 ~ 2462MHz                                                                                                           |
| Number of Channel     | 802.11b, 802.11g, 802.11n (HT20): 11<br>802.11n (HT40): 7                                                                |
| Output Power          | 902.894mW                                                                                                                |
| Antenna Type          | Refer to Note                                                                                                            |
| Antenna Connector     | Refer to Note                                                                                                            |
| Accessory Device      | Adapter                                                                                                                  |
| Data Cable Supplied   | 1.8m non-shielded RJ45 cable without core                                                                                |

Note:

1. The following brands are are for marketing purpose.

| Brand                               | Model     | Difference             |
|-------------------------------------|-----------|------------------------|
| SONICWALL<br>DELL SONICWALL<br>DELL | APL29-0B7 | For marketing purpose. |

2. The EUT incorporates a MIMO function. Physically, the EUT provides 3 completed transmitters and 3 receivers.

| Modulation Mode | TX Function |
|-----------------|-------------|
| 802.11b         | 3TX         |
| 802.11g         | 3TX         |
| 802.11n (HT20)  | 3TX         |
| 802.11n (HT40)  | 3TX         |

3. The following antennas were provided to the EUT.

| No. | Type   | Gain(dBi)   |           | Connector |
|-----|--------|-------------|-----------|-----------|
|     |        | 2.4GHz Band | 5GHz Band |           |
| 1   | DIPOLE | 2.5         | 2.5       | TNC       |
| 2   | DIPOLE | 2.5         | 2.5       | TNC       |
| 3   | DIPOLE | 3           | 3         | R-SMA     |

4. The EUT consumes power from the following adapters.

| Adapter 1    |                                                                                                      |
|--------------|------------------------------------------------------------------------------------------------------|
| Brand        | AMIGO                                                                                                |
| Model        | AMS118-1203000F2                                                                                     |
| Input Power  | 100-240Vac, 50/60Hz, 1.0A Max                                                                        |
| Output Power | 12Vdc, 3.0A                                                                                          |
| Power Line   | AC 1.75m non-shielded power line without core<br>DC 1.5m power cable with 1 core attached on adapter |

| Adapter 2    |                                                                                                       |
|--------------|-------------------------------------------------------------------------------------------------------|
| Brand        | Sunny COMPUTER TECHNOLOGY CO.,LTD.                                                                    |
| Model        | SYS1546-3612-T3                                                                                       |
| Input Power  | 100-240Vac, 50-60Hz, 1.5A Max                                                                         |
| Output Power | 12Vdc, 3.0A, 36W MAX                                                                                  |
| Power Line   | AC 1.75m non-shielded power line without core<br>DC 1.85m power cable with 1 core attached on adapter |

\*After pre-tested two of adapters found adapter 1 was the worst case, therefore chosen for final tests and presented in the test report.

### 3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 7       | 2442MHz   |
| 2       | 2417MHz   | 8       | 2447MHz   |
| 3       | 2422MHz   | 9       | 2452MHz   |
| 4       | 2427MHz   | 10      | 2457MHz   |
| 5       | 2432MHz   | 11      | 2462MHz   |
| 6       | 2437MHz   |         |           |

7 channels are provided for 802.11n (HT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 3       | 2422MHz   | 7       | 2442MHz   |
| 4       | 2427MHz   | 8       | 2447MHz   |
| 5       | 2432MHz   | 9       | 2452MHz   |
| 6       | 2437MHz   |         |           |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT CONFIGURE MODE | APPLICABLE TO |       |     |      | DESCRIPTION |
|--------------------|---------------|-------|-----|------|-------------|
|                    | RE≥1G         | RE<1G | PLC | APCM |             |
| -                  | √             | √     | √   | √    | -           |

Where **RE≥1G**: Radiated Emission above 1GHz & Bandedge Measurement  
**RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission  
**APCM**: Antenna Port Conducted Measurement

**NOTE:** The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on **Y-plane**.

#### Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11b        | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1.0              |
| -                  | 802.11g        | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.0              |
| -                  | 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 7.2              |
| -                  | 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 15.0             |

#### Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11n (HT20) | 1 to 11           | 6              | OFDM                  | BPSK            | 7.2              |

#### Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11n (HT20) | 1 to 11           | 6              | OFDM                  | BPSK            | 7.2              |

### **Antenna Port Conducted Measurement:**

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| -                  | 802.11b        | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1.0              |
| -                  | 802.11g        | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.0              |
| -                  | 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 7.2              |
| -                  | 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 15.0             |

### **Test Condition:**

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | INPUT POWER  | TESTED BY   |
|---------------|--------------------------|--------------|-------------|
| RE $\geq$ 1G  | 22deg. C, 67%RH          | 120Vac, 60Hz | Jones Chang |
| RE<1G         | 22deg. C, 67%RH          | 120Vac, 60Hz | Jones Chang |
| PLC           | 20deg. C, 70%RH          | 120Vac, 60Hz | Jones Chang |
| APCM          | 25deg. C, 60%RH          | 120Vac, 60Hz | Antony Lee  |

### 3.3 Duty Cycle of Test Signal

**802.11b:** Duty cycle of test signal is > 98 %, duty factor is not required.


Duty cycle of test signal is < 98%, duty factor shall be considered.

**802.11g:** Duty cycle =  $2.020/2.115 = 0.955$ , Duty factor =  $10 * \log(1/0.955) = 0.20$


**802.11n (HT20):** Duty cycle =  $1.888/2.020 = 0.935$ , Duty factor =  $10 * \log(1/0.935) = 0.29$

**802.11n (HT40):** Duty cycle =  $0.924/0.997 = 0.927$ , Duty factor =  $10 * \log(1/0.927) = 0.33$


802.11b




802.11g



802.11n (HT20)



802.11n (HT40)



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


| No. | Product     | Brand   | Model No. | Serial No.   | FCC ID           |
|-----|-------------|---------|-----------|--------------|------------------|
| A   | Notebook    | DELL    | E5410     | 1HC2XM1      | FCC DoC Approved |
| B   | Load        | NA      | NA        | NA           | NA               |
| C   | USB 3.0 HDD | TOSHIBA | V63700-B  | 53E2CFNUTSX4 | NA               |
| D   | USB 3.0 HDD | TOSHIBA | V63700-B  | 633APITLTSX4 | NA               |

| No. | Signal Cable Description Of The Above Support Units |
|-----|-----------------------------------------------------|
| 1   | 3m RJ45 cable.                                      |
| 2   | 1.5m non-shielded console cable w/o core            |
| 3   | 1.8m RJ45 cable X8.                                 |
| 4   | 0.5m USB cable w/o core x2                          |

Note:

1. All power cords of the above support units are non-shielded (1.8 m).
2. Item A acted as a communication partner to transfer data.
3. The console cable was provided by the client.

#### 3.4.1 Configuration of System under Test



### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specification of the EUT declared by the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**558074 D01 DTS Meas Guidance v03r02**

**662911 D01 Multiple Transmitter Output v02r01**

ANSI C63.10: 2009

All test items have been performed and recorded as per the above standards.

**NOTE:** The EUT is also considered as a kind of computer peripheral, because the connection to computer is necessary for typical use. It has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC). The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

| Frequencies<br>(MHz) | Field Strength<br>(microvolts/meter) | Measurement Distance<br>(meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009 ~ 0.490        | 2400/F(kHz)                          | 300                              |
| 0.490 ~ 1.705        | 24000/F(kHz)                         | 30                               |
| 1.705 ~ 30.0         | 30                                   | 30                               |
| 30 ~ 88              | 100                                  | 3                                |
| 88 ~ 216             | 150                                  | 3                                |
| 216 ~ 960            | 200                                  | 3                                |
| Above 960            | 500                                  | 3                                |

#### NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 Test Instruments

| Description & Manufacturer           | Model No.                    | Serial No.           | Date Of Calibration | Due Date Of Calibration |
|--------------------------------------|------------------------------|----------------------|---------------------|-------------------------|
| Test Receiver<br>ROHDE & SCHWARZ     | ESIB7                        | 100187               | Apr. 10, 2015       | Apr. 09, 2016           |
| Spectrum Analyzer<br>ROHDE & SCHWARZ | FSP40                        | 100041               | Aug. 29, 2014       | Aug. 28, 2015           |
| BILOG Antenna<br>SCHWARZBECK         | VULB9168                     | 9168-160             | Feb. 05, 2015       | Feb. 04, 2016           |
| HORN Antenna<br>SCHWARZBECK          | 9120D                        | 209                  | Feb. 09, 2015       | Feb. 08, 2016           |
| HORN Antenna<br>SCHWARZBECK          | BBHA 9170                    | BBHA9170241          | Feb. 09, 2015       | Feb. 08, 2016           |
| Preamplifier<br>Agilent              | 8447D                        | 2944A10738           | Oct.18, 2014        | Oct. 17, 2015           |
| Preamplifier<br>Agilent              | 8449B                        | 3008A01964           | Aug. 22, 2014       | Aug. 21, 2015           |
| RF signal cable<br>HUBER+SUHNNER     | SUCOFLEX 104                 | 214378/4             | Aug. 22, 2014       | Aug. 21, 2015           |
| RF signal cable<br>HUBER+SUHNNER     | SUCOFLEX 106                 | 12738/6<br>+309224/4 | Aug. 22, 2014       | Aug. 21, 2015           |
| Software<br>BV ADT                   | ADT_Radiated_<br>V7.6.15.9.4 | NA                   | NA                  | NA                      |
| Antenna Tower<br>inn-co GmbH         | MA 4000                      | 013303               | NA                  | NA                      |
| Antenna Tower Controller<br>BV ADT   | AT100                        | AT93021702           | NA                  | NA                      |
| Turn Table<br>BV ADT                 | TT100                        | TT93021702           | NA                  | NA                      |
| Turn Table Controller<br>BV ADT      | SC100                        | SC93021702           | NA                  | NA                      |
| High Speed Power Meter               | ML2495A                      | 0824011              | Jul. 26, 2014       | Jul. 25, 2015           |
| Power Sensor                         | MA2411B                      | 0738171              | Jul. 26, 2014       | Jul. 25, 2015           |

- NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in HwaYa Chamber 3.
3. The horn antenna and HP preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 988962.
5. The IC Site Registration No. is IC 7450F-3.

#### 4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


1. For emission measurements above 1 GHz, the EUT shall be placed at a height of 1.5 m above the ground at 3 meter chamber room for test
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
5. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
6. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Set Up

##### <Frequency Range below 1GHz>



##### <Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

- Connected the EUT with HDDs and placed the EUT on the testing table.
- Prepared a notebook to act as a communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command "PING".

#### 4.1.7 Test Results

Above 1GHz Data:

802.11b

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2386.00     | 61.9 PK                 | 74.0           | -12.1       | 1.56 H             | 356                  | 29.40            | 32.50                    |
| 2                                                   | 2386.00     | 52.4 AV                 | 54.0           | -1.6        | 1.56 H             | 356                  | 19.90            | 32.50                    |
| 3                                                   | *2412.00    | 117.4 PK                |                |             | 1.72 H             | 26                   | 84.80            | 32.60                    |
| 4                                                   | *2412.00    | 114.4 AV                |                |             | 1.72 H             | 26                   | 81.80            | 32.60                    |
| 5                                                   | 4824.00     | 53.9 PK                 | 74.0           | -20.1       | 1.76 H             | 172                  | 48.00            | 5.90                     |
| 6                                                   | 4824.00     | 52.7 AV                 | 54.0           | -1.3        | 1.76 H             | 172                  | 46.80            | 5.90                     |
| 7                                                   | #7236.00    | 57.9 PK                 | 74.0           | -16.1       | 1.13 H             | 14                   | 46.10            | 11.80                    |
| 8                                                   | #7236.00    | 51.3 AV                 | 54.0           | -2.7        | 1.13 H             | 14                   | 39.50            | 11.80                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2389.00     | 62.0 PK                 | 74.0           | -12.0       | 1.03 V             | 261                  | 29.50            | 32.50                    |
| 2                                                   | 2389.00     | 51.9 AV                 | 54.0           | -2.1        | 1.03 V             | 261                  | 19.40            | 32.50                    |
| 3                                                   | *2412.00    | 115.7 PK                |                |             | 1.00 V             | 251                  | 83.10            | 32.60                    |
| 4                                                   | *2412.00    | 112.4 AV                |                |             | 1.00 V             | 251                  | 79.80            | 32.60                    |
| 5                                                   | 4824.00     | 51.5 PK                 | 74.0           | -22.5       | 1.19 V             | 79                   | 45.60            | 5.90                     |
| 6                                                   | 4824.00     | 45.8 AV                 | 54.0           | -8.2        | 1.19 V             | 79                   | 39.90            | 5.90                     |
| 7                                                   | #7236.00    | 56.2 PK                 | 74.0           | -17.8       | 1.02 V             | 82                   | 44.40            | 11.80                    |
| 8                                                   | #7236.00    | 48.2 AV                 | 54.0           | -5.8        | 1.02 V             | 82                   | 36.40            | 11.80                    |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 117.6 PK                      |                   |                | 1.53 H                   | 359                        | 84.90                  | 32.70                          |
| 2                                                   | *2437.00       | 114.2 AV                      |                   |                | 1.53 H                   | 359                        | 81.50                  | 32.70                          |
| 3                                                   | 4874.00        | 54.7 PK                       | 74.0              | -19.3          | 2.03 H                   | 13                         | 48.80                  | 5.90                           |
| 4                                                   | 4874.00        | 52.8 AV                       | 54.0              | -1.2           | 2.03 H                   | 13                         | 46.90                  | 5.90                           |
| 5                                                   | 7311.00        | 59.3 PK                       | 74.0              | -14.7          | 1.57 H                   | 8                          | 47.60                  | 11.70                          |
| 6                                                   | 7311.00        | 52.1 AV                       | 54.0              | -1.9           | 1.57 H                   | 8                          | 40.40                  | 11.70                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 109.2 PK                      |                   |                | 2.11 V                   | 250                        | 76.50                  | 32.70                          |
| 2                                                   | *2437.00       | 106.4 AV                      |                   |                | 2.11 V                   | 250                        | 73.70                  | 32.70                          |
| 3                                                   | 4874.00        | 50.3 PK                       | 74.0              | -23.7          | 1.95 V                   | 20                         | 44.40                  | 5.90                           |
| 4                                                   | 4874.00        | 40.4 AV                       | 54.0              | -13.6          | 1.95 V                   | 20                         | 34.50                  | 5.90                           |
| 5                                                   | 7311.00        | 52.6 PK                       | 74.0              | -21.4          | 1.07 V                   | 19                         | 40.90                  | 11.70                          |
| 6                                                   | 7311.00        | 40.3 AV                       | 54.0              | -13.7          | 1.07 V                   | 19                         | 28.60                  | 11.70                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 115.4 PK                      |                   |                | 1.67 H                   | 0                          | 82.80                  | 32.60                          |
| 2                                                   | *2462.00       | 112.2 AV                      |                   |                | 1.67 H                   | 0                          | 79.60                  | 32.60                          |
| 3                                                   | 2483.50        | 58.1 PK                       | 74.0              | -15.9          | 1.67 H                   | 0                          | 25.40                  | 32.70                          |
| 4                                                   | 2483.50        | 47.8 AV                       | 54.0              | -6.2           | 1.67 H                   | 0                          | 15.10                  | 32.70                          |
| 5                                                   | 4924.00        | 57.6 PK                       | 74.0              | -16.4          | 2.08 H                   | 12                         | 51.60                  | 6.00                           |
| 6                                                   | 4924.00        | 52.5 AV                       | 54.0              | -1.5           | 2.08 H                   | 12                         | 46.50                  | 6.00                           |
| 7                                                   | 7386.00        | 54.2 PK                       | 74.0              | -19.8          | 1.21 H                   | 356                        | 42.60                  | 11.60                          |
| 8                                                   | 7386.00        | 41.1 AV                       | 54.0              | -12.9          | 1.21 H                   | 356                        | 29.50                  | 11.60                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 108.2 PK                      |                   |                | 1.45 V                   | 251                        | 75.60                  | 32.60                          |
| 2                                                   | *2462.00       | 104.3 AV                      |                   |                | 1.45 V                   | 251                        | 71.70                  | 32.60                          |
| 3                                                   | 2483.50        | 57.8 PK                       | 74.0              | -16.2          | 1.42 V                   | 240                        | 25.10                  | 32.70                          |
| 4                                                   | 2483.50        | 46.2 AV                       | 54.0              | -7.8           | 1.42 V                   | 240                        | 13.50                  | 32.70                          |
| 5                                                   | 4924.00        | 51.4 PK                       | 74.0              | -22.6          | 1.10 V                   | 64                         | 45.40                  | 6.00                           |
| 6                                                   | 4924.00        | 44.6 AV                       | 54.0              | -9.4           | 1.10 V                   | 64                         | 38.60                  | 6.00                           |
| 7                                                   | 7386.00        | 53.1 PK                       | 74.0              | -20.9          | 1.05 V                   | 99                         | 41.50                  | 11.60                          |
| 8                                                   | 7386.00        | 39.9 AV                       | 54.0              | -14.1          | 1.05 V                   | 99                         | 28.30                  | 11.60                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 802.11g

|                 |              |                   |              |
|-----------------|--------------|-------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                   | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2390.00     | 71.3 PK                 | 74.0           | -2.7        | 1.06 H             | 2                    | 38.80            | 32.50                    |
| 2                                                   | 2390.00     | 52.1 AV                 | 54.0           | -1.9        | 1.06 H             | 2                    | 19.60            | 32.50                    |
| 3                                                   | *2412.00    | 114.4 PK                |                |             | 1.39 H             | 0                    | 81.80            | 32.60                    |
| 4                                                   | *2412.00    | 104.9 AV                |                |             | 1.39 H             | 0                    | 72.30            | 32.60                    |
| 5                                                   | 4824.00     | 50.4 PK                 | 74.0           | -23.6       | 1.23 H             | 288                  | 44.50            | 5.90                     |
| 6                                                   | 4824.00     | 37.3 AV                 | 54.0           | -16.7       | 1.23 H             | 288                  | 31.40            | 5.90                     |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2390.00     | 58.6 PK                 | 74.0           | -15.4       | 1.60 V             | 25                   | 26.10            | 32.50                    |
| 2                                                   | 2390.00     | 47.4 AV                 | 54.0           | -6.6        | 1.60 V             | 25                   | 14.90            | 32.50                    |
| 3                                                   | *2412.00    | 108.3 PK                |                |             | 1.68 V             | 243                  | 75.70            | 32.60                    |
| 4                                                   | *2412.00    | 97.7 AV                 |                |             | 1.68 V             | 243                  | 65.10            | 32.60                    |
| 5                                                   | 4824.00     | 48.7 PK                 | 74.0           | -25.3       | 1.11 V             | 229                  | 42.80            | 5.90                     |
| 6                                                   | 4824.00     | 35.8 AV                 | 54.0           | -18.2       | 1.11 V             | 229                  | 29.90            | 5.90                     |

## REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 70.6 PK                       | 74.0              | -3.4           | 1.08 H                   | 357                        | 38.10                  | 32.50                          |
| 2                                                   | 2390.00        | 52.2 AV                       | 54.0              | -1.8           | 1.08 H                   | 357                        | 19.70                  | 32.50                          |
| 3                                                   | *2437.00       | 120.7 PK                      |                   |                | 1.36 H                   | 8                          | 88.00                  | 32.70                          |
| 4                                                   | *2437.00       | 111.7 AV                      |                   |                | 1.36 H                   | 8                          | 79.00                  | 32.70                          |
| 5                                                   | 2483.50        | 62.5 PK                       | 74.0              | -11.5          | 1.84 H                   | 17                         | 29.80                  | 32.70                          |
| 6                                                   | 2483.50        | 50.2 AV                       | 54.0              | -3.8           | 1.84 H                   | 17                         | 17.50                  | 32.70                          |
| 7                                                   | 4824.00        | 55.6 PK                       | 74.0              | -18.4          | 1.38 H                   | 12                         | 49.70                  | 5.90                           |
| 8                                                   | 4824.00        | 41.7 AV                       | 54.0              | -12.3          | 1.38 H                   | 12                         | 35.80                  | 5.90                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 61.4 PK                       | 74.0              | -12.6          | 1.90 V                   | 269                        | 28.90                  | 32.50                          |
| 2                                                   | 2390.00        | 48.0 AV                       | 54.0              | -6.0           | 1.90 V                   | 269                        | 15.50                  | 32.50                          |
| 3                                                   | *2437.00       | 112.6 PK                      |                   |                | 1.92 V                   | 266                        | 79.90                  | 32.70                          |
| 4                                                   | *2437.00       | 103.6 AV                      |                   |                | 1.92 V                   | 266                        | 70.90                  | 32.70                          |
| 5                                                   | 2483.50        | 60.0 PK                       | 74.0              | -14.0          | 1.92 V                   | 266                        | 27.30                  | 32.70                          |
| 6                                                   | 2483.50        | 46.7 AV                       | 54.0              | -7.3           | 1.92 V                   | 266                        | 14.00                  | 32.70                          |
| 7                                                   | 4874.00        | 48.9 PK                       | 74.0              | -25.1          | 1.23 V                   | 66                         | 43.00                  | 5.90                           |
| 8                                                   | 4874.00        | 35.8 AV                       | 54.0              | -18.2          | 1.23 V                   | 66                         | 29.90                  | 5.90                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 115.5 PK                      |                   |                | 1.35 H                   | 161                        | 82.90                  | 32.60                          |
| 2                                                   | *2462.00       | 105.7 AV                      |                   |                | 1.35 H                   | 161                        | 73.10                  | 32.60                          |
| 3                                                   | 2483.50        | 68.8 PK                       | 74.0              | -5.2           | 1.49 H                   | 358                        | 36.10                  | 32.70                          |
| 4                                                   | 2483.50        | 52.2 AV                       | 54.0              | -1.8           | 1.49 H                   | 358                        | 19.50                  | 32.70                          |
| 5                                                   | 4924.00        | 50.6 PK                       | 74.0              | -23.4          | 1.37 H                   | 168                        | 44.60                  | 6.00                           |
| 6                                                   | 4924.00        | 37.7 AV                       | 54.0              | -16.3          | 1.37 H                   | 168                        | 31.70                  | 6.00                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 109.0 PK                      |                   |                | 1.00 V                   | 269                        | 76.40                  | 32.60                          |
| 2                                                   | *2462.00       | 99.5 AV                       |                   |                | 1.00 V                   | 269                        | 66.90                  | 32.60                          |
| 3                                                   | 2483.50        | 61.1 PK                       | 74.0              | -12.9          | 1.00 V                   | 263                        | 28.40                  | 32.70                          |
| 4                                                   | 2483.50        | 48.6 AV                       | 54.0              | -5.4           | 1.00 V                   | 263                        | 15.90                  | 32.70                          |
| 5                                                   | 4824.00        | 47.9 PK                       | 74.0              | -26.1          | 1.10 V                   | 69                         | 42.00                  | 5.90                           |
| 6                                                   | 4824.00        | 35.0 AV                       | 54.0              | -19.0          | 1.10 V                   | 69                         | 29.10                  | 5.90                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

# 802.11n (HT20)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 70.2 PK                       | 74.0              | -3.8           | 1.38 H                   | 14                         | 37.70                  | 32.50                          |
| 2                                                   | 2390.00        | 52.9 AV                       | 54.0              | -1.1           | 1.38 H                   | 14                         | 20.40                  | 32.50                          |
| 3                                                   | *2412.00       | 114.0 PK                      |                   |                | 1.54 H                   | 19                         | 81.40                  | 32.60                          |
| 4                                                   | *2412.00       | 104.4 AV                      |                   |                | 1.54 H                   | 19                         | 71.80                  | 32.60                          |
| 5                                                   | 4824.00        | 48.5 PK                       | 74.0              | -25.5          | 1.95 H                   | 17                         | 42.60                  | 5.90                           |
| 6                                                   | 4824.00        | 35.6 AV                       | 54.0              | -18.4          | 1.95 H                   | 17                         | 29.70                  | 5.90                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 63.6 PK                       | 74.0              | -10.4          | 1.01 V                   | 254                        | 31.10                  | 32.50                          |
| 2                                                   | 2390.00        | 49.4 AV                       | 54.0              | -4.6           | 1.01 V                   | 254                        | 16.90                  | 32.50                          |
| 3                                                   | *2412.00       | 107.2 PK                      |                   |                | 1.00 V                   | 254                        | 74.60                  | 32.60                          |
| 4                                                   | *2412.00       | 97.9 AV                       |                   |                | 1.00 V                   | 254                        | 65.30                  | 32.60                          |
| 5                                                   | 4824.00        | 47.9 PK                       | 74.0              | -26.1          | 1.23 V                   | 45                         | 42.00                  | 5.90                           |
| 6                                                   | 4824.00        | 34.7 AV                       | 54.0              | -19.3          | 1.23 V                   | 45                         | 28.80                  | 5.90                           |

## REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 69.2 PK                       | 74.0              | -4.8           | 1.55 H                   | 18                         | 36.70                  | 32.50                          |
| 2                                                   | 2390.00        | 52.1 AV                       | 54.0              | -1.9           | 1.55 H                   | 18                         | 19.60                  | 32.50                          |
| 3                                                   | *2437.00       | 121.0 PK                      |                   |                | 1.49 H                   | 0                          | 88.30                  | 32.70                          |
| 4                                                   | *2437.00       | 111.0 AV                      |                   |                | 1.49 H                   | 0                          | 78.30                  | 32.70                          |
| 5                                                   | 2483.50        | 69.7 PK                       | 74.0              | -4.3           | 1.33 H                   | 8                          | 37.00                  | 32.70                          |
| 6                                                   | 2483.50        | 52.0 AV                       | 54.0              | -2.0           | 1.33 H                   | 8                          | 19.30                  | 32.70                          |
| 7                                                   | 4874.00        | 50.1 PK                       | 74.0              | -23.9          | 1.59 H                   | 33                         | 44.20                  | 5.90                           |
| 8                                                   | 4874.00        | 37.5 AV                       | 54.0              | -16.5          | 1.59 H                   | 33                         | 31.60                  | 5.90                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 59.1 PK                       | 74.0              | -14.9          | 1.03 V                   | 250                        | 26.60                  | 32.50                          |
| 2                                                   | 2390.00        | 48.5 AV                       | 54.0              | -5.5           | 1.03 V                   | 250                        | 16.00                  | 32.50                          |
| 3                                                   | *2437.00       | 114.4 PK                      |                   |                | 1.28 V                   | 254                        | 81.70                  | 32.70                          |
| 4                                                   | *2437.00       | 105.1 AV                      |                   |                | 1.28 V                   | 254                        | 72.40                  | 32.70                          |
| 5                                                   | 2483.50        | 58.8 PK                       | 74.0              | -15.2          | 1.00 V                   | 256                        | 26.10                  | 32.70                          |
| 6                                                   | 2483.50        | 48.5 AV                       | 54.0              | -5.5           | 1.00 V                   | 256                        | 15.80                  | 32.70                          |
| 7                                                   | 4874.00        | 48.4 PK                       | 74.0              | -25.6          | 1.13 V                   | 221                        | 42.50                  | 5.90                           |
| 8                                                   | 4874.00        | 35.5 AV                       | 54.0              | -18.5          | 1.13 V                   | 221                        | 29.60                  | 5.90                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 113.4 PK                      |                   |                | 1.44 H                   | 22                         | 80.80                  | 32.60                          |
| 2                                                   | *2462.00       | 103.3 AV                      |                   |                | 1.44 H                   | 22                         | 70.70                  | 32.60                          |
| 3                                                   | 2483.50        | 68.2 PK                       | 74.0              | -5.8           | 1.31 H                   | 19                         | 35.50                  | 32.70                          |
| 4                                                   | 2483.50        | 52.9 AV                       | 54.0              | -1.1           | 1.31 H                   | 19                         | 20.20                  | 32.70                          |
| 5                                                   | 4924.00        | 49.2 PK                       | 74.0              | -24.8          | 1.86 H                   | 66                         | 43.20                  | 6.00                           |
| 6                                                   | 4924.00        | 36.1 AV                       | 54.0              | -17.9          | 1.86 H                   | 66                         | 30.10                  | 6.00                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 105.3 PK                      |                   |                | 1.20 V                   | 85                         | 72.70                  | 32.60                          |
| 2                                                   | *2462.00       | 95.7 AV                       |                   |                | 1.20 V                   | 85                         | 63.10                  | 32.60                          |
| 3                                                   | 2483.50        | 58.4 PK                       | 74.0              | -15.6          | 1.03 V                   | 250                        | 25.70                  | 32.70                          |
| 4                                                   | 2483.50        | 47.5 AV                       | 54.0              | -6.5           | 1.03 V                   | 250                        | 14.80                  | 32.70                          |
| 5                                                   | 4924.00        | 47.9 PK                       | 74.0              | -26.1          | 1.37 V                   | 96                         | 41.90                  | 6.00                           |
| 6                                                   | 4924.00        | 34.8 AV                       | 54.0              | -19.2          | 1.37 V                   | 96                         | 28.80                  | 6.00                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

### 802.11n (HT40)

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 3 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 66.0 PK                       | 74.0              | -8.0           | 1.39 H                   | 3                          | 33.50                  | 32.50                          |
| 2                                                   | 2390.00        | 52.7 AV                       | 54.0              | -1.3           | 1.39 H                   | 3                          | 20.20                  | 32.50                          |
| 3                                                   | *2422.00       | 107.4 PK                      |                   |                | 1.51 H                   | 20                         | 74.80                  | 32.60                          |
| 4                                                   | *2422.00       | 98.2 AV                       |                   |                | 1.51 H                   | 20                         | 65.60                  | 32.60                          |
| 5                                                   | 4844.00        | 48.7 PK                       | 74.0              | -25.3          | 1.72 H                   | 43                         | 42.80                  | 5.90                           |
| 6                                                   | 4844.00        | 35.7 AV                       | 54.0              | -18.3          | 1.72 H                   | 43                         | 29.80                  | 5.90                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 58.6 PK                       | 74.0              | -15.4          | 1.19 V                   | 251                        | 26.10                  | 32.50                          |
| 2                                                   | 2390.00        | 47.5 AV                       | 54.0              | -6.5           | 1.19 V                   | 251                        | 15.00                  | 32.50                          |
| 3                                                   | *2422.00       | 100.5 PK                      |                   |                | 1.00 V                   | 265                        | 67.90                  | 32.60                          |
| 4                                                   | *2422.00       | 90.5 AV                       |                   |                | 1.00 V                   | 265                        | 57.90                  | 32.60                          |
| 5                                                   | 4844.00        | 47.6 PK                       | 74.0              | -26.4          | 1.20 V                   | 222                        | 41.70                  | 5.90                           |
| 6                                                   | 4844.00        | 34.4 AV                       | 54.0              | -19.6          | 1.20 V                   | 222                        | 28.50                  | 5.90                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 66.6 PK                       | 74.0              | -7.4           | 1.05 H                   | 9                          | 34.10                  | 32.50                          |
| 2                                                   | 2390.00        | 52.5 AV                       | 54.0              | -1.5           | 1.05 H                   | 9                          | 20.00                  | 32.50                          |
| 3                                                   | *2437.00       | 112.1 PK                      |                   |                | 1.19 H                   | 359                        | 79.40                  | 32.70                          |
| 4                                                   | *2437.00       | 102.0 AV                      |                   |                | 1.19 H                   | 359                        | 69.30                  | 32.70                          |
| 5                                                   | 2483.50        | 63.6 PK                       | 74.0              | -10.4          | 1.31 H                   | 351                        | 30.90                  | 32.70                          |
| 6                                                   | 2483.50        | 50.2 AV                       | 54.0              | -3.8           | 1.31 H                   | 351                        | 17.50                  | 32.70                          |
| 7                                                   | 4874.00        | 49.4 PK                       | 74.0              | -24.6          | 1.39 H                   | 130                        | 43.50                  | 5.90                           |
| 8                                                   | 4874.00        | 36.3 AV                       | 54.0              | -17.7          | 1.39 H                   | 130                        | 30.40                  | 5.90                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 59.0 PK                       | 74.0              | -15.0          | 1.03 V                   | 254                        | 26.50                  | 32.50                          |
| 2                                                   | 2390.00        | 47.8 AV                       | 54.0              | -6.2           | 1.03 V                   | 254                        | 15.30                  | 32.50                          |
| 3                                                   | *2437.00       | 103.8 PK                      |                   |                | 1.00 V                   | 265                        | 71.10                  | 32.70                          |
| 4                                                   | *2437.00       | 94.7 AV                       |                   |                | 1.00 V                   | 265                        | 62.00                  | 32.70                          |
| 5                                                   | 2483.50        | 58.5 PK                       | 74.0              | -15.5          | 1.10 V                   | 266                        | 25.80                  | 32.70                          |
| 6                                                   | 2483.50        | 47.6 AV                       | 54.0              | -6.4           | 1.10 V                   | 266                        | 14.90                  | 32.70                          |
| 7                                                   | 4874.00        | 48.3 PK                       | 74.0              | -25.7          | 1.19 V                   | 231                        | 42.40                  | 5.90                           |
| 8                                                   | 4874.00        | 35.1 AV                       | 54.0              | -18.9          | 1.19 V                   | 231                        | 29.20                  | 5.90                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 9 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 109.0 PK                      |                   |                | 1.35 H                   | 355                        | 76.30                  | 32.70                          |
| 2                                                   | *2452.00       | 99.2 AV                       |                   |                | 1.35 H                   | 355                        | 66.50                  | 32.70                          |
| 3                                                   | 2483.50        | 67.2 PK                       | 74.0              | -6.8           | 1.00 H                   | 18                         | 34.50                  | 32.70                          |
| 4                                                   | 2483.50        | 52.7 AV                       | 54.0              | -1.3           | 1.00 H                   | 18                         | 20.00                  | 32.70                          |
| 5                                                   | 4904.00        | 48.7 PK                       | 74.0              | -25.3          | 1.56 H                   | 67                         | 42.90                  | 5.80                           |
| 6                                                   | 4904.00        | 35.6 AV                       | 54.0              | -18.4          | 1.56 H                   | 67                         | 29.80                  | 5.80                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 100.1 PK                      |                   |                | 1.28 V                   | 262                        | 67.40                  | 32.70                          |
| 2                                                   | *2452.00       | 91.2 AV                       |                   |                | 1.28 V                   | 262                        | 58.50                  | 32.70                          |
| 3                                                   | 2483.50        | 58.8 PK                       | 74.0              | -15.2          | 1.00 V                   | 265                        | 26.10                  | 32.70                          |
| 4                                                   | 2483.50        | 48.6 AV                       | 54.0              | -5.4           | 1.00 V                   | 265                        | 15.90                  | 32.70                          |
| 5                                                   | 4924.00        | 47.5 PK                       | 74.0              | -26.5          | 1.29 V                   | 212                        | 41.50                  | 6.00                           |
| 6                                                   | 4924.00        | 34.6 AV                       | 54.0              | -19.4          | 1.29 V                   | 212                        | 28.60                  | 6.00                           |

#### REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.

# Below 1GHz Worst-Case Data:

## 802.11n (HT20)

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 6 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 80.45       | 31.1 QP                 | 40.0           | -8.9        | 1.50 H             | 249                  | 49.50            | -18.40                   |
| 2                                                   | 313.77      | 29.0 QP                 | 46.0           | -17.0       | 1.00 H             | 67                   | 41.20            | -12.20                   |
| 3                                                   | 500.42      | 33.5 QP                 | 46.0           | -12.5       | 1.50 H             | 198                  | 41.90            | -8.40                    |
| 4                                                   | 624.85      | 34.3 QP                 | 46.0           | -11.7       | 1.00 H             | 192                  | 39.90            | -5.60                    |
| 5                                                   | 751.23      | 37.1 QP                 | 46.0           | -8.9        | 1.00 H             | 138                  | 40.30            | -3.20                    |
| 6                                                   | 875.67      | 39.7 QP                 | 46.0           | -6.3        | 1.50 H             | 194                  | 40.80            | -1.10                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 39.55       | 35.4 QP                 | 40.0           | -4.6        | 1.00 V             | 9                    | 50.50            | -15.10                   |
| 2                                                   | 49.45       | 34.7 QP                 | 40.0           | -5.3        | 1.00 V             | 342                  | 49.10            | -14.40                   |
| 3                                                   | 59.06       | 37.8 QP                 | 40.0           | -2.2        | 1.50 V             | 2                    | 52.30            | -14.50                   |
| 4                                                   | 624.85      | 34.5 QP                 | 46.0           | -11.5       | 1.50 V             | 176                  | 40.10            | -5.60                    |
| 5                                                   | 751.23      | 36.3 QP                 | 46.0           | -9.7        | 1.00 V             | 165                  | 39.50            | -3.20                    |
| 6                                                   | 875.67      | 39.4 QP                 | 46.0           | -6.6        | 1.00 V             | 182                  | 40.50            | -1.10                    |

### REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB)  
– Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value

## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

**Note:** 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

| Description & Manufacturer              | Model No.                | Serial No.     | Date Of Calibration | Due Date Of Calibration |
|-----------------------------------------|--------------------------|----------------|---------------------|-------------------------|
| Test Receiver<br>ROHDE & SCHWARZ        | ESCI                     | 100613         | Nov. 11, 2014       | Nov. 10, 2015           |
| RF signal cable<br>Woken                | 5D-FB                    | Cable-HYC01-01 | Dec. 26, 2014       | Dec. 25, 2015           |
| LISN<br>ROHDE & SCHWARZ<br>(EUT)        | ESH3-Z5                  | 835239/001     | Mar. 02, 2015       | Mar. 01, 2016           |
| LISN<br>ROHDE & SCHWARZ<br>(Peripheral) | ESH3-Z5                  | 100311         | Jul. 21, 2014       | Jul. 20, 2015           |
| Software<br>ADT                         | BV ADT_Conf_<br>V7.3.7.3 | NA             | NA                  | NA                      |

**NOTE:** 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 1.

3. The VCCI Site Registration No. is C-2040.

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) were not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions


Same as 4.1.6.

#### 4.2.7 Test Results

| Phase | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |       |                |       |           |       |        |        |
|-------|----------|-------------------|--------------------------------|-------|----------------|-------|-----------|-------|--------|--------|
| No    | Freq.    | Corr. Factor      | Reading Value                  |       | Emission Level |       | Limit     |       | Margin |        |
|       | [MHz]    | (dB)              | [dB (uV)]                      |       | [dB (uV)]      |       | [dB (uV)] |       | (dB)   |        |
|       |          |                   | Q.P.                           | AV.   | Q.P.           | AV.   | Q.P.      | AV.   | Q.P.   | AV.    |
| 1     | 0.15391  | 0.05              | 45.01                          | 31.00 | 45.06          | 31.05 | 65.79     | 55.79 | -20.73 | -24.74 |
| 2     | 0.19301  | 0.06              | 38.48                          | 21.45 | 38.54          | 21.51 | 63.91     | 53.91 | -25.37 | -32.40 |
| 3     | 0.43464  | 0.06              | 36.02                          | 27.96 | 36.08          | 28.02 | 57.16     | 47.16 | -21.08 | -19.14 |
| 4     | 3.09814  | 0.16              | 32.32                          | 24.27 | 32.48          | 24.43 | 56.00     | 46.00 | -23.52 | -21.57 |
| 5     | 8.14204  | 0.37              | 30.98                          | 25.42 | 31.35          | 25.79 | 60.00     | 50.00 | -28.65 | -24.21 |
| 6     | 18.52700 | 0.83              | 35.64                          | 30.33 | 36.47          | 31.16 | 60.00     | 50.00 | -23.53 | -18.84 |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|       |             |                   |                                |
|-------|-------------|-------------------|--------------------------------|
| Phase | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|-------------|-------------------|--------------------------------|

| No | Freq.<br>[MHz] | Corr.<br>Factor<br>(dB) | Reading Value<br>[dB (uV)] |              | Emission Level<br>[dB (uV)] |              | Limit<br>[dB (uV)] |              | Margin<br>(dB) |               |
|----|----------------|-------------------------|----------------------------|--------------|-----------------------------|--------------|--------------------|--------------|----------------|---------------|
|    |                |                         |                            |              |                             |              |                    |              |                |               |
|    |                |                         | Q.P.                       | AV.          | Q.P.                        | AV.          | Q.P.               | AV.          | Q.P.           | AV.           |
| 1  | 0.16569        | 0.05                    | 42.70                      | 27.50        | 42.75                       | 27.55        | 65.17              | 55.17        | -22.42         | -27.62        |
| 2  | 0.21256        | 0.05                    | 37.52                      | 23.16        | 37.57                       | 23.21        | 63.10              | 53.10        | -25.53         | -29.89        |
| 3  | <b>0.42370</b> | <b>0.06</b>             | <b>36.54</b>               | <b>29.97</b> | <b>36.60</b>                | <b>30.03</b> | <b>57.38</b>       | <b>47.38</b> | <b>-20.77</b>  | <b>-17.34</b> |
| 4  | 3.12551        | 0.16                    | 32.48                      | 24.80        | 32.64                       | 24.96        | 56.00              | 46.00        | -23.36         | -21.04        |
| 5  | 10.36683       | 0.43                    | 31.85                      | 26.22        | 32.28                       | 26.65        | 60.00              | 50.00        | -27.72         | -23.35        |
| 6  | 18.41752       | 0.68                    | 36.62                      | 31.49        | 37.30                       | 32.17        | 60.00              | 50.00        | -22.70         | -17.83        |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




### 4.3 6dB Bandwidth Measurement

#### 4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

Set resolution bandwidth (RBW) = 100kHz

- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Result

##### 802.11b

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------------------|-------------|
|         |                 | CHAIN 0             | CHAIN 1 | CHAIN 2 |                     |             |
| 1       | 2412            | 7.10                | 7.56    | 7.09    | 0.5                 | Pass        |
| 6       | 2437            | 7.11                | 7.09    | 7.08    | 0.5                 | Pass        |
| 11      | 2462            | 7.09                | 7.09    | 7.10    | 0.5                 | Pass        |

##### 802.11g

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------------------|-------------|
|         |                 | CHAIN 0             | CHAIN 1 | CHAIN 2 |                     |             |
| 1       | 2412            | 16.38               | 16.37   | 15.97   | 0.5                 | Pass        |
| 6       | 2437            | 16.37               | 16.33   | 16.07   | 0.5                 | Pass        |
| 11      | 2462            | 16.38               | 16.37   | 16.39   | 0.5                 | Pass        |

##### 802.11n (HT20)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------------------|-------------|
|         |                 | CHAIN 0             | CHAIN 1 | CHAIN 2 |                     |             |
| 1       | 2412            | 17.23               | 16.96   | 16.41   | 0.5                 | Pass        |
| 6       | 2437            | 17.33               | 16.92   | 16.38   | 0.5                 | Pass        |
| 11      | 2462            | 17.58               | 16.97   | 17.19   | 0.5                 | Pass        |


##### 802.11n (HT40)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------|---------------------|-------------|
|         |                 | CHAIN 0             | CHAIN 1 | CHAIN 2 |                     |             |
| 3       | 2422            | 35.87               | 35.87   | 35.84   | 0.5                 | Pass        |
| 6       | 2437            | 35.59               | 35.82   | 35.80   | 0.5                 | Pass        |
| 9       | 2452            | 36.14               | 35.81   | 35.81   | 0.5                 | Pass        |


# Spectrum Plot of Worst Value

802.11b

802.11g




A D T




A D T

802.11n (HT20)

802.11n (HT40)



A D T



A D T

## 4.4 Conducted Output Power Measurement

### 4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for  $NANT \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any NANT;

Array Gain =  $5 \log(NANT/NSS)$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $NANT \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(NANT/NSS)$  dB.

### 4.4.2 Test Setup



### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.4.4 Test Procedures

A peak / average power sensor was used on the output port of the EUT. A power meter was used to read the response of the peak / average power sensor. Record the power level.

- Set the RBW  $\geq$  DTS bandwidth.
- Set VBW  $\geq 3 \times$  RBW.
- Set span  $\geq 3 \times$  RBW
- Sweep time = auto couple.
- Detector = peak.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use peak marker function to determine the peak amplitude level.

### 4.4.5 Deviation from Test Standard

No deviation.

### 4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

#### 4.4.7 Test Results

##### FOR PEAK POWER

###### 802.11b

| Chan. | Chan. Freq. (MHz) | Peak Power (dBm) |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------|-------------------|------------------|---------|---------|------------------|-------------------|-------------|-------------|
|       |                   | Chain 0          | Chain 1 | Chain 2 |                  |                   |             |             |
| 1     | 2412              | 20.64            | 20.81   | 22.08   | 397.818          | 26.00             | 30          | Pass        |
| 6     | 2437              | 20.79            | 20.78   | 21.90   | 394.506          | 25.96             | 30          | Pass        |
| 11    | 2462              | 19.38            | 19.41   | 20.58   | 288.281          | 24.60             | 30          | Pass        |

###### 802.11g

| Chan. | Chan. Freq. (MHz) | Peak Power (dBm) |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------|-------------------|------------------|---------|---------|------------------|-------------------|-------------|-------------|
|       |                   | Chain 0          | Chain 1 | Chain 2 |                  |                   |             |             |
| 1     | 2412              | 19.07            | 19.74   | 20.57   | 288.938          | 24.61             | 30          | Pass        |
| 6     | 2437              | 24.54            | 24.29   | 25.24   | 887.175          | 29.48             | 30          | Pass        |
| 11    | 2462              | 20.39            | 20.64   | 24.41   | 501.332          | 27.00             | 30          | Pass        |

###### 802.11n (HT20)

| Chan. | Chan. Freq. (MHz) | Peak Power (dBm) |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------|-------------------|------------------|---------|---------|------------------|-------------------|-------------|-------------|
|       |                   | Chain 0          | Chain 1 | Chain 2 |                  |                   |             |             |
| 1     | 2412              | 18.21            | 18.56   | 19.90   | 235.725          | 23.72             | 30          | Pass        |
| 6     | 2437              | 24.71            | 24.36   | 25.24   | <b>902.894</b>   | 29.56             | 30          | Pass        |
| 11    | 2462              | 19.36            | 19.56   | 20.81   | 297.167          | 24.73             | 30          | Pass        |

###### 802.11n (HT40)

| Chan. | Chan. Freq. (MHz) | Peak Power (dBm) |         |         | Total Power (mW) | Total Power (dBm) | Limit (dBm) | Pass / Fail |
|-------|-------------------|------------------|---------|---------|------------------|-------------------|-------------|-------------|
|       |                   | Chain 0          | Chain 1 | Chain 2 |                  |                   |             |             |
| 3     | 2422              | 14.61            | 14.83   | 16.06   | 99.681           | 19.99             | 30          | Pass        |
| 6     | 2437              | 20.09            | 20.15   | 21.37   | 342.696          | 25.35             | 30          | Pass        |
| 9     | 2452              | 16.13            | 16.34   | 17.52   | 140.567          | 21.48             | 30          | Pass        |

## FOR AVERAGE POWER

### 802.11b

| Chan. | Frequency (MHz) | Avg. Power (dBm) |         |         | Total Power (mW) | Total Power (dBm) |
|-------|-----------------|------------------|---------|---------|------------------|-------------------|
|       |                 | Chain 0          | Chain 1 | Chain 2 |                  |                   |
| 1     | 2412            | 17.79            | 17.98   | 19.24   | 206.869          | 23.16             |
| 6     | 2437            | 17.91            | 17.82   | 19.12   | 203.994          | 23.10             |
| 11    | 2462            | 16.31            | 16.46   | 17.77   | 146.856          | 21.67             |

### 802.11g

| Chan. | Frequency (MHz) | Avg. Power (dBm) |         |         | Total Power (mW) | Total Power (dBm) |
|-------|-----------------|------------------|---------|---------|------------------|-------------------|
|       |                 | Chain 0          | Chain 1 | Chain 2 |                  |                   |
| 1     | 2412            | 13.41            | 14.07   | 15.16   | 80.265           | 19.05             |
| 6     | 2437            | 20.04            | 19.83   | 21.06   | 324.730          | 25.12             |
| 11    | 2462            | 14.63            | 14.76   | 15.98   | 98.591           | 19.94             |

### 802.11n (HT20)

| Chan. | Frequency (MHz) | Avg. Power (dBm) |         |         | Total Power (mW) | Total Power (dBm) |
|-------|-----------------|------------------|---------|---------|------------------|-------------------|
|       |                 | Chain 0          | Chain 1 | Chain 2 |                  |                   |
| 1     | 2412            | 12.45            | 13.09   | 14.11   | 63.712           | 18.04             |
| 6     | 2437            | 19.89            | 19.68   | 21.34   | 326.540          | 25.14             |
| 11    | 2462            | 13.56            | 13.60   | 14.91   | 76.582           | 18.84             |

### 802.11n (HT40)


| Chan. | Frequency (MHz) | Avg. Power (dBm) |         |         | Total Power (mW) | Total Power (dBm) |
|-------|-----------------|------------------|---------|---------|------------------|-------------------|
|       |                 | Chain 0          | Chain 1 | Chain 2 |                  |                   |
| 3     | 2422            | 8.75             | 9.11    | 10.22   | 26.166           | 14.18             |
| 6     | 2437            | 14.23            | 14.33   | 15.50   | 89.068           | 19.50             |
| 9     | 2452            | 10.45            | 10.26   | 11.71   | 36.534           | 15.63             |

## 4.5 Power Spectral Density Measurement

### 4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedure

- Set analyzer center frequency to DTS channel center frequency.
- Set the span to 1.5 times the DTS bandwidth.
- Set the RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set the VBW  $\geq 3 \times \text{RBW}$ .
- Detector = peak.
- Sweep time = auto couple.
- Trace mode = max hold.
- Allow trace to fully stabilize.
- Use the peak marker function to determine the maximum amplitude level within the RBW.

### 4.5.5 Deviation from Test Standard

No deviation.

### 4.5.6 EUT Operating Condition

Same as Item 4.3.6

#### 4.5.7 Test Results

##### 802.11b

| TX chain | Channel | Freq. (MHz) | PSD (dBm) | 10 log (N=3) dB | Total PSD (dBm) | Limit (dBm) | PASS /FAIL |
|----------|---------|-------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 1       | 2412        | -3.05     | 4.77            | 1.72            | 6.56        | Pass       |
|          | 6       | 2437        | -3.15     | 4.77            | 1.62            | 6.56        | Pass       |
|          | 11      | 2462        | -5.62     | 4.77            | -0.85           | 6.56        | Pass       |
| 1        | 1       | 2412        | -3.42     | 4.77            | 1.35            | 6.56        | Pass       |
|          | 6       | 2437        | -2.88     | 4.77            | 1.89            | 6.56        | Pass       |
|          | 11      | 2462        | -4.14     | 4.77            | 0.63            | 6.56        | Pass       |
| 2        | 1       | 2412        | -2.35     | 4.77            | 2.42            | 6.56        | Pass       |
|          | 6       | 2437        | -2.82     | 4.77            | 1.95            | 6.56        | Pass       |
|          | 11      | 2462        | -4.51     | 4.77            | 0.26            | 6.56        | Pass       |

##### NOTE:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10G1 / 20 + 10G2 / 20 + \dots + 10GN / 20)2/3] = 7.44 \text{ dBi} > 6\text{dBi}$  , so the power density limit shall be reduced to  $8-(7.44-6) = 6.56\text{dBm}$ .

##### 802.11g

| TX chain | Channel | Freq. (MHz) | PSD (dBm) | 10 log (N=3) dB | Total PSD (dBm) | Limit (dBm) | PASS /FAIL |
|----------|---------|-------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 1       | 2412        | -12.38    | 4.77            | -7.61           | 6.56        | Pass       |
|          | 6       | 2437        | -6.18     | 4.77            | -1.41           | 6.56        | Pass       |
|          | 11      | 2462        | -10.97    | 4.77            | -6.20           | 6.56        | Pass       |
| 1        | 1       | 2412        | -11.04    | 4.77            | -6.27           | 6.56        | Pass       |
|          | 6       | 2437        | -5.80     | 4.77            | -1.03           | 6.56        | Pass       |
|          | 11      | 2462        | -10.53    | 4.77            | -5.76           | 6.56        | Pass       |
| 2        | 1       | 2412        | -4.45     | 4.77            | 0.32            | 6.56        | Pass       |
|          | 6       | 2437        | -4.39     | 4.77            | 0.38            | 6.56        | Pass       |
|          | 11      | 2462        | -9.31     | 4.77            | -4.54           | 6.56        | Pass       |

##### NOTE:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10G1 / 20 + 10G2 / 20 + \dots + 10GN / 20)2/3] = 7.44 \text{ dBi} > 6\text{dBi}$  , so the power density limit shall be reduced to  $8-(7.44-6) = 6.56\text{dBm}$ .

### 802.11n (HT20)

| TX chain | Channel | Freq. (MHz) | PSD (dBm) | 10 log (N=3) dB | Total PSD (dBm) | Limit (dBm) | PASS /FAIL |
|----------|---------|-------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 1       | 2412        | -13.88    | 4.77            | -9.11           | 6.56        | Pass       |
|          | 6       | 2437        | -5.93     | 4.77            | -1.16           | 6.56        | Pass       |
|          | 11      | 2462        | -12.76    | 4.77            | -7.99           | 6.56        | Pass       |
| 1        | 1       | 2412        | -12.85    | 4.77            | -8.08           | 6.56        | Pass       |
|          | 6       | 2437        | -5.95     | 4.77            | -1.18           | 6.56        | Pass       |
|          | 11      | 2462        | -12.84    | 4.77            | -8.07           | 6.56        | Pass       |
| 2        | 1       | 2412        | -11.58    | 4.77            | -6.81           | 6.56        | Pass       |
|          | 6       | 2437        | -5.32     | 4.77            | -0.55           | 6.56        | Pass       |
|          | 11      | 2462        | -11.11    | 4.77            | -6.34           | 6.56        | Pass       |

#### NOTE:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10G1 / 20 + 10G2 / 20 + \dots + 10GN / 20)2/3] = 7.44 \text{ dBi} > 6\text{dBi}$  , so the power density limit shall be reduced to  $8-(7.44-6) = 6.56\text{dBm}$ .

### 802.11n (HT40)

| TX chain | Channel | Freq. (MHz) | PSD (dBm) | 10 log (N=3) dB | Total PSD (dBm) | Limit (dBm) | PASS /FAIL |
|----------|---------|-------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 3       | 2422        | -20.06    | 4.77            | -15.29          | 6.56        | Pass       |
|          | 6       | 2437        | -15.72    | 4.77            | -10.95          | 6.56        | Pass       |
|          | 9       | 2452        | -18.80    | 4.77            | -14.03          | 6.56        | Pass       |
| 1        | 3       | 2422        | -19.40    | 4.77            | -14.63          | 6.56        | Pass       |
|          | 6       | 2437        | -15.23    | 4.77            | -10.46          | 6.56        | Pass       |
|          | 9       | 2452        | -19.23    | 4.77            | -14.46          | 6.56        | Pass       |
| 2        | 3       | 2422        | -17.72    | 4.77            | -12.95          | 6.56        | Pass       |
|          | 6       | 2437        | -13.68    | 4.77            | -8.91           | 6.56        | Pass       |
|          | 9       | 2452        | -16.81    | 4.77            | -12.04          | 6.56        | Pass       |



#### NOTE:

- Method 1 of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain =  $10 \log[(10G1 / 20 + 10G2 / 20 + \dots + 10GN / 20)2/3] = 7.44 \text{ dBi} > 6\text{dBi}$  , so the power density limit shall be reduced to  $8-(7.44-6) = 6.56\text{dBm}$ .

# Spectrum Plot of Worst Value



802.11b

802.11g



802.11n (HT20)

802.11n (HT40)




## 4.6 Conducted Out of Band Emission Measurement

### 4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 20dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedure

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = average.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Ensure that the number of measurement points  $\geq$  span/RBW
4. According to measurement points to set differ measurement span.
5. Detector = peak.
6. Trace Mode = max hold.
7. Sweep = auto couple.

### 4.6.5 Deviation from Test Standard

No deviation.


### 4.6.6 EUT Operating Condition

Same as Item 4.3.6


## 4.6.7 Test Results

### 802.11b CHAIN 0


#### CH 1




#### CH 6




#### CH 11



#### CH 1 Band edge





#### CH 11 Band edge





# CHAIN 1



## CH 1




## CH 6




## CH 11



## CH 1 Band edge



## CH 11 Band edge









A D T

## CHAIN 2



### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge




# 802.11g\_CHAIN 0

## CH 1




A D T




A D T

## CH 6




A D T




A D T

## CH 11




A D T




A D T

## CH 1 Band edge



A D T

## CH 11 Band edge




A D T




A D T

## CHAIN 1


## CH 1



## CH 6




## CH 11





## CH 1 Band edge

## CH 11 Band edge





## CHAIN 2



### CH 1





### CH 6



### CH 11





### CH 1 Band edge





# 802.11n (HT20)\_CHAIN 0



## CH 1




## CH 6




## CH 11



## CH 1 Band edge





## CH 11 Band edge





# CHAIN 1



## CH 1





## CH 6



## CH 11





## CH 1 Band edge





## CHAIN 2



### CH 1




### CH 6




### CH 11



### CH 1 Band edge





### CH 11 Band edge





# 802.11n (HT40)\_CHAIN 0



## CH 3





## CH 6



## CH 9



## CH 3 Band edge









A D T

## CHAIN 1



## CH 3




## CH 6




## CH 9



## CH 3 Band edge





## CH 9 Band edge





## CHAIN 2



### CH 3




### CH 6




### CH 9



### CH 3 Band edge



### CH 9 Band edge



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---