

# Standalone SAR test exclusion considerations

November 18, 2014

- Device category =  Portable device  Mobile device
- Transmitting mode =  Single Transmitting  Simultaneous Transmitting
- Max. transmitting frequency = **2480** MHz
- Min. test separation distance = **200** mm
- Max. Antenna Gain = **1.57** dBi
- Max. power with turn-up tolerance = **10.00** dBm = **10.0** mW ( Typical Power = **Max. 10.00** dBm )

Note. **This device does not transmit simultaneously.**

## KDB 447498 D01 clause 4.3.1 Step 2-2) SAR test exclusion thresholds for 1500MHz to 6GHz at test separation distances > 50 mm

[ Threshold at 50 mm + ( test separation distance - 50 mm ) X 10 ] mW

$$= [ 0.08 + ( 200\text{mm} - 50\text{mm} \times 10 ) ] = 1500.1$$

Note. The calculation result was rounded to one decimal place for comparison.

→ ***SAR evaluation for general population exposure conditions by measurement or numerical simulation is not required.***

## Maximum Permissible Exposure(MPE) evaluation for mobile device

$$S = P G / ( 4 R^2 \pi ) , \text{ mW/cm}^2$$

S = Maximum power density

P = Maximum power with turn-up tolerance

$$= 0.002856 \text{ mW/cm}^2$$

G = Numeric power gain of the antenna

R = Distance from transmitting antenna

**Conclusion: The exposure condition of this device is compliant with FCC rules.**

The limit for maximum permissible exposure = **1.000000 mW/cm<sup>2</sup>**