

EMISSION TEST REPORT

Test Report No. : 19I0053-02

OMRON Corporation

Model: G8C-214M

FCC Part 15 Subpart B

1. This test report shall not be reproduced except in full, without the written approval of A-Pex International Co., Ltd.
2. This test report does not constitute an endorsement by NIST/NVLAP or U.S. Government.
3. This equipment is in compliance with above regulation. We hereby certify that the data are contain a true representation of the emission profile.
4. The results in this report apply only to the sample tested.
5. This test report clearly shows that Keyless Entry System (Receiver), G8C-214M is in compliance with FCC Part 15 Subpart B Class B, specification.

Date of test: September 30, 1999 **Issued date:** October 7, 1999

Tested by: _____

Naoki Sakamoto
Engineer, EMC Dept.

Approved by: _____

Kazutoyo Nakanishi
Group Leader of EMC section

Form Version No. 1



This laboratory is registered by the NIST/NVLAP, U.S.A. The tests reported herein have been performed in accordance with its terms of registration.

Testing Laboratory

A-pex International Co., Ltd.

Telephone: +81 596 39 1485

108 Yokowa-cho, Ise-shi, Mie-ken 516-1106 JAPAN Facsimile: +81 596 39 0232

Table of Contents	Page
1 GENERAL INFORMATION	3
1.1 Product Description	4
1.2 Tested System Details	4
1.3 Tested Methodology	5
1.4 Test Facility	5
2 SYSTEM TEST CONFIGURATION	6
2.1 Operation Environment	6
2.2 Justification	6
2.3 EUT Exercise Software	6
2.4 Test Procedure	7
Figure 2.1 Configuration of Tested System	8
3 RADIATED MEASUREMENT PHOTOS	10
Figure 3.1 Radiated Measurement Photos	10
3.1 Measurement Uncertainty	11
4 RADIATED EMISSION DATA	12
4.1 Field Strength Calculation	13
5 TEST EQUIPMENT USED	14
APPENDIX	15
A:Test Data	A1 - A2

1 GENERAL INFORMATION

APPLICANT : OMRON Corporation

ADDRESS : 1-501, Yashirogaoka, Meito-ku, Nagoya-city
Aichi, 465-0051 Japan
Tel: +81-52-704-2525
Fax: +81-52-704-2769

REGULATION(S) : FCC Part 15 Subpart B, Class B

MODEL NUMBER : G8C-214M

SERIAL NUMBER : -

KIND OF EQUIPMENT : Keyless Entry System (Receiver)

TESTED DATE : September 30, 1999

RECEIPT DATE OF SAMPLE : September 24, 1999

TEST REPORT NUMBER : 19I0053-02

TEST SITE : A-PEX Yokowa NO.3 Open Test Site

1.1 Product Description

OMRON Corporation, Model G8C-214M (referred to as the EUT in this report) is a Keyless Entry System (Receiver).

The specification is as following :

Operation Frequency : 8.2MHz
Local Clock Frequency : 315MHz
Operation Voltage : DC 12V, 30mA

1.2 Tested System Details

The FCC IDs for all equipment, plus description of all cables used in the tested system are:

Model	FCC ID	Description	Cable description	Backshell Material
(1) OMRON M/N: G8C-214M S/N: - (EUT)	E4EG8C-214M	Keyless Entry System (Receiver)	Unshielded I/F Cable Unshielded DC Power Cable	P.V.C. P.V.C.
(2) OMRON M/N: G8D-522M-A S/N: -	E4EG8D-522M-A	Keyless Entry System (Transmitter)	-	-
(3) OMRON M/N: - S/N: -	N/A	Simulator	-	-
(4) Shin-kobe Electric Machinery Co., Ltd. M/N: 38 B/9R S/N: -	N/A	Battery	-	-

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi, Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

Test report
FCC ID : E4EG8C-214M
Our reference : 19I0053-02
Page : 5 of 15
Issued date : 99-10-07

1.3 Tested Methodology

Both conducted and radiated testing were performed according to the procedures in FCC/ANSI C63.4(1992). Radiated testing was performed at a distance of 3 meters from the antenna to EUT.

1.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at 108 Yokowa-cho, Ise-shi, Mie-ken 516-1106 Japan.
This site has been fully described in a report dated Aug. 1, 1997 submitted to FCC office, and Listed dated Sep. 16, 1997 (31040/SIT 1300F2).

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi, Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

2 SYSTEM TEST CONFIGURATION

2.1 Operation Environment

Radiation

Temperature : 26 Degree

Humidity : 55%

Power supply : DC 12V

2.2 Justification

The system was configured in typical fashion (as a customer would normally use it) for testing.

2.3 EUT Exercise Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to typical use.

The sequence is used:

Operation: Receiving mode

2.4 Test Procedure

2.4.1 Tabletop Equipment Radiated Emissions

EUT was placed on a platform of nominal size, 1m by 1.5m, raised 80cm above the conducting ground plane.

The rear of EUT, including peripherals was aligned and flush with rear of tabletop.

I/O cables that were connected to the peripherals were bundled in center.

They were folded back and forth forming a bundle 30cm to 40cm long and were hanged 40cm height to the ground plane.

Test was made with the antenna positioned in both the horizontal and vertical planes of polarization.

The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

The measurement distance was 3m.

Figure2.1 Configuration of Tested System

Front View

* Cabling was taken into consideration and test data was taken under worse case conditions.

Test report
FCC ID : E4EG8C-214M
Our reference : 19I0053-02
Page : 9 of 15
Issued date : 99-10-07

Top View

* Cabling was taken into consideration and test data was taken under worse case conditions.

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi, Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

Test report
FCC ID : E4EG8C-214M
Our reference : 19I0053-02
Page : 10 of 15
Issued date : 99-10-07

3 RADIATED MEASUREMENT PHOTOS

Figure 3.1 Radiated Measurement Photos

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi, Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

Test report
FCC ID : E4EG8C-214M
Our reference : 19I0053-02
Page : 11 of 15
Issued date : 99-10-07

3.1 Measurement Uncertainty

Radiated Emission Test

The measurement uncertainty (with a 95% confidence level) for this test was $\pm 3.3\text{dB}$.

The data listed in this test report has enough margin, more than 3.3dB.

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi, Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

4 RADIATED EMISSION DATA

The initial step in collecting radiated data was a spectrum analyzer peak scan of the measurement range(30MHz-1000MHz).
The final data was reported in the worst-case emissions.
The minimum margin to the limit is as follows :

Frequency (MHz)	Receiver Reading (dBuV)	Correction Factor (dBuV)	Field Strength (dBuV/m)	Limit (dBuV/m)	Margin (dBuV)
32.80	26.0	-3.2	22.8	40.0	17.2

* All readings are quasi-peak mode.

5.1 Field Strength Calculation

The field strength is calculated by adding the Antenna Factor, Cable Factor and Antenna Pad, and subtracting the Amplifier Gain from the measured reading. The sample calculation is as follows :

$$FS = RA + AF + CF + AT - AG$$

where FS = Field Strength
RA = Receiver Amplitude
AF = Antenna Factor
CF = Cable Factor
AT = Antenna Pad
AG = Amplifier Gain

Assume a receiver reading of 26.0 dBuV is obtained. The antenna Factor of 17.4 dB, Cable Factor of 1.5 dB and Antenna Pad of 6.0 dB is added. The Amplifier Gain of 28.1 dB is subtracted, giving a field strength of 22.8 dBuV/m.

$$FS = 26.0 + 17.4 + 1.5 + 6.0 - 28.1 = 22.8 \text{dBuV/m}$$

Test report
FCC ID : E4EG8C-214M
Our reference : 19I0053-02
Page : 14 of 15
Issued date : 99-10-07

6 TEST EQUIPMENT USED

INSTRUMENTS	Mfr.	MODEL	C/N	Calibrated Until
Pre Amplifier	Hewlett Puckered	8447D	AF1	November 30, 1999
Biconical Antenna	Schwarzbeck	BBA9106	BA2	April 30, 2000
Logperiodic Antenna	Schwarzbeck	UHALP9108-A	LA5	August 8 , 2000
Spectrum Analyzer	Hewlett Packard	8567A	SA4	November 30, 1999
Test Receiver	Rohde & Schwarz	ESVS-10	TR6	April 20, 2000

*All measurement equipment is traceable to national standard.

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi, Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232

Test report
FCC ID : E4EG8C-214M
Our reference : 19I0053-02
Page : 15 of 15
Issued date : 99-10-07

APPENDIX

A : Test Data

Radiated emissions : A1 to A2

Testing Laboratory

A-pex International Co., Ltd.

108 Yokowa-cho, Ise-shi, Mie-ken 516-1106 JAPAN

Telephone: +81 596 39 1485

Facsimile: +81 596 39 0232