



5473A Clouds Rest Road : Mariposa, CA 95338 : Phone 209-966-5420 : Fax 209-742-6133

FCC 1.1310(b), Maximum Permissible Exposure Calculations RSS133 Sun clause 8 Exposure of Humans to RF Field

Date of Report: 8/12/05

Calculations prepared for:

Printronic

PO Box 19559

Irvine CA 92623-9559

Calculations prepared by:

Eddie Wong

110 N. Olinda Place

Brea, CA 9283

Model Number: SL-5304R MP2

FCC Identification: NA

Fundamental Operating Frequency:

902-928MHz

Maximum Rated Output Power:

0.0008

Measured Output Power:

0.0008

MPE Limit in accordance with 1.1310(b): Limits for general population/uncontrolled exposure

MPE Limit for 902-928 MHz = 0.6 mW/cm^2 (6 W/m^2)

1

Power Output (Watts)	Power Density Limit (mW/cm ²)	Minimum Distance (Meters)
0.0008	0.6	0.003m

$$\text{Power Density (W/m}^2\text{)} = \frac{30 \times P_t \times G}{d^2 \times Z_0}$$

P_t = Power Delivered to the Antenna
 d = Distance in meters

G = Antenna Gain
 Z_0 = Impedance of Free Space

The typical antennas to be used with the EUT are structure mount antennas which under normal operation has an enclosure that keep a distance of at least 0.1 m from the user. As can be seen from the MPE result, this device passes the limit specified in 1.1310 at a distance of 0.003 meter.

Calculation:

$$d = \sqrt{\frac{30 \times 0.0008 \times 1}{6 \times 377}}$$

$$= 0.003 \text{ meter.}$$