

Specifications

Product specifications

Platform Support	PC
Software Drivers	Windows 95/98/ME/NT/2000
Hardware Interfaces	915MHz (U.S.) or 433MHz (other countries) proprietary radio interface RS-232 to computer via MeetingPad Manager receiver
Resolution	1000 lines per inch / 39.37 lines per mm
Sensing Proximity	0.25 in / 6 mm above writing surface
Technology	Patented electromagnetic position-sensing
Power Supply	Internal rechargeable batteries, with external charger
Battery Life (pen)	Approximately 200 hours of continuous use
Battery Life (tablet)	Approximately 35 hours of continuous use per charge
Charging time	3 hours or less
Certification	FCC Part 15 Subpart B (Class B) and Subpart C EN55022, ETS 300 683 (1997), ETS 300 220-1 (2000-09)
Operating Temperature	40 to 115°F / 5 to 40°C

Tablet Physical Dimensions (measurements include pen tray and control box)

Active Area	10.0 in / 25.4 cm diagonal	(6.0 in H x 8.0 in W / 15.2 cm H x 20.3 cm W)
Width	11.9 in / 30.2 cm	
Height	11.2 in / 28.4 cm	
Depth	1.6 in / 4.1 cm	
Weight	2 lb, 2 oz / 0.96 kg	

MeetingPad Manager Physical Dimensions

Width	3.2 in / 8.1 cm
Height	4.2 in / 10.6 cm
Depth	1.9 in / 4.8 cm (915MHz version), 3.5 in / 8.9 cm (433MHz version)
Weight	0 lb, 5 oz / 0.14 kg

- END -