



REPORT No.: SZ20050353S01

RF EXPOSURE EVALUATION REPORT

APPLICANT : Nortek Security & Control LLC

PRODUCT NAME : Edge Remote Keypad

MODEL NAME : 2GIG-EDG-RK

BRAND NAME : 2GIG

FCC ID : EF400189

STANDARD(S) : 47CFR 2.1091
KDB 447498

RECEIPT DATE : 2020-06-16

TEST DATE : 2020-06-18 to 2020-06-29

ISSUE DATE : 2020-07-07

Edited by: Chen Bilian
Chen Bilian (Rapporteur)

Approved by: Peng Huarui
Peng Huarui (Supervisor)

NOTE: This document is issued by MORLAB, the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

SHENZHEN MORLAB COMMUNICATIONS TECHNOLOGY Co., Ltd.
FL1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen , Guangdong Province, P. R. China

Tel: 86-755-36698555
Http://www.morlab.cn

Fax: 86-755-36698525
E-mail: service@morlab.cn





DIRECTORY

1. Technical Information	3
1.1 Applicant and Manufacturer Information	3
1.2 Equipment under Test (EUT) Description	3
1.3 Applied Reference Documents	4
2. Device Category and RF Exposure Limit	5
3. RF Output Power	6
4. RF Exposure Evaluation	8
Annex A General Information	9

Change History		
Version	Date	Reason of Changed
1.0	2020-07-07	Original



1. Technical Information

Note: Provide by applicant.

1.1 Applicant and Manufacturer Information

Applicant:	Nortek Security & Control LLC
Applicant Address:	5919 Sea Otter Place, Carlsbad, CA 92010, United States
Manufacturer:	Flextronics Electronics Technology (Shenzhen) Co., Ltd
Manufacturer Address:	89 Yong Fu Road, Tong Fu Yu Industrial Park, Fu Yong Town, Bao An District, Shenzhen, Guangdong, 518103, China

1.2 Equipment under Test (EUT) Description

Product Name:	Edge Remote Keypad
Serial No:	(N/A, marked #1 by test site)
Hardware Version:	2GIG-EDG-RK
Software Version:	20200426. 002457
Frequency Bands:	WLAN 2.4GHz: 2412 MHz ~ 2462 MHz WLAN 5.2GHz: 5180 MHz ~ 5240 MHz WLAN 5.8GHz: 5745 MHz ~ 5825 MHz
Modulation Mode:	802.11b: DSSS 802.11a/g/n-HT20/HT40: OFDM
Antenna Type:	FPC Antenna
Antenna Gain:	WLAN 2.4GHz: 2.1dBi WLAN 5GHz: 3.4dBi



1.3 Applied Reference Documents

Leading reference documents for testing:

No.	Identity	Document Title	Method determination /Remark
1	47 CFR§2.1091	Radio Frequency Radiation Exposure Evaluation: mobile devices	No deviation
2	KDB 447498 D01v06	General RF Exposure Guidance	No deviation
Note 1: Additions to, deviation, or exclusions from the method shall be judged in the "method determination" column of add, deviate or exclude from the specific method shall be explained in the "Remark" of the above table.			



2. Device Category and RF Exposure Limit

Per user manual, Based on 47CFR 2.1091, this device belongs to mobile device category with General Population/Uncontrolled exposure.

Mobile Devices:

47CFR 2.1091(b)

For purposes of this section, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 centimeters is normally maintained between the transmitter's radiating structure(s) and the body of the user or nearby persons. In this context, the term "fixed location" means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 centimeter separation requirement.

General Population/Uncontrolled Exposure:

The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity. Warning labels placed on low-power consumer devices such as cellular telephones are not considered sufficient to allow the device to be considered under the occupational/controlled category, and the general population/uncontrolled exposure limits apply to these devices.

Table 1—Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	-	-	f/1500	30
1500-100,000	-	-	1.0	30

f = frequency in MHz* = Plane-wave equivalent power density



3. RF Output Power

<WLAN 2.4GHz>

2.4GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
	802.11b 1Mbps	CH 1	2412	12.84	14.00	97.62
		CH 6	2437	12.51	14.00	
		CH 11	2462	13.29	14.00	
	802.11g 6Mbps	CH 1	2412	13.24	14.00	86.45
		CH 6	2437	12.87	14.00	
		CH 11	2462	13.10	14.00	
	802.11n-HT20 MCS0	CH 1	2412	13.47	14.00	85.19
		CH 6	2437	12.94	14.00	
		CH 11	2462	13.27	14.00	
	802.11n-HT40 MCS0	CH 3	2422	13.65	14.00	74.36
		CH 6	2437	12.86	14.00	
		CH 9	2452	12.72	14.00	

<WLAN 5GHz>

5.2GHz WLAN	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
	802.11a 6Mbps	CH 36	5180	15.42	16.00	87.18
		CH 44	5220	15.83	16.00	
		CH 48	5240	15.86	16.00	
	802.11n-HT20 MCS0	CH 36	5180	14.88	16.00	85.16
		CH 44	5220	15.02	16.00	
		CH 48	5240	15.26	16.00	
	802.11n-HT40 MCS0	CH 38	5190	14.79	16.00	74.93
		CH 46	5230	14.98	16.00	



	Mode	Channel	Frequency (MHz)	Average power (dBm)	Tune-up Power	Duty Cycle %
5.8GHz WLAN	802.11a MCS0	CH 149	5745	11.97	12.00	87.18
		CH 157	5785	15.05	16.00	
		CH 165	5825	15.08	16.00	
	802.11n-HT20 MCS0	CH 149	5745	14.47	15.00	85.16
		CH 157	5785	14.24	15.00	
		CH 165	5825	14.21	15.00	
	802.11n-HT40 MCS0	CH 151	5755	14.47	15.00	74.93
		CH 159	5795	14.16	15.00	

Note 1: According to KDB 447498 Section 4.3, MPE evaluation is based on source-based time-averaged maximum conducted output power of the RF channel requiring evaluation, adjusted for tune-up tolerance, and the minimum test separation distance required for the exposure conditions.

Note 2: The output power refers to report (Report No.: SZ20050353W01/W02).

4. RF Exposure Evaluation

➤ Standalone Transmission Evaluation:

Bands	Maximum Tune-up Power(dBm)	Antenna Gain (dBi)	EIRP (mW)	Power Density (mW/cm ²)	Limit for MPE (mW/cm ²)
WLAN 2.4GHz	14.00	2.1	40.74	0.008	1.0
WLAN 5GHz	16.00	3.4	87.10	0.017	1.0

Note:

1. The WLAN 2.4G, WLAN 5G transmitter share the same antenna, Therefore simultaneous transmission assessment is not required.
2. For 5GHz WLAN, only the worst case will be used for calculating the power density.
3. MPE calculate method

$$\text{Power Density} = \text{EIRP}/4\pi R^2$$

Where: EIRP = P+G

P = Output Power (dBm)

G = Antenna Gain (dBi)

R = Separation Distance (20cm)

➤ Simultaneous Transmission Evaluation:

This device contains transmitters that cannot operate simultaneously, therefore simultaneous transmission analysis is not required.

➤ Conclusion:

According to 47 CFR §2.1091, this device complies with human exposure basic restrictions.



Annex A General Information

1. Identification of the Responsible Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Laboratory Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525

2. Identification of the Responsible Testing Location

Name:	Shenzhen Morlab Communications Technology Co., Ltd. Morlab Laboratory
Address:	FL.3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

3. Facilities and Accreditations

The FCC designation number is CN1192, the test firm registration number is 226174.

_____ END OF REPORT _____