

FCC RF Exposure Exemption report
for

Edge Touch

Model No.: 2GIG TOUCH-NA-VA;

2G1G TOUCH-NA-AA

FCC ID: EF400264

of

Applicant: Nice North America LLC
Address: 5919 Sea Otter Place Suite 100 Carlsbad CA 92010

Tested and Prepared

by

Worldwide Testing Services (Taiwan) Co., Ltd.

FCC Registration No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634



Report No.: W6M22505-24445-EE



Registration number: W6M22505-24445-EE

FCC ID: EF400264

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	2
1.1	NOTES	2
1.2	TESTING LABORATORY	2
1.3	APPLICATION DETAILS.....	3
1.4	GENERAL INFORMATION OF TEST ITEM.....	4
1.5	TEST STANDARDS	5
2	TEST CONFIGURATION	6
2.1	TEST ENVIRONMENT	6
2.2	MEASUREMENT UNCERTAINTY	6
2.3	TEST EQUIPMENT LIST.....	6
3	EQUIVALENT ISOTROPIC RADIATED POWER (EIRP).....	7
3.1	EXEMPTION LIMITS FOR ROUTINE EVALUATION	7



Registration number: W6M22505-24445-EE

FCC ID: EF400264

1 General Information

1.1 Notes

The purpose of conformity testing is to increase the probability of adherence to the essential requirements or conformity specifications, as appropriate.

The complexity of the technical specifications, however, means that full and thorough testing is impractical for both technical and economic reasons.

Furthermore, there is no guarantee that a test sample which has passed all the relevant tests conforms to a specification.

Neither is there any guarantee that such a test sample will interwork with other genuinely open systems.

The existence of the tests nevertheless provides the confidence that the test sample possesses the qualities as maintained and that its performance generally conforms to representative cases of communications equipment.

Laboratory disclaimer-

1. The test results of this test report relate exclusively to the item tested as specified in 1.5.
2. The test report may only be reproduced or published in full.
3. Reproduction or publication of extracts from the report requires the prior written approval of the Worldwide Testing Services(Taiwan) Co., Ltd.
4. Antenna gain is provided by applicant and laboratory issue relevant data and results.

Tester:

June 11, 2025

Ken Kang

Date

WTS-Lab.

Name

Signature

Technical responsibility for area of testing:

June 11, 2025


Kevin Wang

Date

WTS

Name

Signature



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22505-24445-EE

FCC ID: EF400264

1.2 Testing laboratory

1.2.1 Location

10m OATS

No.5-1, Lishui, Shuang Sing Village, Wanli Dist.,
New Taipei City 207, Taiwan (R.O.C.)

3 meter semi-anechoic chamber/Conducted Emission

No. 99, Sec. 1, Balian Rd., Xizhi Dist.,
New Taipei City 221032, Taiwan (R.O.C.)

Worldwide Testing Services (Taiwan) Co., Ltd.

6F., No. 58, Ln. 188, Ruiguang Rd., Neihu Dist.,

Taipei City 114, Taiwan (R.O.C.)

Tel: 886-2-6606-8877

1.2.2 Details of accreditation status

Accredited testing laboratory

FCC filed test laboratory Reg. No.: TW1072, TW1140, TW1146, TW1477, TW0037

Industry Canada filed test laboratory Reg. No.: 20037, 31634

Test location, where different from Worldwide Testing Services (Taiwan) Co., Ltd. :

Name: ./.

Accredited no.: ./.

Street: ./.

Town: ./.

Country: ./.


1.3 Application details

Approval holder

Name: Nice North America LLC
Street: 5919 Sea Otter Place Suite 100
City: Carlsbad CA 92010
Country: USA

Manufacturer: (if applicable)

Name: CLIMAX TECHNOLOGY CO., LTD.
Street: No. 258, Sinhu 2nd Rd., Neihu District,
Town: Taipei City 114,
Country: Taiwan (R.O.C.)



Registration number: W6M22505-24445-EE

FCC ID: EF400264

Date of receipt of test item: May 22, 2025

Date of test: from May 23, 2025 to June 11, 2025

1.4 General information of Test item

Type of test item: Edge Touch

Model no.: 2GIG TOUCH-NA-VA; 2G1G TOUCH-NA-AA

Multi-listing model no.: ./.

Brand name: 2GIG

Power supply: Adapter (I/P: 100-240Va.c. 50/60Hz 0.6A Max
O/P: 14V=1.7A)

Battery 3.7V, 2500mAh, 9.25W

Type of antenna: Monopole antenna

Antenna gain: WLAN & BT & BLE: 4.17723dBi

LTE

Part 2/22/24/27


Band 2: 2.83 dBi 、 Band 4: 1.53 dBi 、 Band 5: 0.16 dBi 、

Band 12: 1.32 dBi 、 Band 13: 1.71 dBi 、 Band 25: 2.83 dBi
、 Band 26: 0.16 dBi

Part 90: Band 26: 0.16 dBi

Technical data:

WLAN		
Mode	Channel	Conducted Power (dBm)
802.11b	Ch 1 : 2412 MHz	19.49
	Ch 6 : 2437 MHz	19.04
	Ch 11 : 2462 MHz	18.67
802.11g	Ch 1 : 2412 MHz	16.64
	Ch 6 : 2437 MHz	16.30
	Ch 11 : 2462 MHz	15.98
802.11n 20MHz	Ch 1 : 2412 MHz	16.68
	Ch 6 : 2437 MHz	16.34
	Ch 11 : 2462 MHz	16.00
802.11n 40MHz	Ch 1 : 2422 MHz	16.36
	Ch 4 : 2437 MHz	16.47
	Ch 7 : 2452 MHz	9.83



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22505-24445-EE

FCC ID: EF400264

BT			
Band	Mode	Channel	Power(dBm)
2.4GHz	BR	Ch 0 : 2402 MHz	6.74
		Ch 39 : 2441 MHz	7.01
		Ch 78 : 2480 MHz	7.03
	EDR	Ch 0 : 2402 MHz	7.37
		Ch 39 : 2441 MHz	8.16
		Ch 78 : 2480 MHz	7.52
	BLE 1M	Ch 0 : 2402 MHz	6.68
		Ch 19 : 2440 MHz	6.99
		Ch 39 : 2480 MHz	7.01

LTE		
Band	Channel/Frequency(MHz)	EIRP/ERP (dBm)
Band 2	18900/1880	23.64
Band 4	20050/1720	23.54
Band 5	20600/844	24.31
Band 12	23173/715.3	24.02
Band 13	23255/784.5	24.21
Band 25	26365/1882.5	23.56
Band 26 (Part 2/22/24/27)	27033/848.3	24.27
Band 26 (Part 90)	26740/819	23.89

Operation modes:

Duplex

Modulation type:

WLAN & BT & BLE:

O-QPSK 、DSSS/OFDM 、GFSK 、 $\pi/4$ DQPSK 、8DPSK

LTE: QPSK, 16QAM

Sample no.:

#01


Classification:

Fixed Device	☒
Mobile Device (Human Body distance > 20cm)	☐
Portable Device (Human Body distance < 20cm)	☐

1.5 Test standards

15 SUBPART C § 15.247 (2023-10)

47CFR Part 22 (2023-10), Part 24 (2023-10), Part 27 (2023-10) and Part 90 (2024-10)



Registration number: W6M22505-24445-EE

FCC ID: EF400264

2 Test configuration

2.1 Test environment

Relative humidity content: 20 ... 75 %

Air pressure: 86 ... 103 kPa

Extreme conditions parameters: ./.

2.2 Measurement uncertainty

Test item Name	Uncertainty
Estimation Result of Uncertainty of Conducted Output Power Measurement (Peak Output Power (transmitter))	Expanded Uncertainty : 1.63 dB

The decision rule is: Measurement uncertainty is not included in the calculation of test results.

2.3 Test Equipment List

Max Output Power

WLAN & BT & BLE

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2025/2/14	2026/2/13
ETSTW-RE 055	SPECTRUM ANALYZER	FSU 26	200074	R&S	2025/3/5	2026/3/4
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2025/2/14	2026/2/13
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2025/2/14	2026/2/13

LTE

Code No.	Test equipment	Mode No.	Serial No.	Brand	Cal. Date	Next Cal. Date
ETSTW-RE 050	Attenuator 10dB	50HF-010-1	None	JFW	2025/2/14	2026/2/13
ETSTW-RE 099	DC Block	50DB-007-1	None	JFW	2025/2/14	2026/2/13
ETSTW-GSM 003	Radio Communication Analyzer	MT8820C	6201342073	Anritsu	2025/5/8	2026/5/7
ETSTW-Cable 030	Microwave Cable	SUCOFLEX 104 (S_Cable 9)	279067	HUBER+SUHNER	2024/8/26	2025/8/25



Registration number: W6M22505-24445-EE

FCC ID: EF400264

3 Equivalent Isotropic Radiated Power (EIRP)

3.1 Exemption Limits for Routine Evaluation

according to 47 CFR FCC Part 2 Subpart J, section 2.1091

FCC OET Bulletin 65 Edition 97.01 determines the equations for predicting RF fields and applicable limits.

The prediction for power density in the far-field but will over-predict power density in the near field, where it could be used for walking a “worst case” or conservative prediction.

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 20 cm normally can be maintained between the user and the device.

MPE Calculation Method

(A) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f ²)*	6
30-300	61.4	0.163	1.0	6
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6

(B) Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	--	--	f/1500	30
1500-100,000	--	--	1.0	30

f = frequency in MHz


*Plane-wave equivalent power density

E = Electric field (V/m) P = output power (W) G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2} \quad \text{mW/cm}^2.$$



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22505-24445-EE


FCC ID: EF400264

WLAN

Band	Frequency (MHz)	Max output power (dBm)	Antenna Gain (dBi)	Power density (mW/cm ²)	Limit (mW/cm ²)	Ratio
802.11b	Ch 1 : 2412 MHz	19.49	4.17723	0.0463	1	0.0463
	Ch 6 : 2437 MHz	19.04	4.17723	0.0417	1	--
	Ch 11 : 2462 MHz	18.67	4.17723	0.0383	1	--
802.11g	Ch 1 : 2412 MHz	16.64	4.17723	0.024	1	--
	Ch 6 : 2437 MHz	16.30	4.17723	0.0222	1	--
	Ch 11 : 2462 MHz	15.98	4.17723	0.0206	1	--
802.11n 20MHz	Ch 1 : 2412 MHz	16.68	4.17723	0.0243	1	--
	Ch 6 : 2437 MHz	16.34	4.17723	0.0224	1	--
	Ch 11 : 2462 MHz	16.00	4.17723	0.0207	1	--
802.11n 40MHz	Ch 1 : 2422 MHz	16.36	4.17723	0.0225	1	--
	Ch 4 : 2437 MHz	16.47	4.17723	0.0231	1	--
	Ch 7 : 2452 MHz	9.83	4.17723	0.005	1	--

Bluetooth

Band	Frequency (MHz)	Max output power (dBm)	Antenna Gain (dBi)	Power density (mW/cm ²)	Limit (mW/cm ²)	Ratio
BR	Ch 0 : 2402 MHz	6.74	4.17723	0.0024	1	--
	Ch 39 : 2441 MHz	7.01	4.17723	0.0026	1	--
	Ch 78 : 2480 MHz	7.03	4.17723	0.0026	1	--
EDR	Ch 0 : 2402 MHz	7.37	4.17723	0.0029	1	--
	Ch 39 : 2441 MHz	8.16	4.17723	0.0034	1	0.0034
	Ch 78 : 2480 MHz	7.52	4.17723	0.0029	1	--
BLE 1M	Ch 0 : 2402 MHz	6.68	4.17723	0.0024	1	--
	Ch 19 : 2440 MHz	6.99	4.17723	0.0026	1	--
	Ch 39 : 2480 MHz	7.01	4.17723	0.0026	1	--



Worldwide Testing Services(Taiwan) Co., Ltd.

Registration number: W6M22505-24445-EE

FCC ID: EF400264

LTE

Band	Frequency (MHz)	Max output power (dBm)	Antenna Gain (dBi)	Power density (mW/cm ²)	Limit (mW/cm ²)	Ratio
Band 2	18900/1880	23.64	2.83	0.0882	1	--
Band 4	20050/1720	23.54	1.53	0.0639	1	--
Band 5	20600/844	24.31	0.16	0.0557	0.5626	--
Band 12	23173/715.3	24.02	1.32	0.068	0.4768	--
Band 13	23255/784.5	24.21	1.71	0.0777	0.523	0.1486
Band 25	26365/1882.5	23.56	2.83	0.0866	1	--
Band 26 (Part 2/22/24/27)	27033/848.3	24.27	0.16	0.0552	0.5655	--
Band 26 (Part 90)	26740/819	23.89	0.16	0.0505	0.546	--

From the peak EUT RF output power, the minimum mobile separation distance, $d = 20$ cm, as well as the gain of the used antenna, the RF power density can be obtained.

Simultaneous evaluation-

0.0463 (WLAN 2.4G) + 0.0034 (Bluetooth) + 0.1486 (LTE) = $0.1983 < 1$