

2. TEST STATEMENT

2.1 TEST STATEMENT

TO whom it may concern,

This letter is to explain the test condition of this project.
The EUT be tested as the following status.

RESOLUTION : 640 * 480

The data was shown in this report reflects the worst-case data
for the condition as listed above.

2. TEST STATEMENT

2.2 DEPARTURE FROM DOCUMENT POLICIES, PROCEDURE OR SPECIFICATIONS

DID HAVE
ANY DEPARTURE FROM DOCUMENT POLICIES
& PROCEDURES OR FROM SPECIFICATIONS.

YES _____, NO N/A .

IF YES, THE DESCRIPTION AS BELOW.

2.3 TEST STATEMENT

1. THE CERTIFICATE OR REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL, WITHOUT THE WRITTEN APPROVAL OF THE LABORATORY.
2. THE REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT ENDORSEMENT BY NVLAP OR ANY AGENCY OF THE U.S. GOVERNMENT.

3. EUT MODIFICATIONS

THE FOLLOWING ACCESSORIES WERE ADDED TO THE EUT
DURING TESTING:

NO MODIFICATION BY SRT LAB.

4. MODIFICATION LETTER

THIS SECTION CONTAINS THE FOLLOWING DOCUMENTS:

A. LETTER OF MODIFICATIONS

MACROTEK INTERNATIONAL CORP.
Manufacturers & Exporters

2 FL. NO. 29, LANE 46
KWANG FU S. ROAD
TAIPEI TAIWAN R.O.C.
TEL: 886-2-5785015-5782217
FAX: 886-2-5780827-5780868

Federal Communications Commission
Authorization and Evaluation Division
7435 Oakland Mills Road
Columbia, MD 21046

To whom it may concern :

This is to serve as proper notice that our company agrees to make
all modifications to FCC ID : EF9CS-4000 as listed in
section 3.0 of modification to submitted by Spectrum Research and
Testing Laboratory, Inc.

Respectfully,

Dinkai Chen
(Name, Surname)

Effective Dates :

From 1999 to 2004

Vice President
(Position/Title)

DATE : 1999/1/5

5. CONDUCTED POWER LINE TEST

5.1 TEST EQUIPMENT

THE FOLLOWING TEST EQUIPMENT WAS USED DURING THE CONDUCTED POWER LINE TEST :

EQUIPMENT/ FACILITIES	SPECIFICAT - IONS	MANUFACTURER	MODEL#/ SERIAL#	DATE OF CAL. & CAL. CENTER	DUE DATE
SPECTRUM ANALYZER	9 KHz TO 1 GHz	HP	8590L/ 3624A01317	AUGUST, 1998 ETC	1Y
EMI TEST RECEIVER	9 KHz TO 30 MHz	ROHDE & SCHWARZ	ESHS30/ 826003/008	AUGUST, 1998 ETC	1Y
LISN	50 uH, 50 ohm	SOLAR ELECTRONICS	9252-50- R24-BNC/ 951315	AUGUST, 1998 ETC	1Y
LISN	50 uH, 50 ohm	SOLAR ELECTRONICS	9252-50- R24-BNC/ 951318	AUGUST, 1998 ETC	1Y
SIGNAL GENERATOR	9 KHz TO 1080 MHz	ROHDE & SCHWARZ	SMY01/ 841104/019	APRIL, 1998 ITRI	1Y
POWER CONVERTER	0 TO 300 VAC 47 - 500 Hz	AFC	AFC-1KW/ 850510	APRIL, 1998 SRT	1Y

5.2 CONFIGURATION OF THE EUT

THE EUT WAS CONFIGURED ACCORDING TO ANSI C63.4 - 1992. ALL INTERFACE PORTS WERE CONNECTED TO THE APPROPRIATE PERIPHERALS. ALL PERIPHERALS AND CABLES ARE LISTED BELOW.

- EUT

DEVICE	MANUFACTURER	MODEL #	FCCID
SCANNER	MICROTEK INTERNATIONAL INC.	CS-4000	EF9CS-4000

- REMARK- INTERNAL DEVICESDEVICEMANUFACTURERMODEL #FCCID

-PERIPHERALS

DEVICE	MANUFAC -TURER	MODEL# / SERIAL#	FCCID	CABLE
MONITOR	OPTIQUEST	4500DC-E	GWGMULTI82	POWER-UNS DATA-S
PRINTER	HP	2225C	BS46XU2225C	POWER-UNS DATA-S
MODEM	DATARONICS	1200CK	E2050V-1200CK	POWER-UNS DATA-S
KEYBOARD	CHICONY	KKB-5162	E8H5IKKB-5162	DATA-UNS
MOUSE	HP	M-S34	DZL211029	DATA-UNS
PC	HP	SG60500383	B94VECTRA500T	POWER-UNS
SCANNER	POLAROLD	CS-1950	EF9PTS-1950	DATA-UNS

-REMARK

(1) . CABLE - UNS : UNSHIELDED CABLE
S : SHIELDED CABLE

(2) . CABLES - ALL 1m OR GREATER IN LENGTH-
BUNDLED ACCORDING TO ANSI C63.4 - 1992.

5.3 EUT OPERATING CONDITION



OPERATING CONDITION IS ACCORDING TO ANSI C63.4 - 1992.

1. EUT POWER ON.
2. "H" PATTERN SENT TO THE FOLLOWING PERIPHERALS :
 - PRINTER
 - MONITOR
 - MODEM
3. RESOLUTION : 640 * 480

5.4 TEST PROCEDURE

THE EUT WAS TESTED ACCORDING TO ANSI C63.4 - 1992. THE CONDUCTED TEST WAS PERFORMED IN AN ANECHOIC CHAMBER. THE FREQUENCY SPECTRUM FROM 0.45 MHz TO 30 MHz WAS INVESTIGATED. THE LISN USED WAS 50 ohm / 50 uHenry AS SPECIFIED BY SECTION 5.1 OF ANSI C63.4 - 1992. CABLES AND PERIPHERALS WERE MOVED TO FIND THE MAXIMUM EMISSION LEVELS FOR EACH FREQUENCY.

5.5 TEST SETUP

SEMI-ANECHOIC CHAMBER

5.6 CONDUCTED POWER LINE EMISSION LIMIT

FREQUENCY RANGE (MHz)	CLASS A	CLASS B
0.045 - 1.705	1000 uV	250 uV
1.705 - 30	3000 uV	250 uV

NOTE : IN THE ABOVE TABLE, THE TIGHTER LIMIT APPLIES AT THE BAND EDGES.

5.7 CONDUCTED POWER LINE TEST RESULT

THE FREQUENCY SPECTRUM FROM 0.45 MHZ TO 30 MHZ WAS INVESTIGATED. ALL READINGS ARE QUASI-PEAK VALUES WITH A RESOLUTION BANDWIDTH OF 9 KHZ.

TEMPERATURE : 28 C

HUMIDITY : 78 %RH

FREQUENCY (MHz)	LINE 1 (uv)	LINE 2 (uv)	LIMIT (uv)
0.53	*	22.13	250
0.60	11.22	*	250
0.83	10.72	17.78	250
1.05	20.42	29.17	250
10.7	69.18	34.28	250
28.6	54.33	60.26	250

REMARKS : (1).* = MEMENT DOES NOT APPLY FOR THIS FREQUENCY

(2).UNCERTAINTY IN CONDUCTED EMISSION MEASURED IS
<+/-2dB

(3).RESOLUTION : 640 * 480

(4).TEST CONFIGURATION PLEASE SEE 5.2

(5).TEST EQUIPMENT PLEASE SEE 5.1

(6).ANY DEPARTURE FROM SPECIFICATION:N/A

SIGNED BY TESTING ENGINEER : John G. Johnson

6. RADIATED EMISSION TEST

6.1 TEST EQUIPMENT

THE FOLLOWING TEST EQUIPMENT WAS USED DURING THE
RADIATED EMISSION TEST :

EQUIPMENT / FACILITIES	SPECIFICAT - IONS	MANUFACTUR -ER	MODEL#/ SERIAL#	DATE OF CAL. & CAL. CENTER	DU E DA TE
RECEIVER	20 MHZ TO 1000 MHZ	R & S	ESVS 30/ 841977/003	APRIL, 1998 ITRI	1Y
SPECTRUM ANALYZER	100 Hz TO 1500 MHZ	HP	8568B/ 3019A05294	OCT, 1998 ETC	1Y
SPECTRUM ANALYZER	9 KHz TO 22 GHz	HP	8593E/ 3322A00670	APRIL, 1998 ITRI	1Y
SPECTRUM ANALYZER	100 Hz TO 1000 MHZ	IFR	A-7550/ 2684/1248	JULY, 1998 ETC	1Y
SIGNAL GENERATOR	9 KHz TO 1080 MHZ	ROHDE & SCHWARZ	SMY01/ 841104/019	APRIL, 1998 ITRI	1Y
DIPOLE ANTENNA	28 MHZ TO 1000 MHZ	EMCO	3121C/ 9003-535	NOV, 1998 SRT	1Y
DIPOLE ANTENNA	28 MHZ TO 1000 MHZ	EMCO	3121C/ 9611-1239	NOV, 1998 SRT	1Y
BI-LOG ANTENNA	26 MHZ TO 2000 MHZ	EMCO	3142/ 96081-1073	NOV, 1998 SRT	1Y
BI-LOG ANTENNA	26 MHZ TO 1100 MHZ	EMCO	3143/ 9509-1152	NOV, 1998 SRT	1Y
PRE-AMPLIFIER	0.1 MHZ TO 1300 MHZ	HP	8447D/ 2944A08402	APRIL, 1998 ITRI	1Y
PRE-AMPLIFIER	0.1 MHZ TO 1300 MHZ	HP	8447D/ 2944A06412	AUGUST, 1998 ETC	1Y
HORN ANTENNA	1 GHz TO 18 GHz	EMCO	3115/ 9012-3619	NOV, 1998 SRT	1Y

6.2 CONFIGURATION OF THE EUT

SAME AS SECTION 5.2 OF THIS REPORT.

6.3 EUT OPERATING CONDITION

SAME AS SECTION 5.3 OF THIS REPORT.

6.4 TEST PROCEDURE


THE EUT WAS TESTED ACCORDING TO ANSI C63.4 - 1992. THE RADIATED TEST WAS PERFORMED AT SRT LAB's OPEN SITE. THIS SITE IS ON FILE WITH THE FCC LABORATORY DIVISION, REFERENCE 31040/SIT.

THE FREQUENCY SPECTRUM FROM 30 MHZ TO 1 GHZ WAS INVESTIGATED. MEASUREMENTS WERE MADE AT THREE METERS WITH AN ADJUSTABLE DIPOLE ANTENNA. PERIPHERALS, CABLES, EUT ORIENTATION, AND ANTENNA HEIGHT WERE VARIED TO FIND THE MAXIMUM EMISSION FOR EACH FREQUENCY.

THE FREQUENCY SPECTRUM FROM 30 MHZ TO 2 GHZ WAS INVESTIGATED. THE MEASUREMENTS UNDER 1 GHZ WITH RESOLUTION BANDWIDTH OF 120 KHZ ARE QUASI-PEAK READING MADE AT THREE METERS USING AN ADJUSTABLE DIPOLE ANTENNA. PERIPHERALS, CABLES, EUT ORIENTATION, AND ANTENNA HEIGHT WERE VARIED TO FIND THE MAXIMUM EMISSION FOR EACH FREQUENCY.


THE MEASUREMENTS ABOVE 1 GHZ WITH A RESOLUTION BANDWIDTH OF 1 MHZ ARE PEAK READING AT A DISTANCE OF THREE METERS WITH A HORN ANTENNA.

6.5 RADIATED TEST SETUP



6.5 RADIATED TEST SETUP

ELECTRICAL AND ELECTRONIC EQUIPMENT IN THE RANGE OF 9 kHz TO 40 GHz

ANSI
C63.4-1992**LEGEND:**

1. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth forming a bundle 30 to 40 cm long, hanging approximately in the middle between ground plane and table.
2. I/O cables that are connected to a peripheral shall be bundled in center. The end of the cable may be terminated if required using correct terminating impedance. The total length shall not exceed 1 m.
3. If LISNs are kept in the test setup for radiated emissions, it is preferred that they be installed under the ground plane with the receptacle flush with the ground plane.
4. Cables of hand-operated devices, such as keyboards, mouses, etc., have to be placed as close as possible to the controller.
5. Non-EUT components of EUT system being tested
6. The rear of all components of the system under test shall be located flush with the rear of the table.
7. No vertical conducting wall used.
8. Power cords drape to the floor and are routed over to receptacle

6.6 RADIATED EMISSION LIMIT

ALL EMISSION FROM A DIGITAL DEVICE, INCLUDING ANY NETWORK OF CONDUCTORS AND APPARATUS CONNECTED THERETO, SHALL NOT EXCEED THE LEVEL OF FIELD STRENGTH SPECIFIED BELOW :

CLASS B

FREQUENCY (MHz)	DISTANCE (m)	FIELD STRENGTH (uV/m)
30 - 88	3	100
88 - 216	3	150
216 - 960	3	200
ABOVE 960	3	500

CLASS B (OPEN CASE)

FREQUENCY (MHz)	DISTANCE (m)	FIELD STRENGTH (uV/m)
30 - 88	3	199.5
88 - 216	3	298.5
216 - 960	3	398.1

CLASS A

FREQUENCY (MHz)	DISTANCE (m)	FIELD STRENGTH (uV/m)
30 - 88	3	316.3
88 - 216	3	473.2
216 - 960	3	613.0
ABOVE 960	3	1000.0

NOTE : 1. IN THE EMISSION TABLES ABOVE, THE TIGHTER LIMIT APPLIES AT THE BAND EDGES.

2. DISTANCE REFERS TO THE DISTANCE BETWEEN MEASURING INSTRUMENT, ANTENNA, AND THE CLOSEST POINT OF ANY PART OF THE DEVICE OR SYSTEM.

6.7 RADIATED EMISSION TEST RESULT

THE FREQUENCY SPECTRUM FROM 30 MHz TO 1 GHz WAS INVESTIGATED. ALL READINGS UNDER 1 GHz ARE QUASI-PEAK VALUES WITH A RESOLUTION BANDWIDTH OF 120 KHZ. MEASUREMENTS WERE MADE AT 3 METERS.

THE MEASUREMENTS ABOVE 1 GHz WITH A RESOLUTION BANDWIDTH OF 1 MHz ARE PEAK READING AT A DISTANCE OF 3 METERS.

TEMPERATURE : 28 C HUMIDITY : 78 %RH

FREQ. (MHz)	CABLE LOSS (dB)	ANT. FACTOR (dB)	READING (dBuV)		EMISSION (uV)		LMTS (uV)
			HORIZ	VERT	HORIZ	VERT	
99.89	0.6	11.9	24.0	23.1	66.83	60.26	150
113.3	0.8	11.3	10.7	8.70	13.80	10.96	150
138.8	0.6	11.0	17.2	13.7	27.54	18.41	150
165.0	0.9	12.5	16.0	14.7	29.51	25.41	150
180.0	1.0	11.9	16.1	15.2	28.18	25.41	150
430.0	2.0	18.6	18.8	16.5	93.33	71.61	200
629.5	1.8	21.5	13.8	12.8	71.61	63.83	200

REMARKS : (1). MEASUREMENT DOES NOT APPLY FOR THIS FREQUENCY.

(2). THE MAXIMUM CONDITION WAS WITH THE MONITOR POWER CORD CONNECTED TO THE PERSONAL COMPUTER.

(3). SAMPLE CALCULATION
 $20 \log(\text{EMISSION}) \text{uV/m} = \text{CABLE LOSS (dB)} + \text{FACTOR (dB)} + \text{READING (dBuV/m)}$

(4). RESOLUTION : 640 * 480

(5). TEST EQUIPMENT PLEASE SEE 6.1

(6). UNCERTAINTY IN RADIATED EMISSION MEASURED IS <+/-4dB

(7). ANY DEPARTURE FROM SPECIFICATION: N/A

SIGNED BY TESTING ENGINEER : John Smith