

CLASS B CERTIFICATION APPLICATION  
UNDER PART 15, SUBPART B

**EUT: SCANNER  
MODEL: DUOSCAN T1200  
FCC ID: EF9DUOSCANT1200**

SRT REPORT # T8D34-1

PREPARED FOR :

MICROTEK INTERNATIONAL INC.  
NO. 6, INDUSTRY E. RD. 3,  
SCIENCE-BASED INDUSTRIAL PARK,  
HSINCHU, TAIWAN, R.O.C.

EMI TESTING REPORT

EUT : SCANNER

MODEL: DUOSCAN T1200

FCCID: EF9DUOSCANT1200

PREPARED FOR:

MICROTEK INTERNATIONAL INC.

NO. 6, INDUSTRY E. RD. 3,

SCIENCE-BASED INDUSTRIAL PARK,

HSINCHU, TAIWAN, R.O.C.

PREPARED BY:

SPECTRUM RESEARCH & TESTING  
LABORATORY INC.

NO. 101-10, LING 8, SHAN-TONG LI  
CHUNG-LI CITY, TAOYUAN, TAIWAN, R.O.C.

TEL: (03) 4987684  
FAX: (03) 4986528

TABLE OF CONTENTS

1. TEST REPORT CERTIFICATION.....	4
2. TEST STATEMENT	
2.1 TEST STATEMENT.....	5
2.2 DEPARTURE FROM DOCUMENT POLICIES, PROCEDURE OR SPECIFICATIONS.....	6
3. EUT MODIFICATIONS.....	7
4. MODIFICATION LETTER.....	8
5. CONDUCTED POWER LINE TEST	
5.1 TEST EQUIPMENT.....	9
5.2 TEST PROCEDURE.....	10-11
5.3 EUT OPERATING CONDITION.....	12
5.4 TEST PROCEDURE.....	13
5.5 TEST SETUP.....	14
5.6 RADIATED EMISSION LIMIT.....	15
5.7 CONDUCTED POWER LINE TEST RESULT.....	16
6. RADIATED EMISSION TEST	
6.1 TEST EQUIPMENT.....	17
6.2 CONFIGURATION OF THE EUT.....	18
6.3 EUT OPERATING CONDITION.....	18
6.4 TEST PROCEDURE.....	18
6.5 TEST SETUP.....	19-20
6.6 RADIATED EMISSION LIMIT.....	21
6.7 RADIATED EMISSION TEST RESULT.....	22
7. PHOTOS OF TESTING.....	23-36

1. TEST REPORT CERTIFICATION

APPLICANT : MICROTEK INTERNATIONAL INC.

ADDRESS : NO. 6, INDUSTRY E. RD. 3,  
SCIENCE-BASED INDUSTRIAL PARK,  
HSINCHU, TAIWAN, R.O.C.

EUT DESCRIPTION : SCANNER

(A) POWER SUPPLY : 100-240V, 47-63Hz

(B) MODEL : DUOSCAN T1200

(C) FCC ID : EF9DUOSCANT1200

FINAL TEST DATE : 04/30/1998

MEASUREMENT PROCEDURE USED :

PART 15 SUB PART B OF FCC RULES AND

REGULATIONS ( 47 CFR PART 15 )

FCC / ANSI C63.4 - 1992

WE HEREBY SHOW THAT:

THE MEASUREMENTS SHOWN IN THE ATTACHMENT WERE  
MADE IN ACCORDANCE WITH THE PROCEDURES INDICATED,  
AND THE ENERGY EMITTED BY THE EQUIPMENT WAS  
FOUND TO BE WITHIN THE LIMITS APPLICABLE.

TESTING ENGINEER : Henry Lee DATE 4/30/98

SUPERVISOR : T. T. Lee DATE 4/30/98

APPROVED BY : W. L. Lee DATE 4/30/98

2. TEST STATEMENT

2.1 TEST STATEMENT

TO whom it may concern,

This letter is to explain the test condition of this project.  
The EUT be tested as the following status.

CPU: PENTIUM - 100 MHz

CPU Clock Signal: 66 MHz

The data shown in this report reflects the worst-case data for the condition as listed above.

2. TEST STATEMENT

2.2 DEPARTURE FROM DOCUMENT POLICIES, PROCEDURE OR SPECIFICATIONS

DID HAVE

ANY DEPARTURE FROM DOCUMENT POLICIES  
& PROCEDURES OR FROM SPECIFICATIONS.

YES \_\_\_\_\_, NO N/A .

IF YES, THE DESCRIPTION AS BELOW.

2.3 TEST STATEMENT

1. THE CERTIFICATE OR REPORT SHALL NOT BE REPRODUCED EXCEPT IN FULL, WITHOUT THE WRITTEN APPROVAL OF THE LABORATORY.
2. THE REPORT MUST NOT BE USED BY THE CLIENT TO CLAIM PRODUCT ENDORSEMENT BY NVLAP OR ANY AGENCY OF THE U.S. GOVERNMENT.

3. EUT MODIFICATIONS

THE FOLLOWING ACCESSORIES WERE ADDED TO THE EUT  
DURING TESTING:

NO MODIFICATION BY SRT LAB.

4. MODIFICATION LETTER

THIS SECTION CONTAINS THE FOLLOWING DOCUMENTS:

A. LETTER OF MODIFICATIONS

N/A

# MICROTEK

Microtek International Inc.

6, Industry East Road 3  
Science-Based Industry Park  
Hsinchu, Taiwan 30077, R.O.C.

Tel: 886-3-5772155  
Fax: 886-3-5772598

Federal Communications Commission  
Authorization and Evaluation Division  
7435 Oakland Mills Road  
Columbia, MD 21046

To whom it may concern:

This is to serve as proper notice that our company agrees to make all modifications to FCCID: EF9DUOSCANT1200 as listed in section 3.0 of the test report submitted by Spectrum Research and Testing Laboratory, Inc.

Respectfully,

Effective Dates:

S. J. Chu  
(Name, Surname)

From April 01, 98 to April 01, 99

Manager

(Position/Title)

DATE: 4/1/98

## 5. CONDUCTED POWER LINE TEST

## 5.1 TEST EQUIPMENT

THE FOLLOWING TEST EQUIPMENT WAS USED DURING THE CONDUCTED POWER LINE TEST :

EQUIPMENT/ FACILITIES	SPECIFICAT - IONS	MANUFACTURER	MODEL#/ SERIAL#	DATE OF CAL. & CAL. CENTER	DU E DATE
SPECTRUM ANALZER	9 KHz TO 1 GHz	HP	8590L/ 3624A01317	OCT, 1997 ETC	1Y
EMI TEST RECEIVER	9 KHz TO 30 MHz	ROHDE & SCHWARZ	ESHS30/ 893517/013	OCT, 1997 ETC	1Y
LISN	50 uH, 50 ohm	SOLAR ELECTRONICS	9252-50- R24-BNC/ 951315	AUGUST, 1997 ETC	1Y
LISN	50 uH, 50 ohm	SOLAR ELECTRONICS	9252-50- R24-BNC/ 951318	AUGUST, 1997 ETC	1Y
SIGNAL GENERATOR	9 KHz TO 1080 MHz	ROHDE & SCHWARZ	SMY01/ 841104/019	MAY, 1997 ETC	1Y
POWER CONVERTER	0 TO 300 VAC 47 - 500 Hz	AFC	AFC-1KW/ 850510	APRIL, 1998 SRT	1Y

## 5.2 CONFIGURATION OF THE EUT

THE EUT WAS CONFIGURED ACCORDING TO ANSI C63.4 - 1992.  
ALL INTERFACE PORTS WERE CONNECTED TO THE APPROPRIATE  
PERIPHERALS. ALL PERIPHERALS AND CABLES ARE LISTED  
BELOW.

### -EUT

DEVICE	MANUFACTURER	MODEL #	FCCID
SCANNER	MICROTEK INTERNATIONAL INC.	DUOSCAN T1200	EF9DUOSCANT1200

### -REMARK

### -INTERNAL DEVICES

<u>DEVICE</u>	<u>MANUFACTURER</u>	<u>MODEL #</u>	<u>FCCID</u>
POWER BOARD	KENTEX	01-311332503	N/A

-PERIPHERALS

DEVICE	MANUFAC-TURER	MODEL# / SERIAL#	FCCID	CABLE
MONITOR	PHILIPS	14B1320W	A3KM064	POWER-S DATA-S
PRINTER	HP	2225C+	DSI6XU2225C	POWER-UNS DATA-S
MODEM	SMARTTEAM	103/212A	EF56A5103/212A	POWER-UNS DATA-S
KEYBOARD	CHICONY	KKB-5162	E8H5IKKB-5162	DATA-UNS
MOUSE	LOGITECH	M-S34-6MD	DZL211029	DATA-UNS
PC	HP	VL SERIES 45/100	C94VECTRA500T	POWER-UNS

-REMARK

(1). CABLE - UNS : UNSHIELDED CABLE  
S : SHIELDED CABLE

(2). CABLES - ALL 1m OR GREATER IN LENGTH-  
BUNDLED ACCORDING TO ANSI C63.4 - 1992.

5.3 EUT OPERATING CONDITION



OPERATING CONDITION IS ACCORDING TO ANSI C63.4 - 1992.

1. EUT POWER ON.
2. "H" PATTERN SENT TO THE FOLLOWING PERIPHERALS:
  - PRINTER
  - MONITOR
  - MODEM
3. CPU : PENTIUM - 100MHZ  
CLOCK CHIP : 66MHz

#### 5.4 TEST PROCEDURE

THE EUT WAS TESTED ACCORDING TO ANSI C63.4 - 1992. THE CONDUCTED TEST WAS PERFORMED IN AN ANECHOIC CHAMBER. THE FREQUENCY SPECTRUM FROM 0.45 MHz TO 30 MHz WAS INVESTIGATED. THE LISN USED WAS 50 ohm / 50 uHenry AS SPECIFIED BY SECTION 5.1 OF ANSI C63.4 - 1992. CABLES AND PERIPHERALS WERE MOVED TO FIND THE MAXIMUM EMISSION LEVELS FOR EACH FREQUENCY.

## 5.5 TEST SETUP



5.6 CONDUCTED POWER LINE EMISSION LIMIT

FREQUENCY RANGE (MHz)	CLASS A	CLASS B
0.045 - 1.705	1000 uV	250 uV
1.705 - 30	3000 uV	250 uV

NOTE : IN THE ABOVE TABLE, THE TIGHTER LIMIT APPLIES AT THE BAND EDGES.

5.7 CONDUCTED POWER LINE TEST RESULT

THE FREQUENCY SPECTRUM FROM 0.45 MHZ TO 30 MHZ WAS INVESTIGATED. ALL READINGS ARE QUASI-PEAK VALUES WITH A RESOLUTION BANDWIDTH OF 9 KHZ.

TEMPERATURE : 28 C

HUMIDITY : 78 %RH

FREQUENCY (MHz)	LINE 1 (uv)	LINE 2 (uv)	LIMIT (uv)
0.81	18.20	20.18	250
1.14	12.74	13.49	250
1.73	5.888	12.30	250
11.1	10.72	11.48	250
20.4	*	29.51	250
28.6	10.96	*	250

REMARKS : (1).\* = MEMENT DOES NOT APPLY FOR THIS FREQUENCY

(2).UNCERTAINTY IN CONDUCTED EMISSION MEASURED IS  
<+/-2dB

(3).CPU: PENTIUM - 100MHz CLOCK CHIP : 66MHz

(4).TEST CONFIGURATION PLEASE SEE 4.2

(5).TEST EQUIPMENT PLEASE SEE 4.1

(6).ANY DEPARTURE FROM SPECIFICATION:N/A

SIGNED BY TESTING ENGINEER : \_\_\_\_\_

## 6. RADIATED EMISSION TEST

## 6.1 TEST EQUIPMENT

THE FOLLOWING TEST EQUIPMENT WAS USED DURING THE  
RADIATED EMISSION TEST :

EQUIPMENT / FACILITIES	SPECIFICAT -IONS	MANUFACTUR -ER	MODEL#/ SERIAL#	DATE OF CAL. & CAL. CENTER	DU E DATE
RECEIVER	20 MHz TO 1000 MHz	R & S	ESVS 30/ 841977/003	APRIL, 1998 ITRI	1Y
SPECTRUM ANALYZER	100 Hz TO 1500 MHz	HP	8568B/ 3019A05294	OCT, 1997 ETC	1Y
SPECTRUM ANALYZER	9 KHz TO 22 GHz	HP	8593E/ 3322A00670	OCT, 1997 ETC	1Y
SPECTRUM ANALYZER	100 Hz TO 1000 MHz	IFR	A-7550/ 2684/1248	AUGUST, 1997 ETC	1Y
SPECTRUM ANALYZER	9 KHz TO 2900 MHz	HP	8594A/ 3229A00399	MAY, 1997 ETC	1Y
SIGNAL GENERATOR	9 KHz TO 1080 MHz	ROHDE & SCHWARZ	SMY01/ 841104/019	MAY, 1997 ETC	1Y
DIPOLE ANTENNA	28 MHz TO 1000 MHz	EMCO	3121C/ 9003-535	DEC, 1997 SRT	1Y
DIPOLE ANTENNA	28 MHz TO 1000 MHz	EMCO	3121C/ 9611-1239	DEC, 1997 SRT	1Y
BI-LOG ANTENNA	26 MHz TO 2000 MHz	EMCO	3142/ 96081-1073	DEC, 1997 SRT	1Y
BI-LOG ANTENNA	26 MHz TO 1100 MHz	EMCO	3143/ 9509-1152	DEC, 1997 SRT	1Y
PRE-AMPLIFIER	0.1 MHz TO 1300 MHz	HP	8447D/ 2944A08402	APRIL, 1998 ITRI	1Y
PRE-AMPLIFIER	0.1 MHz TO 1300 MHz	HP	8447D/ 2944A06412	OCT, 1997 ETC	1Y
HORN ANTENNA	1 GHz TO 18 GHz	EMCO	3115/ 9012-3619	DEC, 1997 SRT	1Y

## 6.2 CONFIGURATION OF THE EUT

SAME AS SECTION 5.4 OF THIS REPORT.

## 6.3 EUT OPERATING CONDITION

SAME AS SECTION 5.3 OF THIS REPORT.

## 6.4 TEST PROCEDURE


THE EUT WAS TESTED ACCORDING TO ANSI C63.4 - 1992. THE RADIATED TEST WAS PERFORMED AT SRT LAB's OPEN SITE. THIS SITE IS ON FILE WITH THE FCC LABORATORY DIVISION, REFERENCE 31040/SIT.

THE FREQUENCY SPECTRUM FROM 30 MHZ TO 1 GHZ WAS INVESTIGATED. MEASUREMENTS WERE MADE AT THREE METERS WITH AN ADJUSTABLE DIPOLE ANTENNA. PERIPHERALS, CABLES, EUT ORIENTATION, AND ANTENNA HEIGHT WERE VARIED TO FIND THE MAXIMUM EMISSION FOR EACH FREQUENCY.


THE FREQUENCY SPECTRUM FROM 30 MHZ TO 2 GHZ WAS INVESTIGATED. THE MEASUREMENTS UNDER 1 GHZ WITH RESOLUTION BANDWIDTH OF 120 KHZ ARE QUASI-PEAK READING MADE AT THREE METERS USING AN ADJUSTABLE DIPOLE ANTENNA. PERIPHERALS, CABLES, EUT ORIENTATION, AND ANTENNA HEIGHT WERE VARIED TO FIND THE MAXIMUM EMISSION FOR EACH FREQUENCY.

THE MEASUREMENTS ABOVE 1 GHZ WITH A RESOLUTION BANDWIDTH OF 1 MHZ ARE PEAK READING AT A DISTANCE OF THREE METERS WITH A HORN ANTENNA.

### 6.5 RADIATED TEST SETUP



## 6.5 RADIATED TEST SETUP



1100-1101

- 1 Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth forming a bundle 30 to 40 cm long, hanging approximately in the middle between ground plane and table.
- 2 1/4" cables that are connected to a peripheral shall be bundled in center. The end of the cable may be terminated if required using correct terminating impedance. The total length shall not exceed 1 m.
- 3 If USNs are kept in the test setup for radiated emissions, it is preferred that they be installed under the ground plane with the receptacle flush with the ground plane.
- 4 Cables of hand operated devices, such as keyboards, mice, etc. have to be placed as close as possible to the controller.
- 5 Use of UUT components of EUT system being tested.
- 6 The rear of all components of the system under test shall be in contact with the rear of the table.
- 7 No vertical conducting wall used.
- 8 Power cords drape to the floor and are routed away to the rear.

## 6.6 RADIATED EMISSION LIMIT

ALL EMISSION FROM A DIGITAL DEVICE, INCLUDING ANY NETWORK OF CONDUCTORS AND APPARATUS CONNECTED THERETO, SHALL NOT EXCEED THE LEVEL OF FIELD STRENGTH SPECIFIED BELOW :

## CLASS B

FREQUENCY (MHz)	DISTANCE (m)	FIELD STRENGTH (uV/m)
30 - 88	3	100
88 - 216	3	150
216 - 960	3	200
ABOVE 960	3	500

## CLASS B ( OPEN CASE )

FREQUENCY (MHz)	DISTANCE (m)	FIELD STRENGTH (uV/m)
30 - 88	3	199.5
88 - 216	3	298.5
216 - 960	3	398.1

## CLASS A

FREQUENCY (MHz)	DISTANCE (m)	FIELD STRENGTH (uV/m)
30 - 88	3	316.3
88 - 216	3	473.2
216 - 960	3	613.0
ABOVE 960	3	1000.0

NOTE : 1. IN THE EMISSION TABLES ABOVE, THE TIGHTER LIMIT APPLIES AT THE BAND EDGES.

2. DISTANCE REFERS TO THE DISTANCE BETWEEN MEASURING INSTRUMENT, ANTENNA, AND THE CLOSEST POINT OF ANY PART OF THE DEVICE OR SYSTEM.

## 6.7 RADIATED EMISSION TEST RESULT

THE FREQUENCY SPECTRUM FROM 30 MHz TO 1 GHz WAS INVESTIGATED. ALL READINGS UNDER 1 GHz ARE QUASI-PEAK VALUES WITH A RESOLUTION BANDWIDTH OF 120 KHZ. MEASUREMENTS WERE MADE AT 3 METERS.

THE MEASUREMENTS ABOVE 1 GHz WITH A RESOLUTION BANDWIDTH OF 1 MHz ARE PEAK READING AT A DISTANCE OF 3 METERS.

TEMPERATURE : 28 C HUMIDITY : 78 %RH

FREQ. (MHz)	CABLE LOSS (dB)	ANT. FACTOR (dB)	READING (dBuV)		EMISSION (uV)		LMTS (uV)
			HORIZ	VERT	HORIZ	VERT	
74.600	0.6	8.00	26.54	25.45	57.15	50.41	100
208.45	1.2	10.3	28.10	21.62	95.50	45.29	150
219.45	1.3	10.4	29.84	22.57	119.4	51.70	200
228.85	1.3	11.8	27.85	14.58	111.6	24.21	200
299.66	1.4	13.7	27.15	22.94	129.6	79.80	200
479.11	1.9	17.5	18.81	17.54	81.38	70.31	200
549.92	2.1	19.3	17.84	17.19	91.62	85.02	200

REMARKS : (1). MEASUREMENT DOES NOT APPLY FOR THIS FREQUENCY.

(2). THE MAXIMUM CONDITION WAS WITH THE MONITOR POWER CORD CONNECTED TO THE PERSONAL COMPUTER.

(3). SAMPLE CALCULATION  
 $20 \log(\text{EMISSION}) \text{ uV/m} = \text{CABLE LOSS (dB)} + \text{FACTOR (dB)} + \text{READING (dBuV/m)}$

(4). CPU: 100MHz CLOCK CHIP: 66MHz

(5). TEST EQUIPMENT PLEASE SEE 5.1

(6). UNCERTAINTY IN RADIATED EMISSION MEASURED IS  $<+/-4\text{dB}$

(7). ANY DEPARTURE FROM SPECIFICATION:N/A

SIGNED BY TESTING ENGINEER : Teeling