


FCC PART 15 CLASS B
EMI MEASUREMENT AND TEST REPORT
FOR

MICROTEK LABS. INC.

3715 Doolittle Drive
Redondo, CA 90278

FCC ID: EF9ID-600

August 24, 1998

This Report Concerns: <input checked="" type="checkbox"/> Original Report	Equipment Type: Scanner - Subassembly, ITE
Test Engineer: Philip Wei	
Test Date: July 19, 1998	
Certified By:	 John Y. Chan - Director, Compliance Engineering
Prepared By:	Bay Area Compliance Laboratory Corporation 230 Commercial Street, Suite 2 Sunnyvale, CA 94086 (408) 732-9162

Note: This report may not be duplicated without prior written consent of Bay Area Compliance Laboratory Corporation. This report **must not** be used by the client to claim product endorsement by NVLAP or any agency of the U.S. Government.

TABLE OF CONTENTS

1 - GENERAL INFORMATION	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
1.2 OBJECTIVE	4
1.3 TEST METHODOLOGY	4
1.4 TEST FACILITY	4
1.5 TEST EQUIPMENT LIST AND DETAILS	5
1.6 EQUIPMENT UNDER TEST (EUT)	5
1.7 EUT CONFIGURATION DETAILS	5
1.8 HOST COMPUTER CONFIGURATION LIST AND DETAILS	6
1.10 EXTERNAL I/O CABLING LIST AND DETAILS	6
2 - SYSTEM TEST CONFIGURATION.....	7
2.1 JUSTIFICATION	7
2.2 EUT EXERCISE SOFTWARE	7
2.3 SPECIAL ACCESSORIES	7
2.4 SCHEMATICS / BLOCK DIAGRAM	7
2.5 CONFIGURATION OF TEST SYSTEM	8
2.6 TEST SETUP BLOCK DIAGRAM	9
2.7 EQUIPMENT MODIFICATIONS	10
3 - CONDUCTED EMISSIONS TEST DATA	11
3.1 MEASUREMENT UNCERTAINTY	11
3.2 EUT SETUP	11
3.3 SPECTRUM ANALYZER SETUP	11
3.4 TEST PROCEDURE	12
3.5 SUMMARY OF TEST RESULTS	12
3.6 CONDUCTED EMISSIONS TEST DATA	12
3.7 PLOT OF CONDUCTED EMISSIONS TEST DATA	12
4 - RADIATED EMISSION DATA	13
4.1 MEASUREMENT UNCERTAINTY	13
4.2 EUT SETUP	13
4.3 SPECTRUM ANALYZER SETUP	13
4.4 TEST PROCEDURE	14
4.5 CORRECTED AMPLITUDE & MARGIN CALCULATION	14
4.6 SUMMARY OF TEST RESULTS	14
4.7 RADIATED EMISSIONS TEST DATA	15
5- FCC PRODUCT LABELING AND WARNING STATEMENT.....	17
5.1 FCC ID LABEL	17
5.2 PROPOSED LABEL LOCATION ON EUT	17
5.3 FCC WARNING STATEMENT	17
6 - CONDUCTED AND RADIATED SETUP PHOTOGRAPHS.....	18
6.1 CONDUCTED EMISSION PHOTOGRAPH – FRONT VIEW	18
6.2 CONDUCTED EMISSION PHOTOGRAPH – REAR VIEW	19
6.3 RADIATED EMISSION PHOTOGRAPH – FRONT VIEW	20
6.4 RADIATED EMISSION PHOTOGRAPH – REAR VIEW	21
7 – PHOTOGRAPHS.....	22
7.1 EUT: FRONT VIEW	22
7.2 EUT: REAR VIEW	23
7.3 EUT: INSIDE COVER OFF VIEW	24
APPENDIX A – EUT SCHEMATICS / BLOCK DIAGRAM	25
APPENDIX B – PLOT(S) OF CONDUCTED EMISSION TEST DATA	26

APPENDIX C – USER MANUAL (NOT AVAILABE AT TIME OF TEST) 27

1 - GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

The *MICROTEK LAB. INC.* 's *ID-600* or the "EUT" as referred to in this report is a 36-bit, legal-size high-resolution scanner.

The EUT has a four-layered printed circuit board and a one-layered printed Power Supply circuit boards.

The EUT measures approximately 19.0" L x 12.5" W x 5.25" H.

1.2 Objective

The following Class B report is prepared on behalf of *MICROTEK LAB. INC.* in accordance with Part 2, Subpart J, and Part 15, Subparts A and B of the Federal Communication Commissions rules and regulations and to ICES-003 of the Canadian Interference-Causing Equipment Regulations.

The objective of the manufacturer is to demonstrate compliance with FCC Part 15 Class B limits and to ICES-003 requirements for Information Technology Equipment.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.4 –1992, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratory, Corp. The radiated testing was performed at an antenna-to-EUT distance of 10 meters.

1.4 Test Facility

The Open Area Test site used by Bay Area Compliance Laboratory Corporation to collect radiated and conducted emission measurement data is located in the back parking lot of the building at 230 Commercial Street, Suite 2, Sunnyvale, California, USA.

Test sites at Bay Area Compliance Laboratory Corporation has been fully described in reports submitted to the Federal Communication Commission (FCC) and Voluntary Control Council for Interference (VCCI). The details of these reports has been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on February 11 and December 10, 1997 and Article 8 of the VCCI regulations on December 25, 1997. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-1992.

The Federal Communications Commission and Voluntary Control Council for Interference has the reports on file and is listed under FCC file 31040/SIT 1300F2 and VCCI Registration No.: C-674 and R-657. The test sites has been approved by the FCC and VCCI for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratory Corporation is a National Institute of Standards and Technology (NIST) accredited laboratory, under the National Voluntary Laboratory Accredited Program (NVLAP). The scope of the accreditation covers the FCC Method - 47 CFR Part 15 - Digital Devices,

1.5 Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Cal. Due Date
HP	Spectrum Analyzer	8568B	2610A02165	2/6/99
HP	Spectrum Analyzer	8593B	2919A00242	12/20/98
HP	Amplifier	8349B	2644A02662	12/20/98
HP	Quasi-Peak Adapter	85650A	917059	2/6/99
HP	Amplifier	8447E	1937A01046	2/6/99
A.H. System	Horn Antenna	SAS0200/571	261	2/27/99
Com-Power	Log Periodic Antenna	AL-100	16005	1/2/99
Com-Power	Biconical Antenna	AB-100	14012	1/2/99
Solar Electronics	LISN	8012-50-R-24-BNC	968447	12/28/98
Com-Power	LISN	LI-200	12208	12/20/98
Com-Power	LISN	LI-200	12005	12/20/98
BACL	Data Entry Software	DES1	0001	12/20/98

1.6 Equipment Under Test (EUT)

Manufacturer	Description	Model	Serial Number	FCC ID
MICROTEK LABS. NC.	Scanner	ID-600	None	EF9ID-600

1.7 EUT Configuration Details

Manufacturer	Description	Model	Serial Number	FCC ID
Mitsumi Microtek	Floppy Drive Power Supply	D359M3 None	8E22DT5003 None	None None

1.8 Host Computer Configuration List and Details

Manufacturer	Description	Model	Serial Number	FCC ID
EPoX	Motherboard	EP-61BXA-M	980348300	None
SONY	Floppy Drive	MPF920E	50478514	None
SPI	Power Supply	SPI-235HP	W10872277	None
Jaton	Video Card	VCS38261 PCI	None	None
In Win	Chassis	Q-500	None	None

1.9 Local Support Equipment List and Details

Manufacturer	Description	Model	Serial Number	FCC ID
Epox	PC System	Mid-desk	None	None
Compaq	Keyboard	104WN	B03C80A39E4 G6K	AQ6-MTN41Z15DIP
Compaq	Mouse	MUS9J	B01920H67	EMJMUSJJ
NEC	Monitor	JC-14W1VMA	5122300408	C5F7NFCMC1423B

1.10 External I/O Cabling List and Details

Cable Description	Length (M)	Port/From	To
Shielded Scaner Cable	2.0	Data out / EUT	Parallel Port / Host
Shielded Keyboard Cable	1.6	Keyboard / Host	Compaq Keyboard
Shielded Mouse Cable	1.8	Mouse / Host	Compaq Mouse
Shielded Video Cable	1.8	VGA/Video Card/Host	NEC Monitor

2 - SYSTEM TEST CONFIGURATION

2.1 Justification

The system was configured for testing in a typical fashion (as a normally used by a typical user).

The motherboard provided the following I/O ports and connectors: two (2) serial ports, one (1) parallel port, one (1) ATX keyboard port, one (1) floppy interface connector, and two (2) IDE interface connectors.

The EUT was tested in the native mode to represent worst case results during the final qualification test. The parallel port (LPT1), ATX keyboard port, and both serial ports (COM1 and COM2) were also tested.

2.2 EUT Exercise Software

The EUT exercising program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use. The test software, contained on the hard drive is started the Windows 95 terminal program under the Windows 95 operating system. Once loaded, the program sequentially exercises each system component.

The sequence used is as follows:

- 1) Send H pattern to the monitor.
- 2) The H program sends commands to the EUT.
- 3) The modem receives Hs.

This process is continuous throughout all tests.

2.3 Special Accessories


As shown in section 2.5, all interface cables used for compliance testing are shielded as normally supplied by INMAC and their respective support equipment manufacturers. The monitor featured shielded metal connectors.

2.4 Schematics / Block Diagram


Appendix A contains a copy of the EUT's schematics diagram as reference.

2.5 Configuration of Test System

EUT FCC ID: EF9ID-600



2.6 Test Setup Block Diagram



2.7 Equipment Modifications

No modification(s) were necessary for the EUT to comply with the applicable standards and limits.

3 - CONDUCTED EMISSIONS TEST DATA

3.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, and LISN.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of any conducted emissions measurement at BACL is ± 2.4 dB.

3.2 EUT Setup

The measurement was performed at the Open Area Test Site, using the same setup per ANSI C63.4 - 1992 measurement procedure. The specification used was the EN55022 Class B limits.

The EUT was placed on the test table. The VGA monitor was placed on one side of the EUT with the Full Tower chassis on the other side. The rear of the PC system and peripherals were placed flushed with the rear/sides of the tabletop.

The keyboard was placed in front of the EUT, flushed with the front of the tabletop. The mouse was placed next to the keyboard and flushed with the back of the keyboard.

The spacing between the peripherals was 10 cm.

3.3 Spectrum Analyzer Setup

The spectrum analyzer was set with the following configuration during the conduction test:

Start Frequency.....	150 kHz
Stop Frequency.....	30 MHz
Sweep Speed	Auto
IF Bandwidth.....	100 kHz
Video Bandwidth.....	100 kHz
Quasi-Peak Adapter Bandwidth	9 kHz
Quasi-Peak Adapter Mode	Normal

3.4 Test Procedure

During the conducted emission test, the power cord of the host system was connected to the auxiliary outlet of the first LISN. The VGA monitor and all other support equipment power cords were connected to the auxiliary power outlet of the second LISN.

Maximizing procedure was performed on the six (6) highest emissions to ensure EUT is compliant with all installation combination.

All data was recorded in the peak detection mode. Quasi-peak readings were only performed when an emission was found to be marginal (less than $-4 \text{ dB}\mu\text{V}$). Quasi-peak readings are distinguished with a "Qp".

The EUT was operating at normal (native) mode tested during the final qualification test to represent worst case results.

Additionally, the EUT was tested with the *EUT Inside Power Supply (110 V)*.

3.5 Summary of Test Results

According to the data in section 3.6, the EUT complied with the EN55022 Conducted margin for a Class B device and these test results is deemed as satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations, with the *worst* margin reading of:

-2.3 dB μV at 0.420 MHz in the **Line** mode, native operating mode with the *EUT Inside* power supply (110V).

3.6 Conducted Emissions Test Data

3.6.1 Test Data with EUT Inside Power Supply, 110V, 0.15 - 30 MHz.

LINE CONDUCTED EMISSIONS				EN55022 CLASS B	
Frequency	Amplitude	Detector	Phase	Limit	Margin
MHz	dB μV	Qp/Ave/Peak	Line/Neutral	dB μV	dB
0.420	55.1	QP	Line	57.4	-2.3
0.420	51.2	QP	Neutral	57.4	-6.2
7.880	48.5	QP	Neutral	60.0	-11.5
8.090	47.0	QP	Line	60.0	-13.0
10.120	43.0	QP	Line	60.0	-17.0
27.160	42.3	QP	Neutral	60.0	-17.7

3.7 Plot of Conducted Emissions Test Data

Plot(s) of Conducted Emissions Test Data with *EUT Inside Power Supply* is presented in Appendix B of this report as reference.

4 - RADIATED EMISSION DATA

4.1 Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on NIS 81, The Treatment of Uncertainty in EMC Measurements, the best estimate of the uncertainty of a radiation emissions measurement at BACL is ± 4.0 dB.

4.2 EUT Setup

The radiated emission tests were performed in the open area *3 meter* test site, using the setup accordance with the ANSI C63.4 - 1992. The specification used was the FCC Part 15 Class B limits.

The EUT was placed on the test table. The VGA monitor was placed on one side of the EUT with the Full Tower chassis on the other side. The rear of the PC system and peripherals were placed flushed with the rear/sides of the tabletop.

The keyboard was placed in front of the EUT, flushed with the front of the tabletop. The Mouse was placed next to the keyboard, Which was placed flushed with the back of the keyboard.

The spacing between the peripherals was 10 cm.

4.3 Spectrum Analyzer Setup

According to FCC Rules, 47 CFR 15.33, since the internal operating clock speed is below 108 MHz, the system was tested to 1000 MHz.

During the radiated emission test, the spectrum analyzer was set with the following configurations:

Start Frequency	30 MHz
Stop Frequency	1000 MHz
Sweep Speed	Auto
IF Bandwidth	100 kHz
Video Bandwidth	1 MHz
Quasi-Peak Adapter Bandwidth	120 kHz
Quasi-Peak Adapter Mode	Normal
Resolution Bandwidth	1MHz

4.7 Radiated Emissions Test Data

4.7.1 Test Data for Normal (Native) Mode, 30-1000 MHz –10 meters

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR			CORRECTED AMPLITUDE	EN55022 CLASS B	
Frequency MHz	Ampl. dB ₁ uV/m	Angle Degree	Height Meter	Polar	Antenna dB ₁ uV/m	Cable dB	Amp. dB	Corr. Ampl. dB ₁ uV/m	Limit dB ₁ uV/m	Margin dB
215.98	29.1	0	1.5	H	15.9	4.9	21.8	27.9	30	-2.1
80.85	37.3	340	1.5	V	9.2	3.0	21.0	27.5	30	-2.5
503.99	32.1	0	1.8	H	16.8	7.5	23.6	34.4	37	-2.6
211.25	27.4	270	1.4	H	15.7	4.9	22.4	26.0	30	-4.0
455.99	31.2	270	1.5	V	16.2	7.4	23.5	32.8	37	-4.2
212.18	24.9	180	1.4	V	17.8	4.9	22.4	25.6	30	-4.4
336.05	35.2	0	1.6	H	13.0	6.1	22.6	32.3	37	-4.7
52.49	34.6	180	1.7	V	10.2	2.5	21.7	25.3	30	-4.7
551.99	28.9	290	1.6	V	17.2	8.2	23.3	32.3	37	-4.7
432.05	32.0	30	1.6	H	15.0	7.0	23.4	32.0	37	-5.0
336.00	34.1	120	1.5	V	13.7	6.1	22.6	34.9	37	-5.1
192.95	26.9	180	1.6	H	15.0	4.7	21.6	24.6	30	-5.4
110.00	33.2	160	1.6	V	10.4	3.0	21.4	24.6	30	-5.4
139.99	29.9	120	1.7	H	11.6	3.8	21.2	28.3	30	-6.7
240.03	30.5	300	1.5	H	16.5	5.1	22.1	30.1	37	-6.9
69.99	33.1	270	1.5	H	9.2	2.7	21.6	23.0	30	-7.0
194.20	25.7	270	1.6	V	14.3	4.7	21.6	22.7	30	-7.3
109.99	31.0	80	1.4	H	9.8	3.0	21.6	24.8	30	-8.2
141.46	28.0	225	1.4	V	11.5	4.0	21.2	21.5	30	-8.5
125.20	27.5	90	1.8	H	11.2	3.7	21.4	20.4	30	-9.6
249.16	24.0	0	1.9	V	18.5	5.2	22.4	25.7	37	-11.3

4.7.2 Test Data for Normal (Native) mode, 30-1000 MHz –10 meters– After Maximized Procedure

INDICATED		TABLE	ANTENNA		CORRECTION FACTOR		CORRECTED AMPLITUDE		EN55022 CLASS B	
Frequency	Ampl.	Angle	Height	Polar	Antenna	Cable	Ampl.	Corr. Ampl.	Limit	Margin
MHz	dB _μ V/m	Degree	Meter	H/V	dB _μ V/m	dB	dB	dB _μ V/m	dB _μ V/m	dB
503.99	33.1	180	1.7	H	16.8	7.5	23.6	35.4	37	-1.6
215.98	29.3	180	2.0	H	15.9	4.9	21.8	28.1	30	-1.9
80.85	37.9	200	1.3	V	9.2	3.0	21.0	28.1	30	-1.9
455.99	33.0	120	1.6	V	16.2	7.4	23.5	34.6	37	-2.4
211.25	27.6	180	1.8	H	15.7	4.9	22.4	26.2	30	-3.8
212.18	25.2	290	1.5	V	17.8	4.9	22.4	25.9	30	-4.1

4.4 Test Procedure

For the radiated emissions test, the power cord of the EUT, VGA monitor and all support equipment were connected to the AC floor outlet since the power supply used inside the EUT did not provide an accessory power outlet.

Maximizing procedure was performed on the highest emissions to ensure EUT is compliant with all installation combinations.

All data was recorded in the peak detection mode. Quasi-peak readings were performed only when an emission was found to be marginal (less than -4 dB μ V), and are distinguished with a "Qp" in the data table.

The EUT was operating at normal (native) mode tested during the final qualification test to represent worst case results.

4.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

$$\text{Corr. Ampl.} = \text{Indicated Reading} + \text{Antenna Factor} + \text{Cable Factor} - \text{Amplifier Gain}$$

The "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB μ V means the emission is 7dB μ V below the maximum limit for FCC Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{FCC Class B Limit}$$

4.6 Summary of Test Results


According to the data in section 4.7, the EUT complied with the EN55022 Class B standards and these test results are deemed satisfactory evidence of compliance with ICES-003 of the Canadian Interference-Causing Equipment Regulations, and had the worst margin of:

-2.1 dB μ V at 215.98 MHz in the Horizontal polarization.

-1.6 dB μ V at 503.99 MHz in the Horizontal polarization – After maximized procedure.

MICROTEK IMAGEDESK (SCANNER)
REF 66.0 dB μ V ATTEN 0 dB
10 dB/

MKR 420 kHz
55.10 dB μ V



START 150 kHz
RES BW 10 kHz VBW 30 kHz

STOP 30.00 MHz
SWP 20 sec