



Global Product Certification
EMC-EMF Safety Approvals

EMC Technologies Pty Ltd
ABN 82 057 105 549
176 Harrick Road
Keilor Park Victoria Australia 3042

Ph: + 613 9365 1000
Fax: + 613 9331 7455
email: melb@emctech.com.au

EMI TEST REPORT FOR CERTIFICATION to FCC PART 15 Subpart E (Section 15.407) & RSS-210

FCC ID: EJE-WB0060
Industry Canada ID: 337J-WB0060

Test Sample: LifeBook T Series
Model: T1010

Radio Modules: 512AN_HMW INTEL Shirley Peak 1x2 Half Mini-PCI
WLAN Module & EYSMJCS Bluetooth Module

Report Number M080522_Cert_512AN_HMW_NII_BT

Issue Date: 25th June 2008

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



This document is issued in accordance with NATA's accreditation requirements. The results of tests, calibration and/or measurements included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing and calibration reports.

This document shall not be reproduced except in full.

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart E (Section 15.407) & RSS-210**

EMC Technologies Report No. M080522_Cert_512AN_HMW_NII_BT

Issue Date: 25th June 2008

CONTENTS

**1.0 INTRODUCTION
2.0 GENERAL INFORMATION**

FCC 15.407 (U-NII) RESULTS

- 3.0 CONDUCTED EMI MEASUREMENTS**
- 4.0 RADIATED EMI MEASUREMENTS**
- 5.0 PEAK OUTPUT POWER**
- 6.0 CHANNEL BANDWIDTH**
- 7.0 PEAK POWER SPECTRAL DENSITY**
- 8.0 PEAK EXCURSION**
- 9.0 FREQUENCY STABILITY**
- 10.0 DYNAMIC FREQUENCY SELECTION**
- 11.0 DISCONTINUE TRANSMISSION**
- 12.0 RADIO FREQUENCY EXPOSURE**
- 13.0 ANTENNA REQUIREMENT**
- 14.0 COMPLIANCE STATEMENT**
- 15.0 MEASUREMENT UNCERTAINTIES**
- 16.0 TEST REPORT APPENDICES**

APPENDIX A: MEASUREMENT INSTRUMENT DETAILS

APPENDIX B: PHOTOGRAPHS
APPENDIX C: OPERATIONAL DESCRIPTION
APPENDIX D: BLOCK DIAGRAM
APPENDIX E: ANTENNA INFORMATION
APPENDIX F: SCHEMATIC
APPENDIX G: FCC LABELLING DETAILS
APPENDIX H: USER MANUAL

Attachment 1: RF Exposure Information

Attachment 2: FCC DOC for LifeBook T Series

Attachment 3: FCC Part 15B Test Report (Report: FG08-052EAL)

Attachment 4: Part 15.407 Test Report (Report: R71111 Rev 2)

Attachment 5: Part 15.407 DFS Test Report (Report: R71303 Rev 2)

FCC 15.247 (DTS) RESULTS - WLAN

Refer to Report No: M080522_Cert_512AN_HMW_DTS_BT

FCC 15.247 (DSS) RESULTS - BT

Refer to Report No: M080522_Cert_EYSMJCS_512AN_HMW



Accreditation No. 5292

This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.
www.emctech.com.au

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart E (Section 15.407) & RSS-210

Report No. M080522_Cert_512AN_HMW_NII_BT

Test Sample: LifeBook T Series
Model: T1010
Radio Modules: Shirley Peak 1x2 Half Mini-PCI WLAN Module, Model: 512AN_HMW (Intel Corp.)
Bluetooth Module, Model: EYSMJCS (TAIYO YUDEN)

FCC ID: EJE-WB0060
Industry Canada ID: 337J-WB0060
Equipment Type: Intentional Radiator (Transceiver)

Manufacturer (LifeBook): Fujitsu Ltd - Mobile Computing Division
Address: 1-1 Kamikodanaka 4-Chome, Nakahara-Ku, Kawasaki, Japan
Contact: Mr. Tsuyoshi Uchihara


Test Standards: FCC Part 15 – Radio Frequency Devices (September 2007)
FCC Part 15, Subpart E – Unlicensed National Information, Infrastructure Devices
FCC Part 15.407, General Technical Requirements
ANSI C63.4 – 2003
OET Bulletin No. 65

RSS-210 Issue 7 Low Power Licence-Exempt RadioCommunication Devices
Annex 9: Local Area Network Devices

RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and Portable Radio Transmitters with respect to Health Canada's Safety Code 6 for Exposure of Humans to Radio Frequency Fields

Test Dates: 18th to 24th May 2008

Senior Engineer:


Chieu Huynh - B.Eng (Hons) Electronics
Lee Hopkins

Attestation:

I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.



Authorised Signatory:

Chieu Huynh
Senior EMC Engineer
EMC Technologies Pty Ltd



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.
www.emctech.com.au

Accreditation No. 5292

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart E (Section 15.407) & RSS-210

1.0 INTRODUCTION

EMI testing was performed on the Fujitsu notebook PC, Model: T1010 with INTEL Mini-PCI Wireless LAN Module (Shirley Peak 802.11a/b/g/n 1x2), Model: 512AN_HMW & TAIYO YUDEN Bluetooth Module, Model: EYSMJCS.

The Shirley Peak 1x2 WLAN module was originally certified by INTEL as a modular approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH). The Radio modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

The Bluetooth module was originally certified by TAIYO YUDEN as a modular approval under FCC ID: RYYEYSMJCS (Canada ID: 4389B-EYSMJCS). The Radio modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

The 512AN_HMW 1x2 WLAN supports IEEE 802.11b, IEEE 802.11g, IEEE 802.11a and IEEE 802.11n (DTS & U-NII) configurations.

NII results for configurations IEEE 802.11a and IEEE 802.11n are reported in this test report.

The DTS and DSS results are reported separately.

Refer to EMC Technologies' test report: M080522_Cert_512AN_HMW_DTS_BT (DTS).

Refer to EMC Technologies' test report: M080522_Cert_EYSMJCS_512AN_HMW (DSS)

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart E:	Unlicensed National Information Infrastructure Devices (U-NII) operating in the 5.15-5.35 GHz, 5.47-5.725 GHz and 5.725-5.825 GHz frequency bands
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.407:	General Technical Requirements

The results and technical details of the test sample are detailed in this report. The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart E - Section 15.407.

The test sample also complied with the Industry Canada RSS-210 issue 7 - Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Annex 9 and the RF exposure requirements of RSS-102.

The measurement procedure used was in accordance with ANSI C63.4-2003 and OET Bulletin No. 65. The instrumentation conformed to the requirements of ANSI C63.2-1996.



1.1 Summary of Results

1.1.1 FCC Subpart E, Section 15.407

FCC Part 15, Subpart E Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Complies
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Note 1
15.209	6.3	Radiated Emissions	Complies
15.407 (a)(1) (a)(2)	Annex A9.2	Peak Transmit Power	Note 2
15.407 (a)(5)	Annex A9.2	Peak Power Spectral Density	Note 2
15.407 (a)(6)		Peak Excursion	Note 2
15.407 (b)	Annex A9.3	Undesirable Emission	Complies
15.407 (c)	Annex A9.5(4)	Discontinue Transmission	Complies
15.407 (d)		Reserved	-
15.407 (e)	2.2 (Table 1)	Restricted to Indoor Operations	Complies
15.407 (f)	RSS-Gen (5.5)	Radio Frequency Hazard	Complies
15.407 (g)	Annex A9.5(5)	Frequency Stability	Note 2
15.407 (h)		Transmit Power Control	Not Applicable E.I.R.P < 500 mW
15.407 (h)	Annex A9.4	Dynamic Frequency Selection	Note 3

Note 1: Refer to Attachment 3, FCC Part 15B test report: FG08-052EAL dated May 15 2008

Note 2: Refer to Attachment 4, FCC 15.407 test report: R71111 Rev 2 dated June 12 2008 (re-issue)

Note 3: Refer to Attachment 5, FCC 15.407 DFS test report: R71303 Rev 2 dated April 18 2008

1.1.2 FCC Subpart C, Section 15.247 - WLAN

Refer to EMC Technologies Report No: M080522_Cert_512AN_HMW_DTS_BT

1.1.3 FCC Subpart C, Section 15.247 - BT

Refer to EMC Technologies' test report: M080522_Cert_EYSMJCS_512AN_HMW

1.2 Modifications by EMC Technologies

No modifications were required.



2.0 GENERAL INFORMATION

(Information supplied by the Client)

2.1 EUT (WLAN) Details

Transmitter:	Half Mini-Card Wireless LAN Module
Wireless Module:	Shirley Peak 1x2 (11a/b/g/n)
Model Number:	512AN_HMW
Manufacturer:	Intel Corporation
Modulation Type:	Direct Sequence Spread Spectrum (DSSS for 802.11b) Orthogonal Frequency Division Multiplexing (OFDM for 802.11a/g/n)
2.4 GHz (802.11b/g/n):	DBPSK, DQPSK, CCK, 16QAM and 64QAM
5 GHz (802.11a/n):	BPSK, QPSK, 16QAM and 64QAM
Maximum Data Rate:	802.11b = 11Mbps, 802.11g and 802.11a = 54Mbps 802.11n = Tx 150 Mbps Rx 300 Mbps
Frequency Ranges:	2.412 –2.462 GHz for 11b/g/n 5.18 - 5.32 GHz, 5.5 – 5.7 GHz and 5.745 - 5.825 GHz for 11a/n
Number of Channels:	11 channels for 11b/g/n 24 channels for 11a/n with 20 MHz bandwidth 18 channels for 11n with 40 MHz bandwidth
Antenna Types:	Tx: Nissei Electric Inverted F Antenna Model: CP405102 and CP405101 Location: Top edge of LCD screen
Antenna gain:	Max antenna gain is less than 6 dBi. Refer antenna data provided separately
Power Supply:	3.3 VDC from PCI bus



Channels Tested and Output power setting:

Modes	Channels	Frequency MHz	Average Output Power (dBm)
802.11b	1*	2412	18.8
	6*	2437	16.5
	11*	2462	19.6
802.11g	1*	2412	14.5
	6*	2437	16.5
	11*	2462	14.0
802.11a	36**	5180	18.4
	40 and 48**	5200 and 5240	16.5
	52, 60 and 64**	5260, 5300 and 5320	
	100**	5500	19.1
	120 and 140**	5600 and 5700	16.5
	149, 157 and 165*	5745, 5785 and 5825	
802.11n 20MHz Bandwidth	1*	2412	13.1
	6*	2437	16.5
	11*	2462	14.0
	36, 40 and 48**	5180, 5200 and 5240	16.5
	52, 60 and 64**	5260, 5300 and 5320	
	100, 120 and 140**	5500, 5600 and 5700	
	149, 157 and 165*	5745, 5785 and 5825	
802.11n 40MHz Bandwidth	3*	2422	10.1
	6*	2437	16.5
	9*	2452	14.1
	38, 54 and 62**	5190, 5270 and 5310	16.5
	102, 118 and 134**	5510, 5590 and 5670	
	151 and 159*	5755 and 5795	

**Channels tested and reported in this report

*Channels tested and reported in the DTS submission (M080522_Cert_512AN_HMW_DTS_BT)

2.2 EUT (Bluetooth) Details

Transmitter:	Bluetooth
Model Number:	EYSMJCS
Manufacturer:	TAIYO YUDEN
Network Standard:	Bluetooth™ RF Test Specification
Modulation Type:	Frequency Hopping Spread Spectrum (FHSS)
Frequency Range:	2402 MHz to 2480 MHz
Number of Channels:	79
Carrier Spacing:	1.0 MHz
Antenna Types:	Included BT module
Antenna gain:	Location: left side of hinge Max antenna gain is less than 6 dBi. Refer antenna data provided separately
Max. Output Power:	4 dBm
Reference Oscillator:	16 MHz (Built-in)
Power Supply:	3.3 VDC from host.



Frequency allocation:

Channel Number	Frequency (MHz)	Bluetooth Utility power setting
1*	2402	
2	2403	
3	2404	
.	.	
.	.	
39	2440	
40*	2441	Power (Ext, Int) = 0, 96
41	2442	
.	.	
.	.	
77	2478	
78	2479	
79*	2480	

*Channels tested and reported in The DSS submission (M080522_Cert_EYSMJCS_512AN_HMW)

2.3 EUT (Notebook PC) Details

EUT: LifeBook T series
Model Name: T1010
Serial Number: Pre-production Sample
Manufacturer: FUJITSU LIMITED

CPU Type and Speed: Core2 Duo T9600 2.8GHz
LCD: 13.3"WXGA (LED: T5010, CCFL: T1010)
Wired LAN: Intel 82567LM : 10 Base-T/100 Base-TX/1000Base-T(T5010)
Modem: Marvell 88E8055 : 10 Base-T/100 Base-TX/1000Base-T(T1010)
Port Replicator Model: Agere MDC1.5 modem Model: D40

AC Adapter Model: SEC100P2-19.0(Sanken) / SEC100P3-19.0(Sanken, 3pin) / ADP-80NB A(Delta) / SED100P2-19.0(Sanken)
Voltage: 19 V
Current Specs: 4.22A
Watts: 80W

2.4 Test Configuration

The Intel WLAN test software "CRTU" was used to transmit continuously during the tests.

Conducted tests were performed at the WLAN Antenna ports.

Radiated harmonics and spurious emissions were performed while the transmitter transmits continuously.

2.5 Support Equipment

Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG08-052EAL)

2.6 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 1 and 3 metres from the EUT. OET Bulletin 65 dated June 2001 was used for reference.



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.
www.emctech.com.au

Accreditation No. 5292

2.7 Test Facility

2.7.1 General

Radiated Emission measurements were performed at EMC Technologies open area test site (OATS) situated at Lerderderg Gorge, near the township of Bacchus Marsh in Victoria, Australia. Conducted measurements at an antenna ports were performed at EMC Technologies' laboratory in Keilor Park, Victoria Australia.

The above test sites have been accepted for testing by the Federal Communications Commission (FCC) - **FCC Registration Number 90560**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional). **Industry Canada File Number IC 3569B-1.**

2.7.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

"FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E)."

The current full scope of accreditation can be found on the NATA website: www.nata.asn.au
It also includes a large number of emissions, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Institute (NMI) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A²LA).

2.8 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Institute (NMI). All equipment calibration is traceable to Australia national standards at the National Measurements Institute. The reference antenna calibration was performed by NMI and the working antennas (biconical and log-periodic) calibrated by the NATA approved procedures. The complete list of test equipment used for the measurements, including calibration dates and traceability is contained in Appendix A

2.9 Ambients at OATS

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.



FCC 15.407 (U-NII) RESULTS

3.0 CONDUCTED EMISSION MEASUREMENTS

Testing was performed in accordance with the requirements of FCC Part 15.207
Refer to Attachment 3 – FCC Part 15B Test Report (Report: FG08-052EAL)

4.0 RADIATED EMISSION MEASUREMENTS

4.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.407(b).

Radiated emission measurements were performed to the limits as per section 15.209 and 15.407. The measurements were made at the open area test site. All measurements above 1 GHz were made over a distance of 3 and 1 metres.

Calibrated EMCO 3115, EMCO 3116 and ETS standard gain horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions between 30 - 1000 MHz, refer to Attachment 3 – FCC Part 15B Test Report (Report: FG08-052EAL).

The measurement of emissions above 1000 MHz was measured using a following setting:

Peak measurements setting: RBW = VBW = 1 MHz

Average measurements setting: RBW = 1 MHz and VBW = 10 Hz

The receiver bandwidth was set to 6 dB.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Peak/Average Detectors. The measurement data for each frequency range was corrected for cable losses, antenna factors and preamplifier gain. This process was performed for both horizontal and vertical antenna polarisations.

4.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

E = V + AF - G + L Where:

E = Radiated Field Strength in dB μ V/m.

V = EMI Receiver Voltage in dB μ V. (measured value)

AF = Antenna Factor in dB(m⁻¹). (stored as a data array)

G = Preamplifier Gain in dB. (stored as a data array)

L = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

- Example Field Strength Calculation**

Assuming a receiver reading of 34.0 dB μ V is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$



4.3 Results - Out of Band Emissions (Spurious and Harmonics)

4.3.1 Frequency Band: 1 – 40 GHz

The peak limits for undesirable emission outside of the restricted bands are –27 dBm (68.3 dB μ V/m @ 3m). The 74 dB μ V/m @ 3m and 54 dB μ V/m @ 3m limits are applied for emissions fall in the restricted bands.

Testing was performed while the WLAN transmitter continuously operated. Harmonics related to the WLAN transmitter operated in the frequency bands 5.15 – 5.35 GHz and 5.47 – 5.725 GHz are reported below. Harmonics in the frequency bands 2.4 – 2.4835 GHz and 5.725 – 5.850 GHz, refer to M080522_Cert_512AN_HMW_DTS_BT.

Configuration 802.11a and 802.11n

Initial investigations were performed with all data rates: (6 Mbps to 54 Mbps and MCS0 to MCS7). Final testing was performed while the transmitter continuously operated.

Channel 36 - 5180 MHz, Tx BW = 20 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dB μ V/m	Average Detector dB μ V/m	Peak Limit dB μ V/m	Average Limit dB μ V/m	Result
802.11a	6 Mbps	5180	105.0	94.7	-	-	-
		10360	58.3	43.8	68.3	-	Complies
		15540	56.7	43.3	74.0	54.0	Complies
		5150	70.7	54.0	74.0	54.0	Complies
802.11n	MCS0	5180	102.0	92.3	-	-	-
		Others harmonics emissions results are lower than to the 6 Mbps					
		5150	67.7	51.3	74.0	54.0	Complies

Channel 40 - 5200 MHz, Tx BW = 20 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dB μ V/m	Average Detector dB μ V/m	Peak Limit dB μ V/m	Average Limit dB μ V/m	Result
802.11a	6 Mbps	5200	100.8	90.7	-	-	-
		10400	54.0	39.1	68.3	-	Complies
802.11n	MCS0	5200	100.6	90.6	-	-	-
		Others harmonics emissions results are similar to the 6 Mbps					

Channel 48 - 5240 MHz, Tx BW = 20 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dB μ V/m	Average Detector dB μ V/m	Peak Limit dB μ V/m	Average Limit dB μ V/m	Result
802.11a	6 Mbps	5240	100.5	90.4	-	-	-
		10480	54.3	39.7	68.3	-	Complies
802.11n	MCS0	5240	100.3	90.7	-	-	-
		Others harmonics emissions results are similar to the 6 Mbps					



Channel 52 - 5260 MHz, Tx BW = 20 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit	Average Limit	Result
					dBuV/m	dBuV/m	
802.11a	6 Mbps	5260	100.2	90.2	-	-	-
		10520	54.3	41.1	68.3	-	Complies
802.11n	MCS0	5260	101.2	90.7	-	-	-
		Others harmonics emissions results are similar to the 6 Mbps					

Channel 60 - 5300 MHz, Tx BW = 20 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit	Average Limit	Result
					dBuV/m	dBuV/m	
802.11a	6 Mbps	5300	100.7	90.4	-	-	-
		10600	57.6	44.3	68.3	54	Complies
802.11n	MCS0	5300	100.4	90.3	-	-	-
		Others harmonics emissions results are similar to the 6 Mbps					

Channel 64 - 5320 MHz, Tx BW = 20 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
802.11a	6 Mbps	5320	100.5	90.6	-	-	-
		10640	60.8	47.3	74.0	54.0	Complies
		15960	55.0	41.3	74.0	54.0	Complies
		5350	64.0	50.1	74.0	54.0	Complies
802.11n	MCS0	5320	100.0	89.9	-	-	-
		Others harmonics emissions results are lower than to the 6 Mbps					
		5150	67.8	51.2	74.0	54.0	Complies

Channel 100 - 5500 MHz, Tx BW = 20 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
802.11a	6 Mbps	5500	107.3	97.2	-	-	-
		11000	58.5	45.1	74.0	54.0	Complies
		16500	55.9	42.5	68.3	-	Complies
		*5470	78.3	64.5	78.8	-	Complies
802.11n	MCS0	5550	105.1	95.0	-	-	-
		Others harmonics emissions results are lower than to the 6 Mbps					
		*5470	66.7	-	78.8	-	Complies

*Measurement was performed at 1 m distance.



Channel 120 - 5600 MHz, Tx BW = 20 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak	Average	Result
					Limit dBuV/m	Limit dBuV/m	
802.11a	6 Mbps	5600	101.9	91.8	-	-	-
		11200	57.8	45.2	74.0	54	Complies
		16800	53.0	41.6	68.3	-	Complies
802.11n	MCS0	5600	102.7	92.6	-	-	-
		Others harmonics emissions results are similar to the 6 Mbps					

Channel 140 - 5700 MHz, Tx BW = 20 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit dBuV/m	Average Limit dBuV/m	Result
802.11a	6 Mbps	5700	100.9	90.7	-	-	-
		11400	62.7	48.8	74.0	54.0	Complies
		17100	54.0	39.1	68.3	-	Complies
		5725	64.7	49.8	68.3	-	Complies
802.11n	MCS0	5700	101.0	90.3	-	-	-
		Others harmonics emissions results are lower than to the 6 Mbps					
		5725	68.2	-	68.3	-	Complies

Channel 38 - 5190 MHz, Tx BW = 40 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak	Average	Result
					Limit	Limit	
					dBuV/m	dBuV/m	
802.11n	MCS0	5190	100.5	89.7	-	-	-
		10380	57.0	44.1	68.3	-	Complies
		*5150	80.1	64.0	84.5	64.5	Complies

*Measurement was performed at 1 m distance.

Channel 54 - 5270 MHz, Tx BW = 40 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak	Average	Result
					Limit	Limit	
					dBuV/m	dBuV/m	
802.11n	MCS0	5270	100.6	89.4	-	-	-
		10540	57.8	44.5	68.3	-	Complies

Channel 62 - 5310 MHz, Tx BW = 40 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak	Average	Result
					Limit	Limit	
					dBuV/m	dBuV/m	
802.11n	MCS0	5310	98.8	88.0	-	-	-
		10620	55.6	44.0	74.0	54.0	Complies
		5350	70.1	54.0	74.0	54.0	Complies



Channel 102 - 5510 MHz, Tx BW = 40 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit	Average Limit	Result
					dBuV/m	dBuV/m	
802.11n	MCS0	5510	101.8	91.0	-	-	-
		11020	54.7	41.3	74.0	54.0	Complies
		*5470	78.7	-	78.8	-	Complies

*Measurement was performed at 1 m distance.

Channel 118 - 5590 MHz, Tx BW = 40 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit	Average Limit	Result
					dBuV/m	dBuV/m	
802.11n	MCS0	5590	100.3	90.2	-	-	-
		11180	57.7	44.3	74.0	54.0	Complies

Channel 134 - 5670 MHz, Tx BW = 40 MHz

Modes	Data Rates	Frequency MHz	Peak Detector dBuV/m	Average Detector dBuV/m	Peak Limit	Average Limit	Result
					dBuV/m	dBuV/m	
802.11n	MCS0	5670	100.1	88.4	-	-	-
		11340	57.5	44.6	74.0	54.0	Complies
		5725	64.5	48.9	68.3	-	Complies

Result: Harmonics and spurious emissions were recorded up to 40 GHz. Harmonics were low and confirmed with both RBW and VBW reduced. Emissions complied with the FCC limits of sections 15.209 and 15.407 by a margin of 0 dB.

4.3.2 Frequency Band: 30 - 1000 MHz

Refer to attachment 3 – FCC Part 15B test report number: FG08-052EAL dated: May 15 2008.

Testing was performed by Fujitsu General EMC Laboratory, JAPAN accredited by NVLAP (Lab Code: 200373-0).

4.3.3 RF Conducted Measurements at the antenna terminal

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Refer to attachment 4, FCC 15.407 test report number: R71111 Rev 2 dated June 12 2008 (re-issue).

Testing was performed by Elliott Laboratories, Inc CA, USA accredited by A2LA (Certificate Number: 2016.01)

4.3.4 Radiated Band Edge Measurements

Complied (refer to section 4.3 – radiated emissions).



5.0 PEAK OUTPUT POWER - Section 15.407(a)

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Refer to attachment 4, FCC 15.407 test report number: R71111 Rev 2 dated June 12 2008 (re-issue).

Testing was performed by Elliott Laboratories, Inc CA, USA accredited by A2LA (Certificate Number: 2016.01)

6.0 CHANNEL BANDWIDTH

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Refer to attachment 4, FCC 15.407 test report number: R71111 Rev 2 dated June 12 2008 (re-issue).

Testing was performed by Elliott Laboratories, Inc CA, USA accredited by A2LA (Certificate Number: 2016.01)

7.0 PEAK POWER SPECTRAL DENSITY

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Refer to attachment 4, FCC 15.407 test report number: R71111 Rev 2 dated June 12 2008 (re-issue).

Testing was performed by Elliott Laboratories, Inc CA, USA accredited by A2LA (Certificate Number: 2016.01)

8.0 PEAK EXCURSION

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Refer to attachment 4, FCC 15.407 test report number: R71111 Rev 2 dated June 12 2008 (re-issue).

Testing was performed by Elliott Laboratories, Inc CA, USA accredited by A2LA (Certificate Number: 2016.01)

9.0 FREQUENCY STABILITY

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Refer to attachment 4, FCC 15.407 test report number: R71111 Rev 2 dated June 12 2008 (re-issue).

Testing was performed by Elliott Laboratories, Inc CA, USA accredited by A2LA (Certificate Number: 2016.01)



10.0 DYNAMIC FREQUENCY SELECTION

The EUT is a Client Device without Radar Interference Detection Function.

Ad-hoc operation (not under control of a Master Device) is supported in the 2.4 GHz & 5.15 - 5.25 GHz bands only. This Ad-hoc capability is limited in hardware via factory programmed EEPROM settings that cannot be accessed or changed by end users. The Ad-hoc supported channels of operation cannot be modified – regardless of which client utility or operating system control is used.

Refer to original approval under FCC ID: PD9512ANH (Canada ID: 1000M-512ANH) certified by INTEL.

Refer to attachment 5, FCC 15.407 DFS test report: R71303 Rev 2 dated April 18 2008

Testing was performed by Elliott Laboratories, Inc CA, USA accredited by A2LA (Certificate Number: 2016.01)

11.0 DISCONTINUE TRANSMISSION

Data Transmission is always initiated by software, which is then passed down through the MAC, through the digital and analog baseband, finally to the RF chip. Several special packets (ACKs, CTS, PSPoll, etc) are initiated by the MAC. These are the only ways the digital baseband portion will turn on the RF transmitter, which then turns off at the end of the packet. Therefore, the transmitter will be ON only while one of the four mentioned packets is being transmitted.

12.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.407(f)

Spread spectrum transmitters operating in the 5.15 – 5.35 GHz and 5.47 – 5.725 GHz are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

In accordance with this section and also section 2.1093 this device has been defined as a portable device.

SAR testing was performed in accordance with OET Bulletin 65 and reported under EMC Technologies reports M080506_Cert_512AN_HMW_SAR_2.4 (2.4 GHz) and M080506_Cert_512AN_HMW_SAR_5.6 (5.18 – 5.825 GHz). SAR value of 0.108 mW/g is measured which complies with the FCC human exposure requirements of 47 CFR 2.1093 (d).

13.0 ANTENNA REQUIREMENT

This intentional radiator was designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.
www.emctech.com.au

Accreditation No. 5292

14.0 COMPLIANCE STATEMENT

The Fujitsu notebook PC, Model: T1010 with INTEL Mini-PCI Wireless LAN Module (Shirley Peak 802.11a/b/g/n 1x2), Model: 512AN_HMW & TAIYO YUDEN Bluetooth Module, Model: EYSMJCS, **complied** with the requirements of 47 CFR, Part 15 Subpart E -Section 15.407 (5.15-5.35 GHz and 5.47 – 5.725 GHz bands).

The test sample also complied with the Industry Canada RSS-210 issue 7 - Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Annex 9 Local Area Network Devices requirements and the RF exposure requirements of RSS-102.

Results were as follows:

FCC Subpart E, Section 15.407

FCC Part 15, Subpart E Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Complies
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Note 1
15.209	6.3	Radiated Emissions	Complies
15.407 (a)(1) (a)(2)	Annex A9.2	Peak Transmit Power	Note 2
15.407 (a)(5)	Annex A9.2	Peak Power Spectral Density	Note 2
15.407 (a)(6)		Peak Excursion	Note 2
15.407 (b)	Annex A9.3	Undesirable Emission	Complies
15.407 (c)	Annex A9.5(4)	Discontinue Transmission	Complies
15.407 (d)		Reserved	-
15.407 (e)	2.2 (Table 1)	Restricted to Indoor Operations	Complies
15.407 (f)	RSS-Gen (5.5)	Radio Frequency Hazard	Complies
15.407 (g)	Annex A9.5(5)	Frequency Stability	Note 2
15.407 (h)		Transmit Power Control	Not Applicable E.I.R.P < 500 mW
15.407 (h)	Annex A9.4	Dynamic Frequency Selection	Note 3

Note 1: Refer to Attachment 3, FCC Part 15B test report: FG08-052EAL dated May 15 2008

Note 2: Refer to Attachment 4, FCC 15.407 test report: R71111 Rev 2 dated June 12 2008 (re-issue)

Note 3: Refer to Attachment 5, FCC 15.407 DFS test report: R71303 Rev 2 dated April 18 2008

FCC Subpart E, Section 15.247 - WLAN

Refer to EMC Technologies Report No: M080522_Cert_512AN_HMW_DTS_BT

FCC Subpart C, Section 15.247 - BT

Refer to EMC Technologies' test report: M080522_Cert_EYSMJCS_512AN_HMW



15.0 MEASUREMENT UNCERTAINTIES

EMC Technologies has evaluated the equipment and the methods used to perform the emissions testing. The estimated measurement uncertainties for emissions tests shown within this report are as follows:

Conducted Emissions:	9 kHz to 30 MHz	±3.2 dB
Radiated Emissions:	30 MHz to 300 MHz	±5.1 dB
	300 MHz to 1000 MHz	±4.7 dB
	1 GHz to 18 GHz	±4.6 dB

The above expanded uncertainties are based on standard uncertainties multiplied by a coverage factor of $k=2$, providing a level of confidence of approximately 95%.

16.0 TEST REPORT APPENDICES

APPENDIX A: MEASUREMENT INSTRUMENT DETAILS

APPENDIX B: PHOTOGRAPHS

APPENDIX C: OPERATIONAL DESCRIPTION

APPENDIX D: BLOCK DIAGRAM

APPENDIX E: ANTENNA INFORMATION

APPENDIX F: SCHEMATIC

APPENDIX G: FCC LABELLING DETAILS

APPENDIX H: USER MANUAL

Attachment 1: RF Exposure Information

Attachment 2: FCC DOC for LifeBook T Series

Attachment 3: FCC Part 15B Test Report (Report: FG08-052EAL)

Attachment 4: Part 15.407 Test Report (Report: R71111 Rev 2)

Attachment 5: Part 15.407 DFS Test Report (Report: R71303 Rev 2)



This document must not be copied or reproduced, except in full without the written permission of the Manager, EMC Technologies Pty Ltd. The certificate of pg 3 may be reproduced in full.
www.emctech.com.au