

APPENDIX B PLOTS OF THE SAR MEASUREMENTS

Plots of the measured SAR distributions inside the phantom are given in this Appendix for all tested configurations.



Accredited for compliance with ISO/IEC 17025. The results of the test, calibrations and/or measurement included in this document are traceable to Australian/national standards. NATA is a signatory to the ILAC Mutual Recognition Arrangement for the mutual recognition of the equivalence of testing, calibration and inspection reports.

This document shall not be reproduced except in full.

Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:2

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 1 2450 MHz Antenna B (2) 27-10-14**

Communication System: 0 - OFDM 2450 MHz 6 Mbs (0); Communication System Band: ISM 2.4 GHz; Frequency: 2437 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2437$ MHz; $\sigma = 1.93$ S/m; $\epsilon_r = 51.2$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 2450 MHz Antenna B (2) 27-10-14/Channel 6 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.268 W/kg


Edge 1 2450 MHz Antenna B (2) 27-10-14/Channel 6 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 4.737 V/m; **Power Drift = -0.19 dB**

Averaged SAR: SAR(1g) = 0.246 W/kg; SAR(10g) = 0.113 W/kg

Maximum value of SAR (interpolated) = 0.647 W/kg



SAR Measurement Plot 1



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:3

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 1 2450 MHz Antenna B (2) DSSS 27-10-14**

Communication System: 0 - DSSS 2450 MHz 1Mbps (0); Communication System Band: ISM 2.4 GHz; Frequency: 2412 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=2412$ MHz; $\sigma = 1.89$ S/m; $\epsilon_r = 51.3$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 1 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.261 W/kg


Edge 1 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 5.536 V/m; **Power Drift = 0.04 dB**

Averaged SAR: SAR(1g) = 0.241 W/kg; SAR(10g) = 0.107 W/kg

Maximum value of SAR (interpolated) = 0.662 W/kg



SAR Measurement Plot 2



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:3

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 1 2450 MHz Antenna B (2) DSSS 27-10-14**

Communication System: 0 - DSSS 2450 MHz 1Mbs (0); Communication System Band: ISM 2.4 GHz; Frequency: 2437 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=2437$ MHz; $\sigma = 1.93$ S/m; $\epsilon_r = 51.2$; $\rho = 1000.0\text{g/cm}^3$
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 6 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.248 W/kg


Edge 1 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 6 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 5.498 V/m; **Power Drift = -0.03 dB**

Averaged SAR: SAR(1g) = 0.232 W/kg; SAR(10g) = 0.104 W/kg

Maximum value of SAR (interpolated) = 0.637 W/kg



SAR Measurement Plot 3



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:3

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 1 2450 MHz Antenna B (2) DSSS 27-10-14**

Communication System: 0 - DSSS 2450 MHz 1Mbps (0); Communication System Band: ISM 2.4 GHz; Frequency: 2412 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
 Medium Parameters used: $f=2412$ MHz; $\sigma = 1.89$ S/m; $\epsilon_r = 51.3$; $\rho = 1000.0$ g/cm³
 Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
 Sensor-Surface: 4 mm (Mechanical Surface Detection)
 Electronics: DAE3 Sn442; Calibrated: 10/12/2013
 Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
 DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 11 Test/Area Scan (81x101x1): Interpolated grid:
 $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.236 W/kg


Edge 1 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 11 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated
 grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 5.750 V/m; **Power Drift = -0.05 dB**

Averaged SAR: SAR(1g) = 0.232 W/kg; SAR(10g) = 0.102 W/kg

Maximum value of SAR (interpolated) = 0.638 W/kg



SAR Measurement Plot 4



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:4

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 1 2450 MHz Antenna A (1) 27-10-14**

Communication System: 0 - OFDM 2450 MHz 6 Mbs (0); Communication System Band: ISM 2.4 GHz; Frequency: 2437 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2437$ MHz; $\sigma = 1.93$ S/m; $\epsilon_r = 51.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 1 2450 MHz Antenna A (1) 27-10-14/Channel 6 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.023 W/kg


Edge 1 2450 MHz Antenna A (1) 27-10-14/Channel 6 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 2.552 V/m; **Power Drift = -0.10 dB**

Averaged SAR: SAR(1g) = 0.023 W/kg; SAR(10g) = 0.011 W/kg

Maximum value of SAR (interpolated) = 0.065 W/kg



SAR Measurement Plot 5



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:6

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 2450 MHz Antenna A (1) 27-10-14**

Communication System: 0 - OFDM 2450 MHz 6 Mbs (0); Communication System Band: ISM 2.4 GHz; Frequency: 2437 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2437$ MHz; $\sigma = 1.93$ S/m; $\epsilon_r = 51.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 2450 MHz Antenna A (1) 27-10-14/Channel 6 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.099 W/kg


Edge 2 2450 MHz Antenna A (1) 27-10-14/Channel 6 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 5.386 V/m; **Power Drift = -0.00 dB**

Averaged SAR: SAR(1g) = 0.098 W/kg; SAR(10g) = 0.044 W/kg

Maximum value of SAR (interpolated) = 0.239 W/kg



SAR Measurement Plot 6



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:7

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 2450 MHz Antenna A (1) DSSS 27-10-14**

Communication System: 0 - DSSS 2450 MHz 1Mbps (0); Communication System Band: ISM 2.4 GHz; Frequency: 2412 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2412$ MHz; $\sigma = 1.89$ S/m; $\epsilon_r = 51.3$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 2450 MHz Antenna A (1) DSSS 27-10-14/Channel 1 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.083 W/kg

Edge 2 2450 MHz Antenna A (1) DSSS 27-10-14/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 5.344 V/m; **Power Drift = -0.05 dB**


Averaged SAR: SAR(1g) = 0.083 W/kg; SAR(10g) = 0.038 W/kg

Maximum value of SAR (interpolated) = 0.205 W/kg



0 dB = 0.0830 W/kg = -10.81 dBW/kg

SAR Measurement Plot 7



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:7

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 2450 MHz Antenna A (1) DSSS 27-10-14**

Communication System: 0 - DSSS 2450 MHz 1Mbps (0); Communication System Band: ISM 2.4 GHz; Frequency: 2437 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2437$ MHz; $\sigma = 1.93$ S/m; $\epsilon_r = 51.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 2450 MHz Antenna A (1) DSSS 27-10-14/Channel 6 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.093 W/kg


Edge 2 2450 MHz Antenna A (1) DSSS 27-10-14/Channel 6 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 5.351 V/m; **Power Drift = -0.15 dB**

Averaged SAR: SAR(1g) = 0.091 W/kg; SAR(10g) = 0.042 W/kg

Maximum value of SAR (interpolated) = 0.216 W/kg



SAR Measurement Plot 8



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:7

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 2450 MHz Antenna A (1) DSSS 27-10-14**

Communication System: 0 - DSSS 2450 MHz 1Mbps (0); Communication System Band: ISM 2.4 GHz; Frequency: 2462 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2462$ MHz; $\sigma = 1.97$ S/m; $\epsilon_r = 51.1$; $\rho = 1000.0$ g/cm³
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 2450 MHz Antenna A (1) DSSS 27-10-14/Channel 11 Test/Area Scan (81x101x1): Interpolated grid: dx=1.2 mm, dy=1.2 mm; Maximum value of SAR (interpolated) = 0.084 W/kg

Edge 2 2450 MHz Antenna A (1) DSSS 27-10-14/Channel 11 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: dx=1.0 mm, dy=1.0 mm, dz=1.0 mm; Reference Value = 4.861 V/m; **Power Drift = -0.07 dB**


Averaged SAR: SAR(1g) = 0.084 W/kg; SAR(10g) = 0.039 W/kg

Maximum value of SAR (interpolated) = 0.199 W/kg



0 dB = 0.0840 W/kg = -10.76 dBW/kg

SAR Measurement Plot 9



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:8

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 2450 MHz Antenna B (2) 27-10-14**

Communication System: 0 - OFDM 2450 MHz 6 Mbs (0); Communication System Band: ISM 2.4 GHz; Frequency: 2437 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2437$ MHz; $\sigma = 1.93$ S/m; $\epsilon_r = 51.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 2450 MHz Antenna B (2) 27-10-14/Channel 6 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.059 W/kg


Edge 2 2450 MHz Antenna B (2) 27-10-14/Channel 6 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 4.991 V/m; **Power Drift = -0.20 dB**

Averaged SAR: SAR(1g) = 0.057 W/kg; SAR(10g) = 0.027 W/kg

Maximum value of SAR (interpolated) = 0.138 W/kg



SAR Measurement Plot 10



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:9

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 2450 MHz Antenna B (2) DSSS 27-10-14**

Communication System: 0 - DSSS 2450 MHz 1Mbps (0); Communication System Band: ISM 2.4 GHz; Frequency: 2412 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2412$ MHz; $\sigma = 1.89$ S/m; $\epsilon_r = 51.3$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 1 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.047 W/kg

Edge 2 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 4.644 V/m; **Power Drift = -0.04 dB**


Averaged SAR: SAR(1g) = 0.047 W/kg; SAR(10g) = 0.023 W/kg

Maximum value of SAR (interpolated) = 0.116 W/kg



0 dB = 0.0471 W/kg = -13.27 dBW/kg

SAR Measurement Plot 11



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:9

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 2450 MHz Antenna B (2) DSSS 27-10-14**

Communication System: 0 - DSSS 2450 MHz 1Mbps (0); Communication System Band: ISM 2.4 GHz; Frequency: 2437 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2437$ MHz; $\sigma = 1.93$ S/m; $\epsilon_r = 51.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 6 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.051 W/kg


Edge 2 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 6 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 4.711 V/m; **Power Drift = -0.16 dB**

Averaged SAR: SAR(1g) = 0.050 W/kg; SAR(10g) = 0.024 W/kg

Maximum value of SAR (interpolated) = 0.122 W/kg



SAR Measurement Plot 12



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:9

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Edge 2 2450 MHz Antenna B (2) DSSS 27-10-14**

Communication System: 0 - DSSS 2450 MHz 1Mbps (0); Communication System Band: ISM 2.4 GHz; Frequency: 2462 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2462$ MHz; $\sigma = 1.97$ S/m; $\epsilon_r = 51.1$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Edge 2 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 11 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.055 W/kg


Edge 2 2450 MHz Antenna B (2) DSSS 27-10-14/Channel 11 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 4.691 V/m; **Power Drift = -0.08 dB**

Averaged SAR: SAR(1g) = 0.053 W/kg; SAR(10g) = 0.026 W/kg

Maximum value of SAR (interpolated) = 0.128 W/kg



SAR Measurement Plot 13



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:10

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Lap Held 2450 MHz Antenna A (1) 27-10-14**

Communication System: 0 - OFDM 2450 MHz 6 Mbs (0); Communication System Band: ISM 2.4 GHz; Frequency: 2437 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2437$ MHz; $\sigma = 1.93$ S/m; $\epsilon_r = 51.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held 2450 MHz Antenna A (1) 27-10-14/Channel 6 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.072 W/kg


Lap Held 2450 MHz Antenna A (1) 27-10-14/Channel 6 Test/Zoom Scan (31x36x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 4.924 V/m; **Power Drift = -0.08 dB**

Averaged SAR: SAR(1g) = 0.068 W/kg; SAR(10g) = 0.033 W/kg

Maximum value of SAR (interpolated) = 0.157 W/kg



SAR Measurement Plot 14



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:11

DUT Name: Fujitsu Tablet Trust with Intel WLAN, Type: 7265NGW, Serial: WMF: 605718005785**Configuration: Lap Held 2450 MHz Antenna B (2) 27-10-14**

Communication System: 0 - OFDM 2450 MHz 6 Mbs (0); Communication System Band: ISM 2.4 GHz; Frequency: 2437 MHz, Communication System PAR: 0.00 dB; PMF: 1.00; Duty Cycle: 1:1.00
Medium Parameters used: $f=2437$ MHz; $\sigma = 1.93$ S/m; $\epsilon_r = 51.2$; $\rho = 1000.0\text{g/cm}^3$
Phantom section: Flat Section

DASY Configuration:


Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;
Sensor-Surface: 4 mm (Mechanical Surface Detection)
Electronics: DAE3 Sn442; Calibrated: 10/12/2013
Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101
DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

Lap Held 2450 MHz Antenna B (2) 27-10-14/Channel 6 Test/Area Scan (81x101x1): Interpolated grid: $dx=1.2$ mm, $dy=1.2$ mm; Maximum value of SAR (interpolated) = 0.087 W/kg

Lap Held 2450 MHz Antenna B (2) 27-10-14/Channel 6 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 5.259 V/m; **Power Drift = -0.08 dB**


Averaged SAR: SAR(1g) = 0.084 W/kg; SAR(10g) = 0.040 W/kg

Maximum value of SAR (interpolated) = 0.210 W/kg



0 dB = 0.0865 W/kg = -10.63 dBW/kg

SAR Measurement Plot 15



Test Lab: EMCTech

Test File: M141024 Tablet 2450 MHz WLAN 11bg.da52:12

DUT Name: Dipole 2450 MHz, Type: DV2450V2, Serial: 724**Configuration: System Check 27-10-14**

Communication System: 0 - CW; Communication System Band: 2450 MHz; Frequency: 2450 MHz,

Communication System PAR: 0.00 dB; PMF: 0.00; Duty Cycle: 1:1.00

Medium Parameters used: $f=2450$ MHz; $\sigma = 1.95$ S/m; $\epsilon_r = 51.2$; $\rho = 1000.0\text{g/cm}^3$

Phantom section: Flat Section

DASY Configuration:

Probe: ET3DV6 - SN1380; ConvF: (4.12,4.12,4.12); Calibrated: 13/12/2013;

Sensor-Surface: 4 mm (Mechanical Surface Detection)

Electronics: DAE3 Sn442; Calibrated: 10/12/2013

Phantom: ELI 4.0; Type: QDOVA001BA; Serial: 1101


DASY52 52.8.8(1222); SEMCAD X Version 14.6.10 (7331)

System Check 27-10-14/Channel 1 Test/Area Scan (51x51x1): Interpolated grid: $dx=1.5$ mm, $dy=1.5$ mm;

Maximum value of SAR (interpolated) = 18.300 W/kg

System Check 27-10-14/Channel 1 Test/Zoom Scan (31x31x36)/Cube 0: Interpolated grid: $dx=1.0$ mm, $dy=1.0$ mm, $dz=1.0$ mm; Reference Value = 86.695 V/m; **Power Drift = -0.02 dB****Averaged SAR: SAR(1g) = 13.500 W/kg; SAR(10g) = 6.110 W/kg**

Maximum value of SAR (interpolated) = 34.300 W/kg



SAR Measurement Plot 16

