



EMC Technologies Pty Ltd
ABN 82 057 105 549
57 Assembly Drive
Tullamarine Victoria Australia 3043

Ph: + 613 9335 3333
Fax: + 613 9338 9260
email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210
Class II Permissive Change**

FCC ID: EJE-WL0010
Industry Canada ID: 337J-WL0010

Test Sample: GOLAN INTEL Mini-PCI WLAN Module
Model: WM3945ABG

Report Number: M060434_Cert_WM3945ABG_DTS_Class_2

Tested for: Fujitsu Australia Ltd.

Issue Date: 4th May 2006

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements which include the requirements of ISO/IEC 17025 and are traceable to national standards of measurement. This document shall not be reproduced, except in full. The certificate on page 3 may be reproduced in full.

NATA Accredited Laboratory Number:
5292

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210
Class II Permissive Change**

EMC Technologies Report No. M060434_Cert_WM3945ABG_DTS_Class_2

Issue Date: 4th May 2006

CONTENTS

**1.0 INTRODUCTION
2.0 GENERAL INFORMATION**

RESULTS – WLAN, WM3945ABG (802.11b, 802.11g and *802.11a)

**3.0 SPURIOUS EMI MEASUREMENTS
4.0 RADIO FREQUENCY EXPOSURE
5.0 COMPLIANCE STATEMENT**

***RESULTS of 802.11a (5.15 – 5.35 GHz Band)**

Refer to Report No: M060434_Cert_WM3945ABG_NII_Class_2

APPENDIX A: ANTENNA INFORMATION

APPENDIX B: WLAN, BT and ANTENNA LOCATIONS PHOTOS

Attachment 1: RF Exposure Information



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210
Class II Permissive Change

Report Number: M060434_Cert_WM3945ABG_DTS_Class_2

Test Sample: GOLAN INTEL Mini-PCI WLAN Module
Model: WM3945ABG
Manufacturer: INTEL Corp

FCC ID: EJE-WL0010
Industry Canada ID: 337J-WL0010
Equipment Type: Intentional Radiator (Transceiver)

Host Notebook Fujitsu Ltd.
Manufacturer: Mobile Computing Division
Address: 1-1 Kamikodanaka 4-Chome, Nakahara-Ku, Kawasaki, Japan
Contact: Mr. Tsuyoshi Uchihara

Tested for: Fujitsu Australia Ltd

Test Standards: FCC Part 15, Subpart C – Intentional Radiators
FCC Part 15.247: 2400 – 2483.5 MHz & 5725 – 5850 MHz Operation Band
ANSI C63.4 – 2003
OET Bulletin No. 65

RSS-210 Issue 6 Low Power Licence-Exempt RadioCommunication Devices:
6.2.2 (o) 2400 – 2483.5 MHz & 5725 – 5850 MHz Spread Spectrum

RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and Portable
Radio Transmitters with respect to Health Canada's Safety Code 6 for
Exposure of Humans to Radio Frequency Fields

Test Dates: 27th April to 1st May 2006

Test Officer: 
Chieu Huynh - B.Eng (Hons) Electronics

Attestation: *I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.*

Authorised Signatory: 
Chris Zombolas
Technical Director
EMC Technologies Pty Ltd



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210
Class II Permissive Change

1.0 INTRODUCTION

Testing was performed on the INTEL Mini-PCI Wireless LAN Module (GOLAN 11a+b/g), Model: WM3945ABG installed in Fujitsu notebook PC.

The WM3945ABG WLAN module has been recently certified by Fujitsu Australia Ltd under the FCC ID: EJE-WL0010 (IC: 337J-WL0010). The intention of this application is to add host models (Fujitsu Notebooks) and re-certify the WM3945ABG WLAN module installed in, model: C1410 as a **Class II Permissive Change**.

The GOLAN WLAN module was originally certified by INTEL as a modular approval under FCC ID: PD9WM3945ABG (Canada ID: 1000M-WM3945ABG). The intention of this application is to get a Limited Modular approval for this WLAN module for use in Fujitsu notebook PCs. The Radio modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

The GOLAN WLAN supports IEEE 802.11b, IEEE 802.11g and IEEE802.11a (DTS & U-NII) configurations. Tests were performed in all three configurations.

The results for configurations IEEE 802.11b, IEEE 802.11g and IEEE802.11a (DTS: 5725 – 5850 MHz) are reported in this test report.

The results for IEEE 802.11a (U-NII) are reported separately.

Refer to EMC Technologies' test report: M060434_Cert_WM3945ABG_NII_Class_2 (U-NII)

The second transmitter in the notebook is a Bluetooth module, model: EYTF3CSFT. This Bluetooth module has been recently certified by Fujitsu Australia Ltd under the FCC ID: EJE-BT0001 (IC: 337J-BT0001).

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart C:	Rules for intentional radiators (particularly section 15.247)
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.247:	Operation in the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz

The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart C - Section 15.247.

The test sample also complies with the Industry Canada RSS-210 issue 6 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) 2400 – 2483.5 MHz and 5725 - 5850 MHz Spread Spectrum requirements and the RF exposure requirements of RSS-102.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

1.1 Summary of Results

1.1.1 FCC Subpart C, Section 15.247

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Note 1
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Note 1
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	Note 1
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	Note 1
15.247 (i)		Radio Frequency Hazard	Complies
15.247 (d)	6.2.2(o)(e1)	Out of Band Emissions	Complies
15.247 (e)	6.2.2(o)(iv)	Peak Power Spectral Density	Note 1

Note 1: Refer to EMC test report M060108_Cert_WM3945ABG_DTS and M060108_Cert_WM3945ABG_DTS_Class_2 with FCC ID: EJE-WL0010 (IC ID: 337J-WL0010)

1.1.2 FCC Subpart E, Section 15.407

FCC Part 15, Subpart E Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Note 1
15.205	6.3	Operation in Restricted Band	Note 1
15.207	6.6	Conducted Emissions	Note 1
15.209	6.3	Radiated Emissions	Note 1
15.407 (a)(1) (a)(2)	6.2.2(q1)	Peak Transmit Power	Note 1
15.407 (a)(5)	6.2.2(q1)	Peak Power Spectral Density	Note 1
15.407 (a)(6)		Peak Excursion	Note 1
15.407 (b)	6.2.2(q1)	Undesirable Emission	Note 1
15.407 (f)		Radio Frequency Hazard	Note 1
15.407 (g)	6.4	Frequency Stability	Note 1

Note 1: Refer to EMC Technologies Report No: M060434_Cert_WM3945ABG_NII_Class_2

Refer to EMC test report M060108_Cert_WM3945ABG_NII and M060108_Cert_WM3945ABG_NII_Class_2 with FCC ID: EJE-WL0010 (IC ID: 337J-WL0010)

The measurement procedure used was in accordance with ANSI C63.4-2003 and OET Bulletin No. 65. The instrumentation conformed to the requirements of ANSI C63.2-1996.

1.2 Modifications by EMC Technologies

No modifications were required.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.0 GENERAL INFORMATION

(Information supplied by the Client)

2.1 EUT (WLAN) Details

Transmitter:	Mini-PCI Wireless LAN Module
Wireless Module:	GOLAN (11a+b/g)
Model Number:	WM3945ABG
Manufacturer:	Intel Corporation
Modulation Type:	Direct Sequence Spread Spectrum (DSSS for 802.11b) Orthogonal Frequency Division Multiplexing (OFDM for 802.11g) Orthogonal Frequency Division Multiplexing (OFDM for 802.11a)
802.11a and 802.11g	BPSK – 6Mbps, 9Mbps QPSK – 12Mbps, 18Mbps 16QAM – 24Mbps, 36Mbps 64QAM – 48Mbps, 54Mbps
802.11b	DBPSK – 1Mbps DQPSK – 2Mbps CCK – 5.5Mbps, 11Mbps
Frequency Range:	2.4 – 2483.5 GHz for 11b/g 5.15 - 5.35 GHz and 5.725 - 5.850 GHz for 11a
Number of Channels:	11 channels for 11b or 11g 13 channels for 11a
Power Supply:	3.3 VDC from PCI bus

Frequency Allocation Table:

Band	Channel	Lower Frequency	Upper Frequency	Americas	Europe	Japan	High Band
		SKU #1 MOW1	SKU #2 MOW2	SKU #3 Japan	SKU #4 ROW		
802.11b/g	1-11	2.401 GHz	2.473 GHz	X	X	X	X
802.11b/g	12-13	2.467 GHz	2.483 GHz		X	X	X
802.11a	34-46	5.08 GHz	5.22 GHz		X	X	
802.11a	36-48	5.150 GHz	5.250 GHz	X	X		
802.11a	52-64	5.250 GHz	5.350 GHz	X	X		
802.11a	100-140	5.470 GHz	5.725 GHz		X		
802.11a	149-161	5.725 GHz	5.825 GHz	X			X
802.11a	165	5.815 GHz	5.835 GHz	X			X

Channels Tested and Output power setting:

Channel and Mode:	Output Power setting (average, dBm)
802.11b mode	
*Channels 1	16
*Channel 6 and 11	18
802.11g mode	
*Channel 1	16
*Channel 6	17
*Channel 11	15
802.11a mode	
***Channel 36	16
***Channels 52 and 64	17
**Channels 149, 157 and 165	17

*Channels tested, refer to EMC report M060108_Cert_WM3945ABG_DTS and M060108_Cert_WM3945ABG_DTS_Class_2

**Channels tested and reported in this report

***Channels tested, refer to EMC report M060108_Cert_WM3945ABG_NII and M060108_Cert_WM3945ABG_NII_Class_2



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.2 Operational Description

The GOLAN WLAN Module was tested in Fujitsu host notebook C1410.

The Intel WLAN test software "CRTU" was used to transmit continuously during the tests. For Spurious and Harmonics tests both radio modules (WLAN and Bluetooth) were simultaneously transmitting.

2.3 Test Configuration

Radiated tests were performed for measuring the harmonics and spurious from the transmitters.

Limited Modular Approval (LMA) details to cover the following Fujitsu notebook configurations:

Fujitsu Notebook Model	WLAN Module	WLAN Antenna	FCC/IC CERTIFICATION STATUS
E8110	GOLAN WM3945ABG	2 x Inverted F antenna	GRANT Issued FCC ID: EJE-WL0010
E8210		2 x Inverted F antenna	
S7110		2 x Monopole Antenna	
Q2010		2 x Inverted F antenna	
S6310		2 x Inverted F antenna	
Following NEW Model to be added			
C1410	GOLAN WM3945ABG	2 x Inverted F Antenna	Tested model in this application

Fujitsu Notebook Model	WLAN antenna type	WLAN antenna Peak gain [dBi]			
		2.4GHz band	5GHz low band	5GHz Mid band	5GHz High band
E8110	Inverted F	-0.99	-1.12	-0.56	-0.56
E8210	Inverted F	2.47	-0.44	0.38	0.38
S7110	Monopole	2.08	1.66	0.59	1.79
Q2010	Inverted F	2.32	3.23	3.36	1.48
S6310	Inverted F	-0.38	1.09	0.64	0.90
C1410	Inverted F	2.42	2.72	2.42	3.08

The location of the WLAN antennas and the design of the WLAN antennas (Inverted F) in host C1410 notebook (new model added) are identical to the antenna in other host notebooks (had been certified).

Only the highest band of the 5 GHz WLAN (5725 – 5850 MHz) was tested for host C1410 notebook as the antenna gain for this band is higher than in other host notebooks (refer to the table above). The result for this band is reported under section 3.0.

For harmonics and spurious emissions of the WLAN installed in other host notebooks were reported under EMC Technologies report number: M060108_Cert_WM3945ABG_DTS and M060108_Cert_WM3945ABG_DTS_Class_2.

There are no IM spurious emissions recorded for host C1410 when both radio modules (WLAN and Bluetooth) simultaneously transmitting.

Refer to Appendix_A_C1410 for antenna details.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

To qualify for a class 2 permissive change, the output power was re-measured on host C1410. The highest output powers are report below.

The highest output powers were granted:

Frequency MHz	Output Power Granted dBm
5800	17.9
2400	17.1

The highest new output powers are measured:

Frequency MHz	New Output Power Measured dBm
5800	16.6
2400	16.8

2.4 Host PC Details

Host notebook :	LifeBook C series
Model Name:	C1410
Serial Number:	Pre-production Sample
Manufacturer:	FUJITSU LIMITED
CPU Type and Speed:	Yonah-DC 2.16GHz
LCD	15"WXGA / 15"XGA
Wired LAN:	Marvell 88E8055 : 10 Base-T/100 Base-TX/1000Base-T
Modem:	Agere MDC1.5 modem Model: D40
Port Replicator Model:	FPCPR63
AC Adapter Model:	SEC100P2-19.0(Sanken) / SQ2N80W19P-01(Nagano JRC)
Voltage:	19 V
Current Specs:	4.22A
Watts:	80W
RADIO MODULES	
Module # 1:	WLAN (Golan IEEE802.11a+b/g)
WLAN Model Number:	WM3945ABG
WLAN Manufacturer:	Intel Corp.
Interface Type:	Mini-Card Wireless LAN Module
Antenna Types:	Nissei Electric Inverted F Antenna Model: CP250925
Antenna gain:	Located on top edge of LCD screen
Module # 2:	Refer antenna data provided separately (Appendix A)
Model Number:	Bluetooth Module
Manufacturer:	EYTF3CS FT
Interface Type:	TAIYO YUDEN
Antenna Types:	USB
Antenna gain:	Yokowo Inverted F Antenna, Model: YCE-5250
Max. Output Power:	Location: right hinge of LCD
Antenna gain:	3.27 dBi
Max. Output Power:	4 dBm



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.5 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 1 and 3 metres from the EUT. OET Bulletin 65 dated June 2001 was used for reference.

2.6 Test Facility

2.6.1 General

Radiated Emission measurements were performed at EMC Technologies open area test site (OATS) situated at Lerderderg Gorge, near the township of Bacchus Marsh in Victoria, Australia. Conducted measurements at an antenna ports were performed at EMC Technologies' laboratory in Tullamarine, Victoria Australia.

The above test sites have been accepted for testing by the Federal Communications Commission (FCC) - **FCC Registration Number 90560**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional). **Industry Canada File Number IC 4161.**

2.6.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

"FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E)."

The current full scope of accreditation can be found on the NATA website: www.nata.asn.au. It also includes a large number of emission, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Laboratory (NML) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A²LA).

2.7 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Laboratory (NML). All equipment calibration is traceable to Australia national standards at the National Measurements Laboratory. The reference antenna calibration was performed by NML and the working antennas (biconical and log-periodic) calibrated by the NATA approved procedures.

2.8 Ambients at OATS

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

RESULTS

WLAN Module – WM3945ABG (802.11b, 802.11g and 802.11a (DTS))

3.0 SPURIOUS EMISSION MEASUREMENTS

3.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.247(d).

Radiated emission measurements were performed to the limits as per section 15.209. The measurements were made at the open area test site.

The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report. The EMI Receiver was operated under software control via the PC Controller through the IEEE.488 Interface Bus Card Adaptor. The test frequency range was sub-divided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks while also permitting fast frequency scan times. Calibrated EMCO 3115, EMCO 3116 and ETS standard gain horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions between 30 - 1000 MHz, refer to EMC test report M060108_Cert_WM3945ABG_DTS with FCC ID: EJE-WL0010 (IC ID: 337J-WL0010)

The measurement of emissions above 1000 MHz, appearing in the restricted bands, was made using an average detector with a bandwidth of 1.0 MHz.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Quasi-Peak/Average Detectors. The software for cable losses automatically corrected the measurement data for each frequency range, antenna factors and preamplifier gain and all data was then stored on disk in sequential data files. This process was performed for both horizontal and vertical antenna polarisations.

3.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

E = V + AF - G + L Where:

E = Radiated Field Strength in dB μ V/m.

V = EMI Receiver Voltage in dB μ V. (measured value)

AF = Antenna Factor in dB(m⁻¹). (stored as a data array)

G = Preamplifier Gain in dB. (stored as a data array)

L = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

- **Example Field Strength Calculation**

Assuming a receiver reading of 34.0 dB μ V is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V/m}$$

Measurement uncertainty with a confidence interval of 95% is:

- Free radiation tests (1000 MHz – 18,000 MHz) \pm 4.1 dB



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

3.3 Radiated Emissions

All measurements above 1 GHz were initially made over a distance of 3 metres. This was decreased to 1.0 metre as the emission levels from the device were very low.

Measurements were performed on Fujitsu host notebook C1410. Only the highest band of the 5 GHz WLAN (5725 – 5850 MHz) was tested.

Testing was performed while both the WLAN transmitter and Bluetooth transmitter continuously operated.

3.3.1 Spurious and Harmonics

Initial investigations were performed with four modulation types: (BPSK, QPSK, 16QAM and 64QAM). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 6 Mbps (BPSK).

The EUT was operating at its highest channel (5825 MHz), the field strength at 5850 MHz was: 65.9 dB μ V/m peak and 52.7 dB μ V/m average

The levels were > 20 dB below the maximum field strength of the in-band carrier.

The EUT was operating at its lowest channel (5745 MHz), the field strength at 5725 MHz was: 77.1 dB μ V/m peak and 57.3 dB μ V/m average

The levels were > 20 dB below the maximum field strength of the in-band carrier.

Channel 149 - 5745 MHz

Frequency MHz	Peak Detector dB μ V	Average Detector dB μ V	Peak Limit dB μ V/m	Average Limit dB μ V/m	Result
5745	107.1	96.4	-	-	-
11490	54.3	42.0	74.0	54.0	Pass
17235	58.5	47.6	-	-	-
22980	69	56	84.0*	64.0*	Pass
28725	79	67	-	-	-
34470	80	68	-	-	-
4933	51.3	40.2	74.0	54.0	Pass

*Limits were corrected for 1 metre measurement.

Channel 157 - 5785 MHz

Frequency MHz	Peak Detector dB μ V	Average Detector dB μ V	Peak Limit dB μ V/m	Average Limit dB μ V/m	Result
5785	106.6	95.8	-	-	-
11570	54.0	42.2	74.0	54.0	Pass
17355	58.3	46.9	-	-	-
23140	69	56	-	-	-
28925	79	67	-	-	-
34710	80	68	-	-	-
4821	53.6	43.1	74.0	54.0	Pass

*Limits were corrected for 1 metre measurement.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

Channel 165 - 5825 MHz

Frequency MHz	Peak Detector dBuV	Average Detector dBuV	Peak Limit dBuV/m	Average Limit dBuV/m	Result
5825	106.7	95.5	-	-	-
11650	54.3	41.9	74.0	54.0	Pass
17475	56.8	45.4	-	-	-
23300	69	56	-	-	-
29125	79	67	-	-	-
34950	80	68	-	-	-
4856	55.8	44.4	74.0	54.0	Pass

*Limits were corrected for 1 metre measurement.

Result: Harmonic and spurious emissions were recorded within the restricted bands of up to 40 GHz. Harmonics were low and confirmed with both RBW and VBW reduced (the peak and average levels listed in the above tables were noise floor readings). Emissions were complied with the FCC limits in section 15.209 and 15.247 by a margin of 9.6 dB. The measurement uncertainty for radiated emissions in this band was ± 4.1 dB.

3.3.2 IM Spurious

There are no IM spurious emissions recorded when both radio modules (WLAN and Bluetooth) simultaneously transmitting.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

4.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.247(i)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

Transmitter # 1: The WLAN antennas are located on the top edge of LCD screen (2 antennas left and right) and projected distance of greater than 20cm from user.

Transmitter # 2: The Bluetooth antenna is located right hinge of LCD and projected distance of less than 20cm from user.

SAR is not required as the WLAN transmitter is mobile device and the power for the Bluetooth transmitter is below the low threshold.

The separation distance between the WLAN and BT antennas is greater than 20cm. Therefore, they are not co-located transmitters.

The MPE calculation shown below is for the WLAN power density.

In accordance with Section 1.1310, the Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure of 1.0 has been applied, i.e 1mW/cm².

Friis transmission formula: $P_d = (P * G) / (4 * \pi * r^2)$

where: P_d = power density (mW/cm²)

P = power input to the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of the antenna (cm)

The result was extracted from EMC report: M060108_Cert_WM3945ABG_DTS (WLAN)

Prediction frequency = **5785 MHz**

Maximum peak output power = 17.9 dBm = 61.7 mW

Antenna (Inverted F) gain (max) = 3.08 dBi = 2.03 numeric

The power density calculated = 0.025 mW/cm²

Prediction frequency = **2437 MHz**

Maximum peak output power = 17.1 dBm = 51.3 mW

Antenna (Inverted F) gain (max) = 2.47 dBi = 1.77 numeric

The power density calculated = 0.02 mW/cm²

MPE limit for uncontrolled exposure at prediction frequency = 1 mW/cm²

Results: Calculations show that the Radio devices with described antennas complied with Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

5.0 COMPLIANCE STATEMENT

The INTEL Mini-PCI Wireless LAN Module (GOLAN 11a+b/g), Model: WM3945ABG installed in Fujitsu notebook PCs tested on behalf of Fujitsu Australia Ltd, **comply** with the **Class II Permissive Change** requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators), Section 15.247 - Operation in the frequency band 2400 - 2483.5 MHz and 5725 – 5850 MHz.

The test sample also complies with the Industry Canada RSS-210 issue 6 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) 2400 – 2483.5 MHz Spread Spectrum requirements and the RF exposure requirements of RSS-102.

Results were as follows:

FCC Subpart C, Section 15.247

FCC Part 15, Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Result
15.203	5.5	Antenna Requirement	Note 1
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Note 1
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	Note 1
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	Note 1
15.247 (i)		Radio Frequency Hazard	Complies
15.247 (d)	6.2.2(o)(e1)	Out of Band Emissions	Complies
15.247 (e)	6.2.2(o)(iv)	Peak Power Spectral Density	Note 1

Note 1: Refer to EMC test report M060108_Cert_WM3945ABG_DTS and M060108_Cert_WM3945ABG_DTS_Class_2 with FCC ID: EJE-WL0010 (IC ID: 337J-WL0010)

The results for IEEE 802.11a (U-NII) is reported separately.

Refer to EMC Technologies' test report: M060434_Cert_WM3945ABG_NII_Class_2 (U-NII)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

TEST REPORT APPENDICES

APPENDIX A: ANTENNA INFORMATION

APPENDIX B: WLAN, BT and ANTENNA LOCATIONS PHOTOS

Attachment 1: RF Exposure Information



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.