



EMC Technologies Pty Ltd
ABN 82 057 105 549
176 Harrick Road
Keilor Park Victoria Australia 3042

Ph: +613 9365 1000
Fax: +613 9331 7455
email: melb@emctech.com.au

**EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210
Class II Permissive Change**

FCC ID: EJE-WL0011
Industry Canada ID: 337J-WL0011

Test Sample: XB62 Atheros Mini-PCI WLAN Module
Model: AR5BXB6

Report Number: M070317_Cert_AR5BXB6_DTS_C2PC

Tested for: Fujitsu Australia Ltd.

Issue Date: 23rd April 2007

EMC Technologies Pty Ltd reports apply only to the specific samples tested under stated test conditions. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. EMC Technologies Pty Ltd shall have no liability for any deductions, inferences or generalisations drawn by the client or others from EMC Technologies Pty Ltd issued reports. This report shall not be used to claim, constitute or imply product endorsement by EMC Technologies Pty Ltd.



The tests, calibrations or measurements covered by this document have been performed in accordance with NATA requirements which include the requirements of ISO/IEC 17025 and are traceable to national standards of measurement. This document shall not be reproduced, except in full. The certificate on page 3 may be reproduced in full.

NATA Accredited Laboratory Number:
5292

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210
Class II Permissive Change

EMC Technologies Report No. M070317_Cert_AR5BXB6_DTS_C2PC

Issue Date: 23rd April 2007

CONTENTS

1.0 INTRODUCTION
2.0 GENERAL INFORMATION

FCC 15.247 (DTS) RESULTS
3.0 SPURIOUS EMI MEASUREMENTS
4.0 RADIO FREQUENCY EXPOSURE
5.0 COMPLIANCE STATEMENT

FCC 15.407 (U-NII) RESULTS
Refer to Report No: M070317_Cert_AR5BXB6_NII_C2PC

APPENDIX A: ANTENNA INFORMATION

APPENDIX B: WLAN and ANTENNA LOCATIONS PHOTOS

Attachment 1: RF Exposure Information



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210
Class II Permissive Change

Report Number: M070317_Cert_AR5BXB6_DTS_C2PC

Test Sample: XB62 Mini-PCI WLAN Module

Model: AR5BXB6

Manufacturer: Atheros Communications

FCC ID: EJE-WL0011

Industry Canada ID: 337J-WL0011

Equipment Type: Intentional Radiator (Transceiver)

Host Notebook Fujitsu Ltd.

Manufacturer: Mobile Computing Division

Address: 1-1 Kamikodanaka 4-Chome, Nakahara-Ku, Kawasaki, Japan

Contact: Mr. Tsuyoshi Uchihara

Tested for: Fujitsu Australia Ltd

Test Standards: FCC Part 15 – Radio Frequency Devices (August 2006)

FCC Part 15 Subpart C - Intentional Radiators

Section 15.247: 2400 – 2483.5 MHz & 5725 – 5850 MHz Operation Bands

ANSI C63.4 – 2003

OET Bulletin No. 65

RSS-210 Issue 6 Low Power Licence-Exempt RadioCommunication Devices:
 6.2.2 (o) 2400 – 2483.5 MHz & 5725 – 5850 MHz Spread Spectrum

RSS-102 Issue 1 (Provisional), Evaluation Procedure for Mobile and Portable
 Radio Transmitters with respect to Health Canada's Safety Code 6 for
 Exposure of Humans to Radio Frequency Fields

Test Dates: 12th to 23rd April 2007

Test Engineer:




Chieu Huynh - B.Eng (Hons) Electronics

Attestation:

I hereby certify that the device(s) described herein were tested as described in this report and that the data included is that which was obtained during such testing.

Authorised Signatory:


Chris Zombolas
 Technical Director
 EMC Technologies Pty Ltd



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

EMI TEST REPORT FOR CERTIFICATION
to
FCC PART 15 Subpart C (Section 15.247) & RSS-210
Class II Permissive Change

1.0 INTRODUCTION

Testing was performed on the Atheros Mini-PCI Wireless LAN Module (XB62 11a+b/g), Model: AR5BXB6 installed in Fujitsu notebook PC.

The AR5BXB6 WLAN module has been certified by Fujitsu Australia Ltd under the FCC ID: EJE-WL0011 (IC: 337J-WL0011). The intention of this application is to add host models (Fujitsu Notebooks) and re-certify the AR5BXB6 WLAN module installed in host, model: E8410/E8490 as a **Class II Permissive Change**.

The Atheros WLAN module was originally certified by Atheros as a modular approval under FCC ID: PPD-AR5BXB6-M (Canada ID: 4104A-AR5BXB6). The intention of this application is to get a Limited Modular approval for this WLAN module for use in Fujitsu notebook PCs. The Radio modules are installed in a controlled environment at the Fujitsu notebook production/assembly factory.

The Atheros WLAN supports IEEE 802.11b, IEEE 802.11g and IEEE802.11a (DTS & U-NII) configurations. Tests were performed in all three configurations.

The results for configurations IEEE 802.11b, IEEE 802.11g and IEEE802.11a (DTS: 5725 – 5850 MHz) are reported in this test report.

The results for IEEE 802.11a (U-NII) are reported separately.

Refer to EMC Technologies' test report: M070317_Cert_AR5BXB6_NII_C2PC (U-NII)

The second transmitter in the notebook is a Bluetooth module, model: EYTF3CSFT. This Bluetooth module has been recently certified by Fujitsu Australia Ltd under the FCC ID: EJE-BT0001 (IC: 337J-BT0001).

Test results and procedures were performed in accordance with the following Federal Communications Commission (FCC) standards/regulations:

47 CFR, Part 15, Subpart C:	Rules for intentional radiators (particularly section 15.247)
Section 15.203:	Antenna requirements
Section 15.205:	Restricted bands of operation
Section 15.207:	Conducted Emission Limits
Section 15.209:	Radiated Emission Limits (General requirements)
Section 15.247:	Operation in the bands 902-928 MHz, 2400-2483.5 MHz, 5725-5850 MHz

The test sample **complied** with the requirements of 47 CFR, Part 15 Subpart C - Section 15.247.

The test sample also complies with the Industry Canada RSS-210 issue 6 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) 2400 – 2483.5 MHz and 5725 - 5850 MHz Spread Spectrum requirements and the RF exposure requirements of RSS-102.

The measurement procedure used was in accordance with ANSI C63.4-2003 and OET Bulletin No. 65. The instrumentation conformed to the requirements of ANSI C63.2-1996.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

1.1 Summary of Results

1.1.1 FCC Subpart C, Section 15.247

FCC Part 15 Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Results
15.203	5.5	Antenna Requirement	Note 1
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Note 1
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	Note 1
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	Note 1
15.247 (c)		Antenna Gain > 6 dBi	Not Applicable. Antenna gain < 6 dBi
15.247 (d)	6.2.2(o)(e1)	Out of Band Emissions	Complies
15.247 (e)	6.2.2(o)(iv)	Peak Power Spectral Density	Note 1
15.247 (f)		*Hybrid Systems	Not Applicable. EUT does not employ a hybrid system
15.247 (g)		Frequency Hopping	Not Applicable. EUT is not a frequency hopping
15.247 (h)		Frequency Hopping	Not Applicable. EUT is not a frequency hopping
15.247 (i)		Radio Frequency Hazard	Complies

*Hybrid systems are those that employ a combination of both frequency hopping and digital modulations technique.

Note 1: Refer to EMC test report M060223_Cert_AR5BXB6_DTS with FCC ID: EJE-WL0011 (IC ID: 337J-WL0011)

1.1.2 FCC Subpart E, Section 15.407 - WLAN

Refer to EMC Technologies Report M070317_Cert_AR5BXB6_NII_C2PC

1.2 Modifications by EMC Technologies

No modifications were required.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.0 GENERAL INFORMATION

(Information supplied by the Client)

2.1 EUT (WLAN) Details

Transmitter:	Mini-Card Wireless LAN Module
Wireless Module:	XB62 (11a+b/g)
Model Number:	AR5BXB6
Manufacturer:	Atheros
Modulation Type:	Direct Sequence Spread Spectrum (DSSS for 802.11b) Orthogonal Frequency Division Multiplexing (OFDM for 802.11g) Orthogonal Frequency Division Multiplexing (OFDM for 802.11a)
802.11a and 802.11g	BPSK – 6Mbps, 9Mbps QPSK – 12Mbps, 18Mbps 16QAM – 24Mbps, 36Mbps 64QAM – 48Mbps, 54Mbps Turbo mode: 12 Mbps - 108 Mbps
802.11b	DBPSK – 1Mbps DQPSK – 2Mbps CCK – 5.5Mbps, 11Mbps
Frequency Range:	2.4 – 2483.5 GHz for 11b/g 5.15 - 5.35 GHz, 5.47 – 5.725 GHz and 5.725 - 5.850 GHz for 11a
Antenna gain:	Max antenna gain is less than 6 dBi.
Power Supply:	3.3 VDC from PCI bus

Frequency Allocation Table:

Band	Channel	Lower Freq.	Upper Freq.	WWF1	WWF2	JPF4	KRF1
802.11b/g	1-11	2.412GHz	2.462GHz	X	X	X	X
802.11b/g	12-13	2.467GHz	2.472GHz		X	X	X
802.11a	36-48	5.150GHz	5.250GHz	X	X	X (Note 1)	X
802.11a	52-64	5.250GHz	5.350GHz	X	X	X	X
802.11a	100-140	5.470GHz	5.725GHz	X	X		X
802.11a	149-165	5.725GHz	5.850GHz	X	X		X

Note 1: Odd channel support

Channels Tested and Output power setting:

Channel and Mode:	Output Power setting (average, dBm)
802.11b mode	
*Channel 1, 6 and 11	17 (1 Mbps to 11 Mbps)
802.11g mode	
*Channel 1, 6 and 11	16 (6 Mbps to 48 Mbps)
*Channel 1, 6 and 11	15 (54 Mbps)
802.11a mode	
**Channel 36, 52, 64, 100, 120 and 140	16 (6 Mbps to 36 Mbps)
**Channel 36, 52, 64, 100, 120 and 140	14 (48 Mbps)
**Channel 36, 52, 64, 100, 120 and 140	13 (54 Mbps)
*Channels 149, 152, 157, 160 and 165	16 (6 Mbps to 36 Mbps)
*Channels 149, 152, 157, 160 and 165	14 (48 Mbps)
*Channels 149, 152, 157, 160 and 165	11 (54 Mbps)

*Channels tested and reported in this report

**Channels tested and reported in the U-NII submission (M070317_Cert_AR5BXB6_NII_C2PC)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.2 Operational Description

The Atheros WLAN Module was tested in Fujitsu host notebook E8410(80W) / E8490(100W).

The Atheros WLAN test software "CRTU" was used to transmit continuously during the tests. For Spurious and Harmonics tests both radio modules (WLAN and Bluetooth) were simultaneously transmitting.

2.3 Test Configuration

Radiated tests were performed for measuring the harmonics and spurious from the transmitters.

Limited Modular Approval (LMA) details to cover the following Fujitsu notebook configurations:

Fujitsu Notebook Model	WLAN Module	WLAN Antenna	FCC/IC CERTIFICATION STATUS
E8210	Atheros XB62	2 x Inverted F antenna	GRANT Issued FCC ID: EJE-WL0011
Q2010		2 x Inverted F antenna	
S7110		2 x Monopole Antenna	
Following NEW Model to be added			
E8410/E8490	Atheros XB62	2 x Inverted F antenna	Tested model in this application

Fujitsu Notebook Model	WLAN antenna type	WLAN antenna Peak gain [dBi]			
		2.4GHz band	5GHz low band	5GHz Mid band	5GHz High band
E8210	Inverted F	2.47	-0.44	0.38	0.38
S7110	Monopole	2.08	1.66	0.59	1.79
Q2010	Inverted F	2.32	3.23	3.36	1.48
E8410/E8490	Inverted F	1.65	3.96	3.24	3.36

The WLAN Module was tested in Fujitsu host notebook E8410/E8490 as this notebook has the highest antenna gain (5 GHz low band, 5 GHz mid band and 5 GHz high band).

Refer to Appendix_A_E8410/E8490 for details.

To qualify for a class 2 permissive change, the output power was re-measured on host E8410/E8490. The highest output powers are report below.

The highest output powers were granted:

Frequency MHz	Output Power Granted dBm
5800	17.4
2400	18.0

The highest new output powers are measured:

Frequency MHz	New Output Power Measured dBm
5800	17.6
2400	17.8



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.4 Host PC Details

Host notebook :	LifeBook E series
Model Name:	E8410(80W) / E8490(100W)
Serial Number:	Pre-production Sample
Manufacturer:	FUJITSU LIMITED
CPU Type and Speed:	Core2 Duo T7700 2.40GHz
LCD	15" WUXGA / 15" WSXGA+ / 15" WXGA
Wired LAN:	Intel 82566MM : 10 Base-T/100 Base-TX/1000Base-T
Modem:	Agere MDC1.5 modem Model: D40
Port Replicator Model:	FPCPR63
AC Adapter Model:	80W: SEC100P2-19.0(Sanken), ADP-80NB A(Delta), SEC100P3-19.0(Sanken, 3pin) 100W: SED110P2-19.0(Sanken)
Voltage:	19 V
Current Specs:	4.22A / 5.27
Watts:	80W / 100W
RADIO MODULES	
Module # 1:	WLAN (XB62 IEEE802.11a+b/g)
WLAN Model Number:	AR5BXB6
WLAN Manufacturer:	Atheros
Interface Type:	Mini-Card Wireless LAN Module
Antenna Types:	Nissei Electric Inverted F Antenna Model: CP313551(T1:Left), CP313552(T2:Right) Location: Top edge of LCD screen
Antenna gain:	Refer antenna data provided separately (Appendix A)
Module # 2:	Bluetooth Module
Model Number:	EYTF3CS FT
Manufacturer:	TAIYO YUDEN
Interface Type:	USB
Antenna Types:	Taiyo Yuden Monopole Antenna, Model: CP331590 Location: Right hinge of LCD screen
Max. Output Power:	4 dBm



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

2.5 Test Procedure

Emissions measurements were performed in accordance with the procedures of ANSI C63.4-2003. Radiated emissions tests were performed at a distance of 1 and 3 metres from the EUT. OET Bulletin 65 dated June 2001 was used for reference.

2.6 Test Facility

2.6.1 General

Radiated Emission measurements were performed at EMC Technologies open area test site (OATS) situated at Lerderderg Gorge, near the township of Bacchus Marsh in Victoria, Australia. Conducted measurements at an antenna ports were performed at EMC Technologies' laboratory in Tullamarine, Victoria Australia.

The above test sites have been accepted for testing by the Federal Communications Commission (FCC) - **FCC Registration Number 90560**.

EMC Technologies open area test site (OATS) has also been accepted by Industry Canada for the performance of radiated measurements in accordance with RSS 212, Issue 1 (Provisional). **Industry Canada File Number IC 4161.**

2.6.2 NATA Accreditation

EMC Technologies is accredited in Australia to test to the following standards by the National Association of Testing Authorities (NATA).

"FCC Part 15 unintentional and intentional emitters in the frequency range 9kHz to 18 GHz excluding TV receivers (15.117 and 15.119), TV interface devices (15.115), cable ready consumer electronic equipment (15.118), cable locating equipment (15.213) and unlicensed national information infrastructure devices (Sub part E)."

The current full scope of accreditation can be found on the NATA website: www.nata.asn.au. It also includes a large number of emission, immunity, SAR, EMR and Safety standards.

NATA is the Australian national laboratory accreditation body and has accredited EMC Technologies to operate to the IEC/ISO17025 requirements. A major requirement for accreditation is the assessment of the company and its personnel as being technically competent in testing to the standards. This requires fully documented test procedures, continued calibration of all equipment to the National Standard at the National Measurements Laboratory (NML) and an internal quality system to ISO 9002. NATA has mutual recognition agreements with the National Voluntary Laboratory Accreditation Program (NVLAP) and the American Association for Laboratory Accreditation (A²LA).

2.7 Test Equipment Calibration

All measurement instrumentation and transducers were calibrated in accordance with the applicable standards by an independent NATA registered laboratory such as Agilent Technologies (Australia) Pty Ltd or the National Measurement Laboratory (NML). All equipment calibration is traceable to Australia national standards at the National Measurements Laboratory. The reference antenna calibration was performed by NML and the working antennas (biconical and log-periodic) calibrated by the NATA approved procedures.

2.8 Ambients at OATS

The Open Area Test Site (OATS) is an area of low background ambient signals. No significant broadband ambients are present however commercial radio and TV signals exceed the limit in the FM radio, VHF and UHF television bands. Radiated prescan measurements were performed in the shielded enclosure to check for possible radiated emissions at the frequencies where the OATS ambient signals exceeded the test limit.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

FCC 15.247 (DTS) RESULTS

3.0 SPURIOUS EMISSION MEASUREMENTS

3.1 Test Procedure

Testing was performed in accordance with the requirements of FCC Part 15.247(d).

Radiated emission measurements were performed to the limits as per section 15.209. The measurements were made at the open area test site.

The EUT was set up on the table top (placed on turntable) of total height 80 cm above the ground plane, and operated as described in section 2 of this report. The EMI Receiver was operated under software control via the PC Controller through the IEEE.488 Interface Bus Card Adaptor. The test frequency range was sub-divided into smaller bands with sufficient frequency resolution to permit reliable display and identification of possible EMI peaks while also permitting fast frequency scan times. Calibrated EMCO 3115, EMCO 3116 and ETS standard gain horn antennas were used for measurements between 1 to 40 GHz.

The measurement of emissions between 30 - 1000 MHz, refer to EMC test report M060223_Cert_AR5BXB6_DTS with FCC ID: EJE-WL0011 (IC ID: 337J-WL0011).

The measurement of emissions above 1000 MHz was measured using a following setting:

Peak measurements setting: RBW = VBW = 1 MHz

Average measurements setting: RBW = 1 MHz and VBW = 10 Hz

The receiver bandwidth was set to 6 dB.

The EUT was slowly rotated with the Peak Detector set to Max-Hold. This was performed for two antenna heights. When an emission was located, it was positively identified and its maximum level found by rotating the automated turntable, and by varying the antenna height. Each significant peak was investigated with the Quasi-Peak/Average Detectors. The software for cable losses automatically corrected the measurement data for each frequency range, antenna factors and preamplifier gain and all data was then stored on disk in sequential data files. This process was performed for both horizontal and vertical antenna polarisations.

3.2 Calculation of field strength

The field strength was calculated automatically by the software using all the pre-stored calibration data. The method of calculation is shown below:

$E = V + AF - G + L$ Where:

E = Radiated Field Strength in $\text{dB}\mu\text{V}/\text{m}$.

V = EMI Receiver Voltage in $\text{dB}\mu\text{V}$. (measured value)

AF = Antenna Factor in $\text{dB}(\text{m}^{-1})$. (stored as a data array)

G = Preamplifier Gain in dB. (stored as a data array)

L = Cable loss in dB. (stored as a data array of Insertion Loss versus frequency)

- Example Field Strength Calculation**

Assuming a receiver reading of 34.0 $\text{dB}\mu\text{V}$ is obtained at 90 MHz, the Antenna Factor at that frequency is 9.2 dB. The cable loss is 1.9 dB while the preamplifier gain is 20 dB. The resulting Field Strength is therefore as follows:

$$34.0 + 9.2 + 1.9 - 20 = 25.1 \text{ dB}\mu\text{V}/\text{m}$$

Measurement uncertainty with a confidence interval of 95% is:

- Free radiation tests $(1000 \text{ MHz} - 18,000 \text{ MHz}) \pm 4.1 \text{ dB}$



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

3.3 Radiated Emissions (IM Spurious)

All measurements above 1 GHz were initially made over a distance of 3 metres. This was decreased to 1.0 metre as the emission levels from the device were very low.

The 74 dB_μV/m @ 3m and 54 dB_μV/m @ 3m limits are applied for emissions fall in the restricted bands.

Measurements were performed on Fujitsu host notebook E8410/E8490 (5 GHz high band) and the test results are reported.

Testing was performed while both the WLAN transmitter and Bluetooth transmitter continuously operated. Emissions related to the WLAN transmitter (5.725 – 5.850 GHz) is reported below. Emissions in the frequency band (5.15 – 5.35 GHz), refer to M070317_Cert_AR5BXB6_NII_C2PC. Emissions in the frequency band (2.4 – 2.4835 GHz, 802.11b/g) refer to EMC test report M060223_Cert_AR5BXB6_DTS with FCC ID: EJE-WL0011 (IC ID: 337J-WL0011)

Configuration 802.11a (5.725 – 5.850 MHz)

Initial investigations were performed with all data rates: (6 Mbps to 54 Mbps). No significant differences in emissions were observed. Final testing was performed while the transmitter continuously operated with the modulation rate of 6 Mbps (BPSK).

Channel 149 - 5745 MHz

Frequency MHz	Peak Detector dB _μ V	Average Detector dB _μ V	Peak Limit dB _μ V/m	Average Limit dB _μ V/m	Result
5745	103.8	93.1	-	-	-
11490	69.2	53.0	74.0	54.0	Pass
17235	55.9	42.6	-	-	-

Channel 157 - 5785 MHz

Frequency MHz	Peak Detector dB _μ V	Average Detector dB _μ V	Peak Limit dB _μ V/m	Average Limit dB _μ V/m	Result
5785	103.5	92.8	-	-	-
11570	69.6	53.3	74.0	54.0	Pass
17355	55.3	42.1	-	-	-

Channel 165 - 5825 MHz

Frequency MHz	Peak Detector dB _μ V	Average Detector dB _μ V	Peak Limit dB _μ V/m	Average Limit dB _μ V/m	Result
5825	104.2	93.6	-	-	-
11650	70.9	53.8	74.0	54.0	Pass
17475	55.8	42.5	-	-	-

Channel 152 TURBO - 5760 MHz

Frequency MHz	Peak Detector dB _μ V	Average Detector dB _μ V	Peak Limit dB _μ V/m	Average Limit dB _μ V/m	Result
5760	100.9	91.1	-	-	-
11520	67.1	52.4	74.0	54.0	Pass
17280	54.8	41.0	-	-	-



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

Channel 160 TURBO - 5800 MHz

Frequency MHz	Peak Detector dBuV	Average Detector dBuV	Peak Limit dBuV/m	Average Limit dBuV/m	Result
5800	100.4	90.7	-	-	-
11600	68.1	52.6	74.0	54.0	Pass
17400	54.5	41.3	-	-	-

Result: Harmonics were recorded up to 40 GHz. Other harmonics were confirmed low with both RBW and VBW reduced. The worst case emissions were complied with the FCC limits in sections 15.209 and 15.247 by a margin of 0.2 dB. The measurement uncertainty for radiated emissions in this band was ± 4.1 dB.

3.3.2 Both WLAN and Bluetooth Transmitters Transmitting

Result: IM spurious emissions were recorded within the restricted bands of up to 40 GHz. Emissions complied with the FCC limits of section 15.209 and 15.247.

3.3.3 Band Edge Measurements

Refer to EMC test reports: M060223_Cert_AR5BXB6_DTS FCC ID: EJE-WL0011 (IC ID: 337J-WL0011)



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

4.0 RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.247(i)

Spread spectrum transmitters operating in the 2400 - 2483.5 MHz and 5725 – 5850 MHz bands are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

Transmitter # 1: The WLAN antennas are located on the top edge of LCD screen (2 antennas left and right) and projected distance of greater than 20cm from user.

Transmitter # 2: The Bluetooth antenna is located right hinge of LCD screen and projected distance of less than 20cm from user.

SAR is not required as the WLAN transmitter is mobile device and the power for the Bluetooth transmitter is below the low threshold.

The separation distance between the WLAN and BT antennas is greater than 20cm. Therefore, they are not co-located transmitters.

The MPE calculation shown below is for the WLAN power density.

In accordance with Section 1.1310, the Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure of 1.0 has been applied, i.e 1mW/cm².

Friis transmission formula: $P_d = (P \cdot G) / (4 \cdot \pi \cdot r^2)$

where: P_d = power density (mW/cm²)

P = power input to the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of the antenna (cm)

Prediction frequency = 5745 MHz

Maximum peak output power = 17.4 dBm = 55.0 mW

Antenna (Inverted F) gain (max) = 3.36 dBi = 2.17 numeric

The power density calculated = 0.03 mW/cm²

Prediction frequency = 2462 MHz

Maximum peak output power = 18.0 dBm = 63.1 mW

Antenna (Inverted F) gain (max) = 2.47 dBi = 1.77 numeric

The power density calculated = 0.03 mW/cm²

MPE limit for uncontrolled exposure at prediction frequency = 1 mW/cm²

Results: Calculations show that the Radio devices with described antennas complied with Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure.



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

5.0 COMPLIANCE STATEMENT

The Atheros Mini-PCI Wireless LAN Module (XB62 11a+b/g), Model: AR5BXB6 installed in Fujitsu notebook PCs tested on behalf of Fujitsu Australia Ltd, **comply** with the **Class II Permissive Change** requirements of 47 CFR, Part 15 Subpart C - Rules for Radio Frequency Devices (intentional radiators), Section 15.247 - Operation in the frequency band 2400 - 2483.5 MHz and 5725 – 5850 MHz.

The test sample also complies with the Industry Canada RSS-210 issue 6 (Low Power Licence-Exempt Radiocommunication Devices (All Frequency Bands)) clause 6.2.2(o) 2400 – 2483.5 MHz and 5725 - 5850 MHz Spread Spectrum requirements and the RF exposure requirements of RSS-102.

Results were as follows:

FCC Subpart C, Section 15.247

FCC Part 15 Subpart C Clauses	Industry Canada RSS-210 Clauses	Test Performed	Results
15.203	5.5	Antenna Requirement	Note 1
15.205	6.3	Operation in Restricted Band	Complies
15.207	6.6	Conducted Emissions	Note 1
15.209	6.3	Radiated Emissions	Complies
15.247 (a)(2)	6.2.2(o)(iv)	Channel Bandwidth	Note 1
15.247 (b)(3)	6.2.2(o)(b)	Peak Output Power	Note 1
15.247 (c)		Antenna Gain > 6 dBi	Not Applicable. Antenna gain < 6 dBi
15.247 (d)	6.2.2(o)(e1)	Out of Band Emissions	Complies
15.247 (e)	6.2.2(o)(iv)	Peak Power Spectral Density	Note 1
15.247 (f)		*Hybrid Systems	Not Applicable. EUT does not employ a hybrid system
15.247 (g)		Frequency Hopping	Not Applicable. EUT is not a frequency hopping
15.247 (h)		Frequency Hopping	Not Applicable. EUT is not a frequency hopping
15.247 (i)		Radio Frequency Hazard	Complies

*Hybrid systems are those that employ a combination of both frequency hopping and digital modulations technique.

Note 1: Refer to EMC test report M060223_Cert_AR5BXB6_DTS with FCC ID: EJE-WL0011 (IC ID: 337J-WL0011)

FCC Subpart E, Section 15.407 - WLAN

Refer to EMC Technologies Report M070317_Cert_AR5BXB6_NII_C2PC



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.

TEST REPORT APPENDICES

APPENDIX A: ANTENNA INFORMATION

APPENDIX B: WLAN and ANTENNA LOCATIONS PHOTOS

Attachment 1: RF Exposure Information



This Laboratory is accredited by the National Association of Testing Authorities, Australia. The tests reported herein have been performed in accordance with its terms of accreditation for FCC Part 15. This document shall not be reproduced, except in full.