

Attachment 1
RF EXPOSURE INFORMATION

RADIO FREQUENCY EXPOSURE (HAZARD) INFORMATION

Testing was performed in accordance with the requirements of FCC Part 15.407(f)

Spread spectrum transmitters operating in the 5.15 – 5.35 GHz and 5.47 – 5.725 GHz are required to be operated in a manner that ensures that the public is not exposed to RF energy levels in accordance with CFR 47, Section 1.1307(b)(1).

In accordance with Section 1.1310, the Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure of 1.0 has been applied, i.e 1mW/cm².

Friss transmission formula: $P_d = (P \cdot G) / (4 \cdot \pi \cdot r^2)$

where: P_d = power density (mW/cm²)

P = power input to the antenna (mW)

G = antenna gain (numeric)

r = distance to the center of radiation of the antenna (cm)

The MPE calculations shown below are for the WLAN module.

Transmitter Modules	FCC ID	Frequency GHz	Peak Power dBm	Antenna Type	Antenna Gain (dBi)	Power Density @ 20 cm mW/cm ²	MPE Limit mW/cm ²
WLAN (802.11abgn)	EJE-WL0014	2.4	29.6	Inverted-F	1.94	0.284	1.0
		5.0	29.85		1.96	0.302	1.0
Worst Case Power Densities						0.302	1.0

Calculations show that the radio modules with described antennas complied with Maximum Permissible Exposure (MPE) limit for the General Population/Uncontrolled Exposure.