

## RF Exposure Evaluation

E.U.T. : Transmitter (TX)

Model Number : CATXCOMP

Applicant : Nutek Corporation


Address : No. 167, Lane 235, Bauchiau Rd., Xindian District, New  
Taipei City 23145, Taiwan

Issued By : Interocean EMC Technology Corp.

LAB Location : No. 5-2, Lin 1, Tin-Fu, Lin-Kou Dist., New Taipei City,  
Taiwan 244, R.O.C.


Report Issued : 2012/04/23

Project Engineer :



Elli Chang

Approved :



Jerry Liu

### Portable Device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB 447498 (2)(a)(i)

Frequency Range (MHz)		Center Frequency (MHz)	60/f SAR Limitation (mW)
Low Freq.	High Freq.		
909.6	919.024	914.759	66

### Maximum measured transmitter power

Output power To antenna (mW)	Maximum Antenna gain (numeric)	EIRP (mW)
34.0408	1	34.0408

Threshold at which no SAR required is 66 mW.

Maximum Tx power is 34.0408 mW EIRP.

**Conclusion:** No SAR is required.

### SIMULTANEOUS TRANSMISSION EVALUATION

N/A