

**ELECTROMAGNETIC EMISSIONS COMPLIANCE REPORT
INTENTIONAL RADIATOR CERTIFICATION TO
FCC PART 15 SUBPART C REQUIREMENT**

OF

Rechargeable Mini Bluetooth Speaker

Model No.: B27, CA-B27, DE-B27, MV-B27, Vi-B27PN

Trademark: iHome, Marvel, Descendants

FCC ID: EMOB27

Report No.: KAD150505007E2

Issue Date: June 24, 2015

Prepared for

**SDI Technologies Inc
1299, Main Street, Rahway, NJ 07065, U.S.A.**

Prepared by

DONGGUAN EMTEK CO., LTD.

**No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China
TEL: 86-769-22807078
FAX: 86-769-22807079**

**This report shall not be reproduced, except in full, without the written approval of
DONGGUAN EMTEK CO., LTD.**

VERIFICATION OF COMPLIANCE

| | |
|----------------------|---|
| Applicant: | SDI Technologies Inc 1299, Main Street, Rahway, NJ 07065, U.S.A. |
| Manufacturer: | SDI Technologies Inc 1299, Main Street, Rahway, NJ 07065, U.S.A. |
| Product Description: | Rechargeable Mini Bluetooth Speaker |
| Trade Mark: | iHome, Marvel Descendants |
| Model Number: | B27, CA-B27, DE-B27, MV-B27, Vi-B27PN (Note: The samples are the same except model number. So B27 was selected for full test.) |

We hereby certify that:

The above equipment was tested by DONGGUAN EMTEK CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10-2013 and the energy emitted by the sample EUT tested as described in this report is in compliance with conducted and radiated emission limits of FCC Rules Part 15.247(2014).

Date of Test : May 05, 2015 to June 13, 2015

Prepared by : 
Ivy Huang/Editor

Reviewer : 
Hong Yang/Supervisor

Approved & Authorized Signer : 
Sam Lv/Manager

Modified Information

| Version | Summary | Revision Date | Report No. |
|---------|-----------------|---------------|----------------|
| Ver.1.0 | Original Report | / | KAD150505007E2 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

Table of Contents

| | |
|--|-----------|
| 1. GENERAL INFORMATION | 6 |
| 1.1 PRODUCT DESCRIPTION | 6 |
| 2. TEST FACILITY | 7 |
| 3. DESCRIPTION OF TEST MODES | 8 |
| 4. TEST SYSTEM UNCERTAINTY..... | 9 |
| 5. CONDUCTED EMISSIONS TEST | 10 |
| 5.1 MEASUREMENT PROCEDURE:..... | 10 |
| 5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 10 |
| 5.3 MEASUREMENT EQUIPMENT USED: | 10 |
| 5.4 CONDUCTED EMISSION LIMIT | 10 |
| 5.5 MEASUREMENT RESULT:..... | 11 |
| 5.6 CONDUCTED MEASUREMENT PHOTOS: | 14 |
| 6. RADIATED EMISSION TEST..... | 15 |
| 5.1 MEASUREMENT PROCEDURE | 15 |
| 5.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 17 |
| 5.3 MEASUREMENT EQUIPMENT USED: | 18 |
| 5.4 RADIATED EMISSION LIMIT | 19 |
| 5.5 MEASUREMENT RESULT | 20 |
| 5.6 RADIATED MEASUREMENT PHOTOS: | 26 |
| 7. 6DB BANDWIDTH MEASUREMENT | 27 |
| 6.1 MEASUREMENT PROCEDURE | 27 |
| 6.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 27 |
| 6.3 MEASUREMENT EQUIPMENT USED: | 27 |
| 6.4 LIMIT..... | 27 |
| 6.5 MEASUREMENT RESULTS:..... | 27 |
| 7. MAXIMUM PEAK OUTPUT POWER TEST | 30 |
| 7.1 MEASUREMENT PROCEDURE | 30 |
| 7.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION) | 30 |
| 7.3 MEASUREMENT EQUIPMENT USED: | 30 |
| 7.4 PEAK POWER OUTPUT LIMIT | 30 |
| 7.5 MEASUREMENT RESULTS:..... | 30 |
| 8. POWER SPECTRAL DENSITY MEASUREMENT..... | 33 |
| 8.1 MEASUREMENT PROCEDURE | 33 |
| 8.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)..... | 33 |
| 8.3 MEASUREMENT EQUIPMENT USED: | 33 |
| 8.4 MEASUREMENT PROCEDURE | 33 |

8.5 MEASUREMENT RESULTS:.....34

9. BAND EDGE TEST.....38

9.1 MEASUREMENT PROCEDURE 38

9.2 TEST SET-UP (BLOCK DIAGRAM OF CONFIGURATION)38

9.3 MEASUREMENT EQUIPMENT USED:39

9.4 MEASUREMENT RESULTS:.....40

10 ANTENNA APPLICATION41

10.1 ANTENNA REQUIREMENT41

10.2 RESULT41

1. GENERAL INFORMATION

1.1 Product Description

| Characteristics | Description |
|---------------------------|---|
| Product Name | Rechargeable Mini Bluetooth Speaker |
| Model number | B27 |
| Power Supply | DC 5V, 1A or DC 3.7V, 630mA Lithium Battery |
| Kind of Device | Bluetooth Ver.4.0 BLE |
| Modulation | GFSK |
| Operating Frequency Range | 2402-2480MHz |
| Number of Channels | 40 |
| Transmit Power Max | 4.30dBm(0.002692W) |
| Antenna Type | Internal PCB antenna |
| Antenna Gain | 0 dBi |
| Hardware Version | IBN27-0A(20150309) |
| Software Version | ibt27_2015_05_08fcc.psr |

1.2 Test Methodology

All the test program has follow FCC new test procedure KDB 558074 D01 DTS Meas Guidance v03r03, Both conducted and radiated testing was performed according to the procedures in ANSI C63.10-2013. Radiated testing was performed at an antenna to EUT distance 3 meters.

1.3 Support Equipment

Adapter : Model : YSV6-0501000 US
Input: AC 100-240V, 50/60Hz
Output: DC 5V, 1000mA

2. Test Facility

Site Description

EMC Lab. : Registered on FCC, June 18, 2014
The Certificate Number is 247565

Registered on Industry Canada, February 19, 2014
The Certificate Number is 9444A.

Name of Firm : DONGGUAN EMTEK CO., LTD

Site Location : No.281, Guantai Road, Nancheng District,
Dongguan, Guangdong, China

3. Description of test modes

The EUT has been tested under its typical operating condition. Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting. Only the worst case data were reported.

The EUT has been associated with peripherals pursuant to ANSI C63.10-2013 and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation (9 KHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

For Radiated: The EUT's antenna was pre-tested under the following modes:

| Test Mode | Description |
|---------------|-----------------|
| Mode A | X-Y axis |
| Mode B | Y-Z axis |
| Mode C | X-Z axis |

From the above modes, the worst case was found in Mode A. Therefore only the test data of the mode was recorded in this report.

The details of test channels and bandwidth were for RF conductive measurement.

Channel List:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|-----------|-----------------|-----------|-----------------|-----------|-----------------|
| 00 | 2402 | 14 | 2430 | 28 | 2458 |
| 01 | 2404 | 15 | 2432 | 29 | 2460 |
| 02 | 2406 | 16 | 2434 | 30 | 2462 |
| 03 | 2408 | 17 | 2436 | 31 | 2464 |
| 04 | 2410 | 18 | 2438 | 32 | 2466 |
| 05 | 2412 | 19 | 2440 | 33 | 2468 |
| 06 | 2414 | 20 | 2442 | 34 | 2470 |
| 07 | 2416 | 21 | 2444 | 35 | 2472 |
| 08 | 2418 | 22 | 2446 | 36 | 2474 |
| 09 | 2420 | 23 | 2448 | 37 | 2476 |
| 10 | 2422 | 24 | 2450 | 38 | 2478 |
| 11 | 2424 | 25 | 2452 | 39 | 2480 |
| 12 | 2426 | 26 | 2454 | | |
| 13 | 2428 | 27 | 2456 | | |

Note:

1. Test of channel was included the lowest 2402MHz, middle 2440MHz and highest frequency 2480MHz in highest data rate and to perform the test, then record on this report.

4. TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Parameter | Uncertainty |
|--------------------------------|-------------------------|
| Radio Frequency | $\pm 1 \times 10^{-5}$ |
| Maximum Peak Output Power Test | $\pm 1.0\text{dB}$ |
| Conducted Emissions Test | $\pm 2.0\text{dB}$ |
| Radiated Emission Test | $\pm 2.0\text{dB}$ |
| Power Density | $\pm 2.0\text{dB}$ |
| Occupied Bandwidth Test | $\pm 1.0\text{dB}$ |
| Band Edge Test | $\pm 3\text{dB}$ |
| All emission, radiated | $\pm 3\text{dB}$ |
| Antenna Port Emission | $\pm 3\text{dB}$ |
| Temperature | $\pm 0.5^\circ\text{C}$ |
| Humidity | $\pm 3\%$ |


Measurement Uncertainty for a level of Confidence of 95%

5. Conducted Emissions Test

5.1 Measurement Procedure:

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured was complete.

5.2 Test SET-UP (Block Diagram of Configuration)



5.3 Measurement Equipment Used:

| Conducted Emission Test Site | | | | | |
|------------------------------|-----------------|--------------|---------------|------------|------------|
| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | Last Cal. | Due date |
| Test Receiver | Rohde & Schwarz | ESCS30 | 100018 | 03/16/2015 | 03/15/2016 |
| L.I.S.N | Rohde & Schwarz | ENV216 | 100017 | 03/16/2015 | 03/15/2016 |
| RF Switching Unit | CDS | RSU-M2 | 38401 | 03/16/2015 | 03/15/2016 |
| Coaxial Cable | CDS | 79254 | 46107086 | 03/16/2015 | 03/15/2016 |

5.4 Conducted Emission Limit

(7) Conducted Emission Frequency(MHz)

0.15-0.5
0.5-5.0
5.0-30.0

Quasi-peak

66-56
56
60

Average

56-46
46
50

Note:

1. The lower limit shall apply at the transition frequencies
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

5.5 Measurement Result:

Pass.

The data of the worst mode (GFSK TX 2402MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following data.

4.6 Conducted Measurement Photos:



6. Radiated Emission Test

5.1 Measurement Procedure

1. The testing follows the guidelines in ANSI C63.10-2013.
2. Below 1000MHz, The EUT was placed on a turn table which is 0.8m above ground plane. And above 1000MHz, The EUT was placed on a styrofoam table which is 1.5m above ground plane.
3. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
4. The EUT was arranged to its worst case and then tune the Antenna tower (From 1m to 4m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
5. For measurement below 1GHz, if the emission level of the EUT measured by the peak detector is 3dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
6. Final measurement (Above 1GHz): The frequency range will be divided into different sub ranges depending of the frequency range of the used horn antenna. The EMI Receiver set to peak and average mode and a resolution bandwidth of 1MHz. The measurement will be performed in horizontal and vertical polarization of the measuring antenna and while rotating the EUT in its vertical axis in the range of 0 degree to 360 degree in order to have the antenna inside the cone of radiation.
7. Test Procedure of measurement (For Above 1GHz):
 - 1) Monitor the frequency range at horizontal polarization and move the antenna over all sides of the EUT(if necessary move the EUT to another orthogonal axis).
 - 2) Change the antenna polarization and repeat 1) with vertical polarization.
 - 3) Make a hardcopy of the spectrum.
 - 4) Measure the frequency of the detected emissions with a lower span and resolution bandwidth to increase the accuracy and note the frequency value.
 - 5) Change the analyser mode to Clear/ Write and found the cone of emission.
 - 6) Rotate and move the EUT, so that the measuring distance can be enlarged to 3m and the antenna will be still inside the cone of emission.
 - 7) Measure the level of the detected frequency with the correct resolution bandwidth, with the antenna polarization and azimuth and the peak and average detector, which causes the maximum emission.
 - 8) Repeat steps 1) to 7) for the next antenna spot if the EUT is larger than the antenna beamwidth.

Use the following spectrum analyzer settings:

When spectrum scanned from 30MHz to 1GHz setting resolution bandwidth 120KHz and video bandwidth 300KHz:

| | |
|-------------------|----------|
| EMI Test Receiver | Setting |
| Attenuation | Auto |
| RB | 120KHz |
| VB | 300KHz |
| Detector | QP |
| Trace | Max hold |

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 3MHz:

| | |
|-------------------|----------|
| EMI Test Receiver | Setting |
| Attenuation | Auto |
| RB | 1MHz |
| VB | 3MHz |
| Detector | Peak |
| Trace | Max hold |

When spectrum scanned above 1GHz setting resolution bandwidth 1MHz, video bandwidth 10Hz:

| | |
|-------------------|----------|
| EMI Test Receiver | Setting |
| Attenuation | Auto |
| RB | 1MHz |
| VB | 10Hz |
| Detector | Peak |
| Trace | Max hold |

For Average Measurement:


VBW=10Hz, when duty cycle is no less than 98 percent.

$VBW \geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.


| Band | Duty Cycle(%) | T(μ s) | 1/T(KHz) | Average Correction Factor | VBW Setting |
|-----------|---------------|-------------|----------|---------------------------|-------------|
| 2402-2480 | 100 | - | - | 0 | 10Hz |

5.2 Test SET-UP (Block Diagram of Configuration)


(A) Radiated Emission Test Set-Up, Frequency Below 30MHz



(B) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(C) Radiated Emission Test Set-Up, Frequency above 1000MHz



5.3 Measurement Equipment Used:

| Item | Equipment | Manufacturer | Model No. | Serial No. | Characteristics | Last Cal. | Cal. Interval |
|------|--------------------------------|-----------------|------------|--------------|-----------------|------------|---------------|
| 1. | Test Receiver | Rohde & Schwarz | ESCI | 1166.5950.03 | 9KHz-3GHz | 3/15/2015 | 1 Year |
| 2. | Loop Antenna | Schwarzbeck | FMZB 1519 | 012 | 9 KHz -30MHz | 12/29/2014 | 1 Year |
| 3. | Bilog Antenna | Schwarzbeck | VULB9163 | 000141 | 25MHz-2GHz | 3/15/2015 | 1 Year |
| 4. | Power Amplifier | CDS | RSU-M352 | 818 | 1MHz-1GHz | 3/15/2015 | 1 Year |
| 5. | Power Amplifier | HP | 8447F | OPT H64 | 1GHz-26.5GHz | 3/15/2015 | 1 Year |
| 6. | Color Monitor | SUNSP0 | SP-140A | N/A | -- | 3/15/2015 | 1 Year |
| 7. | Single Line Filter | JIANLI | XL-3 | N/A | -- | 3/15/2015 | 1 Year |
| 8. | Single Phase Power Line Filter | JIANLI | DL-2X100B | N/A | -- | 3/15/2015 | 1 Year |
| 9. | 3 Phase Power Line Filter | JIANLI | DL-4X100B | N/A | -- | 3/15/2015 | 1 Year |
| 10. | DC Power Filter | JIANLI | DL-2X50B | N/A | -- | 3/15/2015 | 1 Year |
| 11. | Cable | Schwarzbeck | PLF-100 | 549489 | 9KHz-3GHz | 3/15/2015 | 1 Year |
| 12. | Cable | Rosenberger | CIL02 | A0783566 | 9KHz-3GHz | 3/15/2015 | 1 Year |
| 13. | Cable | Rosenberger | RG 233/U | 525178 | 9KHz-3GHz | 3/15/2015 | 1 Year |
| 14. | Signal Analyzer | Rohde & Schwarz | FSV30 | 103040 | 9KHz-40GHz | 12/29/2014 | 1 Year |
| 15. | Horn Antenna | Schwarzbeck | BBHA9120D | 9120D-1272 | 1GHz-18GHz | 12/29/2014 | 1 Year |
| 16. | Horn Antenna | Schwarzbeck | BBHA 9170 | BBHA9170399 | 14GHz -26.5GHz | 12/29/2014 | 1 Year |
| 17. | Power Amplifier | LUNAR EM | LNA1G18-40 | J10100000081 | 1GHz-26.5GHz | 12/29/2014 | 1 Year |
| 18. | Cable | H+S | CBL-26 | N/A | 1GHz-26.5GHz | 12/29/2014 | 1 Year |
| 19. | Cable | H+S | CBL-26 | N/A | 1GHz-26.5GHz | 12/29/2014 | 1 Year |
| 20. | Cable | H+S | CBL-26 | N/A | 1GHz-26.5GHz | 12/29/2014 | 1 Year |

5.4 Radiated emission limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table 15.209(a):

| Frequencies (MHz) | Field Strength (micровolts/meter) | Measurement Distance (meters) |
|----------------------|--------------------------------------|----------------------------------|
| 0.009~0.490 | 2400/F(KHz) | 300 |
| 0.490~1.705 | 24000/F(KHz) | 30 |
| 1.705~30.0 | 30 | 30 |
| 30~88 | 100 | 3 |
| 88~216 | 150 | 3 |
| 216~960 | 200 | 3 |
| Above 960 | 500 | 3 |

15.205 Restricted bands of operation

| MHz | MHz | MHz | GHz |
|----------------------------|-----------------------|-----------------|------------------|
| 0.090 - 0.110 | 16.42 - 16.423 | 399.9 - 410 | 4.5 - 5.15 |
| ¹ 0.495 - 0.505 | 16.69475 - 16.69525 | 608 - 614 | 5.35 - 5.46 |
| 2.1735 - 2.1905 | 16.80425 - 16.80475 | 960 - 1240 | 7.25 - 7.75 |
| 4.125 - 4.128 | 25.5 - 25.67 | 1300 - 1427 | 8.025 - 8.5 |
| 4.17725 - 4.17775 | 37.5 - 38.25 | 1435 - 1626.5 | 9.0 - 9.2 |
| 4.20725 - 4.20775 | 73 - 74.6 | 1645.5 - 1646.5 | 9.3 - 9.5 |
| 6.215 - 6.218 | 74.8 - 75.2 | 1660 - 1710 | 10.6 - 12.7 |
| 6.26775 - 6.26825 | 108 - 121.94 | 1718.8 - 1722.2 | 13.25 - 13.4 |
| 6.31175 - 6.31225 | 123 - 138 | 2200 - 2300 | 14.47 - 14.5 |
| 8.291 - 8.294 | 149.9 - 150.05 | 2310 - 2390 | 15.35 - 16.2 |
| 8.362 - 8.366 | 156.52475 - 156.52525 | 2483.5 - 2500 | 17.7 - 21.4 |
| 8.37625 - 8.38675 | 156.7 - 156.9 | 2690 - 2900 | 22.01 - 23.12 |
| 8.41425 - 8.41475 | 162.0125 - 167.17 | 3260 - 3267 | 23.6 - 24.0 |
| 12.29 - 12.293 | 167.72 - 173.2 | 3332 - 3339 | 31.2 - 31.8 |
| 12.51975 - 12.52025 | 240 - 285 | 3345.8 - 3358 | 36.43 - 36.5 |
| 12.57675 - 12.57725 | 322 - 335.4 | 3600 - 4400 | (²) |

Remark 1. Emission level in dBuV/m=20 log (uV/m)

- : 2. Measurement was performed at an antenna to the closed point of EUT distance of meters.
- 3. Only spurious frequency is permitted to locate within the Restricted Bands specified in provision of § 15.205, and the emissions located in restricted bands also comply with 15.209 limit.

5.5 Measurement Result

Below 30MHz:

| | | | |
|--------------------|------------|---------------|--------------|
| Operation Mode: | TX | Test Date : | May 20, 2015 |
| Frequency Range: | 9KHz~30MHz | Temperature : | 28°C |
| Test Result: | PASS | Humidity : | 65 % |
| Measured Distance: | 3m | Test By: | Andy |

| Freq. (MHz) | Ant.Pol. H/V | Emission Level (dBuV/m) | Limit 3m (dBuV/m) | Over (dB) |
|----------------|-----------------|-------------------------------|----------------------|--------------|
| -- | -- | -- | -- | -- |


Note: The low frequency, which started from 9KHz-30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

Below 1000MHz:

Pass.

The data of the worst mode (TX 2402MHz) are recorded in the following pages and the others modulation methods do not exceed the limits.

Please refer to the following data.



Site Chamber #1 Polarization: **Horizontal** Temperature: 24
 Limit: (RE)FCC PART 15 class B 3m Power: AC 120V/60Hz Humidity: 55 %
 Mode: TX 2402
 Note:

| No. | Mk. | Freq. | Reading Level | Correct Factor | Measurement | Limit | Over | Antenna Height | Table Degree | |
|-----|-----|----------|---------------|----------------|-------------|--------|--------|----------------|--------------|---------|
| | | MHz | dBuV | dB | dBuV/m | dBuV/m | dB | cm | degree | Comment |
| 1 | * | 31.9400 | 38.22 | -14.63 | 23.59 | 40.00 | -16.41 | QP | | |
| 2 | | 41.6400 | 33.38 | -13.58 | 19.80 | 40.00 | -20.20 | QP | | |
| 3 | | 54.2500 | 36.19 | -17.08 | 19.11 | 40.00 | -20.89 | QP | | |
| 4 | | 109.5400 | 37.51 | -17.62 | 19.89 | 43.50 | -23.61 | QP | | |
| 5 | | 168.7100 | 41.28 | -18.42 | 22.86 | 43.50 | -20.64 | QP | | |
| 6 | | 190.0500 | 40.73 | -18.32 | 22.41 | 43.50 | -21.09 | QP | | |

*:Maximum data x:Over limit !:over margin

Operator: Snake

Above 1000MHz~10th Harmonics:

Operation Mode: TX Mode (CH00: 2402MHz) Test Date : May 20, 2015
 Frequency Range: 1-25GHz Temperature : 25 °C
 Test Result: PASS Humidity : 50 %
 Measured Distance: 3m Test By: Andy

| Freq. (MHz) | Ant. Pol. H/V | Emission Level(dBuV/m) | | Limit 3m(dBuV/m) | | Margin(dB) | |
|----------------|------------------|------------------------|-------|------------------|----|------------|--------|
| | | PK | AV | PK | AV | PK | AV |
| 4804 | V | 63.01 | 45.15 | 74 | 54 | -10.99 | -8.85 |
| 7206 | V | 62.41 | 44.32 | 74 | 54 | -11.59 | -9.68 |
| 9608 | V | 61.52 | 43.05 | 74 | 54 | -12.48 | -10.95 |
| 12010 | V | 60 | 42.15 | 74 | 54 | -14 | -11.85 |
| 14412 | V | 58.79 | 41.05 | 74 | 54 | -15.21 | -12.95 |
| 16814 | V | 57.42 | 40.71 | 74 | 54 | -16.58 | -13.29 |
| 4804 | H | 64.35 | 44.33 | 74 | 54 | -9.65 | -9.67 |
| 7206 | H | 63.62 | 43.15 | 74 | 54 | -10.38 | -10.85 |
| 9608 | H | 62.15 | 42.15 | 74 | 54 | -11.85 | -11.85 |
| 12010 | H | 61.48 | 41.05 | 74 | 54 | -12.52 | -12.95 |
| 14412 | H | 60.25 | 40.36 | 74 | 54 | -13.75 | -13.64 |
| 16814 | H | 59.33 | 39.78 | 74 | 54 | -14.67 | -14.22 |

Other harmonics emissions are lower than 20dB below the allowable limit.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) Measuring frequencies from 1GHz to 25GHz.

Operation Mode: TX Mode (CH19: 2440MHz) Test Date : May 20, 2015
 Frequency Range: 1-25GHz Temperature : 25 °C
 Test Result: PASS Humidity : 50 %
 Measured Distance: 3m Test By: Andy

| Freq. (MHz) | Ant. Pol. H/V | Emission Level(dBuV/m) | | Limit 3m(dBuV/m) | | Margin(dB) | |
|----------------|------------------|------------------------|-------|------------------|----|------------|--------|
| | | PK | AV | PK | AV | PK | AV |
| 4880 | V | 64.15 | 45 | 74 | 54 | -9.85 | -9 |
| 7320 | V | 63.95 | 44.15 | 74 | 54 | -10.05 | -9.85 |
| 9760 | V | 62.04 | 43.62 | 74 | 54 | -11.96 | -10.38 |
| 12200 | V | 61.33 | 42.05 | 74 | 54 | -12.67 | -11.95 |
| 14640 | V | 60.72 | 41.92 | 74 | 54 | -13.28 | -12.08 |
| 17080 | V | 59.48 | 40.74 | 74 | 54 | -14.52 | -13.26 |
| 4880 | H | 65.33 | 39.55 | 74 | 54 | -8.67 | -14.45 |
| 7320 | H | 64.05 | 45.15 | 74 | 54 | -9.95 | -8.85 |
| 9760 | H | 63.15 | 43.62 | 74 | 54 | -10.85 | -10.38 |
| 12200 | H | 62.28 | 42.05 | 74 | 54 | -11.72 | -11.95 |
| 14640 | H | 61.74 | 41.28 | 74 | 54 | -12.26 | -12.72 |
| 17080 | H | 60.38 | 40.75 | 74 | 54 | -13.62 | -13.25 |

Other harmonics emissions are lower than 20dB below the allowable limit.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) Measuring frequencies from 1GHz to 25GHz.


Operation Mode: TX Mode (CH39: 2480MHz) Test Date : May 20, 2015
 Frequency Range: 1-25GHz Temperature : 25 °C
 Test Result: PASS Humidity : 50 %
 Measured Distance: 3m Test By: Andy

| Freq. (MHz) | Ant. Pol. H/V | Emission Level(dBuV/m) | | Limit 3m(dBuV/m) | | Margin(dB) | |
|----------------|------------------|------------------------|-------|------------------|----|------------|--------|
| | | PK | AV | PK | AV | PK | AV |
| 4960 | V | 64.35 | 45.33 | 74 | 54 | -9.65 | -8.67 |
| 7440 | V | 63.25 | 44.05 | 74 | 54 | -10.75 | -9.95 |
| 9920 | V | 62.15 | 43.62 | 74 | 54 | -11.85 | -10.38 |
| 12400 | V | 61.04 | 42.15 | 74 | 54 | -12.96 | -11.85 |
| 14880 | V | 60.58 | 41.82 | 74 | 54 | -13.42 | -12.18 |
| 17360 | V | 60.72 | 40.35 | 74 | 54 | -13.28 | -13.65 |
| 4960 | H | 66.33 | 44.25 | 74 | 54 | -7.67 | -9.75 |
| 7440 | H | 65.02 | 43.62 | 74 | 54 | -8.98 | -10.38 |
| 9920 | H | 64.15 | 42.15 | 74 | 54 | -9.85 | -11.85 |
| 12400 | H | 63.5 | 41.92 | 74 | 54 | -10.5 | -12.08 |
| 14880 | H | 62.69 | 40.25 | 74 | 54 | -11.31 | -13.75 |
| 17360 | H | 61.74 | 39.55 | 74 | 54 | -12.26 | -14.45 |

Other harmonics emissions are lower than 20dB below the allowable limit.

- Note:**
- (1) All Readings are Peak Value and AV.
 - (2) Emission Level= Reading Level+ Probe Factor +Cable Loss.
 - (3) The average measurement was not performed when the peak measured data under the limit of average detection.
 - (4) Measuring frequencies from 1GHz to 25GHz.

5.6 Radiated Measurement Photos:




7. 6dB Bandwidth Measurement

6.1 Measurement Procedure

The EUT was operating in Bluetooth mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

6.2 Test SET-UP (Block Diagram of Configuration)



6.3 Measurement Equipment Used:

| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | Characteristics | LAST CAL. | CAL DUE. |
|-------------------|-----------------|--------------|---------------|-----------------|------------|------------|
| Spectrum Analyzer | Rohde & Schwarz | FSV30 | 1321.3008K | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |
| Coaxial Cable | CDS | 79254 | 46107086 | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |
| Antenna Connector | ARTHUR-YANG | 2244-N1TG1 | N/A | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

6.4 Limit

The minimum 6dB bandwidth shall be at least 500kHz.


6.5 Measurement Results:

Refer to attached data chart.


| | | | |
|--------------------|------|---------------|--------------|
| Spectrum Detector: | PK | Test Date : | May 20, 2015 |
| Test By: | Andy | Temperature : | 25 °C |
| Test Result: | PASS | Humidity : | 50 % |

| Channel number | Channel frequency (MHz) | Measurement level (KHz) | Required Limit (KHz) |
|----------------|-------------------------|-------------------------|----------------------|
| 00 | 2402 | 698 | >500 |
| 19 | 2440 | 699 | >500 |
| 39 | 2480 | 697 | >500 |


Channel 00:



Channel 19:



Channel 39:



7. MAXIMUM PEAK OUTPUT POWER TEST

7.1 Measurement Procedure

- The Transmitter output (antenna port) was connected to the spectrum Analyzer.
- Turn on the EUT and then record the peak power value.
- Repeat above procedures on all channels needed to be tested.

7.2 Test SET-UP (Block Diagram of Configuration)



7.3 Measurement Equipment Used:

| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | Characteristics | LAST CAL. | CAL DUE. |
|-------------------|-----------------|--------------|---------------|-----------------|------------|------------|
| Spectrum Analyzer | Rohde & Schwarz | FSV30 | 1321.3008K | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |
| Coaxial Cable | CDS | 79254 | 46107086 | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |
| Antenna Connector | ARTHUR-YANG | 2244-N1TG1 | N/A | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

7.4 Peak Power output limit

The maximum peak power shall be less 1Watt.


7.5 Measurement Results:

Refer to attached data chart.


| | | | |
|--------------------|------|---------------|--------------|
| Spectrum Detector: | PK | Test Date : | May 20, 2015 |
| Test By: | Andy | Temperature : | 25 °C |
| Test Result: | PASS | Humidity : | 50 % |

| Channel number | Channel Frequency (MHz) | Peak Power output(dBm) | Peak Power output(mW) | Peak Power Limit(W) | Pass/Fail |
|----------------|-------------------------|------------------------|-----------------------|---------------------|-----------|
| 0 | 2402 | 2.86 | 1.932 | 1W(30dBm) | PASS |
| 19 | 2440 | 3.94 | 2.477 | 1W(30dBm) | PASS |
| 39 | 2480 | 4.3 | 2.692 | 1W(30dBm) | PASS |


Channel 00:



Channel 19:



Channel 39:




8. Power Spectral Density Measurement

8.1 Measurement Procedure

The EUT was operating in Bluetooth mode or could be controlled its channel. Printed out the test result from the spectrum by hard copy function.

8.2 Test SET-UP (Block Diagram of Configuration)



8.3 Measurement Equipment Used:

| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | Characteristics | LAST CAL. | CAL DUE. |
|-------------------|-----------------|--------------|---------------|-----------------|------------|------------|
| Spectrum Analyzer | Rohde & Schwarz | FSV30 | 1321.3008K | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |
| Coaxial Cable | CDS | 79254 | 46107086 | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |
| Antenna Connector | ARTHUR-YANG | 2244-N1TG1 | N/A | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

8.4 Measurement Procedure

8.4.1 The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

8.4.2. Set to the maximum power setting and enable the EUT transmit continuously.

8.4.3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)

8.4.4. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.

8.4.5. Measure and record the results in the test report.

8.4.6. The Measured power density (dBm)/ 100KHz is a reference level and used as 20dBc down limit line for Conducted Band Edges and Conducted Spurious Emission.

8.5 Measurement Results:

The following table is the setting of spectrum analyzer.

| | |
|-------------------|--|
| Spectrum analyzer | Setting |
| Attenuation | Auto |
| Span Frequency | Set the span to 1.5 times the DTS bandwidth. |
| RB | 3KHz |
| VB | 10KHz |
| Detector | Peak |
| Trace | Max hold |
| Sweep Time | Automatic |

Refer to attached data chart.


| | | | |
|--------------------|------|---------------|--------------|
| Spectrum Detector: | PK | Test Date : | May 20, 2015 |
| Test By: | Andy | Temperature : | 25 °C |
| Test Result: | PASS | Humidity : | 50 % |

| Channel number | Channel frequency (MHz) | Measurement level (dBm) | | Required Limit (dBm/3kHz) | Pass/Fail |
|----------------|-------------------------|-------------------------|----------|---------------------------|-----------|
| | | PSD/100kHz | PSD/3kHz | | |
| 00 | 2402 | 2.50 | -12.28 | 8 | PASS |
| 19 | 2440 | 3.77 | -11.68 | 8 | PASS |
| 39 | 2480 | 4.17 | -11.23 | 8 | PASS |


Note:

1. Measured power density(dBm) has offset with cable loss.
2. The measured power density(dBm)/100KHz is reference level and used as 20dBc down for Conducted Band Edges and Conducted Spurious Emission limit line.


PSD 100kHz Plot:
Channel 00




Channel 19




Channel 39




PSD 3KHz Plot:
Channel 00



Channel 19



Channel 39



9. Band EDGE test

9.1 Measurement Procedure

For Conducted Test

1. The transmitter output is connected to a spectrum analyzer. The resolution bandwidth is set to 100KHz. The video bandwidth is set to 300KHz.
2. The spectrum from 30MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels.

For Radiated emission Test

The EUT was placed on a styrofoam table which is 1.5m above ground plane. The measurement procedure at the ban edges was simplified by performing the measurement in just one plot. Both, the in-band-emission and the unwanted emission were be encompassed by the span. After trace stabilization, the maximum peak was be determined by a peak detector and the value was marked by an appropriate limit line. The second limit line, which is 20dB below the first, marks the limit for the emissions in the unrestricted band. A maximum-peak-detector marks the highest emission in the unrestricted band next to the band edge.


The measurements were performed at the lower end of the 2.4GHz band.

9.2 Test SET-UP (Block Diagram of Configuration)

For Conducted Test



For Radiated emission Test



9.3 Measurement Equipment Used:

For Conducted Test

| EQUIPMENT TYPE | MFR | MODEL NUMBER | SERIAL NUMBER | Characteristics | LAST CAL. | CAL DUE. |
|-------------------|-----------------|--------------|---------------|-----------------|------------|------------|
| Spectrum Analyzer | Rohde & Schwarz | FSV30 | 1321.3008K | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |
| Coaxial Cable | CDS | 79254 | 46107086 | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |
| Antenna Connector | ARTHUR-YANG | 2244-N1TG1 | N/A | 10Hz-30GHz | 03/15/2015 | 03/14/2016 |

Remark: The temporary antenna connector is soldered on the PCB board in order to perform conducted tests and this temporary antenna connector is listed in the equipment list.

For Radiated emission Test

| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Cal. | Cal. Interval |
|------|-----------------|-----------------|------------|--------------|--------------|---------------|
| 1 | Signal Analyzer | Rohde & Schwarz | FSV30 | 103040 | 12/29/2014 | 1 Year |
| 2 | Horn Antenna | Schwarzbeck | BBHA9120D | 9120D-1272 | Dec 27, 2014 | 1 Year |
| 3 | Power Amplifier | LUNAR EM | LNA1G18-40 | J10100000081 | 12/29/2014 | 1 Year |
| 4 | Cable | H+S | CBL-26 | N/A | 12/29/2014 | 1 Year |
| 5 | Cable | H+S | CBL-26 | N/A | 12/29/2014 | 1 Year |
| 6 | Cable | H+S | CBL-26 | N/A | 12/29/2014 | 1 Year |

9.4 Measurement Results:

Refer to attached data chart.

| | | | |
|--------------------|------|---------------|--------------|
| Spectrum Detector: | PK | Test Date : | May 20, 2015 |
| Test By: | Andy | Temperature : | 25 °C |
| Test Result: | PASS | Humidity : | 50 % |

1. Conducted Test

| Frequency (MHz) | Peak Power Output(dBm) | Emission read Value(dBm) | Result of Band edge(dBc) | Band edge Limit(dBc) |
|-----------------|------------------------|--------------------------|--------------------------|----------------------|
| 2399.99 | 2.86 | -46.95 | 49.81 | >20dBc |
| 2483.99 | 4.3 | -59.24 | 63.54 | >20dBc |

2. Radiated emission Test

| Frequency (MHz) | Antenna polarization (H/V) | Emission (dBuV/m) | | Band edge Limit (dBuV/m) | | Margin (dB) | |
|-----------------|----------------------------|-------------------|-------|--------------------------|----|-------------|--------|
| | | PK | AV | PK | AV | PK | AV |
| 2399.05 | H | 64.15 | 45.01 | 74 | 54 | -9.85 | -8.99 |
| 2399.48 | V | 60.25 | 40.59 | 74 | 54 | -13.75 | -13.41 |
| 2483.95 | H | 63.01 | 44.15 | 74 | 54 | -10.99 | -9.85 |
| 2484.01 | V | 57.43 | 38.17 | 74 | 54 | -16.57 | -15.83 |

10 Antenna Application

10.1 Antenna requirement

The EUT'S antenna is met the requirement of FCC part 15C section 15.203 and 15.247.

FCC part 15C section 15.247 requirements:

Systems operating in the 2402-2480MHz band that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1dB for every 3dB that the directional gain of the antenna exceeds 6dBi.

10.2 Result

The EUT's antenna, permanent attached antenna, used a PCB antenna and integrated on PCB, The antenna's gain is 0 dBi and meets the requirement.

APPENDIX I (PHOTOS OF EUT)

