

FCC RF EXPOSURE REPORT

FCC ID: EMOIBT210

Project No. : 1601C243
**Equipment : BT Alarm Clock Speaker with
Speakerphone and USB charging**
**Model : iBT210, iBT210, iB210X, iBT210XC "X"= a to Z;
denote as color of cabinet**
Applicant : SDI TECHNOLOGIES INC.
Address : 1299 Main Street, Rahway, NJ 07065, U.S.A

**According: : FCC Guidelines for Human Exposure IEEE
C95.1**

B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

MPE CALCULATION METHOD:

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi^2} = \frac{EIRP}{4\pi^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	N/A	N/A	PIFA	N/A	0

TEST RESULTS

EUT :	BT Alarm Clock Speaker with Speakerphone and USB charging	Model Name :	iBT210
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode _1Mbps		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
0	1.0000	5.72	3.7325	0.00074293	1	Complies
0	1.0000	6.19	4.1591	0.00082785	1	Complies
0	1.0000	5.96	3.9446	0.00078515	1	Complies

EUT :	BT Alarm Clock Speaker with Speakerphone and USB charging	Model Name :	iBT210
Temperature :	25 °C	Relative Humidity:	55 %
Test Voltage :	AC 120V/60Hz		
Test Mode :	TX Mode _3Mbps		

Antenna Gain (dBi)	Antenna Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
0	1.0000	4.55	2.8510	0.00056748	1	Complies
0	1.0000	5.36	3.4356	0.00068383	1	Complies
0	1.0000	5.28	3.3729	0.00067135	1	Complies

Note: the calculated distance is 20 cm.