

# FCC&IC Radio Test Report

## FCC ID: EMOIBT55

## IC: 986B-IBT55

This report concerns (check one): Original Grant Class II Change

**Project No.** : 1412C179  
**Equipment** : Bluetooth Rechargeable Micro Speaker  
**Model Name For FCC** : iBT55; iBT55X; iBT55XC; MICRO GO+("X"= a to Z; denote as color of cabinet)  
**Model Name For IC** : iBT55  
**Applicant** : SDI TECHNOLOGIES INC.  
**Address** : 1299 Main Street, Rahway, NJ 07065, U.S.A

**Date of Receipt** : Dec. 30, 2014  
**Date of Test** : Dec. 30, 2014~Jan. 16, 2015  
**Issued Date** : Jan. 19, 2015  
**Tested by** : BTL Inc.

**Testing Engineer** : David Mao  
(David Mao)

**Technical Manager** : Leo My  
(Leo Hung)

**Authorized Signatory** : Steven Lu  
(Steven Lu)

# B T L I N C .

No.3, Jinshagang 1st Road, Shixia, Dalang Town, Dongguan,  
Guangdong, China.

TEL: +86-769-8318-3000 FAX: +86-769-8319-6000

**Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with the standards traceable to National Measurement Laboratory (**NML**) of **CHINA**, or National Institute of Standards and Technology (**NIST**) of **U.S.A.**

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

**BTL's** reports must not be used by the client to claim product endorsement by the authorities or any agency of the Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and **BTL-self**, extracts from the test report shall not be reproduced except in full with **BTL's** authorized written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO Guide 17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

**Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

<b>Table of Contents</b>	<b>Page</b>
<b>1 . CERTIFICATION</b>	<b>7</b>
<b>2 . SUMMARY OF TEST RESULTS</b>	<b>8</b>
2.1 TEST FACILITY	9
2.2 MEASUREMENT UNCERTAINTY	9
<b>3 . GENERAL INFORMATION</b>	<b>10</b>
3.1 GENERAL DESCRIPTION OF EUT	10
3.2 DESCRIPTION OF TEST MODES	12
3.3 TABLE OF PARAMETERS OF TEXT SOFTWARE SETTING	12
3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED	13
3.5 DESCRIPTION OF SUPPORT UNITS	14
<b>4 . EMC EMISSION TEST</b>	<b>15</b>
4.1 CONDUCTED EMISSION MEASUREMENT	15
4.1.1 POWER LINE CONDUCTED EMISSION LIMITS	15
4.1.2 TEST PROCEDURE	15
4.1.3 DEVIATION FROM TEST STANDARD	15
4.1.4 TEST SETUP	16
4.1.5 EUT OPERATING CONDITIONS	16
4.1.6 EUT TEST CONDITIONS	16
4.1.7 TEST RESULTS	16
4.2 RADIATED EMISSION MEASUREMENT	17
4.2.1 RADIATED EMISSION LIMITS	17
4.2.2 TEST PROCEDURE	18
4.2.3 DEVIATION FROM TEST STANDARD	18
4.2.4 TEST SETUP	19
4.2.5 EUT OPERATING CONDITIONS	20
4.2.6 EUT TEST CONDITIONS	20
4.2.7 TEST RESULTS (9KHZ TO 30MHZ)	20
4.2.8 TEST RESULTS (BETWEEN 30MHZ TO 1000 MHZ)	21
4.2.9 TEST RESULTS (ABOVE 1000 MHZ)	21
<b>5 . NUMBER OF HOPPING CHANNEL</b>	<b>22</b>
5.1 APPLIED PROCEDURES	22
5.1.1 TEST PROCEDURE	22
5.1.2 DEVIATION FROM STANDARD	22
5.1.3 TEST SETUP	22
5.1.4 EUT OPERATION CONDITIONS	22
5.1.5 EUT TEST CONDITIONS	22
5.1.6 TEST RESULTS	22

<b>Table of Contents</b>	<b>Page</b>
<b>6 . AVERAGE TIME OF OCCUPANCY</b>	<b>23</b>
<b>6.1 APPLIED PROCEDURES / LIMIT</b>	<b>23</b>
6.1.1 TEST PROCEDURE	23
6.1.2 DEVIATION FROM STANDARD	23
6.1.3 TEST SETUP	23
6.1.4 EUT OPERATION CONDITIONS	24
6.1.5 EUT TEST CONDITIONS	24
6.1.6 TEST RESULTS	24
<b>7 . HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>25</b>
<b>7.1 APPLIED PROCEDURES / LIMIT</b>	<b>25</b>
7.1.1 TEST PROCEDURE	25
7.1.2 DEVIATION FROM STANDARD	25
7.1.3 TEST SETUP	25
7.1.4 EUT TEST CONDITIONS	25
7.1.5 TEST RESULTS	25
<b>8 . BANDWIDTH TEST</b>	<b>26</b>
<b>8.1 APPLIED PROCEDURES</b>	<b>26</b>
8.1.1 TEST PROCEDURE	26
8.1.2 DEVIATION FROM STANDARD	26
8.1.3 TEST SETUP	26
8.1.4 EUT OPERATION CONDITIONS	26
8.1.5 EUT TEST CONDITIONS	26
8.1.6 TEST RESULTS	26
<b>9 . PEAK OUTPUT POWER TEST</b>	<b>27</b>
<b>9.1 APPLIED PROCEDURES / LIMIT</b>	<b>27</b>
9.1.1 TEST PROCEDURE	27
9.1.2 DEVIATION FROM STANDARD	27
9.1.3 TEST SETUP	27
9.1.4 EUT OPERATION CONDITIONS	27
9.1.5 EUT TEST CONDITIONS	27
9.1.6 TEST RESULTS	27
<b>10 . ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>28</b>
<b>10.1 APPLIED PROCEDURES / LIMIT</b>	<b>28</b>
10.1.1 TEST PROCEDURE	28
10.1.2 DEVIATION FROM STANDARD	28
10.1.3 TEST SETUP	28
10.1.4 EUT OPERATION CONDITIONS	28
10.1.5 EUT TEST CONDITIONS	28
10.1.6 TEST RESULTS	28
<b>11 . MEASUREMENT INSTRUMENTS LIST</b>	<b>29</b>

<b>Table of Contents</b>	<b>Page</b>
<b>12 . EUT TEST PHOTO</b>	<b>31</b>
<b>ATTACHMENT A - CONDUCTED EMISSION</b>	<b>35</b>
<b>ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)</b>	<b>38</b>
<b>ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)</b>	<b>40</b>
<b>ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)</b>	<b>47</b>
<b>ATTACHMENT E - NUMBER OF HOPPING CHANNEL</b>	<b>72</b>
<b>ATTACHMENT F - AVERAGE TIME OF OCCUPANCY</b>	<b>74</b>
<b>ATTACHMENT G - HOPPING CHANNEL SEPARATION MEASUREMENT</b>	<b>87</b>
<b>ATTACHMENT H - BANDWIDTH</b>	<b>92</b>
<b>ATTACHMENT I - PEAK OUTPUT POWER</b>	<b>97</b>
<b>ATTACHMENT J - ANTENNA CONDUCTED SPURIOUS EMISSION</b>	<b>102</b>

### REPORT ISSUED HISTORY

Issued No.	Description	Issued Date
BTL-FICP-1-1412C179	Original Issue.	Jan. 19, 2015

## 1. CERTIFICATION

Equipment : Bluetooth Rechargeable Micro Speaker  
Brand Name : iHome  
Model Name : iBT55; iBT55X; iBT55XC; MICRO GO+("X"= a to Z; denote as color of cabinet)  
For FCC  
Model Name : iBT55  
For IC  
Applicant : SDI TECHNOLOGIES INC.  
Manufacturer : SDI TECHNOLOGIES INC.  
Address : 1299 Main Street, Rahway, NJ 07065, U.S.A  
Factory : Winty Industries Corporation (Shen Zhen) Co. Ltd.  
Address : San Lian Industry Zone. Shi Yan Town, Bao An District, ShenZhen, China  
Date of Test : Dec. 30, 2014~Jan. 16, 2015  
Test Sample : ENGINEERING SAMPLE  
Standard(s) : FCC Part15, Subpart C : 2013 (15.247) / ANSI C63.4 : 2009 /  
FCC Public Notice DA 00-705, March 30, 2000.  
Canada RSS-210: 2010  
RSS-GEN Issue 4, Nov 2014

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

The test data, data evaluation, and equipment configuration contained in our test report (Ref No. BTL-FICP-1-1412C179) were obtained utilizing the test procedures, test instruments, test sites that has been accredited by the Authority of TAF according to the ISO-17025 quality assessment standard and technical standard(s).

## 2. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

Applied Standard(s): 47 CFR Part 15, Subpart C: 2013; Canada RSS-210:2010; RSS-GEN Issue 4, Nov 2014				
Standard(s) Section		Test Item	Judgment	Remark
FCC	IC			
15.207	RSS-GEN 8.8	Conducted Emission	PASS	
15.247(d)	RSS-210, Issue 8, Annex 8, A8.5	Antenna conducted Spurious Emission	PASS	
15.247 (a)(1)	RSS-210, Issue 8, Annex 8, A8.1(b)	Hopping Channel Separation	PASS	
15.247 (b)(1)	RSS-210, Issue 8, Annex 8, A8.1(b)	Peak Output Power	PASS	
15.247(d) 15.209	RSS-210, Issue 8, Annex 8, Section 8.5	Radiated Spurious Emission	PASS	
15.247 (a)(1)(iii)	RSS-210, Issue 8, Annex 8, A8.1(d)	Number of Hopping Frequency	PASS	
15.247 (a)(1)(iii)	RSS-210, Issue 8, Annex 8, A8.1(d)	Dwell Time	PASS	
15.205	RSS-GEN 8.10	Restricted Bands	PASS	
15.203	-	Antenna Requirement	PASS	

Note:

- (1) "N/A" denotes test is not applicable in this test report
- (2) According to FCC Public Notice DA 00-705, March 30, 2000.

## 2.1 TEST FACILITY

The test facilities used to collect the test data in this report is **DG-C02/DG-CB03** at the location of No.3,Jinshagang 1st Road, Shixia, Dalang Town, Dong Guan, Guangdong, China.523792

BTL's test firm number for FCC: 319330

BTL's test firm number for IC: 4428B-1

## 2.2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately **95** %.

### A. Conducted Measurement :

Test Site	Method	Measurement Frequency Range	U, (dB)	Note
DG-C02	CISPR	150 KHz ~ 30MHz	1.94	

### B. Radiated Measurement :

Test Site	Method	Measurement Frequency Range	Ant. H / V	U, (dB)	Note
DG-CB03	CISPR	9KHz~30MHz	V	3.79	
		9KHz~30MHz	H	3.57	
		30MHz ~ 200MHz	V	3.82	
		30MHz ~ 200MHz	H	3.60	
		200MHz ~ 1,000MHz	V	3.86	
		200MHz ~ 1,000MHz	H	3.94	
		1GHz~18GHz	V	3.12	
		1GHz~18GHz	H	3.68	
		18GHz~40GHz	V	4.15	
18GHz~40GHz	H	4.14			

### 3. GENERAL INFORMATION

#### 3.1 GENERAL DESCRIPTION OF EUT

Equipment	Bluetooth Rechargeable Micro Speaker	
Brand Name	iHome	
Model Name For FCC	iBT55; iBT55X; iBT55XC; MICRO GO+	
Model Name For IC	iBT55	
Model Difference For FCC	"X" = a to Z; denote as color of cabinet	
Output Power (Max.)	Operation Frequency	2402~2480 MHz
	Modulation Technology	GFSK(1Mbps) $\pi$ /4-DQPSK(2Mbps)
	Bit Rate of Transmitter	8-DPSK(3Mbps)
	Output Power Max.	2.35 dBm(1Mbps) 2.44 dBm(3Mbps)
Power Source	#1 DC Voltage supplied from USB Port. #2 Supplied from Lithium-ion battery.	
Power Rating	#1 O/P:DC 5V #2 DC 3.7V 280mAh	

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

2. Channel List:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	27	2429	54	2456
01	2403	28	2430	55	2457
02	2404	29	2431	56	2458
03	2405	30	2432	57	2459
04	2406	31	2433	58	2460
05	2407	32	2434	59	2461
06	2408	33	2435	60	2462
07	2409	34	2436	61	2463
08	2410	35	2437	62	2464
09	2411	36	2438	63	2465
10	2412	37	2439	64	2466
11	2413	38	2440	65	2467
12	2414	39	2441	66	2468
13	2415	40	2442	67	2469
14	2416	41	2443	68	2470
15	2417	42	2444	69	2471
16	2418	43	2445	70	2472
17	2419	44	2446	71	2473
18	2420	45	2447	72	2474
19	2421	46	2448	73	2475
20	2422	47	2449	74	2476
21	2423	48	2450	75	2477
22	2424	49	2451	76	2478
23	2425	50	2452	77	2479
24	2426	51	2453	78	2480
25	2427	52	2454		
26	2428	53	2455		

3 Table for Filed Antenna:

Ant.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	printed	N/A	0

### 3.2 DESCRIPTION OF TEST MODES

To investigate the maximum EMI emission characteristics generated from EUT, the test system was pre-scanning tested based on the consideration of following EUT operation mode or test configuration mode which possibly have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	TX Mode <b>Note (1)</b>
Mode 2	Normal Link

The EUT system operated these modes were found to be the worst case during the pre-scanning test as following:

For Conducted Emission	
Final Test Mode	Description
Mode 2	Normal Link

For Radiated Emission	
Final Test Mode	Description
Mode 1	TX Mode <b>Note (1)</b>

**Note:**

- (1) The measurements are performed at the high, middle, low available channels.
- (2) The measurements for Hopping Channel Separation, Bandwidth and Peak Output Power were tested during 1Mbps, 2Mbps and 3Mbps, the worst case are 1Mbps and 3Mbps, only worst case was documented.

### 3.3 TABLE OF PARAMETERS OF TEST SOFTWARE SETTING

During testing, channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of FHSS


1Mbps

Test Software Version	AB1500FamilyLabTestTool		
Frequency (MHz)	2402	2441	2480
Parameters	63	63	63


3Mbps

Test Software Version	AB1500FamilyLabTestTool		
Frequency (MHz)	2402	2441	2480
Parameters	63	63	63

### 3.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED Conducted TX Mode:



### Radiated TX Mode:



### 3.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

#### Conducted / Radiated TX Mode:

Item	Equipment	Mfr/Brand	Model/Type No.	FCC ID/IC	Series No.	Note
A	ADAPTER	DELL	AA65NM121	N/A	CNORGFH0713004 31039OA03	
B	NOTEBOOK	DELL	INSPIRON 1420	DOC	JX193A01SDC2	

Item	Shielded Type	Ferrite Core	Length	Note
1	YES	NO	1.2m	
2	YES	NO	0.8m	

## 4. EMC EMISSION TEST

### 4.1 CONDUCTED EMISSION MEASUREMENT

#### 4.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

Frequency of Emission (MHz)	Conducted Limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 -0.5	66 to 56*	56 to 46*
0.50 -5.0	56	46
5.0 -30.0	60	50

Note:

- (1) The limit of " \* " decreases with the logarithm of the frequency
- (2) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Insertion Loss + Cable Loss + Attenuator Factor(if use)  
 Margin Level = Measurement Value - Limit Value

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 KHz


#### 4.1.2 TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.1.3 DEVIATION FROM TEST STANDARD

No deviation

#### 4.1.4 TEST SETUP



- Note:**
1. Support units were connected to second LISN.
  2. Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

#### 4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical function (as a customer would normally use it), EUT was programmed to be in continuously transmitting/receiving data or hopping on mode.

#### 4.1.6 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: AC 120V/60Hz

#### 4.1.7 TEST RESULTS

**Please refer to the Attachment A.**

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of Note. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform in this case, a "\*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150KHz to 30MHz.

## 4.2 RADIATED EMISSION MEASUREMENT

### 4.2.1 RADIATED EMISSION LIMITS (Frequency Range 9KHz -1000MHz)

20dB in any 100 KHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a) & RSS-210 section 2.2& Annex 8 (A8.5), then the 15.209(a) & RSS-Gen limit in the table below has to be followed.

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
960~1000	500	3

### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

Frequency (MHz)	dB(uV/m) (at 3 meters)	
	Peak	Average
Above 1000	74	54

Notes:

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m) = 20log Emission level (uV/m).
- (4) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)  
 Margin Level = Measurement Value - Limit Value

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	10th carrier harmonic
RBW / VBW (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

Spectrum Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9KHz ~90KHz for PK/AVG detector
Start ~ Stop Frequency	90KHz ~110KHz for QP detector
Start ~ Stop Frequency	110KHz ~490KHz for PK/AVG detector
Start ~ Stop Frequency	490KHz ~30MHz for QP detector
Start ~ Stop Frequency	30MHz~1000MHz for QP detector

#### 4.2.2 TEST PROCEDURE


- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8 m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- e. If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed.
- f. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.2.3 DEVIATION FROM TEST STANDARD


No deviation

#### 4.2.4 TEST SETUP


(A) Radiated Emission Test Set-Up Frequency Below 1 GHz



(B) Radiated Emission Test Set-Up Frequency Above 1 GHz



(C) For radiated emissions below 30MHz



#### 4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing

#### 4.2.6 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: DC 3.7V

#### 4.2.7 TEST RESULTS (9KHZ TO 30MHZ)

Please refer to the Attachment B

Remark:

- (1) The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.
- (2) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB).
- (3) Limit line = specific limits (dBuV) + distance extrapolation factor.

#### **4.2.8 TEST RESULTS (BETWEEN 30MHZ TO 1000 MHZ)**

**Please refer to the Attachment C.**

Remark:

- (1) Reading in which marked as QP or Peak means measurements by using are Quasi-Peak Mode or Peak Mode with Detector BW=120KHz ; SPA setting in RBW=120KHz, VBW =120KHz, Swp. Time = 0.3 sec./MHz.
- (2) All readings are Peak unless otherwise stated QP in column of 『Note』 . Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform.
- (3) Measuring frequency range from 30MHz to 1000MHz.
- (4) If the peak scan value lower limit more than 20dB, then this signal data does not show in table.

#### **4.2.9 TEST RESULTS (ABOVE 1000 MHZ)**

**Please refer to the Attachment D.**

Remark:

- (1) Radiated emissions measured in frequency range above 1000MHz were made with an instrument using Peak detector mode and AV detector mode of the emission
- (2) A preamp and high pass filter were used for this test in order to provide sufficient measurement sensitivity.
- (3) EUT Orthogonal Axis:  
"X" - denotes Laid on Table ; "Y" - denotes Vertical Stand ; "Z" - denotes Side Stand
- (4) During the measurements above 1 GHz it is taken care of that the EUT is always within the 3 dB cone of radiation BW of the used antenna
- (5) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

## 5. NUMBER OF HOPPING CHANNEL

### 5.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C/ RSS-GEN and RSS-210			
Section	Test Item	Frequency Range (MHz)	Result
15.247(a)(1)(iii) RSS-210, Issue 8, Annex 8, A8.1(d)	Number of Hopping Channel	2400-2483.5	PASS

Spectrum Parameters	Setting
Attenuation	Auto
Span Frequency	> Operating Frequency Range
RBW	100 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 5.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW=100KHz, VBW=100KHz, Sweep time = Auto.

#### 5.1.2 DEVIATION FROM STANDARD

No deviation.

#### 5.1.3 TEST SETUP



#### 5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 5.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: DC 3.7V

#### 5.1.6 TEST RESULTS

Please refer to the Attachment E

## 6. AVERAGE TIME OF OCCUPANCY

### 6.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C/ RSS-GEN and RSS-210				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(1)(iii) RSS-210, Issue 8, Annex 8, A8.1(d)	Average Time of Occupancy	0.4sec	2400-2483.5	PASS

#### 6.1.1 TEST PROCEDURE

- a. The transmitter output (antenna port) was connected to the spectrum analyzer
- b. Set RBW of spectrum analyzer to 1MHz and VBW to 1MHz.
- c. Use a video trigger with the trigger level set to enable triggering only on full pulses.
- d. Sweep Time is more than once pulse time.
- e. Set the center frequency on any frequency would be measure and set the frequency span to zero span.
- f. Measure the maximum time duration of one single pulse.
- g. Set the EUT for DH5, DH3 and DH1 packet transmitting.
- h. Measure the maximum time duration of one single pulse.
- i. DH5 Packet permit maximum  $1600 / 79 / 6 = 3.37$  hops per second in each channel (5 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $3.37 \times 31.6 = 106.6$  within 31.6 seconds.
- j. DH3 Packet permit maximum  $1600 / 79 / 4 = 5.06$  hops per second in each channel (3 time slots TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $5.06 \times 31.6 = 160$  within 31.6 seconds.
- k. DH1 Packet permit maximum  $1600 / 79 / 2 = 10.12$  hops per second in each channel (1 time slot TX, 1 time slot RX). So, the dwell time is the time duration of the pulse times  $10.12 \times 31.6 = 320$  within 31.6 seconds.

#### 6.1.2 DEVIATION FROM STANDARD

No deviation.

#### 6.1.3 TEST SETUP



#### **6.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### **6.1.5 EUT TEST CONDITIONS**

Temperature: 25°C

Relative Humidity: 55%

Test Voltage: DC 3.7V

#### **6.1.6 TEST RESULTS**

**Please refer to the Attachment F**

## 7. HOPPING CHANNEL SEPARATION MEASUREMENT

### 7.1 APPLIED PROCEDURES / LIMIT

Frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 KHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater.

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz
VBW	100 KHz
Detector	Peak
Trace	Max Hold
Sweep Time	Auto


#### 7.1.1 TEST PROCEDURE

- a. The EUT must have its hopping function enabled
- b. Span = wide enough to capture the peaks of two adjacent channels
  - Resolution (or IF) Bandwidth (RBW)  $\geq$  1% of the span
  - Video (or Average) Bandwidth (VBW)  $\geq$  RBW
  - Sweep = Auto
  - Detector function = Peak
  - Trace = Max Hold

#### 7.1.2 DEVIATION FROM STANDARD

No deviation.

#### 7.1.3 TEST SETUP



#### 7.1.4 EUT TEST CONDITIONS

Temperature: 25°C  
 Relative Humidity: 55%  
 Test Voltage: DC 3.7V

#### 7.1.5 TEST RESULTS

Please refer to the Attachment G

## 8. BANDWIDTH TEST

### 8.1 APPLIED PROCEDURES

FCC Part15 (15.247) , Subpart C/ RSS-GEN and RSS-210		
Section	Test Item	Frequency Range (MHz)
15.247(a)(2) RSS-GEN section 6.6 RSS-210, Issue 8, Annex 8, A8.1(b)	Bandwidth	2400-2483.5

Spectrum Parameter	Setting
Attenuation	Auto
Span Frequency	> Measurement Bandwidth or Channel Separation
RBW	30 KHz (20dB Bandwidth) / 30 KHz (Channel Separation)
VBW	100 KHz (20dB Bandwidth) / 100 KHz (Channel Separation)
Detector	Peak
Trace	Max Hold
Sweep Time	Auto

#### 8.1.1 TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 30KHz, VBW=100KHz, Sweep Time = Auto.

#### 8.1.2 DEVIATION FROM STANDARD

No deviation.

#### 8.1.3 TEST SETUP



#### 8.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 8.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: DC 3.7V

#### 8.1.6 TEST RESULTS

**Please refer to the Attachment H**

## 9. PEAK OUTPUT POWER TEST

### 9.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C/ RSS-GEN and RSS-210				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(1) RSS-GEN section 6.12 RSS-210, Issue 8, Annex 8, A8.1(b)	Peak Output Power	1 Watt or 30dBm	2400-2483.5	PASS

#### 9.1.1 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- Spectrum Setting: RBW= 1MHz/3MHz, VBW= 1MHz/3MHz, Sweep time = Auto.

#### 9.1.2 DEVIATION FROM STANDARD

No deviation.

#### 9.1.3 TEST SETUP



#### 9.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### 9.1.5 EUT TEST CONDITIONS

Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: DC 3.7V

#### 9.1.6 TEST RESULTS

Please refer to the Attachment I

## **10. ANTENNA CONDUCTED SPURIOUS EMISSION**

### **10.1 APPLIED PROCEDURES / LIMIT**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.

#### **10.1.1 TEST PROCEDURE**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below,
- b. Spectrum Setting: RBW= 100KHz, VBW=100KHz, Sweep time = Auto.

#### **10.1.2 DEVIATION FROM STANDARD**

No deviation.

#### **10.1.3 TEST SETUP**



#### **10.1.4 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.1.5 Unless otherwise a special operating condition is specified in the follows during the testing.

#### **10.1.5 EUT TEST CONDITIONS**

Temperature: 25°C  
Relative Humidity: 55%  
Test Voltage: DC 3.7V

#### **10.1.6 TEST RESULTS**

**Please refer to the Attachment J**

## 11. MEASUREMENT INSTRUMENTS LIST

Conducted Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	LISN	EMCO	3816/2	00052765	Mar. 29, 2015
2	LISN	R&S	ENV216	101447	Mar. 29, 2015
3	Test Cable	N/A	C_17	N/A	Mar. 14, 2015
4	EMI TEST RECEIVER	R&S	ESCS30	833364/017	Mar. 29, 2015
5	50Ω Terminator	SHX	TF2-3G-A	08122902	Mar. 29, 2015

Radiated Emission Measurement					
Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Antenna	Schwarzbeck	VULB9160	9160-3232	Mar. 29, 2015
2	Amplifier	HP	8447D	2944A09673	Mar. 29, 2015
3	Receiver	AGILENT	N9038A	MY52130039	Sep. 30, 2015
4	Test Cable	N/A	C-01_CB03	N/A	Jul. 01, 2015
5	Controller	CT	SC100	N/A	N/A
6	Measurement Software	Farad	EZ-EMC Ver.NB-03A1-0 1	N/A	N/A
7	Antenna	ETS	3115	00075789	Mar. 29, 2015
8	Amplifier	Agilent	8449B	3008A02274	Mar. 29, 2015
9	Receiver	AGILENT	N9038A	MY52130039	Sep. 30, 2015
10	Test Cable	HUBER+SUHNER	C-48	N/A	Apr. 30, 2015
11	Controller	CT	SC100	N/A	N/A
12	Broad-Band Horn Antenna	Schwarzbeck	BBHA 9170	9170319	Feb. 22, 2015
13	Microwave Pre-amplifier With Adaptor	EMC INSTRUMENT	EMC2654045	980039 & HA01	Feb. 22, 2015
14	Active Loop Antenna	R&S	HFH2-Z2	830749/020	Mar. 29, 2015

### Number of Hopping Channel

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015

### Average Time of Occupancy

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015

### Hopping Channel Separation Measurement

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015

### Bandwidth

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015

### Peak Output Power

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015

### Antenna Conducted Spurious Emission

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Calibrated until
1	Spectrum Analyzer	R&S	FSP 40	100185	Nov. 02, 2015

Remark: "N/A" denotes no model name, serial no. or calibration specified.  
 All calibration period of equipment list is one year.

## 12. EUT TEST PHOTO

### Conducted Measurement Photos



## Radiated Measurement Photos

9KHz to 30MHz




## Radiated Measurement Photos

30MHz to 1000MHz



## Radiated Measurement Photos


Above 1000MHz



## ATTACHMENT A - CONDUCTED EMISSION

Test Mode: TX Mode


### Line



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1852	45.93	9.49	55.42	64.25	-8.83	peak	
2		0.1852	25.80	9.49	35.29	54.25	-18.96	AVG	
3		0.2242	39.04	9.51	48.55	62.66	-14.11	peak	
4		0.3141	34.35	9.55	43.90	59.86	-15.96	peak	
5		0.4352	29.45	9.61	39.06	57.15	-18.09	peak	
6		5.1172	26.80	9.67	36.47	60.00	-23.53	peak	
7		15.1016	37.50	9.88	47.38	60.00	-12.62	peak	

Test Mode: TX Mode

### Neutral



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measurement dBuV	Limit dBuV	Over dB	Detector	Comment
1	*	0.1891	45.54	9.57	55.11	64.08	-8.97	peak	
2		0.1891	27.10	9.57	36.67	54.08	-17.41	AVG	
3		0.2281	39.28	9.57	48.85	62.52	-13.67	peak	
4		0.3218	35.41	9.57	44.98	59.66	-14.68	peak	
5		0.4742	28.10	9.58	37.68	56.44	-18.76	peak	
6		4.9062	26.36	9.68	36.04	56.00	-19.96	peak	
7		15.2421	38.41	9.94	48.35	60.00	-11.65	peak	

**ATTACHMENT B - RADIATED EMISSION (9KHZ-30MHZ)**

Test Mode:	TX Mode
------------	---------

Frequency (MHz)	Ant 0°/90°	Read level dBuV/m	Factor (dB)	Measured(FS) (dBuV/m)	Limit(QP) (dBuV/m)	Margin (dB)	Note
0.0073	0°	12.12	25.10	37.22	110.34	-73.11	AVG
0.0073	0°	14.38	25.10	39.48	130.34	-90.85	PEAK
0.0141	0°	5.07	24.67	29.74	104.62	-74.88	AVG
0.0141	0°	7.44	24.67	32.11	124.62	-92.51	PEAK
0.0257	0°	3.76	23.94	27.70	99.41	-71.71	AVG
0.0257	0°	5.47	23.94	29.41	119.41	-90.00	PEAK
0.0336	0°	0.99	23.44	24.43	97.08	-72.65	AVG
0.0336	0°	2.85	23.44	26.29	117.08	-90.79	PEAK
0.4960	0°	30.34	19.81	50.15	73.69	-23.54	QP
1.8250	0°	21.29	19.52	40.81	69.54	-28.73	QP

Frequency (MHz)	Ant 0°/90°	Read level dBuV/m	Factor (dB)	Measured(FS) (dBuV/m)	Limit(QP) (dBuV/m)	Margin (dB)	Note
0.0065	90°	12.47	24.30	36.77	131.35	-94.58	AVG
0.0068	90°	14.11	24.30	38.41	151.35	-112.94	PEAK
0.0327	90°	6.12	23.50	29.62	117.31	-87.70	AVG
0.0327	90°	8.39	23.50	31.89	137.31	-105.43	PEAK
0.0438	90°	3.24	22.79	26.03	114.77	-88.74	AVG
0.0438	90°	5.65	22.79	28.44	134.77	-106.33	PEAK
0.0472	90°	0.62	22.58	23.20	114.13	-90.93	AVG
0.0472	90°	2.95	22.58	25.53	134.13	-108.60	PEAK
0.4860	90°	30.13	19.83	49.96	93.87	-43.91	QP
1.7840	90°	21.75	19.52	41.27	69.54	-28.27	QP

**ATTACHMENT C - RADIATED EMISSION (30MHZ TO 1000MHZ)**

Test Mode: TX 2402MHz \_CH00\_1Mbps

### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		171.6200	28.41	-12.78	15.63	43.50	-27.87	peak	
2		297.7200	28.31	-11.03	17.28	46.00	-28.72	peak	
3		438.3700	29.26	-8.83	20.43	46.00	-25.57	peak	
4		570.2900	29.83	-7.92	21.91	46.00	-24.09	peak	
5		676.0200	29.90	-5.04	24.86	46.00	-21.14	peak	
6	*	793.3900	30.43	-3.12	27.31	46.00	-18.69	peak	

Test Mode: TX 2402MHz \_CH00\_1Mbps

### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		180.3500	33.21	-13.05	20.16	43.50	-23.34	peak	
2		299.6600	32.25	-10.99	21.26	46.00	-24.74	peak	
3		384.0500	35.84	-10.25	25.59	46.00	-20.41	peak	
4		455.8300	32.88	-8.84	24.04	46.00	-21.96	peak	
5		670.2000	29.95	-5.06	24.89	46.00	-21.11	peak	
6	*	800.1800	29.76	-2.89	26.87	46.00	-19.13	peak	

Test Mode: TX 2441MHz \_CH39\_1Mbps

### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		176.4700	29.48	-12.90	16.58	43.50	-26.92	peak	
2		380.1700	29.05	-10.42	18.63	46.00	-27.37	peak	
3		464.5600	30.70	-9.18	21.52	46.00	-24.48	peak	
4		676.0200	29.90	-5.04	24.86	46.00	-21.14	peak	
5		723.5500	31.50	-4.78	26.72	46.00	-19.28	peak	
6	*	793.3900	30.43	-3.12	27.31	46.00	-18.69	peak	

Test Mode: TX 2441MHz \_CH39\_1Mbps


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		191.9900	36.28	-14.48	21.80	43.50	-21.70	peak	
2		252.1300	36.83	-13.98	22.85	46.00	-23.15	peak	
3		299.6600	34.78	-10.99	23.79	46.00	-22.21	peak	
4		395.6900	35.88	-9.73	26.15	46.00	-19.85	peak	
5		509.1800	33.97	-10.05	23.92	46.00	-22.08	peak	
6	*	788.5400	29.89	-3.29	26.60	46.00	-19.40	peak	

Test Mode: TX 2480MHz \_CH78\_1Mbps

### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		176.4700	31.98	-12.90	19.08	43.50	-24.42	peak	
2		318.0900	30.65	-11.27	19.38	46.00	-26.62	peak	
3		444.1900	32.06	-8.73	23.33	46.00	-22.67	peak	
4		516.9400	34.25	-9.64	24.61	46.00	-21.39	peak	
5		723.5500	33.00	-4.78	28.22	46.00	-17.78	peak	
6	*	820.5500	31.88	-3.00	28.88	46.00	-17.12	peak	

Test Mode: TX 2480MHz \_CH78\_1Mbps

### Horizontal




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		180.3500	36.63	-13.05	23.58	43.50	-19.92	peak	
2		255.0400	37.41	-13.90	23.51	46.00	-22.49	peak	
3		299.6600	37.78	-10.99	26.79	46.00	-19.21	peak	
4		372.4100	37.62	-10.77	26.85	46.00	-19.15	peak	
5		395.6900	37.38	-9.73	27.65	46.00	-18.35	peak	
6	*	834.1300	31.21	-3.07	28.14	46.00	-17.86	peak	

## **ATTACHMENT D - RADIATED EMISSION (ABOVE 1000MHZ)**

Orthogonal Axis :	X
Test Mode :	TX 2402MHz _CH00_1Mbps


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	22.83	31.88	54.71	74.00	-19.29	peak	
2		2390.000	13.44	31.88	45.32	54.00	-8.68	AVG	
3	X	2401.900	64.25	31.89	96.14	74.00	22.14	peak	no limit
4	*	2401.900	53.21	31.89	85.10	54.00	31.10	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX 2402MHz _CH00_1Mbps


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4804.260	55.12	3.58	58.70	74.00	-15.30	peak	
2	*	4804.260	44.96	3.58	48.54	54.00	-5.46	AVG	
3		7206.320	40.79	9.45	50.24	74.00	-23.76	peak	
4		7206.320	31.68	9.45	41.13	54.00	-12.87	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2402MHz _CH00_1Mbps

### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	23.61	31.88	55.49	74.00	-18.51	peak	
2		2390.000	13.43	31.88	45.31	54.00	-8.69	AVG	
3	X	2401.900	58.62	31.89	90.51	74.00	16.51	peak	no limit
4	*	2401.900	49.25	31.89	81.14	54.00	27.14	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX 2402MHz _CH00_1Mbps


### Horizontal



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4803.800	47.61	3.58	51.19	74.00	-22.81	peak	
2 *	4803.800	37.59	3.58	41.17	54.00	-12.83	AVG	
3	7205.960	35.69	9.45	45.14	74.00	-28.86	peak	
4	7205.960	26.21	9.45	35.66	54.00	-18.34	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2441MHz _CH39_1Mbps

### Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2440.850	64.38	31.95	96.33	74.00	22.33	peak	no limit
2	*	2440.850	53.41	31.95	85.36	54.00	31.36	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX 2441MHz _CH39_1Mbps


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4882.160	53.16	3.73	56.89	74.00	-17.11	peak	
2	*	4882.160	43.28	3.73	47.01	54.00	-6.99	AVG	
3		7323.080	43.59	9.88	53.47	74.00	-20.53	peak	
4		7323.080	33.49	9.88	43.37	54.00	-10.63	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2441MHz _CH39_1Mbps

### Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2440.900	61.76	31.95	93.71	74.00	19.71	peak	no limit
2	*	2440.900	50.09	31.95	82.04	54.00	28.04	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX 2441MHz _CH39_1Mbps


### Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1		4881.800	46.19	3.73	49.92	74.00	-24.08	peak	
2	*	4881.800	36.02	3.73	39.75	54.00	-14.25	AVG	
3		7322.950	38.52	9.88	48.40	74.00	-25.60	peak	
4		7322.950	29.04	9.88	38.92	54.00	-15.08	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_1Mbps

### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2479.900	63.72	32.00	95.72	74.00	21.72	peak	no limit
2	*	2479.900	54.11	32.00	86.11	54.00	32.11	AVG	no limit
3		2483.500	24.77	32.01	56.78	74.00	-17.22	peak	
4		2483.500	13.46	32.01	45.47	54.00	-8.53	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_1Mbps


### Vertical



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4960.320	53.57	3.88	57.45	74.00	-16.55	peak	
2 *	4960.320	43.25	3.88	47.13	54.00	-6.87	AVG	
3	7440.020	44.26	10.29	54.55	74.00	-19.45	peak	
4	7440.020	34.17	10.29	44.46	54.00	-9.54	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_1Mbps

### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2479.900	57.68	32.00	89.68	74.00	15.68	peak	no limit
2	*	2479.900	48.77	32.00	80.77	54.00	26.77	AVG	no limit
3		2483.500	22.06	32.01	54.07	74.00	-19.93	peak	
4		2483.500	13.45	32.01	45.46	54.00	-8.54	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_1Mbps


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4959.750	45.64	3.88	49.52	74.00	-24.48	peak	
2	*	4959.750	36.19	3.88	40.07	54.00	-13.93	AVG	
3		7439.880	36.42	10.29	46.71	74.00	-27.29	peak	
4		7439.880	25.63	10.29	35.92	54.00	-18.08	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2402MHz_CH00_3Mbps


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	23.10	31.88	54.98	74.00	-19.02	peak	
2		2390.000	13.47	31.88	45.35	54.00	-8.65	AVG	
3	X	2402.250	63.54	31.89	95.43	74.00	21.43	peak	no limit
4	*	2402.250	53.97	31.89	85.86	54.00	31.86	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX 2402MHz _CH00_3Mbps


### Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4803.960	47.34	3.58	50.92	54.00	-3.08	AVG	
2		4804.300	57.57	3.58	61.15	74.00	-12.85	peak	
3		7205.790	48.72	9.45	58.17	74.00	-15.83	peak	
4		7205.790	39.04	9.45	48.49	54.00	-5.51	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2402MHz _CH00_3Mbps

### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		2390.000	22.95	31.88	54.83	74.00	-19.17	peak	
2		2390.000	13.42	31.88	45.30	54.00	-8.70	AVG	
3	X	2402.000	58.95	31.89	90.84	74.00	16.84	peak	no limit
4	*	2402.000	49.66	31.89	81.55	54.00	27.55	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX 2402MHz _CH00_3Mbps


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1		4803.900	46.19	3.58	49.77	74.00	-24.23	peak	
2	*	4804.000	37.67	3.58	41.25	54.00	-12.75	AVG	
3		7206.080	37.62	9.45	47.07	74.00	-26.93	peak	
4		7206.080	28.06	9.45	37.51	54.00	-16.49	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2441MHz _CH39_3Mbps

### Vertical



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2441.000	62.77	31.95	94.72	74.00	20.72	peak	no limit
2	*	2441.000	52.92	31.95	84.87	54.00	30.87	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX 2441MHz _CH39_3Mbps


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	*	4882.000	43.78	3.73	47.51	54.00	-6.49	AVG	
2		4882.200	53.21	3.73	56.94	74.00	-17.06	peak	
3		7323.120	44.18	9.88	54.06	74.00	-19.94	peak	
4		7323.120	35.12	9.88	45.00	54.00	-9.00	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2441MHz _CH39_3Mbps


### Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	X	2441.000	57.19	31.95	89.14	74.00	15.14	peak	no limit
2	*	2441.000	49.55	31.95	81.50	54.00	27.50	AVG	no limit

Orthogonal Axis :	X
Test Mode :	TX 2441MHz _CH39_3Mbps


### Horizontal



No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector	Comment
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB		
1	*	4881.850	35.99	3.73	39.72	54.00	-14.28	AVG	
2		4881.950	46.80	3.73	50.53	74.00	-23.47	peak	
3		7323.060	28.41	9.88	38.29	54.00	-15.71	AVG	
4		7323.065	38.19	9.88	48.07	74.00	-25.93	peak	

Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_3Mbps


### Vertical



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2480.000	64.28	32.00	96.28	74.00	22.28	peak	no limit
2	*	2480.000	53.97	32.00	85.97	54.00	31.97	AVG	no limit
3		2483.500	22.43	32.01	54.44	74.00	-19.56	peak	
4		2483.500	13.44	32.01	45.45	54.00	-8.55	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_3Mbps


### Vertical



No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4960.000	53.33	3.88	57.21	74.00	-16.79	peak	
2 *	4960.000	42.92	3.88	46.80	54.00	-7.20	AVG	
3	7439.920	36.16	10.29	46.45	74.00	-27.55	peak	
4	7439.920	26.43	10.29	36.72	54.00	-17.28	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_3Mbps


### Horizontal



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	X	2480.000	54.12	32.00	86.12	74.00	12.12	peak	no limit
2	*	2480.000	49.65	32.00	81.65	54.00	27.65	AVG	no limit
3		2483.500	24.05	32.01	56.06	74.00	-17.94	peak	
4		2483.500	13.48	32.01	45.49	54.00	-8.51	AVG	

Orthogonal Axis :	X
Test Mode :	TX 2480MHz _CH78_3Mbps

### Horizontal




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Comment
1	4959.900	48.08	3.88	51.96	74.00	-22.04	peak	
2 *	4960.000	37.54	3.88	41.42	54.00	-12.58	AVG	
3	7440.280	35.47	10.29	45.76	74.00	-28.24	peak	
4	7440.280	26.08	10.29	36.37	54.00	-17.63	AVG	

**ATTACHMENT E - NUMBER OF HOPPING CHANNEL**

**Test Mode      Hopping Mode\_1Mbps**


Number of Hopping Channel      79



Date: 12.JAN.2015 17:25:27

**Test Mode      Hopping Mode\_3Mbps**

Number of Hopping Channel      79




Date: 12.JAN.2015 18:06:15

**ATTACHMENT F - AVERAGE TIME OF OCCUPANCY**

Test Mode :	TX Mode_1Mbps
-------------	---------------


Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402	3.1990	0.3412	0.4000	Complies
DH3	2402	1.7990	0.2878	0.4000	Complies
DH1	2402	0.4790	0.1533	0.4000	Complies
DH5	2441	3.0790	0.3284	0.4000	Complies
DH3	2441	1.8190	0.2910	0.4000	Complies
DH1	2441	0.4690	0.1501	0.4000	Complies
DH5	2480	3.1200	0.3328	0.4000	Complies
DH3	2480	1.7800	0.2848	0.4000	Complies
DH1	2480	0.4790	0.1533	0.4000	Complies

### CH00-DH1




Date: 12.JAN.2015 17:19:59

### CH00-DH3




Date: 12.JAN.2015 17:40:36

### CH00-DH5




Date: 12.JAN.2015 17:41:38

### CH39-DH1




Date: 12.JAN.2015 17:20:11

### CH39-DH3




Date: 12.JAN.2015 17:40:50

### CH39-DH5




Date: 12.JAN.2015 17:41:52

## CH78-DH1




Date: 12.JAN.2015 17:20:23

## CH78-DH3



Date: 12.JAN.2015 17:41:00

**CH78-DH5**




Date: 12.JAN.2015 17:42:07

Test Mode :	TX Mode_3Mbps
-------------	---------------


Data Packet	Frequency (MHz)	Pulse Duration (ms)	Dwell Time (s)	Limits (s)	Test Result
DH5	2402	3.3190	0.3540	0.4000	Complies
DH3	2402	1.7590	0.2814	0.4000	Complies
DH1	2402	0.4640	0.1485	0.4000	Complies
DH5	2441	3.0390	0.3242	0.4000	Complies
DH3	2441	1.7790	0.2846	0.4000	Complies
DH1	2441	0.4940	0.1581	0.4000	Complies
DH5	2480	3.1590	0.3370	0.4000	Complies
DH3	2480	1.8390	0.2942	0.4000	Complies
DH1	2480	0.4590	0.1469	0.4000	Complies

### CH00-DH1




Date: 12.JAN.2015 17:55:59

### CH00-DH3




Date: 12.JAN.2015 18:08:14

### CH00-DH5



Date: 12.JAN.2015 18:09:37


### CH39-DH1



Date: 12.JAN.2015 17:56:10




### CH78-DH1




Date: 12.JAN.2015 17:56:22

### CH78-DH3



Date: 12.JAN.2015 18:08:33

### CH78-DH5




Date: 12.JAN.2015 18:10:01

## **ATTACHMENT G - HOPPING CHANNEL SEPARATION MEASUREMENT**


Test Mode : Hopping on \_1Mbps

Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	1.002	0.423	Complies
2441	1.002	0.427	Complies
2480	1.002	0.425	Complies




Date: 12.JAN.2015 17:45:46

### CH39



Date: 12.JAN.2015 17:46:56


### CH78



Date: 12.JAN.2015 17:23:37


Test Mode : Hopping on \_3Mbps

Frequency (MHz)	Channel Separation (MHz)	2/3 of 20dB Bandwidth (MHz)	Test Result
2402	1.002	0.752	Complies
2441	1.003	0.753	Complies
2480	0.999	0.754	Complies




Date: 12.JAN.2015 18:01:46

### CH39



Date: 12.JAN.2015 18:03:05

### CH78




Date: 12.JAN.2015 18:04:26

## ATTACHMENT H - BANDWIDTH


Test Mode : TX Mode \_1Mbps

Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	0.634	0.808	Complies
2441	0.640	0.816	Complies
2480	0.637	0.816	Complies




Date: 12.JAN.2015 17:17:01

### CH39



Date: 12.JAN.2015 17:18:05

### CH78




Date: 12.JAN.2015 17:18:46

Test Mode : TX Mode \_3Mbps


Frequency (MHz)	20dB Bandwidth (MHz)	99% Occupied BW (MHz)	Test Result
2402	1.128	1.096	Complies
2441	1.129	1.096	Complies
2480	1.131	1.092	Complies

### CH00




Date: 12.JAN.2015 17:51:19

### CH39



Date: 12.JAN.2015 17:53:40

### CH78




Date: 12.JAN.2015 17:55:14

## **ATTACHMENT I - PEAK OUTPUT POWER**

Test Mode : TX Mode \_1Mbps

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watt)	Max. Limit (dBm)	Max. Limit (Watt)	Test Result
2402	2.35	0.0017	30.00	1.0000	Complies
2441	1.82	0.0015	30.00	1.0000	Complies
2480	1.53	0.0014	30.00	1.0000	Complies




Date: 12.JAN.2015 17:17:22



Test Mode : TX Mode \_3Mbps

Frequency (MHz)	Conducted Power (dBm)	Conducted Power (Watt)	Max. Limit (dBm)	Max. Limit (Watt)	Test Result
2402	2.44	0.0018	30.00	1.0000	Complies
2441	1.93	0.0016	30.00	1.0000	Complies
2480	1.68	0.0015	30.00	1.0000	Complies




Date: 12.JAN.2015 17:53:02




**ATTACHMENT J - ANTENNA CONDUCTED SPURIOUS  
EMISSION**

### CH00 (Lower)\_1Mbps




Date: 12.JAN.2015 17:44:08

### CH78 (Upper)\_1Mbps




Date: 12.JAN.2015 17:44:29

### CH00 Hopping on mode (Lower)\_1Mbps




Date: 12.JAN.2015 17:26:04

### CH78 Hopping on mode (Upper)\_1Mbps




Date: 12.JAN.2015 17:26:39

### CH00 (10 Harmonic of the frequency) \_1Mbps



Date: 12.JAN.2015 17:17:15


### CH39 (10 Harmonic of the frequency) \_1Mbps



Date: 12.JAN.2015 17:17:57




### CH00 (Lower) \_3Mbps




Date: 12.JAN.2015 17:50:30

### CH78 (Upper) \_3Mbps




Date: 12.JAN.2015 17:55:01

### CH00 Hopping on mode (Lower)\_3Mbps




Date: 12.JAN.2015 18:06:52

### CH78 Hopping on mode (Upper)\_3Mbps




Date: 12.JAN.2015 18:07:27

### CH00 (10 Harmonic of the frequency) \_3Mbps




Date: 12.JAN.2015 17:51:39

### CH39 (10 Harmonic of the frequency) \_3Mbps



Date: 12.JAN.2015 17:54:29

### CH78 (10 Harmonic of the frequency) \_3Mbps



Date: 12.JAN.2015 17:55:28