



MAXIMUM PERMISSIBLE EXPOSURE REPORT

FOR THE
CELL CONTROL UNIT (FHSS RADIO)

MODEL NUMBERS:
CCU100, CCU100 REPEATER, CCU100R, AND CCU100R REPEATER

DATE OF ISSUE: MARCH 8, 2011

PREPARED FOR:

Itron, Inc.
2111 N Molter Road
Liberty Lake, WA 99019

W.O. No.: 90893

PREPARED BY:

Jeff Gilbert
CKC Laboratories, Inc.
22116 23rd Drive SE, Suite A
Bothell, WA 98021

Date of test: December 6th, 2010

Report No.: 90893-35

**Purpose of Test:**

To demonstrate compliance with United States and Canada RF Exposure requirements for Mobile Equipment (devices used >20cm from the body), where Maximum Permissible Exposure (MPE) Calculations apply.

United States MPE Limits in accordance with 1.1310:*Occupational / Controlled Exposure*

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1	6
300-1500	---	---	f/300	6
1500-100,000	---	---	5	6

General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	---	---	f/1500	30
1500-100,000	---	---	1	30

Note: Limit is calculated based on the mid-band frequency used in the operating frequency range.



Canadian MPE Limits in accordance with RSS-102:

Occupational / Controlled Exposure:

Frequency Range (MHz)	Electric Field (V/M rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Time Averaging (min)
0.003-1	600	4.9	-	6
1-10	600 / f	4.9 / f	-	6
10-30	60	4.9 / f	-	6
30-300	60	0.163	10 [*]	6
300-1500	3.54 $f^{0.5}$	0.0094 $f^{0.5}$	$f / 30$	6
1500-15000	137	0.364	50	6
15000-150000	137	0.364	50	616000 / $f^{1.2}$
150000-300000	0.354 $f^{0.5}$	9.4 x 10 ⁻⁴ $f^{0.5}$	3.33 x 10 ⁻⁴ f	616000 / $f^{1.2}$

General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field (V/M rms)	Magnetic Field (A/m rms)	Power Density (W/m ²)	Time Averaging (min)
0.003-1	280	2.19	-	6
1-10	280 / f	2.19 / f	-	6
10-30	28	2.19 / f	-	6
30-300	28	0.073	2 [*]	6
300-1 500	1.585 $f^{0.5}$	0.0042 $f^{0.5}$	$f / 150$	6
1 500-15 000	61.4	0.163	10	6
15 000-150 000	61.4	0.163	10	616000 / $f^{1.2}$
150 000-300 000	0.158 $f^{0.5}$	4.21 x 10 ⁻⁴ $f^{0.5}$	6.67 x 10 ⁻⁵ f	616000 / $f^{1.2}$

Note: f is frequency in MHz

* Power density limit is applicable at frequencies greater than 100 MHz



Equipment operational details:

Operating Frequency (MHz)	Measured Output Power (dBm)	Maximum Mobile Antenna Gain (dBi)	Maximum EIRP (dBm)
902-928	28.0	5.15	33.15

Measurements based from EMC Test Report: 90893-10D

Device and Antenna Operating Configuration:

Device operating at maximum output power with continuous transmission of modulated data.

Test Procedure:

This equipment is evaluated in accordance with the guidelines set forth in OET Guide 65 & ANSI C95.1 for the US and Health Canada Safety Code 6 & RSS 102 for Canada.

Other Considerations:

None

MPE Calculations:

Limit used:

	Occupational / Controlled Exposure
X	General Population / Uncontrolled Exposure

$$\begin{aligned} \text{MPE Limit (US)} &= 0.610 \text{ (mW/cm}^2\text{)} \\ \text{MPE Limit (Canada)} &= 6.10 \text{ (W/m}^2\text{)} \end{aligned}$$

$$\text{Power Density (mW/cm}^2\text{)} = \frac{\text{EIRP}}{4\pi d^2} \quad \text{Given: EIRP in mW and d in cm}$$

EIRP (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2065.38	20	0.410894	0.610
EIRP (W)	Distance (m)	Power Density (W/m ²)	Limit (W/m ²)
2.06538	0.2	4.108943	6.10



Statement of Compliance:

This device demonstrates compliance under the operating conditions specified in this document. Under normal operating conditions, the antenna is designed to be installed in accordance with the manufacturer's instructions in such a manner to maintain the minimum separation distance. The MPE calculations shown above demonstrate compliance to the provisions of US and Canadian requirements.

As can be seen from the MPE results, this device passes the specified limits at a distance of 20cm at the maximum output power under normal operating conditions.