

# Itron, Inc.

## TEST REPORT FOR

### AMR Transceiver Device For Communicating With Utility Meters Models: IMRD-INT and IMRD-EXT

**Tested to The Following Standards:**

**FCC Part 15 Subpart C Section(s)**

**15.207 & 15.231a  
(PERIODIC OPERATION >70MHZ)**

**Report No.: 105444-5**

**Date of issue: August 31, 2021**



This test report bears the accreditation symbol indicating that the testing performed herein meets the test and reporting requirements of ISO/IEC 17025 under the applicable scope of testing for CKC Laboratories, Inc.

We strive to create long-term, trust based relationships by providing sound, adaptive, customer first testing services. We embrace each of our customers' unique EMC challenges, not as an interruption to set processes, but rather as the reason we are in business.

**Test Certificate # 803.01**

This report contains a total of 80 pages and may be reproduced in full only. Partial reproduction may only be done with the written consent of CKC Laboratories, Inc.

## TABLE OF CONTENTS

Administrative Information .....	3
Test Report Information .....	3
Report Authorization .....	3
Test Facility Information .....	4
Software Versions .....	4
Site Registration & Accreditation Information .....	4
Summary of Results .....	5
Modifications During Testing .....	5
Conditions During Testing .....	5
Equipment Under Test .....	6
General Product Information .....	7
FCC Part 15 Subpart C .....	14
15.231(c) Occupied Bandwidth (20dB BW) .....	14
15.231(b) Field Strength of Fundamental .....	16
15.231(a) Periodic Operation Requirements .....	32
15.231(a)(1) Manual Triggered Deactivation Time .....	32
15.231(b) Radiated Emissions .....	34
15.207 AC Conducted Emissions .....	60
Supplemental Information .....	79
Measurement Uncertainty .....	79
Emissions Test Details .....	79

## ADMINISTRATIVE INFORMATION

### Test Report Information

**REPORT PREPARED FOR:**

Ittron, Inc.  
2111 N. Molter Road  
Liberty Lake WA 99019

Representative: Jay Holcomb  
Customer Reference Number: 238223

**REPORT PREPARED BY:**

Terri Rayle  
CKC Laboratories, Inc.  
5046 Sierra Pines Drive  
Mariposa, CA 95338

Project Number: 105444

**DATE OF EQUIPMENT RECEIPT:**

June 25, 2021


**DATE(S) OF TESTING:**

June 25, 2021, July 6 and 20, 2021

August 20, 2021

### Report Authorization

The test data contained in this report documents the observed testing parameters pertaining to and are relevant for only the equipment provided by the client, tested in the agreed upon operational mode(s) and configuration(s) as identified herein. Compliance assessment remains the client's responsibility. This report may not be used to claim product endorsement by A2LA or any government agencies. This test report has been authorized for release under quality control from CKC Laboratories, Inc.



*Steve Behm*  
Director of Quality Assurance & Engineering Services  
CKC Laboratories, Inc.

## Test Facility Information



Our laboratories are configured to effectively test a wide variety of product types. CKC utilizes first class test equipment, anechoic chambers, data acquisition and information services to create accurate, repeatable and affordable test results.

**TEST LOCATION(S):**  
 CKC Laboratories, Inc.  
 22116 23rd Drive S.E.,  
 Canyon Park, Bothell, WA 98021

## Software Versions

CKC Laboratories Proprietary Software	Version
EMITest Emissions	5.03.19

## Site Registration & Accreditation Information

Location	*NIST CB #	FCC	Canada	Japan
Canyon Park, Bothell, WA	US0103	US1024	3082C	A-0136
Brea, CA	US0103	US1024	3082D	A-0136
Fremont, CA	US0103	US1024	3082B	A-0136
Mariposa, CA	US0103	US1024	3082A	A-0136

\*CKC's list of NIST designated countries can be found at: <https://standards.gov/cabs/designations.html>

## SUMMARY OF RESULTS

### Standard / Specification: FCC Part 15 Subpart C - 15.231a

Test Procedure	Description	Modifications	Results
15.231(c)	Occupied Bandwidth	NA	Pass
15.231(b)	Field Strength of Fundamental	NA	Pass
15.231(a)	Periodic Operation Requirements	NA	Pass
15.231(b)	Field Strength of Spurious Emissions	NA	Pass
15.207	AC Conducted Emissions	NA	Pass

NA = Not Applicable

#### ISO/IEC 17025 Decision Rule

The declaration of pass or fail herein is based upon assessment to the specification(s) listed above, including where applicable, assessment of measurement uncertainties. For performance related tests, equipment was monitored for specified criteria identified in that section of testing.

## Modifications During Testing

This list is a summary of the modifications made to the equipment during testing.

#### Summary of Conditions

No modifications were made during testing.

**Modifications listed above must be incorporated into all production units.**

## Conditions During Testing

This list is a summary of the conditions noted to the equipment during testing.

#### Summary of Conditions

None

## EQUIPMENT UNDER TEST (EUT)

During testing, numerous configurations may have been utilized. The configurations listed below support compliance to the standard(s) listed in the Summary of Results section.

### Configuration 1

*Equipment Tested:*

Device	Manufacturer	Model #	S/N
AMR transceiver device for communicating with utility meters	Itron, Inc.	IMRD-EXT	105444-ext

*Support Equipment:*

Device	Manufacturer	Model #	S/N
Toughpad	Panasonic	FZ-G1	NA
DC Power Supply	Rigol	DP711	NA

### Configuration 3

*Equipment Tested:*

Device	Manufacturer	Model #	S/N
AMR transceiver device for communicating with utility meters	Itron, Inc.	IMRD-EXT	105444-ext

*Support Equipment:*

Device	Manufacturer	Model #	S/N
Toughpad	Panasonic	FZ-G1	NA
DC Power Supply	Rigol	DP711	NA
Attached Antenna	L-comm	3dBi Rubber Duck	NA
TNC to RMA Adapter	Molex	73386-1250	NA

### Configuration 5

*Equipment Tested:*

Device	Manufacturer	Model #	S/N
AMR transceiver device for communicating with utility meters	Itron, Inc.	IMRD-EXT	105444-ext

*Support Equipment:*

Device	Manufacturer	Model #	S/N
Toughpad	Panasonic	FZ-G1	NA
DC Power Supply	Rigol	DP711	NA
Ground Plane	Itron, Inc.	4ft	NA
Vehicle Antenna	PCTEL	5dBi Vehicle Mount	NA

## Configuration 7

### Equipment Tested:

Device	Manufacturer	Model #	S/N
AMR transceiver device for communicating with utility meters	Itron, Inc.	IMRD-INT	105444-int rad

### Support Equipment:

Device	Manufacturer	Model #	S/N
Toughpad	Panasonic	FZ-G1	NA
DC Power Supply	Rigol	DP711	NA

## Configuration 9

### Equipment Tested9

Device	Manufacturer	Model #	S/N
AMR transceiver device for communicating with utility meters	Itron, Inc.	IMRD-INT	105444-int rad

### Support Equipment:

Device	Manufacturer	Model #	S/N
AC-USB Adapter	ELJINTEK. INC	GUSB05	NA

## General Product Information:

Product Information	Manufacturer-Provided Details
Equipment Type:	Stand-Alone Equipment
Operating Frequency Range:	952-953MHz  Note: At time of test, 952MHz is the frequency available for test. The manufacturer declares testing on this frequency is representative of worst case.
Modulation Type(s):	OOK
Maximum Duty Cycle:	Assume 100% as worst case
Antenna Type(s) and Gain:	Internal PIFA 2.0 dBi External Omni Vehicle 5 dBi External Omni Attached 3dBi
Antenna Connection Type:	Integral and External variant
Operational Trigger Type:	Manually Activated Trigger
Nominal Input Voltage:	120VAC 60Hz to AC Adapter on Internal Unit 13.8V DC on External Unit
Firmware / Software used for Test:	DSP Version 7.00.00.26 / FPGA Version 3.08 / MC3 Test v 4.0.3.5  900BcrCycles.exe (1/27/2010 last modified) and DSP Version 7.00.00.34 for 5 second turn off test

**EUT Photo(s)**



**Support Equipment Photo(s)**



AC-USB Adapter



Attached Antenna with adapter



DC Power Supply




External Antenna + Ground Plane




Tablet

## Block Diagram of Test Setup(s)


### Test Setup Block Diagram




### Test Setup Block Diagram




### Test Setup Block Diagram



### Test Setup Block Diagram



### Test Setup Block Diagram



## FCC Part 15 Subpart C

### 15.231(c) Occupied Bandwidth (20dB BW)

#### Test Setup/Conditions

Test Location:	Bothell Lab Bench	Test Engineer:	M. Atkinson
Test Method:	ANSI C63.10 (2013)	Test Date(s):	7/6/2021
Configuration:	1		
Test Setup:	EUT directly connected to spectrum analyzer through appropriate cables and attenuators. EUT is continuously transmitting with modulation.		

#### Environmental Conditions

Temperature (°C)	24	Relative Humidity (%):	50
------------------	----	------------------------	----

#### Test Equipment


Asset#	Description	Manufacturer	Model	Cal Date	Cal Due
02871	Spectrum Analyzer	Agilent	E4440A	3/12/2020	3/12/2022
P07670	Attenuator	Paternack	PE7389-20	8/20/2020	8/20/2022
P06454	Cable	Andrews	Heliax	1/20/2020	1/20/2022

#### Test Data Summary

$$Limit = \begin{cases} 0.25\% f_c & | 70 MHz < f_c < 900 MHz \\ 0.5\% f_c & | f_c > 900 MHz \end{cases}$$

Frequency (MHz)	Antenna Port	Modulation	Measured (MHz)	Limit (MHz)	Results
952	1	OOK	1.609	≤4.76	Pass

### Plot(s)



### Test Setup Photo(s)



## 15.231(b) Field Strength of Fundamental

### Test Equipment not on data sheets

Asset#	Description	Manufacturer	Model	Cal Date	Cal Due
P06996	Multimeter	Fluke	87-5	6/16/2020	6/16/2022
P07527	Variac	Simpson	NA	1/27/2021	1/27/2023
02272	Power Source, AC	California Instruments	1251WP	1/18/2021	1/18/2023
P07355	Power Supply	YescomUSA	DCP305D	3/3/2020	3/3/2022
P06123	Attenuator	Aeroflex	18N-6	4/2/2021	4/2/2023

### Test Data Summary - Voltage Variations

Frequency (MHz)	Modulation / Ant Port	V <sub>Minimum</sub> (dBuV/m@3m)	V <sub>Nominal</sub> (dBuV/m@3m)	V <sub>Maximum</sub> (dBuV/m@3m)	Max Deviation from V <sub>Nominal</sub> (dB)
952	External Attached	77.4	77.6	77.6	0.2
952	External Vehicle	76.7	76.8	76.8	0.1
952	Internal	81.1	81.2	81.2	0.1

Test performed using operational mode with the highest output power, representing worst case.

#### Parameter Definitions (Internal Antenna Version):

Measurements performed at input voltage V<sub>Nominal</sub> ± 15%.

Parameter	Value
V <sub>Nominal</sub> :	120 VAC
V <sub>Minimum</sub> :	102.00 VAC
V <sub>Maximum</sub> :	138.00 VAC

#### Parameter Definitions (External Antenna Version):

Measurements performed at input voltage V<sub>Nominal</sub> ± 15%.


Parameter	Value
V <sub>Nominal</sub> :	13.8VDC
V <sub>Minimum</sub> :	11.7VDC
V <sub>Maximum</sub> :	15.9VDC

### Test Data Summary – Radiated Field Strength Measurement


Frequency (MHz)	Modulation	Ant. Type	Measured (dBuV/m @ 3m)	Limit (dBuV/m @ 3m)	Results
952	OOK	External Attached	77.6	≤81.9	Pass
952	OOK	External Vehicle	76.8	≤81.9	Pass
952	OOK	Internal	81.2	≤81.9	Pass

Note: Peaks values recorded as worst case, see data sheets for QP measurements.


## Plot(s)



Configuration 3



Configuration 5



Configuration 7

## Test Setup / Conditions / Data

Test Location: CKC Laboratories • 22116 23rd Drive SE, Suite A • Bothell, WA 98021 • 1-800-500-4EMC (4362)  
 Customer: **Itron, Inc.**  
 Specification: **15.231(b) Fundamental Field Strength**  
 Work Order #: **105444** Date: 8/20/2021  
 Test Type: **Maximized Emissions** Time: 09:06:26  
 Tested By: Michael Atkinson Sequence#: 50  
 Software: EMITest 5.03.19

***Equipment Tested:***

Device	Manufacturer	Model #	S/N
Configuration 3			

***Support Equipment:***

Device	Manufacturer	Model #	S/N
Configuration 3			

***Test Conditions / Notes:***

Setup: EUT is on foam table. EUT is connected to support tablet. EUT is transmitting using test software on support tablet to control EUT. XYZ axes investigated, horizontal and vertical antenna polarities investigated, worst case reported.


EUT with external attached antenna.

Test Location: Bothell Lab C3

Temperature (°C): 22

Relative Humidity (%): 45

Test Method: ANSI C63.10 (2013)

Itron, Inc. WO#: 105444 Sequence#: 50 Date: 8/20/2021  
 15.231(b) Fundamental Field Strength Test Distance: 3 Meters H+V

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP06540	Cable	Heliax	8/23/2019	8/23/2021
T2	ANP05305	Cable	ETSI-50T	9/6/2019	9/6/2021
T3	ANP05360	Cable	RG214	2/3/2020	2/3/2022
T4	AN02307	Preamp	8447D	1/10/2020	1/10/2022
	AN02871	Spectrum Analyzer	E4440A	3/12/2020	3/12/2022
T5	AN03628	Biconilog Antenna	3142E	6/3/2021	6/3/2023

**Measurement Data:** Reading listed by margin. Test Distance: 3 Meters

#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5				Table	dB $\mu$ V/m	dB $\mu$ V/m		
			MHz	dB $\mu$ V	dB	dB	dB				Ant
1	951.250M	68.8	+0.4	+1.5	+2.2	-27.2	+0.0	76.8	81.9	-5.1	H+V
	QP		+31.1								
^	951.250M	69.6	+0.4	+1.5	+2.2	-27.2	+0.0	77.6	81.9	-4.3	H+V
			+31.1								
3	951.985M	67.8	+0.4	+1.5	+2.2	-27.2	+0.0	75.8	81.9	-6.1	H+V
	QP		+31.1								



Test Location: CKC Laboratories • 22116 23rd Drive SE, Suite A • Bothell, WA 98021 • 1-800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.231(b) Fundamental Field Strength**  
Work Order #: **105444** Date: 8/20/2021  
Test Type: **Maximized Emissions** Time: 09:12:45  
Tested By: Michael Atkinson Sequence#: 51  
Software: EMITest 5.03.19

***Equipment Tested:***

Device	Manufacturer	Model #	S/N
Configuration 5			

***Support Equipment:***


Device	Manufacturer	Model #	S/N
Configuration 5			

***Test Conditions / Notes:***

Setup: EUT is on foam table. EUT is connected to support tablet. EUT is transmitting using test software on support tablet to control EUT. XYZ axes investigated, horizontal and vertical antenna polarities investigated, worst case reported.

EUT with external vehicle antenna

Test Location: Bothell Lab C3  
Temperature (°C): 22  
Relative Humidity (%): 45  
Test Method: ANSI C63.10 (2013)

Itron, Inc. WO#: 105444 Sequence#: 51 Date: 8/20/2021  
 15.231(b) Fundamental Field Strength Test Distance: 3 Meters H+V

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP06540	Cable	Heliax	8/23/2019	8/23/2021
T2	ANP05305	Cable	ETSI-50T	9/6/2019	9/6/2021
T3	ANP05360	Cable	RG214	2/3/2020	2/3/2022
T4	AN02307	Preamp	8447D	1/10/2020	1/10/2022
	AN02871	Spectrum Analyzer	E4440A	3/12/2020	3/12/2022
T5	AN03628	Biconilog Antenna	3142E	6/3/2021	6/3/2023

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5				Table	dB $\mu$ V/m	dB $\mu$ V/m		
			MHz	dB $\mu$ V	dB	dB	dB				Ant
1	951.250M	67.9	+0.4	+1.5	+2.2	-27.2	+0.0	75.9	81.9	-6.0	H+V
	QP		+31.1								
^	951.250M	68.8	+0.4	+1.5	+2.2	-27.2	+0.0	76.8	81.9	-5.1	H+V
			+31.1								
3	951.969M	67.3	+0.4	+1.5	+2.2	-27.2	+0.0	75.3	81.9	-6.6	H+V
	QP		+31.1								



Test Location: CKC Laboratories • 22116 23rd Drive SE, Suite A • Bothell, WA 98021 • 1-800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.231(b) Fundamental Field Strength**  
Work Order #: **105444** Date: 8/20/2021  
Test Type: **Maximized Emissions** Time: 09:18:44  
Tested By: Michael Atkinson Sequence#: 53  
Software: EMITest 5.03.19

***Equipment Tested:***

Device	Manufacturer	Model #	S/N
Configuration 7			

***Support Equipment:***


Device	Manufacturer	Model #	S/N
Configuration 7			

***Test Conditions / Notes:***

Setup: EUT is on foam table. EUT is connected to support tablet. EUT is transmitting using test software on support tablet to control EUT. XYZ axes investigated, horizontal and vertical antenna polarities investigated, worst case reported.

EUT with internal antenna.

Test Location: Bothell Lab C3  
Temperature (°C): 22  
Relative Humidity (%): 45  
Test Method: ANSI C63.10 (2013)

Itron, Inc. WO#: 105444 Sequence#: 53 Date: 8/20/2021  
 15.231(b) Fundamental Field Strength Test Distance: 3 Meters H+V

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP06540	Cable	Heliax	8/23/2019	8/23/2021
T2	ANP05305	Cable	ETSI-50T	9/6/2019	9/6/2021
T3	ANP05360	Cable	RG214	2/3/2020	2/3/2022
T4	AN02307	Preamp	8447D	1/10/2020	1/10/2022
	AN02871	Spectrum Analyzer	E4440A	3/12/2020	3/12/2022
T5	AN03628	Biconilog Antenna	3142E	6/3/2021	6/3/2023

**Measurement Data:**


Reading listed by margin.

Test Distance: 3 Meters

#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5				Table	dB $\mu$ V/m	dB $\mu$ V/m		
			MHz	dB $\mu$ V	dB	dB	dB				Ant
1	951.389M	QP	72.4	+0.4	+1.5	+2.2	-27.2	+0.0	80.4	81.9	-1.5
				+31.1							H+V
^	951.389M		73.2	+0.4	+1.5	+2.2	-27.2	+0.0	81.2	81.9	-0.7
				+31.1							H+V
3	951.990M	QP	72.2	+0.4	+1.5	+2.2	-27.2	+0.0	80.2	81.9	-1.7
				+31.1							H+V

**Test Setup Photo(s)**

**Configuration 3**



X Axis, View #1



X Axis, View #2



Y Axis



Z Axis




Below 1GHz

**Configuration 5**



X Axis



Y Axis




Z Axis



Below 1GHz

**Configuration 7**



X Axis



Y Axis



Z Axis



Below 1GHz

## 15.225(a) Periodic Operation Requirements

Test Setup/Conditions			
Test Location:	Bothell Lab Bench	Test Engineer:	M. Atkinson
Test Method:	ANSI C63.10 (2013)	Test Date(s):	7/20/2021
Configuration:	1		
Test Setup:	EUT directly connected to spectrum analyzer through appropriate cables and attenuators. EUT is setup to transmit with manual activation from test software.		
Declarations:	15.231(a)(2): The manufacturer declares the EUT cannot be activated automatically. 15.231(a)(3): The manufacturer declares the EUT has no polling or supervision transmission mode. 15.231(a)(4): The manufacturer declares the EUT has no alarm condition transmission mode. 15.231(a)(5): The manufacturer declares the EUT has no setup transmission duration.		


Environmental Conditions			
Temperature (°C)	22	Relative Humidity (%):	50

Test Equipment					
Asset#	Description	Manufacturer	Model	Cal Date	Cal Due
02871	Spectrum Analyzer	Agilent	E4440A	3/12/2020	3/12/2022
P07670	Attenuator	Pasternack	PE7389-20	8/20/2020	8/20/2022
P06454	Cable	Andrews	Heliax	1/20/2020	1/20/2022

## 15.231(a)(1) Manual Triggered Deactivation Time

Test Data Summary					
Frequency (MHz)	Antenna Port	Modulation	Measured (s)	Limit (s)	Results
952	1	OOK	4.994	≤5	Pass

### Plot(s)



5 Second

### Test Setup Photo(s)



## 15.231(b) Radiated Emissions

Note: Per ANSI C63.10 (2013) 100kHz RBW was used for restricted band edge peak data per 6.10.5.2 (e) (6) (iii).

### Test Setup / Conditions / Data

Test Location: CKC Laboratories • 22116 23rd Drive SE, Suite A • Bothell, WA 98021 • 1-800-500-4EMC (4362)  
 Customer: **Itron, Inc.**  
 Specification: **15.231(b) Spurious Field Strength (>470 MHz Transmitter) (Band Edge)**  
 Work Order #: **105444** Date: 7/6/2021  
 Test Type: **Maximized Emissions** Time: 20:00:45  
 Tested By: Michael Atkinson Sequence#: 14  
 Software: EMITest 5.03.19

#### *Equipment Tested:*


Device	Manufacturer	Model #	S/N
Configuration 3			

#### *Support Equipment:*

Device	Manufacturer	Model #	S/N
Configuration 3			

#### *Test Conditions / Notes:*

Frequency: 9kHz to 10GHz
Setup: EUT is on foam table. EUT is connected to support tablet. EUT is transmitting using test software on support tablet to control EUT. XYZ axes investigated, horizontal and vertical antenna polarities investigated above 30MHz, 3 orthogonal axes investigated below 30MHz, worst case reported.
EUT with external attached antenna.
Temperature (°C): 22-23
Relative Humidity (%): 43-50
Test Location: Bothell Lab C3
Test Method: ANSI C63.10 (2013)

Itron, Inc. W/O#: 105444 Sequence#: 14 Date: 7/6/2021  
 15.231(b) Spurious Field Strength (>470 MHz Transmitter) (Band Edge) Test Distance: 3 Meters Various

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	AN02673	Spectrum Analyzer	E4446A	2/3/2021	2/3/2023
T2	ANP06540	Cable	Heliax	8/23/2019	8/23/2021
T3	ANP05305	Cable	ETSI-50T	9/6/2019	9/6/2021
T4	ANP05360	Cable	RG214	2/3/2020	2/3/2022
T5	AN03628	Biconilog Antenna	3142E	6/3/2021	6/3/2023
T6	AN02307	Preamp	8447D	1/10/2020	1/10/2022
T7	AN02374ANSI	Horn Antenna	RGA-60	5/25/2021	5/25/2023
T8	ANP06515	Cable	Heliax	7/1/2020	7/1/2022
T9	AN03540	Preamp	83017A	5/14/2021	5/14/2023
T10	ANP07505	Cable	CLU40-KMKM-02.00F	1/26/2021	1/26/2023
T11	AN00052	Loop Antenna	6502	5/4/2020	5/4/2022

<b>Measurement Data:</b>			Reading listed by margin.				Test Distance: 3 Meters				
#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5	T6	T7	T8	Table	dB $\mu$ V/m	dB $\mu$ V/m	dB	Ant
			MHz	dB $\mu$ V	dB	dB	dB				
1	4998.067M	46.1	+0.0	+0.9	+0.0	+0.0	+0.0	50.8	54.0	-3.2	Vert
			+0.0	+0.0	+0.0	+3.8					
			+0.0	+0.0	+0.0						
2	7615.860M	39.9	+0.0	+1.6	+0.0	+0.0	+0.0	49.9	54.0	-4.1	Horiz
			+0.0	+0.0	+37.4	+5.4					
			-34.9	+0.5	+0.0						
3	4976.000M	44.2	+0.0	+0.9	+0.0	+0.0	+0.0	49.8	54.0	-4.2	Horiz
			+0.0	+0.0	+33.8	+3.8					
			-33.4	+0.5	+0.0						
4	9519.840M	41.2	+0.0	+1.4	+0.0	+0.0	+0.0	53.2	61.9	-8.7	Vert
			+0.0	+0.0	+38.5	+5.5					
			-34.1	+0.7	+0.0						
5	282.200M	43.7	+0.0	+0.2	+0.8	+1.0	+0.0	36.8	46.0	-9.2	Horiz
			+18.1	-27.0	+0.0	+0.0					
			+0.0	+0.0	+0.0						
6	255.000M	42.5	+0.0	+0.2	+0.8	+1.0	+0.0	35.9	46.0	-10.1	Horiz
			+18.4	-27.0	+0.0	+0.0					
			+0.0	+0.0	+0.0						
7	3806.620M	39.8	+0.0	+0.9	+0.0	+0.0	+0.0	43.1	54.0	-10.9	Vert
			+0.0	+0.0	+32.4	+3.5					
			-33.8	+0.3	+0.0						
8	73.489M	42.5	+0.0	+0.1	+0.4	+0.5	+0.0	28.6	40.0	-11.4	Vert
QP			+12.9	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0						
^	73.507M	47.4	+0.0	+0.1	+0.4	+0.5	+0.0	33.4	40.0	-6.6	Vert
			+12.8	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0						
10	3808.160M	38.6	+0.0	+0.9	+0.0	+0.0	+0.0	41.9	54.0	-12.1	Vert
			+0.0	+0.0	+32.4	+3.5					
			-33.8	+0.3	+0.0						
11	1084.000M	51.5	+0.0	+0.4	+0.0	+0.0	+0.0	41.9	54.0	-12.1	Vert
			+0.0	+0.0	+24.5	+1.8					
			-36.6	+0.3	+0.0						
12	252.100M	39.6	+0.0	+0.2	+0.8	+1.0	+0.0	32.8	46.0	-13.2	Vert
			+18.2	-27.0	+0.0	+0.0					
			+0.0	+0.0	+0.0						
13	1050.000M	50.2	+0.0	+0.4	+0.0	+0.0	+0.0	40.1	54.0	-13.9	Horiz
			+0.0	+0.0	+24.3	+1.7					
			-36.8	+0.3	+0.0						
14	1000.000M	49.9	+0.0	+0.4	+0.0	+0.0	+0.0	39.6	54.0	-14.4	Horiz
			+0.0	+0.0	+24.3	+1.7					
			-37.0	+0.3	+0.0						

15	7615.600M	28.5	+0.0	+1.6	+0.0	+0.0	+0.0	38.5	54.0	-15.5	Vert
	Ave		+0.0	+0.0	+37.4	+5.4					
			-34.9	+0.5	+0.0						
^	7615.600M	40.6	+0.0	+1.6	+0.0	+0.0	+0.0	50.6	54.0	-3.4	Vert
			+0.0	+0.0	+37.4	+5.4					
			-34.9	+0.5	+0.0						
17	6664.570M	37.9	+0.0	+1.2	+0.0	+0.0	+0.0	46.0	61.9	-15.9	Horiz
			+0.0	+0.0	+35.4	+5.2					
			-34.1	+0.4	+0.0						
18	999.000M	30.8	+0.0	+0.4	+1.5	+2.3	+0.0	38.0	54.0	-16.0	Horiz
			+30.0	-27.0	+0.0	+0.0					
			+0.0	+0.0	+0.0						
19	614.000M	27.4	+0.0	+0.3	+1.2	+1.7	+0.0	29.6	46.0	-16.4	Horiz
			+27.2	-28.2	+0.0	+0.0					
			+0.0	+0.0	+0.0						
20	112.400M	38.8	+0.0	+0.1	+0.5	+0.6	+0.0	26.3	43.5	-17.2	Horiz
			+14.0	-27.7	+0.0	+0.0					
			+0.0	+0.0	+0.0						
21	5711.480M	37.8	+0.0	+1.0	+0.0	+0.0	+0.0	44.3	61.9	-17.6	Horiz
			+0.0	+0.0	+34.3	+4.5					
			-33.6	+0.3	+0.0						
22	3496.000M	41.7	+0.0	+0.8	+0.0	+0.0	+0.0	43.5	61.9	-18.4	Vert
			+0.0	+0.0	+31.2	+3.3					
			-33.8	+0.3	+0.0						
23	1764.000M	47.8	+0.0	+0.5	+0.0	+0.0	+0.0	42.7	61.9	-19.2	Vert
			+0.0	+0.0	+26.6	+2.3					
			-34.8	+0.3	+0.0						
24	960.000M	26.8	+0.0	+0.4	+1.5	+2.2	+0.0	34.5	54.0	-19.5	Horiz
			+30.7	-27.1	+0.0	+0.0					
			+0.0	+0.0	+0.0						
25	3500.000M	40.4	+0.0	+0.8	+0.0	+0.0	+0.0	42.3	61.9	-19.6	Horiz
			+0.0	+0.0	+31.3	+3.3					
			-33.8	+0.3	+0.0						
26	4464.000M	38.6	+0.0	+0.9	+0.0	+0.0	+0.0	42.3	61.9	-19.6	Horiz
			+0.0	+0.0	+32.3	+3.7					
			-33.5	+0.3	+0.0						
27	1904.000M	44.6	+0.0	+0.6	+0.0	+0.0	+0.0	41.3	61.9	-20.6	Vert
			+0.0	+0.0	+28.0	+2.4					
			-34.6	+0.3	+0.0						
28	4988.067M	26.0	+0.0	+0.9	+0.0	+0.0	+0.0	31.6	54.0	-22.4	Vert
	Ave		+0.0	+0.0	+33.8	+3.8					
			-33.4	+0.5	+0.0						
29	1904.360M	42.0	+0.0	+0.6	+0.0	+0.0	+0.0	38.7	61.9	-23.2	Horiz
			+0.0	+0.0	+28.0	+2.4					
			-34.6	+0.3	+0.0						
30	892.300M	32.0	+0.0	+0.3	+1.4	+2.1	+0.0	37.6	61.9	-24.3	Vert
			+29.2	-27.4	+0.0	+0.0					
			+0.0	+0.0	+0.0						
31	201.700M	46.6	+0.0	+0.2	+0.7	+0.9	+0.0	37.3	61.9	-24.6	Horiz
			+16.1	-27.2	+0.0	+0.0					
			+0.0	+0.0	+0.0						

32	9520.358M	24.9	+0.0	+1.4	+0.0	+0.0	+0.0	36.9	61.9	-25.0	Vert
	Ave		+0.0	+0.0	+38.5	+5.5					
			-34.1	+0.7	+0.0						
33	75.600M	49.8	+0.0	+0.1	+0.4	+0.5	+0.0	35.8	61.9	-26.1	Vert
			+12.8	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0						
34	879.700M	29.8	+0.0	+0.3	+1.4	+2.1	+0.0	35.0	61.9	-26.9	Horiz
			+28.8	-27.4	+0.0	+0.0					
			+0.0	+0.0	+0.0						
35	203.600M	43.3	+0.0	+0.2	+0.7	+0.9	+0.0	34.2	61.9	-27.7	Vert
			+16.3	-27.2	+0.0	+0.0					
			+0.0	+0.0	+0.0						
36	122.200M	46.1	+0.0	+0.1	+0.5	+0.7	+0.0	32.9	61.9	-29.0	Vert
			+13.1	-27.6	+0.0	+0.0					
			+0.0	+0.0	+0.0						
37	148.300M	43.7	+0.0	+0.2	+0.6	+0.7	+0.0	32.3	61.9	-29.6	Vert
			+14.6	-27.5	+0.0	+0.0					
			+0.0	+0.0	+0.0						
38	431.600M	33.5	+0.0	+0.2	+1.0	+1.4	+0.0	31.1	61.9	-30.8	Vert
			+22.8	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0						
39	144.500M	43.2	+0.0	+0.1	+0.5	+0.7	+0.0	31.0	61.9	-30.9	Horiz
			+14.0	-27.5	+0.0	+0.0					
			+0.0	+0.0	+0.0						
40	395.700M	32.2	+0.0	+0.2	+1.0	+1.3	+0.0	30.6	61.9	-31.3	Vert
			+23.5	-27.6	+0.0	+0.0					
			+0.0	+0.0	+0.0						
41	480.100M	31.3	+0.0	+0.3	+1.1	+1.4	+0.0	30.0	61.9	-31.9	Vert
			+23.9	-28.0	+0.0	+0.0					
			+0.0	+0.0	+0.0						
42	76.600M	39.1	+0.0	+0.1	+0.4	+0.5	+0.0	25.0	61.9	-36.9	Horiz
			+12.7	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0						
43	48.400M	38.9	+0.0	+0.1	+0.4	+0.4	+0.0	24.6	61.9	-37.3	Vert
			+12.7	-27.9	+0.0	+0.0					
			+0.0	+0.0	+0.0						
44	61.000M	33.5	+0.0	+0.1	+0.4	+0.5	+0.0	19.3	61.9	-42.6	Horiz
			+12.6	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0						
45	48.400M	31.9	+0.0	+0.1	+0.4	+0.4	+0.0	17.6	61.9	-44.3	Horiz
			+12.7	-27.9	+0.0	+0.0					
			+0.0	+0.0	+0.0						
46	1.958M	27.7	+0.0	+0.0	+0.0	+0.0	-40.0	-2.7	61.9	-64.6	Perp
			+0.0	+0.0	+0.0	+0.1					
			+0.0	+0.0	+9.5						
47	28.650M	25.0	+0.0	+0.1	+0.0	+0.0	-40.0	-9.8	61.9	-71.7	Perp
			+0.0	+0.0	+0.0	+0.3					
			+0.0	+0.0	+4.8						
48	19.863M	22.6	+0.0	+0.1	+0.0	+0.0	-40.0	-9.8	61.9	-71.7	Perp
			+0.0	+0.0	+0.0	+0.2					
			+0.0	+0.0	+7.3						



Test Location: CKC Laboratories • 22116 23rd Drive SE, Suite A • Bothell, WA 98021 • 1-800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.231(b) Spurious Field Strength (>470 MHz Transmitter) (Band Edge)**  
Work Order #: **105444** Date: 7/6/2021  
Test Type: **Maximized Emissions** Time: 19:45:43  
Tested By: Michael Atkinson Sequence#: 13  
Software: EMITest 5.03.19

***Equipment Tested:***

Device	Manufacturer	Model #	S/N
Configuration 5			

***Support Equipment:***

Device	Manufacturer	Model #	S/N
Configuration 5			

***Test Conditions / Notes:***

Frequency: 9kHz to 10GHz

Setup: EUT is on foam table. EUT is connected to support tablet. EUT is transmitting using test software on support tablet to control EUT. XYZ axes investigated, horizontal and vertical antenna polarities investigated above 30MHz, 3 orthogonal axes investigated below 30MHz, worst case reported.


EUT with external vehicle antenna.

Temperature (°C): 22-23

Relative Humidity (%): 43-50

Test Location: Bothell Lab C3

Test Method: ANSI C63.10 (2013)

Itron, Inc. WO#: 105444 Sequence#: 13 Date: 7/6/2021  
 15.231(b) Spurious Field Strength (>470 MHz Transmitter) (Band Edge) Test Distance: 3 Meters Various

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	AN02673	Spectrum Analyzer	E4446A	2/3/2021	2/3/2023
T2	ANP06540	Cable	Heliax	8/23/2019	8/23/2021
T3	ANP05305	Cable	ETSI-50T	9/6/2019	9/6/2021
T4	ANP05360	Cable	RG214	2/3/2020	2/3/2022
T5	AN03628	Biconilog Antenna	3142E	6/3/2021	6/3/2023
T6	AN02307	Preamp	8447D	1/10/2020	1/10/2022
T7	AN02374ANSI	Horn Antenna	RGA-60	5/25/2021	5/25/2023
T8	AN03540	Preamp	83017A	5/14/2021	5/14/2023
T9	ANP06515	Cable	Heliax	7/1/2020	7/1/2022
T10	ANP07505	Cable	CLU40-KMKM-02.00F	1/26/2021	1/26/2023
T11	AN00052	Loop Antenna	6502	5/4/2020	5/4/2022

<b>Measurement Data:</b>			Reading listed by margin.				Test Distance: 3 Meters				
#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5	T6	T7	T8	Table	dB $\mu$ V/m	dB $\mu$ V/m	dB	Ant
			MHz	dB $\mu$ V	dB	dB	dB				
1	74.600M	48.3	+0.0	+0.1	+0.4	+0.5	+0.0	34.3	40.0	-5.7	Horiz
	QP		+12.8	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
^	74.600M	48.5	+0.0	+0.1	+0.4	+0.5	+0.0	34.5	40.0	-5.5	Horiz
			+12.8	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
3	73.419M	47.9	+0.0	+0.1	+0.4	+0.5	+0.0	34.0	40.0	-6.0	Horiz
	QP		+12.9	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
^	73.419M	48.0	+0.0	+0.1	+0.4	+0.5	+0.0	34.1	40.0	-5.9	Horiz
			+12.9	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
5	4976.000M	41.0	+0.0	+0.9	+0.0	+0.0	+0.0	46.6	54.0	-7.4	Horiz
			+0.0	+0.0	+33.8	-33.4					
			+3.8	+0.5	+0.0	+0.0					
6	131.800M	45.1	+0.0	+0.1	+0.5	+0.7	+0.0	32.5	43.5	-11.0	Vert
			+13.7	-27.6	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
7	1000.000M	52.6	+0.0	+0.4	+0.0	+0.0	+0.0	42.3	54.0	-11.7	Vert
			+0.0	+0.0	+24.3	-37.0					
			+1.7	+0.3	+0.0	+0.0					
8	3807.590M	38.8	+0.0	+0.9	+0.0	+0.0	+0.0	42.1	54.0	-11.9	Vert
			+0.0	+0.0	+32.4	-33.8					
			+3.5	+0.3	+0.0	+0.0					
9	1050.000M	51.9	+0.0	+0.4	+0.0	+0.0	+0.0	41.8	54.0	-12.2	Vert
			+0.0	+0.0	+24.3	-36.8					
			+1.7	+0.3	+0.0	+0.0					
10	1660.000M	46.3	+0.0	+0.5	+0.0	+0.0	+0.0	40.2	54.0	-13.8	Vert
			+0.0	+0.0	+25.8	-34.9					
			+2.2	+0.3	+0.0	+0.0					
11	2855.690M	40.0	+0.0	+0.7	+0.0	+0.0	+0.0	39.4	54.0	-14.6	Vert
			+0.0	+0.0	+29.5	-34.1					
			+3.0	+0.3	+0.0	+0.0					
12	614.000M	27.5	+0.0	+0.3	+1.2	+1.7	+0.0	29.7	46.0	-16.3	Vert
			+27.2	-28.2	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
13	5714.390M	37.6	+0.0	+1.0	+0.0	+0.0	+0.0	44.1	61.9	-17.8	Vert
			+0.0	+0.0	+34.3	-33.6					
			+4.5	+0.3	+0.0	+0.0					
14	1903.570M	45.6	+0.0	+0.6	+0.0	+0.0	+0.0	42.3	61.9	-19.6	Vert
			+0.0	+0.0	+28.0	-34.6					
			+2.4	+0.3	+0.0	+0.0					
15	960.000M	26.1	+0.0	+0.4	+1.5	+2.2	+0.0	33.8	54.0	-20.2	Vert
			+30.7	-27.1	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					

16	1794.000M	45.8	+0.0	+0.5	+0.0	+0.0	+0.0	41.3	61.9	-20.6	Horiz
			+0.0	+0.0	+27.1	-34.7					
			+2.3	+0.3	+0.0						
17	4987.942M	27.6	+0.0	+0.9	+0.0	+0.0	+0.0	33.2	54.0	-20.8	Vert
	Ave		+0.0	+0.0	+33.8	-33.4					
			+3.8	+0.5	+0.0						
^	4987.942M	47.0	+0.0	+0.9	+0.0	+0.0	+0.0	51.7	54.0	-2.3	Vert
			+0.0	+0.0	+0.0	+0.0					
19	75.600M	53.2	+0.0	+0.1	+0.4	+0.5	+0.0	39.2	61.9	-22.7	Vert
			+12.8	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0						
20	919.500M	32.1	+0.0	+0.4	+1.5	+2.1	+0.0	38.8	61.9	-23.1	Horiz
			+30.0	-27.3	+0.0	+0.0					
			+0.0	+0.0	+0.0						
21	190.000M	44.4	+0.0	+0.2	+0.7	+0.8	+0.0	34.1	61.9	-27.8	Vert
			+15.3	-27.3	+0.0	+0.0					
			+0.0	+0.0	+0.0						
22	223.000M	41.8	+0.0	+0.2	+0.7	+0.9	+0.0	33.3	61.9	-28.6	Horiz
			+16.8	-27.1	+0.0	+0.0					
			+0.0	+0.0	+0.0						
23	72.700M	46.5	+0.0	+0.1	+0.4	+0.5	+0.0	32.6	61.9	-29.3	Vert
			+12.9	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0						
24	148.300M	43.8	+0.0	+0.2	+0.6	+0.7	+0.0	32.4	61.9	-29.5	Horiz
			+14.6	-27.5	+0.0	+0.0					
			+0.0	+0.0	+0.0						
25	68.800M	43.2	+0.0	+0.1	+0.4	+0.5	+0.0	29.3	61.9	-32.6	Vert
			+12.9	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0						
26	94.000M	42.3	+0.0	+0.1	+0.5	+0.6	+0.0	28.9	61.9	-33.0	Vert
			+13.1	-27.7	+0.0	+0.0					
			+0.0	+0.0	+0.0						
27	103.700M	41.3	+0.0	+0.1	+0.5	+0.6	+0.0	28.9	61.9	-33.0	Vert
			+14.1	-27.7	+0.0	+0.0					
			+0.0	+0.0	+0.0						
28	431.600M	30.8	+0.0	+0.2	+1.0	+1.4	+0.0	28.4	61.9	-33.5	Vert
			+22.8	-27.8	+0.0	+0.0					
			+0.0	+0.0	+0.0						
29	1.928M	27.7	+0.0	+0.0	+0.0	+0.0	-40.0	-2.7	61.9	-64.6	Para
			+0.0	+0.0	+0.0	+0.0					
			+0.1	+0.0	+9.5						
30	19.743M	22.6	+0.0	+0.1	+0.0	+0.0	-40.0	-9.7	61.9	-71.6	Para
			+0.0	+0.0	+0.0	+0.0					
			+0.2	+0.0	+7.4						
31	28.500M	20.8	+0.0	+0.1	+0.0	+0.0	-40.0	-14.0	61.9	-75.9	Para
			+0.0	+0.0	+0.0	+0.0					
			+0.3	+0.0	+4.8						



Test Location: CKC Laboratories • 22116 23rd Drive SE, Suite A • Bothell, WA 98021 • 1-800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.231(b) Spurious Field Strength (>470 MHz Transmitter) (Band Edge)**  
Work Order #: **105444** Date: 7/6/2021  
Test Type: **Maximized Emissions** Time: 19:35:42  
Tested By: Michael Atkinson Sequence#: 14  
Software: EMITest 5.03.19

***Equipment Tested:***

Device	Manufacturer	Model #	S/N
Configuration 7			

***Support Equipment:***

Device	Manufacturer	Model #	S/N
Configuration 7			

***Test Conditions / Notes:***

Frequency: 9kHz to 10GHz

Setup: EUT is on foam table. EUT is connected to support tablet. EUT is transmitting using test software on support tablet to control EUT. XYZ axes investigated, horizontal and vertical antenna polarities investigated above 30MHz, 3 orthogonal axes investigated below 30MHz, worst case reported.


EUT with internal antenna.

Temperature (°C): 22-23

Relative Humidity (%): 43-50

Test Location: Bothell Lab C3

Test Method: ANSI C63.10 (2013)

Itron, Inc. WO#: 105444 Sequence#: 14 Date: 7/6/2021  
 15.231(b) Spurious Field Strength (>470 MHz Transmitter) (Band Edge) Test Distance: 3 Meters Various

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
	AN02673	Spectrum Analyzer	E4446A	2/3/2021	2/3/2023
T1	ANP06540	Cable	Heliax	8/23/2019	8/23/2021
T2	ANP05305	Cable	ETSI-50T	9/6/2019	9/6/2021
T3	ANP05360	Cable	RG214	2/3/2020	2/3/2022
T4	AN03628	Biconilog Antenna	3142E	6/3/2021	6/3/2023
T5	AN02307	Preamp	8447D	1/10/2020	1/10/2022
T6	ANP06515	Cable	Heliax	7/1/2020	7/1/2022
T7	AN03540	Preamp	83017A	5/14/2021	5/14/2023
T8	ANP07505	Cable	CLU40-KMKM-02.00F	1/26/2021	1/26/2023
T9	AN02374ANSI	Horn Antenna	RGA-60	5/25/2021	5/25/2023
T10	AN00052	Loop Antenna	6502	5/4/2020	5/4/2022

<b>Measurement Data:</b>			Reading listed by margin.				Test Distance: 3 Meters				
#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5	T6	T7	T8	Table	dB $\mu$ V/m	dB $\mu$ V/m	dB	Ant
			T9	T10							
			MHz	dB $\mu$ V	dB	dB	dB	dB $\mu$ V/m	dB $\mu$ V/m	dB	Ant
1	73.600M	44.2	+0.1	+0.4	+0.5	+12.8	+0.0	30.2	40.0	-9.8	Vert
			-27.8	+0.0	+0.0	+0.0					
			+0.0	+0.0							
2	3807.760M	39.3	+0.9	+0.0	+0.0	+0.0	+0.0	42.6	54.0	-11.4	Vert
			+0.0	+3.5	-33.8	+0.3					
			+32.4	+0.0							
3	7616.760M	32.2	+1.6	+0.0	+0.0	+0.0	+0.0	42.2	54.0	-11.8	Vert
			+0.0	+5.4	-34.9	+0.5					
			+37.4	+0.0							
4	1082.000M	51.0	+0.4	+0.0	+0.0	+0.0	+0.0	41.3	54.0	-12.7	Horiz
			+0.0	+1.8	-36.6	+0.3					
			+24.4	+0.0							
5	1000.000M	51.3	+0.4	+0.0	+0.0	+0.0	+0.0	41.0	54.0	-13.0	Vert
			+0.0	+1.7	-37.0	+0.3					
			+24.3	+0.0							
6	1306.000M	48.5	+0.4	+0.0	+0.0	+0.0	+0.0	40.7	54.0	-13.3	Vert
			+0.0	+1.9	-35.7	+0.2					
			+25.4	+0.0							
7	7615.280M	30.3	+1.6	+0.0	+0.0	+0.0	+0.0	40.3	54.0	-13.7	Horiz
			+0.0	+5.4	-34.9	+0.5					
			+37.4	+0.0							
8	114.400M	42.4	+0.1	+0.5	+0.6	+13.9	+0.0	29.8	43.5	-13.7	Horiz
			-27.7	+0.0	+0.0	+0.0					
			+0.0	+0.0							
9	3496.000M	46.1	+0.8	+0.0	+0.0	+0.0	+0.0	47.9	61.9	-14.0	Horiz
			+0.0	+3.3	-33.8	+0.3					
			+31.2	+0.0							
10	74.600M	38.9	+0.1	+0.4	+0.5	+12.8	+0.0	24.9	40.0	-15.1	Vert
			-27.8	+0.0	+0.0	+0.0					
			+0.0	+0.0							
11	614.000M	28.2	+0.3	+1.2	+1.7	+27.2	+0.0	30.4	46.0	-15.6	Vert
			-28.2	+0.0	+0.0	+0.0					
			+0.0	+0.0							
12	115.400M	40.4	+0.1	+0.5	+0.6	+13.8	+0.0	27.7	43.5	-15.8	Vert
			-27.7	+0.0	+0.0	+0.0					
			+0.0	+0.0							
13	2855.760M	38.7	+0.7	+0.0	+0.0	+0.0	+0.0	38.1	54.0	-15.9	Vert
			+0.0	+3.0	-34.1	+0.3					
			+29.5	+0.0							
14	73.512M	37.7	+0.1	+0.4	+0.5	+12.8	+0.0	23.7	40.0	-16.3	Vert
			-27.8	+0.0	+0.0	+0.0					
			+0.0	+0.0							
15	3808.360M	33.2	+0.9	+0.0	+0.0	+0.0	+0.0	36.5	54.0	-17.5	Vert
			+0.0	+3.5	-33.8	+0.3					
			+32.4	+0.0							



16	4988.000M	29.9	+0.9	+0.0	+0.0	+0.0	+0.0	35.5	54.0	-18.5	Vert
	Ave		+0.0	+3.8	-33.4	+0.5					
			+33.8	+0.0							
^	4988.000M	48.0	+0.9	+0.0	+0.0	+0.0	+0.0	53.6	54.0	-0.4	Vert
			+0.0	+3.8	-33.4	+0.5					
			+33.8	+0.0							
18	115.400M	37.5	+0.1	+0.5	+0.6	+13.8	+0.0	24.8	43.5	-18.7	Vert
			-27.7	+0.0	+0.0	+0.0					
			+0.0	+0.0							
19	960.000M	26.9	+0.4	+1.5	+2.2	+30.7	+0.0	34.6	54.0	-19.4	Vert
			-27.1	+0.0	+0.0	+0.0					
			+0.0	+0.0							
20	1894.780M	44.2	+0.6	+0.0	+0.0	+0.0	+0.0	40.8	61.9	-21.1	Horiz
			+0.0	+2.4	-34.6	+0.3					
			+27.9	+0.0							
21	2855.840M	33.2	+0.7	+0.0	+0.0	+0.0	+0.0	32.6	54.0	-21.4	Horiz
			+0.0	+3.0	-34.1	+0.3					
			+29.5	+0.0							
22	836.100M	34.8	+0.3	+1.4	+2.0	+29.5	+0.0	40.4	61.9	-21.5	Vert
			-27.6	+0.0	+0.0	+0.0					
			+0.0	+0.0							
23	778.800M	35.8	+0.3	+1.3	+1.9	+28.8	+0.0	40.3	61.9	-21.6	Vert
			-27.8	+0.0	+0.0	+0.0					
			+0.0	+0.0							
24	6664.350M	32.2	+1.2	+0.0	+0.0	+0.0	+0.0	40.3	61.9	-21.6	Horiz
			+0.0	+5.2	-34.1	+0.4					
			+35.4	+0.0							
25	2855.880M	31.7	+0.7	+0.0	+0.0	+0.0	+0.0	31.1	54.0	-22.9	Vert
			+0.0	+3.0	-34.1	+0.3					
			+29.5	+0.0							
26	872.000M	32.2	+0.3	+1.4	+2.0	+28.8	+0.0	37.3	61.9	-24.6	Vert
			-27.4	+0.0	+0.0	+0.0					
			+0.0	+0.0							
27	1903.760M	40.6	+0.6	+0.0	+0.0	+0.0	+0.0	37.3	61.9	-24.6	Vert
			+0.0	+2.4	-34.6	+0.3					
			+28.0	+0.0							
28	872.000M	31.4	+0.3	+1.4	+2.0	+28.8	+0.0	36.5	61.9	-25.4	Horiz
			-27.4	+0.0	+0.0	+0.0					
			+0.0	+0.0							
29	147.400M	46.9	+0.2	+0.6	+0.7	+14.4	+0.0	35.3	61.9	-26.6	Horiz
			-27.5	+0.0	+0.0	+0.0					
			+0.0	+0.0							
30	205.600M	43.4	+0.2	+0.7	+0.9	+16.4	+0.0	34.4	61.9	-27.5	Horiz
			-27.2	+0.0	+0.0	+0.0					
			+0.0	+0.0							
31	6664.240M	25.9	+1.2	+0.0	+0.0	+0.0	+0.0	34.0	61.9	-27.9	Vert
	Ave		+0.0	+5.2	-34.1	+0.4					
			+35.4	+0.0							
^	6664.240M	41.1	+1.2	+0.0	+0.0	+0.0	+0.0	49.2	61.9	-12.7	Vert
			+0.0	+5.2	-34.1	+0.4					
			+35.4	+0.0							

33	48.400M	48.1	+0.1	+0.4	+0.4	+12.7	+0.0	33.8	61.9	-28.1	Vert
			-27.9	+0.0	+0.0	+0.0					
			+0.0	+0.0							
34	6664.360M	25.1	+1.2	+0.0	+0.0	+0.0	+0.0	33.2	61.9	-28.7	Vert
	Ave		+0.0	+5.2	-34.1	+0.4			BW		
			+35.4	+0.0							
^	6664.360M	36.6	+1.2	+0.0	+0.0	+0.0	+0.0	44.7	61.9	-17.2	Vert
			+0.0	+5.2	-34.1	+0.4			BW		
			+35.4	+0.0							
36	527.600M	31.8	+0.3	+1.1	+1.5	+26.2	+0.0	32.7	61.9	-29.2	Vert
			-28.2	+0.0	+0.0	+0.0					
			+0.0	+0.0							
37	222.100M	41.0	+0.2	+0.7	+0.9	+16.7	+0.0	32.4	61.9	-29.5	Vert
			-27.1	+0.0	+0.0	+0.0					
			+0.0	+0.0							
38	48.400M	46.6	+0.1	+0.4	+0.4	+12.7	+0.0	32.3	61.9	-29.6	Vert
			-27.9	+0.0	+0.0	+0.0					
			+0.0	+0.0							
39	431.600M	34.4	+0.2	+1.0	+1.4	+22.8	+0.0	32.0	61.9	-29.9	Vert
			-27.8	+0.0	+0.0	+0.0					
			+0.0	+0.0							
40	1904.310M	35.1	+0.6	+0.0	+0.0	+0.0	+0.0	31.8	61.9	-30.1	Horiz
			+0.0	+2.4	-34.6	+0.3			BW		
			+28.0	+0.0							
41	431.600M	33.6	+0.2	+1.0	+1.4	+22.8	+0.0	31.2	61.9	-30.7	Vert
			-27.8	+0.0	+0.0	+0.0					
			+0.0	+0.0							
42	1904.000M	34.2	+0.6	+0.0	+0.0	+0.0	+0.0	30.9	61.9	-31.0	Vert
			+0.0	+2.4	-34.6	+0.3			BW		
			+28.0	+0.0							
43	223.000M	38.9	+0.2	+0.7	+0.9	+16.8	+0.0	30.4	61.9	-31.5	Vert
			-27.1	+0.0	+0.0	+0.0					
			+0.0	+0.0							
44	148.300M	40.8	+0.2	+0.6	+0.7	+14.6	+0.0	29.4	61.9	-32.5	Vert
			-27.5	+0.0	+0.0	+0.0					
			+0.0	+0.0							
45	76.600M	42.8	+0.1	+0.4	+0.5	+12.7	+0.0	28.7	61.9	-33.2	Vert
			-27.8	+0.0	+0.0	+0.0					
			+0.0	+0.0							
46	144.500M	39.9	+0.1	+0.5	+0.7	+14.0	+0.0	27.7	61.9	-34.2	Vert
			-27.5	+0.0	+0.0	+0.0					
			+0.0	+0.0							



47	96.900M	37.3	+0.1	+0.5	+0.6	+13.5	+0.0	24.3	61.9	-37.6	Vert
			-27.7	+0.0	+0.0	+0.0					
			+0.0	+0.0							
48	19.833M	23.6	+0.1	+0.0	+0.0	+0.0	-40.0	-8.7	61.9	-70.6	Para
			+0.0	+0.2	+0.0	+0.0					
			+0.0	+7.4							
49	28.500M	22.0	+0.1	+0.0	+0.0	+0.0	-40.0	-12.8	61.9	-74.7	Para
			+0.0	+0.3	+0.0	+0.0					
			+0.0	+4.8							
50	16.024M	12.2	+0.1	+0.0	+0.0	+0.0	-40.0	-18.7	61.9	-80.6	Para
			+0.0	+0.2	+0.0	+0.0					
			+0.0	+8.8							

## Plot(s)



### Configuration 3



Configuration 5



**Configuration 7**



**Test Setup Photo(s)**

**Configuration 3**



X Axis, View #1



X Axis, View #2



Y Axis



Z Axis



Below 1GHz




Above 1GHz

Configuration 5



X Axis



Y Axis



Z Axis



Below 1GHz



Above 1GHz

**Configuration 7**



X Axis




Y Axis



Z Axis



Below 1GHz



Above 1GHz

## 15.207 AC Conducted Emissions

### Test Setup / Conditions / Data

Test Location: CKC Laboratories • 22116 23rd Drive SE, Suite A • Bothell, WA 98021 • 1-800-500-4EMC (4362)  
 Customer: **Itron, Inc.**  
 Specification: **15.207 AC Mains - Average**  
 Work Order #: **105444** Date: 7/9/2021  
 Test Type: **Conducted Emissions** Time: 17:43:57  
 Tested By: Michael Atkinson Sequence#: 24  
 Software: EMITest 5.03.19 115VAC 60Hz

***Equipment Tested:***

Device	Manufacturer	Model #	S/N
Configuration 3			

***Support Equipment:***

Device	Manufacturer	Model #	S/N
Configuration 3			

***Test Conditions / Notes:***

Frequency: 0.15-30MHz

Setup: EUT is on foam table. EUT is connected to support tablet with USB cable. EUT is transmitting using test software on support tablet to control EUT. EUT is connected to a DC power supply which connects to AC mains.

High power and Low power MAS investigated, worst case reported. EUT has external attached antenna connected. Also investigated with vehicle antenna, data collected is representative of worst case.


Temperature (°C): 23

Relative Humidity (%): 45

Test Location: Bothell Lab C3

Test Method: ANSI C63.10 (2013)

Itron, Inc. WO#: 105444 Sequence#: 24 Date: 7/9/2021  
 15.207 AC Mains - Average Test Lead: 115VAC 60Hz Line



**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
	AN02673	Spectrum Analyzer	E4446A	2/3/2021	2/3/2023
T1	AN02611	High Pass Filter	HE9615-150K-50-720B	1/10/2020	1/10/2022
T2	ANP06540	Cable	Heliax	8/23/2019	8/23/2021
T3	ANP06515	Cable	Heliax	7/1/2020	7/1/2022
T4	ANP06219	Attenuator	768-10	4/7/2020	4/7/2022
T5	AN01492	50uH LISN-Line (L1)	3816/2NM	10/14/2019	10/14/2021
	AN01492	50uH LISN-Neutral (L2)	3816/2NM	10/14/2019	10/14/2021

<b>Measurement Data:</b>			Reading listed by margin.				Test Lead: Line				
#	Freq MHz	Rdng dB $\mu$ V	T1 dB	T2 dB	T3 dB	T4 dB	Dist Table	Corr dB $\mu$ V	Spec dB $\mu$ V	Margin dB	Polar Ant
1	526.851k Ave	21.9 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	31.8	46.0	-14.2	Line
^	526.850k	36.1 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	46.0	46.0	+0.0	Line
3	482.703k Ave	7.5 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	17.3	46.3	-29.0	Line
4	481.191k Ave	7.5 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	17.3	46.3	-29.0	Line
^	482.703k	36.7 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	46.5	46.3	+0.2	Line
^	481.191k	36.6 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	46.4	46.3	+0.1	Line
7	434.322k Ave	8.1 +0.7	+0.2	+0.0	+0.0	+9.1	+0.0	18.1	47.2	-29.1	Line
8	491.170k Ave	7.1 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	17.0	46.1	-29.1	Line
^	491.169k	35.9 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	45.8	46.1	-0.3	Line
10	432.633k Ave	8.1 +0.7	+0.2	+0.0	+0.0	+9.1	+0.0	18.1	47.2	-29.1	Line
^	434.321k	38.5 +0.7	+0.2	+0.0	+0.0	+9.1	+0.0	48.5	47.2	+1.3	Line
^	432.632k	38.2 +0.7	+0.2	+0.0	+0.0	+9.1	+0.0	48.2	47.2	+1.0	Line
13	425.156k Ave	8.1 +0.7	+0.2	+0.0	+0.0	+9.1	+0.0	18.1	47.3	-29.2	Line
^	425.156k	38.5 +0.7	+0.2	+0.0	+0.0	+9.1	+0.0	48.5	47.3	+1.2	Line
15	418.392k Ave	8.3 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	18.2	47.5	-29.3	Line
16	415.900k Ave	8.2 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	18.1	47.5	-29.4	Line
17	406.643k Ave	8.3 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	18.2	47.7	-29.5	Line
18	414.298k Ave	8.2 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	18.1	47.6	-29.5	Line
^	418.391k	38.6 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	48.5	47.5	+1.0	Line
^	415.899k	38.3 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	48.2	47.5	+0.7	Line
21	409.669k Ave	8.2 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	18.1	47.7	-29.6	Line
^	409.669k	38.7 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	48.6	47.7	+0.9	Line
^	414.297k	38.5 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	48.4	47.6	+0.8	Line

24	404.151k	8.2	+0.2	+0.0	+0.0	+9.1	+0.0	18.1	47.8	-29.7	Line
	Ave		+0.6								
^	406.642k	38.7	+0.2	+0.0	+0.0	+9.1	+0.0	48.6	47.7	+0.9	Line
			+0.6								
^	404.150k	38.4	+0.2	+0.0	+0.0	+9.1	+0.0	48.3	47.8	+0.5	Line
			+0.6								
27	396.674k	8.2	+0.2	+0.0	+0.0	+9.1	+0.0	18.2	47.9	-29.7	Line
	Ave		+0.7								
^	396.674k	38.4	+0.2	+0.0	+0.0	+9.1	+0.0	48.4	47.9	+0.5	Line
			+0.7								
29	383.323k	8.2	+0.2	+0.0	+0.0	+9.1	+0.0	18.2	48.2	-30.0	Line
	Ave		+0.7								
^	383.323k	38.3	+0.2	+0.0	+0.0	+9.1	+0.0	48.3	48.2	+0.1	Line
			+0.7								
31	173.894k	11.3	+0.4	+0.0	+0.0	+9.1	+0.0	22.5	54.8	-32.3	Line
	Ave		+1.7								
32	164.777k	11.5	+0.5	+0.0	+0.0	+9.1	+0.0	22.9	55.2	-32.3	Line
	Ave		+1.8								
33	175.361k	11.3	+0.4	+0.0	+0.0	+9.1	+0.0	22.4	54.7	-32.3	Line
	Ave		+1.6								
^	175.361k	43.7	+0.4	+0.0	+0.0	+9.1	+0.0	54.8	54.7	+0.1	Line
			+1.6								
^	173.893k	43.6	+0.4	+0.0	+0.0	+9.1	+0.0	54.8	54.8	+0.0	Line
			+1.7								
36	181.125k	10.9	+0.4	+0.0	+0.0	+9.1	+0.0	21.9	54.4	-32.5	Line
	Ave		+1.5								
^	181.125k	42.9	+0.4	+0.0	+0.0	+9.1	+0.0	53.9	54.4	-0.5	Line
			+1.5								
38	160.794k	11.4	+0.6	+0.0	+0.0	+9.1	+0.0	22.8	55.4	-32.6	Line
	Ave		+1.7								
^	164.776k	44.0	+0.5	+0.0	+0.0	+9.1	+0.0	55.4	55.2	+0.2	Line
			+1.8								
^	160.794k	43.7	+0.6	+0.0	+0.0	+9.1	+0.0	55.1	55.4	-0.3	Line
			+1.7								



Test Location: CKC Laboratories • 22116 23rd Drive SE, Suite A • Bothell, WA 98021 • 1-800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.207 AC Mains - Average**  
Work Order #: **105444** Date: 7/9/2021  
Test Type: **Conducted Emissions** Time: 17:34:31  
Tested By: Michael Atkinson Sequence#: 23  
Software: EMITest 5.03.19 115VAC 60Hz

***Equipment Tested:***

Device	Manufacturer	Model #	S/N
Configuration 3			

***Support Equipment:***

Device	Manufacturer	Model #	S/N
Configuration 3			

***Test Conditions / Notes:***

Frequency: 0.15-30MHz

Setup: EUT is on foam table. EUT is connected to support tablet with USB cable. EUT is transmitting using test software on support tablet to control EUT. EUT is connected to a DC power supply which connects to AC mains.


High power and Low power MAS investigated, worst case reported. EUT has external attached antenna connected. Also investigated with vehicle antenna, data collected is representative of worst case.

Temperature (°C): 23

Relative Humidity (%): 45

Test Location: Bothell Lab C3

Test Method: ANSI C63.10 (2013)

Itron, Inc. WO#: 105444 Sequence#: 23 Date: 7/9/2021  
 15.207 AC Mains - Average Test Lead: 115VAC 60Hz Neutral

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
	AN02673	Spectrum Analyzer	E4446A	2/3/2021	2/3/2023
T1	AN02611	High Pass Filter	HE9615-150K-50-720B	1/10/2020	1/10/2022
T2	ANP06540	Cable	Heliax	8/23/2019	8/23/2021
T3	ANP06515	Cable	Heliax	7/1/2020	7/1/2022
T4	ANP06219	Attenuator	768-10	4/7/2020	4/7/2022
	AN01492	50uH LISN-Line (L1)	3816/2NM	10/14/2019	10/14/2021
T5	AN01492	50uH LISN-Neutral (L2)	3816/2NM	10/14/2019	10/14/2021

<b>Measurement Data:</b>			Reading listed by margin.				Test Lead: Neutral				
#	Freq MHz	Rdng dB $\mu$ V	T1 dB	T2 dB	T3 dB	T4 dB	Dist Table	Corr dB $\mu$ V	Spec dB $\mu$ V	Margin dB	Polar
1	528.363k Ave	21.8 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	31.7	46.0	-14.3	Neutr
2	532.596k Ave	15.3 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	25.2	46.0	-20.8	Neutr
^	528.362k	35.9 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	45.8	46.0	-0.2	Neutr
^	532.596k	35.8 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	45.7	46.0	-0.3	Neutr
5	520.501k Ave	9.4 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	19.2	46.0	-26.8	Neutr
^	520.500k	35.7 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	45.5	46.0	-0.5	Neutr
7	441.881k Ave	8.2 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	18.0	47.0	-29.0	Neutr
^	441.881k	38.6 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	48.4	47.0	+1.4	Neutr
9	432.810k Ave	8.2 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	18.1	47.2	-29.1	Neutr
^	432.810k	37.6 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	47.5	47.2	+0.3	Neutr
11	419.460k Ave	8.3 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	18.2	47.5	-29.3	Neutr
^	419.459k	38.9 +0.6	+0.2	+0.0	+0.0	+9.1	+0.0	48.8	47.5	+1.3	Neutr
13	592.468k Ave	5.4 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	15.3	46.0	-30.7	Neutr
^	592.467k	31.6 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	41.5	46.0	-4.5	Neutr
15	618.170k Ave	5.1 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	15.0	46.0	-31.0	Neutr
^	618.170k	30.1 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	40.0	46.0	-6.0	Neutr
17	632.382k Ave	5.0 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	14.9	46.0	-31.1	Neutr
^	632.382k	30.1 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	40.0	46.0	-6.0	Neutr
19	625.427k Ave	5.0 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	14.9	46.0	-31.1	Neutr
^	625.427k	30.2 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	40.1	46.0	-5.9	Neutr
21	166.243k Ave	12.4 +1.7	+0.5	+0.0	+0.0	+9.1	+0.0	23.7	55.1	-31.4	Neutr
^	166.242k	45.5 +1.7	+0.5	+0.0	+0.0	+9.1	+0.0	56.8	55.1	+1.7	Neutr
23	176.722k Ave	12.1 +1.6	+0.4	+0.0	+0.0	+9.1	+0.0	23.2	54.6	-31.4	Neutr
24	173.474k Ave	12.2 +1.6	+0.4	+0.0	+0.0	+9.1	+0.0	23.3	54.8	-31.5	Neutr

^	173.473k	45.2	+0.4 +1.6	+0.0	+0.0	+9.1	+0.0	56.3	54.8	+1.5	Neutr
^	176.722k	44.9	+0.4 +1.6	+0.0	+0.0	+9.1	+0.0	56.0	54.6	+1.4	Neutr
27	155.972k	12.3	+0.8 +1.9	+0.0	+0.0	+9.1	+0.0	24.1	55.7	-31.6	Neutr
28	151.781k	12.1	+1.1 +1.9	+0.0	+0.0	+9.1	+0.0	24.2	55.9	-31.7	Neutr
^	155.972k	44.8	+0.8 +1.9	+0.0	+0.0	+9.1	+0.0	56.6	55.7	+0.9	Neutr
^	151.780k	43.2	+1.1 +1.9	+0.0	+0.0	+9.1	+0.0	55.3	55.9	-0.6	Neutr
31	192.652k	10.1	+0.3 +1.4	+0.0	+0.0	+9.1	+0.0	20.9	53.9	-33.0	Neutr
32	191.813k	10.2	+0.3 +1.4	+0.0	+0.0	+9.1	+0.0	21.0	54.0	-33.0	Neutr
33	196.215k	9.5	+0.2 +1.3	+0.0	+0.0	+9.1	+0.0	20.1	53.8	-33.7	Neutr
^	191.813k	41.5	+0.3 +1.4	+0.0	+0.0	+9.1	+0.0	52.3	54.0	-1.7	Neutr
^	192.651k	41.3	+0.3 +1.4	+0.0	+0.0	+9.1	+0.0	52.1	53.9	-1.8	Neutr
36	201.036k	8.9	+0.2 +1.3	+0.0	+0.0	+9.1	+0.0	19.5	53.6	-34.1	Neutr
^	196.214k	40.1	+0.2 +1.3	+0.0	+0.0	+9.1	+0.0	50.7	53.8	-3.1	Neutr
38	204.284k	8.4	+0.2 +1.3	+0.0	+0.0	+9.1	+0.0	19.0	53.4	-34.4	Neutr
^	201.035k	38.5	+0.2 +1.3	+0.0	+0.0	+9.1	+0.0	49.1	53.6	-4.5	Neutr
^	204.284k	37.5	+0.2 +1.3	+0.0	+0.0	+9.1	+0.0	48.1	53.4	-5.3	Neutr



Test Location: CKC Laboratories • 22116 23rd Drive SE, Suite A • Bothell, WA 98021 • 1-800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.207 AC Mains - Quasi-peak**  
Work Order #: **105444** Date: 7/9/2021  
Test Type: **Conducted Emissions** Time: 19:53:29  
Tested By: Michael Atkinson Sequence#: 29  
Software: EMITest 5.03.19 115VAC 60Hz

***Equipment Tested:***


Device	Manufacturer	Model #	S/N
Configuration 9			

***Support Equipment:***

Device	Manufacturer	Model #	S/N
Configuration 9			

***Test Conditions / Notes:***

Frequency: 0.15-30MHz
Setup: EUT is on foam table. EUT is connected to AC-USB adapter which is connected to AC mains. EUT is configured to transmit while connected to AC-USB adapter.
High power and Low power MAS investigated, worst case reported. EUT has internal antenna.
Temperature (°C): 23 Relative Humidity (%): 45 Test Location: Bothell Lab C3 Test Method: ANSI C63.10 (2013)

Itron, Inc. WO#: 105444 Sequence#: 29 Date: 7/9/2021  
 15.207 AC Mains - Quasi-peak Test Lead: 115VAC 60Hz Line

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
	AN02673	Spectrum Analyzer	E4446A	2/3/2021	2/3/2023
T1	AN02611	High Pass Filter	HE9615-150K-50-720B	1/10/2020	1/10/2022
T2	ANP06540	Cable	Heliax	8/23/2019	8/23/2021
T3	ANP06515	Cable	Heliax	7/1/2020	7/1/2022
T4	ANP06219	Attenuator	768-10	4/7/2020	4/7/2022
T5	AN01492	50uH LISN-Line (L1)	3816/2NM	10/14/2019	10/14/2021
	AN01492	50uH LISN-Neutral (L2)	3816/2NM	10/14/2019	10/14/2021

<b>Measurement Data:</b>			Reading listed by margin.				Test Lead: Line				
#	Freq MHz	Rdng dB $\mu$ V	T1 dB	T2 dB	T3 dB	T4 dB	Dist Table	Corr dB $\mu$ V	Spec dB $\mu$ V	Margin dB	Polar Ant
1	791.178k QP	43.4 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	53.2	56.0	-2.8	Line
2	835.864k QP	42.4 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	52.1	56.0	-3.9	Line
3	804.019k QP	42.1 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	51.9	56.0	-4.1	Line
4	817.373k QP	42.1 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	51.8	56.0	-4.2	Line
5	850.246k QP	40.2 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	49.9	56.0	-6.1	Line
6	791.178k Ave	30.0 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	39.8	46.0	-6.2	Line
^	791.177k	45.7 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	55.5	46.0	+9.5	Line
8	835.864k Ave	28.9 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	38.6	46.0	-7.4	Line
^	835.864k	45.5 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	55.2	46.0	+9.2	Line
10	817.373k Ave	28.4 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	38.1	46.0	-7.9	Line
^	817.373k	46.0 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	55.7	46.0	+9.7	Line
12	804.019k Ave	26.3 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	36.1	46.0	-9.9	Line
^	804.018k	45.0 +0.5	+0.2	+0.0	+0.0	+9.1	+0.0	54.8	46.0	+8.8	Line
14	1.510M QP	34.9 +0.5	+0.2	+0.0	+0.1	+9.1	+0.0	44.8	56.0	-11.2	Line
15	676.832k Ave	24.7 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	34.6	46.0	-11.4	Line
^	676.832k	41.2 +0.5	+0.3	+0.0	+0.0	+9.1	+0.0	51.1	46.0	+5.1	Line
17	850.246k Ave	24.9 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	34.6	46.0	-11.4	Line
^	850.246k	42.8 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	52.5	46.0	+6.5	Line
19	4.653M Ave	24.1 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	33.9	46.0	-12.1	Line
^	4.653M	41.0 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	50.8	46.0	+4.8	Line
21	4.208M Ave	24.0 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	33.7	46.0	-12.3	Line
^	4.208M	40.7 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	50.4	46.0	+4.4	Line
23	3.006M Ave	23.9 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	33.6	46.0	-12.4	Line
^	3.006M	41.4 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	51.1	46.0	+5.1	Line

25	3.214M	23.7	+0.1	+0.0	+0.1	+9.1	+0.0	33.4	46.0	-12.6	Line
	Ave		+0.4								
^	3.214M	40.6	+0.1	+0.0	+0.1	+9.1	+0.0	50.3	46.0	+4.3	Line
		+0.4									
27	3.911M	23.5	+0.1	+0.0	+0.1	+9.1	+0.0	33.2	46.0	-12.8	Line
	Ave	+0.4									
^	3.911M	41.9	+0.1	+0.0	+0.1	+9.1	+0.0	51.6	46.0	+5.6	Line
		+0.4									
29	3.452M	23.3	+0.1	+0.0	+0.1	+9.1	+0.0	33.0	46.0	-13.0	Line
	Ave	+0.4									
^	3.452M	40.9	+0.1	+0.0	+0.1	+9.1	+0.0	50.6	46.0	+4.6	Line
		+0.4									
31	2.238M	22.9	+0.2	+0.0	+0.1	+9.1	+0.0	32.8	46.0	-13.2	Line
	Ave	+0.5									
^	2.238M	40.9	+0.2	+0.0	+0.1	+9.1	+0.0	50.8	46.0	+4.8	Line
		+0.5									
33	1.510M	21.6	+0.2	+0.0	+0.1	+9.1	+0.0	31.5	46.0	-14.5	Line
	Ave	+0.5									
34	2.333M	21.6	+0.1	+0.0	+0.1	+9.1	+0.0	31.4	46.0	-14.6	Line
	Ave	+0.5									
35	2.341M	21.4	+0.1	+0.0	+0.1	+9.1	+0.0	31.2	46.0	-14.8	Line
	Ave	+0.5									
^	2.341M	40.9	+0.1	+0.0	+0.1	+9.1	+0.0	50.7	46.0	+4.7	Line
		+0.5									
^	2.333M	40.8	+0.1	+0.0	+0.1	+9.1	+0.0	50.6	46.0	+4.6	Line
		+0.5									
38	1.931M	20.9	+0.2	+0.0	+0.1	+9.1	+0.0	30.7	46.0	-15.3	Line
	Ave	+0.4									
^	1.931M	41.5	+0.2	+0.0	+0.1	+9.1	+0.0	51.3	46.0	+5.3	Line
		+0.4									
40	645.520k	20.8	+0.3	+0.0	+0.0	+9.1	+0.0	30.7	46.0	-15.3	Line
	Ave	+0.5									
41	1.888M	20.6	+0.2	+0.0	+0.1	+9.1	+0.0	30.4	46.0	-15.6	Line
	Ave	+0.4									
^	1.888M	42.4	+0.2	+0.0	+0.1	+9.1	+0.0	52.2	46.0	+6.2	Line
		+0.4									
43	979.684k	20.4	+0.2	+0.0	+0.0	+9.1	+0.0	30.1	46.0	-15.9	Line
	Ave	+0.4									
^	979.683k	41.5	+0.2	+0.0	+0.0	+9.1	+0.0	51.2	46.0	+5.2	Line
		+0.4									
45	599.100k	20.1	+0.3	+0.0	+0.0	+9.1	+0.0	30.0	46.0	-16.0	Line
	Ave	+0.5									
^	599.100k	39.3	+0.3	+0.0	+0.0	+9.1	+0.0	49.2	46.0	+3.2	Line
		+0.5									
47	643.570k	19.9	+0.3	+0.0	+0.0	+9.1	+0.0	29.8	46.0	-16.2	Line
	Ave	+0.5									
^	643.570k	41.5	+0.3	+0.0	+0.0	+9.1	+0.0	51.4	46.0	+5.4	Line
		+0.5									
^	643.570k	41.5	+0.3	+0.0	+0.0	+9.1	+0.0	51.4	46.0	+5.4	Line
		+0.5									

50	1.518M	19.9	+0.2	+0.0	+0.1	+9.1	+0.0	29.7	46.0	-16.3	Line
	Ave		+0.4								
^	1.510M	42.7	+0.2	+0.0	+0.1	+9.1	+0.0	52.6	46.0	+6.6	Line
			+0.5								
^	1.518M	41.4	+0.2	+0.0	+0.1	+9.1	+0.0	51.2	46.0	+5.2	Line
			+0.4								
53	1.593M	19.7	+0.2	+0.0	+0.1	+9.1	+0.0	29.5	46.0	-16.5	Line
	Ave		+0.4								
^	1.593M	41.3	+0.2	+0.0	+0.1	+9.1	+0.0	51.1	46.0	+5.1	Line
			+0.4								
55	1.543M	19.2	+0.2	+0.0	+0.1	+9.1	+0.0	29.0	46.0	-17.0	Line
	Ave		+0.4								
^	1.543M	41.0	+0.2	+0.0	+0.1	+9.1	+0.0	50.8	46.0	+4.8	Line
			+0.4								
57	1.949M	19.1	+0.2	+0.0	+0.1	+9.1	+0.0	29.0	46.0	-17.0	Line
	Ave		+0.5								
^	1.949M	40.9	+0.2	+0.0	+0.1	+9.1	+0.0	50.8	46.0	+4.8	Line
			+0.5								
59	567.840k	18.1	+0.3	+0.0	+0.0	+9.1	+0.0	28.0	46.0	-18.0	Line
	Ave		+0.5								
^	567.840k	39.3	+0.3	+0.0	+0.0	+9.1	+0.0	49.2	46.0	+3.2	Line
			+0.5								
61	5.476M	22.2	+0.1	+0.0	+0.1	+9.1	+0.0	32.0	50.0	-18.0	Line
	Ave		+0.5								
^	5.476M	41.2	+0.1	+0.0	+0.1	+9.1	+0.0	51.0	50.0	+1.0	Line
			+0.5								
63	482.060k	18.2	+0.2	+0.0	+0.0	+9.1	+0.0	28.0	46.3	-18.3	Line
	Ave		+0.5								
^	482.060k	40.4	+0.2	+0.0	+0.0	+9.1	+0.0	50.2	46.3	+3.9	Line
			+0.5								
65	1.230M	17.8	+0.2	+0.0	+0.1	+9.1	+0.0	27.6	46.0	-18.4	Line
	Ave		+0.4								
^	1.230M	40.9	+0.2	+0.0	+0.1	+9.1	+0.0	50.7	46.0	+4.7	Line
			+0.4								
67	511.700k	17.7	+0.2	+0.0	+0.0	+9.1	+0.0	27.5	46.0	-18.5	Line
	Ave		+0.5								
^	511.700k	39.4	+0.2	+0.0	+0.0	+9.1	+0.0	49.2	46.0	+3.2	Line
			+0.5								
69	533.530k	16.6	+0.3	+0.0	+0.0	+9.1	+0.0	26.5	46.0	-19.5	Line
	Ave		+0.5								
^	533.530k	39.2	+0.3	+0.0	+0.0	+9.1	+0.0	49.1	46.0	+3.1	Line
			+0.5								
71	444.570k	17.5	+0.2	+0.0	+0.0	+9.1	+0.0	27.3	47.0	-19.7	Line
	Ave		+0.5								
^	444.570k	40.6	+0.2	+0.0	+0.0	+9.1	+0.0	50.4	47.0	+3.4	Line
			+0.5								
73	430.720k	17.3	+0.2	+0.0	+0.0	+9.1	+0.0	27.3	47.2	-19.9	Line
	Ave		+0.7								
^	430.720k	39.8	+0.2	+0.0	+0.0	+9.1	+0.0	49.8	47.2	+2.6	Line
			+0.7								



Test Location: CKC Laboratories • 22116 23rd Drive SE, Suite A • Bothell, WA 98021 • 1-800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.207 AC Mains - Quasi-peak**  
Work Order #: **105444** Date: 7/9/2021  
Test Type: **Conducted Emissions** Time: 20:04:51  
Tested By: Michael Atkinson Sequence#: 30  
Software: EMITest 5.03.19 115VAC 60Hz

***Equipment Tested:***


Device	Manufacturer	Model #	S/N
Configuration 9			

***Support Equipment:***

Device	Manufacturer	Model #	S/N
Configuration 9			

***Test Conditions / Notes:***

Frequency: 0.15-30MHz
Setup: EUT is on foam table. EUT is connected to AC-USB adapter which is connected to AC mains. EUT is configured to transmit while connected to AC-USB adapter.
High power and Low power MAS investigated, worst case reported. EUT has internal antenna.
Temperature (°C): 23 Relative Humidity (%): 45 Test Location: Bothell Lab C3 Test Method: ANSI C63.10 (2013)

Itron, Inc. WO#: 105444 Sequence#: 30 Date: 7/9/2021  
 15.207 AC Mains - Quasi-peak Test Lead: 115VAC 60Hz Neutral

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
	AN02673	Spectrum Analyzer	E4446A	2/3/2021	2/3/2023
T1	AN02611	High Pass Filter	HE9615-150K-50-720B	1/10/2020	1/10/2022
T2	ANP06540	Cable	Heliax	8/23/2019	8/23/2021
T3	ANP06515	Cable	Heliax	7/1/2020	7/1/2022
T4	ANP06219	Attenuator	768-10	4/7/2020	4/7/2022
	AN01492	50uH LISN-Line (L1)	3816/2NM	10/14/2019	10/14/2021
T5	AN01492	50uH LISN-Neutral (L2)	3816/2NM	10/14/2019	10/14/2021

<b>Measurement Data:</b>			Reading listed by margin.				Test Lead: Neutral				
#	Freq MHz	Rdng dB $\mu$ V	T1 dB	T2 dB	T3 dB	T4 dB	Dist Table	Corr dB $\mu$ V	Spec dB $\mu$ V	Margin dB	Polar Ant
1	794.260k QP	43.0 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	52.7	56.0	-3.3	Neutr
2	819.942k QP	42.4 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	52.1	56.0	-3.9	Neutr
3	794.260k Ave	28.5 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	38.2	46.0	-7.8	Neutr
^	794.259k	46.4 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	56.1	46.0	+10.1	Neutr
5	819.942k Ave	28.2 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	37.9	46.0	-8.1	Neutr
^	819.941k	47.2 +0.4	+0.2	+0.0	+0.0	+9.1	+0.0	56.9	46.0	+10.9	Neutr
7	2.959M QP	37.0 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	46.8	56.0	-9.2	Neutr
8	2.972M QP	36.2 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	46.0	56.0	-10.0	Neutr
9	3.335M Ave	25.3 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	35.0	46.0	-11.0	Neutr
^	3.335M	40.7 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	50.4	46.0	+4.4	Neutr
11	3.452M Ave	25.0 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	34.8	46.0	-11.2	Neutr
^	3.452M	41.4 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	51.2	46.0	+5.2	Neutr
13	3.714M Ave	25.0 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	34.7	46.0	-11.3	Neutr
^	3.714M	40.6 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	50.3	46.0	+4.3	Neutr
15	3.408M Ave	24.9 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	34.7	46.0	-11.3	Neutr
^	3.408M	40.7 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	50.5	46.0	+4.5	Neutr
17	4.127M Ave	24.8 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	34.6	46.0	-11.4	Neutr
^	4.127M	40.5 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	50.3	46.0	+4.3	Neutr
19	2.959M Ave	24.0 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	33.8	46.0	-12.2	Neutr
^	2.959M	41.6 +0.5	+0.1	+0.0	+0.1	+9.1	+0.0	51.4	46.0	+5.4	Neutr
21	4.228M Ave	24.1 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	33.8	46.0	-12.2	Neutr
^	4.228M	41.4 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	51.1	46.0	+5.1	Neutr
23	3.055M Ave	23.8 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	33.5	46.0	-12.5	Neutr
^	3.055M	40.7 +0.4	+0.1	+0.0	+0.1	+9.1	+0.0	50.4	46.0	+4.4	Neutr

25	678.344k	23.4	+0.3 +0.5	+0.0	+0.0	+9.1	+0.0	33.3	46.0	-12.7	Neutr
Ave											
^	678.344k	41.3	+0.3 +0.5	+0.0	+0.0	+9.1	+0.0	51.2	46.0	+5.2	Neutr
27	2.972M	23.0	+0.1 +0.5	+0.0	+0.1	+9.1	+0.0	32.8	46.0	-13.2	Neutr
Ave											
^	2.972M	41.5	+0.1 +0.5	+0.0	+0.1	+9.1	+0.0	51.3	46.0	+5.3	Neutr
29	4.417M	23.1	+0.1 +0.4	+0.0	+0.1	+9.1	+0.0	32.8	46.0	-13.2	Neutr
Ave											
^	4.417M	40.9	+0.1 +0.4	+0.0	+0.1	+9.1	+0.0	50.6	46.0	+4.6	Neutr
31	2.913M	22.6	+0.1 +0.4	+0.0	+0.1	+9.1	+0.0	32.3	46.0	-13.7	Neutr
Ave											
^	2.913M	40.9	+0.1 +0.4	+0.0	+0.1	+9.1	+0.0	50.6	46.0	+4.6	Neutr
33	4.892M	21.5	+0.1 +0.5	+0.0	+0.1	+9.1	+0.0	31.3	46.0	-14.7	Neutr
Ave											
^	4.892M	40.5	+0.1 +0.5	+0.0	+0.1	+9.1	+0.0	50.3	46.0	+4.3	Neutr
35	2.269M	21.4	+0.2 +0.5	+0.0	+0.1	+9.1	+0.0	31.3	46.0	-14.7	Neutr
Ave											
^	2.269M	40.1	+0.2 +0.5	+0.0	+0.1	+9.1	+0.0	50.0	46.0	+4.0	Neutr
37	2.602M	21.6	+0.1 +0.4	+0.0	+0.1	+9.1	+0.0	31.3	46.0	-14.7	Neutr
Ave											
^	2.602M	41.0	+0.1 +0.4	+0.0	+0.1	+9.1	+0.0	50.7	46.0	+4.7	Neutr
39	1.351M	21.5	+0.2 +0.4	+0.0	+0.0	+9.1	+0.0	31.2	46.0	-14.8	Neutr
Ave											
^	1.351M	39.3	+0.2 +0.4	+0.0	+0.0	+9.1	+0.0	49.0	46.0	+3.0	Neutr
41	1.040M	21.1	+0.2 +0.4	+0.0	+0.0	+9.1	+0.0	30.8	46.0	-15.2	Neutr
Ave											
^	1.040M	39.7	+0.2 +0.4	+0.0	+0.0	+9.1	+0.0	49.4	46.0	+3.4	Neutr
43	2.710M	20.9	+0.1 +0.5	+0.0	+0.1	+9.1	+0.0	30.7	46.0	-15.3	Neutr
Ave											
^	2.710M	40.8	+0.1 +0.5	+0.0	+0.1	+9.1	+0.0	50.6	46.0	+4.6	Neutr
45	2.658M	21.0	+0.1 +0.4	+0.0	+0.1	+9.1	+0.0	30.7	46.0	-15.3	Neutr
Ave											
^	2.658M	40.5	+0.1 +0.4	+0.0	+0.1	+9.1	+0.0	50.2	46.0	+4.2	Neutr

47	1.803M	20.7	+0.2	+0.0	+0.1	+9.1	+0.0	30.6	46.0	-15.4	Neutr
Ave			+0.5								
^	1.803M	40.4	+0.2	+0.0	+0.1	+9.1	+0.0	50.3	46.0	+4.3	Neutr
			+0.5								
49	650.525k	20.3	+0.3	+0.0	+0.0	+9.1	+0.0	30.2	46.0	-15.8	Neutr
Ave			+0.5								
^	650.525k	40.9	+0.3	+0.0	+0.0	+9.1	+0.0	50.8	46.0	+4.8	Neutr
			+0.5								
51	1.543M	17.0	+0.2	+0.0	+0.1	+9.1	+0.0	26.8	46.0	-19.2	Neutr
Ave			+0.4								
^	1.543M	40.4	+0.2	+0.0	+0.1	+9.1	+0.0	50.2	46.0	+4.2	Neutr
			+0.4								

**Test Setup Photo(s)**



Configuration 3



Configuration 9

## SUPPLEMENTAL INFORMATION

### Measurement Uncertainty

Uncertainty Value	Parameter
4.73 dB	Radiated Emissions
3.34 dB	Mains Conducted Emissions
3.30 dB	Disturbance Power

Uncertainties reported are worst case for all CKC Laboratories' sites and represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of k=2. Compliance is deemed to occur provided measurements are below the specified limits.

### Emissions Test Details

#### TESTING PARAMETERS

Unless otherwise indicated, the following configuration parameters are used for equipment setup: The cables were routed consistent with the typical application by varying the configuration of the test sample. Interface cables were connected to the available ports of the test unit. The effect of varying the position of the cables was investigated to find the configuration that produced maximum emissions. Cables were of the type and length specified in the individual requirements. The length of cable that produced maximum emissions was selected.

The equipment under test (EUT) was set up in a manner that represented its normal use, as shown in the setup photographs. Any special conditions required for the EUT to operate normally are identified in the comments that accompany the emissions tables.

The emissions data was taken with a spectrum analyzer or receiver. Incorporating the applicable correction factors for distance, antenna, cable loss and amplifier gain, the data was reduced as shown in the table below. The corrected data was then compared to the applicable emission limits. Preliminary and final measurements were taken in order to ensure that all emissions from the EUT were found and maximized.

#### CORRECTION FACTORS

The basic spectrum analyzer reading was converted using correction factors as shown in the highest emissions readings in the tables. For radiated emissions in dB $\mu$ V/m, the spectrum analyzer reading in dB $\mu$ V was corrected by using the following formula. This reading was then compared to the applicable specification limit. Individual measurements were compared with the displayed limit value in the margin column. The margin was calculated based on subtracting the limit value from the corrected measurement value; a positive margin represents a measurement exceeding the limit, while a negative margin represents a measurement less than the limit.

SAMPLE CALCULATIONS	
Meter reading	(dB $\mu$ V)
+ Antenna Factor	(dB/m)
+ Cable Loss	(dB)
- Distance Correction	(dB)
- Preamplifier Gain	(dB)
= Corrected Reading	(dB $\mu$ V/m)

## TEST INSTRUMENTATION AND ANALYZER SETTINGS

The test instrumentation and equipment listed were used to collect the emissions data. A spectrum analyzer or receiver was used for all measurements. Unless otherwise specified, the following table shows the measuring equipment bandwidth settings that were used in designated frequency bands. For testing emissions, an appropriate reference level and a vertical scale size of 10 dB per division were used.

MEASURING EQUIPMENT BANDWIDTH SETTINGS PER FREQUENCY RANGE			
TEST	BEGINNING FREQUENCY	ENDING FREQUENCY	BANDWIDTH SETTING
CONDUCTED EMISSIONS	150 kHz	30 MHz	9 kHz
RADIATED EMISSIONS	9 kHz	150 kHz	200 Hz
RADIATED EMISSIONS	150 kHz	30 MHz	9 kHz
RADIATED EMISSIONS	30 MHz	1000 MHz	120 kHz
RADIATED EMISSIONS	1000 MHz	>1 GHz	1 MHz

## SPECTRUM ANALYZER/RECEIVER DETECTOR FUNCTIONS

The notes that accompany the measurements contained in the emissions tables indicate the type of detector function used to obtain the given readings. Unless otherwise noted, all readings were made in the "positive peak" detector mode. Whenever a "quasi-peak" or "average" reading was recorded, the measurement was annotated with a "QP" or an "Ave" on the appropriate rows of the data sheets. In cases where quasi-peak or average limits were employed and data exists for multiple measurement types for the same frequency then the peak measurement was retained in the report for reference, however the numbering for the affected row was removed and an arrow or caret ("^") was placed in the far left-hand column indicating that the row above takes precedence for comparison to the limit. The following paragraphs describe in more detail the detector functions and when they were used to obtain the emissions data.

### Peak

In this mode, the spectrum analyzer or receiver recorded all emissions at their peak value as the frequency band selected was scanned. By combining this function with another feature called "peak hold," the measurement device had the ability to measure intermittent or low duty cycle transient emission peak levels. In this mode the measuring device made a slow scan across the frequency band selected and measured the peak emission value found at each frequency across the band.

### Quasi-Peak

Quasi-peak measurements were taken using the quasi-peak detector when the true peak values exceeded or were within 2 dB of a quasi-peak specification limit. Additional QP measurements may have been taken at the discretion of the operator.

### Average

Average measurements were taken using the average detector when the true peak values exceeded or were within 2 dB of an average specification limit. Additional average measurements may have been taken at the discretion of the operator. If the specification or test procedure requires trace averaging, then the averaging was performed using 100 samples or as required by the specification. All other average measurements are performed using video bandwidth averaging. To make these measurements, the test engineer reduces the video bandwidth on the measuring device until the modulation of the signal is filtered out. At this point, the measuring device is set into the linear mode and the scan time is reduced.