



# PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

<http://www.pctestlab.com>



## SAR COMPLIANCE EVALUATION REPORT

**Applicant Name:**

Crestron Electronics, Inc  
15 Volvo Drive  
Rockleigh, New Jersey 07647  
USA

**Date of Testing:**

11/30/10

**Test Site/Location:**

PCTEST Lab, Columbia, MD, USA

**Test Report Serial No.:**

0Y1011301928.ERO

**FCC ID:**

**EROUFO-WPR-3ER**

**APPLICANT:**

**CRESTRON ELECTRONICS, INC**

**EUT Type:**

802.15 ZigBee Waterproof Remote Controller

**Application Type:**

Certification

**FCC Rule Part(s):**

CFR §2.1093; FCC/OET Bulletin 65 Supplement C [July 2001]

**FCC Classification:**

FCC Part 15 Frequency Hopping Spread Spectrum Transceiver  
(DSS)

**Model(s):**

UFO-WPR-3ER

**Tx Frequency:**

2405.0 - 2480.0 MHz (ZigBee)

**Conducted Power:**

18.95 dBm (Zigbee)

**Max. SAR Measurement:**

1.18 W/kg ZigBee Body SAR

**Test Device Serial No.:**

Pre-Production [S/N: 0]

This wireless portable device has been shown to be capable of compliance for localized specific absorption rate (SAR) for uncontrolled environment/general population exposure limits specified in ANSI/IEEE C95.1-1992 and has been tested in accordance with the measurement procedures specified in FCC/OET Bulletin 65 Supplement C (2001), IEEE 1528-2003 and in applicable Industry Canada Radio Standards Specifications (RSS); for North American frequency bands only.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them. Test results reported herein relate only to the item(s) tested.

*PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.*

  
\_\_\_\_\_  
Randy Ortanez  
President



| FCC ID: EROUFO-WPR-3ER        |                         | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
|-------------------------------|-------------------------|---|--|---------------------------------|
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10 | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |  | Page 1 of 28                    |

## T A B L E   O F   C O N T E N T S

---

|    |  |    |
|----|--|----|
| 1  | INTRODUCTION .....                         | 3  |
| 2  | TEST SITE LOCATION .....                   | 4  |
| 3  | SAR MEASUREMENT SETUP .....                | 5  |
| 4  | DASY E-FIELD PROBE SYSTEM .....            | 7  |
| 5  | PROBE CALIBRATION PROCESS .....            | 8  |
| 6  | PHANTOM AND EQUIVALENT TISSUES.....        | 9  |
| 7  | DOSIMETRIC ASSESSMENT & PHANTOM SPECS..... | 10 |
| 8  | TEST CONFIGURATION POSITIONS .....         | 11 |
| 9  | NOTEBOOK PCS AND USB DONGLES .....         | 13 |
| 10 | RF EXPOSURE LIMITS .....                   | 14 |
| 11 | MEASUREMENT UNCERTAINTIES .....            | 15 |
| 12 | SYSTEM VERIFICATION.....                   | 16 |
| 13 | FCC 3G MEASUREMENT PROCEDURES.....         | 18 |
| 14 | SAR DATA SUMMARY .....                     | 19 |
| 15 | EQUIPMENT LIST.....                        | 20 |
| 16 | CONCLUSION.....                            | 21 |
| 17 | REFERENCES .....                           | 22 |
| 18 | SAR TEST SETUP PHOTOGRAPHS.....            | 24 |

|                               |   |   |   |                                 |
|-------------------------------|---|---|---|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 2 of 28                    |

# 1 INTRODUCTION

The FCC has adopted the guidelines for evaluating the environmental effects of radio frequency (RF) radiation in ET Docket 93-62 on Aug. 6, 1996 to protect the public and workers from the potential hazards of RF emissions due to FCC-regulated portable devices.[1]

The safety limits used for the environmental evaluation measurements are based on the criteria published by the American National Standards Institute (ANSI) for localized specific absorption rate (SAR) in IEEE/ANSI C95.1-1992 Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz[2] and Health Canada RF Exposure Guidelines Safety Code 6 [26]. The measurement procedure described in IEEE/ANSI C95.3-2002 Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave [3] is used for guidance in measuring the Specific Absorption Rate (SAR) due to the RF radiation exposure from the Equipment Under Test (EUT). These criteria for SAR evaluation are similar to those recommended by the International Committee for Non-Ionizing Radiation Protection (ICNIRP) in Biological Effects and Exposure Criteria for Radiofrequency Electromagnetic Fields," Report No. Vol 74. SAR is a measure of the rate of energy absorption due to exposure to an RF transmitting source. SAR values have been related to threshold levels for potential biological hazards.

## 1.1 SAR Definition

Specific Absorption Rate is defined as the time derivative (rate) of the incremental energy (dU) absorbed by (dissipated in) an incremental mass (dm) contained in a volume element (dV) of a given density ( $\rho$ ). It is also defined as the rate of RF energy absorption per unit mass at a point in an absorbing body (see Fig. 1-1).

$$SAR = \frac{d}{d t} \left( \frac{d U}{d m} \right) = \frac{d}{d t} \left( \frac{d U}{\rho d v} \right)$$

**Figure 1-1**  
**SAR Mathematical Equation**

**SAR is expressed in units of Watts per Kilogram (W/kg).**

$$SAR = \frac{\sigma \cdot E^2}{\rho}$$

where:

- $\sigma$  = conductivity of the tissue-simulating material (S/m)  
 $\rho$  = mass density of the tissue-simulating material (kg/m<sup>3</sup>)  
E = Total RMS electric field strength (V/m)

NOTE: The primary factors that control rate of energy absorption were found to be the wavelength of the incident field in relation to the dimensions and geometry of the irradiated organism, the orientation of the organism in relation to the polarity of field vectors, the presence of reflecting surfaces, and whether conductive contact is made by the organism with a ground plane.[6]

|                               |   |   |   |                                 |
|-------------------------------|---|---|---|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 3 of 28                    |

## 2 TEST SITE LOCATION


### 2.1 INTRODUCTION

The map at the right shows the location of the PCTEST LABORATORY in Columbia, Maryland. It is in proximity to the FCC Laboratory, the Baltimore-Washington International (BWI) airport, the city of Baltimore and Washington, DC (See Figure 2).


These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49' 38" W longitude. The facility is 1.5 miles north of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4 on January 27, 2006 and Industry Canada.

### 2.2 Test Facility / Accreditations:

Measurements were performed at an independent accredited PCTEST Engineering Lab located in Columbia, MD 21045, U.S.A.



- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing-Aid Compatibility (HAC), CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (IC-2451).
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and all Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (IC-2451) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS and CDMA, and EVDO mobile phones.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO Data, CDMA 1xRTT Data



**Figure 2-1**  
Map of the Greater Baltimore and Metropolitan Washington, D.C. area

| FCC ID: EROUO-WPR-3ER       |  PCTEST<br>Engineering Laboratory, Inc. | SAR COMPLIANCE REPORT                                   |  CRESTRON | Reviewed by:<br>Quality Manager |
|-----------------------------|--|---|--|---------------------------------|
| Filename:<br>0Y11301928.ERO | Test Dates:<br>11/30/10  | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |  | Page 4 of 28                    |

## 3 SAR MEASUREMENT SETUP


### 3.1 Robotic System

Measurements are performed using the DASY4 automated dosimetric assessment system. The DASY4 is made by Schmid & Partner Engineering AG (SPEAG) in Zurich, Switzerland and consists of high precision robotics system (Staubli), robot controller, Pentium 4 computer, near-field probe, probe alignment sensor, and the generic twin phantom containing the brain equivalent material. The robot is a six-axis industrial robot performing precise movements to position the probe to the location (points) of maximum electromagnetic field (EMF) (see Figure 3-1).

### 3.2 System Hardware

A cell controller system contains the power supply, robot controller, teach pendant (Joystick), and a remote control used to drive the robot motors. The PC consists of the Gateway Pentium 4 2.53 GHz computer with Windows XP system and SAR Measurement Software DASY4, A/D interface card, monitor, mouse, and keyboard. The Staubli Robot is connected to the cell controller to allow software manipulation of the robot. A data acquisition electronic (DAE) circuit that performs the signal amplification, signal multiplexing, AD-conversion, offset measurements, mechanical surface detection, collision detection, etc. is connected to the Electro-optical coupler (EOC). The EOC performs the conversion from the optical into digital electric signal of the DAE and transfers data to the PC plug-in card.

### 3.3 System Electronics



**Figure 3-1**  
**SAR Measurement System Setup**

The DAE4 consists of a highly sensitive electrometer-grade preamplifier with auto-zeroing, a channel and gain-switching multiplexer, a fast 16 bit AD-converter and a command decoder and control logic unit. Transmission to the PC-card is accomplished through an optical downlink for data and status information and an optical uplink for commands and clock lines. The mechanical probe mounting device includes two different sensor systems for frontal and sidewise probe contacts. They are also used for mechanical surface detection and probe collision detection. The robot uses its own controller with a built in VME-bus computer. The system is described in detail in [7].

|                               |                         |   |  |                                 |
|-------------------------------|-------------------------|---|--|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |                         | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10 | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |  | Page 5 of 28                    |

### 3.4 Automated Test System Specifications

#### Positioner

Robot: Stäubli Unimation Corp. Robot RX60L  
 Repeatability: 0.02 mm  
 No. of Axes: 6

#### Data Acquisition Electronic System (DAE)

##### Cell Controller

Processor: Pentium 4  
 Clock Speed: 2.53 GHz  
 Operating System: Windows XP Professional

##### Data Converter

Features: Signal Amplifier, multiplexer, A/D converter & control logic  
 Software: DASY4, SEMCAD software  
 Connecting Lines: Optical Downlink for data and status info  
 Optical upload for commands and clock

##### PC Interface Card

Function: 166MHz low power Pentium MMX 32MB chipdisk  
 Link to DAE  
 16-bit A/D converter for surface detection system  
 Two Serial & Ethernet link to robotics  
 Direct emergency stop output for robot

##### Phantom

Type: SAM Twin Phantom (V4.0)  
 Shell Material: Composite  
 Thickness:  $2.0 \pm 0.2$  mm



**Figure 3-2**  
**DASY4 SAR Measurement System**

|                               |   |   |   |                                 |
|-------------------------------|---|---|---|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 6 of 28                    |

## 4 DASY E-FIELD PROBE SYSTEM

### 4.1 Probe Measurement System



Figure 4-1  
SAR System

The SAR measurements were conducted with the dosimetric probe EX3DV4, designed in the classical triangular configuration [7] (see Figure 4-3) and optimized for dosimetric evaluation. The probe is constructed using the thick film technique; with printed resistive lines on ceramic substrates. The probe is equipped with an optical multi-fiber line ending at the front of the probe tip. It is connected to the EOC box on the robot arm and provides an automatic detection of the phantom surface. Half of the fibers are connected to a pulsed infrared transmitter, the other half to a synchronized receiver. As the probe approaches the surface, the reflection from the surface produces a coupling from the transmitting to the receiving fibers. This reflection increases first during the approach, reaches maximum and then decreases. If the probe is flatly touching the surface, the coupling is zero. The distance of the coupling maximum to the surface is independent of the surface reflectivity and largely independent of the surface to probe angle. The DASY4 software reads the reflection during a software approach

and looks for the maximum using a 2nd order fitting (see Figure 5-1). The approach is stopped at reaching the maximum.

### 4.2 Probe Specifications

|                          |   |
|--------------------------|---|
| <b>Model:</b>            | ES3DV3, EX3DV4  |
| <b>Frequency Range:</b>  | 10 MHz – 6.0 GHz (EX3DV4)<br>10 MHz – 4 GHz (ES3DV3)  |
| <b>Calibration:</b>      | In brain and muscle simulating tissue at Frequencies from 835 up to 5800MHz                       |
| <b>Linearity:</b>        | ± 0.2 dB (30 MHz to 6 GHz) for EX3DV4<br>± 0.2 dB (30 MHz to 4 GHz) for ES3DV3                    |
| <b>Dynamic Range:</b>    | 10 mW/kg – 100 W/kg   |
| <b>Probe Length:</b>     | 330 mm  |
| <b>Probe Tip Length:</b> | 20 mm   |
| <b>Body Diameter:</b>    | 12 mm   |
| <b>Tip Diameter:</b>     | 2.5 mm (3.9mm for ES3DV3)   |
| <b>Tip-Center:</b>       | 1 mm (2.0 mm for ES3DV3)  |
| <b>Application:</b>      | SAR Dosimetry Testing<br>Compliance tests of mobile phones<br>Dosimetry in strong gradient fields |



Figure 4-2  
Near-Field Probe



Figure 4-3  
Triangular Probe Configuration

|                               |                         |   |  |                                 |
|-------------------------------|-------------------------|---|--|---------------------------------|
| FCC ID: EROUO-WPR-3ER         |                         | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10 | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |  | Page 7 of 28                    |

## 5

## PROBE CALIBRATION PROCESS

### 5.1 Dosimetric Assessment Procedure

Each E-Probe/Probe amplifier combination has unique calibration parameters. A TEM cell calibration procedure is conducted to determine the proper amplifier settings to enter in the probe parameters. The amplifier settings are determined for a given frequency by subjecting the probe to a known E-field density (1 mW/cm<sup>2</sup>) using an RF Signal generator, TEM cell, and RF Power Meter.

### 5.2 Free Space Assessment

The free space E-field from amplified probe outputs is determined in a test chamber. This calibration can be performed in a TEM cell if the frequency is below 1 GHz and in a waveguide or other methodologies above 1 GHz for free space. For the free space calibration, the probe is placed in the volumetric center of the cavity and at the proper orientation with the field. The probe is rotated 360 degrees until the three channels show the maximum reading. The power density readings equates to 1 mW/cm<sup>2</sup>.

### 5.3 Temperature Assessment

E-field temperature correlation calibration is performed in a flat phantom filled with the appropriate simulated brain tissue. The E-field in the medium correlates with the temperature rise in the dielectric medium. For temperature correlation calibration a RF transparent thermistor-based temperature probe is used in conjunction with the E-field probe.

$$\text{SAR} = C \frac{\Delta T}{\Delta t}$$

where:

$\Delta t$  = exposure time (30 seconds),

$C$  = heat capacity of tissue (brain or muscle),

$\Delta T$  = temperature increase due to RF exposure.

$$\text{SAR} = \frac{|E|^2 \cdot \sigma}{\rho}$$

where:

$\sigma$  = simulated tissue conductivity,

$\rho$  = Tissue density (1.25 g/cm<sup>3</sup> for brain tissue)

SAR is proportional to  $\Delta T/\Delta t$ , the initial rate of tissue heating, before thermal diffusion takes place. Now it's possible to quantify the electric field in the simulated tissue by equating the thermally derived SAR to the E-field;




Figure 5-1 E-Field and Temperature measurements at 900MHz [7]




Figure 5-2 E-Field and temperature measurements at 1.9GHz [7]

|                               |                         |   |  |                                 |
|-------------------------------|-------------------------|---|--|---------------------------------|
| FCC ID: EROUO-WPR-3ER         |                         | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10 | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |  | Page 8 of 28                    |

## 6

## PHANTOM AND EQUIVALENT TISSUES

### 6.1 SAM Phantoms



Figure 6-1  
SAM Phantoms

The SAM Twin Phantom V4.0 is constructed of a fiberglass shell integrated in a wooden table. The shape of the shell is based on data from an anatomical study designed to determine the maximum exposure in at least 90% of all users [11][12]. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region. A cover prevents the evaporation of the liquid. Reference markings on the Phantom allow the complete setup of all predefined phantom positions and measurement grids by manually teaching three points in the robot. (see Fig. 5.1)

### 6.2 Brain & Muscle Simulating Mixture Characterization



Figure 6-2  
Head Simulated

The brain and muscle mixtures consist of a viscous gel using hydroxethylcellulose (HEC) gelling agent and saline solution (see Table 6-1). Preservation with a bactericide is added and visual inspection is made to make sure air bubbles are not trapped during the mixing process. The mixture is calibrated to obtain proper dielectric constant (permittivity) and conductivity of the desired tissue. The head tissue dielectric parameters recommended by the IEEE SCC-34/SC-2 have been incorporated in the following table. Other head and body tissue parameters that have not been specified in IEEE-1528 are derived from the tissue dielectric parameters computed from the 4-Cole-Cole equations. The mixture characterizations used for the brain and muscle tissue simulating liquids are according to the data by C. Gabriel and G. Hartsgrave [13]. (See Table 6-1)

Table 6-1  
Composition of the Brain & Muscle Tissue Equivalent Matter

| Frequency (MHz)                        | 300   | 450   | 835   | 900   | 1450  | 1800  | 1900  | 1950  | 2000  | 2100  | 2450  | 3000  |       |       |       |       |       |
|--|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| Recipe #                               | 1     | 1     | 3     | 1     | 1     | 2     | 3     | 1     | 1     | 2     | 4     | 1     | 1     | 2     | 2     | 3     | 2     |
| Ingredient: (% by weight)              |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| 1,2-Propanediol                        |       |       |       |       | 64.81 |       |       |       |       |       |       |       |       |       |       |       |       |
| Bactericide                            | 0.19  | 0.19  | 0.50  | 0.10  | 0.10  |       | 0.50  |       |       | 0.50  |       |       |       |       |       |       | 0.50  |
| Diacetin                               |       |       | 48.90 |       |       | 49.20 |       |       | 49.43 |       |       |       |       |       |       |       | 48.75 |
| DGBE                                   |       |       |       |       |       | 45.41 | 47.00 | 13.84 | 44.92 |       | 44.94 | 13.84 | 45.00 | 50.00 | 50.00 | 7.99  | 7.99  |
| HEC                                    | 0.98  | 0.98  |       | 1.00  | 1.00  |       |       |       |       |       |       |       |       |       |       |       |       |
| NaCl                                   | 5.95  | 3.95  | 1.70  | 1.45  | 1.48  | 0.79  | 1.10  | 0.67  | 0.36  | 0.35  | 0.18  | 0.64  | 0.18  | 0.35  |       | 0.16  | 0.16  |
| Sucrose                                | 55.32 | 56.32 |       | 57.00 | 56.50 |       |       |       |       |       |       |       |       |       |       |       |       |
| Triton X-100                           |       |       |       |       |       |       |       | 30.45 |       |       | 30.45 |       |       |       |       | 19.97 | 19.97 |
| Water                                  | 37.36 | 38.56 | 48.90 | 40.43 | 40.92 | 34.40 | 49.20 | 53.80 | 52.64 | 55.36 | 54.90 | 49.43 | 54.90 | 55.36 | 55.00 | 50.00 | 71.88 |
| Measured dielectric parameters         |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| $\epsilon'_r$                          | 46.00 | 43.4  | 44.3  | 41.6  | 41.2  | 41.8  | 42.7  | 40.9  | 39.3  | 41    | 40.4  | 39.2  | 38.9  | 41    | 40.1  | 37    | 36.8  |
| $\sigma(S/m)$                          | 0.86  | 0.85  | 0.9   | 0.9   | 0.98  | 0.97  | 0.99  | 1.21  | 1.39  | 1.38  | 1.4   | 1.4   | 1.42  | 1.38  | 1.41  | 1.4   | 1.31  |
| Temp. (°C)                             | 22    | 22    | 20    | 22    | 22    | 22    | 20    | 22    | 22    | 21    | 22    | 20    | 21    | 21    | 20    | 22    | 20    |
| Target dielectric parameters (Table 2) |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |       |
| $\epsilon'_r$                          | 45.30 | 43.50 | 41.5  |       | 41.50 | 40.5  |       |       |       | 40.0  |       |       | 39.80 |       | 39.2  |       | 37.9  |
| $\sigma(S/m)$                          | 0.87  | 0.87  | 0.9   |       | 0.97  | 1.2   |       |       |       | 1.4   |       |       | 1.49  |       | 1.8   |       | 2.46  |

NOTE—Multiple columns for any single frequency are optional recipes. Recipe #, reference: 1 (Karak et al. [B85]), 2 (Vigness [B145]), 3 (Payman and Gabriel [B119]), 4 (Fukusaga et al. [B50]).

\*The formulas containing Triton X-100 and corresponding measured parameters are under review and verification.

|                               |                         |   |  |                                 |
|-------------------------------|-------------------------|---|--|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |                         | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10 | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |  | Page 9 of 28                    |

## 7.1 Measurement Procedure

The evaluation was performed using the following procedure:

1. The SAR measurement was taken at a selected spatial reference point to monitor power variations during testing. This fixed point was measured and used as a reference value.
2. The SAR distribution at the exposed side of the head was measured at a distance of 3.0mm from the inner surface of the shell. The area covered the entire dimension of the head and the horizontal grid spacing was 15mm x 15mm.
3. Based on the area scan data, the area of the maximum absorption was determined by spline interpolation. Around this point, a volume of 32mm x 32mm x 30mm (fine resolution volume scan, zoom scan) was assessed by measuring 5 x 5 x 7 points. On this basis of this data set, the spatial peak SAR value was evaluated with the following procedure (see Figure 7-1):
  - a. The data at the surface was extrapolated, since the center of the dipoles is 2.7mm away from the tip of the probe and the distance between the surface and the lowest measuring point is 1.2mm. The extrapolation was based on a least square algorithm [15]. A polynomial of the fourth order was calculated through the points in z-axes. This polynomial was then used to evaluate the points between the surface and the probe tip.
  - b. The maximum interpolated value was searched with a straight-forward algorithm. Around this maximum the SAR values averaged over the spatial volumes (1g or 10g) were computed using the 3D-Spline interpolation algorithm. The 3D-spline is composed of three one-dimensional splines with the "Not a knot" condition (in x, y, and z directions) [15][16]. The volume was integrated with the trapezoidal algorithm. One thousand points (10 x 10 x 10) were interpolated to calculate the average.
  - c. All neighboring volumes were evaluated until no neighboring volume with a higher average value was found.
4. The SAR reference value, at the same location as step 1, was re-measured. If the value changed by more than 5%, the evaluation is repeated.



**Figure 7-1**  
**Sample SAR Area Scan**

## 7.2 Specific Anthropomorphic Mannequin (SAM) Specifications

The phantom for handset SAR assessment testing is a low-loss dielectric shell, with shape and dimensions derived from the anthropometric data of the 90th percentile adult male head dimensions as tabulated by the US Army. The SAM Twin Phantom shell is bisected along the mid-sagittal plane into right and left halves (see Figure 7-2). The perimeter sidewalls of each phantom halves are extended to allow filling with liquid to a depth that is sufficient to minimize reflections from the upper surface. The liquid depth is maintained at a minimum depth of 15cm to minimize reflections from the upper surface.



**Figure 7-2**  
**SAM Twin Phantom Shell**

|                               |   |   |   |                                 |
|-------------------------------|---|---|---|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 10 of 28                   |

## 8 TEST CONFIGURATION POSITIONS

### 8.1 Body Holster /Belt Clip Configurations

Body-worn operating configurations are tested with the belt-clips and holsters attached to the device and positioned against a flat phantom in a normal use configuration (see Figure 9-5). A device with a headset output is tested with a headset connected to the device.

Accessories for Body-worn operation configurations are divided into two categories: those that do not contain metallic components and those that do contain metallic components. When multiple accessories that do not contain metallic components are supplied with the device, the device is tested with only the accessory that dictates the closest spacing to the body. Then multiple accessories that contain metallic components are tested with the device with each accessory. If multiple accessories share an identical metallic component (i.e. the same metallic belt-clip used with different holsters with no other metallic components) only the accessory that dictates the closest spacing to the body is tested.

Body-worn accessories may not always be supplied or available as options for some devices intended to be authorized for body-worn use. In this case, a test configuration with a separation distance between the back of the device and the flat phantom is used. Test position spacing was documented. Transmitters that are designed to operate in front of a person's face, as in push-to-talk configurations, are tested for SAR compliance with the front of the device positioned to face the flat phantom in brain fluid. For devices that are carried next to the body such as a shoulder, waist or chest-worn transmitters, SAR compliance is tested with the accessories, including headsets and microphones, attached to the device and positioned against a flat phantom in a normal use configuration.

### 8.2 SAR Testing with IEEE 802.11 a/b/g Transmitters (if applicable)

Normal network operating configurations are not suitable for measuring the SAR of 802.11 a/b/g transmitters. Unpredictable fluctuations in network traffic and antenna diversity conditions can introduce undesirable variations in SAR results. The SAR for these devices should be measured using chipset based test mode software to ensure the results are consistent and reliable.

#### 8.2.1 General Device Setup

Chipset based test mode software is hardware dependent and generally varies among manufacturers. The device operating parameters established in test mode for SAR measurements must be identical to those programmed in production units, including output power levels, amplifier gain settings and other RF performance tuning parameters. The test frequencies should correspond to actual channel frequencies defined for domestic use. SAR for devices with switched diversity should be measured with only one antenna transmitting at a time during each SAR measurement, according to a fixed modulation and data rate. The same data pattern should be used for all measurements.



#### 8.2.2 Frequency Channel Configurations<sup>22</sup>

802.11 a/b/g and 4.9 GHz operating modes are tested independently according to the service requirements in each frequency band. 802.11 b/g modes are tested on channels 1, 6 and 11. 802.11a is tested for UNII operations on channels 36 and 48 in the 5.15-5.25 GHz band; channels 52 and 64 in the 5.25-5.35 GHz band; channels 104, 116, 124 and 136 in the 5.470-5.725 GHz band; and channels 149 and 161 in the 5.8 GHz band. When 5.8 GHz §15.247 is also available, channels 149, 157 and 165 should be tested instead of the UNII channels. 4.9 GHz is tested on channels 1, 10 and 5 or 6, whichever has the higher output power, for 5 MHz channels; channels 11, 15 and 19 for 10 MHz channels; and channels 21 and 25 for 20 MHz channels.

|                               |   |   |   |                                 |
|-------------------------------|---|---|---|---------------------------------|
| FCC ID: EROUO-WPR-3ER         |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 11 of 28                   |

These are referred to as the “default test channels”. 802.11g mode was evaluated only if the output power was 0.25 dB higher than the 802.11b mode.

**Table 8-1**  
**802.11 Test Channels per FCC Requirements**

| Mode            | GHz     | Channel | Turbo Channel  | “Default Test Channels” |                 | UNII |
|-----------------|---------|---------|----------------|-------------------------|-----------------|------|
|                 |         |         |                | §15.247                 | 802.11b 802.11g |      |
| 802.11 b/g      | 2.412   | 1       |                | ✓                       | ✓               |      |
|                 | 2.437   | 6       | 6              | ✓                       | ✓               |      |
|                 | 2.462   | 11      |                | ✓                       | ✓               |      |
| 802.11a         | 5.18    | 36      |                |                         |                 | ✓    |
|                 | 5.20    | 40      | 42 (5.21 GHz)  |                         |                 | *    |
|                 | 5.22    | 44      |                |                         |                 | *    |
|                 | 5.24    | 48      | 50 (5.25 GHz)  |                         |                 | ✓    |
|                 | 5.26    | 52      |                |                         |                 | ✓    |
|                 | 5.28    | 56      | 58 (5.29 GHz)  |                         |                 | *    |
|                 | 5.30    | 60      |                |                         |                 | *    |
|                 | 5.32    | 64      |                |                         |                 | ✓    |
|                 | 5.500   | 100     | Unknown        |                         |                 | *    |
|                 | 5.520   | 104     |                |                         |                 | ✓    |
|                 | 5.540   | 108     |                |                         |                 | *    |
|                 | 5.560   | 112     |                |                         |                 | *    |
|                 | 5.580   | 116     |                |                         |                 | ✓    |
|                 | 5.600   | 120     |                |                         |                 | *    |
|                 | 5.620   | 124     |                |                         |                 | ✓    |
|                 | 5.640   | 128     |                |                         |                 | *    |
|                 | 5.660   | 132     |                |                         |                 | *    |
|                 | 5.680   | 136     |                |                         |                 | ✓    |
|                 | 5.700   | 140     |                |                         |                 | *    |
| UNII or §15.247 | 5.745   | 149     |                | ✓                       | ✓               |      |
|                 | 5.765   | 153     | 152 (5.76 GHz) |                         | *               | *    |
|                 | 5.785   | 157     |                | ✓                       |                 | *    |
|                 | 5.805   | 161     |                |                         | *               | ✓    |
|                 | §15.247 | 5.825   | 165            | ✓                       |                 |      |

### 8.3 EROCWD1015 Test Configurations

EROCWD1015 SAR compliance tests were performed using test configurations per KDB Inquiry 679720. It was confirmed with the applicant that the device is capable of sustaining 100% transmission for the duration of the SAR tests.

The primary function of the EUT is for wireless remote control of home automation functions such as lighting, heating and media.

|                               |   |   |   |                                 |
|-------------------------------|---|---|---|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 12 of 28                   |

## 9.1 SAR for Notebooks and Lap-touching Devices

Lap-touching devices that have transmitting antennas located less than 20 cm from the lap of the user require routine SAR evaluation. Such devices are considered portable and are capable of being held to the body. Devices are to be setup touching the phantom and are configured with maximum output power during SAR assessment for a worst-case SAR evaluation.




**Figure 9-1**  
Notebook Setup for SAR

## 9.2 Positioning for Convertible and Slate Tablet Computers




**Figure 9-2**  
Tablet Computer Form Factors



**Figure 9-3**  
Tablet PC Body SAR

KDB 447498. Tablet (notepad) computers are tested in a lap-held position with the bottom of the computer in direct contact against a flat phantom for all user-enabled portrait and landscape positions.

## 9.3 SAR test procedure for USB Dongles



Note: these are USB connector orientations on laptop computers; USB dongles have the reverse configuration for plugging into the corresponding laptop computers.

**Figure 9-4**  
USB Dongle Test Configurations

KDB 447498. USB orientations (see Figure 9-4) with a device to phantom separation distance of 5 mm or less, according to KDB 447498 requirements. Current generation laptop computers should be used to ensure proper measurement distances. The same test separation distance should be used for all frequency bands and modes in each USB orientation. The typical Horizontal-Up USB connection (A), found in the majority of laptop computers, must be tested using an appropriate laptop computer. A laptop with either Vertical-Front (C) or Vertical-Back (D) USB connection should be used to test one of the vertical USB orientations. If laptop computers are not available for testing the Horizontal-Down (B) or the remaining Vertical USB orientation, a short and high quality USB cable (12 inches or less) may be used for testing these other orientations. It should be ensured that the USB cable does not affect device radiating characteristics and output power of the dongle.

|                               |                         |   |  |                                 |
|-------------------------------|-------------------------|---|--|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |                         | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10 | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |  | Page 13 of 28                   |

## 10 RF EXPOSURE LIMITS

### 10.1 Uncontrolled Environment

UNCONTROLLED ENVIRONMENTS are defined as locations where there is the exposure of individuals who have no knowledge or control of their exposure. The general population/uncontrolled exposure limits are applicable to situations in which the general public may be exposed or in which persons who are exposed as a consequence of their employment may not be made fully aware of the potential for exposure or cannot exercise control over their exposure. Members of the general public would come under this category when exposure is not employment-related; for example, in the case of a wireless transmitter that exposes persons in its vicinity.

### 10.2 Controlled Environment

CONTROLLED ENVIRONMENTS are defined as locations where there is exposure that may be incurred by persons who are aware of the potential for exposure, (i.e. as a result of employment or occupation). In general, occupational/controlled exposure limits are applicable to situations in which persons are exposed as a consequence of their employment, who have been made fully aware of the potential for exposure and can exercise control over their exposure. This exposure category is also applicable when the exposure is of a transient nature due to incidental passage through a location where the exposure levels may be higher than the general population/uncontrolled limits, but the exposed person is fully aware of the potential for exposure and can exercise control over his or her exposure by leaving the area or by some other appropriate means.

**Table 10-1**  
**SAR Human Exposure Specified in ANSI/IEEE C95.1-1992 and Health Canada Safety Code 6**

| HUMAN EXPOSURE LIMITS                           |   |   |
|---|---|---|
|   | UNCONTROLLED ENVIRONMENT<br><i>General Population</i><br>(W/kg) or (mW/g) | CONTROLLED ENVIRONMENT<br><i>Occupational</i><br>(W/kg) or (mW/g) |
| SPATIAL PEAK SAR<br>Brain                       | 1.6   | 8.0   |
| SPATIAL AVERAGE SAR<br>Whole Body               | 0.08  | 0.4   |
| SPATIAL PEAK SAR<br>Hands, Feet, Ankles, Wrists | 4.0   | 20  |

- The Spatial Peak value of the SAR averaged over any 1 gram of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.
- The Spatial Average value of the SAR averaged over the whole body.
- The Spatial Peak value of the SAR averaged over any 10 grams of tissue (defined as a tissue volume in the shape of a cube) and over the appropriate averaging time.

|                               |   |   |   |                                 |
|-------------------------------|---|---|---|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 14 of 28                   |

## 11 MEASUREMENT UNCERTAINTIES

| a   | b              | c          | d           | e= f(d,k) | f              | g              | h = c x f/e | i = c x g/e | k              |
|---|----------------|------------|-------------|-----------|----------------|----------------|-------------|-------------|----------------|
| Uncertainty Component   | IEEE 1528 Sec. | Tol. (± %) | Prob. Dist. | Div.      | c <sub>i</sub> | c <sub>i</sub> | 1gm         | 10gms       | v <sub>i</sub> |
| <b>Measurement System</b>   |                |            |             |           |                |                |             |             |                |
| Probe Calibration   | E2.1           | 6.6        | N           | 1         | 1.0            | 1.0            | 6.6         | 6.6         | ∞              |
| Axial Isotropy  | E2.2           | 0.25       | N           | 1         | 0.7            | 0.7            | 0.2         | 0.2         | ∞              |
| Hemispherical Isotropy  | E2.2           | 1.3        | N           | 1         | 1.0            | 1.0            | 1.3         | 1.3         | ∞              |
| Boundary Effect   | E2.3           | 0.4        | N           | 1         | 1.0            | 1.0            | 0.4         | 0.4         | ∞              |
| Linearity   | E2.4           | 0.3        | N           | 1         | 1.0            | 1.0            | 0.3         | 0.3         | ∞              |
| System Detection Limits   | E2.5           | 5.1        | N           | 1         | 1.0            | 1.0            | 5.1         | 5.1         | ∞              |
| Readout Electronics   | E2.6           | 1.0        | N           | 1         | 1.0            | 1.0            | 1.0         | 1.0         | ∞              |
| Response Time   | E2.7           | 0.8        | R           | 1.73      | 1.0            | 1.0            | 0.5         | 0.5         | ∞              |
| Integration Time  | E2.8           | 2.6        | R           | 1.73      | 1.0            | 1.0            | 1.5         | 1.5         | ∞              |
| RF Ambient Conditions   | E6.1           | 3.0        | R           | 1.73      | 1.0            | 1.0            | 1.7         | 1.7         | ∞              |
| Probe Positioner Mechanical Tolerance   | E6.2           | 0.4        | R           | 1.73      | 1.0            | 1.0            | 0.2         | 0.2         | ∞              |
| Probe Positioning w/ respect to Phantom                                       | E6.3           | 2.9        | R           | 1.73      | 1.0            | 1.0            | 1.7         | 1.7         | ∞              |
| Extrapolation, Interpolation & Integration algorithms for Max. SAR Evaluation | E5             | 1.0        | R           | 1.73      | 1.0            | 1.0            | 0.6         | 0.6         | ∞              |
| <b>Test Sample Related</b>  |                |            |             |           |                |                |             |             |                |
| Test Sample Positioning   | E4.2           | 6.0        | N           | 1         | 1.0            | 1.0            | 6.0         | 6.0         | 287            |
| Device Holder Uncertainty   | E4.1           | 3.32       | R           | 1.73      | 1.0            | 1.0            | 1.9         | 1.9         | ∞              |
| Output Power Variation - SAR drift measurement                                | 6.6.2          | 5.0        | R           | 1.73      | 1.0            | 1.0            | 2.9         | 2.9         | ∞              |
| <b>Phantom &amp; Tissue Parameters</b>  |                |            |             |           |                |                |             |             |                |
| Phantom Uncertainty (Shape & Thickness tolerances)                            | E3.1           | 4.0        | R           | 1.73      | 1.0            | 1.0            | 2.3         | 2.3         | ∞              |
| Liquid Conductivity - deviation from target values                            | E3.2           | 5.0        | R           | 1.73      | 0.64           | 0.43           | 1.8         | 1.2         | ∞              |
| Liquid Conductivity - measurement uncertainty                                 | E3.3           | 3.8        | N           | 1         | 0.64           | 0.43           | 2.4         | 1.6         | 6              |
| Liquid Permittivity - deviation from target values                            | E3.2           | 5.0        | R           | 1.73      | 0.60           | 0.49           | 1.7         | 1.4         | ∞              |
| Liquid Permittivity - measurement uncertainty                                 | E3.3           | 4.5        | N           | 1         | 0.60           | 0.49           | 2.7         | 2.2         | 6              |
| <b>Combined Standard Uncertainty (k=1)</b>                                    | RSS            |            |             |           |                |                | 12.4        | 12.0        | 299            |
| <b>Expanded Uncertainty</b><br>(95% CONFIDENCE LEVEL)                         | k=2            |            |             |           |                |                | 24.7        | 24.0        |                |

The above measurement uncertainties are according to IEEE Std. 1528-2003

|                               |   |   |   |                                 |
|-------------------------------|---|---|---|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 15 of 28                   |

## 12 SYSTEM VERIFICATION

### 12.1 Tissue Verification

Table 12-1  
Measured Tissue Properties

| Calibrated Date: | Tissue Type | Measured Frequency (MHz) | Measured Conductivity, $\sigma$ (S/m) | Measured Dielectric Constant, $\epsilon$ | TARGET Conductivity, $\sigma$ (S/m) | TARGET Dielectric Constant, $\epsilon$ | % dev $\sigma$ | % dev $\epsilon$ |
|------------------|-------------|--------------------------|---------------------------------------|--|-------------------------------------|--|----------------|------------------|
| 11/30/2010       | 2450M       | 2401                     | 1.950                                 | 51.43                                    | <b>1.95</b>                         | <b>52.70</b>                           | 0.00%          | -2.41%           |
|                  |             | 2450                     | 2.015                                 | 51.29                                    | <b>1.95</b>                         | <b>52.70</b>                           | 3.33%          | -2.68%           |
|                  |             | 2499                     | 2.046                                 | 51.10                                    | <b>1.95</b>                         | <b>52.70</b>                           | 4.92%          | -3.04%           |

Note: KDB 450824 was ensured to be applied for probe calibration frequencies greater than or equal to 50 MHz of the DUT frequencies.

The above measured tissue parameters were used in the DASY software to perform interpolation via the DASY software to determine actual dielectric parameters at the test frequencies (per IEEE 1528 6.6.1.2). The SAR test plots may slightly differ from the table above since the DASY software rounds to three significant digits.

### 12.2 Measurement Procedure for Tissue verification

- 1) The network analyzer and probe system was configured and calibrated.
- 2) The probe was immersed in the sample which was placed in a nonmetallic container. Trapped air bubbles beneath the flange were minimized by placing the probe at a slight angle.
- 3) The complex admittance with respect to the probe aperture was measured
- 4) The complex relative permittivity  $\epsilon'$ , for example from the below equation (Pournaropoulos and Misra):

$$Y = \frac{j2\omega\epsilon_r'\epsilon_0}{[\ln(b/a)]^2} \int_a^b \int_a^b \int_0^\pi \cos\phi' \frac{\exp[-j\omega r(\mu_0\epsilon_r\epsilon_0)^{1/2}]}{r} d\phi' d\rho' d\rho$$

where  $Y$  is the admittance of the probe in contact with the sample, the primed and unprimed coordinates refer to source and observation points, respectively,  $r^2 = \rho^2 + \rho'^2 - 2\rho\rho'\cos\phi'$ ,  $\omega$  is the angular frequency, and  $j = \sqrt{-1}$ .

|                               |   |   |   |                                 |
|-------------------------------|---|---|---|---------------------------------|
| FCC ID: EROUO-WPR-3ER         |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 16 of 28                   |

## 12.3 Justification for Extended SAR Dipole Calibrations

Usage of SAR dipoles calibrated less than 2 years ago but more than 1 year ago were confirmed in maintaining return loss (< - 20 dB, within 20% of prior calibration) and impedance (within 5 ohm from prior calibration) requirements per extended calibrations in KDB Publication 450824:


| D2450V2 SN: 719     |                  |            |                        |                |
|---------------------|------------------|------------|------------------------|----------------|
| Date of Measurement | Return Loss (dB) | $\Delta$ % | Impedance ( $\Omega$ ) | $\Delta\Omega$ |
| 8/27/2009           | -28.6            |            | 53.4                   |                |
| 8/19/2010           | -27.5            | -3.8%      | 51                     | -2.4           |

## 12.4 Test System Verification

Prior to assessment, the system is verified to  $\pm 10\%$  of the manufacturer SAR measurements on the reference dipole at the time of calibration.

**Table 12-2**  
**System Verification Results**

| System Verification<br>TARGET & MEASURED |                |                  |                 |                        |           |             |                                   |                                     |   |               |
|--|----------------|------------------|-----------------|------------------------|-----------|-------------|-----------------------------------|-------------------------------------|---|---------------|
| Date:                                    | Amb. Temp (°C) | Liquid Temp (°C) | Input Power (W) | Tissue Frequency (MHz) | Dipole SN | Tissue Type | Measured SAR <sub>1g</sub> (W/kg) | 1 W Target SAR <sub>1g</sub> (W/kg) | 1 W Normalized SAR <sub>1g</sub> (W/kg) | Deviation (%) |
| 11/30/2010                               | 23.4           | 21.8             | 0.025           | 2450                   | 719       | Muscle      | 1.31                              | 51.400                              | 52.40                                   | 1.95%         |



**Figure 12-1**  
**System Verification Setup Diagram**



**Figure 12-2**  
**System Verification Setup Photo**

|                               |                         |   |  |                                 |
|-------------------------------|-------------------------|---|--|---------------------------------|
| FCC ID: EROUO-WPR-3ER         |                         | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10 | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |  | Page 17 of 28                   |

## 13 FCC 3G MEASUREMENT PROCEDURES

Power measurements were performed using a base station simulator under digital peak power.

### 13.1 Procedures Used to Establish RF Signal for SAR

The device was placed into a simulated call using a base station simulator in a shielded chamber. Such test signals offer a consistent means for testing SAR and are recommended for evaluating SAR [4]. SAR measurements were taken with a fully charged battery. In order to verify that the device was tested and maintained at full power, it was configured with the base station simulator. The SAR measurement software calculates a reference point at the start and end of the test to check for power drifts. If conducted power deviations of more than 5% occurred, the tests were repeated.

### 13.2 RF Conducted Powers:

ZigBee 802.15 Output Power

| Freq [MHz] | Channel | Device Power Level | Peak Power (dBm) |
|------------|---------|--------------------|------------------|
| 2405       | 11      | 6                  | 1.97             |
| 2410       | 12      | 16                 | 18.95            |
| 2415       | 13      | 16                 | 18.94            |
| 2420       | 14      | 16                 | 18.93            |
| 2425       | 15      | 16                 | 18.92            |
| 2430       | 16      | 16                 | 18.92            |
| 2435       | 17      | 16                 | 18.88            |
| 2440       | 18      | 16                 | 18.86            |
| 2445       | 19      | 16                 | 18.83            |
| 2450       | 20      | 16                 | 18.81            |
| 2455       | 21      | 16                 | 18.78            |
| 2460       | 22      | 16                 | 18.75            |
| 2465       | 23      | 16                 | 18.72            |
| 2470       | 24      | 10                 | 9.81             |
| 2475       | 25      | 6                  | 0.70             |
| 2480       | 26      | 2                  | -2.78            |



Figure 13-1  
Power Measurement Setup

|                               |                         |   |  |                                 |
|-------------------------------|-------------------------|---|--|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |                         | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>OY1011301928.ERO | Test Dates:<br>11/30/10 | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |  | Page 18 of 28                   |

## 14 SAR DATA SUMMARY

### 14.1 Body SAR Results

| MEASUREMENT RESULTS                      |     |        |              |       |         |                      |         |      |          |
|--|-----|--------|--------------|-------|---------|----------------------|---------|------|----------|
| FREQUENCY                                |     | Mode   | C_Power[dBm] |       | Phantom | Test Position        | Spacing | Side | SAR (1g) |
| MHz                                      | Ch. |        | Start        | End   |         |                      |         |      | (W/kg)   |
| 2410.00                                  | 12  | ZigBee | 18.95        | 18.89 | Body    | Top Edge             | 0.0 cm  | back | 0.225    |
| 2435.00                                  | 17  | ZigBee | 18.88        | 18.85 | Body    | Top Edge             | 0.0 cm  | back | 0.227    |
| 2465.00                                  | 23  | ZigBee | 18.72        | 18.72 | Body    | Top Edge             | 0.0 cm  | back | 0.249    |
| 2410.00                                  | 12  | ZigBee | 18.95        | 18.94 | Body    | Front Side           | 0.0 cm  | back | 1.180    |
| 2435.00                                  | 17  | ZigBee | 18.88        | 18.94 | Body    | Front Side           | 0.0 cm  | back | 1.040    |
| 2465.00                                  | 23  | ZigBee | 18.72        | 18.71 | Body    | Front Side           | 0.0 cm  | back | 1.000    |
| 2435.00                                  | 17  | ZigBee | 18.88        | 18.91 | Body    | Back Tilt            | 0.0 cm  | back | 0.104    |
| 2435.00                                  | 17  | ZigBee | 18.88        | 18.93 | Body    | Back Side            | 0.0 cm  | back | 0.070    |
| ANSI / IEEE C95.1 1992 - SAFETY LIMIT    |     |        |              |       |         | Body                 |         |      |          |
| Spatial Peak                             |     |        |              |       |         | 1.6 W/kg (mW/g)      |         |      |          |
| Uncontrolled Exposure/General Population |     |        |              |       |         | averaged over 1 gram |         |      |          |

Notes:

1. The test data reported are the worst-case SAR values with the positions set in a typical configuration. Test procedures used were according to FCC/OET Bulletin 65, Supplement C [July 2001].
2. All modes of operation were investigated, and worst-case results are reported.
3. Tissue parameters and temperatures are listed on the SAR plots.
4. Batteries are fully charged for all readings.
5. Liquid tissue depth was at least 15.0 cm
6. Device was tested using a fixed spacing.
7. SAR test configurations per KDB Inquiry 679720.

|                               |   |   |   |                                 |
|-------------------------------|---|---|---|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 19 of 28                   |

## 15 EQUIPMENT LIST

| Manufacturer       | Model       | Description                       | Cal Date   | Cal Interval | Cal Due    | Serial Number |
|--------------------|-------------|-----------------------------------|------------|--------------|------------|---------------|
| Agilent            | E8257D      | (250kHz-20GHz) Signal Generator   | 3/30/2010  | Annual       | 3/30/2011  | MY45470194    |
| Agilent            | 8753E       | (30kHz-6GHz) Network Analyzer     | 3/31/2010  | Annual       | 3/31/2011  | JP38020182    |
| Agilent            | 8648D       | Signal Generator                  | 4/1/2010   | Annual       | 4/1/2011   | 3629U00687    |
| Agilent            | E5515C      | Wireless Communications Tester    | 4/14/2010  | Annual       | 4/14/2011  | US41140256    |
| Agilent            | E5515C      | Wireless Communications Test Set  | 8/12/2010  | Annual       | 8/12/2011  | GB41450275    |
| Agilent            | 85070B      | Dielectric Probe Kit              | 8/22/2010  | Annual       | 8/22/2011  | US33020316    |
| Agilent            | 8648D       | (9kHz-4GHz) Signal Generator      | 10/11/2010 | Annual       | 10/11/2011 | 3613A00315    |
| Agilent            | E5515C      | Wireless Communications Test Set  | 10/11/2010 | Annual       | 10/11/2011 | GB46110872    |
| Agilent            | E5515C      | Wireless Communications Test Set  | 10/11/2010 | Annual       | 10/11/2011 | GB46310798    |
| Amplifier Research | 5S1G4       | 5W, 800MHz-4.2GHz                 | N/A        |              |            | 17042         |
| Anritsu            | MA2481A     | Power Sensor                      | 12/2/2009  | Annual       | 12/2/2010  | 5318          |
| Anritsu            | MA2481A     | Power Sensor                      | 12/2/2009  | Annual       | 12/2/2010  | 5821          |
| Anritsu            | MA2481A     | Power Sensor                      | 12/3/2009  | Annual       | 12/3/2010  | 5442          |
| Anritsu            | ML2438A     | Power Meter                       | 12/3/2009  | Annual       | 12/3/2010  | 1190013       |
| Anritsu            | ML2438A     | Power Meter                       | 12/3/2009  | Annual       | 12/3/2010  | 98150041      |
| Anritsu            | ML2438A     | Power Meter                       | 12/3/2009  | Annual       | 12/3/2010  | 1070030       |
| Anritsu            | MA2481A     | Power Sensor                      | 12/3/2009  | Annual       | 12/3/2010  | 8013          |
| Anritsu            | MA2481A     | Power Sensor                      | 12/3/2009  | Annual       | 12/3/2010  | 2400          |
| Aprel              | ALS-PR-DIEL | Dielectric Probe Kit              | N/A        |              | N/A        | 260-00959     |
| Gigatronics        | 80701A      | (0.05-18GHz) Power Sensor         | 10/11/2010 | Annual       | 10/11/2011 | 1833460       |
| Gigatronics        | 8651A       | Universal Power Meter             | 10/11/2010 | Annual       | 10/11/2011 | 8650319       |
| Index SAR          | IXTL-010    | Dielectric Measurement Kit        | N/A        |              | N/A        | N/A           |
| Index SAR          | IXTL-030    | 30MM TEM line for 6 GHz           | N/A        |              | N/A        | N/A           |
| Rohde & Schwarz    | NRV-Z32     | Peak Power Sensor (100uW-2W)      | 12/5/2008  | Biennial     | 12/5/2010  | 100155        |
| Rohde & Schwarz    | NRV-Z33     | Peak Power Sensor (1mW-20W)       | 12/5/2008  | Biennial     | 12/5/2010  | 100004        |
| Rohde & Schwarz    | SMIQ03B     | Signal Generator                  | 4/1/2010   | Annual       | 4/1/2011   | DE27259       |
| Rohde & Schwarz    | CMU200      | Base Station Simulator            | 6/21/2010  | Annual       | 6/21/2011  | 833855/0010   |
| Rohde & Schwarz    | CMW500      | LTE Radio Communication Tester    | 8/30/2010  | Annual       | 8/30/2011  | 100976        |
| Rohde & Schwarz    | CMU200      | Base Station Simulator            | 11/11/2010 | Annual       | 11/11/2011 | 836371/0079   |
| SPEAG              | D2450V2     | 2450 MHz SAR Dipole               | 1/8/2009   | Biennial     | 1/8/2011   | 797           |
| SPEAG              | D5GHzV2     | 5 GHz SAR Dipole                  | 1/15/2009  | Biennial     | 1/15/2011  | 1057          |
| SPEAG              | D835V2      | 835 MHz SAR Dipole                | 1/19/2009  | Biennial     | 1/19/2011  | 4d047         |
| SPEAG              | D1900V2     | 1900 MHz SAR Dipole               | 1/20/2009  | Biennial     | 1/20/2011  | 502           |
| SPEAG              | DAE4        | Dasy Data Acquisition Electronics | 1/22/2010  | Annual       | 1/22/2011  | 649           |
| SPEAG              | EX3DV4      | SAR Probe                         | 1/26/2010  | Annual       | 1/26/2011  | 3550          |
| SPEAG              | ES3DV3      | SAR Probe                         | 2/10/2010  | Annual       | 2/10/2011  | 3173          |
| SPEAG              | ES3DV3      | SAR Probe                         | 3/16/2010  | Annual       | 3/16/2011  | 3213          |
| SPEAG              | DAE4        | Dasy Data Acquisition Electronics | 3/22/2010  | Annual       | 3/22/2011  | 704           |
| SPEAG              | ES3DV3      | SAR Probe                         | 4/20/2010  | Annual       | 4/20/2011  | 3209          |
| SPEAG              | DAE4        | Dasy Data Acquisition Electronics | 4/21/2010  | Annual       | 4/21/2011  | 665           |
| SPEAG              | D1765V2     | 1765 MHz SAR Dipole               | 5/19/2009  | Biennial     | 5/19/2011  | 1008          |
| SPEAG              | D1450V2     | 1450 MHz SAR Dipole               | 5/20/2009  | Biennial     | 5/20/2011  | 1025          |
| SPEAG              | DAE4        | Dasy Data Acquisition Electronics | 7/8/2010   | Annual       | 7/8/2011   | 859           |
| SPEAG              | D2600V2     | 2600 MHz SAR Dipole               | 8/12/2009  | Biennial     | 8/12/2011  | 1004          |
| SPEAG              | D1900V2     | 1900 MHz SAR Dipole               | 8/18/2009  | Biennial     | 8/18/2011  | 5d080         |
| SPEAG              | D5GHzV2     | 5 GHz SAR Dipole                  | 8/19/2009  | Biennial     | 8/19/2011  | 1007          |
| SPEAG              | EX3DV4      | SAR Probe                         | 8/19/2010  | Annual       | 8/19/2011  | 3561          |
| SPEAG              | D835V2      | 835 MHz SAR Dipole                | 8/24/2009  | Biennial     | 8/24/2011  | 4d026         |
| SPEAG              | D2450V2     | 2450 MHz SAR Dipole               | 8/27/2009  | Biennial     | 8/27/2011  | 719           |
| SPEAG              | ES3DV2      | SAR Probe                         | 9/21/2010  | Annual       | 9/21/2011  | 3022          |
| SPEAG              | DAE3        | Dasy Data Acquisition Electronics | 11/18/2010 | Annual       | 11/18/2011 | 455           |
| SPEAG              | D1640V2     | 1640 MHz Dipole                   | 8/17/2010  | Biennial     | 8/17/2012  | 321           |
| SPEAG              | D750V3      | 750 MHz Dipole                    | 8/19/2010  | Biennial     | 8/19/2012  | 1003          |

### Notes:

The E-field probe was calibrated by SPEAG, by the waveguide technique procedure. Dipole Validation measurement is performed by PCTEST prior to SAR evaluation. The brain simulating material is calibrated by PCTEST using the dielectric probe system and network analyzer to determine the conductivity and permittivity (dielectric constant) of the brain-equivalent material.

| FCC ID: EROUFO-WPR-3ER        |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
|-------------------------------|---|---|---|---------------------------------|
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 20 of 28                   |

## 16 CONCLUSION

### 16.1 Measurement Conclusion

The SAR evaluation indicates that the EUT complies with the RF radiation exposure limits of the FCC and Health Canada, with respect to all parameters in the requirements. These measurements were taken to simulate the RF effects of RF exposure under worst-case conditions. Precise laboratory measures were taken to assure repeatability of the tests. The results and statements relate only to the item(s) tested.

Please note that the absorption and distribution of electromagnetic energy in the body are very complex phenomena that depend on the mass, shape, and size of the body, the orientation of the body with respect to the field vectors, and the electrical properties of both the body and the environment. Other variables that may play a substantial role in possible biological effects are those that characterize the environment (e.g. ambient temperature, air velocity, relative humidity, and body insulation) and those that characterize the individual (e.g. age, gender, activity level, debilitation, or disease). Because various factors may interact with one another to vary the specific biological outcome of an exposure to electromagnetic fields, any protection guide should consider maximal amplification of biological effects as a result of field-body interactions, environmental conditions, and physiological variables. [3]

|                               |   |   |   |                                 |
|-------------------------------|---|---|---|---------------------------------|
| FCC ID: EROUFO-WPR-3ER        |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
| Filename:<br>0Y1011301928.ERO | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller |   | Page 21 of 28                   |

## 17 REFERENCES

- [1] Federal Communications Commission, ET Docket 93-62, Guidelines for Evaluating the Environmental Effects of Radiofrequency Radiation, Aug. 1996.
- [2] ANSI/IEEE C95.1-2005, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, 2006.
- [3] ANSI/IEEE C95.1-1992, American National Standard safety levels with respect to human exposure to radio frequency electromagnetic fields, 300kHz to 100GHz, New York: IEEE, Sept. 1992.
- [4] ANSI/IEEE C95.3-2002, IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields - RF and Microwave, New York: IEEE, December 2002.
- [5] Federal Communications Commission, OET Bulletin 65 (Edition 97-01), Supplement C (Edition 01-01), Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, July 2001.
- [6] IEEE Standards Coordinating Committee 34 – IEEE Std. 1528-2003, Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Body Due to Wireless Communications Devices.
- [7] NCRP, National Council on Radiation Protection and Measurements, Biological Effects and Exposure Criteria for RadioFrequency Electromagnetic Fields, NCRP Report No. 86, 1986. Reprinted Feb. 1995.
- [8] T. Schmid, O. Egger, N. Kuster, Automated E-field scanning system for dosimetric assessments, IEEE Transaction on Microwave Theory and Techniques, vol. 44, Jan. 1996, pp. 105-113.
- [9] K. Pokovic, T. Schmid, N. Kuster, Robust setup for precise calibration of E-field probes in tissue simulating liquids at mobile communications frequencies, ICECOM97, Oct. 1997, pp. 120-124.
- [10] K. Pokovic, T. Schmid, and N. Kuster, E-field Probe with improved isotropy in brain simulating liquids, Proceedings of the ELMAR, Zadar, Croatia, June 23-25, 1996, pp. 172-175.
- [11] Schmid & Partner Engineering AG, Application Note: Data Storage and Evaluation, June 1998, p2.
- [12] V. Hombach, K. Meier, M. Burkhardt, E. Kuhn, N. Kuster, The Dependence of EM Energy Absorption upon Human Head Modeling at 900 MHz, IEEE Transaction on Microwave Theory and Techniques, vol. 44 no. 10, Oct. 1996, pp. 1865-1873.
- [13] N. Kuster and Q. Balzano, Energy absorption mechanism by biological bodies in the near field of dipole antennas above 300MHz, IEEE Transaction on Vehicular Technology, vol. 41, no. 1, Feb. 1992, pp. 17-23.
- [14] G. Hartsgrove, A. Kraszewski, A. Surowiec, Simulated Biological Materials for Electromagnetic Radiation Absorption Studies, University of Ottawa, Bioelectromagnetics, Canada: 1987, pp. 29-36.
- [15] Q. Balzano, O. Garay, T. Manning Jr., Electromagnetic Energy Exposure of Simulated Users of Portable Cellular Telephones, IEEE Transactions on Vehicular Technology, vol. 44, no.3, Aug. 1995.

| FCC ID: EROUO-WPR-3ER                      |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
|--|---|---|---|---------------------------------|
| Filename:<br>0Y1011301928.ERO              | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller | Page 22 of 28   |                                 |
| © 2011 PCTEST Engineering Laboratory, Inc. |   |   |   |                                 |

- [16] W. Gander, Computermathematick, Birkhaeuser, Basel, 1992.
- [17] W.H. Press, S.A. Teukolsky, W.T. Vetterling, and B.P. Flannery, Numerical Receipes in C, The Art of Scientific Computing, Second edition, Cambridge University Press, 1992.
- [18] Federal Communications Commission, OET Bulletin 65, Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields. Supplement C, Dec. 1997.
- [19] N. Kuster, R. Kastle, T. Schmid, Dosimetric evaluation of mobile communications equipment with known precision, IEEE Transaction on Communications, vol. E80-B, no. 5, May 1997, pp. 645-652.
- [20] CENELEC CLC/SC111B, European Prestandard (prENV 50166-2), Human Exposure to Electromagnetic Fields High-frequency: 10kHz-300GHz, Jan. 1995.
- [21] Prof. Dr. Niels Kuster, ETH, Eidgenössische Technische Hochschule Zürich, Dosimetric Evaluation of the Cellular Phone.
- [22] IEC 62209-1, Human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices - Human models, instrumentation, and procedures - Part 1: Procedure to determine the specific absorption rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz), Feb. 2005.
- [23] Industry Canada RSS-102 Radio Frequency Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands) Issue 3, June 2009
- [24] Health Canada Safety Code 6 Limits of Human Exposure to Radio Frequency Electromagnetic Fields in the Frequency Range from 3 kHz – 300 GHz, 2009
- [25] FCC Public Notice DA-02-1438. Office of Engineering and Technology Announces a Transition Period for the Phantom Requirements of Supplement C to OET Bulletin 65, June 19, 2002
- [26] FCC SAR Measurement Procedures for 3G Devices KDB 941225
- [27] SAR Measurement procedures for IEEE 802.11a/b/g KDB 248227
- [28] FCC SAR Considerations for Handsets with Multiple Transmitters and Antennas, KDB 648474
- [29] FCC Application Note for SAR Probe Calibration and System Verification Consideration for Measurements at 150 MHz – 3 GHz, KDB 450824
- [30] FCC SAR Evaluation Considerations for Laptop Computers with Antennas Built-in on Display Screens, KDB 616217
- [31] FCC SAR Measurement Requirements for 3 – 6 GHz, KDB 865664
- [32] FCC Mobile Portable RF Exposure Procedure, KDB 447498
- [33] FCC SAR Procedures for Dongle Transmitters, KDB 447498
- [34] Anexo à Resolução No. 533, de 10 de Septembro de 2009.

| FCC ID: EROUFO-WPR-3ER                     |  | SAR COMPLIANCE REPORT                                   |  | Reviewed by:<br>Quality Manager |
|--|---|---|---|---------------------------------|
| Filename:<br>0Y1011301928.ERO              | Test Dates:<br>11/30/10   | EUT Type:<br>802.15 ZigBee Waterproof Remote Controller | Page 23 of 28   |                                 |
| © 2011 PCTEST Engineering Laboratory, Inc. |   |   | REV 7.5<br>03/17/10   |                                 |

## **APPENDIX A: SAR TEST DATA**

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Crestron UFO-WPR-3ER; Type: 802.15 Zigbee Waterproof Remote Controller; Serial: 0**

Communication System: IEEE 802.15 ; Frequency: 2435 MHz; Duty Cycle: 1:1

Medium: 2450 Muscle Medium parameters used (interpolated):

$f = 2435$  MHz;  $\sigma = 2$  mho/m;  $\epsilon_r = 51.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 11-30-2010; Ambient Temp: 23.4 °C; Tissue Temp: 21.8 °C

Probe: EX3DV4 - SN3550; ConvF(6.4, 6.4, 6.4); Calibrated: 1/26/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/22/2010

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Mode: IEEE 802.15, Body SAR, Ch.17, Mid Ch., Back Side, Touch**


**Area Scan (9x9x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 6.02 V/m; Power Drift = 0.051 dB

Peak SAR (extrapolated) = 0.125 W/kg

**SAR(1 g) = 0.070 mW/g; SAR(10 g) = 0.037 mW/g**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Crestron UFO-WPR-3ER; Type: 802.15 Zigbee Waterproof Remote Controller; Serial: 0**

Communication System: IEEE 802.15 ; Frequency: 2435 MHz; Duty Cycle: 1:1

Medium: 2450 Muscle Medium parameters used (interpolated):

$f = 2435$  MHz;  $\sigma = 2.00$  mho/m;  $\epsilon_r = 51.3$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 11-30-2010; Ambient Temp: 23.4 °C; Tissue Temp: 21.8 °C

Probe: EX3DV4 - SN3550; ConvF(6.4, 6.4, 6.4); Calibrated: 1/26/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/22/2010

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Mode: IEEE 802.15, Body SAR, Ch.17, Mid Ch., Back Side Tilt, Touch**


**Area Scan (6x6x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 7.03 V/m; Power Drift = 0.029 dB

Peak SAR (extrapolated) = 0.208 W/kg

**SAR(1 g) = 0.104 mW/g; SAR(10 g) = 0.052 mW/g**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Crestron UFO-WPR-3ER; Type: 802.15 Zigbee Waterproof Remote Controller; Serial: 0**

Communication System: IEEE 802.15 ; Frequency: 2410 MHz; Duty Cycle: 1:1

Medium: 2450 Muscle Medium parameters used (interpolated):

$f = 2410 \text{ MHz}$ ;  $\sigma = 1.96 \text{ mho/m}$ ;  $\epsilon_r = 51.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 11-30-2010; Ambient Temp: 23.4 °C; Tissue Temp: 21.8 °C

Probe: EX3DV4 - SN3550; ConvF(6.4, 6.4, 6.4); Calibrated: 1/26/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/22/2010

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Mode: IEEE 802.15, Body SAR, Ch.12, Low Ch., Front Side, Touch**


**Area Scan (9x9x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.9 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 2.74 W/kg

**SAR(1 g) = 1.18 mW/g; SAR(10 g) = 0.512 mW/g**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Crestron UFO-WPR-3ER; Type: 802.15 Zigbee Waterproof Remote Controller; Serial: 0**

Communication System: IEEE 802.15 ; Frequency: 2410 MHz; Duty Cycle: 1:1

Medium: 2450 Muscle Medium parameters used (interpolated):

$f = 2410 \text{ MHz}$ ;  $\sigma = 1.96 \text{ mho/m}$ ;  $\epsilon_r = 51.4$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 11-30-2010; Ambient Temp: 23.4 °C; Tissue Temp: 21.8 °C

Probe: EX3DV4 - SN3550; ConvF(6.4, 6.4, 6.4); Calibrated: 1/26/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/22/2010

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Mode: IEEE 802.15, Body SAR, Ch.12, Low Ch., Front Side, Touch**


**Area Scan (9x9x1):** Measurement grid: dx=15mm, dy=15mm

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 26.9 V/m; Power Drift = -0.012 dB

Peak SAR (extrapolated) = 2.74 W/kg

**SAR(1 g) = 1.18 mW/g; SAR(10 g) = 0.512 mW/g**



# PCTEST ENGINEERING LABORATORY, INC.

**DUT: Crestron UFO-WPR-3ER; Type: 802.15 Zigbee Waterproof Remote Controller; Serial: 0**

Communication System: IEEE 802.15 ; Frequency: 2465 MHz; Duty Cycle: 1:1

Medium: 2450 Muscle Medium parameters used (interpolated):

$f = 2465 \text{ MHz}$ ;  $\sigma = 2.04 \text{ mho/m}$ ;  $\epsilon_r = 51.2$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 0.0 cm

Test Date: 11-30-2010; Ambient Temp: 23.4 °C; Tissue Temp: 21.8 °C

Probe: EX3DV4 - SN3550; ConvF(6.4, 6.4, 6.4); Calibrated: 1/26/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/22/2010

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

**Mode: IEEE 802.15, Body SAR, Ch.23, High Ch., Top Edge, Touch**


**Area Scan (6x6x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Reference Value = 11.8 V/m; Power Drift = -0.003 dB

Peak SAR (extrapolated) = 0.514 W/kg

**SAR(1 g) = 0.249 mW/g; SAR(10 g) = 0.115 mW/g**



## **APPENDIX B: DIPOLE VALIDATION**

# PCTEST ENGINEERING LABORATORY, INC.

**DUT: SAR Dipole 2450 MHz; Type: D2450V2; Serial: 719**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: 2450 Muscle Medium parameters used:

$f = 2450 \text{ MHz}$ ;  $\sigma = 2.015 \text{ mho/m}$ ;  $\epsilon_r = 51.29$ ;  $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section; Space: 1.5 cm

Test Date: 11-30-2010; Ambient Temp: 23.4 °C; Tissue Temp: 21.8 °C

Probe: EX3DV4 - SN3550; ConvF(6.4, 6.4, 6.4); Calibrated: 1/26/2010

Sensor-Surface: 3mm (Mechanical Surface Detection)

Electronics: DAE4 Sn649; Calibrated: 1/22/2010

Phantom: SAM Sub; Type: SAM 4.0; Serial: TP-1357

Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

## 2450MHz System Verification


**Area Scan (5x7x1):** Measurement grid:  $dx=15\text{mm}$ ,  $dy=15\text{mm}$

**Zoom Scan (5x5x7)/Cube 0:** Measurement grid:  $dx=8\text{mm}$ ,  $dy=8\text{mm}$ ,  $dz=5\text{mm}$

Input Power = 14.0 dBm (25 mW)

**SAR(1 g) = 1.31 mW/g; SAR(10 g) = 0.602 mW/g**

Deviation = 1.95 %



## **APPENDIX C: PROBE CALIBRATION**



Accredited by the Swiss Accreditation Service (SAS)  
The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

Client PC Test

Certificate No. D2450V2-719\_Aug09

## CALIBRATION CERTIFICATE

Object D2450V2 - SN: 719

Calibration procedure(s) QA CAL-05.v7  
Calibration procedure for dipole-validation kits

Calibration date: August 27, 2009

Condition of the calibrated item In Tolerance

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards           | ID #               | Cal Date (Calibrated by, Certificate No.) | Scheduled Calibration |
|-----------------------------|--------------------|---|-----------------------|
| Power meter EPM-442A        | GB37480704         | 08-Oct-08 (No. 217-00898)                 | Oct-09                |
| Power sensor HP 8481A       | US37292783         | 08-Oct-08 (No. 217-00898)                 | Oct-09                |
| Reference 20 dB Attenuator  | SN: 5086 (20g)     | 31-Mar-09 (No. 217-01025)                 | Mar-10                |
| Type-N mismatch combination | SN: 5047.2 / 06327 | 31-Mar-09 (No. 217-01029)                 | Mar-10                |
| Reference Probe ES3DV3      | SN: 3205           | 26-Jun-09 (No. ES3-3205_Jun09)            | Jun-10                |
| DAE4                        | SN: 601            | 07-Mar-09 (No. DAE4-601_Mar09)            | Mar-10                |

| Secondary Standards       | ID #             | Check Date (in house)             | Scheduled Check        |
|---------------------------|------------------|-----------------------------------|------------------------|
| Power sensor HP 8481A     | MY41092317       | 18-Oct-02 (in house check Oct-07) | In house check: Oct-09 |
| RF generator R&S SMT-06   | 100005           | 4-Aug-99 (in house check Oct-07)  | In house check: Oct-09 |
| Network Analyzer HP 8753E | US37390585 S4206 | 18-Oct-01 (in house check Oct-08) | In house check: Oct-09 |

| Calibrated by: | Name           | Function              | Signature |
|----------------|----------------|-----------------------|-----------|
|                | Jelon Kastrati | Laboratory Technician |           |
| Approved by:   | Katja Pokovic  | Technical Manager     |           |

Issued: August 27, 2009

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: SCS 108

#### Glossary:

|       |                                 |
|-------|---------------------------------|
| TSL   | tissue simulating liquid        |
| ConvF | sensitivity in TSL / NORM x,y,z |
| N/A   | not applicable or not measured  |

#### Calibration is Performed According to the Following Standards:

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005
- c) Federal Communications Commission Office of Engineering & Technology (FCC OET), "Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields; Additional Information for Evaluating Compliance of Mobile and Portable Devices with FCC Limits for Human Exposure to Radiofrequency Emissions", Supplement C (Edition 01-01) to Bulletin 65

#### Additional Documentation:

- d) DASY4/5 System Handbook

#### Methods Applied and Interpretation of Parameters:

- *Measurement Conditions:* Further details are available from the Validation Report at the end of the certificate. All figures stated in the certificate are valid at the frequency indicated.
- *Antenna Parameters with TSL:* The dipole is mounted with the spacer to position its feed point exactly below the center marking of the flat phantom section, with the arms oriented parallel to the body axis.
- *Feed Point Impedance and Return Loss:* These parameters are measured with the dipole positioned under the liquid filled phantom. The impedance stated is transformed from the measurement at the SMA connector to the feed point. The Return Loss ensures low reflected power. No uncertainty required.
- *Electrical Delay:* One-way delay between the SMA connector and the antenna feed point. No uncertainty required.
- *SAR measured:* SAR measured at the stated antenna input power.
- *SAR normalized:* SAR as measured, normalized to an input power of 1 W at the antenna connector.
- *SAR for nominal TSL parameters:* The measured TSL parameters are used to calculate the nominal SAR result.

## Measurement Conditions

DASY system configuration, as far as not given on page 1.

|                              |                           |             |
|------------------------------|---------------------------|-------------|
| DASY Version                 | DASY5                     | V5.0        |
| Extrapolation                | Advanced Extrapolation    |             |
| Phantom                      | Modular Flat Phantom V5.0 |             |
| Distance Dipole Center - TSL | 10 mm                     | with Spacer |
| Zoom Scan Resolution         | dx, dy, dz = 5 mm         |             |
| Frequency                    | 2450 MHz $\pm$ 1 MHz      |             |

## Head TSL parameters

The following parameters and calculations were applied.

|                                  | Temperature         | Permittivity   | Conductivity         |
|----------------------------------|---------------------|----------------|----------------------|
| Nominal Head TSL parameters      | 22.0 °C             | 39.2           | 1.80 mho/m           |
| Measured Head TSL parameters     | (22.0 $\pm$ 0.2) °C | 40.1 $\pm$ 6 % | 1.80 mho/m $\pm$ 6 % |
| Head TSL temperature during test | (22.3 $\pm$ 0.2) °C | ----           | ----                 |

## SAR result with Head TSL

|   |                    |                                |
|---|--------------------|--------------------------------|
| SAR averaged over 1 cm <sup>3</sup> (1 g) of Head TSL | Condition          |                                |
| SAR measured  | 250 mW input power | 13.3 mW / g                    |
| SAR normalized  | normalized to 1W   | 53.2 mW / g                    |
| SAR for nominal Head TSL parameters <sup>1</sup>      | normalized to 1W   | 53.5 mW / g $\pm$ 17.0 % (k=2) |

|   |                    |                                |
|---|--------------------|--------------------------------|
| SAR averaged over 10 cm <sup>3</sup> (10 g) of Head TSL | condition          |                                |
| SAR measured  | 250 mW input power | 6.23 mW / g                    |
| SAR normalized  | normalized to 1W   | 24.9 mW / g                    |
| SAR for nominal Head TSL parameters <sup>1</sup>        | normalized to 1W   | 25.0 mW / g $\pm$ 16.5 % (k=2) |

<sup>1</sup> Correction to nominal TSL parameters according to d), chapter "SAR Sensitivities"

## Body TSL parameters

The following parameters and calculations were applied.

|   | Temperature     | Permittivity | Conductivity     |
|---|-----------------|--------------|------------------|
| <b>Nominal Body TSL parameters</b>      | 22.0 °C         | 52.7         | 1.95 mho/m       |
| <b>Measured Body TSL parameters</b>     | (22.0 ± 0.2) °C | 53.2 ± 6 %   | 2.01 mho/m ± 6 % |
| <b>Body TSL temperature during test</b> | (22.5 ± 0.2) °C | ----         | ----             |

## SAR result with Body TSL

| SAR averaged over 1 cm <sup>3</sup> (1 g) of Body TSL | Condition          |                           |
|---|--------------------|---------------------------|
| SAR measured  | 250 mW input power | 13.0 mW / g               |
| SAR normalized  | normalized to 1W   | 52.0 mW / g               |
| SAR for nominal Body TSL parameters <sup>2</sup>      | normalized to 1W   | 51.4 mW /g ± 17.0 % (k=2) |

| SAR averaged over 10 cm <sup>3</sup> (10 g) of Body TSL | condition          |                           |
|---|--------------------|---------------------------|
| SAR measured  | 250 mW input power | 6.00 mW / g               |
| SAR normalized  | normalized to 1W   | 24.0 mW / g               |
| SAR for nominal Body TSL parameters <sup>2</sup>        | normalized to 1W   | 23.9 mW /g ± 16.5 % (k=2) |

<sup>2</sup> Correction to nominal TSL parameters according to d), chapter "SAR Sensitivities"

## Appendix

### Antenna Parameters with Head TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $53.4 \Omega + 1.8 j\Omega$ |
| Return Loss                          | - 28.6 dB                   |

### Antenna Parameters with Body TSL

|                                      |                             |
|--------------------------------------|-----------------------------|
| Impedance, transformed to feed point | $48.2 \Omega + 3.9 j\Omega$ |
| Return Loss                          | - 27.2 dB                   |

### General Antenna Parameters and Design

|                                  |          |
|----------------------------------|----------|
| Electrical Delay (one direction) | 1.150 ns |
|----------------------------------|----------|

After long term use with 100W radiated power, only a slight warming of the dipole near the feedpoint can be measured.

The dipole is made of standard semirigid coaxial cable. The center conductor of the feeding line is directly connected to the second arm of the dipole. The antenna is therefore short-circuited for DC-signals.

No excessive force must be applied to the dipole arms, because they might bend or the soldered connections near the feedpoint may be damaged.

### Additional EUT Data

|                 |                    |
|-----------------|--------------------|
| Manufactured by | SPEAG              |
| Manufactured on | September 10, 2002 |

# DASY5 Validation Report for Head TSL

Date/Time: 27.08.2009 11:14:47

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN719**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: HSL U11 BB

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 1.8$  mho/m;  $\epsilon_r = 40.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.53, 4.53, 4.53); Calibrated: 26.06.2009
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 07.03.2009
- Phantom: Flat Phantom 5.0 (front); Type: QD000P50AA; Serial: 1001
- Measurement SW: DASY5, V5.0 Build 120; SEMCAD X Version 13.4 Build 45


**Pin = 250 mW; d = 10 mm/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 101.4 V/m; Power Drift = 0.025 dB

Peak SAR (extrapolated) = 27 W/kg


**SAR(1 g) = 13.3 mW/g; SAR(10 g) = 6.23 mW/g**

Maximum value of SAR (measured) = 17.2 mW/g



0 dB = 17.2mW/g

## Impedance Measurement Plot for Head TSL



# DASY5 Validation Report for Body TSL

Date/Time: 17.08.2009 15:35:28

Test Laboratory: SPEAG, Zurich, Switzerland

**DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:719**

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium: MSL U10 BB

Medium parameters used:  $f = 2450$  MHz;  $\sigma = 2.01$  mho/m;  $\epsilon_r = 53.1$ ;  $\rho = 1000$  kg/m<sup>3</sup>

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC)

DASY5 Configuration:

- Probe: ES3DV3 - SN3205; ConvF(4.31, 4.31, 4.31); Calibrated: 26.06.2009
- Sensor-Surface: 3mm (Mechanical Surface Detection)
- Electronics: DAE4 Sn601; Calibrated: 07.03.2009
- Phantom: Flat Phantom 5.0 (back); Type: QD000P50AA; Serial: 1002
- Measurement SW: DASY5, V5.0 Build 120; SEMCAD X Version 13.4 Build 45


**Pin = 250 mW; d = 10 mm/Zoom Scan (7x7x7)/Cube 0:** Measurement grid: dx=5mm, dy=5mm, dz=5mm

Reference Value = 94.8 V/m; Power Drift = -0.00649 dB

Peak SAR (extrapolated) = 27.2 W/kg


**SAR(1 g) = 13 mW/g; SAR(10 g) = 6 mW/g**

Maximum value of SAR (measured) = 17 mW/g



0 dB = 17mW/g

## Impedance Measurement Plot for Body TSL





Accredited by the Swiss Accreditation Service (SAS)

Accreditation No.: **SCS 108**

The Swiss Accreditation Service is one of the signatories to the EA  
Multilateral Agreement for the recognition of calibration certificates

Client **PC Test**

Certificate No: **EX3-3550\_Jan10**

## CALIBRATION CERTIFICATE

Object **EX3DV4 - SN:3550**

Calibration procedure(s) **QA CAL-01.v6, QA CAL-14.v3, QA CAL-23.v3 and QA CAL-25.v2  
Calibration procedure for dosimetric E-field probes**

Calibration date: **January 26, 2010**

*✓ s  
1/26/10*

This calibration certificate documents the traceability to national standards, which realize the physical units of measurements (SI).  
The measurements and the uncertainties with confidence probability are given on the following pages and are part of the certificate.

All calibrations have been conducted in the closed laboratory facility: environment temperature (22 ± 3)°C and humidity < 70%.

Calibration Equipment used (M&TE critical for calibration)

| Primary Standards          | ID #            | Cal Date (Certificate No.)     | Scheduled Calibration |
|----------------------------|-----------------|--------------------------------|-----------------------|
| Power meter E4419B         | GB41293874      | 1-Apr-09 (No. 217-01030)       | Apr-10                |
| Power sensor E4412A        | MY41495277      | 1-Apr-09 (No. 217-01030)       | Apr-10                |
| Power sensor E4412A        | MY41498087      | 1-Apr-09 (No. 217-01030)       | Apr-10                |
| Reference 3 dB Attenuator  | SN: S5054 (3c)  | 31-Mar-09 (No. 217-01026)      | Mar-10                |
| Reference 20 dB Attenuator | SN: S5086 (20b) | 31-Mar-09 (No. 217-01028)      | Mar-10                |
| Reference 30 dB Attenuator | SN: S5129 (30b) | 31-Mar-09 (No. 217-01027)      | Mar-10                |
| Reference Probe ES3DV2     | SN: 3013        | 30-Dec-09 (No. ES3-3013_Dec09) | Dec-10                |
| DAE4                       | SN: 660         | 29-Sep-09 (No. DAE4-660_Sep09) | Sep-10                |


| Secondary Standards       | ID #         | Check Date (in house)             | Scheduled Check        |
|---------------------------|--------------|-----------------------------------|------------------------|
| RF generator HP 8648C     | US3642U01700 | 4-Aug-99 (in house check Oct-09)  | In house check: Oct-11 |
| Network Analyzer HP 8753E | US37390585   | 18-Oct-01 (in house check Oct-09) | In house check: Oct10  |

| Calibrated by: | Name          | Function          | Signature |
|----------------|---------------|-------------------|-----------|
|                | Kalja Pokovic | Technical Manager |           |

| Approved by: | Name        | Function     | Signature |
|--------------|-------------|--------------|-----------|
|              | Fin Bomholt | R&D Director |           |

Issued: January 26, 2010

This calibration certificate shall not be reproduced except in full without written approval of the laboratory.



Accredited by the Swiss Accreditation Service (SAS)

The Swiss Accreditation Service is one of the signatories to the EA  
 Multilateral Agreement for the recognition of calibration certificates

Accreditation No.: **SCS 108**

### **Glossary:**

|                          |   |
|--------------------------|---|
| TS                       | tissue simulating liquid  |
| NORM <sub>x,y,z</sub>    | sensitivity in free space   |
| ConvF                    | sensitivity in TSL / NORM <sub>x,y,z</sub>  |
| DCP                      | diode compression point   |
| CF                       | crest factor (1/duty_cycle) of the RF signal  |
| A, B, C                  | modulation dependent linearization parameters   |
| Polarization $\varphi$   | $\varphi$ rotation around probe axis  |
| Polarization $\vartheta$ | $\vartheta$ rotation around an axis that is in the plane normal to probe axis (at measurement center),<br>i.e., $\vartheta = 0$ is normal to probe axis |

### **Calibration is Performed According to the Following Standards:**

- a) IEEE Std 1528-2003, "IEEE Recommended Practice for Determining the Peak Spatial-Averaged Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques", December 2003
- b) IEC 62209-1, "Procedure to measure the Specific Absorption Rate (SAR) for hand-held devices used in close proximity to the ear (frequency range of 300 MHz to 3 GHz)", February 2005

### **Methods Applied and Interpretation of Parameters:**

- *NORM<sub>x,y,z</sub>*: Assessed for E-field polarization  $\vartheta = 0$  ( $f \leq 900$  MHz in TEM-cell;  $f > 1800$  MHz: R22 waveguide). *NORM<sub>x,y,z</sub>* are only intermediate values, i.e., the uncertainties of *NORM<sub>x,y,z</sub>* does not effect the  $E^2$ -field uncertainty inside TSL (see below *ConvF*).
- *NORM(f)x,y,z = NORM<sub>x,y,z</sub> \* frequency\_response* (see Frequency Response Chart). This linearization is implemented in DASY4 software versions later than 4.2. The uncertainty of the frequency response is included in the stated uncertainty of *ConvF*.
- *DCPx,y,z*: DCP are numerical linearization parameters assessed based on the data of power sweep with CW signal (no uncertainty required). DCP does not depend on frequency nor media.
- *Ax,y,z; Bx,y,z; Cx,y,z; VRx,y,z*: *A, B, C* are numerical linearization parameters assessed based on the data of power sweep for specific modulation signal. The parameters do not depend on frequency nor media. VR is the maximum calibration range expressed in RMS voltage across the diode.
- *ConvF and Boundary Effect Parameters*: Assessed in flat phantom using E-field (or Temperature Transfer Standard for  $f \leq 800$  MHz) and inside waveguide using analytical field distributions based on power measurements for  $f > 800$  MHz. The same setups are used for assessment of the parameters applied for boundary compensation (alpha, depth) of which typical uncertainty values are given. These parameters are used in DASY4 software to improve probe accuracy close to the boundary. The sensitivity in TSL corresponds to *NORM<sub>x,y,z</sub> \* ConvF* whereby the uncertainty corresponds to that given for *ConvF*. A frequency dependent *ConvF* is used in DASY version 4.4 and higher which allows extending the validity from  $\pm 50$  MHz to  $\pm 100$  MHz.
- *Spherical Isotropy (3D deviation from isotropy)*: in a field of low gradients realized using a flat phantom exposed by a patch antenna.
- *Sensor Offset*: The sensor offset corresponds to the offset of virtual measurement center from the probe tip (on probe axis). No tolerance required.

# Probe EX3DV4

## SN:3550

Manufactured: May 19, 2004  
Last calibrated: January 21, 2009  
Recalibrated: January 26, 2010

Calibrated for DASY Systems

(Note: non-compatible with DASY2 system!)

## DASY - Parameters of Probe: EX3DV4 SN:3550

### Basic Calibration Parameters

|  | Sensor X | Sensor Y | Sensor Z | Unc (k=2)   |
|--|----------|----------|----------|-------------|
| Norm ( $\mu$ V/(V/m) <sup>2</sup> ) <sup>A</sup> | 0.48     | 0.47     | 0.48     | $\pm$ 10.1% |
| DCP (mV) <sup>B</sup>                            | 92.9     | 88.4     | 91.4     |             |

### Modulation Calibration Parameters

| UID   | Communication System Name | PAR  |             | A<br>dB              | B<br>dBuV            | C                    | VR<br>mV          | Unc <sup>E</sup><br>(k=2) |
|-------|---------------------------|------|-------------|----------------------|----------------------|----------------------|-------------------|---------------------------|
| 10000 | CW                        | 0.00 | X<br>Y<br>Z | 0.00<br>0.00<br>0.00 | 0.00<br>0.00<br>0.00 | 1.00<br>1.00<br>1.00 | 300<br>300<br>300 | $\pm$ 1.5%                |

The reported uncertainty of measurement is stated as the standard uncertainty of measurement multiplied by the coverage factor k=2, which for a normal distribution corresponds to a coverage probability of approximately 95%.

<sup>A</sup> The uncertainties of NormX,Y,Z do not affect the E<sup>2</sup>-field uncertainty inside TSL (see Pages 5 and 6).

<sup>B</sup> Numerical linearization parameter: uncertainty not required.

<sup>E</sup> Uncertainty is determined using the maximum deviation from linear response applying rectangular distribution and is expressed for the square of the field value.

## DASY - Parameters of Probe: EX3DV4 SN:3550

### Calibration Parameter Determined in Head Tissue Simulating Media

| f [MHz] | Validity [MHz] <sup>c</sup> | Permittivity | Conductivity | ConvF X | ConvF Y | ConvF Z | Alpha | Depth Unc (k=2) |
|---------|-----------------------------|--------------|--------------|---------|---------|---------|-------|-----------------|
| 835     | ± 50 / ± 100                | 41.5 ± 5%    | 0.90 ± 5%    | 8.28    | 8.28    | 8.28    | 0.45  | 0.70 ± 11.0%    |
| 1750    | ± 50 / ± 100                | 40.1 ± 5%    | 1.37 ± 5%    | 7.03    | 7.03    | 7.03    | 0.39  | 0.75 ± 11.0%    |
| 1900    | ± 50 / ± 100                | 40.0 ± 5%    | 1.40 ± 5%    | 6.81    | 6.81    | 6.81    | 0.32  | 0.81 ± 11.0%    |
| 2450    | ± 50 / ± 100                | 39.2 ± 5%    | 1.80 ± 5%    | 6.21    | 6.21    | 6.21    | 0.22  | 1.07 ± 11.0%    |

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.

## DASY - Parameters of Probe: EX3DV4 SN:3550


### Calibration Parameter Determined in Body Tissue Simulating Media

| f [MHz] | Validity [MHz] <sup>c</sup> | Permittivity | Conductivity | ConvF X | ConvF Y | ConvF Z | Alpha | Depth Unc (k=2) |
|---------|-----------------------------|--------------|--------------|---------|---------|---------|-------|-----------------|
| 835     | ± 50 / ± 100                | 55.2 ± 5%    | 0.97 ± 5%    | 8.30    | 8.30    | 8.30    | 0.47  | 0.76 ± 11.0%    |
| 1750    | ± 50 / ± 100                | 53.4 ± 5%    | 1.49 ± 5%    | 6.90    | 6.90    | 6.90    | 0.49  | 0.69 ± 11.0%    |
| 1900    | ± 50 / ± 100                | 53.3 ± 5%    | 1.52 ± 5%    | 6.63    | 6.63    | 6.63    | 0.76  | 0.54 ± 11.0%    |
| 2450    | ± 50 / ± 100                | 52.7 ± 5%    | 1.95 ± 5%    | 6.40    | 6.40    | 6.40    | 0.22  | 1.09 ± 11.0%    |
| 2600    | ± 50 / ± 100                | 52.5 ± 5%    | 2.16 ± 5%    | 6.26    | 6.26    | 6.26    | 0.19  | 1.42 ± 11.0%    |
| 4950    | ± 50 / ± 100                | 49.4 ± 5%    | 5.01 ± 5%    | 3.64    | 3.64    | 3.64    | 0.50  | 1.75 ± 13.1%    |
| 5200    | ± 50 / ± 100                | 49.0 ± 5%    | 5.30 ± 5%    | 3.73    | 3.73    | 3.73    | 0.50  | 1.75 ± 13.1%    |
| 5300    | ± 50 / ± 100                | 48.5 ± 5%    | 5.42 ± 5%    | 3.52    | 3.52    | 3.52    | 0.52  | 1.75 ± 13.1%    |
| 5500    | ± 50 / ± 100                | 48.6 ± 5%    | 5.65 ± 5%    | 3.26    | 3.26    | 3.26    | 0.55  | 1.80 ± 13.1%    |
| 5600    | ± 50 / ± 100                | 48.5 ± 5%    | 5.77 ± 5%    | 3.16    | 3.16    | 3.16    | 0.65  | 1.80 ± 13.1%    |
| 5800    | ± 50 / ± 100                | 48.2 ± 5%    | 6.00 ± 5%    | 3.30    | 3.30    | 3.30    | 0.60  | 1.75 ± 13.1%    |

<sup>c</sup> The validity of ± 100 MHz only applies for DASY v4.4 and higher (see Page 2). The uncertainty is the RSS of the ConvF uncertainty at calibration frequency and the uncertainty for the indicated frequency band.



## Frequency Response of E-Field

(TEM-Cell:ifi110 EXX, Waveguide: R22)



Uncertainty of Frequency Response of E-field:  $\pm 6.3\%$  (k=2)


## Receiving Pattern ( $\phi$ ), $\vartheta = 0^\circ$



Uncertainty of Axial Isotropy Assessment:  $\pm 0.5\%$  ( $k=2$ )


## Dynamic Range $f(\text{SAR}_{\text{head}})$

(Waveguide R22,  $f = 1800$  MHz)




Uncertainty of Linearity Assessment:  $\pm 0.6\%$  ( $k=2$ )

## Conversion Factor Assessment



## Deviation from Isotropy in HSL

Error ( $\phi, \theta$ ), f = 900 MHz



Uncertainty of Spherical Isotropy Assessment:  $\pm 2.6\%$  (k=2)

## Other Probe Parameters

|   |                |
|---|----------------|
| Sensor Arrangement                            | Triangular     |
| Connector Angle (°)                           | Not applicable |
| Mechanical Surface Detection Mode             | enabled        |
| Optical Surface Detection Mode                | disabled       |
| Probe Overall Length                          | 337 mm         |
| Probe Body Diameter                           | 10 mm          |
| Tip Length                                    | 9 mm           |
| Tip Diameter                                  | 2.5 mm         |
| Probe Tip to Sensor X Calibration Point       | 1 mm           |
| Probe Tip to Sensor Y Calibration Point       | 1 mm           |
| Probe Tip to Sensor Z Calibration Point       | 1 mm           |
| Recommended Measurement Distance from Surface | 2 mm           |