

October 27, 1998

Federal Communications Commission  
Equipment Authorization Division  
7435 Oakland Mills Road  
Columbia, MD 21046

Subject: Maximum Permissible Exposure calculations for **FCC ID: EV9WNIP2458R**

To whom it may concern,

Wireless is submitting a low power transmitter for the WaveNet IP System. The unit has a low power frequency hopping spread spectrum radio operating in the 5725 - 5850 MHz range with a radiated output power of 205 W.

Assuming a worst case of no duty cycle.

For an Isotropic radiator the surface area of a sphere can be used to determine the area over which the transmitter energy is radiated.

$$\text{Surface area of a sphere} = 4\pi r^2$$

In the case where there is antenna gain, the worst case energy density is increased by the antenna gain. The exposure level can be calculated as follows for the antenna gain:

$$\text{MPE distance} = (\text{output power} * \text{duty cycle} * 10(\text{antenna gain}/10)) / (4\pi \text{Exposure Limit (mW/cm}^2)^{1/2}$$

#### **EV9WNIP2458R MPE distance**

SP1-2/5 Dual Band Antenna	$= (304 \text{ mW} * 1 * 213/4 * 3.14 * 1)^{1/2}$
	$= 71.8 \text{ cm}$
	$= 28.3 \text{ in}$

SP2I-2/5 Dual Band Antenna	$= (304 \text{ mW} * 1 * 676/4 * 3.14 * 1)^{1/2}$
	$= 127 \text{ cm}$
	$= 50.3 \text{ in}$

If you have any questions please do not hesitate to call me.

Sincerely,

Chris Byleckie  
Technical Director  
Electronic Compliance Laboratories