

# TEST REPORT

Applicant: FCC: VTech Telecommunications Ltd  
Name: IC: VTECH TELECOMMUNICATIONS LIMITED  
Address: FCC: 23/F Tai Ping Ind Center Block 1 57 Ting Kok Rd Tai Po NT, Hong Kong  
IC: BL.1 23/F Tai Ping Industr Ctr. 57 Ting Kok Road Tai Po, NT Hongkong  
Report Number: 2401V83797E-RFA  
FCC ID: EW780-3674-00  
IC: 1135B-80367400

## Test Standard (s)

FCC PART 15.247; RSS-GEN ISSUE 5, FEBRUARY 2021 AMENDMENT 2;  
RSS-247 ISSUE 3, AUGUST 2023

## Sample Description

Product Type: DECT 6.0 cordless phone  
Model No.: EL1101-2  
Multiple Model(s) No.: FCC: EL1101, EL1101-3, EL1101-4, EL1101-5, EL1101-XY  
IC: EL1101, EL1101-3, EL1101-4, EL1101-5  
Trade Mark: AT&T  
Date Received: 2024/07/01  
Issue Date: 2025/04/01

|              |                   |
|--------------|-------------------|
| Test Result: | Pass <sup>▲</sup> |
|--------------|-------------------|

▲ In the configuration tested, the EUT complied with the standards above.

## Prepared and Checked By:

*Bruce Lin*

Bruce Lin  
RF Engineer

## Approved By:

*Nancy Wang*

Nancy Wang  
RF Supervisor

Note: The information marked # is provided by the applicant, the laboratory is not responsible for its authenticity and this information can affect the validity of the result in the test report. Customer model name, addresses, names, trademarks etc. are included.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

This report must not be used by the customer to claim product certification, approval, or endorsement by NVLAP or any agency of the U.S. Government.

This report may contain data that are not covered by the NVLAP accreditation and are marked with an asterisk "▼".

## Bay Area Compliance Laboratories Corp. (Shenzhen)

5F(B-West), 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, Futian Free Trade Zone, Shenzhen, China

Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

## **TABLE OF CONTENTS**

|                                                                                            |           |
|--------------------------------------------------------------------------------------------|-----------|
| <b>DOCUMENT REVISION HISTORY .....</b>                                                     | <b>4</b>  |
| <b>GENERAL INFORMATION.....</b>                                                            | <b>5</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                                   | 5         |
| OBJECTIVE .....                                                                            | 5         |
| TEST METHODOLOGY .....                                                                     | 6         |
| MEASUREMENT UNCERTAINTY .....                                                              | 6         |
| TEST FACILITY .....                                                                        | 6         |
| <b>SYSTEM TEST CONFIGURATION .....</b>                                                     | <b>7</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                                    | 7         |
| EUT EXERCISE SOFTWARE .....                                                                | 7         |
| SPECIAL ACCESSORIES .....                                                                  | 7         |
| EQUIPMENT MODIFICATIONS .....                                                              | 7         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                                   | 7         |
| EXTERNAL I/O CABLE.....                                                                    | 8         |
| BLOCK DIAGRAM OF TEST SETUP .....                                                          | 8         |
| <b>SUMMARY OF TEST RESULTS .....</b>                                                       | <b>10</b> |
| <b>TEST EQUIPMENT LIST .....</b>                                                           | <b>11</b> |
| <b>FCC §15.247 (I) &amp; §1.1307 (B) (3) &amp; §2.1091- MPE-BASED EXEMPTION.....</b>       | <b>13</b> |
| APPLICABLE STANDARD .....                                                                  | 13        |
| RESULT .....                                                                               | 13        |
| <b>RSS-102 § 6.6 - FIELD REFERENCE LEVEL EXPOSURE EXEMPTION LIMITS.....</b>                | <b>14</b> |
| APPLICABLE STANDARD .....                                                                  | 14        |
| RESULT .....                                                                               | 14        |
| <b>FCC §15.203 &amp; RSS-GEN §6.8 - ANTENNA REQUIREMENT .....</b>                          | <b>15</b> |
| APPLICABLE STANDARD .....                                                                  | 15        |
| ANTENNA CONNECTOR CONSTRUCTION .....                                                       | 15        |
| <b>FCC §15.207 (A) &amp; RSS-GEN § 8.8 - AC LINE CONDUCTED EMISSIONS.....</b>              | <b>16</b> |
| APPLICABLE STANDARD .....                                                                  | 16        |
| EUT SETUP.....                                                                             | 16        |
| EMI TEST RECEIVER SETUP.....                                                               | 16        |
| TEST PROCEDURE .....                                                                       | 16        |
| FACTOR & OVER LIMIT CALCULATION.....                                                       | 17        |
| TEST DATA .....                                                                            | 17        |
| <b>FCC §15.209, §15.205 &amp; §15.247(D) &amp; RSS-247§ 5.5 - SPURIOUS EMISSIONS .....</b> | <b>24</b> |
| APPLICABLE STANDARD .....                                                                  | 24        |
| EUT SETUP .....                                                                            | 24        |
| EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP .....                                          | 25        |
| TEST PROCEDURE .....                                                                       | 26        |
| FACTOR & OVER LIMIT/MARGIN CALCULATION .....                                               | 26        |
| TEST DATA .....                                                                            | 26        |

|                                                                                                                                |           |
|--------------------------------------------------------------------------------------------------------------------------------|-----------|
| <b>FCC §15.247(A) (1) &amp; RSS-247 § 5.1 (B) - CHANNEL SEPARATION TEST .....</b>                                              | <b>52</b> |
| APPLICABLE STANDARD .....                                                                                                      | 52        |
| TEST PROCEDURE .....                                                                                                           | 52        |
| TEST DATA .....                                                                                                                | 53        |
| <b>FCC §15.247(A) (1) &amp; RSS-247 § 5.1 (A), RSS-GEN § 6.7 - 20 DB EMISSION BANDWIDTH &amp; 99% OCCUPIED BANDWIDTH .....</b> | <b>54</b> |
| APPLICABLE STANDARD .....                                                                                                      | 54        |
| TEST PROCEDURE .....                                                                                                           | 55        |
| TEST DATA .....                                                                                                                | 56        |
| <b>FCC §15.247(A) (1) (III) &amp; RSS-247 § 5.1 (D) - QUANTITY OF HOPPING CHANNEL TEST.....</b>                                | <b>57</b> |
| APPLICABLE STANDARD .....                                                                                                      | 57        |
| TEST PROCEDURE .....                                                                                                           | 57        |
| TEST DATA .....                                                                                                                | 58        |
| <b>FCC §15.247(A) (1) (III) &amp; RSS-247 § 5.1 (D) - TIME OF OCCUPANCY (DWELL TIME) .....</b>                                 | <b>59</b> |
| APPLICABLE STANDARD .....                                                                                                      | 59        |
| TEST PROCEDURE .....                                                                                                           | 59        |
| TEST DATA .....                                                                                                                | 60        |
| <b>FCC §15.247(B) (1) &amp; RSS-247§ 5.1(B) &amp;§ 5.4(B) - PEAK OUTPUT POWER MEASUREMENT .....</b>                            | <b>61</b> |
| APPLICABLE STANDARD .....                                                                                                      | 61        |
| TEST PROCEDURE .....                                                                                                           | 61        |
| TEST DATA .....                                                                                                                | 62        |
| <b>FCC §15.247(D) &amp; RSS-247 § 5.5 - BAND EDGES TESTING .....</b>                                                           | <b>63</b> |
| APPLICABLE STANDARD .....                                                                                                      | 63        |
| TEST PROCEDURE .....                                                                                                           | 63        |
| TEST DATA .....                                                                                                                | 64        |
| <b>EUT PHOTOGRAPHS .....</b>                                                                                                   | <b>65</b> |
| <b>TEST SETUP PHOTOGRAPHS .....</b>                                                                                            | <b>66</b> |
| <b>APPENDIX .....</b>                                                                                                          | <b>67</b> |
| APPENDIX A: 20dB EMISSION BANDWIDTH.....                                                                                       | 67        |
| APPENDIX B: OCCUPIED CHANNEL BANDWIDTH .....                                                                                   | 70        |
| APPENDIX C: MAXIMUM CONDUCTED PEAK OUTPUT POWER.....                                                                           | 73        |
| APPENDIX D: CARRIER FREQUENCY SEPARATION .....                                                                                 | 76        |
| APPENDIX E: TIME OF OCCUPANCY .....                                                                                            | 77        |
| APPENDIX F: NUMBER OF HOPPING CHANNELS .....                                                                                   | 80        |
| APPENDIX G: BAND EDGE MEASUREMENTS .....                                                                                       | 82        |

DOCUMENT REVISION HISTORY

| Revision Number | Report Number   | Description of Revision | Date of Revision |
|-----------------|-----------------|-------------------------|------------------|
| 0               | 2401V83797E-RFA | Original Report         | 2025/04/01       |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                                                                                                                                                                                                                                                 |                                                                                                                                                                                                                                                                                     |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| HVIN                                                                                                                                                                                                                                            | 35-202431BS                                                                                                                                                                                                                                                                         |
| FVIN                                                                                                                                                                                                                                            | 4610Be4106                                                                                                                                                                                                                                                                          |
| Product                                                                                                                                                                                                                                         | DECT 6.0 cordless phone                                                                                                                                                                                                                                                             |
| Tested Model                                                                                                                                                                                                                                    | EL1101-2                                                                                                                                                                                                                                                                            |
| Multiple Model(s)                                                                                                                                                                                                                               | FCC: EL1101, EL1101-3, EL1101-4, EL1101-5, EL1101-XY<br>IC: EL1101, EL1101-3, EL1101-4, EL1101-5                                                                                                                                                                                    |
| Frequency Range                                                                                                                                                                                                                                 | Bluetooth: 2402-2480MHz                                                                                                                                                                                                                                                             |
| Transmit Power                                                                                                                                                                                                                                  | 3.42dBm                                                                                                                                                                                                                                                                             |
| Modulation Technique                                                                                                                                                                                                                            | Bluetooth: GFSK, $\pi/4$ -DQPSK, 8DPSK                                                                                                                                                                                                                                              |
| Antenna Specification <sup>#</sup>                                                                                                                                                                                                              | 0dBi (provided by the applicant)                                                                                                                                                                                                                                                    |
| Voltage Range                                                                                                                                                                                                                                   | DC 6V from adapter                                                                                                                                                                                                                                                                  |
| Sample serial number                                                                                                                                                                                                                            | 2NUP-3 for Conducted and Radiated Emissions Test<br>2NUP-4 for RF Conducted Test (Assigned by BACL, Shenzhen)                                                                                                                                                                       |
| Sample/EUT Status                                                                                                                                                                                                                               | Good condition                                                                                                                                                                                                                                                                      |
| Adapter Information                                                                                                                                                                                                                             | Adapter 1<br>Model: A318-060040W-US1<br>Input: 100-120V~50-60Hz, 0.15A<br>Output: 6.0V, 0.4A<br>Adapter 2<br>Model: GQ06-060040-ZU<br>Input: 100-120V~50-60Hz, 0.15A<br>Output: 6.0V, 0.4A<br>Adapter 3<br>Model: VT05UUS06040<br>Input: 100-120V~60Hz 150mA<br>Output: 6.0V, 400mA |
| Note: The Multiple models are electrically identical with the test model except for model name, color and combination and collocation. Please refer to the declaration letter <sup>#</sup> for more detail, which was provided by manufacturer. |                                                                                                                                                                                                                                                                                     |

### Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commissions rules and RSS-247 Issue 3, August 2023, RSS-GEN Issue 5, Feb. 2021 Amendment 2 of the Innovation, Science and Economic Development Canada rules.

## Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices and RSS-247 Issue 3, August 2023, RSS-GEN Issue 5, Feb. 2021 Amendment 2 of the Innovation, Science and Economic Development Canada rules.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Each test item follows test standards and with no deviation.

## Measurement Uncertainty

| Parameter                          |                             | Uncertainty                           |
|------------------------------------|-----------------------------|---------------------------------------|
| Occupied Channel Bandwidth         |                             | ±5%                                   |
| RF output power, conducted         |                             | 0.72 dB(k=2, 95% level of confidence) |
| AC Power Lines Conducted Emissions | 9kHz-150kHz                 | 3.94dB(k=2, 95% level of confidence)  |
|                                    | 150kHz-30MHz                | 3.84dB(k=2, 95% level of confidence)  |
| Radiated Emissions                 | 9kHz - 30MHz                | 3.30dB(k=2, 95% level of confidence)  |
|                                    | 30MHz~200MHz (Horizontal)   | 4.48dB(k=2, 95% level of confidence)  |
|                                    | 30MHz~200MHz (Vertical)     | 4.55dB(k=2, 95% level of confidence)  |
|                                    | 200MHz~1000MHz (Horizontal) | 4.85dB(k=2, 95% level of confidence)  |
|                                    | 200MHz~1000MHz (Vertical)   | 5.05dB(k=2, 95% level of confidence)  |
|                                    | 1GHz - 6GHz                 | 5.35dB(k=2, 95% level of confidence)  |
|                                    | 6GHz - 18GHz                | 5.44dB(k=2, 95% level of confidence)  |
| Temperature                        |                             | ±1°C                                  |
| Humidity                           |                             | ±1%                                   |
| Supply voltages                    |                             | ±0.4%                                 |

*Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.*

## Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 5F(B-West) , 6F, 7F, the 3rd Phase of Wan Li Industrial Building D, Shihua Rd, FuTian Free Trade Zone, Shenzhen, China.

The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No. : 715558, the FCC Designation No. : CN5045.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0023.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The system was configured for testing in an engineering mode.

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 0       | 2402            | 40      | 2442            |
| 1       | 2403            | 41      | 2443            |
| 2       | 2404            | 42      | 2444            |
| ...     | ...             | ...     | ...             |
| ...     | ...             | ...     | ...             |
| 36      | 2438            | 75      | 2477            |
| 37      | 2439            | 76      | 2478            |
| 38      | 2440            | 77      | 2479            |
| 39      | 2441            | 78      | 2480            |

EUT was tested with Channel 0, 39 and 78.

### EUT Exercise Software

Software “SerilalPortUtility<sup>#</sup>” was used and the power level is 8<sup>#</sup>. The power level was provided by the applicant.

### Special Accessories

No special accessory.

### Equipment Modifications

No modification was made to the EUT tested.

### Support Equipment List and Details


| Manufacturer | Description | Model    | Serial Number |
|--------------|-------------|----------|---------------|
| YIKE         | PBX         | TC-208   | N/A           |
| Kinhao       | Telephone   | KT86AS   | N/A           |
| VTech        | PP          | EL1101-2 | N/A           |

**External I/O Cable**


| Cable Description                 | Length (m) | From Port | To  |
|-----------------------------------|------------|-----------|-----|
| Unshielded Un-detachable DC cable | 1.2        | Adapter   | EUT |
| Unshielded detachable RJ11 cable  | 3.0        | EUT       | PBX |

**Block Diagram of Test Setup**


For Conducted Emissions:



For Radiated Emissions below 1GHz:



For Radiated Emissions above 1GHz:



**SUMMARY OF TEST RESULTS**

| <b>FCC Rules</b>                        | <b>RSS Rules</b>                | <b>Description of Test</b>                        | <b>Result</b> |
|-----------------------------------------|---------------------------------|---------------------------------------------------|---------------|
| § 15.247 (i), §1.1307 (b) (3) & §2.1091 | /                               | MPE-Based Exemption                               | Compliant     |
|                                         | RSS-102 § 6.6                   | Field reference level exposure exemption limits   | Compliant     |
| FCC §15.203                             | RSS-Gen §6.8                    | Antenna Requirement                               | Compliant     |
| FCC §15.207(a)                          | RSS-Gen §8.8                    | AC Line Conducted Emissions                       | Compliant     |
| FCC §15.205, §15.209, §15.247(d)        | RSS-247 § 5.5, RSS-GEN § 8.10   | Radiated Emissions                                | Compliant     |
| FCC §15.247(a)(1)                       | RSS-247 § 5.1(a), RSS-GEN § 6.7 | 20 dB Emission Bandwidth & 99% Occupied Bandwidth | Compliant     |
| FCC §15.247(a)(1)                       | RSS-247 § 5.1 (b)               | Channel Separation Test                           | Compliant     |
| FCC §15.247(a)(1)(iii)                  | RSS-247 § 5.1 (d)               | Time of Occupancy (Dwell Time)                    | Compliant     |
| FCC §15.247(a)(1)(iii)                  | RSS-247 § 5.1 (d)               | Quantity of hopping channel Test                  | Compliant     |
| FCC §15.247(b)(1)                       | RSS-247 § 5.1(b) & § 5.4(b)     | Peak Output Power Measurement                     | Compliant     |
| FCC §15.247(d)                          | RSS-247 § 5.5                   | Band edges                                        | Compliant     |

**TEST EQUIPMENT LIST**

| Manufacturer                   | Description                       | Model             | Serial Number          | Calibration Date | Calibration Due Date |
|--------------------------------|-----------------------------------|-------------------|------------------------|------------------|----------------------|
| <b>Conducted Emission Test</b> |                                   |                   |                        |                  |                      |
| Rohde & Schwarz                | EMI Test Receiver                 | ESCI              | 101120                 | 2024/12/04       | 2025/12/03           |
| Rohde & Schwarz                | LISN                              | ENV216            | 101613                 | 2024/12/04       | 2025/12/03           |
| Rohde & Schwarz                | Transient Limiter                 | ESH3Z2            | DE25985                | 2024/05/21       | 2025/05/20           |
| Unknown                        | CE Cable                          | Unknown           | UF A210B-1-0720-504504 | 2024/05/21       | 2025/05/20           |
| Audix                          | EMI Test software                 | E3                | 191218(V9)             | NCR              | NCR                  |
| <b>Radiated Emission Test</b>  |                                   |                   |                        |                  |                      |
| Rohde & Schwarz                | EMI Test Receiver                 | ESR3              | 102455                 | 2024/12/04       | 2025/12/03           |
| Sonoma instrument              | Pre-amplifier                     | 310 N             | 186238                 | 2024/05/21       | 2025/05/20           |
| Sunol Sciences                 | Broadband Antenna                 | JB1               | A040904-1              | 2023/07/20       | 2026/07/19           |
| Unknown                        | Cable                             | Chamber A Cable 1 | N/A                    | 2024/06/18       | 2025/06/17           |
| Unknown                        | Cable                             | XH500C            | J-10M-A                | 2024/06/18       | 2025/06/17           |
| BACL                           | Active Loop Antenna               | 1313-1A           | 4031911                | 2024/05/14       | 2027/05/13           |
| Unknown                        | Cable                             | 2Y194             | 0735                   | 2024/12/04       | 2025/12/03           |
| Unknown                        | Cable                             | PNG214            | 1354                   | 2024/12/04       | 2025/12/03           |
| Audix                          | EMI Test software                 | E3                | 19821b(V9)             | NCR              | NCR                  |
| Rohde & Schwarz                | Spectrum Analyzer                 | FSV40             | 101605                 | 2024/03/27       | 2025/03/26           |
| A.H.System                     | Preamplifier                      | PAM-0118P         | 489                    | 2024/11/15       | 2025/11/14           |
| Schwarzbeck                    | Horn Antenna                      | BBHA9120D(1201)   | 1143                   | 2023/07/26       | 2026/07/25           |
| Unknown                        | RF Cable                          | KMSE              | 735                    | 2024/12/04       | 2025/12/03           |
| Unknown                        | RF Cable                          | UFA147            | 219661                 | 2024/12/04       | 2025/12/03           |
| Unknown                        | RF Cable                          | XH750A-N          | J-10M                  | 2024/12/04       | 2025/12/03           |
| JD                             | Filter Switch Unit                | DT7220FSU         | DS79906                | 2024/09/09       | 2025/09/08           |
| JD                             | Multiplex Switch Test Control Set | DT7220SCU         | DS79903                | 2024/09/09       | 2025/09/08           |
| A.H.System                     | Pre-amplifier                     | PAM-1840VH        | 190                    | 2024/06/18       | 2025/06/17           |
| Electro-Mechanics Co           | Horn Antenna                      | 3116              | 9510-2270              | 2023/09/18       | 2026/09/17           |
| UTIFLEX                        | RF Cable                          | NO. 13            | 232308-001             | 2024/06/18       | 2025/06/17           |
| Audix                          | EMI Test software                 | E3                | 191218(V9)             | NCR              | NCR                  |

| Manufacturer      | Description       | Model   | Serial Number | Calibration Date | Calibration Due Date |
|-------------------|-------------------|---------|---------------|------------------|----------------------|
| RF Conducted Test |                   |         |               |                  |                      |
| Rohde & Schwarz   | Spectrum Analyzer | FSU26   | 200120        | 2024/12/04       | 2025/12/03           |
| Unknown           | 10dB Attenuator   | Unknown | F-03-EM122    | 2024/06/27       | 2025/06/26           |

\* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## FCC §15.247 (i) & §1.1307 (b) (3) & §2.1091- MPE-BASED EXEMPTION

### Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(3)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

| RF Source frequency (MHz) | Threshold ERP (watts) |
|---------------------------|-----------------------|
| 0.3-1.34                  | $1,920 R^2$ .         |
| 1.34-30                   | $3,450 R^2/f^2$ .     |
| 30-300                    | $3.83 R^2$ .          |
| 300-1,500                 | $0.0128 R^2 f$ .      |
| 1,500-100,000             | $19.2 R^2$ .          |

R is the minimum separation distance in meters

f = frequency in MHz

### Result

| Mode | Frequency (MHz)   | Tune up conducted power <sup>#</sup> | Antenna Gain <sup>#</sup> |       | ERP   |        | Evaluation Distance (m) | ERP Limit (W) |
|------|-------------------|--------------------------------------|---------------------------|-------|-------|--------|-------------------------|---------------|
|      |                   | (dBm)                                | (dBi)                     | (dBd) | (dBm) | (W)    |                         |               |
| BT   | 2402-2480         | 3.5                                  | 0                         | -2.15 | 1.35  | 0.0014 | 0.2                     | 0.768         |
| DECT | 1921.536-1928.448 | 20.2                                 | 0                         | -2.15 | 18.05 | 0.064  | 0.2                     | 0.768         |

Note 1: The tune-up power and antenna gain was declared by the applicant.

Note 2: 0dBd=2.15dBi.

Note 3: The DECT function can transmit at the same time with the BT function.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Compliant.**

## **RSS-102 § 6.6 - FIELD REFERENCE LEVEL EXPOSURE EXEMPTION LIMITS**

---

### **Applicable Standard**

According to RSS-102 Issue 6§6.6:

Field reference level (FRL) exposure evaluation is required if the separation distance between the user and/or bystander and the device's radiating element is greater than 20 cm (i.e. mobile devices), except when the device operates as follows:

- below 20 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 1 W (adjusted for tune-up tolerance)
- at or above 20 MHz and below 48 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than  $4.49/f^{0.5}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz
- at or above 48 MHz and below 300 MHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 0.6 W (adjusted for tune-up tolerance)
- at or above 300 MHz and below 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than  $1.31 \times 10^{-2} f^{0.6834}$  W (adjusted for tune-up tolerance), where  $f$  is in MHz
- at or above 6 GHz and the source-based, time-averaged maximum EIRP of the device is equal to or less than 5 W (adjusted for tune-up tolerance) In these cases, the information contained in the RF exposure technical brief may be limited to information that demonstrates how the EIRP was derived.

### **Result**

#### **Calculated Data:**

The max tune-up conducted output power is 3.5dBm, antenna gain is 0dBi.

Time-averaged maximum e.i.r.p. of the device is  $3.5\text{dBm} + 0\text{dBi} = 3.5\text{dBm} = 0.002\text{W}$

The worst case is  $f = 2402$  MHz:

The limit is  $1.31 \times 10^{-2} f^{0.6834} \text{ W} = 2.68\text{W}$

$0.002\text{W} < 2.68\text{W}$

**So the RF Exposure evaluation can be exempted.**

## FCC §15.203 & RSS-GEN §6.8 - ANTENNA REQUIREMENT

### Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

According to FCC § 15.203, the applicant for equipment certification shall provide a list of all antenna types that may be used with the transmitter, where applicable (i.e. for transmitters with detachable antenna), indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna. The test report shall demonstrate the compliance of the transmitter with the limit for maximum equivalent isotropically radiated power (e.i.r.p.) specified in the applicable RSS, when the transmitter is equipped with any antenna type, selected from this list.

For expediting the testing, measurements may be performed using only the antenna with highest gain of each combination of transmitter and antenna type, with the transmitter output power set at the maximum level. However, the transmitter shall comply with the applicable requirements under all operational conditions and when in combination with any type of antenna from the list provided in the test report (and in the notice to be included in the user manual, provided below).

When measurements at the antenna port are used to determine the RF output power, the effective gain of the device's antenna shall be stated, based on a measurement or on data from the antenna's manufacturer.

The test report shall state the RF power, output power setting and spurious emission measurements with each antenna type that is used with the transmitter being tested.

For licence-exempt equipment with detachable antennas, the user manual shall also contain the following notice in a conspicuous location:

This radio transmitter [enter the device's ISED certification number] has been approved by Innovation, Science and Economic Development Canada to operate with the antenna types listed below, with the maximum permissible gain indicated. Antenna types not included in this list that have a gain greater than the maximum gain indicated for any type listed are strictly prohibited for use with this device. Immediately following the above notice, the manufacturer shall provide a list of all antenna types which can be used with the transmitter, indicating the maximum permissible antenna gain (in dBi) and the required impedance for each antenna type.

### Antenna Connector Construction

The EUT has one internal antenna arrangement which was permanently attached for Bluetooth and the maximum antenna gain<sup>#</sup> is 0dBi, fulfill the requirement of this section. Please refer to the EUT photos.

| Antenna Type | Antenna Gain <sup>#</sup> | Impedance | Frequency Range |
|--------------|---------------------------|-----------|-----------------|
| Integral     | 0dBi                      | 50Ω       | 2.4~2.5GHz      |

**Result: Compliant**

## FCC §15.207 (a) & RSS-GEN § 8.8 - AC LINE CONDUCTED EMISSIONS

### Applicable Standard

FCC §15.207(a), RSS-GEN § 8.8

### EUT Setup



Note: 1. Support units were connected to second LISN.  
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The measurement procedure of EUT setup is according with ANSI C63.10-2013. The related limit was specified in FCC Part 15.207 & RSS-Gen.

The spacing between the peripherals was 10 cm.

### EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

| Frequency Range  | IF B/W |
|------------------|--------|
| 150 kHz – 30 MHz | 9 kHz  |

### Test Procedure

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

## Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Note: The term "cable loss" refers to the combination of a cable and a 10dB transient limiter (attenuator).

## Test Data

### Environmental Conditions


|                    |             |
|--------------------|-------------|
| Temperature:       | 20~25 °C    |
| Relative Humidity: | 45~55 %     |
| ATM Pressure:      | 100~103 kPa |

*The testing was performed by Macy Shi on 2025-02-25.*

*EUT operation mode: Transmitting (Maximum output power mode,  $\pi/4$ -DQPSK High Channel)*

For Adapter 1

AC 120V/60 Hz, Line



Trace: 1

Condition: Line


Project : 2401V83797E-RF

tester : Macy.shi Note:Transmitting

Setting : RBW:9kHz VBW:Auto SWT:Auto

|   | Read  |       | LISN  | Cable  | Limit | Over  |                |
|---|-------|-------|-------|--------|-------|-------|----------------|
|   | Freq  | Level | Level | Factor | Loss  | Line  | Limit          |
|   | MHz   | dBuV  | dBuV  | dB     | dB    | dBuV  | dB             |
| 1 | 2.309 | 23.60 | 44.84 | 11.06  | 10.18 | 56.00 | -11.16 QP      |
| 2 | 2.594 | 26.21 | 47.40 | 11.02  | 10.17 | 56.00 | -8.60 QP       |
| 3 | 3.009 | 27.30 | 48.46 | 10.98  | 10.18 | 56.00 | -7.54 QP       |
| 4 | 3.276 | 28.30 | 49.45 | 10.96  | 10.19 | 56.00 | -6.55 QP       |
| 5 | 3.454 | 27.81 | 48.94 | 10.94  | 10.19 | 56.00 | -7.06 QP       |
| 6 | 3.681 | 26.30 | 47.42 | 10.92  | 10.20 | 56.00 | -8.58 QP       |
|   | Read  |       | LISN  | Cable  | Limit | Over  |                |
|   | Freq  | Level | Level | Factor | Loss  | Line  | Limit          |
|   | MHz   | dBuV  | dBuV  | dB     | dB    | dBuV  | dB             |
| 1 | 2.261 | 12.86 | 34.10 | 11.06  | 10.18 | 46.00 | -11.90 Average |
| 2 | 2.854 | 14.79 | 35.97 | 11.00  | 10.18 | 46.00 | -10.03 Average |
| 3 | 3.241 | 15.29 | 36.44 | 10.96  | 10.19 | 46.00 | -9.56 Average  |
| 4 | 3.454 | 15.92 | 37.05 | 10.94  | 10.19 | 46.00 | -8.95 Average  |
| 5 | 3.799 | 15.02 | 36.13 | 10.91  | 10.20 | 46.00 | -9.87 Average  |
| 6 | 6.878 | 12.48 | 33.28 | 10.61  | 10.19 | 50.00 | -16.72 Average |

## AC 120V/60 Hz, Neutral



Trace: 1

Condition: Neutral

Project : 2401V83797E-RF

tester : Macy.shi Note:Transmitting


Setting : RBW:9kHz VBW:Auto SWT:Auto

|   | Freq  | Read Level | LISN Level | Cable Factor | Cable Loss | Limit Line | Over Limit | Remark |
|---|-------|------------|------------|--------------|------------|------------|------------|--------|
|   | MHz   | dBuV       | dBuV       | dB           | dB         | dBuV       | dB         |        |
| 1 | 2.794 | 20.30      | 41.32      | 10.84        | 10.18      | 56.00      | -14.68     | QP     |
| 2 | 2.978 | 22.30      | 43.35      | 10.87        | 10.18      | 56.00      | -12.65     | QP     |
| 3 | 3.173 | 22.39      | 43.48      | 10.90        | 10.19      | 56.00      | -12.52     | QP     |
| 4 | 3.417 | 21.50      | 42.62      | 10.93        | 10.19      | 56.00      | -13.38     | QP     |
| 5 | 3.681 | 21.90      | 43.06      | 10.96        | 10.20      | 56.00      | -12.94     | QP     |
| 6 | 4.049 | 21.90      | 43.10      | 10.99        | 10.21      | 56.00      | -12.90     | QP     |

|   | Freq  | Read Level | LISN Level | Cable Factor | Cable Loss | Limit Line | Over Limit | Remark  |
|---|-------|------------|------------|--------------|------------|------------|------------|---------|
|   | MHz   | dBuV       | dBuV       | dB           | dB         | dBuV       | dB         |         |
| 1 | 2.854 | 9.85       | 30.88      | 10.85        | 10.18      | 46.00      | -15.12     | Average |
| 2 | 3.074 | 11.08      | 32.15      | 10.89        | 10.18      | 46.00      | -13.85     | Average |
| 3 | 3.454 | 11.70      | 32.83      | 10.94        | 10.19      | 46.00      | -13.17     | Average |
| 4 | 3.799 | 11.03      | 32.21      | 10.98        | 10.20      | 46.00      | -13.79     | Average |
| 5 | 4.092 | 8.78       | 29.97      | 10.98        | 10.21      | 46.00      | -16.03     | Average |
| 6 | 7.025 | 7.94       | 28.73      | 10.60        | 10.19      | 50.00      | -21.27     | Average |

For Adapter 2


AC 120V/60 Hz, Line



|   |        | Read  |       | LISN   | Cable | Limit | Over   |        |
|---|--------|-------|-------|--------|-------|-------|--------|--------|
|   | Freq   | Level | Level | Factor | Loss  | Line  | Limit  | Remark |
|   | MHz    | dBuV  | dBuV  | dB     | dB    | dBuV  | dB     |        |
| 1 | 0.402  | 29.32 | 49.97 | 10.55  | 10.10 | 57.81 | -7.84  | QP     |
| 2 | 0.424  | 25.01 | 45.66 | 10.54  | 10.11 | 57.37 | -11.71 | QP     |
| 3 | 0.529  | 11.05 | 31.75 | 10.57  | 10.13 | 56.00 | -24.25 | QP     |
| 4 | 0.809  | 15.30 | 36.20 | 10.78  | 10.12 | 56.00 | -19.80 | QP     |
| 5 | 6.186  | 14.11 | 34.97 | 10.67  | 10.19 | 60.00 | -25.03 | QP     |
| 6 | 14.594 | 12.31 | 32.83 | 10.30  | 10.22 | 60.00 | -27.17 | QP     |

|   |       | Read  |       | LISN   | Cable | Limit | Over   |         |
|---|-------|-------|-------|--------|-------|-------|--------|---------|
|   | Freq  | Level | Level | Factor | Loss  | Line  | Limit  | Remark  |
|   | MHz   | dBuV  | dBuV  | dB     | dB    | dBuV  | dB     |         |
| 1 | 0.377 | 11.76 | 32.43 | 10.56  | 10.11 | 48.34 | -15.91 | Average |
| 2 | 0.398 | 20.81 | 41.46 | 10.55  | 10.10 | 47.90 | -6.44  | Average |
| 3 | 0.415 | 21.41 | 42.06 | 10.54  | 10.11 | 47.55 | -5.49  | Average |
| 4 | 0.456 | 10.81 | 31.45 | 10.52  | 10.12 | 46.76 | -15.31 | Average |
| 5 | 1.480 | 4.99  | 26.03 | 10.88  | 10.16 | 46.00 | -19.97 | Average |
| 6 | 6.319 | 6.48  | 27.32 | 10.65  | 10.19 | 50.00 | -22.68 | Average |

## AC 120V/60 Hz, Neutral



Condition: Neutral

Project : 2401V83797E-RF


tester : Macy.shi Note:Transmitting

Setting : RBW:9kHz VBW:Auto SWT:Auto

|   | Freq   | Read Level | LISN Level | Cable Factor | Cable Loss | Limit Line | Over Limit | Remark  |
|---|--------|------------|------------|--------------|------------|------------|------------|---------|
|   | MHz    | dBuV       | dBuV       | dB           | dB         | dBuV       | dB         |         |
| 1 | 0.369  | 15.70      | 36.41      | 10.60        | 10.11      | 58.52      | -22.11     | QP      |
| 2 | 0.393  | 23.90      | 44.58      | 10.58        | 10.10      | 57.99      | -13.41     | QP      |
| 3 | 0.415  | 24.60      | 45.27      | 10.56        | 10.11      | 57.55      | -12.28     | QP      |
| 4 | 0.447  | 13.80      | 34.46      | 10.54        | 10.12      | 56.93      | -22.47     | QP      |
| 5 | 1.593  | 10.20      | 31.10      | 10.73        | 10.17      | 56.00      | -24.90     | QP      |
| 6 | 6.121  | 15.59      | 36.48      | 10.70        | 10.19      | 60.00      | -23.52     | QP      |
|   | Freq   | Read Level | LISN Level | Cable Factor | Cable Loss | Limit Line | Over Limit | Remark  |
|   | MHz    | dBuV       | dBuV       | dB           | dB         | dBuV       | dB         |         |
| 1 | 0.373  | 5.40       | 26.11      | 10.60        | 10.11      | 48.43      | -22.32     | Average |
| 2 | 0.393  | 11.41      | 32.09      | 10.58        | 10.10      | 47.99      | -15.90     | Average |
| 3 | 0.415  | 9.68       | 30.35      | 10.56        | 10.11      | 47.55      | -17.20     | Average |
| 4 | 0.471  | 5.62       | 26.27      | 10.52        | 10.13      | 46.49      | -20.22     | Average |
| 5 | 5.805  | 2.32       | 23.23      | 10.73        | 10.18      | 50.00      | -26.77     | Average |
| 6 | 14.594 | 2.88       | 23.41      | 10.31        | 10.22      | 50.00      | -26.59     | Average |

For Adapter 3


AC 120V/60 Hz, Line



Condition: Line  
Project : 2401V83797E-RF  
tester : Macy.shi Note:Transmitting  
Setting : RBW:9kHz VBW:Auto SWT:Auto

|   | Read  |       | LISN  | Cable  | Limit | Over  |                |
|---|-------|-------|-------|--------|-------|-------|----------------|
|   | Freq  | Level | Level | Loss   | Line  | Limit | Remark         |
|   | MHz   | dBuV  | dBuV  | dB     | dB    | dBuV  | dB             |
| 1 | 1.928 | 26.43 | 47.69 | 11.07  | 10.19 | 56.00 | -8.31 QP       |
| 2 | 2.707 | 28.63 | 49.81 | 11.01  | 10.17 | 56.00 | -6.19 QP       |
| 3 | 3.759 | 26.36 | 47.48 | 10.92  | 10.20 | 56.00 | -8.52 QP       |
| 4 | 4.006 | 29.80 | 50.91 | 10.90  | 10.21 | 56.00 | -5.09 QP       |
| 5 | 4.269 | 27.69 | 48.76 | 10.87  | 10.20 | 56.00 | -7.24 QP       |
| 6 | 4.407 | 27.88 | 48.93 | 10.85  | 10.20 | 56.00 | -7.07 QP       |
|   | Read  |       | LISN  | Cable  | Limit | Over  |                |
|   | Freq  | Level | Level | Factor | Loss  | Line  | Limit          |
|   | MHz   | dBuV  | dBuV  | dB     | dB    | dBuV  | dB             |
| 1 | 2.594 | 12.75 | 33.94 | 11.02  | 10.17 | 46.00 | -12.06 Average |
| 2 | 2.707 | 12.07 | 33.25 | 11.01  | 10.17 | 46.00 | -12.75 Average |
| 3 | 3.964 | 13.96 | 35.07 | 10.90  | 10.21 | 46.00 | -10.93 Average |
| 4 | 4.269 | 14.63 | 35.70 | 10.87  | 10.20 | 46.00 | -10.30 Average |
| 5 | 4.647 | 12.90 | 33.91 | 10.82  | 10.19 | 46.00 | -12.09 Average |
| 6 | 7.252 | 13.48 | 34.24 | 10.57  | 10.19 | 50.00 | -15.76 Average |

## AC 120V/60 Hz, Neutral



Trace: 1

Condition: Neutral

Project : 2401V83797E-RF

tester : Macy.shi Note:Transmitting

Setting : RBW:9kHz VBW:Auto SWT:Auto

|   | Freq  | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark |
|---|-------|------------|------------|-------------|------------|------------|------------|--------|
|   | MHz   | dBuV       | dBuV       | dB          | dB         | dBuV       | dB         |        |
| 1 | 2.435 | 25.10      | 46.06      | 10.79       | 10.17      | 56.00      | -9.94      | QP     |
| 2 | 4.006 | 30.10      | 51.31      | 11.00       | 10.21      | 56.00      | -4.69      | QP     |
| 3 | 4.092 | 28.70      | 49.89      | 10.98       | 10.21      | 56.00      | -6.11      | QP     |
| 4 | 4.269 | 26.41      | 47.56      | 10.95       | 10.20      | 56.00      | -8.44      | QP     |
| 5 | 4.407 | 27.50      | 48.63      | 10.93       | 10.20      | 56.00      | -7.37      | QP     |
| 6 | 7.025 | 29.40      | 50.19      | 10.60       | 10.19      | 60.00      | -9.81      | QP     |

|   | Freq  | Read Level | LISN Level | LISN Factor | Cable Loss | Limit Line | Over Limit | Remark  |
|---|-------|------------|------------|-------------|------------|------------|------------|---------|
|   | MHz   | dBuV       | dBuV       | dB          | dB         | dBuV       | dB         |         |
| 1 | 0.385 | 9.69       | 30.39      | 10.59       | 10.11      | 48.17      | -17.78     | Average |
| 2 | 2.622 | 6.35       | 27.34      | 10.82       | 10.17      | 46.00      | -18.66     | Average |
| 3 | 4.006 | 10.68      | 31.89      | 11.00       | 10.21      | 46.00      | -14.11     | Average |
| 4 | 4.269 | 11.05      | 32.20      | 10.95       | 10.20      | 46.00      | -13.80     | Average |
| 5 | 6.878 | 9.34       | 30.14      | 10.61       | 10.19      | 50.00      | -19.86     | Average |
| 6 | 7.407 | 8.70       | 29.47      | 10.58       | 10.19      | 50.00      | -20.53     | Average |


## FCC §15.209, §15.205 & §15.247(D) & RSS-247§ 5.5 - SPURIOUS EMISSIONS

### Applicable Standard


FCC §15.205; §15.209; §15.247(d); RSS-247§ 5.5; RSS-GEN § 8.10


### EUT Setup

9 kHz-30MHz:



30MHz-1GHz:



**Above 1GHz:**

The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247, RSS-247, RSS-Gen limits.

**EMI Test Receiver & Spectrum Analyzer Setup**

The EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

| Frequency Range   | RBW                                                           | Video B/W | IF B/W  | Measurement | Detector |
|-------------------|---------------------------------------------------------------|-----------|---------|-------------|----------|
| 9 kHz – 150 kHz   | /                                                             | /         | 200 Hz  | QP          | QP       |
|                   | 300 Hz                                                        | 1 kHz     | /       | PK          | Peak     |
| 150 kHz – 30 MHz  | /                                                             | /         | 9 kHz   | QP          | QP       |
|                   | 10 kHz                                                        | 30 kHz    | /       | PK          | Peak     |
| 30 MHz – 1000 MHz | /                                                             | /         | 120 kHz | QP          | QP       |
|                   | 100 kHz                                                       | 300 kHz   | /       | PK          | Peak     |
| Above 1 GHz       | Harmonics                                                     |           |         |             |          |
|                   | 1MHz                                                          | 3 MHz     | /       | PK          | Peak     |
|                   | Average Emission Level=Peak Emission Level+20*log(Duty cycle) |           |         |             |          |
|                   | Band Edge & Other Emissions                                   |           |         |             |          |
|                   | 1MHz                                                          | 3 MHz     | /       | PK          | Peak     |
|                   | 1MHz                                                          | ≥10 Hz    | /       | Average     | Peak     |

For Duty cycle measurement:

Use the duty cycle factor correction factor method per 15.35(c).

Duty cycle=On time/100milliseconds, On time= $N_1 \cdot L_1 + N_2 \cdot L_2 + \dots + N_{n-1} \cdot L_{n-1} + N_n \cdot L_n$ ,

Where  $N_1$  is number of type 1 pulses,  $L_1$  is length of type 1 pulse, etc.

## Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

All final data was recorded in Quasi-peak detection mode except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, average detection modes for frequency bands 9–90 kHz and 110–490 kHz, peak and average detection modes for frequencies above 1 GHz.

For 9 kHz-30MHz, the report shall list the six emissions with the smallest margin relative to the limit, for each of the three antenna orientations (parallel, perpendicular, and ground-parallel) unless the margin is greater than 20 dB.

If the maximized peak measured value complies with under the QP/Average limit more than 6dB, then it is unnecessary to perform an QP/Average measurement.

All emissions under the average limit and under the noise floor have not recorded in the report.

## Factor & Over Limit/Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor}\end{aligned}$$

## Test Data

### Environmental Conditions

|                    |                 |
|--------------------|-----------------|
| Temperature:       | 23.2~23.4 °C    |
| Relative Humidity: | 46~47 %         |
| ATM Pressure:      | 101.3~102.8 kPa |

*The testing was performed by Anson Su on 2025-02-26 for below 1GHz and Visen Wu on 2025-02-25 for above 1GHz.*

*EUT operation mode: Transmitting*


*Note: The spurious emission from 9 kHz-30MHz of IC RSS-Gen standard, the unit of final result on the test plots are dBμV/m, so the limit should be added by 51,5 dB from dBμA/m to dBμV/m.*

**9 kHz-30MHz:** (Maximum output power mode,  $\pi/4$ -DQPSK High Channel)

Note: When the test result of peak was less than the limit of QP/Average more than 6dB, just peak value were recorded.


For Adapter 1

Parallel (worst case)



Site : Chamber A  
 Condition : 3m  
 Project Number : 2401V83797E-RF  
 Test Mode : BT Transmitting  
 Detector: Peak RBW/VBW: 0.3/1kHz  
 Tester : Anson Su


|   | Freq | Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|------|--------|------------|--------|------------|------------|--------|
|   | MHz  | dB/m   | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 0.01 | 38.11  | 26.98      | 65.09  | 128.08     | -62.99     | Peak   |
| 2 | 0.02 | 33.04  | 27.20      | 60.24  | 121.98     | -61.74     | Peak   |
| 3 | 0.04 | 26.05  | 21.18      | 47.23  | 116.36     | -69.13     | Peak   |
| 4 | 0.06 | 22.00  | 23.32      | 45.32  | 112.35     | -67.03     | Peak   |
| 5 | 0.10 | 17.49  | 19.39      | 36.88  | 108.00     | -71.12     | Peak   |
| 6 | 0.13 | 15.52  | 18.54      | 34.06  | 105.14     | -71.08     | Peak   |



Site : Chamber A  
 Condition : 3m  
 Project Number : 2401V83797E-RF  
 Test Mode : BT Transmitting  
 Detector: Peak RBW/VBW: 10/30kHz  
 Tester : Anson Su


|   | Freq | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz  | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 0.47 | 4.22   | 34.95         | 39.17  | 94.25         | -55.08        | Peak   |
| 2 | 0.59 | 2.42   | 34.35         | 36.77  | 72.18         | -35.41        | Peak   |
| 3 | 0.88 | -0.70  | 35.18         | 34.48  | 68.61         | -34.13        | Peak   |
| 4 | 1.03 | -1.69  | 32.61         | 30.92  | 67.22         | -36.30        | Peak   |
| 5 | 1.24 | -2.44  | 32.78         | 30.34  | 65.54         | -35.20        | Peak   |
| 6 | 1.42 | -3.06  | 32.05         | 28.99  | 64.34         | -35.35        | Peak   |

For Adapter 2  
Parallel (worst case)



Site : Chamber A  
Condition : 3m  
Project Number : 2401V83797E-RF  
Test Mode : BT Transmitting  
Detector: Peak RBW/VBW: 0.3/1kHz  
Tester : Anson Su


|   | Freq | Factor | Read Level | Level  | Limit  | Over Limit | Remark |
|---|------|--------|------------|--------|--------|------------|--------|
|   | MHz  | dB/m   | dBuV       | dBuV/m | dBuV/m | dB         |        |
| 1 | 0.01 | 37.92  | 27.03      | 64.95  | 127.86 | -62.91     | Peak   |
| 2 | 0.02 | 33.04  | 27.20      | 60.24  | 121.98 | -61.74     | Peak   |
| 3 | 0.04 | 26.05  | 21.18      | 47.23  | 116.36 | -69.13     | Peak   |
| 4 | 0.06 | 22.00  | 23.32      | 45.32  | 112.35 | -67.03     | Peak   |
| 5 | 0.10 | 17.49  | 19.39      | 36.88  | 108.00 | -71.12     | Peak   |
| 6 | 0.13 | 15.52  | 18.54      | 34.06  | 105.14 | -71.08     | Peak   |



Site : Chamber A  
 Condition : 3m  
 Project Number : 2401V83797E-RF  
 Test Mode : BT Transmitting  
 Detector: Peak RBW/VBW: 10/30kHz  
 Tester : Anson Su


|   | Freq | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz  | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 0.50 | 3.47   | 33.75         | 37.22  | 73.60         | -36.38        | Peak   |
| 2 | 0.65 | 1.71   | 34.95         | 36.66  | 71.32         | -34.66        | Peak   |
| 3 | 0.83 | -0.32  | 33.78         | 33.46  | 69.14         | -35.68        | Peak   |
| 4 | 1.05 | -1.77  | 32.73         | 30.96  | 67.02         | -36.06        | Peak   |
| 5 | 1.27 | -2.51  | 32.74         | 30.23  | 65.38         | -35.15        | Peak   |
| 6 | 1.52 | -3.41  | 32.19         | 28.78  | 63.74         | -34.96        | Peak   |

For Adapter 3  
Parallel (worst case)



Site : Chamber A  
Condition : 3m  
Project Number : 2401V83797E-RF  
Test Mode : BT Transmitting  
Detector: Peak RBW/VBW: 0.3/1kHz  
Tester : Anson Su

|   | Freq | Factor | Read Level | Limit Level | Limit Line | Over Limit | Remark |
|---|------|--------|------------|-------------|------------|------------|--------|
|   | MHz  | dB/m   | dBuV       | dBuV/m      | dBuV/m     | dB         |        |
| 1 | 0.01 | 37.92  | 27.03      | 64.95       | 127.86     | -62.91     | Peak   |
| 2 | 0.02 | 33.04  | 27.20      | 60.24       | 121.98     | -61.74     | Peak   |
| 3 | 0.04 | 26.05  | 21.18      | 47.23       | 116.36     | -69.13     | Peak   |
| 4 | 0.06 | 22.00  | 23.32      | 45.32       | 112.35     | -67.03     | Peak   |
| 5 | 0.10 | 17.49  | 19.39      | 36.88       | 108.00     | -71.12     | Peak   |
| 6 | 0.13 | 15.52  | 18.54      | 34.06       | 105.14     | -71.08     | Peak   |




Site : Chamber A  
 Condition : 3m  
 Project Number : 2401V83797E-RF  
 Test Mode : BT Transmitting  
 Detector: Peak RBW/VBW: 10/30kHz  
 Tester : Anson Su

|   | Freq | Factor | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|------|--------|------------|--------|------------|------------|--------|
|   | MHz  | dB/m   | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 0.55 | 2.88   | 33.71      | 36.59  | 72.77      | -36.18     | Peak   |
| 2 | 0.63 | 1.89   | 32.88      | 34.77  | 71.53      | -36.76     | Peak   |
| 3 | 0.73 | 0.72   | 33.10      | 33.82  | 70.25      | -36.43     | Peak   |
| 4 | 1.01 | -1.62  | 33.28      | 31.66  | 67.39      | -35.73     | Peak   |
| 5 | 1.26 | -2.51  | 32.73      | 30.22  | 65.39      | -35.17     | Peak   |
| 6 | 1.54 | -3.46  | 31.00      | 27.54  | 63.66      | -36.12     | Peak   |

30MHz-1GHz: (Maximum output power mode,  $\pi/4$ -DQPSK High Channel)

For Adapter 1


Horizontal



Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2401V83797E-RF  
Test Mode : BT Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su


|   | Freq Factor |        | Read  | Limit  | Over   | Remark    |
|---|-------------|--------|-------|--------|--------|-----------|
|   | MHz         | dB/m   | Level | Level  | Line   |           |
|   | MHz         | dB/m   | dBuV  | dBuV/m | dBuV/m | dB        |
| 1 | 40.17       | -12.47 | 24.25 | 11.78  | 40.00  | -28.22 QP |
| 2 | 82.03       | -17.92 | 26.67 | 8.75   | 40.00  | -31.25 QP |
| 3 | 147.40      | -12.31 | 29.11 | 16.80  | 43.50  | -26.70 QP |
| 4 | 382.09      | -9.04  | 26.94 | 17.90  | 46.00  | -28.10 QP |
| 5 | 665.80      | -3.94  | 26.15 | 22.21  | 46.00  | -23.79 QP |
| 6 | 819.55      | -1.97  | 25.79 | 23.82  | 46.00  | -22.18 QP |

# Vertical



Site : Chamber A  
 Condition : 3m Vertical  
 Project Number : 2401V83797E-RF  
 Test Mode : BT Transmitting  
 Detector: Peak RBW/VBW: 100/300kHz  
 Tester : Anson Su


|   | Freq Factor |        | Read Level | Limit Level | Over Limit | Remark    |
|---|-------------|--------|------------|-------------|------------|-----------|
|   | MHz         | dB/m   | dBuV       | dBuV/m      | dBuV/m     | dB        |
| 1 | 38.48       | -11.41 | 32.61      | 21.20       | 40.00      | -18.80 QP |
| 2 | 52.71       | -17.96 | 30.79      | 12.83       | 40.00      | -27.17 QP |
| 3 | 165.92      | -12.95 | 30.60      | 17.65       | 43.50      | -25.85 QP |
| 4 | 400.08      | -8.41  | 25.70      | 17.29       | 46.00      | -28.71 QP |
| 5 | 699.92      | -3.52  | 26.44      | 22.92       | 46.00      | -23.08 QP |
| 6 | 831.13      | -1.88  | 26.02      | 24.14       | 46.00      | -21.86 QP |

*For Adapter 2***Horizontal**

Site : Chamber A  
Condition : 3m Horizontal  
Project Number : 2401V83797E-RF  
Test Mode : BT Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su

|   | Freq Factor |        | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|-------------|--------|------------|--------|------------|------------|--------|
|   | MHz         | dB/m   | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 40.40       | -12.59 | 24.31      | 11.72  | 40.00      | -28.28     | QP     |
| 2 | 96.90       | -16.53 | 24.64      | 8.11   | 43.50      | -35.39     | QP     |
| 3 | 120.59      | -11.44 | 28.31      | 16.87  | 43.50      | -26.63     | QP     |
| 4 | 385.62      | -8.91  | 26.65      | 17.74  | 46.00      | -28.26     | QP     |
| 5 | 675.21      | -3.82  | 25.86      | 22.04  | 46.00      | -23.96     | QP     |
| 6 | 857.40      | -1.67  | 25.42      | 23.75  | 46.00      | -22.25     | QP     |

## Vertical




Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2401V83797E-RF  
Test Mode : BT Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su

|   | Freq   | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|--------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz    | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 48.78  | -17.25 | 30.50         | 13.25  | 40.00         | -26.75        | QP     |
| 2 | 63.98  | -18.02 | 33.92         | 15.90  | 40.00         | -24.10        | QP     |
| 3 | 139.36 | -11.85 | 25.82         | 13.97  | 43.50         | -29.53        | QP     |
| 4 | 388.33 | -8.82  | 25.94         | 17.12  | 46.00         | -28.88        | QP     |
| 5 | 688.96 | -3.66  | 26.01         | 22.35  | 46.00         | -23.65        | QP     |
| 6 | 889.56 | -1.40  | 25.26         | 23.86  | 46.00         | -22.14        | QP     |

For Adapter 3


### Horizontal



Site : Chamber A  
 Condition : 3m Horizontal  
 Project Number : 2401V83797E-RF  
 Test Mode : BT Transmitting  
 Detector: Peak RBW/VBW: 100/300kHz  
 Tester : Anson Su

|   | Freq Factor |        | Read Level | Level  | Limit Line | Over Limit | Remark |
|---|-------------|--------|------------|--------|------------|------------|--------|
|   | MHz         | dB/m   | dBuV       | dBuV/m | dBuV/m     | dB         |        |
| 1 | 46.73       | -16.13 | 31.42      | 15.29  | 40.00      | -24.71     | QP     |
| 2 | 96.44       | -16.63 | 31.98      | 15.35  | 43.50      | -28.15     | QP     |
| 3 | 112.13      | -12.74 | 34.10      | 21.36  | 43.50      | -22.14     | QP     |
| 4 | 137.42      | -11.72 | 35.55      | 23.83  | 43.50      | -19.67     | QP     |
| 5 | 235.09      | -13.08 | 42.24      | 29.16  | 46.00      | -16.84     | QP     |
| 6 | 895.43      | -1.35  | 25.93      | 24.58  | 46.00      | -21.42     | QP     |

## Vertical



Site : Chamber A  
Condition : 3m Vertical  
Project Number : 2401V83797E-RF  
Test Mode : BT Transmitting  
Detector: Peak RBW/VBW: 100/300kHz  
Tester : Anson Su

|   | Freq   | Factor | Read<br>Level | Level  | Limit<br>Line | Over<br>Limit | Remark |
|---|--------|--------|---------------|--------|---------------|---------------|--------|
|   | MHz    | dB/m   | dBuV          | dBuV/m | dBuV/m        | dB            |        |
| 1 | 45.12  | -15.25 | 47.01         | 31.76  | 40.00         | -8.24         | QP     |
| 2 | 47.04  | -16.29 | 49.90         | 33.61  | 40.00         | -6.39         | QP     |
| 3 | 92.95  | -17.36 | 39.37         | 22.01  | 43.50         | -21.49        | QP     |
| 4 | 115.02 | -12.27 | 37.23         | 24.96  | 43.50         | -18.54        | QP     |
| 5 | 373.31 | -9.34  | 26.60         | 17.26  | 46.00         | -28.74        | QP     |
| 6 | 860.79 | -1.63  | 26.04         | 24.41  | 46.00         | -21.59        | QP     |

**Above 1GHz:**

| Frequency<br>(MHz)     | Receiver          |        | Polar<br>(H/V) | Factor<br>(dB/m) | Corrected<br>Amplitude<br>(dBμV/m) | Limit<br>(dBμV/m) | Margin<br>(dB) |
|------------------------|-------------------|--------|----------------|------------------|------------------------------------|-------------------|----------------|
|                        | Reading<br>(dBμV) | PK/Ave |                |                  |                                    |                   |                |
| π/4-DQPSK              |                   |        |                |                  |                                    |                   |                |
| Low Channel 2402MHz    |                   |        |                |                  |                                    |                   |                |
| 4804.00                | 55.90             | PK     | H              | -7.79            | 48.11                              | 74                | -25.89         |
| 4804.00                | 54.42             | PK     | V              | -7.79            | 46.63                              | 74                | -27.37         |
| Middle Channel 2441MHz |                   |        |                |                  |                                    |                   |                |
| 4882.00                | 54.78             | PK     | H              | -7.58            | 47.20                              | 74                | -26.80         |
| 4882.00                | 54.21             | PK     | V              | -7.58            | 46.63                              | 74                | -27.37         |
| High Channel 2480MHz   |                   |        |                |                  |                                    |                   |                |
| 4960.00                | 54.05             | PK     | H              | -7.56            | 46.49                              | 74                | -27.51         |
| 4960.00                | 53.53             | PK     | V              | -7.56            | 45.97                              | 74                | -28.03         |

**Note:**

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Factor + Reading


Margin = Corrected. Amplitude - Limit


The other spurious emission which is in the noise floor level was not recorded.


The test result of peak was less than the limit of average, so just peak values were recorded.

Test plots for Band Edge Measurements (Radiated):














Listed with the worst harmonic margin test plot:




















## **FCC §15.247(a) (1) & RSS-247 § 5.1 (b) - CHANNEL SEPARATION TEST**

### **Applicable Standard**

According to FCC §15.247(a) (1):

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater provided the systems operate with an output power no greater than 125 mW. The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.


According to RSS-247 § 5.1 (b):

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the -20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

### **Test Procedure**

Test Method: ANSI C63.10-2013 Clause 7.8.2

1. Set the EUT in transmitting mode, max hold the channel.
2. Set the adjacent channel of the EUT and max hold another trace.
3. Measure the channel separation.



**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 24.5 °C   |
| <b>Relative Humidity:</b> | 44 %      |
| <b>ATM Pressure:</b>      | 101.7 kPa |

*The testing was performed by Rainbow Zhu on 2025-01-17.*

*EUT operation mode: Transmitting*

***Test Result: Compliant. Please refer to the Appendix.***

## **FCC §15.247(a) (1) & RSS-247 § 5.1 (a), RSS-GEN § 6.7 - 20 dB EMISSION BANDWIDTH & 99% OCCUPIED BANDWIDTH**

### **Applicable Standard**

According to FCC §15.247(a) (1):

Alternatively, frequency hopping systems operating in the 2400–2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

According to RSS-247 § 5.1 (a), RSS-GEN § 6.7:

The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in-band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

The following conditions shall be observed for measuring the occupied bandwidth and x dB bandwidth:

- The transmitter shall be operated at its maximum carrier power measured under normal test conditions.
- The span of the spectrum analyzer shall be set large enough to capture all products of the modulation process, including the emission skirts, around the carrier frequency, but small enough to avoid having other emissions (e.g. on adjacent channels) within the span.
- The detector of the spectrum analyzer shall be set to “Sample”. However, a peak, or peak hold, may be used in place of the sampling detector since this usually produces a wider bandwidth than the actual bandwidth (worst-case measurement). Use of a peak hold (or “Max Hold”) may be necessary to determine the occupied / x dB bandwidth if the device is not transmitting continuously.
- The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth and the video bandwidth (VBW) shall not be smaller than three times the RBW value. Video averaging is not permitted.

Note: It may be necessary to repeat the measurement a few times until the RBW and VBW are in compliance with the above requirement.

For the 99% emission bandwidth, the trace data points are recovered and directly summed in linear power level terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached, and that frequency recorded. The process is repeated for the highest frequency data points (starting at the highest frequency, at the right side of the span, and going down in frequency). This frequency is then recorded. The difference between the two recorded frequencies is the occupied bandwidth (or the 99% emission bandwidth).

## Test Procedure


Test Method: ANSI C63.10-2013 Clause 7.8.7 & Clause 6.9.2 & RSS-Gen §6.7

The following conditions shall be observed for measuring the occupied bandwidth and 20 dB bandwidth:

- a. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
- b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
- c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (OBW/RBW)]$  below the reference level.
- d) Steps a) through c) might require iteration to adjust within the specified tolerances.
- e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target “-xx dB down” requirement; that is, if the requirement calls for measuring the -20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
- f) Set detection mode to peak and trace mode to max hold.
- g) Determine the reference value: Set the EUT to transmit an un-modulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
- h) Determine the “-xx dB down amplitude” using  $[(\text{reference value}) - xx]$ . Alternatively, this calculation may be made by using the marker-delta function of the instrument.
- i) If the reference value is determined by an un-modulated carrier, then turn the EUT modulation on, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
- j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “- xx” dB down amplitude determined in step h). If a marker is below this “-xx dB down amplitude” value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the “- xx dB down amplitude” determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
- k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

The occupied bandwidth is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers are each equal to 0.5% of the total mean power of the given emission. Procedure as below

- The instrument center frequency is set to the nominal EUT channel center frequency. The frequency span for the spectrum analyzer shall be between 1.5 times and 5.0 times the OBW.
- The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW, and VBW shall be approximately three times the RBW (for RSS rules, VBW shall not be smaller than three times the RBW, unless otherwise specified by the applicable requirement).
- Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than  $[10 \log (\text{OBW}/\text{RBW})]$  below the reference level.
- Step a) through step c) might require iteration to adjust within the specified range.
- Video averaging is not permitted. Where practical, a sample detection and single sweep mode shall be used. Otherwise, peak detection and max hold mode (until the trace stabilizes) shall be used.
- Use the 99% power bandwidth function of the instrument (if available) and report the measured bandwidth.
- If the instrument does not have a 99% power bandwidth function, then the trace data points are recovered and directly summed in linear power terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5% of the total is reached; that frequency is recorded as the lower frequency. The process is repeated until 99.5% of the total is reached; that frequency is recorded as the upper frequency. The 99% power bandwidth is the difference between these two frequencies.
- The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data maybe reported in addition to the plot(s).



## Test Data

### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 24.5 °C   |
| Relative Humidity: | 44 %      |
| ATM Pressure:      | 101.7 kPa |

*The testing was performed by Rainbow Zhu on 2025-01-17.*

*EUT operation mode: Transmitting*

***Test Result: Compliant. Please refer to the Appendix.***

## FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d) - QUANTITY OF HOPPING CHANNEL TEST

### Applicable Standard

According to FCC §15.247(a) (1) (iii):

Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.


According to RSS-247 § 5.1 (d):

Frequency hopping systems (FHSS) operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that at least 15 hopping channels are used.

### Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.3

1. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
2. Set the EUT in hopping mode from first channel to last.
3. By using the max-hold function record the quantity of the channel.



**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 24.5 °C   |
| <b>Relative Humidity:</b> | 44 %      |
| <b>ATM Pressure:</b>      | 101.7 kPa |

*The testing was performed by Rainbow Zhu on 2025-01-17.*

*EUT operation mode: Transmitting*

***Test Result: Compliant. Please refer to the Appendix.***

## FCC §15.247(a) (1) (iii) & RSS-247 § 5.1 (d) - TIME OF OCCUPANCY (DWELL TIME)

### Applicable Standard

According to FCC §15.247(a) (1) (iii):

Frequency hopping systems in the 2400-2483.5 MHz shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.


According to RSS-247 § 5.1 (d):

Frequency hopping systems (FHSs) operating in the band 2400-2483.5 MHz shall use at least 15 hopping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds, multiplied by the number of hopping channels employed. Transmissions on particular hopping frequencies may be avoided or suppressed provided that at least 15 hopping channels are used.

### Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.4

1. The EUT was worked in channel hopping.
2. Set the RBW to: 1MHz.
3. Set the VBW  $\geq 3 \times$  RBW.
4. Set the span to 0Hz.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Recorded the time of single pulses



Note 1: A period time=0.4\*79=31.6(S), Result=BurstWidth\*Totalhops

Note 2: Totalhops=Hopping Number in 3.16s\*10

Note 3: Hopping Number in 3.16s=Total of highest signals in 3.16s(Second high signals were other channel)

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 24.5 °C   |
| <b>Relative Humidity:</b> | 44 %      |
| <b>ATM Pressure:</b>      | 101.7 kPa |

*The testing was performed by Rainbow Zhu on 2025-01-17.*

*EUT operation mode: Transmitting*

***Test Result: Compliant. Please refer to the Appendix.***

## FCC §15.247(b) (1) & RSS-247§ 5.1(b) &§ 5.4(b) - PEAK OUTPUT POWER MEASUREMENT

### Applicable Standard

According to FCC §15.247(b) (1):

For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt. And for all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

According to RSS-247§ 5.1(b) &§ 5.4(b):


For frequency hopping systems (FHSs) operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1.0 W if the hopset uses 75 or more hopping channels; the maximum peak conducted output power shall not exceed 0.125 W if the hopset uses less than 75 hopping channels. The e.i.r.p. shall not exceed 4 W (see Section 5.4(e) for exceptions).

Frequency hopping systems (FHSs) shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the -20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, FHSs operating in the band 2400-2483.5 MHz may have hopping channel carrier frequencies that are separated by 25 kHz or two thirds of the -20 dB bandwidth of the hopping channel, whichever is greater, provided that the systems operate with an output power no greater than 0.125 W.

### Test Procedure

Test Method: ANSI C63.10-2013 Clause 7.8.5

1. Place the EUT on a bench and set in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Note: A short RF cable with low cable loss connected to the EUT antenna port, which was provided by client or lab, the cable loss was add with offset into test equipment, the total offset consists of attenuator and/or RF cable loss.

**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 24.5 °C   |
| <b>Relative Humidity:</b> | 44 %      |
| <b>ATM Pressure:</b>      | 101.7 kPa |

*The testing was performed by Rainbow Zhu on 2025-01-17.*

*EUT operation mode: Transmitting*

***Test Result: Compliant. Please refer to the Appendix.***

## **FCC §15.247(d) & RSS-247 § 5.5 - BAND EDGES TESTING**

### **Applicable Standard**

According to FCC §15.247(d).

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).


According to RSS-247 § 5.5.

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated device is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under Section 5.4(e), the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

### **Test Procedure**

Test Method: ANSI C63.10-2013 Clause 7.8.6 & Clause 6.10

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to a EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



**Test Data****Environmental Conditions**

|                           |           |
|---------------------------|-----------|
| <b>Temperature:</b>       | 24.5 °C   |
| <b>Relative Humidity:</b> | 44 %      |
| <b>ATM Pressure:</b>      | 101.7 kPa |

*The testing was performed by Rainbow Zhu on 2025-01-17.*

*EUT operation mode: Transmitting*

***Test Result: Compliant. Please refer to the Appendix.***

## **EUT PHOTOGRAPHS**

---

Please refer to the attachment 2401V83797E-RF-FP External photo and 2401V83797E-RF-FP Internal photo.

## **TEST SETUP PHOTOGRAPHS**

---

Please refer to the attachment 2401V83797E-RFA Test Setup photo.


## Appendix

### Appendix A: 20dB Emission Bandwidth

#### Test Result


| Mode | Channel        | Result (MHz) |
|------|----------------|--------------|
| DH1  | Low Channel    | 0.941        |
|      | Middle Channel | 0.941        |
|      | High Channel   | 0.893        |
| 2DH1 | Low Channel    | 1.253        |
|      | Middle Channel | <b>1.264</b> |
|      | High Channel   | <b>1.264</b> |
| 3DH1 | Low Channel    | 1.234        |
|      | Middle Channel | 1.234        |
|      | High Channel   | 1.230        |

DH1\_Low 0.941MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:09:58

DH1\_Middle 0.941MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:13:16

DH1\_High 0.893MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:16:20

2DH1\_Low 1.253MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:21:19

2DH1\_Middle 1.264MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:24:05

2DH1\_High 1.264MHz



ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:26:11




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:32:34

**Appendix B: Occupied Channel Bandwidth****Test Result**


| Mode | Channel        | 99% OBW (MHz) |
|------|----------------|---------------|
| DH1  | Low Channel    | 0.851         |
|      | Middle Channel | 0.859         |
|      | High Channel   | 0.851         |
| 2DH1 | Low Channel    | 1.178         |
|      | Middle Channel | <b>1.181</b>  |
|      | High Channel   | 1.174         |
| 3DH1 | Low Channel    | 1.170         |
|      | Middle Channel | 1.174         |
|      | High Channel   | 1.163         |

DH1\_Low 0.851MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:11:30

DH1\_Middle 0.859MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:13:51

DH1\_High 0.851MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:18:43

2DH1\_Low 1.178MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:22:48

2DH1\_Middle 1.181MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:24:39

2DH1\_High 1.174MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:28:19

3DH1\_Low 1.170MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:31:13

3DH1\_Middle 1.174MHz



ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:33:08


3DH1\_High 1.163MHz




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:36:37

**Appendix C: Maximum conducted Peak output power****Test Result**


| Mode | Channel        | Result (dBm) | Limit (dBm) | EIRP (dBm)  | EIRP Limit (dBm) | Verdict |
|------|----------------|--------------|-------------|-------------|------------------|---------|
| DH1  | Low Channel    | 1.12         | 21.00       | 1.12        | 36.00            | Pass    |
|      | Middle Channel | 1.19         | 21.00       | 1.19        | 36.00            | Pass    |
|      | High Channel   | 1.49         | 21.00       | 1.49        | 36.00            | Pass    |
| 2DH1 | Low Channel    | 2.61         | 21.00       | 2.61        | 36.00            | Pass    |
|      | Middle Channel | 2.88         | 21.00       | 2.88        | 36.00            | Pass    |
|      | High Channel   | <b>3.42</b>  | 21.00       | <b>3.42</b> | 36.00            | Pass    |
| 3DH1 | Low Channel    | 1.09         | 21.00       | 1.09        | 36.00            | Pass    |
|      | Middle Channel | 1.27         | 21.00       | 1.27        | 36.00            | Pass    |
|      | High Channel   | 1.47         | 21.00       | 1.47        | 36.00            | Pass    |




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:11:51




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:14:12




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:19:06




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:23:09




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:25:06




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:28:39



ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:31:34



ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:33:28




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:36:57

Appendix D: Carrier frequency separation

Test Result

| Mode | Channel        | Result (MHz) | Limit (MHz) | Verdict |
|------|----------------|--------------|-------------|---------|
| DH1  | Middle Channel | 1.003        | 0.843       | Pass    |

Note: Only the BDR (GFSK) mode result is reported since EDR ( $\pi/4$ -DQPSK) and EDR (8DPSK) modes have the exact same channel plan, and the limit is the maximum 20dB bandwidth \*2/3



ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:41:39

**Appendix E: Time of occupancy****Test Result**

| Mode | Channel         | Pulse width (ms) | Dwell time (s) | Limit (s) | Verdict |
|------|-----------------|------------------|----------------|-----------|---------|
| DH1  | Hopping Channel | 0.403            | 0.129          | 0.400     | Pass    |
| DH3  | Hopping Channel | 1.665            | 0.266          | 0.400     | Pass    |
| DH5  | Hopping Channel | <b>2.931</b>     | 0.313          | 0.400     | Pass    |
| 2DH1 | Hopping Channel | 0.400            | 0.128          | 0.400     | Pass    |
| 2DH3 | Hopping Channel | 1.661            | 0.266          | 0.400     | Pass    |
| 2DH5 | Hopping Channel | 2.925            | 0.312          | 0.400     | Pass    |
| 3DH1 | Hopping Channel | 0.400            | 0.128          | 0.400     | Pass    |
| 3DH3 | Hopping Channel | 1.661            | 0.266          | 0.400     | Pass    |
| 3DH5 | Hopping Channel | <b>2.931</b>     | 0.313          | 0.400     | Pass    |

**Note:**

**DH1:Dwell time=Pulse width (ms) × (1600/2/79) ×31.6 s**

**DH3:Dwell time=Pulse width (ms) × (1600/4/79) ×31.6 s**

**DH5:Dwell time=Pulse width (ms) × (1600/6/79) ×31.6 s**

**2DH1: Dwell time=Pulse width (ms) × (1600/2/79) ×31.6 s**

**2DH3: Dwell time=Pulse width (ms) × (1600/4/79) ×31.6 s**


**2DH5: Dwell time=Pulse width (ms) × (1600/6/79) ×31.6 s**

**3DH1: Dwell time=Pulse width (ms) × (1600/2/79) ×31.6 s**

**3DH3: Dwell time=Pulse width (ms) × (1600/4/79) ×31.6 s**


**3DH5: Dwell time=Pulse width (ms) × (1600/6/79) ×31.6 s**

DH1\_Hopping 0.403ms




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:10:30

DH3\_Hopping 1.665ms




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:12:09

DH5\_Hopping 2.931ms




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:13:43

2DH1\_Hopping 0.400ms




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:15:37

2DH3\_Hopping 1.661ms




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:17:11

2DH5\_Hopping 2.925ms




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:18:53



**Appendix F: Number of hopping channels****Test Result**


| Mode | Channel         | Result | Limit | Verdict |
|------|-----------------|--------|-------|---------|
| DH1  | Hopping Channel | 79     | 15    | Pass    |
| 2DH1 | Hopping Channel | 79     | 15    | Pass    |
| 3DH1 | Hopping Channel | 79     | 15    | Pass    |

DH1\_Hopping 79




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:50:36

2DH1\_Hopping 79



ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:56:11


3DH1\_Hopping 79




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:54:02

Appendix G: Band edge measurements


Test Graphs




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:10:53




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:18:08




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:00:29



ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:02:12




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:22:13




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:27:44

### 2DH1\_Hopping\_Lower




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:03:12

### 2DH1\_Hopping\_Upper




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:04:50

### 3DH1\_Low




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:30:38

### 3DH1\_High




ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 01:36:02

### 3DH1\_Hopping\_Lower



ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:06:01

### 3DH1\_Hopping\_Upper



ProjectNo.:2401V83797E-RF Tester:Rainbow Zhu  
Date: 17.JAN.2025 02:07:37

\*\*\*\*\* END OF REPORT \*\*\*\*\*