



VTech Engineering Canada Ltd.

200 - 7671 Alderbridge Way, Richmond, B.C.
Canada V6X 1Z9

Tel: (604) 273-5131 Fax: (604) 276-9137

**Radio Frequency Exposure Information
For VTech 2625
2.4GHz Cordless Telephones**

Handset (Tx / Rx: 2.4GHz)

Readings from test report :

- (1) Page 34 -- Max. Output Power = 103 mW (20.1 dBm)
- (2) Page 43 -- Duty cycle = $10 \times 850\text{us} / 100\text{ms} = 8.5\%$ (measured in single slot transmission)

Under the worst environment with interference, dual slot diversity gives the max. duty cycle on the handset Tx (ie. $8.5\% \times 2$ or 17%)

Hence, taking the max. power output & max. duty cycle, the average effective output power is :
 $103 \text{ mW} \times 17\% = 17.51 \text{ mW}$

Conclusion : The average effective output power is lower than the 25mW (ie.60/freq.) threshold which starts to require SAR testing. Hence, there is no RF exposure concerns on handset.

Base (Tx / Rx: 2.4GHz)

Readings from test report :

- (1) Page 34 -- Max. Output Power = 115 mW (20.6 dBm)
- (2) Page 42 -- Duty Cycle = $40 \times 800\text{us} / 100\text{ms} = 32\%$

The phone is a TDD, FHSS. The testing was done at the worst case with 4 Tx carrier, equivalent to operating with 2 handsets in dual-slot diversity.

Hence, taking the worst case, the average effective output power is :
 $115 \text{ mW} \times 32\% = 37 \text{ mW}$

Conclusion : The average effective output power is lower than the 50mW (ie.120/freq.) threshold which starts to require RF safety evaluation. Hence, there is no RF exposure concerns on base.

Provided by :

Joseph Poon
Regulatory Compliance Manager
VTech Engineering Canada Ltd.