



VTech Telecommunications Ltd.

Application
For
Permissive Change Class II

Unlicensed Personal Communication Service Devices

FCC ID: EW780-6270-00

Test Report Number: HK08060910-1

Issue Date: July 18, 2008

TL/ ac

- The test report only allows to be revised within three years from its original issued date unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Intertek Testing Services Hong Kong Ltd.

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.
Tel: (852) 2173 8888 Fax: (852) 2785 5487 Website: www.hk.intertek-etlsemko.com

LIST OF EXHIBITS

INTRODUCTION

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Technical Specifications
<i>EXHIBIT 7:</i>	Letter of Agency
<i>EXHIBIT 8:</i>	Confidentiality Request

INTERTEK TESTING SERVICES

MEASUREMENT/TECHNICAL REPORT

**VTech Telecommunications Ltd. - Model: LS6115, LS6115-x, LS6125,
LS6125-x, LS6126, LS6126-x**

FCC ID: EW780-6270-00

This report concerns (check one:) Original Grant ☐ Class II Change ☒

Equipment Type : PUB - Part 15 Unlicensed PCS Base Station
PUE - Part 15 Unlicensed PCS portable Tx held to ear

Deferred grant requested per 47 CFR 0.457(d)(1)(ii)? Yes ☐ No ☒

If yes, defer until :

Date

Company Name agrees to notify the Commission by: _____
Date

of the intended date of announcement of the product so that the grant can be issued on that date.

Transition Rules Request per 15.37? Yes ☐ No ☒

If no, assumed Part 15, Subpart D for Unlicensed Personal Communication Service Device - the new 47 CFR [05-04-07 Edition] Provision.

Report prepared by:

Leung Wai Leung, Tommy

Intertek Testing Services Hong Kong Ltd.
2/F., Garment Centre,
576 Castle Peak Road,
Kowloon, Hong Kong.
Phone : 852-2173-8538
Fax: 852-2741-1693

INTERTEK TESTING SERVICES

Table of Contents

1.0 Summary of Test Results	6
2.0 General Description	8
2.1 Product Description	8
2.2 Purpose of Application.....	9
2.3 Test Methodology.....	9
2.4 Test Facility.....	9
3.0 System Test Configuration.....	11
3.1 Justification	11
3.2 Conducted Emission Test Configuration	12
3.3 Conducted Monitoring and Operational Test Configuration	12
3.4 EUT Exercising Software.....	12
3.5 Details of EUT and Description of Peripherals	13
3.6 Measurement Uncertainty	14
3.7 Equipment Modification	14
4.0 Measurement Results	16
4.1 Antenna Requirement	16
4.2 Emission Bandwidth	17
4.3 Directional Gain of the Antenna	19
4.4 Peak Transmit Power	20
4.5 Power Spectral Density	22
4.6 Unwanted Emission Inside the Sub-Band	24
4.7 Emissions Outside the Sub-Band	26
4.7.1 Radiated Emissions Configuration Photographs	27
4.7.2 Radiated Emissions Data	28
4.7.3 Field Strength Calculation.....	44
4.8 Average Factor Calculation and Transmitter ON Time Measurements	45
4.9 AC Power Lines Conducted Emissions from Transmitter portion of EUT	46
4.9.1 AC Power Lines Conducted Emissions Configuration Photographs.....	47
4.7.2 AC Power Line Conducted Emissions Data	48
4.9 Radio Frequency Radiation Exposure	49
4.10 Frame Jitter	50
4.11 Monitoring Threshold.....	51
4.11.1 Upper Monitoring Threshold	52
4.12 Monitoring Antenna	53
5.0 Equipment Photographs.....	55
6.0 Technical Specifications.....	57
7.0 Letter of Agency	59
8.0 Confidentiality Request	61

INTERTEK TESTING SERVICES

List of Attached Files

Exhibit Type	File Description	Filename
Test Report	Test Report	report.pdf
Operational Description	Technical Description	descri.pdf
Cover Letters	Purpose of Change	product change.pdf
Test Report	Emission Bandwidth and Test Frequency Plots	26bw.pdf
Test Report	Peak Transmit Power Plots	peaktp.pdf
Test Report	Power Spectral Density Plots	psd.pdf
Test Report	Unwanted Emission Inside Sub-Band Plots	inband.pdf
Test Setup Photo	Radiated Emission Test Configuration	config photos. pdf
Test Setup Photo	AC Lines Conducted Emission Test Configuration	
Test Report	AC Lines Conducted Emission Data	conduct.pdf
Test Report	Average Factor Calculation Measurement	dcc.pdf
RF Exposure Info	RF Safety	RF exposure info.pdf
	SAR Report	SAR Report 1 of 2.pdf SAR Report 2 of 2.pdf
External Photos	External Photo	external photos.pdf
Internal Photos	Internal Photo	internal photos.pdf
Block Diagrams	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
Cover Letters	Letter of Agency	letter of agency.pdf
Cover Letters	Confidentiality Request	request.pdf

**EXHIBIT 1
SUMMARY OF TEST RESULTS**

INTERTEK TESTING SERVICES

1.0 Summary of Test Results

**VTech Telecommunications Ltd. - Model: LS6115, LS6115-x, LS6125,
LS6125-x, LS6126, LS6126-x**

FCC ID: EW780-6270-00

Technical Requirements				
Test Items	FCC Part 15 Section	Test Procedure ANSI C63.17 / ANSI C63.4 *	Results	Details see section
Antenna Requirement	15.317	---	Pass	4.1
Emission Bandwidth	15.323(a)	6.1.3	Pass	4.2
Direction Gain of the Antenna	15.319(e)	4.3.1	Pass	4.3
Peak Transmit Power	15.319(c)	6.1.2	Pass	4.4
Power Spectral Density	15.319(d)	6.1.5	Pass	4.5
Unwanted Emission Inside the Sub-Band	15.323(d)	6.1.6.1	Pass	4.6
Emissions Outside the Sub-Band	15.323(d)	6.1.6.2	Pass	4.7
AC Power Lines Conducted Emissions from Transmitter Portion of EUT	15.315	7 *	Pass	4.8
Radio Frequency Radiation Exposure	15.319(i)	---	Pass	4.9
Frame Jitter	15.323(e)	6.2.3	Pass	4.10
Upper Monitoring Threshold	15.323(c)(5)	7.3.2	Pass	4.11.1
Monitoring Antenna	15.323(c)(8)	4	Pass	4.12

Test Engineer:

Approved By:



Ken Sit
Supervisor

Date: July 18, 2008



Leung Wai Leung, Tommy
Senior Manager

Date: July 18, 2008

**EXHIBIT 2
GENERAL DESCRIPTION**

INTERTEK TESTING SERVICES

2.0 General Description

2.1 Product Description

Model LS6115-2 is 1.9GHz Digital Modulation Cordless Phone with Caller ID and Speakerphone, while model LS6125-2 is 1.9GHz Digital Modulation Cordless Phone with Caller ID, Speakerphone and Digital Answering Machine. They operate at frequency range of 1921.536MHz to 1928.448MHz with 5 channels (1921.536MHz, 1923.264MHz, 1924.992MHz, 1926.720MHz and 1928.448MHz). The model LS6115-2, Base Unit is powered by an AC adaptor 117VAC to 6VDC 300mA, while model LS6125-2 is powered by an AC adaptor 117VAC to 6VDC 400mA. The Handset of both models is powered by a "Ni-MH" type rechargeable battery pack (2.4V 500mAh, 550mAh, 600mAh).

The antennas used in base unit and handset are integral, and the test sample is a prototype.

Model LS6115-2 is the one of the model LS6115-x, and the model LS6115 is the same as the model LS6115-2 in hardware aspect. Suffix "x" at the end of the model numbers represents different number of handset in the packing. The difference model number serves as the marketing strategy.

Model LS6125-2 is the one of the model LS6125-x, and the models LS6125, LS6126 and LS6126-x are the same as the model LS6125-2 in hardware aspect. Suffix "x" at the end of the model numbers represents different number of handset in the packing. The difference model number serves as the marketing strategy.

The Handsets are identical among models as follows: electrical designs, including software and firmware, PCB layout and construction design/ physical design/ enclosure.

Connection between the base unit and the telephone network is accomplished through the use of USOC RJ11C in the 2-wire loop calling central office line.

The technical description is saved as filename: descri.pdf

INTERTEK TESTING SERVICES

2.2 Purpose of Application

The purpose of change is saved as filename: product change.pdf

For the Model: LS6115-2 and LS6125-2, the RF circuit and algorithm are the same as the original granted Model: DS6121. The baseband, enclosure and RF layout for Base Unit and Handset are changed.

This is an application for Certification of a PUB - Part 15 Unlicensed PCS Base Station, PUE - Part 15 Unlicensed PCS portable Tx held to ear. The device is also subject to Part 68 Registration. A Verification report has been prepared for the digital device portion.

2.3 Test Methodology

The radiated emission measurements for unintentional radiator (if any) and AC power line-conducted emission measurements were performed according to the test procedures specified in ANSI C63.4 (2003). The radiated emission measurements for intentional radiator contained in UPCS device, conducted emission measurements, Listen Before Transmit (LBT) Test and Time Frame Test were performed according to the test procedures specified in ANSI C63.17 (2006). All radiated measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "Justification Section" of this Application. All other measurements were made in accordance with the procedures in 47 CFR Part 2.

2.4 Test Facility

The open area test site and conducted measurement facility used to collect the emission data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

**EXHIBIT 3
SYSTEM TEST CONFIGURATION**

INTERTEK TESTING SERVICES

3.0 System Test Configuration

3.1 Justification

For emissions testing, the equipment under test (EUT) was setup to transmit continuously in burst mode with pseudo-random data to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables (if any) were manipulated to produce worst-case emissions. The handset (if any) was powered by a fully charged battery.

For the measurements, the EUT was attached to a plastic stand if necessary and placed on the wooden turntable. If the base unit attached to peripherals, they were connected and operational (as typical as possible).

The signal was maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization were varied during the search for maximum signal level. The antenna height was varied from 1 to 4 meters. Detector function was in peak mode. Radiated emissions were taken at three meters unless the signal level was too low for measurement at that distance. If necessary, a pre-amplifier was used and/or the test was conducted at a closer distance.

The spectrum analyzer resolution bandwidth was approximately 1% of the EUT emission bandwidth, unless otherwise specified.

Radiated emission measurements were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

As the base unit has 2 antennas, both have been checked. While conducting the test on one of antennas, another one was being disable its transmission. The data in this report represented the worst-case.

3.2 Conducted Emission Test Configuration

The setup and equipment setting were made in accordance with ANSI C63.17. The antenna of EUT transmitter was replaced by a coaxial cable. The impedance matching of connection, cable loss and external RF attenuator were taken into account. The EUT was arranged to communicate via a fixed carrier frequency between its transmitter and a companion device. The transmission was configured in burst mode with pseudo-random data as typical as normal operation.




Figure 3.2.1

3.3 Conducted Monitoring and Operational Test Configuration




Figure 3.3.1

3.4 EUT Exercising Software

The EUT exercise program (if any) used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

INTERTEK TESTING SERVICES

3.5 Details of EUT and Description of Peripherals

Details of EUT:

An AC adaptor and/or a battery (provided with the unit) were used to power the device. Their description are listed below.

- (1) Base Unit for LS6115-2: An AC adaptor (117VAC to 6VDC 300mA, Model: UD-0603) (Supplied by Client)
- (2) Base Unit for LS6125-2: An AC adaptor (117VAC to 6VDC 400mA, Model: U060040D) (Supplied by Client)
- (2) Handset: A "Ni-MH" Type Rechargeable Battery Pack (2.4V 500mAh, 550mAh, 600mAh) (Supplied by Client)

Description of Peripherals:

- (1) Telecommunication cable with RJ11C connectors (1m, unshielded), terminated (Supplied by Intertek)

INTERTEK TESTING SERVICES

3.6 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty test has been considered.

Uncertainty and Compliance - Unless the standard specifically states that measured values are to be extended by the measurement uncertainty in determining compliance, all compliance determinations are based on the actual measured value.

3.7 Equipment Modification

Any modifications installed previous to testing by VTech Telecommunications Ltd. will be incorporated in each production model sold/leased in the United States.

No modifications were installed by Commercial and Electrical Division, Intertek Testing Services Hong Kong Ltd.

All the items listed under section 3.0 of this report are confirmed by:

Confirmed by:

*Leung Wai Leung, Tommy
Senior Manager
Intertek Testing Services Hong Kong Ltd.
Agent for VTech Telecommunications Ltd.*



Signature

July 18, 2008 Date

**EXHIBIT 4
MEASUREMENT RESULTS**

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.0 **Measurement Results**

4.1 Antenna Requirement, FCC Rule 15.317:

EUT must meet the antenna requirement of FCC Rule 15.203.

- [×] EUT uses a permanently attached antenna which is considered sufficient to comply with the provisions of this rule. Please refer to Exhibit 5: Internal Photos for more details.
- [] EUT uses a unique antenna jack or electrical connector which is considered sufficient to comply with the provisions of this rule. Please refer to Exhibit 5: Internal Photos for more details.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.2 Emission Bandwidth, FCC Rule 15.323(a):

Operation shall be contained within the 1920 – 1930 MHz band. The emission bandwidth (*B*) shall be less than 2.5 MHz and greater than 50 kHz.

Measurements are made in accordance with ANSI C63.17 sub-clause 6.1.3. Test setup is shown in section 3.2 Figure 3.2.1.

Test Results:

I. Traffic Carrier - Base Unit - Model: LS6115-2

Channel	Channel Frequency (MHz)	Measuring Signal Level	Measured Emission Bandwidth (MHz)	Results
Lowest	1921.536	26 dB down	1.52	Pass
Highest	1928.448	26 dB down	1.50	Pass

II. Dummy Carrier - Base Unit - Model: LS6115-2

Channel	Channel Frequency (MHz)	Measuring Signal Level	Measured Emission Bandwidth (MHz)	Results
Lowest	1921.536	26 dB down	1.49	Pass
Highest	1928.448	26 dB down	1.43	Pass

III. Traffic Carrier - Base Unit - Model: LS6125-2

Channel	Channel Frequency (MHz)	Measuring Signal Level	Measured Emission Bandwidth (MHz)	Results
Lowest	1921.536	26 dB down	1.52	Pass
Highest	1928.448	26 dB down	1.50	Pass

IV. Dummy Carrier - Base Unit - Model: LS6125-2

Channel	Channel Frequency (MHz)	Measuring Signal Level	Measured Emission Bandwidth (MHz)	Results
Lowest	1921.536	26 dB down	1.44	Pass
Highest	1928.448	26 dB down	1.42	Pass

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.2 Emission Bandwidth, FCC Rule 15.323(a): - Continued

V. Traffic Carrier - Handset

Channel	Channel Frequency (MHz)	Measuring Signal Level	Measured Emission Bandwidth (MHz)	Results
Lowest	1921.536	26 dB down	1.49	Pass
Highest	1928.448	26 dB down	1.51	Pass

Please refer to the attached plots for more details:

Base Unit - Model: LS6115-2

Plot B1A1: Lowest Channel 26dB Emission Bandwidth (Traffic Carrier)

Plot B1D1: Highest Channel 26dB Emission Bandwidth (Traffic Carrier)

Plot B1G1: Lowest Channel 26dB Emission Bandwidth (Dummy Carrier)

Plot B1J1: Highest Channel 26dB Emission Bandwidth (Dummy Carrier)

Base Unit - Model: LS6125-2

Plot B1A2: Lowest Channel 26dB Emission Bandwidth (Traffic Carrier)

Plot B1D2: Highest Channel 26dB Emission Bandwidth (Traffic Carrier)

Plot B1G2: Lowest Channel 26dB Emission Bandwidth (Dummy Carrier)

Plot B1J2: Highest Channel 26dB Emission Bandwidth (Dummy Carrier)

Handset

Plot H1A: Lowest Channel 26dB Emission Bandwidth (Traffic Carrier)

Plot H1D: Highest Channel 26dB Emission Bandwidth (Traffic Carrier)

The plots of emission bandwidth and test frequency are saved as filename: 26bw.pdf

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: CS6119, CS6129

Date of Test: June 14-18, 2008

4.3 Directional Gain of the Antenna, FCC Rule FCC 15.319(e):

The peak transmit power shall be reduced by the amount in dB that the maximum directional gain of the antenna exceeds 3 dBi.

The requirements are made in accordance with ANSI C63.17 sub-clause 4.3.1.

- ☒ Manufacturer declares that the directional gain of the antenna is less than or equal to 3dBi. No peak transmit power reduction is required.
- ☐ Manufacturer declares that the directional gain of the antenna is greater than 3dBi. The peak transmit power shall be reduced by _____ dB.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.4 Peak Transmit Power, FCC Rule 15.319(c):

The peak transmit power (P_{EUT}) shall not exceed $100\mu W$ multiplied by the square root of the emission bandwidth (B) in Hz or $5 \log_{10} B - 10$ dBm. The peak transmit power shall be reduced by the amount in dB that the maximum directional gain of the antenna exceeds 3 dBi.

Measurements are made in accordance with ANSI C63.17 sub-clause 6.1.2. Test setup is shown in section 3.2 Figure 3.2.1. The cable loss and/or external attenuation are included in OFFSET function of spectrum analyzer.

Calculation of Peak Transmit Power Limit (P_{max}):

$$\begin{aligned} [\times] \quad P_{max} &= 5 \log_{10} B - 10 \text{ dBm} && \text{when } G_A \leq 3 \text{ dBi} \\ [] \quad P_{max} &= 5 \log_{10} B - 10 \text{ dBm} - (G_A - 3 \text{ dBi}) && \text{when } G_A > 3 \text{ dBi} \end{aligned}$$

Where G_A = EUT Antenna Gain: 0 dBi for Base Unit for LS6115-2
0 dBi for Base Unit for LS6125-2
0 dBi for Handset

Test Results:

I. Traffic Carrier - Base Unit - Model: LS6115-2

Channel	Channel Frequency (MHz)	Measured Peak Transmit Power (dBm)	Limit (dBm)	Results
Lowest	1921.536	20.20	20.91	Pass
Highest	1928.448	20.17	20.88	Pass

II. Dummy Carrier - Base Unit - Model: LS6115-2

Channel	Channel Frequency (MHz)	Measured Peak Transmit Power (dBm)	Limit (dBm)	Results
Lowest	1921.536	20.17	20.87	Pass
Highest	1928.448	20.23	20.78	Pass

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.4 Peak Transmit Power, FCC Rule 15.319(c): - Continued

III. Traffic Carrier - Base Unit - Model: LS6125-2

Channel	Channel Frequency (MHz)	Measured Peak Transmit Power (dBm)	Limit (dBm)	Results
Lowest	1921.536	19.87	20.91	Pass
Highest	1928.448	19.87	20.88	Pass

IV. Dummy Carrier - Base Unit - Model: LS6125-2

Channel	Channel Frequency (MHz)	Measured Peak Transmit Power (dBm)	Limit (dBm)	Results
Lowest	1921.536	19.87	20.79	Pass
Highest	1928.448	19.87	20.76	Pass

V. Traffic Carrier - Handset

Channel	Channel Frequency (MHz)	Measured Peak Transmit Power (dBm)	Limit (dBm)	Results
Lowest	1921.536	20.54	20.87	Pass
Highest	1928.448	20.42	20.89	Pass

Please refer to the attached plots for more details:

Base Unit - Model: LS6115-2

Plot B2A1: Lowest Channel Peak Transmit Power (Traffic Carrier)

Plot B2B1: Highest Channel Peak Transmit Power (Traffic Carrier)

Plot B2C1: Lowest Channel Peak Transmit Power (Dummy Carrier)

Plot B2D1: Highest Channel Peak Transmit Power (Dummy Carrier)

Base Unit - Model: LS6125-2

Plot B2A2: Lowest Channel Peak Transmit Power (Traffic Carrier)

Plot B2B2: Highest Channel Peak Transmit Power (Traffic Carrier)

Plot B2C2: Lowest Channel Peak Transmit Power (Dummy Carrier)

Plot B2D2: Highest Channel Peak Transmit Power (Dummy Carrier)

Handset

Plot H2A: Lowest Channel Peak Transmit Power (Traffic Carrier)

Plot H2B: Highest Channel Peak Transmit Power (Traffic Carrier)

The plots of peak transmit power are saved as filename: peaktp.pdf

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.5 Power Spectral Density, FCC Rule 15.319(d):

Power spectral density shall not exceed 3 mW (4.8dBm) in any 3 kHz bandwidth as measured with a spectrum analyzer having a resolution bandwidth of 3 kHz.

Measurements are made in accordance with ANSI C63.17 sub-clause 6.1.5. Test setup is shown in section 3.2 Figure 3.2.1.

Test Results:

I. Traffic Carrier - Base Unit - Model: LS6115-2

Channel	Channel Frequency (MHz)	Measured Power Spectral Density (dBm/3kHz)	Limit (dBm/3 kHz)	Results
Lowest	1921.536	-5.9	4.8	Pass
Highest	1928.448	-9.4	4.8	Pass

II. Dummy Carrier - Base Unit - Model: LS6115-2

Channel	Channel Frequency (MHz)	Measured Power Spectral Density (dBm/3kHz)	Limit (dBm/3 kHz)	Results
Lowest	1921.536	-6.3	4.8	Pass
Highest	1928.448	-20.3	4.8	Pass

III. Traffic Carrier - Base Unit - Model: LS6125-2

Channel	Channel Frequency (MHz)	Measured Power Spectral Density (dBm/3kHz)	Limit (dBm/3 kHz)	Results
Lowest	1921.536	-9.0	4.8	Pass
Highest	1928.448	-9.5	4.8	Pass

IV. Dummy Carrier - Base Unit - Model: LS6125-2

Channel	Channel Frequency (MHz)	Measured Power Spectral Density (dBm/3kHz)	Limit (dBm/3 kHz)	Results
Lowest	1921.536	-20.2	4.8	Pass
Highest	1928.448	-12.9	4.8	Pass

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.5 Power Spectral Density, FCC Rule 15.319(d): - Continued

V. Traffic Carrier - Handset

Channel	Channel Frequency (MHz)	Measured Power Spectral Density (dBm/3kHz)	Limit (dBm/3 kHz)	Results
Lowest	1921.536	-5.0	4.8	Pass
Highest	1928.448	-5.2	4.8	Pass

Please refer to the attached plots for more details:

Base Unit - Model: LS6115-2

Plot B3A1: Lowest Channel Power Spectral Density (Traffic Carrier)

Plot B3B1: Highest Channel Power Spectral Density (Traffic Carrier)

Plot B3C1: Lowest Channel Power Spectral Density (Dummy Carrier)

Plot B3D1: Highest Channel Power Spectral Density (Dummy Carrier)

Base Unit - Model: LS6125-2

Plot B3A2: Lowest Channel Power Spectral Density (Traffic Carrier)

Plot B3B2: Highest Channel Power Spectral Density (Traffic Carrier)

Plot B3C2: Lowest Channel Power Spectral Density (Dummy Carrier)

Plot B3D2: Highest Channel Power Spectral Density (Dummy Carrier)

Handset

Plot H3A: Lowest Channel Power Spectral Density (Traffic Carrier)

Plot H3B: Highest Channel Power Spectral Density (Traffic Carrier)

The plots of the power spectral density are saved as filename: psd.pdf

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.6 Unwanted Emission Inside the Sub-Band, FCC Rule 15.323(d):

Emissions inside the sub-band must comply with the following emission mask:

1. In the bands between $1B$ and $2B$ measured from the center of the emission bandwidth, emission shall be at least 30 dB below the permitted peak transmit power; i.e. -9.5 dBm
2. In the bands between $2B$ and $3B$ measured from the center of the emission bandwidth, emission shall be at least 50 dB below the permitted peak transmit power; i.e. -29.5 dBm
3. In the bands between $3B$ and the band edge, emission shall be at least 60 dB below the permitted peak transmit power. i.e. -39.5 dBm

Where B = emission bandwidth in Hz

Measurements are made in accordance with ANSI C63.17 sub-clause 6.1.6.1. Test setup is shown in section 3.2 Figure 3.2.1.

Test Results:

I. Traffic Carrier - Base Unit

Channel	Channel Frequency (MHz)	Results
Lowest	1921.536	Pass
Highest	1928.448	Pass

II. Dummy Carrier - Base Unit

Channel	Channel Frequency (MHz)	Results
Lowest	1921.536	Pass
Highest	1928.448	Pass

III. Traffic Carrier - Handset

Channel	Channel Frequency (MHz)	Results
Lowest	1921.536	Pass
Highest	1928.448	Pass

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.6 Unwanted Emission Inside the Sub-Band, FCC Rule 15.323(d): - Continued

Please refer to the attached plots for more details:

Base Unit - Model: LS6115-2

Plot B4A1: Lowest Channel Unwanted Emission Inside the Sub-Band (Traffic Carrier)

Plot B4B1: Highest Channel Unwanted Emission Inside the Sub-Band (Traffic Carrier)

Plot B4C1: Lowest Channel Unwanted Emission Inside the Sub-Band (Dummy Carrier)

Plot B4D1: Highest Channel Unwanted Emission Inside the Sub-Band (Dummy Carrier)

Base Unit - Model: LS6125-2

Plot B4A2: Lowest Channel Unwanted Emission Inside the Sub-Band (Traffic Carrier)

Plot B4B2: Highest Channel Unwanted Emission Inside the Sub-Band (Traffic Carrier)

Plot B4C2: Lowest Channel Unwanted Emission Inside the Sub-Band (Dummy Carrier)

Plot B4D2: Highest Channel Unwanted Emission Inside the Sub-Band (Dummy Carrier)

Handset

Plot H4A: Lowest Channel Unwanted Emission Inside the Sub-Band (Traffic Carrier)

Plot H4B: Highest Channel Unwanted Emission Inside the Sub-Band (Traffic Carrier)

The plots of the unwanted emission inside the sub-band are saved as filename:
inband.pdf

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.7 Emissions Outside the Sub-Band, FCC Rule 15.323(d):

Emissions outside the sub-band shall be attenuated below a reference power of 112 mW (20.5 dBm) as follows:

1. 30 dB between the band edge and 1.25 MHz above or below the band;
2. 50 dB between 1.25 and 2.5 MHz above or below the band; and
3. 60 dB at 2.5 MHz or greater above or below the band, or shall not exceed the limits of FCC Rule 15.209.

Example: Calculation of Limit for emissions between the band edge and 1.25 MHz (1920.000 – 1918.750 MHz)

The emissions shall not exceed the Limit: 20.5 dBm – 30 dB = -9.5 dBm

Measurements are made in accordance with ANSI C63.17 sub-clause 6.1.6.2. As EUT has non-detachable antenna(s), radiated emissions test method is used for out-of-band emissions tests. Emissions that are directly caused by digital circuits in the transmit path and transmitter portion are measured. Test setup and procedures are described in section 3.2 Figure 3.2.1.

Test Results:

Base Unit & Handset:

Channel	Carrier Frequency (MHz)	Measured Band (MHz)	Limit (dBm)	Results
Lowest	1921.536	1920.000 - 1918.750	-9.5	Pass
		1918.750 - 1917.500	-29.5	Pass
		0.009 - 1917.500 & 1932.500 - 19300.000	-39.5 / FCC Rule 15.209	Pass
Highest	1928.448	1930.000 - 1931.250	-9.5	Pass
		1931.250 - 1932.500	-29.5	Pass
		0.009 - 1917.500 & 1932.500 - 19300.000	-39.5 / FCC Rule 15.209	Pass

Please refer to the section 4.5.1 to 4.5.4 for more details.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2
Mode: Transmission

Date of Test: June 20-25, 2008

4.7.1 Radiated Emissions Configuration Photographs:

Worst Case Radiated Emission
at

Base Unit - Model: LS6115-2 - 3856.896 MHz

Base Unit - Model: LS6125-2 - 3843.072 MHz

Handset - 5785.344 MHz

The worst case radiated emission configuration photographs are saved as filename:
config photos.pdf

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2
Mode: Transmission

Date of Test: June 20-25, 2008

4.7.2 Radiated Emissions Data:

Data are included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data in tables 1-15 list the significant emission frequencies, the limit and the margin of compliance.

Judgement -

Base Unit - Model: LS6115-2 - Passed by 2.8 dB margin compare with the average limit

Base Unit - Model: LS6125-2 - Passed by 3.8 dB margin compare with the average limit

Handset - Passed by 6.6 dB margin compare with the peak limit

TEST ENGINEER:



Signature

Ken Sit, Supervisor
Typed/Printed Name

July 18, 2008
Date

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 1 - Base Unit

Radiated Emissions Data
Pursuant To FCC Part 15 Section 15.323 (d) Emissions Requirements

Lowest Channel:

Polarization	Frequency (MHz)	Measured Power (dBm)	Power Limit (dBm)	Margin (dB)
H	1919.957	-38.9	-9.5	-29.4
H	1918.506	-51.0	-29.5	-21.5
H	1917.024	-52.7	-39.5	-13.2

NOTES:

1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 2 - Base Unit

Radiated Emissions Data Pursuant To FCC Part 15 Section 15.209 Emissions Requirements

Lowest Channel:

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	3843.072	66.2	33	33.3	66.5	15.6	50.9	54.0	-3.1
H	5764.608	58.3	33	36.6	61.9	15.6	46.3	54.0	-7.7
H	7686.144	52.7	33	38.9	58.6	15.6	43.0	54.0	-11.0
H	9607.680	49.6	33	40.4	57.0	15.6	41.4	54.0	-12.6
H	11529.216	45.7	33	40.5	53.2	15.6	37.6	54.0	-16.4

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	3843.072	66.2	33	33.3	66.5	74.0	-7.5
H	5764.608	58.3	33	36.6	61.9	74.0	-12.1
H	7686.144	52.7	33	38.9	58.6	74.0	-15.4
H	9607.680	49.6	33	40.4	57.0	74.0	-17.0
H	11529.216	45.7	33	40.5	53.2	74.0	-20.8

NOTES:

1. Peak detector is used for the emission measurement over 1000 MHz.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 3 - Base Unit

Radiated Emissions Data
Pursuant To FCC Part 15 Section 15.323 (d) Emissions Requirements

Highest Channel:

Polarization	Frequency (MHz)	Measured Power (dBm)	Power Limit (dBm)	Margin (dB)
H	1930.174	-37.2	-9.5	-27.7
H	1931.321	-49.5	-29.5	-20.0
H	1932.650	-54.2	-39.5	-14.7

NOTES:

1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 4 - Base Unit

Radiated Emissions Data Pursuant To FCC Part 15 Section 15.209 Emissions Requirements

Highest Channel:

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	3856.896	66.5	33	33.3	66.8	15.6	51.2	54.0	-2.8
H	5785.344	57.8	33	36.6	61.4	15.6	45.8	54.0	-8.2
H	7713.792	52.4	33	38.9	58.3	15.6	42.7	54.0	-11.3
H	9642.240	48.6	33	40.4	56.0	15.6	40.4	54.0	-13.6
H	11570.688	46.1	33	40.5	53.6	15.6	38.0	54.0	-16.0

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	3856.896	66.5	33	33.3	66.8	74.0	-7.2
H	5785.344	57.8	33	36.6	61.4	74.0	-12.6
H	7713.792	52.4	33	38.9	58.3	74.0	-15.7
H	9642.240	48.6	33	40.4	56.0	74.0	-18.0
H	11570.688	46.1	33	40.5	53.6	74.0	-20.4

NOTES:

1. Peak detector is used for the emission measurement over 1000 MHz.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2
Mode: Talk

Date of Test: June 20-25, 2008

Table 5 - Base Unit

Radiated Emissions Data
Pursuant To FCC Part 15 Section 15.323 (d) Emissions Requirements

Polarization	Frequency (MHz)	Measured Power (dBm)	Power Limit (dBm)	Margin (dB)
V	41.570	-65.4	-39.5	-25.9
V	56.273	-64.2	-39.5	-24.7
V	69.014	-64.6	-39.5	-25.1
V	82.596	-64.7	-39.5	-25.2
V	96.360	-65.0	-39.5	-25.5
V	124.241	-65.2	-39.5	-25.7

NOTES:

1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6125-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 6 - Base Unit

Radiated Emissions Data
Pursuant To FCC Part 15 Section 15.323 (d) Emissions Requirements

Lowest Channel:

Polarization	Frequency (MHz)	Measured Power (dBm)	Power Limit (dBm)	Margin (dB)
H	1917.066	-52.5	-39.5	-13.0
H	1918.577	-50.6	-29.5	-21.1
H	1919.965	-39.4	-9.5	-29.9

NOTES:

1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6125-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 7 - Base Unit

Radiated Emissions Data Pursuant To FCC Part 15 Section 15.209 Emissions Requirements

Lowest Channel:

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	3843.072	65.5	33	33.3	65.8	15.6	50.2	54.0	-3.8
H	5764.608	57.3	33	36.6	60.9	15.6	45.3	54.0	-8.7
H	7686.144	52.3	33	38.9	58.2	15.6	42.6	54.0	-11.4
H	9607.680	46.2	33	40.4	53.6	15.6	38.0	54.0	-16.0
H	11529.216	45.9	33	40.5	53.4	15.6	37.8	54.0	-16.2

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	3843.072	65.5	33	33.3	65.8	74.0	-8.2
H	5764.608	57.3	33	36.6	60.9	74.0	-13.1
H	7686.144	52.3	33	38.9	58.2	74.0	-15.8
H	9607.680	46.2	33	40.4	53.6	74.0	-20.4
H	11529.216	45.9	33	40.5	53.4	74.0	-20.6

NOTES:

1. Peak detector is used for the emission measurement over 1000 MHz.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 8 - Base Unit

Radiated Emissions Data
Pursuant To FCC Part 15 Section 15.323 (d) Emissions Requirements

Highest Channel:

Polarization	Frequency (MHz)	Measured Power (dBm)	Power Limit (dBm)	Margin (dB)
H	1930.156	-38.0	-9.5	-28.5
H	1931.362	-49.6	-29.5	-20.1
H	1932.654	-54.0	-39.5	-14.5

NOTES:

1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6125-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 9 - Base Unit

Radiated Emissions Data Pursuant To FCC Part 15 Section 15.209 Emissions Requirements

Highest Channel:

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	3856.896	65.1	33	33.3	65.4	15.6	49.8	54.0	-4.2
H	5785.344	57.2	33	36.6	60.8	15.6	45.2	54.0	-8.8
H	7713.792	52.8	33	38.9	58.7	15.6	43.1	54.0	-10.9
H	9642.240	46.6	33	40.4	54.0	15.6	38.4	54.0	-15.6
H	11570.688	46.1	33	40.5	53.6	15.6	38.0	54.0	-16.0

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	3856.896	65.1	33	33.3	65.4	74.0	-8.6
H	5785.344	57.2	33	36.6	60.8	74.0	-13.2
H	7713.792	52.8	33	38.9	58.7	74.0	-15.3
H	9642.240	46.6	33	40.4	54.0	74.0	-20.0
H	11570.688	46.1	33	40.5	53.6	74.0	-20.4

NOTES:

1. Peak detector is used for the emission measurement over 1000 MHz.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6125-2
Mode: Talk

Date of Test: June 20-25, 2008

Table 10 - Base Unit

Radiated Emissions Data
Pursuant To FCC Part 15 Section 15.323 (d) Emissions Requirements

Polarization	Frequency (MHz)	Measured Power (dBm)	Power Limit (dBm)	Margin (dB)
V	41.270	-65.5	-39.5	-26.0
V	56.362	-64.1	-39.5	-24.6
V	69.078	-64.4	-39.5	-24.9
V	82.106	-64.5	-39.5	-25.0
V	96.339	-64.7	-39.5	-25.2
V	124.457	-64.8	-39.5	-25.3

NOTES:

1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6125-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 11 - Handset

Radiated Emissions Data
Pursuant To FCC Part 15 Section 15.323 (d) Emissions Requirements

Lowest Channel:

Polarization	Frequency (MHz)	Measured Power (dBm)	Power Limit (dBm)	Margin (dB)
V	1919.905	-38.5	-9.5	-29.0
V	1918.506	-50.8	-29.5	-21.3
V	1917.403	-53.2	-39.5	-13.7

NOTES:

1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6125-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 12 - Handset

Radiated Emissions Data Pursuant To FCC Part 15 Section 15.209 Emissions Requirements

Lowest Channel:

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	3843.072	65.7	33	33.3	66.0	28.2	37.8	54.0	-16.2
H	5764.608	63.4	33	36.6	67.0	28.2	38.8	54.0	-15.2
H	7686.144	54.4	33	38.9	60.3	28.2	32.1	54.0	-21.9
H	9607.680	47.1	33	40.4	54.5	28.2	26.3	54.0	-27.7
H	11529.216	48.5	33	40.5	56.0	28.2	27.8	54.0	-26.2

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	3843.072	65.7	33	33.3	66.0	74.0	-8.0
H	5764.608	63.4	33	36.6	67.0	74.0	-7.0
H	7686.144	54.4	33	38.9	60.3	74.0	-13.7
H	9607.680	47.1	33	40.4	54.5	74.0	-19.5
H	11529.216	48.5	33	40.5	56.0	74.0	-18.0

NOTES:

1. Peak detector is used for the emission measurement over 1000 MHz.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6125-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 13, Handset

Radiated Emissions Data
Pursuant To FCC Part 15 Section 15.323 (d) Emissions Requirements

Highest Channel:

Polarization	Frequency (MHz)	Measured Power (dBm)	Power Limit (dBm)	Margin (dB)
V	1930.187	-36.4	-9.5	-26.9
V	1931.325	-49.6	-29.5	-20.1
V	1932.630	-53.5	-39.5	-14.0

NOTES:

1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6125-2
Mode: Transmission

Date of Test: June 20-25, 2008

Table 14 - Handset

Radiated Emissions Data Pursuant To FCC Part 15 Section 15.209 Emissions Requirements

Highest Channel:

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Average Factor (dB)	Calculated at 3m (dB μ V/m)	Average Limit at 3m (dB μ V/m)	Margin (dB)
H	3856.896	66.2	33	33.3	66.5	28.2	38.3	54.0	-15.7
H	5785.344	63.8	33	36.6	67.4	28.2	39.2	54.0	-14.8
H	7713.792	54.7	33	38.9	60.6	28.2	32.4	54.0	-21.6
H	9642.240	46.2	33	40.4	53.6	28.2	25.4	54.0	-28.6
H	11570.688	49.0	33	40.5	56.5	28.2	28.3	54.0	-25.7

Polarization	Frequency (MHz)	Reading (dB μ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB μ V/m)	Peak Limit at 3m (dB μ V/m)	Margin (dB)
H	3856.896	66.2	33	33.3	66.5	74.0	-7.5
H	5785.344	63.8	33	36.6	67.4	74.0	-6.6
H	7713.792	54.7	33	38.9	60.6	74.0	-13.4
H	9642.240	46.2	33	40.4	53.6	74.0	-20.4
H	11570.688	49.0	33	40.5	56.5	74.0	-17.5

NOTES:

1. Peak detector is used for the emission measurement over 1000 MHz.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6125-2
Mode: Talk

Date of Test: June 20-25, 2008

Table 15 - Handset

Radiated Emissions Data
Pursuant To FCC Part 15 Section 15.323 (d) Emissions Requirements

Polarization	Frequency (MHz)	Measured Power (dBm)	Power Limit (dBm)	Margin (dB)
V	41.473	-64.1	-39.5	-24.6
V	55.297	-64.4	-39.5	-24.9
V	69.121	-65.4	-39.5	-25.9
V	82.945	-66.4	-39.5	-26.9
V	96.769	-65.7	-39.5	-26.2
H	110.593	-64.1	-39.5	-24.6
H	124.417	-64.8	-39.5	-25.3
H	207.361	-65.2	-39.5	-25.7

NOTES:

1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters.
3. Negative value in the margin column shows emission below limit.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.7.3 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

Where FS = Field Strength in dB μ V/m
 RA = Receiver Amplitude (including preamplifier) in dB μ V
 CF = Cable Attenuation Factor in dB
 AF = Antenna Factor in dB
 AG = Amplifier Gain in dB
 PD = Pulse Desensitization in dB
 AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

Example

Assume a receiver reading of 62.0 dB μ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29.0 dB is subtracted. The pulse desensitization factor of the spectrum analyzer is 0.0 dB, and the resultant average factor is -10.0 dB. The net field strength for comparison to the appropriate emission limit is 32.0 dB μ V/m. This value in dB μ V/m is converted to its corresponding level in μ V/m.

RA = 62.0 dB μ V
AF = 7.4 dB
CF = 1.6 dB
AG = 29.0 dB
PD = 0.0 dB
AV = -10 dB

$$FS = 62.0 + 7.4 + 1.6 - 29.0 + 0.0 + (-10.0) = 32.0 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm } [(32.0 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.8 Average Factor Calculation and Transmitter ON Time Measurements, FCC Rule 15.35(b), (c)

Base Unit - Model: LS6115-2 (for four handsets, single-slot operation with dummy)
Duty Cycle (DC) = Maximum ON time in 10ms/10ms
= (4 x 1 x 0.388ms + 0.101ms)/10ms

Average Factor (AF), dB = $20 \cdot \log(\text{DC})$
= $20 \cdot \log(0.1653)$
= -15.6dB

Base Unit - Model: LS6125-2 (for four handsets, single-slot operation with dummy)
Duty Cycle (DC) = Maximum ON time in 10ms/10ms
= (4 x 1 x 0.388ms + 0.102ms)/10ms

Average Factor (AF), dB = $20 \cdot \log(\text{DC})$
= $20 \cdot \log(0.1654)$
= -15.6dB

Handset (for single-slot operation)
Duty Cycle (DC) = Maximum ON time in 10ms/10ms
= (1 x 0.386ms)/10ms

Average Factor (AF), dB = $20 \cdot \log(\text{DC})$
= $20 \cdot \log(0.0386)$
= -28.2dB

[×] The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SPAN function on the analyzer was set to ZERO. The transmitter ON time was determined from the resultant time-amplitude display:

Please refer to the attached plots for more details:

Base Unit - Model: LS6115-2
Plot B5A1: Transmitter ON Time Measurements (Traffic Carrier)
Plot B5B1: Transmitter ON Time Measurements (Dummy Carrier)

Base Unit - Model: LS6125-2
Plot B5A2: Transmitter ON Time Measurements (Traffic Carrier)
Plot B5B2: Transmitter ON Time Measurements (Dummy Carrier)

Handset
Plot H5A: Transmitter ON Time Measurements (Traffic Carrier)

The plots of Transmitter ON Time Measurements are saved as filename: dcc.pdf

[] Please refer to the attached transmitter timing diagram that are provided by manufacturer

[] Not applicable - No average factor is required.

[] Please refer to Exhibit 2.2 Technical Description for more details

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.9 AC Power Lines Conducted Emissions from Transmitter portion of EUT, FCC Rule 15.315:

The AC power lines conducted emission shall not exceed the limits of FCC Rule 15.207.

Measurements are made in accordance with ANSI C63.4 sub-clause 7. Emissions that are directly caused by digital circuits in the transmit path and transmitter portion are measured.

☐ Not applicable – EUT is only powered by battery for operation.

☒ EUT connects to AC power lines. Emission Data are listed in following pages. Please refer to the section 4.9.1 to 4.9.2 for more details.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2
Mode: Talk

Date of Test: June 20-25, 2008

4.9.1 AC Power Lines Conducted Emissions Configuration Photographs:

Worst Case AC Power Line Conducted Emission
at

Base Unit - Model: LS6125-2 - 1.76500 MHz

The worst case AC power Line conducted emission configuration photographs are saved as filename: config photos.pdf

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2
Mode: Talk

Date of Test: June 20-25, 2008

4.9.2 AC Power Line Conducted Emissions Data:

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgment:

Base Unit - Model: LS6115-2 - Passed by more than 20 dB margin

Base Unit - Model: LS6125-2 - Passed by 15.9 dB margin

The worst case AC power line conducted emission data are saved as filename:
conduct.pdf

TEST ENGINEER:



Signature

Ken Sit, Supervisor
Typed/Printed Name

July 18, 2008
Date

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.9 Radio Frequency Radiation Exposure, FCC Rule 15.319(i):

EUT is subject to the radio frequency exposure requirements specified in FCC Rule §§ 1.1307(b), 2.1091 and 2.1093. It shall be considered to operate in a “general population / uncontrolled” environment.

- [x] Handset Unit: EUT was evaluated for Specific Absorption Rate (SAR) evaluation compliance according to OET Bulletin 65, Supplement C (Edition 01-01). It is in compliance with the SAR evaluation requirements. The caution statement specified in the user manual. A SAR test report was submitted at the same time and saved as SAR report 1 of 2.pdf and SAR report 2 of 2.pdf
- [x] Base Unit: EUT was evaluated for Maximum Permissible Exposure (MPE) evaluation compliance according to OET Bulletin 65, Supplement C (Edition 01-01). The evaluation calculation results are saved as filename: RF exposure info.pdf.

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.10 Frame Jitter, FCC Rule 15.323(e):

The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of EUT operating in these sub-bands shall be 20 ms or 10 ms/X where X is a positive whole number.

The jitter (time-related, abrupt, spurious variations in the duration of the frame interval) introduced at the two ends of such a communication link shall not exceed 25 μ s for any two consecutive transmissions. Transmissions shall be continuous in every time and spectrum window during the frame period defined for EUT.

Measurements are made in accordance with ANSI C63.17 sub-clause 6.2.3. Test setup is shown in section 3.2 Figure 3.2.1. A spectrum analyzer measures the time duration between the rising edges of two consecutive frames. The measurements are taken over 100,000 frames. These measurement values are used to compute mean value and the difference between any two consecutive frame periods. The mean value is the frame period.

Test Results:

I. Jitter - Base Unit - Model: LS6115-2

Measured Maximum Jitter (μ s)	Limit (μ s)	Results
-0.1831	± 25	Pass

II. Jitter - Base Unit - Model: LS6125-2

Measured Maximum Jitter (μ s)	Limit (μ s)	Results
-0.1806	± 25	Pass

III. Jitter - Handset

Measured Maximum Jitter (μ s)	Limit (μ s)	Results
-0.2743	± 25	Pass

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.11 Monitoring Threshold:

Monitoring threshold can be relaxed according to FCC Rule 15.323(c)(9). EUT that has a power output lower than the maximum permitted under FCC Rule 15.319(c) may increase their monitoring detection threshold by one decibel for each one decibel that the transmitter power is below the maximum permitted.

Calculation of Monitoring Threshold Limit:

$$\begin{aligned}\text{Monitoring Threshold (T)} &\leq -174 + 10 \log_{10} B + M + P_{\max} - P_{\text{EUT}} \text{ dBm} \\ &\leq 15 \log_{10} B - 184 + M - P_{\text{EUT}} \text{ dBm}\end{aligned}$$

Where B = Measured Occupied Bandwidth of Base Unit for Model: LS6115-2:
 $\underline{1.43} \times 10^6 \text{ Hz}$
 B = Measured Occupied Bandwidth of Base Unit for Model: LS6125-2:
 $\underline{1.42} \times 10^6 \text{ Hz}$
 B = Measured Occupied Bandwidth of Handset: $\underline{1.49} \times 10^6 \text{ Hz}$
 M = 50 dB for Upper Monitoring Threshold ($T_U + U_m$)
 $P_{\max}$ = $5 \log_{10} B - 10 \text{ dBm}$
 P_{EUT} = Measured Peak Transmit Power of Base Unit for Model: LS6115-2:
 $\underline{20.23} \text{ dBm}$
 P_{EUT} = Measured Peak Transmit Power of Base Unit for Model: LS6125-2:
 $\underline{19.87} \text{ dBm}$
 P_{EUT} = Measured Peak Transmit Power of Handset: $\underline{20.54} \text{ dBm}$

Calculated Monitoring Threshold Limits:

I. Base Unit - Model: LS6115-2

Upper Monitoring Threshold ($T_U + U_m$) in dBm	-55.9
---	-------

II. Base Unit - Model: LS6125-2

Upper Monitoring Threshold ($T_U + U_m$) in dBm	-55.6
---	-------

III. Handset

Upper Monitoring Threshold ($T_U + U_m$) in dBm	-55.9
---	-------

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6115-2, LS6125-2

Date of Test: June 20-25, 2008

4.11.1 Upper Monitoring Threshold, FCC Rule 15.323(c)(5):

Measurements are made in accordance with ANSI C63.17 sub-clause 7.3.2(b). Test setup is shown in section 3.3 Figure 3.3.1. The test is performed on the carrier closest to center of the band. RF signal generators apply uniform CW interference on all EUT carriers each at level $T_U + 10$ dB. Then, the interference level is reduced uniformly on all carriers until the EUT can transmit. The interference level shall be lower than or equal to the threshold limit ($T_U + U_M + 10$ dB).

Test Results:

I. Base Unit - Model: LS6115-2

Measured Maximum Interference Level (dBm)	Upper Monitoring Threshold Limit (dBm)	Results
-62.2	-55.9	Pass

II. Base Unit - Model: LS6125-2

Measured Maximum Interference Level (dBm)	Upper Monitoring Threshold Limit (dBm)	Results
-61.2	-55.6	Pass

III. Handset:

Measured Maximum Interference Level (dBm)	Upper Monitoring Threshold Limit (dBm)	Results
-62.1	-55.9	Pass

INTERTEK TESTING SERVICES

Company: VTech Telecommunications Ltd.
Model: LS6125-2

Date of Test: June 20-25, 2008

4.12 Monitoring Antenna, FCC Rule 15.323(c)(8):

The monitoring system shall use the same antenna used for transmission, or an antenna that yields equivalent reception at that location.

- ☒ EUT uses the same antenna used for transmission and monitoring that is in compliance meet above provision.
- ☐ EUT uses difference antenna used for transmission and monitoring. It must be verified that the monitoring antenna provides coverage equivalent to that of the transmitting antenna. Measurements are made in accordance with ANSI C63.17 sub-clause 4.

**EXHIBIT 5
EQUIPMENT PHOTOGRAPHS**

5.0 Equipment Photographs

The photographs are saved as filename: external photos.pdf & internal photos.pdf

**EXHIBIT 6
TECHNICAL SPECIFICATIONS**

6.0 Technical Specifications

The block diagram and circuit diagram are saved as filename: block.pdf and circuit.pdf respectively.

**EXHIBIT 7
LETTER OF AGENCY**

7.0 Letter of Agency

A copy of the Letter of Agency is saved as filename: letter of agency.pdf

**EXHIBIT 8
CONFIDENTIALITY REQUEST**

8.0 Confidentiality Request

A copy of the Confidentiality Request is saved as filename: request.pdf