

## TEST REPORT

**Report Number: HK12041065-3**

Application  
for

Original Grant of 47 CFR Part 15 Certification  
New Family of RSS-210 Issue 8 Equipment Certification

1.9GHz Digital Modulation Cordless Phone with Caller ID, Speakerphone,  
Digital Answering Machine, Corded Handset and Bluetooth - Base Unit  
Bluetooth Portion

**FCC ID: EW780-8876-00**

**IC: 1135B-80887600**

Prepared and Checked by:

Approved by:

***Signed on File***

Koo Wai Ip  
Senior Lead Engineer

---

Nip Ming Fung, Melvin  
Assistant Manager  
May 10, 2012

- The test report only allows to be revised within the retention period unless further standard or the requirement was noticed.
- This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## INTERTEK TESTING SERVICES

---

### GENERAL INFORMATION

<b>Applicant Name:</b>	VTech Telecommunications Ltd.
<b>Applicant Address:</b>	23/F., Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road, Tai Po, Hong Kong.
<b>FCC Specification Standard:</b>	FCC Part 15, October 1, 2010 Edition
<b>FCC ID:</b>	EW780-8876-00
<b>FCC Model(s):</b>	DS6641, DS6642-4, DS664Z-XY
<b>IC Specification Standard:</b>	RSS-210 Issue 8, December 2010 RSS-Gen Issue 3, December 2010
<b>IC:</b>	1135B-80887600
<b>IC Model(s):</b>	DS6641, DS6642-4
<b>Type of EUT:</b>	Transceiver
<b>Description of EUT:</b>	1.9GHz Digital Modulation Cordless Phone with Caller ID, Speakerphone, Digital Answering Machine, Corded Handset and Bluetooth - Base Unit Bluetooth Portion
<b>Serial Number:</b>	N/A
<b>Sample Receipt Date:</b>	April 24, 2012
<b>Date of Test:</b>	AC power line conducted emission test: May 04, 2012 Other tests: May 02 - 10, 2012
<b>Report Date:</b>	May 10, 2012
<b>Environmental Conditions:</b>	Temperature: +10 to 40°C Humidity: 10 to 90%

---

# INTERTEK TESTING SERVICES

---

## Table of Contents

<b>1.0 Test Results Summary &amp; Statement of Compliance</b> .....	4
1.1 Summary of Test Results .....	4
1.2 Statement of Compliance .....	4
<b>2.0 General Description</b> .....	6
2.1 Product Description .....	6
2.2 Test Methodology .....	7
2.3 Test Facility .....	7
<b>3.0 System Test Configuration</b> .....	9
3.1 Justification .....	9
3.2 EUT Exercising Software .....	10
3.3 Details of EUT and Description of Accessories .....	11
3.4 Measurement Uncertainty .....	11
<b>4.0 Test Results</b> .....	13
4.1 Field Strength Calculation .....	13
4.2 Radiated Emissions .....	14
4.2.1 Radiated Emission Configuration Photograph .....	14
4.2.2 Radiated Emission Data .....	14
4.2.3 Transmitter Duty Cycle Calculation .....	15
4.3 Radiated Emission on the Bandedge .....	20
4.4 AC Power Line Conducted Emission .....	21
4.4.1 AC Power Line Conducted Emission Configuration Photograph .....	21
4.4.2 AC Power Line Conducted Emission Data .....	21
<b>5.0 Equipment List</b> .....	29

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 1  
TEST RESULTS SUMMARY & STATEMENT OF COMPLIANCE**

# INTERTEK TESTING SERVICES

---

## 1.0 Test Results Summary & Statement of Compliance

### 1.1 Summary of Test Results

Test Items	FCC Part 15 Section	RSS-210/ RSS-Gen <sup>#</sup> / RSS-310 <sup>^</sup> Section	Results	Details see section
Antenna Requirement	15.203	7.1.2 <sup>#</sup>	Pass	2.1
Radiated Emission Radiated Emission on the Bandedge	15.249(a), 209, & 109 15.249(d)	A2.9(a) A2.9(b)	Pass Pass	4.2 4.4
Radiated Emission in Restricted Bands	15.205	2.2	Pass	4.2
AC Power Line Conducted Emission	15.207 & 15.107	7.2.4 <sup>#</sup>	Pass	4.4
Radio Frequency Exposure Compliance	N/A	RSS-102	Pass	4.5

Note: Pursuant to FCC Part 15 Section 15.215(c), the 20dB bandwidth of the emission was contained within the frequency band designated (mentioned as above) which the EUT operated. The effects, if any, from frequency sweeping, frequency hopping, other modulation techniques and frequency stability over expected variations in temperature and supply voltage were considered.

### 1.2 Statement of Compliance

The equipment under test is found to be complying with the following standards:

FCC Part 15, October 1, 2010 Edition  
RSS-210 Issue 8, December 2010  
RSS-Gen Issue 3, December 2010

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 2  
GENERAL DESCRIPTION**

## **INTERTEK TESTING SERVICES**

---

### **2.0 General Description**

#### **2.1 Product Description**

The DS6642-4 is a 1.9GHz Digital Modulation Cordless Phone with Caller ID, Speakerphone, Digital Answering Machine, Corded Handset and Bluetooth - Base Unit Bluetooth Portion. It operates at frequency range of 2400MHz to 2483.5MHz. The Base Unit is powered by an adaptor 100-120VAC to 6VDC 400mA.

The antenna used in base unit is integral, and the test sample is a prototype.

For FCC, The Model(s): DS6641 and DS664Z-XY are the same as the Model: DS6642-4 in electronics/electrical designs, including software & firmware, PCB layout and construction design/physical design/enclosure. The only differences between these models are color, model number, packing configuration and material to be sold for marketing purpose. Suffix (X) indicates any alphanumeric character or blank presenting number of handset and extra charger. Suffix (Y) indicates any alphanumeric character or blank presenting different color of enclosure. Suffix (Z) indicates any alphanumeric character presenting different package material.

For IC, The Model(s): DS6641 is the same as the Model: DS6642-4 in electronics/electrical designs, including software & firmware, PCB layout and construction design/physical design/enclosure. The only differences between these models are color, model number, packing configuration and material to be sold for marketing purpose.

The circuit description is saved with filename: descri.pdf.

Connection between the device and the telephone network is accomplished through the use of USOC RJ11C in the 2-wire loop calling central office line.

## INTERTEK TESTING SERVICES

---

### 2.2 Test Methodology

Both AC power line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). Preliminary radiated scans and all radiated measurements were performed in Open Area Test Sites. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application.

### 2.3 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data and conducted data are at Roof Top and 2<sup>nd</sup> Floor respectively of Intertek Testing Services Hong Kong Ltd., which is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC and the Industry Canada.

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 3  
SYSTEM TEST CONFIGURATION**

---

## INTERTEK TESTING SERVICES

---

### 3.0 System Test Configuration

#### 3.1 Justification

For radiated emissions testing, the equipment under test (EUT) was setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables (if any) were manipulated to produce worst case emissions.

The Base Unit was powered by a 100-120VAC to 6VDC 400mA adaptor.

For the measurements, the EUT was attached to a plastic stand if necessary and placed on the wooden turntable. If the base unit attached to peripherals, they were connected and operational to simulate typical use. The handset was remotely located as far from the antenna and the base as possible to ensure full power transmission from the base. Else, the base was wired to transmit full power.

The signal was maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization were varied during the search for maximum signal level. The antenna height was varied from 1 to 4 meters. Radiated emissions were taken at three meters unless the signal level was too low for measurement at that distance. If necessary, a pre-amplifier was used and/or the test was conducted at a closer distance.

For any intentional radiator powered by AC power line, measurements of the radiated signal level of the fundamental frequency component of the emission was performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage.

For transmitter radiated measurement, the spectrum analyzer resolution bandwidth was 100 kHz for frequencies below 1000 MHz. The resolution bandwidth was 1 MHz for frequencies above 1000 MHz.

For radiated measurement, the spectrum analyzer resolution bandwidth was 100 kHz for frequencies below 1000 MHz.

Radiated emission measurement for transmitter was performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower. Emission that are directly caused by digital circuits in the transmit path and transmitter portion were measured, and the limit are according to FCC Part 15 Section 15.209.

---

## INTERTEK TESTING SERVICES

---

The DECT module was put into transmission mode when taking radiated emission data for determining worst-case spurious emission.

Detector function for radiated emissions is in peak mode. Average readings, when required, are taken by measuring the duty cycle of the equipment under test and subtracting the corresponding amount in dB from the measured peak readings. A detailed description for the calculation of the average factor can be found in section 4.2.3.

Determination of pulse desensitization was made according to *Hewlett Packard Application Note 150-2, Spectrum Analysis... Pulsed RF*. The effective period ( $T_{eff}$ ) was  $625\mu s$ . With the resolution bandwidth 1MHz and spectrum analyzer IF bandwidth 3dB, the pulse desensitization factor was 0dB.

For AC line conducted emission test, the EUT along with its peripherals were placed on a 1.0m(W)x1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN), which provided 50ohm coupling impedance for measuring instrument. The LISN housing, measuring instrument case, reference ground plane, and vertical ground plane were bounded together. The excess power cable between the EUT and the LISN was bundled.

All connecting cables of EUT and peripherals were manipulated to find the maximum emission.

All relevant operation modes have been tested, and the worst case data is included in this report.

### 3.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

---

## INTERTEK TESTING SERVICES

---

### 3.3 Details of EUT and Description of Accessories

#### Details of EUT:

An AC adaptor and/or a battery (provided with the unit) were used to power the device. Their descriptions are listed below.

- (1) Base Unit: An AC adaptor (100-120VAC to 6VDC 400mA, Model: S005IU0600040) (Supplied by Client)

#### Description of Accessories:

- (1) Telecommunication cable with RJ11C connectors (1m, unshielded), (Supplied by Intertek)
- (2) Telecommunication cable with RJ11C connectors (3m, unshielded), (Supplied by Intertek)
- (3) Telephone Line Simulator, Model: TLS-5C-01, S/N: 059355 (Supplied by Intertek)
- (4) Handset Unit, Model: DS6642-4, FCC ID: EW780-8876-00, IC: 1135B-80887600 (Supplied by Client)
- (5) Nokia Mobile Phone: Model: 5300, FCC ID: PPIRM-146 (Supplied by Intertek)

### 3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 4  
TEST RESULTS**

---

## INTERTEK TESTING SERVICES

---

### 4.0 Test Results

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included.

#### 4.1 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where

- FS = Field Strength in dB $\mu$ V/m
- RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V
- CF = Cable Attenuation Factor in dB
- AF = Antenna Factor in dB
- AG = Amplifier Gain in dB
- PD = Pulse Desensitization in dB
- AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

#### Example

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$\begin{aligned} RA &= 62.0 \text{ dB}\mu\text{V} \\ AF &= 7.4 \text{ dB} \\ CF &= 1.6 \text{ dB} \\ AG &= 29 \text{ dB} \\ PD &= 0 \text{ dB} \\ AV &= -10 \text{ dB} \\ FS &= 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m} \end{aligned}$$

$$\text{Level in } \mu\text{V/m} = \text{Common Antilogarithm} [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

## INTERTEK TESTING SERVICES

---

### 4.2 Radiated Emissions

#### 4.2.1 Radiated Emission Configuration Photograph

Worst Case Radiated Emission  
at

Base Unit: 85.900 MHz

The worst case radiated emission configuration photographs are saved with filename: config photos.pdf

#### 4.2.2 Radiated Emission Data

The data in tables 1-4 list the significant emission frequencies, the limit and the margin of compliance.

Judgement -

Base Unit: Passed by 5.5 dB margin

## INTERTEK TESTING SERVICES

---

### 4.2.3 Transmitter Duty Cycle Calculation

Based on the Bluetooth Specification Version 2.0 / 2.1 + EDR, the transmitter ON time for each timeslot of Bluetooth is  $625\mu\text{s}$ . DH5 has the maximum duty cycle, which consists of 5 continuous Tx slots and 1 Rx slot. Therefore one hopset take  $(5+1) \times 625\mu\text{s} = 3.75\text{ms}$ . For one period for a pseudo-random hopping through all 79 RF channels, it take:  $79 \times 3.75\text{ms} = 296.25\text{ms}$ .

The dwell time for DH5 is  $5 \times 625\mu\text{s} = 3.125\text{ms}$ .

Therefore,

$$\begin{aligned}\text{Duty Cycle (DC)} &= \text{Maximum On time in } 100\text{ms}/100\text{ms} \\ &= 3.125\text{ms}/100\text{ms} \\ &= 0.03125\end{aligned}$$

$$\begin{aligned}\text{Average Factor (AF) of Bluetooth in dB} &= 20 \log_{10} (0.03125) \\ &= -30.1\text{dB}\end{aligned}$$

## INTERTEK TESTING SERVICES

---

Mode: TX-Channel 00

Table 1, Base Unit

### Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2402.000	99.0	33	29.4	30.1	65.3	94.0	-28.7
<b>H</b>	<b>4804.000</b>	<b>57.5</b>	<b>33</b>	<b>34.9</b>	<b>30.1</b>	<b>29.3</b>	<b>54.0</b>	<b>-24.7</b>
H	7206.000	51.9	33	37.9	30.1	26.7	54.0	-27.3
H	9608.000	48.8	33	40.4	30.1	26.1	54.0	-27.9
<b>H</b>	<b>12010.000</b>	<b>46.9</b>	<b>33</b>	<b>40.5</b>	<b>30.1</b>	<b>24.3</b>	<b>54.0</b>	<b>-29.7</b>
H	14412.000	49.2	33	40.0	30.1	26.1	54.0	-27.9

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2402.000	99.0	33	29.4	95.4	114.0	-18.6
<b>H</b>	<b>4804.000</b>	<b>57.5</b>	<b>33</b>	<b>34.9</b>	<b>59.4</b>	<b>74.0</b>	<b>-14.6</b>
H	7206.000	51.9	33	37.9	56.8	74.0	-17.2
H	9608.000	48.8	33	40.4	56.2	74.0	-17.8
<b>H</b>	<b>12010.000</b>	<b>46.9</b>	<b>33</b>	<b>40.5</b>	<b>54.4</b>	<b>74.0</b>	<b>-19.6</b>
H	14412.000	49.2	33	40.0	56.2	74.0	-17.8

- NOTES:
1. Peak detector is used for the emission measurement.
  2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna is used for the emission over 1000MHz.
  5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

## INTERTEK TESTING SERVICES

Mode: TX-Channel 39

Table 2, Base Unit

### Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2441.000	99.8	33	29.4	30.1	66.1	94.0	-27.9
<b>H</b>	<b>4882.000</b>	<b>57.7</b>	<b>33</b>	<b>34.9</b>	<b>30.1</b>	<b>29.5</b>	<b>54.0</b>	<b>-24.5</b>
<b>H</b>	<b>7323.000</b>	<b>51.9</b>	<b>33</b>	<b>37.9</b>	<b>30.1</b>	<b>26.7</b>	<b>54.0</b>	<b>-27.3</b>
H	9764.000	49.0	33	40.4	30.1	26.3	54.0	-27.7
<b>H</b>	<b>12205.000</b>	<b>47.1</b>	<b>33</b>	<b>40.5</b>	<b>30.1</b>	<b>24.5</b>	<b>54.0</b>	<b>-29.5</b>
H	14646.000	49.8	33	38.4	30.1	25.1	54.0	-28.9

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2441.000	99.8	33	29.4	96.2	114.0	-17.8
<b>H</b>	<b>4882.000</b>	<b>57.7</b>	<b>33</b>	<b>34.9</b>	<b>59.6</b>	<b>74.0</b>	<b>-14.4</b>
<b>H</b>	<b>7323.000</b>	<b>51.9</b>	<b>33</b>	<b>37.9</b>	<b>56.8</b>	<b>74.0</b>	<b>-17.2</b>
H	9764.000	49.0	33	40.4	56.4	74.0	-17.6
<b>H</b>	<b>12205.000</b>	<b>47.1</b>	<b>33</b>	<b>40.5</b>	<b>54.6</b>	<b>74.0</b>	<b>-19.4</b>
H	14646.000	49.8	33	38.4	55.2	74.0	-18.8

- NOTES:
1. Peak detector is used for the emission measurement.
  2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna is used for the emission over 1000MHz.
  5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

## INTERTEK TESTING SERVICES

Mode: TX-Channel 78

Table 3, Base Unit

### Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Average Factor (dB)	Calculated at 3m (dB $\mu$ V/m)	Average Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2480.000	100.0	33	29.4	30.1	66.3	94.0	-27.7
<b>H</b>	<b>4960.000</b>	<b>57.5</b>	<b>33</b>	<b>34.9</b>	<b>30.1</b>	<b>29.3</b>	<b>54.0</b>	<b>-24.7</b>
<b>H</b>	<b>7440.000</b>	<b>52.2</b>	<b>33</b>	<b>37.9</b>	<b>30.1</b>	<b>27.0</b>	<b>54.0</b>	<b>-27.0</b>
H	9920.000	49.4	33	40.4	30.1	26.7	54.0	-27.3
<b>H</b>	<b>12400.000</b>	<b>48.7</b>	<b>33</b>	<b>40.5</b>	<b>30.1</b>	<b>26.1</b>	<b>54.0</b>	<b>-27.9</b>
H	14880.000	49.8	33	38.4	30.1	25.1	54.0	-28.9

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Peak Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	2480.000	100.0	33	29.4	96.4	114.0	-17.6
<b>H</b>	<b>4960.000</b>	<b>57.5</b>	<b>33</b>	<b>34.9</b>	<b>59.4</b>	<b>74.0</b>	<b>-14.6</b>
<b>H</b>	<b>7440.000</b>	<b>52.2</b>	<b>33</b>	<b>37.9</b>	<b>57.1</b>	<b>74.0</b>	<b>-16.9</b>
H	9920.000	49.4	33	40.4	56.8	74.0	-17.2
<b>H</b>	<b>12400.000</b>	<b>48.7</b>	<b>33</b>	<b>40.5</b>	<b>56.2</b>	<b>74.0</b>	<b>-17.8</b>
H	14880.000	49.8	33	38.4	55.2	74.0	-18.8

- NOTES:
1. Peak detector is used for the emission measurement.
  2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna is used for the emission over 1000MHz.
  5. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

---

## INTERTEK TESTING SERVICES

---

Mode: Talk

Table 4, Base Unit

### Radiated Emission Data

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-amp (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	42.950	40.2	16	10.0	34.2	40.0	-5.8
V	85.900	42.5	16	8.0	34.5	40.0	-5.5
<b>H</b>	<b>128.850</b>	<b>36.2</b>	<b>16</b>	<b>14.0</b>	<b>34.2</b>	<b>43.5</b>	<b>-9.3</b>
<b>H</b>	<b>171.800</b>	<b>31.8</b>	<b>16</b>	<b>18.0</b>	<b>33.8</b>	<b>43.5</b>	<b>-9.7</b>
H	214.750	32.6	16	17.0	33.6	43.5	-9.9
<b>H</b>	<b>257.700</b>	<b>27.4</b>	<b>16</b>	<b>21.0</b>	<b>32.4</b>	<b>46.0</b>	<b>-13.6</b>

- NOTES:
1. Peak detector is used for the emission measurement.
  2. All measurements were made at 3 meters. Radiated emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other radiated emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Emission (the row indicated by **bold italic**) within the restricted band meets the requirement of FCC Part 15 Section 15.205 / RSS-210 Section 2.2.

## INTERTEK TESTING SERVICES

---

### 4.3 Radiated Emission on the Bandedge

From the following plots, they show that the fundamental emissions are confined in the specified band 2400MHz and 2483.5MHz. In case of emissions up to two standard bandwidths away from the bandedge, the delta measurement technique is used for determining bandedge compliance. Standard bandwidth is the bandwidth specified by ANSI C63.4 (2003) for frequency being measured.

Emissions radiated outside of the specified frequency bands, except harmonics, are attenuated by 50 dB below the level of the fundamental or to the general radiated emission limits in FCC Part 15 Section 15.209 / Table 5 of RSS-Gen, whichever is the lesser attenuation, which meet the requirement of FCC Part 15 Section 15.249(d) / RSS-210 A2.9(b).

Radiated Emission on bandedge plots are saved with filename: be.pdf

Bandedge compliance is determined by applying marker-delta method, i.e.

Resultant Field Strength = Fundamental Emissions - Delta from the plot

Resultant field strength for the lowest and/or highest channel(s), with corresponding average values are calculated as follows:

	Channel	Fundamental Emission (dB $\mu$ V/m)	Delta from the Plot (dB)	Resultant Field Strength (dB $\mu$ V/m)	Average Limit (dB $\mu$ V/m)	Margin (dB)
Base	Lowest	65.30	29.40	35.90	54.00	-18.10
	Highest	66.30	49.35	16.95	54.00	-37.05

	Channel	Fundamental Emission (dB $\mu$ V/m)	Delta from the Plot (dB)	Resultant Field Strength (dB $\mu$ V/m)	Peak Limit (dB $\mu$ V/m)	Margin (dB)
Base	Lowest	95.40	29.40	66.00	74.00	-8.00
	Highest	96.40	49.35	47.05	74.00	-26.95

The resultant field strength meets the general radiated emission limit in FCC Part 15 Section 15.209 / Table 5 of RSS-Gen, which does not exceed 74dB $\mu$ V/m for peak limit and also 54dB $\mu$ V/m for average limit.

## INTERTEK TESTING SERVICES

---

### 4.4 AC Power Line Conducted Emission

- Not applicable – EUT is only powered by battery for operation.
- EUT connects to AC power line. Emission Data is listed in following pages.
- Base Unit connects to AC power line and has transmission. Handset connects to AC power line but has no transmission. Emission Data of Base Unit is listed in following pages.

#### 4.4.1 AC Power Line Conducted Emission Configuration Photograph

Worst Case Line-Conducted Configuration  
at

0.5505 MHz

The worst case line conducted configuration photographs are saved with filename: config photos.pdf


#### 4.4.2 AC Power Line Conducted Emission Data

The plot(s) and data in the following pages list the significant emission frequencies, the limit and the margin of compliance.

Passed by 16.29 dB margin compare with quasi-peak limit

# INTERTEK TESTING SERVICES

## Worst Case: Ringing



Date: 4.MAY.2012 18:41:26

# INTERTEK TESTING SERVICES

---

## Worst Case: Ringing

### EDIT PEAK LIST (Final Measurement Results)

Trace1: CF15MQP

Trace2: CF15MAV


Trace3: ---

TRACE	FREQUENCY	LEVEL dB $\mu$ V	DELTA LIMIT dB
1 Quasi Peak	172.5 kHz	42.36 N gnd	-22.47
1 Quasi Peak	262.5 kHz	37.94 L1 gnd	-23.40
1 Quasi Peak	357 kHz	40.57 L1 gnd	-18.21
1 Quasi Peak	550.5 kHz	39.70 L1 gnd	-16.29
1 Quasi Peak	640.5 kHz	27.29 L1 gnd	-28.70
1 Quasi Peak	883.5 kHz	34.54 L1 gnd	-21.45
1 Quasi Peak	1.1535 MHz	35.17 L1 gnd	-20.82
1 Quasi Peak	1.581 MHz	28.60 L1 gnd	-27.39
1 Quasi Peak	2.562 MHz	30.91 N gnd	-25.08
1 Quasi Peak	3.606 MHz	29.91 N gnd	-26.09
1 Quasi Peak	4.794 MHz	26.55 L1 gnd	-29.44
1 Quasi Peak	11.976 MHz	18.17 L1 gnd	-41.82

Date: 4.MAY.2012 18:40:36

# INTERTEK TESTING SERVICES

## Worst Case: Answer Machine Recording



Date: 4.MAY.2012 18:48:28

# INTERTEK TESTING SERVICES

---


## Worst Case: Answer Machine Recording

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	CF15MQP			
Trace2:	CF15MAV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL dB $\mu$ V		DELTA LIMIT dB
1 Quasi Peak	177 kHz	41.22	N gnd	-23.40
1 Quasi Peak	357 kHz	37.07	L1 gnd	-21.72
1 Quasi Peak	537 kHz	38.23	L1 gnd	-17.76
1 Quasi Peak	622.5 kHz	34.67	L1 gnd	-21.32
1 Quasi Peak	1.077 MHz	34.11	L1 gnd	-21.88
1 Quasi Peak	1.095 MHz	35.05	L1 gnd	-20.94
1 Quasi Peak	1.5765 MHz	28.37	L1 gnd	-27.62
1 Quasi Peak	2.9175 MHz	24.74	L1 gnd	-31.25
1 Quasi Peak	4.2765 MHz	24.33	L1 gnd	-31.66

Date: 4.MAY.2012 18:48:03

# INTERTEK TESTING SERVICES

## Worst Case: Cordless Handset On Line



Date: 4.MAY.2012 18:55:23

# INTERTEK TESTING SERVICES

---

Worst Case: Cordless Handset On Line

EDIT PEAK LIST (Final Measurement Results)				
Trace1:	CF15MQP			
Trace2:	CF15MAV			
Trace3:	---			
TRACE	FREQUENCY	LEVEL	dB $\mu$ V	DELTA LIMIT dB
1 Quasi Peak	181.5 kHz	41.53	N gnd	-22.88
1 Quasi Peak	271.5 kHz	36.76	L1 gnd	-24.31
1 Quasi Peak	366 kHz	35.09	L1 gnd	-23.50
1 Quasi Peak	537 kHz	38.80	L1 gnd	-17.19
1 Quasi Peak	627 kHz	35.41	L1 gnd	-20.58
1 Quasi Peak	879 kHz	34.35	L1 gnd	-21.64
1 Quasi Peak	1.239 MHz	32.99	L1 gnd	-23.00
1 Quasi Peak	1.581 MHz	30.46	L1 gnd	-25.53
1 Quasi Peak	2.7915 MHz	27.20	L1 gnd	-28.79
1 Quasi Peak	3.336 MHz	27.49	L1 gnd	-28.50

Date: 4.MAY.2012 18:55:01

**INTERTEK TESTING SERVICES**

---

**EXHIBIT 5  
EQUIPMENT LIST**

## INTERTEK TESTING SERVICES

---

### 5.0 Equipment List

#### 1) Radiated Emissions Test

Equipment	Log Periodic Antenna	Double Ridged Guide Antenna	Broad-Band Horn Antenna
Registration No.	EW-0446	EW-1133	EW-1679
Manufacturer	EMCO	EMCO	SCHWARZBECK
Model No.	3146	3115	BBHA9170
Calibration Date	Oct. 31, 2011	Mar.02, 2011	Mar. 21, 2012
Calibration Due Date	Apr. 30, 2013	Sep. 02, 2012	Mar. 21, 2013

Equipment	Biconical Antenna	EMI Test Receiver	Spectrum Analyzer
Registration No.	EW-2512	EW-2500	EW-2188
Manufacturer	EMCO	R&S	AGILENTTECH
Model No.	3104C	ESCI	E4407B
Calibration Date	Nov. 15, 2011	Feb. 24, 2012	Sep. 26, 2011
Calibration Due Date	May. 15, 2013	Feb. 24, 2013	Sep. 26, 2012

#### 2) Conducted Emissions Test

Equipment	EMI Test Receiver	Artificial Mains
Registration No.	EW-2251	EW-2501
Manufacturer	R&S	R&S
Model No.	ESCI	ENV-216
Calibration Date	May. 06, 2011	Mar. 30, 2011
Calibration Due Date	May. 06, 2012	Jun, 29, 2012

**END OF TEST REPORT**