

FCC PART 15D MEASUREMENT AND TEST REPORT

For

VTech Telecommunications Ltd.

23/F, Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road, Tai Po, Hong Kong

FCC ID: EW780-9454-00

Report Type: Original Report	Product Type: DECT 6.0 Cordless Telephone (Handset Unit)
Test Engineer: <u>Gardon Zhang</u>	<i>Gardon Zhang</i>
Report Number: <u>R1DG140123002-00PP</u>	
Report Date: <u>2014-02-27</u>	
Reviewed By: <u>Jimmy Xiao</u> RF Engineer	<i>Jimmy Xiao</i>
Prepared By:	Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn

Note: This test report is prepared for the customer shown above and for the equipment described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	5
TEST FACILITY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
LOCAL SUPPORT EQUIPMENT LIST AND DETAILS	6
EXTERNAL I/O CABLE.....	6
BLOCK DIAGRAM OF TEST SETUP	6
SUMMARY OF TEST RESULTS	7
FCC §1.1307 & §2.1093 - RF EXPOSURE.....	8
APPLICABLE STANDARD	8
TEST RESULT	8
FCC§15.317&§15.203 - ANTENNA REQUIREMENT	9
APPLICABLE STANDARD	9
ANTENNA CONNECTOR CONSTRUCTION	9
FCC§15.315 & §15.207 - CONDUCTED EMISSIONS.....	10
APPLICABLE STANDARD	10
MEASUREMENT UNCERTAINTY.....	10
EUT SETUP.....	10
EMI TEST RECEIVER SETUP.....	11
TEST PROCEDURE	11
TEST EQUIPMENT LIST AND DETAILS.....	11
TEST RESULTS SUMMARY	11
TEST DATA	12
FCC§15.323 (A) - EMISSION BANDWIDTH.....	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST EQUIPMENT LIST AND DETAILS.....	24
TEST DATA	25
FCC§15.319 (C) - PEAK TRANSMIT POWER.....	27
APPLICABLE STANDARD	27
TEST PROCEDURE	27
TEST EQUIPMENT LIST AND DETAILS.....	27
TEST DATA	28
FCC§15.319 (D) - POWER SPECTRAL DENSITY	30
APPLICABLE STANDARD	30
TEST PROCEDURE	30
TEST EQUIPMENT LIST AND DETAILS.....	30
TEST DATA	30

FCC§15.323 (D) - EMISSION INSIDE AND OUTSIDE THE SUB-BAND.....	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST EQUIPMENT LIST AND DETAILS.....	35
TEST DATA	35
FCC§15.319 (G) - RADIATED EMISSIONS.....	45
APPLICABLE STANDARD	45
MEASUREMENT UNCERTAINTY.....	45
EUT SETUP	45
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	46
TEST PROCEDURE	46
TEST EQUIPMENT LIST AND DETAILS.....	46
CORRECTED AMPLITUDE & MARGIN CALCULATION	46
TEST RESULTS SUMMARY	47
TEST DATA	47
FCC§15.323 (F) - FREQUENCY STABILITY.....	54
APPLICABLE STANDARD	54
TEST PROCEDURE	54
TEST EQUIPMENT LIST AND DETAILS.....	54
TEST DATA	55
FCC§15.323 (C) (E) & §15.319(F) – SPECIFIC REQUIREMENTS FOR UPCS DEVICE.....	56
PRODUCT SIMILARITY DECLARATION LETTER.....	61

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The VTech Telecommunications Ltd.'s product, model number: CL83214 (FCC ID: EW780-9454-00) (the "EUT") in this report was a handset unit of DECT 6.0 Cordless Telephone, which was measured approximately: 17.2 cm (L) x 4.2 cm (W) x 2.5 cm (H) for handset 1#, and 19.5 cm (L) x 5.2 cm (W) x 2.5 cm (H) for handset 2#, rated with input voltage: DC 2.4V Ni-MH rechargeable battery pack and DC 6V charging from adapter.

Charger Adapter 1# Information:

Model: UA-0603;

Input: AC 117V, 60Hz, 35mA;

Output: AC 6V, 300mA

Charger Adapter 2# Information:

Model: KU1C-060-0300A;

Input: AC 117V, 60Hz, 50mA;

Output: AC 6V, 300mA

Charger Adapter 3# Information:

Model: U060030A12V;

Input: AC 117V, 60Hz, 50mA;

Output: AC 6V, 300mA

Note: For handset unit of model CL83204, CL83304, CL83404, CL83314, CL83414, CL83XY4, CL80104, CL80114 and CL801Y4 are the same as the handset unit of model CL83214 in electrical designs including software & firmware, PCB layout and construction design/physical design/enclosure. The only differences among these models are model number, LCD, package type, color of enclosure and number of base, handset and charger to be sold for marketing purpose.

The letter "X" indicate any alphanumeric character is presenting number of handset and extra charger, the letter "Y" indicate 0, 5, 7 which present cordless handset with small LCD and different package type or color of enclosure, the letter, the letter "Y" indicate 1, 6, 8 which present cordless handset with big LCD and different package type or color of enclosure; letter "Y" indicate 3 which present cordless handset with big LCD and package with wireless speaker or the letter "Y" indicate 2 which present cordless handset with small LCD and packaged with wireless speaker.

** All measurement and test data in this report was gathered from production sample serial number: 131204003 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2013-12-04.*

Objective

This test report was based on the Electromagnetic Interference (EMI) tests performed on the EUT. The EMI measurements were performed according to the measurement procedure described in ANSI C63.17 - 2006 and ANSI C63.4-2009.

The tests were performed in order to determine the compliance of the EUT with FCC Part 15-Subpart D, section 15.203, 15.315, 15.317, 15.319 and 15.323 rules.

Related Submittal(s)/Grant(s)

FCC part 15D PUB submission of base unit with FCC ID: EW780-9454-00.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.17 - 2006, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz. All radiated and conducted emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen).

The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement uncertainty with radiated emission is 5.91 dB for 30MHz-1GHz and 4.92 dB for above 1GHz, 1.95dB for conducted measurement.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2009.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The system was configured for testing in TBR6 mode which is provided by the manufacturer.

Equipment Modifications

No modification was made to the EUT tested.

Local Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
R&S	Digital Radio-Communication Tester	CMD60	829902/026

External I/O Cable

Cable Description	Length (m)	From/Port	To
DC Power Cable	1.85	EUT	Adapter

Block Diagram of Test Setup

For conducted emissions



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§ 1.1307, §2.1093	RF Exposure (SAR)	Compliance
§ 15.317 § 15.203	Antenna Requirement	Compliance
§ 15.315 § 15.207	Conducted Emission	Compliance
§ 15.323 (a)	Emission Bandwidth	Compliance
§ 15.319 (c)	Peak Transmit Power	Compliance
§ 15.319 (d)	Power Spectral Density	Compliance
§ 15.323 (d)	Emission Inside and Outside the sub-band	Compliance
§ 15.319 (g)	Radiated Emission	Compliance
§ 15.323 (f)	Frequency Stability Handset	Compliance
§ 15.323 (c)(e) § 15.319 (f)	Specific Requirements for UPCS	Compliance

FCC §1.1307 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1307 and §2.1093.

Test Result

Compliance, please refer to the SAR report: R1DG140123004-20.

FCC§15.317&§15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to FCC § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Antenna Connector Construction

The EUT has one PCB antenna arrangement, which was permanently attached and the gain was 0 dBi, fulfill the requirement of this section. Please refer to the internal photos.

Result: Compliant.

FCC§15.315 & §15.207 - CONDUCTED EMISSIONS

Applicable Standard

FCC§15.315, an unlicensed PCS device that is designed to be connected to the public utility (AC) power line must meet the limits specified in §15.207.


Measurement Uncertainty

Input quantities to be considered for conducted disturbance measurements maybe receiver reading, attenuation of the connection between AMN/ISN and receiver, AMN/ISN voltage division factor, AMN/ISN VDF frequency interpolation and receiver related input quantities, etc.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of conducted disturbance test at Bay Area Compliance Laboratories Corp. (Shenzhen) is shown as below. And the uncertainty will not be taken into consideration for the test data recorded in the report

Port	Measurement uncertainty
AC Mains	3.26 dB (k=2, 95% level of confidence)
CAT 3	3.70 dB (k=2, 95% level of confidence)
CAT 5	3.86 dB (k=2, 95% level of confidence)
CAT 6	4.64 dB (k=2, 95% level of confidence)

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.4-2009 measurement procedure. The specification used was with the FCC 15.315 and FCC 15.207 limits.

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All data was recorded in the Quasi-peak and average detection mode.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCS30	100176	2013-06-17	2014-06-17
Rohde & Schwarz	LISN	ENV216	3560.6650.12-101613-Yb	2013-05-07	2014-05-07
Rohde & Schwarz	Transient Limiter	ESH3Z2	DE25985	2013-10-15	2014-10-15
Rohde & Schwarz	CE Test software	EMC 32	V8.53	-	-

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Results Summary

According to the recorded data in following table, with the worst margin reading of:

16.4 dB at 0.490650 MHz in the Neutral conducted mode for 2# handset, adapter 2

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cispr}$$

In BACL, $U_{(Lm)}$ is less than U_{cispr} , if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data**Environmental Conditions**


Temperature:	24 °C
Relative Humidity:	56 %
ATM Pressure:	100.1 kPa

The testing was performed by Gardon Zhang on 2014-02-27.


Test mode: Charging&Transmitting

1# Handset, Charging by Charger Adapter 1**AC 120V/60 Hz, Line**

EMI Auto Test L




Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.253500	38.2	19.5	61.6	23.4	QP
0.253500	32.4	19.5	51.6	19.2	Ave.
0.348750	34.8	19.5	59.0	24.2	QP
0.348750	28.9	19.5	49.0	20.1	Ave.
0.372450	33.3	19.5	58.4	25.1	QP
0.372450	27.9	19.5	48.4	20.5	Ave.
0.396030	32.4	19.5	57.9	25.5	QP
0.396030	28.2	19.5	47.9	19.7	Ave.
0.995030	30.5	19.5	56.0	25.5	QP
0.995030	24.1	19.5	46.0	21.9	Ave.
1.081590	32.3	19.5	56.0	23.7	QP
1.081590	25.5	19.5	46.0	20.5	Ave.

AC 120V/60 Hz, Neutral**EMI Auto Test N**


Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.253500	39.0	19.5	61.6	22.6	QP
0.253500	33.4	19.5	51.6	18.2	Ave.
0.277500	37.0	19.5	60.9	23.9	QP
0.277500	31.3	19.5	50.9	19.6	Ave.
0.305350	35.7	19.5	60.1	24.4	QP
0.305350	30.6	19.5	50.1	19.5	Ave.
0.372450	35.6	19.5	58.4	22.8	QP
0.372450	30.1	19.5	48.4	18.3	Ave.
1.010970	32.2	19.5	56.0	23.8	QP
1.010970	25.0	19.5	46.0	21.0	Ave.
1.069950	33.6	19.5	56.0	22.4	QP
1.069950	27.5	19.5	46.0	18.5	Ave.

1# Handset, Charging by Charger Adapter 2**AC 120V/60 Hz, Line**

EMI Auto Test L




Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.230500	34.3	19.5	62.4	28.1	QP
0.230500	28.8	19.5	52.4	23.6	Ave.
0.249500	36.2	19.5	61.8	25.6	QP
0.249500	30.6	19.5	51.8	21.2	Ave.
0.336930	32.3	19.5	59.3	27.0	QP
0.336930	24.5	19.5	49.3	24.8	Ave.
0.368450	32.4	19.5	58.5	26.1	QP
0.368450	27.3	19.5	48.5	21.2	Ave.
0.514230	29.0	19.6	56.0	27.0	QP
0.514230	23.7	19.6	46.0	22.3	Ave.
1.089590	29.2	19.5	56.0	26.8	QP
1.089590	22.6	19.5	46.0	23.4	Ave.

AC 120V/60 Hz, Neutral**EMI Auto Test N**


Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.301410	37.3	19.5	60.2	22.9	QP
0.301410	31.2	19.5	50.2	19.0	Ave.
0.348750	35.6	19.5	59.0	23.4	QP
0.348750	30.3	19.5	49.0	18.7	Ave.
0.372390	35.8	19.5	58.4	22.6	QP
0.372390	30.4	19.5	48.4	18.0	Ave.
0.419670	34.0	19.6	57.5	23.5	QP
0.419670	29.3	19.6	47.5	18.2	Ave.
0.466950	33.9	19.6	56.6	22.7	QP
0.466950	28.7	19.6	46.6	17.9	Ave.
1.065950	31.9	19.5	56.0	24.1	QP
1.065950	25.7	19.5	46.0	20.3	Ave.

1# Handset, Charging by Charger Adapter 3**AC 120V/60 Hz, Line**

EMI Auto Test L




Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.278501	34.6	19.5	60.9	26.3	QP
0.278501	28.9	19.5	50.9	22.0	Ave.
0.305470	33.4	19.4	60.1	26.7	QP
0.305470	28.3	19.4	50.1	21.8	Ave.
0.368450	34.0	19.5	58.5	24.5	QP
0.368450	27.4	19.5	48.5	21.1	Ave.
0.416150	29.3	19.5	57.5	28.2	QP
0.416150	24.0	19.5	47.5	23.5	Ave.
0.490590	31.3	19.6	56.2	24.9	QP
0.490590	23.1	19.6	46.2	23.1	Ave.
1.018730	30.1	19.5	56.0	25.9	QP
1.018730	23.1	19.5	46.0	22.9	Ave.

AC 120V/60 Hz, Neutral**EMI Auto Test N**


Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.273500	36.2	19.5	61.0	24.8	QP
0.273500	30.6	19.5	51.0	20.4	Ave.
0.344810	35.4	19.5	59.1	23.7	QP
0.344810	28.4	19.5	49.1	20.7	Ave.
0.415670	31.0	19.6	57.5	26.5	QP
0.415670	25.7	19.6	47.5	21.8	Ave.
0.467010	34.0	19.6	56.6	22.6	QP
0.467010	28.5	19.6	46.6	18.1	Ave.
0.975150	28.1	19.5	56.0	27.9	QP
0.975150	21.4	19.5	46.0	24.6	Ave.
1.046430	32.5	19.5	56.0	23.5	QP
1.046430	26.9	19.5	46.0	19.1	Ave.

2# Handset, Charging by Charger Adapter 1**AC 120V/60 Hz, Line**

EMI Auto Test L




Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.2545	35.8	19.5	61.6	25.8	QP
0.2545	30.6	19.5	51.6	21.0	Ave.
0.37555	30.1	19.5	58.4	28.3	QP
0.37555	24.9	19.5	48.4	23.5	Ave.
0.39603	32.1	19.5	57.9	25.8	QP
0.39603	27.7	19.5	47.9	20.2	Ave.
0.99909	28.2	19.5	56	27.8	QP
0.99909	22.2	19.5	46	23.8	Ave.
1.06619	30.3	19.5	56	25.7	QP
1.06619	24.3	19.5	46	21.7	Ave.
1.12905	27.9	19.5	56	28.1	QP
1.12905	20.8	19.5	46	25.2	Ave.

AC 120V/60 Hz, Neutral**EMI Auto Test N**


Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.249500	37.2	19.5	61.8	24.6	QP
0.249500	32.3	19.5	51.8	19.5	Ave.
0.301470	37.0	19.5	60.2	23.2	QP
0.301470	31.1	19.5	50.2	19.1	Ave.
0.466950	33.7	19.6	56.6	22.9	QP
0.466950	28.7	19.6	46.6	17.9	Ave.
1.010730	31.6	19.5	56.0	24.4	QP
1.010730	23.7	19.5	46.0	22.3	Ave.
1.012970	31.4	19.5	56.0	24.6	QP
1.012970	23.9	19.5	46.0	22.1	Ave.
1.109110	30.2	19.5	56.0	25.8	QP
1.109110	23.6	19.5	46.0	22.4	Ave.

2# Handset, Charging by Charger Adapter 2**AC 120V/60 Hz, Line**

EMI Auto Test L




Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.253500	37.7	19.5	61.6	23.9	QP
0.253500	31.9	19.5	51.6	19.7	Ave.
0.326830	33.1	19.5	59.5	26.4	QP
0.326830	28.0	19.5	49.5	21.5	Ave.
0.396030	33.4	19.5	57.9	24.5	QP
0.396030	29.2	19.5	47.9	18.7	Ave.
0.983090	28.6	19.5	56.0	27.4	QP
0.983090	21.0	19.5	46.0	25.0	Ave.
1.073950	31.4	19.5	56.0	24.6	QP
1.073950	25.2	19.5	46.0	20.8	Ave.
19.634850	10.8	19.9	60.0	49.2	QP
19.634850	6.3	19.9	50.0	43.7	Ave.

AC 120V/60 Hz, Neutral**EMI Auto Test N**


Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.249500	38.7	19.5	61.8	23.1	QP
0.249500	33.1	19.5	51.8	18.7	Ave.
0.301500	37.2	19.5	60.2	23.0	QP
0.301500	31.7	19.5	50.2	18.5	Ave.
0.368390	35.7	19.5	58.5	22.8	QP
0.368390	30.1	19.5	48.5	18.4	Ave.
0.471010	33.2	19.6	56.5	23.3	QP
0.471010	28.1	19.6	46.5	18.4	Ave.
0.490650	34.8	19.7	56.2	21.4	QP
0.490650	29.8	19.7	46.2	16.4	Ave.
1.066010	33.2	19.5	56.0	22.8	QP
1.066010	26.8	19.5	46.0	19.2	Ave.

2# Handset, Charging by Charger Adapter 3**AC 120V/60 Hz, Line**

EMI Auto Test L



Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.348750	35.7	19.5	59.0	23.3	QP
0.348750	28.9	19.5	49.0	20.1	Ave.
0.395850	34.0	19.5	57.9	23.9	QP
0.395850	29.5	19.5	47.9	18.4	Ave.
0.490650	32.5	19.6	56.2	23.7	QP
0.490650	27.2	19.6	46.2	19.0	Ave.
1.057630	31.5	19.5	56.0	24.5	QP
1.057630	24.6	19.5	46.0	21.4	Ave.
7.705570	10.8	19.7	60.0	49.2	QP
7.705570	6.3	19.7	50.0	43.7	Ave.
7.729390	10.7	19.7	60.0	49.3	QP
7.729390	6.4	19.7	50.0	43.6	Ave.

AC 120V/60 Hz, Neutral**EMI Auto Test N**

Frequency (MHz)	Corrected Amplitude (dBμV)	Corrected Factor (dB)	Limit (dBμV)	Margin (dB)	Remark (PK/QP/Ave)
0.273500	37.3	19.5	61.0	23.7	QP
0.273500	32.1	19.5	51.0	18.9	Ave.
0.347130	37.4	19.5	59.0	21.6	QP
0.347130	30.7	19.5	49.0	18.3	Ave.
0.391790	32.9	19.6	58.0	25.1	QP
0.391790	27.9	19.6	48.0	20.1	Ave.
0.396030	35.5	19.6	57.9	22.4	QP
0.396030	31.2	19.6	47.9	16.7	Ave.
0.494590	34.0	19.7	56.1	22.1	QP
0.494590	28.8	19.7	46.1	17.3	Ave.
1.026550	31.0	19.5	56.0	25.0	QP
1.026550	24.2	19.5	46.0	21.8	Ave.

Note:


- 1) Correction Factor = LISN VDF (Voltage Division Factor) + Cable Loss + Transient Limiter Attenuation
The corrected factor has been input into the transducer of the test software.
- 2) Corrected Amplitude = Reading + Correction Factor
- 3) Margin = Limit – Corrected Amplitude

FCC§15.323 (a) - EMISSION BANDWIDTH

Applicable Standard

Operation shall be contained within the 1920–1930 MHz band. The emission bandwidth shall be less than 2.5 MHz and greater than 50 kHz.

The emission bandwidth is measured in accordance with ANSI C63.17 sub-clause 6.1.3 using the setup below:



The width, in Hz, of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, that is 26 dB down relative to the maximum level of the modulated carrier. It is based on the use of measurement instrumentation employing a peak detector function with an instrument resolution bandwidth approximately equal to 1% of the emission band-width of the device under measurement. [Extraction from 47 CFR 15, subpart D, 15.303 (C)].

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

Resolution bandwidth	1.0% of the emission bandwidth (as close as possible)
Video bandwidth	>3 times the resolution bandwidth
Number of sweeps	sufficient to stability the trace
Detection mode	peak detection with maximum hold

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-25	2014-09-25

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**


Temperature:	19 °C
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa

The testing was performed by Gardon Zhang on 2014-02-07.

Test mode: Transmitting

Channel	Center Frequency (MHz)	26 dB Emission Bandwidth (MHz)	Limit
Low	1921.536	1.296	50 kHz < EBW < 2.5 MHz
Middle	1924.992	1.296	50 kHz < EBW < 2.5 MHz
High	1928.448	1.296	50 kHz < EBW < 2.5 MHz


Test Result: Compliance. Please refer to the attached plots.

Low Channel

Comment ...

Date: 7.FEB.2014 14:34:04


Middle Channel



Comment ...

Date: 7.FEB.2014 14:31:02

High Channel



Comment ...

Date: 7.FEB.2014 14:17:13

FCC§15.319 (c) - PEAK TRANSMIT POWER

Applicable Standard

The peak power output as measured over an interval of time equal to the frame rate or transmission burst of the device under all conditions of modulation. Usually this parameter is measured as a conducted emission by direct connection of a calibrated test instrument to the equipment under test. If the device cannot be connected directly, alternative techniques acceptable to the Commission may be used [47 CFR 15, subpart D, 15.303].

The peak transmit power is according to ANSI C63.17-2006 §6.1.2

Per FCC Part15.319 (c) Peak transmit power shall not exceed 100 microwatts multiplied by the square root of the emission bandwidth in hertz. Peak transmit power must be measured over any interval of continuous transmission using instrumentation calibrated in terms of an rms-equivalent voltage. The measurement results shall be properly adjusted for any instrument limitations, such as detector response times, limited resolution bandwidth capability when compared to the emission bandwidth, sensitivity, etc., so as to obtain a true peak measurement for the emission in question over the full bandwidth of the channel.

Calculation of Peak Transmit Power Limit:

$$\text{Peak Transmit Power Limit} = 100\mu\text{W} \times (\text{EBW})^{1/2}$$

EBW is the transmit emission bandwidth in Hz determined in the other test item:

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	≥ Emission bandwidth
Video bandwidth	≥ RBW
Span	Zero
Center frequency	Nominal center frequency of channels
Amplitude scale	Log (linear may be used if analyzer has sufficient linear dynamic range and accuracy)
Detection	Peak detection
Trigger	Video
Sweep rate	Sufficiently rapid to permit the transmit pulse to be resolved accurately

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-25	2014-09-25

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	19 °C
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa


The testing was performed by Gardon Zhang on 2014-02-07.

Test Result: Compliance. Please refer to the following plots.

Channel	Frequency (MHz)	Peak Transmit Power (dBm)	Limit (dBm)
Low	1921.536	20.33	20.56
Middle	1924.992	20.35	20.56
High	1928.448	20.38	20.56

EBW_{Low channel} = 1296000 Hz, EBW_{Middle channel} = 1296000 Hz, EBW_{High channel} = 1296000 Hz
 Peak Transmit Power Limit = $100(\text{EBW})^{1/2} \mu\text{W}$


Low Channel



Comment ...

Date: 7.FEB.2014 14:11:25


Middle Channel



Comment ...

Date: 7.FEB.2014 14:13:06

High Channel



Comment ...

Date: 7.FEB.2014 14:13:42

FCC§15.319 (d) - POWER SPECTRAL DENSITY

Applicable Standard

The average pulse energy in a 3 kHz bandwidth is divided by the pulse duration.

The power spectral density shall not exceed 3mW in any 3 kHz bandwidth as measured with a spectrum analyzer having a resolution bandwidth of 3 kHz.

The power spectral density is measured in accordance with ANSI C63.17.2006 Clause 6.1.5.

Test Procedure

Using the manufacturer's information on occupied bandwidth set the spectrum analyzer as follows:

RBW	3 kHz
Video bandwidth	$\geq 3 \times \text{RBW}$
Span	Zero span at frequency with the maximum level (frequency determined in 6.1.3 if the same type of signal (continuous versus burst) was used in 6.1.3)
Center frequency	Spectral peak as determined in 6.1.3
Sweep time	For burst signals, sufficient to include essentially all of the maximum length burst at the output of a 3 kHz filter (e.g., maximum input burst duration plus 600 μs). For continuous signals, 20 ms.
Amplitude scale	Log power
Detection	Sample detection and averaged for a minimum of 100 sweeps
Trigger	External or internal

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-25	2014-09-25

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	19 °C
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa


The testing was performed by Gardon Zhang on 2014-02-07.

Test mode: Transmitting

Test Result: Compliance. Please refer to following tables and plots


Channel	Frequency (MHz)	Power Spectral Density		Limit (mW/3kHz)	Result
		(dBm/3kHz)	(mW/3kHz)		
Low	1921.536	-6.53	0.2223	3	Pass
Middle	1924.992	-6.54	0.2218	3	Pass
High	1928.448	-6.58	0.2198	3	Pass

Low Channel



Comment ...


Date: 7.FEB.2014 14:44:14



Comment ...


Date: 7.FEB.2014 14:46:56

Middle Channel



Comment ...


Date: 7.FEB.2014 14:52:31



Comment ...


Date: 7.FEB.2014 14:54:02

High Channel



Comment ...

Date: 7.FEB.2014 14:59:02



Comment ...

Date: 7.FEB.2014 15:00:33

FCC§15.323 (d) - EMISSION INSIDE AND OUTSIDE THE SUB-BAND

Applicable Standard

Emissions inside the sub-band must comply with the following emission mask:

1. In the bands between 1B and 2B measured from the center of the emission bandwidth the total power emitted by the device shall be at least 30 dB below the transmit power permitted for that device;
2. in the bands between 2B and 3B measured from the center of the emission bandwidth the total power emitted by an intentional radiator shall be at least 50 dB below the transmit power permitted for that radiator;
3. in the bands between 3B and the sub-band edge the total power emitted by an intentional radiator in the measurement bandwidth shall be at least 60 dB below the transmit power permitted for that radiator.

Where B = emission bandwidth

Emission Outside the sub-band shall be attenuated below a reference power of 112 mW (20.5 dBm) as follows:

1. 30 dB between the sub-band and 1.25 MHz above or below the sub-band;
2. 50 dB between 1.25 and 2.5 MHz above or below the sub-band;
3. 60 dB at 2.5 MHz or greater above or below the sub-band.

Test Procedure

According to ANSI C63.17.2006 Clause 6.1.6.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data



Environmental Conditions



Temperature:	20 °C
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa



The testing was performed by Gardon Zhang on 2014-02-11.



Test mode: Transmitting

Test Result: Compliance. Please refer to following plots



Low Channel (Unwanted Emission inside the Sub-band)**Middle Channel (Unwanted Emission inside the Sub-band)**



High Channel (Unwanted Emission inside the Sub-band)**Low Channel (Unwanted Emission outside the Sub-band)**







Middle Channel (Unwanted Emission outside the Sub-band)











High Channel (Unwanted Emission outside the Sub-band)







FCC§15.319 (g) - RADIATED EMISSIONS

Applicable Standard


According to FCC§15.319(g), notwithstanding other technical requirements specified in this subpart, attenuation of emissions below the general emission limits in §15.209 is not required.

Measurement Uncertainty

All measurements involve certain levels of uncertainties, especially in field of EMC. The factors contributing to uncertainties are spectrum analyzer, cable loss, antenna factor calibration, antenna directivity, antenna factor variation with height, antenna phase center variation, antenna factor frequency interpolation, measurement distance variation, site imperfections, mismatch (average), and system repeatability.

Based on CISPR 16-4-2:2011, the expended combined standard uncertainty of radiation emissions at Bay Area Compliance Laboratories Corp. (Shenzhen) will not be taken into consideration for the test data recorded in the report

EUT Setup



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.17 - 2006. The specification used was the FCC 15§ 15.319(g).

The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.

The adapter was connected to a 120 VAC/60 Hz power source.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 20 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Detector
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1 MHz	3 MHz	/	PK
	1 MHz	10 Hz	/	Ave.

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz and peak and Average detection modes for frequencies above 1 GHz.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
HP	Amplifier	HP8447E	1937A01046	2013-09-30	2014-09-30
Rohde & Schwarz	EMI Test Receiver	ESCI	101122	2013-09-25	2014-09-25
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2014-11-27
SUPER ULTRA	Amplifier	ZVA-183-S+	5969001149	2013-04-03	2014-04-03
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2014-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2013-11-12	2014-11-12
the electro-Mechanics Co.	Horn Antenna	3116	9510-2270	2013-10-14	2016-10-13
DUCOMMUN	Pre-amplifier	ALN-22093530-01	991373-01	2013-08-03	2014-08-03

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the maximum limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Results Summary

According to the recorded data in following table, with the worst margin reading of:

8.79 dB at 5785.3 MHz in the Horizontal polarization

Refer to CISPR16-4-2:2011 and CISPR 16-4-1:2009, the measured level is in compliance with the limit if

$$L_m + U_{(Lm)} \leq L_{lim} + U_{cisp\text{r}}$$

In BACL, $U_{(Lm)}$ is less than $U_{cisp\text{r}}$, if L_m is less than L_{lim} , it implies that the EUT complies with the limit.

Test Data

Environmental Conditions

Temperature:	19 °C
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa

*The testing was performed by Gardon Zhang on 2014-02-07.

Test mode: Transmitting

30 MHz ~ 20 GHz:

For 1# Handset

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.319(g)/209/205	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (1921.536 MHz)									
518.5	40.7	QP	228	2.1	V	-9.5	31.2	46	14.8
1921.5	99.71	PK	132	1.6	H	2.63	102.34	/	/
1921.5	104.13	PK	125	1.5	V	2.63	106.76	/	/
3843.1	52.31	PK	293	1.6	H	9.70	62.01	74	11.99
3843.1	52.83	PK	201	2.2	V	9.70	62.53	74	11.47
5764.6	51.22	PK	50	2.3	H	13.51	64.73	74	9.27
5764.6	48.20	PK	77	1.3	V	13.51	61.71	74	12.29
7686.1	40.31	PK	107	1.7	H	16.01	56.32	74	17.68
7686.1	41.89	PK	129	2.4	V	16.01	57.90	74	16.10

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.319(g)/209/205	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Middle Channel (1924.992 MHz)									
518.5	40.90	QP	230	2.1	V	-9.50	31.40	46	14.60
1925.0	98.22	PK	207	1.9	H	2.63	100.85	/	/
1925.0	105.05	PK	72	1.2	V	2.63	107.68	/	/
3850.0	52.58	PK	267	2.5	H	9.70	62.28	74	11.72
3850.0	52.76	PK	351	1.9	V	9.70	62.46	74	11.54
5775.0	51.13	PK	147	1.0	H	13.51	64.64	74	9.36
5775.0	48.27	PK	117	1.7	V	13.51	61.78	74	12.22
7700.0	41.12	PK	238	2.3	H	16.47	57.59	74	16.41
7700.0	39.62	PK	312	1.1	V	16.47	56.09	74	17.91
High Channel (1928.448 MHz)									
518.5	40.40	QP	228	2.1	V	-9.50	30.90	46	15.10
1928.4	99.27	PK	329	1.1	H	2.63	101.90	/	/
1928.4	105.23	PK	220	2.1	V	2.63	107.86	/	/
3856.9	52.25	PK	166	1.4	H	9.70	61.95	74	12.05
3856.9	53.54	PK	193	1.6	V	9.70	63.24	74	10.76
5785.3	51.34	PK	332	2.2	H	13.87	65.21	74	8.79
5785.3	48.35	PK	150	1.8	V	13.87	62.22	74	11.78
7713.8	40.44	PK	287	2.2	H	16.47	56.91	74	17.09
7713.8	40.99	PK	19	2.1	V	16.47	57.46	74	16.54

Field Strength of Radiated Emission Average							
Freq. (MHz)	Peak Corrected Amplitude. @3m (dBμV/m)	Polar (H/V)	Duty Cycle Factor (dB)	Corrected Amplitude. (dBμV/m)	FCC 15.319/15.205/15.209		Comment
					Limit (dBμV/m)	Margin	
Low Channel (1921.536 MHz)							
3843.1	62.01	H	-27.76	34.25	54	19.75	Harmonic
3843.1	62.53	V	-27.76	34.77	54	19.23	Harmonic
5764.6	64.73	H	-27.76	36.97	54	17.03	Harmonic
5764.6	61.71	V	-27.76	33.95	54	20.05	Harmonic
7686.1	56.32	H	-27.76	28.56	54	25.44	Harmonic
7686.1	57.90	V	-27.76	30.14	54	23.86	Harmonic
Middle Channel (1924.992 MHz)							
3850.0	62.28	H	-27.76	34.52	54	19.48	Harmonic
3850.0	62.46	V	-27.76	34.70	54	19.30	Harmonic
5775.0	64.64	H	-27.76	36.88	54	17.12	Harmonic
5775.0	61.78	V	-27.76	34.02	54	19.98	Harmonic
7700.0	57.59	H	-27.76	29.83	54	24.17	Harmonic
7700.0	56.09	V	-27.76	28.33	54	25.67	Harmonic
High Channel (1928.448 MHz)							
3856.9	61.95	H	-27.76	34.19	54	19.81	Harmonic
3856.9	63.24	V	-27.76	35.48	54	18.52	Harmonic
5785.3	65.21	H	-27.76	37.45	54	16.55	Harmonic
5785.3	62.22	V	-27.76	34.46	54	19.54	Harmonic
7713.8	56.91	H	-27.76	29.15	54	24.85	Harmonic
7713.8	57.46	V	-27.76	29.70	54	24.30	Harmonic

For 2# Handset

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB)	Corrected Amplitude (dBμV/m)	FCC Part 15.319(g)/209/205	
	Reading (dBμV)	Detector (PK/QP/Ave.)		Height (m)	Polar (H/V)			Limit (dBμV/m)	Margin (dB)
Low Channel (1921.536 MHz)									
518.5	40.20	QP	213	2.0	V	-9.50	30.70	46	15.30
1921.5	97.89	PK	128	1.5	H	2.63	100.52	/	/
1921.5	102.63	PK	120	1.5	V	2.63	105.26	/	/
3843.1	51.08	PK	285	1.7	H	9.70	60.78	74	13.22
3843.1	51.56	PK	186	2.1	V	9.70	61.26	74	12.74
5764.6	49.23	PK	56	2.1	H	13.51	62.74	74	11.26
5764.6	47.48	PK	80	1.3	V	13.51	60.99	74	13.01
7686.1	41.26	PK	102	1.6	H	16.01	57.27	74	16.73
7686.1	42.47	PK	124	2.0	V	16.01	58.48	74	15.52
Middle Channel (1924.992 MHz)									
518.5	40.50	QP	216	2.0	V	-9.50	31.00	46	15.00
1925.0	97.21	PK	208	1.6	H	2.63	99.84	/	/
1925.0	103.18	PK	69	1.5	V	2.63	105.81	/	/
3850.0	50.28	PK	260	1.8	H	9.70	59.98	74	14.02
3850.0	50.54	PK	345	2.0	V	9.70	60.24	74	13.76
5775.0	49.28	PK	142	1.8	H	13.51	62.79	74	11.21
5775.0	48.14	PK	110	1.4	V	13.51	61.65	74	12.35
7700.0	41.69	PK	232	1.7	H	16.47	58.16	74	15.84
7700.0	40.36	PK	304	1.9	V	16.47	56.83	74	17.17
High Channel (1928.448 MHz)									
518.5	40.00	QP	215	2.0	V	-9.50	30.50	46	15.50
1928.4	98.49	PK	314	1.5	H	2.63	101.12	/	/
1928.4	102.58	PK	209	1.7	V	2.63	105.21	/	/
3856.9	51.58	PK	160	1.4	H	9.70	61.28	74	12.72
3856.9	52.07	PK	200	1.6	V	9.70	61.77	74	12.23
5785.3	50.37	PK	327	2.1	H	13.87	64.24	74	9.76
5785.3	49.17	PK	156	1.8	V	13.87	63.04	74	10.96
7713.8	41.45	PK	243	2.0	H	16.47	57.92	74	16.08
7713.8	41.70	PK	32	1.9	V	16.47	58.17	74	15.83

Field Strength of Radiated Emission Average							
Freq. (MHz)	Peak Corrected Amplitude. @3m (dBμV/m)	Polar (H/V)	Duty Cycle Factor (dB)	Corrected Amplitude. (dBμV/m)	FCC 15.319/15.205/15.209		Comment
					Limit (dBμV/m)	Margin	
Low Channel (1921.536 MHz)							
3843.1	60.78	H	-27.76	33.02	54	20.98	Harmonic
3843.1	61.26	V	-27.76	33.50	54	20.50	Harmonic
5764.6	62.74	H	-27.76	34.98	54	19.02	Harmonic
5764.6	60.99	V	-27.76	33.23	54	20.77	Harmonic
7686.1	57.27	H	-27.76	29.51	54	24.49	Harmonic
7686.1	58.48	V	-27.76	30.72	54	23.28	Harmonic
Middle Channel (1924.992 MHz)							
3850.0	59.98	H	-27.76	32.22	54	21.78	Harmonic
3850.0	60.24	V	-27.76	32.48	54	21.52	Harmonic
5775.0	62.79	H	-27.76	35.03	54	18.97	Harmonic
5775.0	61.65	V	-27.76	33.89	54	20.11	Harmonic
7700.0	58.16	H	-27.76	30.40	54	23.60	Harmonic
7700.0	56.83	V	-27.76	29.07	54	24.93	Harmonic
High Channel (1928.448 MHz)							
3856.9	61.28	H	-27.76	33.52	54	20.48	Harmonic
3856.9	61.77	V	-27.76	34.01	54	19.99	Harmonic
5785.3	64.24	H	-27.76	36.48	54	17.52	Harmonic
5785.3	63.04	V	-27.76	35.28	54	18.72	Harmonic
7713.8	57.92	H	-27.76	30.16	54	23.84	Harmonic
7713.8	58.17	V	-27.76	30.41	54	23.59	Harmonic

Note:

Corrected Amplitude = Corrected Factor + Reading

Corrected Factor = Antenna factor (Rx) + cable loss – amplifier factor


Margin = Limit - Corr. Amplitude

Duty Cycle = Ton/Tp*100%, Ton = 410.60 μs, Tp = 10.0320 ms

Duty Cycle Factor = 20lg (Duty Cycle) = -27.76

Average = PK + Duty Cycle Factor


T_{on}



Comment ...

Date: 7.FEB.2014 15:09:51


T_p



Comment ...

Date: 7.FEB.2014 15:07:40

Duty Cycle (100ms)



Comment ...
Date: 7.FEB.2014 15:06:26

FCC§15.323 (f) - FREQUENCY STABILITY

Applicable Standard

Per §15.323(f), the frequency stability of the carrier frequency of the intentional radiator shall be maintained within ± 10 ppm over 1 hour or the interval between channel access monitoring, whichever is shorter. The frequency stability shall be maintained over a temperature variation of -20°C to $+50^{\circ}\text{C}$ at normal supply voltage, and over a variation in the primary supply voltage of 85 percent to 115 percent of the rated supply voltage at a temperature of 20°C . For equipment that is capable only of operating from a battery, the frequency stability tests shall be performed using a new battery without any further requirement to vary supply voltage

Test Procedure

This procedure should be carried out for each of the following test cases:

Temperature	Supply Voltage
20°C	85-115% or new batteries
-20°C	Normal
$+50^{\circ}\text{C}$	Normal

^a Use the lowest temperature at which the EUT is specified to operate if it is above -20°C .

During test, the equipment shall be placed in the boxes and set the temperature to the specified requirement until the thermal balance has been reached.

Using the mean carrier frequency at 20°C and at nominal supply voltage as the reference, the mean carrier frequency shall be maintained within ± 10 ppm at the two extreme temperatures (or as declared by the manufacturer) and at normal temperature (typically 20°C) at the two extreme supply voltages. This test does not apply to a EUT that is capable only of operating from a battery.

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2013-11-01	2014-11-01
Rohde & Schwarz	Signal Analyzer	FSIQ26	837405/023	2013-05-31	2014-05-31

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	19 °C
Relative Humidity:	55 %
ATM Pressure:	100.1 kPa

The testing was performed by Gardon Zhang on 2014-02-08.

Test mode: Transmitting

Test Result: Compliance.

Temperature (°C)	Voltage (V_{DC})	Channel Frequency (MHz)	Measured Frequency Offset (kHz)	Measured Frequency Offset (ppm)	Limit (ppm)
-20	2.40	1924.992	1.9	0.987	±10
20	2.40	1924.992	1.6	0.831	±10
50	2.40	1924.992	1.8	0.935	±10

FCC§15.323 (c) (e) & §15.319(f) – SPECIFIC REQUIREMENTS FOR UPCS DEVICE

Automatic Discontinuation of Transmission, FCC Part 15.319(f)

The device shall automatically discontinue transmission in case of either absence of information to transmit or operational failure. The provisions in this section are not intended to preclude transmission of control and signaling information or use of repetitive codes used by certain digital technologies to complete frame or burst intervals.

Test Procedure:

According to ANSI C63.17 Annex A

Test result:

Meet the requirement; please refer to the declaration provided by manufacturer.

Monitoring Time FCC Part 15.323 (c)(1)

Immediately prior to initiating transmission, devices must monitor the combined time and spectrum window in which they intend to transmit. For a period of at least 10 milliseconds for systems designed to use a 10 milliseconds or shorter frame period or at least 20 milliseconds for systems designed to use a 20 milliseconds frame period

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 7.3.4.

Test result:

EUT monitors the combined time and spectrum window prior to initiation of transmission. Test result is following

Interference (Refer to ANSI C63.17 clause 7.3.4)	Reaction of EUT	Results
1) Apply the interference on f_1 at level $T_U + U_M$, and no interference on f_2 . Initiate transmission and verify the transmission on f_2 .	EUT transmits on f_2	Pass
2) Apply the interference on f_2 at level $T_U + U_M$, at the same time, no interference on f_1 . After about 20ms, initiate transmission and verify the transmission on f_1 .	EUT transmits on f_1	Pass

Lower Monitoring Threshold Part 15.323 (c)(2)

The monitoring threshold must not be more than 30 dB above the thermal noise power for a bandwidth equivalent to the emission bandwidth used by the device.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 7.3.1

Test result: Not Apply

Note: For the EUT which support LIC there is no need to measure lower threshold because it is automatically met by LIC procedure.

Maximum Transmit Period FCC Part 15.323 (c)(3)

If no signal above the threshold level is detected, transmission may commence and continue with the same emission bandwidth in the monitored time and spectrum windows without further monitoring. However, occupation of the same combined time and spectrum windows by a device or group of cooperating devices continuously over a period of time longer than 8 hours is not permitted without repeating the access criteria.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 8.2.2

Test result:

Repetition of Access Criteria	Measured Maximum Transmission Time (Second)	Limit (Second)	Results
First	17500	28,800	Pass
Second	17500	28,800	Pass

System Acknowledgement, FCC Part 15.323 (c) (4)

Once access to specific combined time and spectrum windows is obtained an acknowledgment from a system participant must be received by the initiating transmitter within one second or transmission must cease. Periodic acknowledgments must be received at least every 30 seconds or transmission must cease. Channels used exclusively for control and signaling information may transmit continuously for 30 seconds without receiving an acknowledgment, at which time the access criteria must be repeated.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 8.1.1, 8.2.1

Test result:

Test	Time taken(second)	Limit (second)	Result
Connection acknowledgement	0.11	1	Pass
Change of access criteria for control information	N/A	30	Pass
Transmission cease time	4.36	30	Pass
Pulse length	0.00041	0.01	Pass

Note: N/A=Not Applicable

Least Interfered Channel (LIC) Selection, FCC Part 15.323 (c) (5)

If access to spectrum is not available as determined by the above, and a minimum of 40 duplex system access channels are defined for the system, the time and spectrum windows with the lowest power level below a monitoring threshold of 50 dB above the thermal noise power determined for the emission bandwidth may be accessed.

Calculation of monitoring threshold limits for isochroous devices:

Lower threshold: $T_L = -174 + 10\log_{10}B + M_u + P_{MAX} - P_{EUT}$ (dBm)

Upper threshold: $T_U = -174 + 10\log_{10}B + M_u + P_{MAX} - P_{EUT}$ (dBm)

Where: B=Emission bandwidth (Hz)

M_u =dB the threshold may exceed thermal noise (30 for T_L & 50 for T_U)

$P_{MAX} = 5\log_{10}B - 10$ (dBm)

P_{EUT} =Transmitted power (dBm)

Calculated thresholds:

Monitor Threshold	B(MHz)	M_u (dB)	P_{MAX} (dBm)	P_{EUT} (dBm)	Threshold (dBm)
T_L	1.296	30	20.56	20.35	-82.66
T_U	1.296	50	20.56	20.35	-62.66

Limit:

Limit (dBm)
$T_{LR} < T_L + U_M = -82.66 + 6 = -76.66$
$T_{UR} < T_U + U_M = -62.66 + 6 = -56.66$

Note: According to 47CFR 15.323(c) (5), the power measurement resolution for this comparison must be accurate to within 6 dB, the limit should be "Threshold+6(dB)"

Test procedure:

Measurement method according to ANSI C63.17 clause 7.3.2, 7.3.3, 7.3.4

Test result:

Monitor threshold	Measured Threshold Level	Limit (dBm)
Lower Threshold(dBm)	N/A	-76.66
Upper Threshold(dBm)	-61.18	-56.66

Note: The upper threshold is applicable as the EUT utilizes more than 40 duplex system channels.

Random waiting FCC 15.323(c)(6)

If the selected combined time and spectrum windows are unavailable, the device may either monitor and select different windows or seek to use the same window after waiting an amount of time, randomly chosen from a uniform random distribution between 10 and 150 milliseconds, commencing when the channel becomes available.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 8.1.3

Test result:

The manufacturer declares that this provision is not utilized by the EUT.

Monitoring Bandwidth, FCC Part 15.323 (c) (7)

The monitoring system bandwidth must be equal to or greater than the emission bandwidth of the intended transmission and have a maximum reaction time less than $50 \times \text{SQRT}(1.25/\text{emission bandwidth in MHz})$ microseconds for signals at the applicable threshold level but shall not be required to be less than 50 microseconds

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 7.5

Test result:

Test Equation (μs)	B(bandwidth)(MHz)	Pulse width(μs)	Limit(μs)	Result
$50 (1.25/B)^{1/2}$	1.296	49.10	50	Pass
$35 (1.25/B)^{1/2}$	1.296	34.37	35	Pass

Monitoring Antenna, FCC Part 15.323 (c) (8)

The monitoring system shall use the same antenna used for transmission, or an antenna that yields equivalent reception at that location.

Test procedure:

Measurement method according to ANSI C63.17 2006 paragraph 4.

Test result:

The antenna of the EUT used for transmission is the same interior antenna that used for monitoring.

Monitoring threshold relation FCC Part 15.323(c)(9)

Devices that have a power output lower than the maximum permitted under the rules can increase their monitoring detection threshold by one decibel for each one decibel that the transmitter power is below the maximum permitted.

Test procedure:

Measurement method according to ANSI C63.17 2006 paragraph 4.

Test result:

Not apply based on 15.323 (c)(5)

Duplex Connections, FCC Part 15.323 (c) (10)

An initiating device may attempt to establish a duplex connection by monitors both its intended transmit and receive time and spectrum windows. If both the intended transmit and receive time and spectrum windows meet the access criteria, then the initiating device can initiate a transmission in the intended transmit time and spectrum window. If the power detected by the responding device can be decoded as a duplex connection signal from the initiating device, then the responding device may immediately begin transmitting on the receive time and spectrum window monitored by the initiating device.

Test procedure:

Measurement method according to ANSI C63.17 clause 8.3

Test result:

The manufacturer declares that this provision is not utilized by the EUT.

Alternative monitoring interval for co-located devices, FCC Part 15.323 (c) (11)

An initiating device that is prevented from monitoring during its intended transmit window due to monitoring system blocking from the transmissions of a co-located (within one meter) transmitter of the same system, may monitor the portions of the time and spectrum windows in which they intend to receive over a period of at least 10 milliseconds. The monitored time and spectrum window must total at least 50 percent of the 10 millisecond frame interval and the monitored spectrum must be within 1.25 MHz of the center frequency of channel(s) already occupied by that device or co-located co-operating devices. If the access criteria is met for the intended receive time and spectrum window under the above conditions, then transmission in the intended transmit window by the initiating device may commence.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 8.4

Test result:

The manufacturer declares that this provision is not utilized by the EUT.

Fair Access, FCC Part 15.323 (c)(12)

The provisions of FCC Part 15.323(c)(10) or (c)(11) shall not be used to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other devices.

Test result:

The manufacturer declares that this device does not use any mechanisms as provided by Part 15.323 (c) (10) or (c) (11) to extend the range of spectrum occupied over space or time for the purpose of denying fair access to spectrum to other device.

Frame Repetition Stability, Part 15.323 (e)

The frame period (a set of consecutive time slots in which the position of each time slot can be identified by reference to a synchronizing source) of an intentional radiator operating in these sub-bands shall be 20 milliseconds or 10 milliseconds/X where X is a positive whole number.

Test procedure:

Measurement method according to ANSI C63.17 2006 clause 6.2.2, 6.2.3

Test result:

Frame Repetition Stability:

Frame Repetition Stability (ppm)	Limit (ppm)	Result (Pass/Fail)
0.58	10	Pass

Frame Period and Jitter:

Max. pos. Jitter (μs)	Max. neg. Jitter (μs)	Frame period (ms)	Limit	
			Frame Period (ms)	Jitter (μs)
0.00	-0.01	10.00	20 or 10/X	0.24

Note: X is a positive whole number.

PRODUCT SIMILARITY DECLARATION LETTER

VTech Telecommunications Ltd

23/F, Tai Ping Industrial Centre, Block 1, 57 Ting Kok Road, Tai Po, Hong Kong.
Tel: 26805398 Fax: 26805252

DECLARATION OF SIMILARITY

Date: January 23, 2014

Dear Sir or Madam:

We, **VTech Telecommunications Ltd.** hereby declare that product: **DECT 6.0 Cordless Telephone**, Models: **CL83304, CL83404, CL83314, CL83414, CL83XY4; CL80104, CL80114, CL801Y4** are electrically identical with the models: **CL83204, CL83214** which were tested by BACL.

Descriptions of the differences among these models and those that are declared similar are as follows:

model	quantity of Base Station	quantity of Cordless Handset	quantity of Charger
CL83204	1	2	1
CL83304	1	3	2
CL83404	1	4	3
CL83214	1	2	1
CL83314	1	3	2
CL83414	1	4	3
CL83XY4	1	X	X-1
CL80104	--	1	1
CL80114	--	1	1
CL801Y4	--	1	1

What's more, they have the different model name, enclosure color and package type or material & no. of Handset and extra Charger. The detail information, please check the reports user manual.

Remark:

X=any alphanumeric character is presenting no. of Handset and extra Charger.

Y=Number (0, 5, 7) is presenting Cordless Handset with small LCD and different package type or color of enclosure;

Y= Number (1, 6, 8) is presenting Cordless Handset with big LCD and different package type color of enclosure;

Y= Number (3) is presenting Cordless Handset with big LCD and package with Wireless Speaker;

Y=Number (2) is presenting Cordless Handset with small LCD and packaged with Wireless Speaker.

Please contact me should there be need for any additional clarification or information.

Best Regards,

Michael Tsui
Approbation Supervisor

******* END OF REPORT *******