

**FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)**

**Applicable Standard**

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f <sup>2</sup> )	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

\* = Plane-wave equivalent power density

**Result**

**Calculated Formulary:**

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For simultaneously transmit system, the calculated power density should comply with:

$$\sum_i \frac{S_i}{S_{Limit,i}} \leq 1$$

Frequency (MHz)	Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm <sup>2</sup> )	MPE Limit (mW/cm <sup>2</sup> )
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2462	1	1.26	19.0	79.43	20	0.02	1
5150-5250	2	1.58	13.0	19.95	20	0.006	1
5250-5350	2	1.58	13.0	19.95	20	0.006	1
5470-5725	2	1.58	13.0	19.95	20	0.006	1
5725-5850	2	1.58	15.0	31.62	20	0.010	1
1921.536 - 1928.448	0	1.0	20	100	20	0.02	1

- Note: 1. The tune up conducted power was declared by the applicant  
 2. The 2.4G Wi-Fi can't transmit at the same time with the 5G Wi-Fi.  
 3. The 2.4G Wi-Fi or 5G Wi-Fi can transmit with DECT function at the same time.

Simultaneous transmitting consideration (worst case):

The ratio= $MPE_{2.4G\ Wi-Fi}/limit + MPE_{DECT}/limit = 0.02 + 0.02 = 0.04 < 1.0$ , so simultaneous exposure is not required.

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

**Result: Pass**