

MPE Analysis Report

The Equipment Under Test (EUT), is a Zigbee Thermostat. It operates at frequency range of 2405 MHz to 2480 MHz with 16 channels, the channels are separated with 5MHz spacing. The EUT is powered by 3 x 1.5V AA batteries or 24VAC.

For Maximum Permissible Exposure (MPE) evaluation of the unit, the maximum power density at 20 cm from this transmitter shall be less than the General Population / Uncontrolled MPE limit in OET Bulletin 65 and meet the requirement listed in KDB447498 D04 v01.

For the RF portion of the unit, the measured powers among all the measured channels were within its production tolerance. The maximum source-based time-averaging duty factor is 100%. From these data and its operating configuration, the exposed power density at a distance (R) of 20 cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

Zigbee Portion

Antenna Type: Internal, Integral antenna

Antenna Gain: 0dBi

Operating Mode	Nominal Power	Range of Peak Conducted Power
Zigbee	9.73dBm	0dBm to 15dBm

For Maximum Permissible Exposure (MPE) evaluation of the EUT, the maximum power density at 20 cm from this mobile transmitter shall be less than the General Population / Uncontrolled MPE limit in OET Bulletin 65.

1) For the Zigbee portion, maximum conducted power was 15dBm. The distance (D) between the antenna and the equipment under test (EUT) was 3 meters. And the maximum source-based time-averaging duty factor is 100%. From these data, the exposed power density at a distance (R) of 20cm from the center of radiation of the antenna can be calculated according to OET Bulletin 65 as follow:

$$\text{The radiated power} = 15\text{dBm} + 0\text{dBi} = 15\text{dBm} (31.62 \text{ mW})$$

$$\begin{aligned} \text{The radiated (EIRP) source-based time-averaging output power} \\ &= (31.62 * 1) \text{ mW} \\ &= 31.62 \text{ mW} \end{aligned}$$

$$\begin{aligned} \text{The power density at 20 cm from the antenna} \\ &= \text{EIRP} / 4\pi R^2 \\ &= 0.006291 \text{ mW cm}^{-2} \end{aligned}$$

INTERTEK TESTING SERVICE

In the frequency range of 1,500 - 100,000MHz, the MPE limit is 1.0 mWcm⁻² for general population and uncontrolled exposure. As the measured power density at 20cm from the transmitter is lower than the MPE limit, the compliance to the MPE limit can be ensured by indicating the minimum 20cm separation between the transmitter's radiating structures and body of the user or nearby persons.

The following RF exposure statement is proposed to be included in the user manual:

“ FCC RF Radiation Exposure Statement

Caution: To maintain compliance with the FCC’s RF exposure guidelines, place the unit at least 20cm from nearby persons.”