

# ltron, Inc.

## TEST REPORT FOR

**Gas Endpoint**  
**Model: 500GB**

**Tested To The Following Standard:**

**FCC Part 15 Subpart C Section(s)**

**15.247**  
**(FHSS 902-928 MHz)**

**Report No.: 99317-4**

**Date of issue: March 9, 2017**



This test report bears the accreditation symbol indicating that the testing performed herein meets the test and reporting requirements of ISO/IEC 17025 under the applicable scope of EMC testing for CKC Laboratories, Inc.

We strive to create long-term, trust based relationships by providing sound, adaptive, customer first testing services. We embrace each of our customers' unique EMC challenges, not as an interruption to set processes, but rather as the reason we are in business.

## TABLE OF CONTENTS

Administrative Information .....	3
Test Report Information .....	3
Report Authorization .....	3
Test Facility Information .....	4
Software Versions.....	4
Site Registration & Accreditation Information .....	4
Summary of Results .....	5
Modifications During Testing.....	5
Conditions During Testing.....	5
Equipment Under Test.....	6
General Product Information.....	7
FCC Part 15 Subpart C .....	8
15.247(d) Radiated Emissions & Band Edge .....	8
Appendix A: Customer Provided Information.....	46
15.35(c) Duty Cycle Correction Factor.....	46
Supplemental Information.....	48
Measurement Uncertainty .....	48
Emissions Test Details.....	48

## ADMINISTRATIVE INFORMATION

### Test Report Information

**REPORT PREPARED FOR:**

Ittron, Inc.  
2111 N. Molter Road  
Liberty Lake, WA 99019

Representative: Jay Holcomb  
Customer Reference Number: 110651

**REPORT PREPARED BY:**

Terri Rayle  
CKC Laboratories, Inc.  
5046 Sierra Pines Drive  
Mariposa, CA 95338

Project Number: 99317

**DATE OF EQUIPMENT RECEIPT:**  
**DATE(S) OF TESTING:**

January 5, 2017  
January 5 -25 , 2017

### Report Authorization

The test data contained in this report documents the observed testing parameters pertaining to and are relevant for only the sample equipment tested in the agreed upon operational mode(s) and configuration(s) as identified herein. Compliance assessment remains the client's responsibility. This report may not be used to claim product endorsement by A2LA or any government agencies. This test report has been authorized for release under quality control from CKC Laboratories, Inc.



*Steve Behm*  
Director of Quality Assurance & Engineering Services  
CKC Laboratories, Inc.

## Test Facility Information



Our laboratories are configured to effectively test a wide variety of product types. CKC utilizes first class test equipment, anechoic chambers, data acquisition and information services to create accurate, repeatable and affordable test results.

TEST LOCATION(S):  
CKC Laboratories, Inc.  
22116 23rd Drive S.E., Suite A  
Canyon Park, Bothell, WA 98021

## Software Versions

CKC Laboratories Proprietary Software	Version
EMITest Emissions	5.03.02

## Site Registration & Accreditation Information

Location	CB #	TAIWAN	CANADA	FCC	JAPAN
Canyon Park, Bothell, WA	US0081	SL2-IN-E- 1145R	3082C-1	US1022	A-0148

## SUMMARY OF RESULTS

### Standard / Specification: FCC Part 15 Subpart C - 15.247 (FHSS 902-928MHz)

Test Procedure	Description	Modifications	Results
15.247(a)(1)(i)	Occupied Bandwidth	NA	NP
15.247(a)(1)	Carrier Separation	NA	NP
15.247(a)(1)(i)	Number of Hopping Channels	NA	NP
15.247(a)(1)(i)	Average Time of Occupancy	NA	NP
15.247(b)(2)	Output Power	NA	NP
15.247(d)	RF Conducted Emissions & Band Edge	NA	NP
15.247(d)	Radiated Emissions & Band Edge	NA	Pass
15.207	AC Conducted Emissions	NA	NP

NA = Not Applicable

NP = CKC Laboratories was not contracted to perform test.

## Modifications During Testing

This list is a summary of the modifications made to the equipment during testing.

### Summary of Conditions

No modifications were made during testing.

Modifications listed above must be incorporated into all production units.

## Conditions During Testing

This list is a summary of the conditions noted to the equipment during testing.

### Summary of Conditions

None

## EQUIPMENT UNDER TEST (EUT)

During testing numerous configurations may have been utilized. The configurations listed below support compliance to the standard(s) listed in the Summary of Results section.

### Configuration 1

*Equipment Tested:*

Device	Manufacturer	Model #	S/N
Gas Endpoint	Itron, Inc.	500GB	0100001747

*Support Equipment:*

Device	Manufacturer	Model #	S/N
None			

### Configuration 2

*Equipment Tested:*

Device	Manufacturer	Model #	S/N
Gas Endpoint	Itron, Inc.	500GB	0100001746

*Support Equipment:*

Device	Manufacturer	Model #	S/N
None			

### Configuration 3

*Equipment Tested:*

Device	Manufacturer	Model #	S/N
Gas Endpoint	Itron, Inc.	500GB	0100001753

*Support Equipment:*

Device	Manufacturer	Model #	S/N
None			

### Configuration 4

*Equipment Tested:*

Device	Manufacturer	Model #	S/N
Gas Endpoint	Itron, Inc.	500GB	0100001743

*Support Equipment:*

Device	Manufacturer	Model #	S/N
None			

## General Product Information:

---

Product Information	Manufacturer-Provided Details
Equipment Type:	Stand-Alone Equipment
Type of Wideband System:	FHSS
Operating Frequency Range:	903-926.8MHz (OOK) 902.4-927.6MHz (FSK 150kbps) 902.2 to 927.75MHz (FSK 10kbps)
Number of Hopping Channels:	See supplemental report
Modulation Type(s):	OOK and FSK
Maximum Duty Cycle:	See supplemental report
Number of TX Chains:	2
Antenna Type(s) and Gain:	See supplemental report
Beamforming Type:	NA
Antenna Connection Type:	Integral
Nominal Input Voltage:	Battery
Firmware / Software used for Test:	See supplemental report

## FCC Part 15 Subpart C

### 15.247(d) Radiated Emissions & Band Edge

#### Test Setup / Conditions / Data

Test Location: CKC Laboratories, Inc. • 22116 23rd Drive SE Suite A • Bothell, WA 98021 • 800-500-4EMC (4362)  
 Customer: **Itron, Inc.**  
 Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
 Work Order #: **99317** Date: 1/25/2017  
 Test Type: **Maximized Emissions** Time: 16:03:45  
 Tested By: Steven Pittsford Sequence#: 4  
 Software: EMITest 5.03.02

**Equipment Tested:**

Device	Manufacturer	Model #	S/N
Configuration 1			

**Support Equipment:**

Device	Manufacturer	Model #	S/N
Configuration 1			

**Test Conditions / Notes:**

Temperature: 20-24°C

Relative Humidity: 21-32%

Frequency range investigated: 9kHz-10GHz

Transmitter Frequency: 902.4-927.6MHz

**Modulation: FSK 150kbps**

**Firmware Power Level: 3**

EUT Firmware: App Version: 1.18.3.0, CSL Version: 2.22.1.0

Antenna Type: Internal Trace

Antenna Gain: -0.94dBi

Duty Cycle: Max


Test Method: ANSI C63.10 (2013)

The EUT is a transmitter operating hopping in band. The EUT is battery operated, fresh batteries installed.

The EUT has no IO ports. Parallel, Perpendicular, Ground parallel antenna polarities investigated below 30MHz, Horizontal and Vertical antenna polarities investigated above 30MHz, only worst case reported.

The EUT orientation selected based on manufacturer declared fixed installation orientation. Hopping operation selected as worst case based on previously collected data.

Itron, Inc. WO#: 99317 Sequence#: 4 Date: 1/25/2017  
15.247(d) / 15.209 Radiated Spurious Emissions Test Distance: 3 Meters Vert



**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP05360	Cable	RG214	11/30/2016	11/30/2018
T2	ANP05963	Cable	RG-214	2/15/2016	2/15/2018
T3	ANP06540	Cable	Heliax	10/29/2015	10/29/2017
T4	AN01816	Log Periodic Antenna-ANSI 63.5	3146	1/8/2016	1/8/2018
T5	AN02872	Spectrum Analyzer	E4440A	11/18/2015	11/18/2017
T6	AN01991	Biconilog Antenna	CBL6111C	3/11/2016	3/11/2018
T7	ANP05657	Attenuator	PE7004-6	12/22/2015	12/22/2017
T8	AN00052	Loop Antenna	6502	4/8/2016	4/8/2018
T9	AN03540	Preamp	83017A	4/30/2015	4/30/2017
T10	AN01467	Horn Antenna- ANSI C63.5 Calibration	3115	8/12/2015	8/12/2017
T11	ANP05305	Cable	ETSI-50T	2/15/2016	2/15/2018
T12	ANP06935	Cable	32026-29801- 29801-18	3/11/2016	3/11/2018
T13	AN03170	High Pass Filter	HM1155-11SS	12/17/2015	12/17/2017

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5	T6	T7	T8					
			T9	T10	T11	T12					
			T13								
	MHz	dB $\mu$ V	dB	dB	dB	dB	Table	dB $\mu$ V/m	dB $\mu$ V/m	dB	Ant
1	4576.029M	47.0	+0.0	+0.0	+0.9	+0.0	+0.0	51.4	54.0	-2.6	Vert
	Ave		+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.4								
^	4576.029M	47.6	+0.0	+0.0	+0.9	+0.0	+0.0	52.0	54.0	-2.0	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.4								
3	4512.090M	46.7	+0.0	+0.0	+0.9	+0.0	+0.0	51.1	54.0	-2.9	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.4								
4	4549.930M	46.2	+0.0	+0.0	+0.9	+0.0	+0.0	50.5	54.0	-3.5	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.3								
5	4514.000M	45.3	+0.0	+0.0	+0.9	+0.0	+0.0	49.7	54.0	-4.3	Horiz
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.4								
6	4575.600M	45.1	+0.0	+0.0	+0.9	+0.0	+0.0	49.5	54.0	-4.5	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.4								

7	4546.000M	45.1	+0.0	+0.0	+0.9	+0.0	+0.0	49.4	54.0	-4.6	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.3								
8	4638.050M	44.7	+0.0	+0.0	+0.9	+0.0	+0.0	49.4	54.0	-4.6	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.6	+4.3	+0.5					
			+0.5								
9	967.200M	20.3	+2.2	+2.5	+0.4	+23.3	+0.0	48.7	54.0	-5.3	Vert
	QP		+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
^	967.200M	24.5	+2.2	+2.5	+0.4	+23.3	+0.0	52.9	54.0	-1.1	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
11	980.410M	19.1	+2.2	+2.5	+0.4	+24.0	+0.0	48.2	54.0	-5.8	Vert
	QP		+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
^	980.410M	23.1	+2.2	+2.5	+0.4	+24.0	+0.0	52.2	54.0	-1.8	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
13	988.005M	18.5	+2.2	+2.5	+0.4	+24.3	+0.0	47.9	54.0	-6.1	Vert
	QP		+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
^	987.940M	21.8	+2.2	+2.5	+0.4	+24.3	+0.0	51.2	54.0	-2.8	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
15	993.197M	18.2	+2.3	+2.5	+0.4	+24.5	+0.0	47.9	54.0	-6.1	Vert
	QP		+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
^	993.180M	21.8	+2.3	+2.5	+0.4	+24.5	+0.0	51.5	54.0	-2.5	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
17	2710.000M	48.6	+0.0	+0.0	+0.7	+0.0	+0.0	47.3	54.0	-6.7	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.5	+28.6	+3.0	+0.4					
			+0.5								
18	9151.590M	35.1	+0.0	+0.0	+1.4	+0.0	+0.0	46.5	54.0	-7.5	Horiz
			+0.0	+0.0	+0.0	+0.0					
			-34.7	+37.7	+6.1	+0.7					
			+0.2								
19	1063.000M	45.9	+0.0	+0.0	+0.4	+0.0	+0.0	46.0	54.0	-8.0	Vert
			+0.0	+0.0	+0.0	+0.0					
			-37.3	+24.2	+1.9	+0.2					
			+10.7								

20	9099.880M	34.5	+0.0	+0.0	+1.3	+0.0	+0.0	45.8	54.0	-8.2	Horiz
			+0.0	+0.0	+0.0	+0.0					
			-34.7	+37.7	+6.1	+0.7					
			+0.2								
21	988.000M	16.3	+2.2	+2.5	+0.4	+24.3	+0.0	45.7	54.0	-8.3	Horiz
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
22	9120.800M	34.1	+0.0	+0.0	+1.3	+0.0	+0.0	45.4	54.0	-8.6	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.7	+37.7	+6.1	+0.7					
			+0.2								
23	980.370M	15.9	+2.2	+2.5	+0.4	+24.0	+0.0	45.0	54.0	-9.0	Horiz
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
24	2708.000M	46.1	+0.0	+0.0	+0.7	+0.0	+0.0	44.8	54.0	-9.2	Horiz
			+0.0	+0.0	+0.0	+0.0					
			-34.5	+28.6	+3.0	+0.4					
			+0.5								
25	162.430M	14.7	+0.7	+1.4	+0.2	+0.0	+0.0	33.4	43.5	-10.1	Horiz
			+0.0	+10.4	+6.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
26	963.110M	8.3	+2.2	+2.5	+0.4	+23.0	+0.0	36.4	54.0	-17.6	Vert
QP			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
^	963.110M	25.8	+2.2	+2.5	+0.4	+23.0	+0.0	53.9	54.0	-0.1	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
28	1833.000M	76.3	+0.0	+0.0	+0.5	+0.0	+0.0	71.7	100.9	-29.2	Horiz
			+0.0	+0.0	+0.0	+0.0					
			-35.1	+26.9	+2.5	+0.3					
			+0.3								
29	1819.000M	75.7	+0.0	+0.0	+0.5	+0.0	+0.0	71.2	100.9	-29.7	Vert
			+0.0	+0.0	+0.0	+0.0					
			-35.1	+26.9	+2.5	+0.3					
			+0.4								
30	1805.000M	73.9	+0.0	+0.0	+0.5	+0.0	+0.0	69.3	100.9	-31.6	Vert
			+0.0	+0.0	+0.0	+0.0					
			-35.1	+26.8	+2.5	+0.3					
			+0.4								
31	1831.000M	72.2	+0.0	+0.0	+0.5	+0.0	+0.0	67.7	100.9	-33.2	Vert
			+0.0	+0.0	+0.0	+0.0					
			-35.1	+26.9	+2.5	+0.3					
			+0.4								
32	1855.000M	69.0	+0.0	+0.0	+0.5	+0.0	+0.0	64.5	100.9	-36.4	Vert
			+0.0	+0.0	+0.0	+0.0					
			-35.1	+27.0	+2.5	+0.3					
			+0.3								

33	957.940M	18.5	+2.2	+2.5	+0.4	+22.7	+0.0	46.3	100.9	-54.6	Horiz
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
34	2467.000M	45.1	+0.0	+0.0	+0.6	+0.0	+0.0	42.6	100.9	-58.3	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.5	+27.7	+2.9	+0.4					
			+0.4								
35	342.200M	19.8	+1.2	+1.7	+0.2	+13.9	+0.0	36.8	100.9	-64.1	Horiz
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
36	557.848M	14.6	+1.5	+2.0	+0.3	+18.3	+0.0	36.7	100.9	-64.2	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
37	37.480M	13.0	+0.3	+0.5	+0.1	+0.0	+0.0	35.6	100.9	-65.3	Horiz
			+0.0	+15.7	+6.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
38	343.180M	16.0	+1.2	+1.7	+0.2	+13.9	+0.0	33.0	100.9	-67.9	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
39	179.090M	14.4	+0.8	+1.4	+0.2	+0.0	+0.0	32.0	100.9	-68.9	Horiz
			+0.0	+9.2	+6.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
40	230.239M	12.0	+0.9	+1.4	+0.2	+10.5	+0.0	25.0	100.9	-75.9	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
41	4.358M	19.9	+0.0	+0.0	+0.0	+0.0	-40.0	-10.6	100.9	-111.5	Para
			+0.0	+0.0	+0.0	+9.4					
			+0.0	+0.0	+0.1	+0.0					
			+0.0								
42	69.000k	54.7	+0.0	+0.0	+0.0	+0.0	-80.0	-15.1	100.9	-116.0	Para
			+0.0	+0.0	+0.0	+10.2					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
43	26.041M	14.1	+0.0	+0.0	+0.0	+0.0	-40.0	-18.9	100.9	-119.8	Para
			+0.0	+0.0	+0.0	+6.7					
			+0.0	+0.0	+0.3	+0.0					
			+0.0								



Test Location: CKC Laboratories, Inc. • 22116 23rd Drive SE Suite A • Bothell, WA 98021 • 800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
Work Order #: **99317** Date: 1/25/2017  
Test Type: **Maximized Emissions** Time: 16:19:01  
Tested By: Steven Pittsford Sequence#: 3  
Software: EMITest 5.03.02

**Equipment Tested:**

Device	Manufacturer	Model #	S/N
Configuration 2			

**Support Equipment:**

Device	Manufacturer	Model #	S/N
Configuration 2			

**Test Conditions / Notes:**

Temperature: 20-24°C

Relative Humidity: 21-32%

Frequency range investigated: 9kHz-10GHz

Transmitter Frequency: 902.2 to 927.75 MHz

**Modulation: FSK 10kbps**

**Firmware Power Level: 3**

EUT Firmware: App Version: 1.18.3.0, CSL Version: 2.22.1.0

Antenna Type: Internal Trace

Antenna Gain: -0.94dBi

Duty Cycle: Max


Test Method: ANSI C63.10 (2013)

The EUT is a transmitter operating hopping in band. The EUT is battery operated, fresh batteries installed.

The EUT has no IO ports. Parallel, Perpendicular, Ground parallel antenna polarities investigated below 30MHz, Horizontal and Vertical antenna polarities investigated above 30MHz, only worst case reported.

The EUT orientation selected based on manufacturer declared fixed installation orientation. Hopping operation selected as worst case based on previously collected data.

Itron, Inc. WO#: 99317 Sequence#: 3 Date: 1/25/2017  
15.247(d) / 15.209 Radiated Spurious Emissions Test Distance: 3 Meters Vert



**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP05360	Cable	RG214	11/30/2016	11/30/2018
T2	ANP05963	Cable	RG-214	2/15/2016	2/15/2018
T3	ANP06540	Cable	Heliax	10/29/2015	10/29/2017
T4	AN01816	Log Periodic Antenna-ANSI 63.5	3146	1/8/2016	1/8/2018
T5	AN02872	Spectrum Analyzer	E4440A	11/18/2015	11/18/2017
T6	AN01991	Biconilog Antenna	CBL6111C	3/11/2016	3/11/2018
T7	ANP05657	Attenuator	PE7004-6	12/22/2015	12/22/2017
T8	AN00052	Loop Antenna	6502	4/8/2016	4/8/2018
T9	AN03540	Preamp	83017A	4/30/2015	4/30/2017
T10	AN01467	Horn Antenna- ANSI C63.5 Calibration	3115	8/12/2015	8/12/2017
T11	ANP05305	Cable	ETSI-50T	2/15/2016	2/15/2018
T12	ANP06935	Cable	32026-29801- 29801-18	3/11/2016	3/11/2018
T13	AN03170	High Pass Filter	HM1155-11SS	12/17/2015	12/17/2017

**Measurement Data:** Reading listed by margin. Test Distance: 3 Meters

#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5	T6	T7	T8					
			T9	T10	T11	T12					
			T13								
	MHz	dB $\mu$ V	dB	dB	dB	dB	Table	dB $\mu$ V/m	dB $\mu$ V/m	dB	Ant
1	4510.958M	48.9	+0.0	+0.0	+0.9	+0.0	+0.0	53.3	54.0	-0.7	Vert
	Ave		+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.4								
^	4510.958M	49.6	+0.0	+0.0	+0.9	+0.0	+0.0	54.0	54.0	+0.0	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.4								
3	9150.000M	39.9	+0.0	+0.0	+1.4	+0.0	+0.0	51.3	54.0	-2.7	Vert
	Ave		+0.0	+0.0	+0.0	+0.0					
			-34.7	+37.7	+6.1	+0.7					
			+0.2								
^	9150.000M	40.5	+0.0	+0.0	+1.4	+0.0	+0.0	51.9	54.0	-2.1	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.7	+37.7	+6.1	+0.7					
			+0.2								
5	4574.879M	46.8	+0.0	+0.0	+0.9	+0.0	+0.0	51.2	54.0	-2.8	Vert
	Ave		+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.4								
^	4574.879M	48.0	+0.0	+0.0	+0.9	+0.0	+0.0	52.4	54.0	-1.6	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.4								

7	4550.089M	46.0	+0.0	+0.0	+0.9	+0.0	+0.0	50.3	54.0	-3.7	Vert
	Ave		+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.3								
^	4550.089M	47.2	+0.0	+0.0	+0.9	+0.0	+0.0	51.5	54.0	-2.5	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.3								
9	4638.625M	44.9	+0.0	+0.0	+0.9	+0.0	+0.0	49.6	54.0	-4.4	Vert
	Ave		+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.6	+4.3	+0.5					
			+0.5								
^	4638.625M	45.4	+0.0	+0.0	+0.9	+0.0	+0.0	50.1	54.0	-3.9	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.6	+4.3	+0.5					
			+0.5								
11	4510.000M	45.2	+0.0	+0.0	+0.9	+0.0	+0.0	49.6	54.0	-4.4	Horiz
			+0.0	+0.0	+0.0	+0.0					
			-34.1	+32.5	+4.2	+0.5					
			+0.4								
12	980.200M	19.4	+2.2	+2.5	+0.4	+24.0	+0.0	48.5	54.0	-5.5	Vert
	QP		+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
^	980.200M	23.3	+2.2	+2.5	+0.4	+24.0	+0.0	52.4	54.0	-1.6	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
14	988.000M	18.9	+2.2	+2.5	+0.4	+24.3	+0.0	48.3	54.0	-5.7	Vert
	QP		+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
^	988.000M	22.6	+2.2	+2.5	+0.4	+24.3	+0.0	52.0	54.0	-2.0	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
16	962.000M	20.1	+2.2	+2.5	+0.4	+23.0	+0.0	48.2	54.0	-5.8	Vert
	QP		+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
^	962.000M	23.4	+2.2	+2.5	+0.4	+23.0	+0.0	51.5	54.0	-2.5	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
18	966.995M	19.5	+2.2	+2.5	+0.4	+23.3	+0.0	47.9	54.0	-6.1	Vert
	QP		+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
^	967.080M	23.8	+2.2	+2.5	+0.4	+23.3	+0.0	52.2	54.0	-1.8	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								

20	993.003M	18.1	+2.3	+2.5	+0.4	+24.5	+0.0	47.8	54.0	-6.2	Vert
	QP		+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
^	993.000M	21.3	+2.3	+2.5	+0.4	+24.5	+0.0	51.0	54.0	-3.0	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
22	9022.500M	36.3	+0.0	+0.0	+1.3	+0.0	+0.0	47.7	54.0	-6.3	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.6	+37.8	+6.0	+0.7					
			+0.2								
23	2728.000M	48.8	+0.0	+0.0	+0.7	+0.0	+0.0	47.6	54.0	-6.4	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.5	+28.7	+3.0	+0.4					
			+0.5								
24	9099.500M	36.1	+0.0	+0.0	+1.3	+0.0	+0.0	47.4	54.0	-6.6	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.7	+37.7	+6.1	+0.7					
			+0.2								
25	9100.030M	34.5	+0.0	+0.0	+1.3	+0.0	+0.0	45.8	54.0	-8.2	Vert
	Ave		+0.0	+0.0	+0.0	+0.0					
			-34.7	+37.7	+6.1	+0.7					
			+0.2								
^	9100.030M	37.0	+0.0	+0.0	+1.3	+0.0	+0.0	48.3	54.0	-5.7	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.7	+37.7	+6.1	+0.7					
			+0.2								
27	2728.000M	46.6	+0.0	+0.0	+0.7	+0.0	+0.0	45.4	54.0	-8.6	Horiz
			+0.0	+0.0	+0.0	+0.0					
			-34.5	+28.7	+3.0	+0.4					
			+0.5								
28	609.600M	15.1	+1.6	+2.1	+0.3	+18.3	+0.0	37.4	46.0	-8.6	Horiz
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
29	980.000M	15.0	+2.2	+2.5	+0.4	+24.0	+0.0	44.1	54.0	-9.9	Horiz
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
30	127.070M	12.6	+0.6	+1.2	+0.1	+0.0	+0.0	32.2	43.5	-11.3	Vert
			+0.0	+11.7	+6.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
31	1801.000M	74.3	+0.0	+0.0	+0.5	+0.0	+0.0	69.7	100.9	-31.2	Vert
			+0.0	+0.0	+0.0	+0.0					
			-35.1	+26.8	+2.5	+0.3					
			+0.4								
32	896.400M	41.3	+2.1	+2.4	+0.3	+22.6	+0.0	68.7	100.9	-32.2	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								

33	1820.100M	70.7	+0.0	+0.0	+0.5	+0.0	+0.0	66.2	100.9	-34.7	Vert
			+0.0	+0.0	+0.0	+0.0					
			-35.1	+26.9	+2.5	+0.3					
			+0.4								
34	1829.800M	69.2	+0.0	+0.0	+0.5	+0.0	+0.0	64.7	100.9	-36.2	Vert
			+0.0	+0.0	+0.0	+0.0					
			-35.1	+26.9	+2.5	+0.3					
			+0.4								
35	1801.000M	65.8	+0.0	+0.0	+0.5	+0.0	+0.0	61.2	100.9	-39.7	Horiz
			+0.0	+0.0	+0.0	+0.0					
			-35.1	+26.8	+2.5	+0.3					
			+0.4								
36	1855.400M	65.1	+0.0	+0.0	+0.5	+0.0	+0.0	60.7	100.9	-40.2	Vert
			+0.0	+0.0	+0.0	+0.0					
			-35.1	+27.1	+2.5	+0.3					
			+0.3								
37	9277.500M	36.9	+0.0	+0.0	+1.4	+0.0	+0.0	48.2	100.9	-52.7	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.8	+37.6	+6.2	+0.7					
			+0.2								
38	831.800M	20.4	+2.0	+2.3	+0.3	+21.3	+0.0	46.3	100.9	-54.6	Horiz
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
39	2467.000M	46.4	+0.0	+0.0	+0.6	+0.0	+0.0	43.9	100.9	-57.0	Vert
			+0.0	+0.0	+0.0	+0.0					
			-34.5	+27.7	+2.9	+0.4					
			+0.4								
40	810.700M	17.8	+1.9	+2.3	+0.3	+20.8	+0.0	43.1	100.9	-57.8	Horiz
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
41	340.000M	20.3	+1.1	+1.7	+0.2	+13.9	+0.0	37.2	100.9	-63.7	Horiz
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
42	33.740M	11.8	+0.3	+0.4	+0.0	+0.0	+0.0	35.8	100.9	-65.1	Vert
			+0.0	+17.3	+6.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
43	192.180M	14.7	+0.8	+1.4	+0.2	+0.0	+0.0	32.1	100.9	-68.8	Horiz
			+0.0	+9.0	+6.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								

44	341.800M	14.1	+1.1	+1.7	+0.2	+13.9	+0.0	31.0	100.9	-69.9	Horiz
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
45	294.100M	14.6	+1.1	+1.6	+0.2	+13.3	+0.0	30.8	100.9	-70.1	Vert
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
46	6.037M	17.3	+0.0	+0.0	+0.0	+0.0	-40.0	-13.3	100.9	-114.2	Para
			+0.0	+0.0	+0.0	+9.3					
			+0.0	+0.0	+0.1	+0.0					
			+0.0								
47	69.000k	54.0	+0.0	+0.0	+0.0	+0.0	-80.0	-15.8	100.9	-116.7	Para
			+0.0	+0.0	+0.0	+10.2					
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
48	27.901M	14.5	+0.0	+0.0	+0.0	+0.0	-40.0	-19.0	100.9	-119.9	Para
			+0.0	+0.0	+0.0	+6.2					
			+0.0	+0.0	+0.3	+0.0					
			+0.0								



Test Location: CKC Laboratories, Inc. • 22116 23rd Drive SE Suite A • Bothell, WA 98021 • 800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
Work Order #: **99317** Date: 1/9/2017  
Test Type: **Maximized Emissions** Time: 09:56:37  
Tested By: Steven Pittsford Sequence#: 3  
Software: EMITest 5.03.02

**Equipment Tested:**

Device	Manufacturer	Model #	S/N
Configuration 3			

**Support Equipment:**

Device	Manufacturer	Model #	S/N
Configuration 3			

**Test Conditions / Notes:**

Temperature: 20-24°C

Relative Humidity: 21-32%

Frequency range investigated: 9kHz-10GHz

Transmitter Frequency: 903-926.8MHz

**Modulation: OOK**

**Firmware Power Level: 3**

EUT Firmware: App Version: 1.18.3.0, CSL Version: 2.22.1.0

Antenna Type: Internal Trace

Antenna Gain: -0.94dBi

Duty Cycle: Max


Test Method: ANSI C63.10 (2013)

The EUT is a transmitter operating hopping in band. The EUT is battery operated, fresh batteries installed.

The EUT has no IO ports. Parallel, Perpendicular, Ground parallel antenna polarities investigated below 30MHz, Horizontal and Vertical antenna polarities investigated above 30MHz, only worst case reported.

The EUT orientation selected based on manufacturer declared fixed installation orientation. Hopping operation selected as worst case based on previously collected data.

Itron, Inc. WO#: 99317 Sequence#: 3 Date: 1/9/2017  
15.247(d) / 15.209 Radiated Spurious Emissions Test Distance: 3 Meters Vert



**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP05360	Cable	RG214	11/30/2016	11/30/2018
T2	ANP05963	Cable	RG-214	2/15/2016	2/15/2018
T3	ANP06540	Cable	Heliax	10/29/2015	10/29/2017
T4	AN01816	Log Periodic Antenna-ANSI 63.5	3146	1/8/2016	1/8/2018
T5	AN02872	Spectrum Analyzer	E4440A	11/18/2015	11/18/2017
T6	AN01991	Biconilog Antenna	CBL6111C	3/11/2016	3/11/2018
T7	ANP05657	Attenuator	PE7004-6	12/22/2015	12/22/2017
T8	AN00052	Loop Antenna	6502	4/8/2016	4/8/2018
T9	AN03540	Preamp	83017A	4/30/2015	4/30/2017
T10	AN01467	Horn Antenna- ANSI C63.5 Calibration	3115	8/12/2015	8/12/2017
T11	ANP05305	Cable	ETSI-50T	2/15/2016	2/15/2018
T12	ANP06935	Cable	32026-29801- 29801-18	3/11/2016	3/11/2018
T13	AN03170	High Pass Filter	HM1155-11SS	12/17/2015	12/17/2017

**Measurement Data:** Reading listed by margin. Test Distance: 3 Meters

#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5	T6	T7	T8					
			T9	T10	T11	T12					
			T13								
	MHz	dB $\mu$ V	dB	dB	dB	dB	Table	dB $\mu$ V/m	dB $\mu$ V/m	dB	Ant
1	4515.002M	48.0	+0.0	+0.0	+0.9	+0.0	+0.0	52.4	54.0	-1.6	Vert
			+0.0	+0.0	+0.0	+0.0					161
			-34.1	+32.5	+4.2	+0.5					
			+0.4								
2	4549.850M	48.0	+0.0	+0.0	+0.9	+0.0	+0.0	52.3	54.0	-1.7	Vert
			+0.0	+0.0	+0.0	+0.0					161
			-34.1	+32.5	+4.2	+0.5					
			+0.3								
3	4634.094M	46.4	+0.0	+0.0	+0.9	+0.0	+0.0	51.1	54.0	-2.9	Vert
			+0.0	+0.0	+0.0	+0.0					157
			-34.1	+32.6	+4.3	+0.5					
			+0.5								
4	4575.070M	46.5	+0.0	+0.0	+0.9	+0.0	+0.0	50.9	54.0	-3.1	Vert
			+0.0	+0.0	+0.0	+0.0					161
			-34.1	+32.5	+4.2	+0.5					
			+0.4								
5	960.026M	22.8	+2.2	+2.5	+0.4	+22.8	+0.0	50.7	54.0	-3.3	Horiz
	QP		+0.0	+0.0	+0.0	+0.0	100				145
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
^	960.000M	28.1	+2.2	+2.5	+0.4	+22.8	+0.0	56.0	54.0	+2.0	Horiz
			+0.0	+0.0	+0.0	+0.0	100				145
			+0.0	+0.0	+0.0	+0.0					
			+0.0								

7	9165.000M	37.5	+0.0	+0.0	+1.4	+0.0	+0.0	48.9	54.0	-5.1	Vert
			+0.0	+0.0	+0.0	+0.0	360				144
			-34.7	+37.7	+6.1	+0.7					
			+0.2								
8	7268.000M	40.6	+0.0	+0.0	+1.2	+0.0	+0.0	48.6	54.0	-5.4	Vert
			+0.0	+0.0	+0.0	+0.0	11				144
			-34.6	+35.9	+4.6	+0.6					
			+0.3								
9	2730.000M	45.8	+0.0	+0.0	+0.7	+0.0	+0.0	44.6	54.0	-9.4	Vert
			+0.0	+0.0	+0.0	+0.0	14				144
			-34.5	+28.7	+3.0	+0.4					
			+0.5								
10	2709.400M	45.9	+0.0	+0.0	+0.7	+0.0	+0.0	44.6	54.0	-9.4	Vert
			+0.0	+0.0	+0.0	+0.0	14				144
			-34.5	+28.6	+3.0	+0.4					
			+0.5								
11	2780.600M	45.5	+0.0	+0.0	+0.7	+0.0	+0.0	44.4	54.0	-9.6	Vert
			+0.0	+0.0	+0.0	+0.0	14				144
			-34.5	+28.9	+3.0	+0.4					
			+0.4								
12	2745.200M	45.3	+0.0	+0.0	+0.7	+0.0	+0.0	44.1	54.0	-9.9	Vert
			+0.0	+0.0	+0.0	+0.0	14				144
			-34.5	+28.8	+3.0	+0.4					
			+0.4								
13	614.000M	11.2	+1.6	+2.1	+0.3	+18.5	+0.0	33.7	46.0	-12.3	Horiz
			+0.0	+0.0	+0.0	+0.0	100				145
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
14	902.000M	57.3	+2.1	+2.4	+0.3	+22.6	+0.0	84.7	99.0	-14.3	Horiz
			+0.0	+0.0	+0.0	+0.0	100				145
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
15	928.000M	56.6	+2.1	+2.4	+0.4	+22.4	+0.0	83.9	99.0	-15.1	Horiz
			+0.0	+0.0	+0.0	+0.0	100				145
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
16	1805.950M	73.4	+0.0	+0.0	+0.5	+0.0	+0.0	68.8	99.0	-30.2	Horiz
			+0.0	+0.0	+0.0	+0.0	315				146
			-35.1	+26.8	+2.5	+0.3					
			+0.4								
17	1819.950M	70.7	+0.0	+0.0	+0.5	+0.0	+0.0	66.2	99.0	-32.8	Horiz
			+0.0	+0.0	+0.0	+0.0	315				146
			-35.1	+26.9	+2.5	+0.3					
			+0.4								
18	1829.950M	68.6	+0.0	+0.0	+0.5	+0.0	+0.0	64.1	99.0	-34.9	Horiz
			+0.0	+0.0	+0.0	+0.0	315				146
			-35.1	+26.9	+2.5	+0.3					
			+0.4								
19	1853.600M	62.4	+0.0	+0.0	+0.5	+0.0	+0.0	57.9	99.0	-41.1	Horiz
			+0.0	+0.0	+0.0	+0.0	315				146
			-35.1	+27.0	+2.5	+0.3					
			+0.3								

20	6499.360M	39.4	+0.0	+0.0	+1.2	+0.0	+0.0	46.3	99.0	-52.7	Vert
			+0.0	+0.0	+0.0	+0.0	222				144
			-34.2	+34.4	+4.6	+0.6					
			+0.3								
21	648.700M	13.8	+1.7	+2.1	+0.3	+19.8	+0.0	37.7	99.0	-61.3	Horiz
			+0.0	+0.0	+0.0	+0.0	360				127
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
22	35.780M	12.3	+0.3	+0.4	+0.0	+0.0	+0.0	35.5	99.0	-63.5	Vert
			+0.0	+16.5	+6.0	+0.0					102
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
23	95.879k	33.9	+0.0	+0.1	+0.0	+0.0	-80.0	-36.1	28.0	-64.1	Paral
			+0.0	+0.0	+0.0	+9.9					102
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
24	432.400M	13.4	+1.3	+1.8	+0.3	+15.9	+0.0	32.7	99.0	-66.3	Horiz
			+0.0	+0.0	+0.0	+0.0	360				127
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
25	102.420M	13.0	+0.6	+1.2	+0.1	+0.0	+0.0	31.2	99.0	-67.8	Vert
			+0.0	+10.3	+6.0	+0.0					102
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
26	184.870M	13.2	+0.8	+1.4	+0.2	+0.0	+0.0	30.7	99.0	-68.3	Vert
			+0.0	+9.1	+6.0	+0.0	73				102
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
27	215.400M	12.4	+0.9	+1.4	+0.2	+10.6	+0.0	25.5	99.0	-73.5	Vert
			+0.0	+0.0	+0.0	+0.0	256				108
			+0.0	+0.0	+0.0	+0.0					
			+0.0								
28	9.762M	11.8	+0.1	+0.2	+0.0	+0.0	-40.0	-18.7	99.0	-117.7	Perpe
			+0.0	+0.0	+0.0	+9.2					102
			+0.0	+0.0	+0.0	+0.0					
			+0.0								



Test Location: CKC Laboratories, Inc. • 22116 23rd Drive SE Suite A • Bothell, WA 98021 • 800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
Work Order #: **99317** Date: 1/9/2017  
Test Type: **Maximized Emissions** Time: 10:47:06  
Tested By: Steven Pittsford Sequence#: 4  
Software: EMITest 5.03.02

**Equipment Tested:**

Device	Manufacturer	Model #	S/N
Configuration 4			

**Support Equipment:**

Device	Manufacturer	Model #	S/N
Configuration 4			

**Test Conditions / Notes:**

Temperature: 20-24°C

Relative Humidity: 21-32%

Frequency range investigated: 9kHz-10GHz

Transmitter Frequency: 903-926.8MHz

**Modulation: OOK**

**Firmware Power Level: 1**

EUT Firmware: App Version: 1.18.3.0, CSL Version: 2.22.1.0

Antenna Type: Internal Trace

Antenna Gain: 1.99dBi

Duty Cycle: Max


Test Method: ANSI C63.10 (2013)

The EUT is a transmitter operating hopping in band. The EUT is battery operated, fresh batteries installed.

The EUT has no IO ports. Parallel, Perpendicular, Ground parallel antenna polarities investigated below 30MHz, Horizontal and Vertical antenna polarities investigated above 30MHz, only worst case reported.

The EUT orientation selected based on manufacturer declared fixed installation orientation. Hopping operation selected as worst case based on previously collected data.

Itron, Inc. WO#: 99317 Sequence#: 4 Date: 1/9/2017  
15.247(d) / 15.209 Radiated Spurious Emissions Test Distance: 3 Meters Vert



**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP05360	Cable	RG214	11/30/2016	11/30/2018
T2	ANP05963	Cable	RG-214	2/15/2016	2/15/2018
T3	ANP06540	Cable	Heliax	10/29/2015	10/29/2017
T4	AN01816	Log Periodic Antenna-ANSI 63.5	3146	1/8/2016	1/8/2018
T5	AN02872	Spectrum Analyzer	E4440A	11/18/2015	11/18/2017
T6	AN01991	Biconilog Antenna	CBL6111C	3/11/2016	3/11/2018
T7	ANP05657	Attenuator	PE7004-6	12/22/2015	12/22/2017
T8	AN00052	Loop Antenna	6502	4/8/2016	4/8/2018
T9	AN03540	Preamp	83017A	4/30/2015	4/30/2017
T10	AN01467	Horn Antenna- ANSI C63.5 Calibration	3115	8/12/2015	8/12/2017
T11	ANP05305	Cable	ETSI-50T	2/15/2016	2/15/2018
T12	ANP06935	Cable	32026-29801- 29801-18	3/11/2016	3/11/2018
T13	AN03170	High Pass Filter	HM1155-11SS	12/17/2015	12/17/2017
T14	AN12.2% DCCF	Test Data Adjustment		1/6/2017	1/6/2019

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

#	Freq	Rdng	T1	T2	T3	T4	Dist	Corr	Spec	Margin	Polar
			T5	T6	T7	T8					
			T9	T10	T11	T12					
			T13	T14							
	MHz	dB $\mu$ V	dB	dB	dB	dB	Table	dB $\mu$ V/m	dB $\mu$ V/m	dB	Ant
1	2780.410M	63.7	+0.0	+0.0	+0.7	+0.0	+0.0	44.4	54.0	-9.6	Horiz
			+0.0	+0.0	+0.0	+0.0	57				136
			-34.5	+28.9	+3.0	+0.4					
			+0.4	-18.2							
2	2709.000M	63.7	+0.0	+0.0	+0.7	+0.0	+0.0	44.2	54.0	-9.8	Horiz
			+0.0	+0.0	+0.0	+0.0	57				136
			-34.5	+28.6	+3.0	+0.4					
			+0.5	-18.2							
3	2745.031M	63.5	+0.0	+0.0	+0.7	+0.0	+0.0	44.1	54.0	-9.9	Horiz
			+0.0	+0.0	+0.0	+0.0	57				136
			-34.5	+28.8	+3.0	+0.4					
			+0.4	-18.2							
4	8341.213M	52.9	+0.0	+0.0	+1.4	+0.0	+0.0	44.1	54.0	-9.9	Vert
			+0.0	+0.0	+0.0	+0.0	88				154
			-35.0	+36.6	+5.4	+0.7					
			+0.3	-18.2							
5	2730.077M	63.3	+0.0	+0.0	+0.7	+0.0	+0.0	43.9	54.0	-10.1	Horiz
			+0.0	+0.0	+0.0	+0.0	57				136
			-34.5	+28.7	+3.0	+0.4					
			+0.5	-18.2							

6	8235.000M	52.8	+0.0	+0.0	+1.3	+0.0	+0.0	43.8	54.0	-10.2	Vert
			+0.0	+0.0	+0.0	+0.0	91				154
			-35.1	+36.7	+5.3	+0.7					
			+0.3	-18.2							
7	8190.005M	52.7	+0.0	+0.0	+1.3	+0.0	+0.0	43.7	54.0	-10.3	Vert
			+0.0	+0.0	+0.0	+0.0	91				154
			-35.1	+36.7	+5.3	+0.7					
			+0.3	-18.2							
8	614.000M	12.7	+1.6	+2.1	+0.3	+18.5	+0.0	35.2	46.0	-10.8	Horiz
			+0.0	+0.0	+0.0	+0.0	100				145
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0							
9	8126.978M	51.8	+0.0	+0.0	+1.3	+0.0	+0.0	42.8	54.0	-11.2	Vert
			+0.0	+0.0	+0.0	+0.0	91				154
			-35.1	+36.7	+5.3	+0.7					
			+0.3	-18.2							
10	960.000M	14.3	+2.2	+2.5	+0.4	+22.8	+0.0	42.2	54.0	-11.8	Horiz
			+0.0	+0.0	+0.0	+0.0	100				145
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0							
11	4634.049M	53.8	+0.0	+0.0	+0.9	+0.0	+0.0	40.3	54.0	-13.7	Vert
			+0.0	+0.0	+0.0	+0.0	6				159
			-34.1	+32.6	+4.3	+0.5					
			+0.5	-18.2							
12	4575.109M	53.8	+0.0	+0.0	+0.9	+0.0	+0.0	40.0	54.0	-14.0	Vert
			+0.0	+0.0	+0.0	+0.0	6				159
			-34.1	+32.5	+4.2	+0.5					
			+0.4	-18.2							
13	4515.061M	53.7	+0.0	+0.0	+0.9	+0.0	+0.0	39.9	54.0	-14.1	Vert
			+0.0	+0.0	+0.0	+0.0	6				159
			-34.1	+32.5	+4.2	+0.5					
			+0.4	-18.2							
14	4550.060M	53.7	+0.0	+0.0	+0.9	+0.0	+0.0	39.8	54.0	-14.2	Vert
			+0.0	+0.0	+0.0	+0.0	6				159
			-34.1	+32.5	+4.2	+0.5					
			+0.3	-18.2							
15	928.000M	41.4	+2.1	+2.4	+0.4	+22.4	+0.0	68.7	83.6	-14.9	Horiz
			+0.0	+0.0	+0.0	+0.0	100				145
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0							
16	902.000M	40.1	+2.1	+2.4	+0.3	+22.6	+0.0	67.5	83.6	-16.1	Horiz
			+0.0	+0.0	+0.0	+0.0	100				145
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0							
17	248.000M	12.7	+1.0	+1.5	+0.2	+11.3	+0.0	26.7	46.0	-19.3	Horiz
			+0.0	+0.0	+0.0	+0.0	263				113
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0							
18	3612.059M	49.3	+0.0	+0.0	+0.8	+0.0	+0.0	31.9	54.0	-22.1	Horiz
			+0.0	+0.0	+0.0	+0.0	147				146
			-34.2	+29.8	+3.6	+0.4					
			+0.4	-18.2							

19	3707.197M	48.7	+0.0	+0.0	+0.7	+0.0	+0.0	31.8	54.0	-22.2	Horiz
			+0.0	+0.0	+0.0	+0.0	152				147
			-34.1	+30.1	+3.8	+0.5					
			+0.3	-18.2							
20	3659.960M	48.8	+0.0	+0.0	+0.7	+0.0	+0.0	31.5	54.0	-22.5	Horiz
			+0.0	+0.0	+0.0	+0.0	149				154
			-34.2	+29.9	+3.7	+0.5					
			+0.3	-18.2							
21	3640.010M	48.2	+0.0	+0.0	+0.7	+0.0	+0.0	31.0	54.0	-23.0	Horiz
			+0.0	+0.0	+0.0	+0.0	147				146
			-34.2	+29.9	+3.7	+0.5					
			+0.4	-18.2							
22	5417.951M	41.0	+0.0	+0.0	+1.0	+0.0	+0.0	28.1	54.0	-25.9	Vert
			+0.0	+0.0	+0.0	+0.0	360				155
			-34.2	+33.1	+4.5	+0.6					
			+0.3	-18.2							
23	5459.715M	40.7	+0.0	+0.0	+1.0	+0.0	+0.0	27.8	54.0	-26.2	Vert
			+0.0	+0.0	+0.0	+0.0	360				155
			-34.2	+33.1	+4.5	+0.6					
			+0.3	-18.2							
24	860.800M	13.8	+2.0	+2.3	+0.3	+22.1	+0.0	40.5	83.6	-43.1	Vert
			+0.0	+0.0	+0.0	+0.0					99
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
25	6404.947M	48.2	+0.0	+0.0	+1.2	+0.0	+0.0	37.2	83.6	-46.4	Vert
			+0.0	+0.0	+0.0	+0.0	24				150
			-34.2	+34.6	+4.7	+0.6					
			+0.3	-18.2							
26	6320.985M	46.7	+0.0	+0.0	+1.3	+0.0	+0.0	36.1	83.6	-47.5	Vert
			+0.0	+0.0	+0.0	+0.0	24				150
			-34.2	+34.8	+4.7	+0.6					
			+0.4	-18.2							
27	6370.005M	46.8	+0.0	+0.0	+1.3	+0.0	+0.0	36.0	83.6	-47.6	Vert
			+0.0	+0.0	+0.0	+0.0	24				150
			-34.2	+34.7	+4.7	+0.6					
			+0.3	-18.2							
28	559.200M	13.0	+1.5	+2.0	+0.3	+18.3	+0.0	35.1	83.6	-48.5	Horiz
			+0.0	+0.0	+0.0	+0.0					99
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
29	6487.576M	46.3	+0.0	+0.0	+1.2	+0.0	+0.0	35.0	83.6	-48.6	Vert
			+0.0	+0.0	+0.0	+0.0	24				150
			-34.2	+34.4	+4.6	+0.6					
			+0.3	-18.2							
30	41.050M	12.9	+0.4	+0.5	+0.1	+0.0	+0.0	33.7	83.6	-49.9	Horiz
			+0.0	+13.8	+6.0	+0.0	360				107
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0	+0.0	+0.0					
31	1853.770M	54.3	+0.0	+0.0	+0.5	+0.0	+0.0	31.6	83.6	-52.0	Vert
			+0.0	+0.0	+0.0	+0.0	62				157
			-35.1	+27.0	+2.5	+0.3					
			+0.3	-18.2							

32	102.420M	13.0	+0.6	+1.2	+0.1	+0.0	+0.0	31.2	83.6	-52.4	Horiz
			+0.0	+10.3	+6.0	+0.0	360				107
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0							
33	194.900M	13.1	+0.8	+1.4	+0.2	+0.0	+0.0	30.5	83.6	-53.1	Horiz
			+0.0	+9.0	+6.0	+0.0	232				107
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0							
34	1806.010M	52.9	+0.0	+0.0	+0.5	+0.0	+0.0	30.1	83.6	-53.5	Vert
			+0.0	+0.0	+0.0	+0.0	62				157
			-35.1	+26.8	+2.5	+0.3					
			+0.4	-18.2							
35	1829.530M	52.7	+0.0	+0.0	+0.5	+0.0	+0.0	30.0	83.6	-53.6	Vert
			+0.0	+0.0	+0.0	+0.0	62				157
			-35.1	+26.9	+2.5	+0.3					
			+0.4	-18.2							
36	1819.930M	52.3	+0.0	+0.0	+0.5	+0.0	+0.0	29.6	83.6	-54.0	Vert
			+0.0	+0.0	+0.0	+0.0	62				157
			-35.1	+26.9	+2.5	+0.3					
			+0.4	-18.2							
37	5490.274M	41.5	+0.0	+0.0	+1.0	+0.0	+0.0	28.7	83.6	-54.9	Vert
			+0.0	+0.0	+0.0	+0.0	360				155
			-34.1	+33.1	+4.5	+0.6					
			+0.3	-18.2							
38	5560.800M	39.1	+0.0	+0.0	+1.0	+0.0	+0.0	26.6	83.6	-57.0	Vert
			+0.0	+0.0	+0.0	+0.0	360				155
			-34.1	+33.4	+4.5	+0.6					
			+0.3	-18.2							
39	100.395k	32.6	+0.0	+0.1	+0.0	+0.0	-80.0	-37.4	27.6	-65.0	Paral
			+0.0	+0.0	+0.0	+9.9					102
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0							
40	9.762M	11.8	+0.1	+0.2	+0.0	+0.0	-40.0	-18.7	83.6	-102.3	Perpe
			+0.0	+0.0	+0.0	+9.2					102
			+0.0	+0.0	+0.0	+0.0					
			+0.0	+0.0							

## Band Edge

### Band Edge Summary

Frequency (MHz)	Modulation	Ant. Type	Field Strength (dBuV/m @3m)	Limit (dBuV/m @3m)	Results
614	Worst Case	Integral	33.7 (QP)	<46	Pass
902	FSK 150kbps Power Level 3	Integral	68.8 (QP)	100.9	Pass
902	FSK 10kbps Power Level 3	Integral	78.1 (QP)	100.9	Pass
902	OOK Power Level 3	Integral	84.7 (Peak)	99.0	Pass
902	OOK Power level 1	Integral	67.5 (Peak)	83.6	Pass
928	FSK 150kbps Power Level 3	Integral	70.0 (QP)	100.9	Pass
928	FSK 10kbps Power Level 3	Integral	79.3 (QP)	100.9	Pass
928	OOK Power Level 3	Integral	83.9 (Peak)	99.0	Pass
928	OOK Power level 1	Integral	68.7 (Peak)	83.6	Pass
960	Worst Case	Integral	50.7 (QP)	<54	Pass

Worst case: OOK Power Level 3

Emissions limits outside of restricted bands are 20dB from maximum measured inband emissions in 100kHz.

## Test Setup / Conditions / Data

Test Location: CKC Laboratories, Inc. • 22116 23rd Drive SE Suite A • Bothell, WA 98021 • 800-500-4EMC (4362)  
 Customer: **Itron, Inc.**  
 Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
 Work Order #: **99317** Date: 1/25/2017  
 Test Type: **Maximized Emissions** Time: 15:25:43  
 Tested By: Steven Pittsford Sequence#: 4  
 Software: EMITest 5.03.02

***Equipment Tested:***

Device	Manufacturer	Model #	S/N
Configuration 1			

***Support Equipment:***

Device	Manufacturer	Model #	S/N
Configuration 1			

***Test Conditions / Notes:***

Temperature: 20-24°C

Relative Humidity: 21-32%

Frequency range investigated: Band Edge

Transmitter Frequency: 902.4-927.6MHz

**Modulation: FSK 150kbps**

**Firmware Power Level: 3**

EUT Firmware: App Version: 1.18.3.0, CSL Version: 2.22.1.0

Antenna Type: Internal Trace

Antenna Gain: -0.94dBi


Duty Cycle: Max

Test Method: ANSI C63.10 (2013)

The EUT is a transmitter operating hopping in band. The EUT is battery operated, fresh batteries installed.

The EUT has no IO ports.

The EUT orientation selected based on manufacturer declared fixed installation orientation. Hopping operation selected as worst case based on previously collected data.

Itron, Inc. WO#: 99317 Sequence#: 4 Date: 1/25/2017  
 15.247(d) / 15.209 Radiated Spurious Emissions Test Distance: 3 Meters Horiz

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP05360	Cable	RG214	11/30/2016	11/30/2018
T2	ANP05963	Cable	RG-214	2/15/2016	2/15/2018
T3	ANP06540	Cable	Heliax	10/29/2015	10/29/2017
T4	AN01816	Log Periodic Antenna-ANSI 63.5	3146	1/8/2016	1/8/2018
	AN02872	Spectrum Analyzer	E4440A	11/18/2015	11/18/2017

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

#	Freq MHz	Rdng dB $\mu$ V	T1 dB	T2 dB	T3 dB	T4 dB	Dist Table	Corr dB $\mu$ V/m	Spec dB $\mu$ V/m	Margin dB	Polar Ant
1	614.000M	12.1	+1.6	+2.1	+0.3	+18.5	+0.0	34.6	46.0	-11.4	Horiz
2	960.000M QP	8.1	+2.2	+2.5	+0.4	+22.8	+0.0	36.0	54.0	-18.0	Horiz
3	928.004M QP	42.7	+2.1	+2.4	+0.4	+22.4	+0.0	70.0	100.9	-30.9	Horiz
4	901.992M QP	41.4	+2.1	+2.4	+0.3	+22.6	+0.0	68.8	100.9	-32.1	Horiz



Test Location: CKC Laboratories, Inc. • 22116 23rd Drive SE Suite A • Bothell, WA 98021 • 800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
Work Order #: **99317** Date: 1/25/2017  
Test Type: **Maximized Emissions** Time: 14:09:04  
Tested By: Steven Pittsford Sequence#: 3  
Software: EMITest 5.03.02

**Equipment Tested:**

Device	Manufacturer	Model #	S/N
Configuration 2			

**Support Equipment:**

Device	Manufacturer	Model #	S/N
Configuration 2			

**Test Conditions / Notes:**

Temperature: 20-24°C

Relative Humidity: 21-32%

Frequency range investigated: Band Edge

Transmitter Frequency: 902.2 to 927.75 MHz

**Modulation: FSK 10kbps**

**Firmware Power Level: 3**

EUT Firmware: App Version: 1.18.3.0, CSL Version: 2.22.1.0

Antenna Type: Internal Trace

Antenna Gain: -0.94dBi


Duty Cycle: Max

Test Method: ANSI C63.10 (2013)

The EUT is a transmitter operating hopping in band. The EUT is battery operated, fresh batteries installed.

The EUT has no IO ports.

The EUT orientation selected based on manufacturer declared fixed installation orientation. Hopping operation selected as worst case based on previously collected data.

Itron, Inc. WO#: 99317 Sequence#: 3 Date: 1/25/2017  
 15.247(d) / 15.209 Radiated Spurious Emissions Test Distance: 3 Meters Horiz

**Test Equipment:**

ID	Asset #/Serial #	Description	Model	Calibration Date	Cal Due Date
T1	ANP05360	Cable	RG214	11/30/2016	11/30/2018
T2	ANP05963	Cable	RG-214	2/15/2016	2/15/2018
T3	ANP06540	Cable	Heliax	10/29/2015	10/29/2017
T4	AN01816	Log Periodic Antenna-ANSI 63.5	3146	1/8/2016	1/8/2018
	AN02872	Spectrum Analyzer	E4440A	11/18/2015	11/18/2017

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

#	Freq MHz	Rdng dB $\mu$ V	T1 dB	T2 dB	T3 dB	T4 dB	Dist Table	Corr dB $\mu$ V/m	Spec dB $\mu$ V/m	Margin dB	Polar Ant
1	614.000M	10.5	+1.6	+2.1	+0.3	+18.5	+0.0	33.0	46.0	-13.0	Horiz
2	960.012M QP	7.9	+2.2	+2.5	+0.4	+22.8	+0.0	35.8	54.0	-18.2	Horiz
3	928.000M QP	52.0	+2.1	+2.4	+0.4	+22.4	+0.0	79.3	100.9	-21.6	Horiz
4	901.992M QP	50.7	+2.1	+2.4	+0.3	+22.6	+0.0	78.1	100.9	-22.8	Horiz



Test Location: CKC Laboratories, Inc. • 22116 23rd Drive SE Suite A • Bothell, WA 98021 • 800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
Work Order #: **99317** Date: 1/5/2017  
Test Type: **Maximized Emissions** Time: 11:56:40  
Tested By: Steven Pittsford Sequence#: 3  
Software: EMITest 5.03.02

**Equipment Tested:**

Device	Manufacturer	Model #	S/N
Configuration 3			

**Support Equipment:**

Device	Manufacturer	Model #	S/N
Configuration 3			

**Test Conditions / Notes:**

Temperature: 20-24°C

Relative Humidity: 21-32%

Frequency range investigated: Band Edge

Transmitter Frequency: 903-926.8MHz

**Modulation: OOK**

**Firmware Power Level: 3**

EUT Firmware: App Version: 1.18.3.0, CSL Version: 2.22.1.0

Antenna Type: Internal Trace

Antenna Gain: -0.94dBi


Duty Cycle: Max

Test Method: ANSI C63.10 (2013)

The EUT is a transmitter operating hopping in band. The EUT is battery operated, fresh batteries installed.

The EUT has no IO ports.

The EUT orientation selected based on manufacturer declared fixed installation orientation. Hopping operation selected as worst case based on previously collected data.

Itron, Inc. WO#: 99317 Sequence#: 3 Date: 1/5/2017  
 15.247(d) / 15.209 Radiated Spurious Emissions Test Distance: 3 Meters Horiz

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP05360	Cable	RG214	11/30/2016	11/30/2018
T2	ANP05963	Cable	RG-214	2/15/2016	2/15/2018
T3	ANP06540	Cable	Heliax	10/29/2015	10/29/2017
T4	AN01816	Log Periodic Antenna-ANSI 63.5	3146	1/8/2016	1/8/2018
T5	AN02872	Spectrum Analyzer	E4440A	11/18/2015	11/18/2017

**Measurement Data:**

Reading listed by margin.

Test Distance: 3 Meters

#	Freq MHz	Rdng dBµV	T1 dB	T2 dB	T3 dB	T4 dB	Dist Table	Corr dBµV/m	Spec dBµV/m	Margin dB	Polar
1	960.026M	22.8	+2.2	+2.5	+0.4	+22.8	+0.0	50.7	54.0	-3.3	Horiz
	QP		+0.0				100				145
2	614.000M	11.2	+1.6	+2.1	+0.3	+18.5	+0.0	33.7	46.0	-12.3	Horiz
			+0.0				100				145
3	902.000M	57.3	+2.1	+2.4	+0.3	+22.6	+0.0	84.7	99.0	-14.3	Horiz
			+0.0				100				145
4	928.000M	56.6	+2.1	+2.4	+0.4	+22.4	+0.0	83.9	99.0	-15.1	Horiz
			+0.0				100				145



Test Location: CKC Laboratories, Inc. • 22116 23rd Drive SE Suite A • Bothell, WA 98021 • 800-500-4EMC (4362)  
Customer: **Itron, Inc.**  
Specification: **15.247(d) / 15.209 Radiated Spurious Emissions**  
Work Order #: **99317** Date: 1/5/2017  
Test Type: **Maximized Emissions** Time: 13:40:12  
Tested By: Steven Pittsford Sequence#: 4  
Software: EMITest 5.03.02

**Equipment Tested:**

Device	Manufacturer	Model #	S/N
Configuration 4			

**Support Equipment:**

Device	Manufacturer	Model #	S/N
Configuration 4			

**Test Conditions / Notes:**

Temperature: 20-24°C

Relative Humidity: 21-32%

Frequency range investigated: Band Edge

Transmitter Frequency: 903-926.8MHz

**Modulation: OOK**

**Firmware Power Level: 1**

EUT Firmware: App Version: 1.18.3.0, CSL Version: 2.22.1.0

Antenna Type: Internal Trace

Antenna Gain: 1.99dBi


Duty Cycle: Max

Test Method: ANSI C63.10 (2013)

The EUT is a transmitter operating hopping in band. The EUT is battery operated, fresh batteries installed.

The EUT has no IO ports.

The EUT orientation selected based on manufacturer declared fixed installation orientation. Hopping operation selected as worst case based on previously collected data.

Itron, Inc. WO#: 99317 Sequence#: 4 Date: 1/5/2017  
 15.247(d) / 15.209 Radiated Spurious Emissions Test Distance: 3 Meters Horiz

**Test Equipment:**

ID	Asset #	Description	Model	Calibration Date	Cal Due Date
T1	ANP05360	Cable	RG214	11/30/2016	11/30/2018
T2	ANP05963	Cable	RG-214	2/15/2016	2/15/2018
T3	ANP06540	Cable	Heliax	10/29/2015	10/29/2017
T4	AN01816	Log Periodic Antenna-ANSI 63.5	3146	1/8/2016	1/8/2018
T5	AN02872	Spectrum Analyzer	E4440A	11/18/2015	11/18/2017

**Measurement Data:**



Reading listed by margin.

Test Distance: 3 Meters



#	Freq MHz	Rdng dB $\mu$ V	T1 dB	T2 dB	T3 dB	T4 dB	Dist Table	Corr dB $\mu$ V/m	Spec dB $\mu$ V/m	Margin dB	Polar
1	614.000M	12.7	+1.6 +0.0	+2.1	+0.3	+18.5	+0.0 100	35.2	46.0	-10.8 145	Horiz
2	960.000M	14.3	+2.2 +0.0	+2.5	+0.4	+22.8	+0.0 100	42.2	54.0	-11.8 145	Horiz
3	928.000M	41.4	+2.1 +0.0	+2.4	+0.4	+22.4	+0.0 100	68.7	83.6	-14.9 145	Horiz
4	902.000M	40.1	+2.1 +0.0	+2.4	+0.3	+22.6	+0.0 100	67.5	83.6	-16.1 145	Horiz



## Band Edge Plots

### Configuration 1





Configuration 2



Configuration 3


### Configuration 4



Test Setup Photos



Below 1GHz



Above 1GHz

## APPENDIX A: CUSTOMER PROVIDED INFORMATION

### 15.35(c) Duty Cycle Correction Factor

Applies to OOK Power Level 1 Only

Test Data Summary			
Antenna Port	Operational Mode	Measured On Time (mS / P <sub>obs</sub> )	Calculated DCCF (dB)
Integral	OOK Power Level 1	12.2	18.2

Observation Period, P<sub>obs</sub> is the duration of the pulse train or maximum 100mS

Measured results are calculated as follows:

$$On\ Time = \left( \sum_{Bursts} RF\ Burst\ On\ Time + \sum_{Control} Control\ Signal\ On\ time \right) \Big|_{P_{obs} \text{ (max 100ms)}}$$


Measured Values:

Parameter	Value
Observation Period (P <sub>obs</sub> ):	100
Number of RF Bursts / P <sub>obs</sub> :	1
On time of RF Burst:	12.2
Number of Control or other signals / P <sub>obs</sub> :	0
On time of Control or other Signals:	0
Total Measured On Time:	12.2


Duty Cycle Correction Factor (DCCF) is calculated in accordance with ANSI C63.10:

$$DCCF = 20 \cdot \log \left( \frac{On\ Time}{P_{obs}} \right)$$

## Plots



DCCF Zoom In



DCCF Zoom Out

## SUPPLEMENTAL INFORMATION

### Measurement Uncertainty

Uncertainty Value	Parameter
4.73 dB	Radiated Emissions
3.34 dB	Mains Conducted Emissions
3.30 dB	Disturbance Power

Reported uncertainties represent expanded uncertainties expressed at approximately the 95% confidence level using a coverage factor of  $k=2$ . Compliance is deemed to occur provided measurements are below the specified limits.

### Emissions Test Details

#### TESTING PARAMETERS

Unless otherwise indicated, the following configuration parameters are used for equipment setup: The cables were routed consistent with the typical application by varying the configuration of the test sample. Interface cables were connected to the available ports of the test unit. The effect of varying the position of the cables was investigated to find the configuration that produced maximum emissions. Cables were of the type and length specified in the individual requirements. The length of cable that produced maximum emissions was selected.

The equipment under test (EUT) was set up in a manner that represented its normal use, as shown in the setup photographs. Any special conditions required for the EUT to operate normally are identified in the comments that accompany the emissions tables.

The emissions data was taken with a spectrum analyzer or receiver. Incorporating the applicable correction factors for distance, antenna, cable loss and amplifier gain, the data was reduced as shown in the table below. The corrected data was then compared to the applicable emission limits. Preliminary and final measurements were taken in order to ensure that all emissions from the EUT were found and maximized.

#### CORRECTION FACTORS

The basic spectrum analyzer reading was converted using correction factors as shown in the highest emissions readings in the tables. For radiated emissions in  $\text{dB}\mu\text{V}/\text{m}$ , the spectrum analyzer reading in  $\text{dB}\mu\text{V}$  was corrected by using the following formula. This reading was then compared to the applicable specification limit. Individual measurements were compared with the displayed limit value in the margin column. The margin was calculated based on subtracting the limit value from the corrected measurement value; a positive margin represents a measurement exceeding the limit, while a negative margin represents a measurement less than the limit.

SAMPLE CALCULATIONS	
Meter reading	( $\text{dB}\mu\text{V}$ )
+ Antenna Factor	( $\text{dB}/\text{m}$ )
+ Cable Loss	(dB)
- Distance Correction	(dB)
- Preamplifier Gain	(dB)
= Corrected Reading	( $\text{dB}\mu\text{V}/\text{m}$ )

## TEST INSTRUMENTATION AND ANALYZER SETTINGS

The test instrumentation and equipment listed were used to collect the emissions data. A spectrum analyzer or receiver was used for all measurements. Unless otherwise specified, the following table shows the measuring equipment bandwidth settings that were used in designated frequency bands. For testing emissions, an appropriate reference level and a vertical scale size of 10 dB per division were used.

MEASURING EQUIPMENT BANDWIDTH SETTINGS PER FREQUENCY RANGE			
TEST	BEGINNING FREQUENCY	ENDING FREQUENCY	BANDWIDTH SETTING
CONDUCTED EMISSIONS	150 kHz	30 MHz	9 kHz
RADIATED EMISSIONS	9 kHz	150 kHz	200 Hz
RADIATED EMISSIONS	150 kHz	30 MHz	9 kHz
RADIATED EMISSIONS	30 MHz	1000 MHz	120 kHz
RADIATED EMISSIONS	1000 MHz	>1 GHz	1 MHz

## SPECTRUM ANALYZER/RECEIVER DETECTOR FUNCTIONS

The notes that accompany the measurements contained in the emissions tables indicate the type of detector function used to obtain the given readings. Unless otherwise noted, all readings were made in the "positive peak" detector mode. Whenever a "quasi-peak" or "average" reading was recorded, the measurement was annotated with a "QP" or an "Ave" on the appropriate rows of the data sheets. In cases where quasi-peak or average limits were employed and data exists for multiple measurement types for the same frequency then the peak measurement was retained in the report for reference, however the numbering for the affected row was removed and an arrow or caret ("^") was placed in the far left-hand column indicating that the row above takes precedence for comparison to the limit. The following paragraphs describe in more detail the detector functions and when they were used to obtain the emissions data.

### Peak

In this mode, the spectrum analyzer or receiver recorded all emissions at their peak value as the frequency band selected was scanned. By combining this function with another feature called "peak hold," the measurement device had the ability to measure intermittent or low duty cycle transient emission peak levels. In this mode the measuring device made a slow scan across the frequency band selected and measured the peak emission value found at each frequency across the band.

### Quasi-Peak

Quasi-peak measurements were taken using the quasi-peak detector when the true peak values exceeded or were within 2 dB of a quasi-peak specification limit. Additional QP measurements may have been taken at the discretion of the operator.

### Average

Average measurements were taken using the average detector when the true peak values exceeded or were within 2 dB of an average specification limit. Additional average measurements may have been taken at the discretion of the operator. If the specification or test procedure requires trace averaging, then the averaging was performed using 100 samples or as required by the specification. All other average measurements are performed using video bandwidth averaging. To make these measurements, the test engineer reduces the video bandwidth on the measuring device until the modulation of the signal is filtered out. At this point the measuring device is set into the linear mode and the scan time is reduced.