



MAXIMUM PERMISSIBLE EXPOSURE REPORT (Measurement)

FOR THE

Water Endpoint
Models: RIVAWA and RIVAWRA

Report No.: 105540-20

Date of issue: July 8, 2021

PREPARED FOR:

Jay Holcomb
2111 N. Molter Road
Liberty Lake WA 99019

PREPARED BY:

Michael Atkinson
CKC Laboratories, Inc.
5046 Sierra Pines Drive
Mariposa, CA 95338

The test data contained in this report documents the observed testing parameters pertaining to and are relevant for only the sample equipment tested in the agreed upon operational mode(s) and configuration(s) as identified herein. Compliance assessment remains the client's responsibility. This report may not be used to claim product endorsement by A2LA or any government agencies. This test report has been authorized for release under quality control from CKC Laboratories, Inc.

Steve Behm
Director of Quality Assurance & Engineering Services
CKC Laboratories, Inc.



Purpose:

To demonstrate compliance with United States, Canada, Australia and/or European Union RF Exposure requirements for Mobile Equipment (devices used >20cm from the body), where MPE measurements apply.

Device and Antenna Operating Configuration:

EUT is connected to support laptop via serial to USB adapter, the laptop is running Command Line Interface Tool software to turn on Tx. North American power level settings were used as representative of worst case. Low, Mid, and High channels investigated, worst case reported.

Test Procedure:

This equipment is evaluated in accordance with the guidelines set forth in KDB 447498 & ANSI C95.1 for the US, Health Canada Safety Code 6 & RSS 102 for Canada, ARPANSA RPS S-1 for AU.

Other Considerations:

Report considers stand-alone configuration only. RF Exposure limits are calculated at the mid-point of each operating band.

The gain values listed in this report were calculated at time of test by measurements collected by the test lab. The test lab collected Radiated and RF Conducted fundamental values, and from these values the manufacturer calculated antenna gain values. This same procedure was performed on previous reports and for the original filing. The antenna design has not changed since the original filing, and with measurement and part tolerances from EUT sample to sample, the measured gain values may vary from the original filing.

Referenced Test Reports:

The following test reports were referenced in conjunction with this assessment:

105540-2A
105540-3A
105540-4A

MPE Measurements

Operational Details					
Power Reported is:	<input checked="" type="checkbox"/> Peak <input type="checkbox"/> Average				
Limit Used is:	<input type="checkbox"/> General Population <input type="checkbox"/> Occupational Exposure				
Operating Band MHz	Power dBm	Ant Type/Gain dBi	EIRP dBm	TX Simultaneous	Antenna Configuration
902.3 to 926.9 (US and Canada) 915.2 to 927.8 (Australia)	28.1 (US and Canada power settings worst case)	5.2 Integral Omni 2.5 External Omni	33.3*	No	Two configurations investigated as worst case: -Remote unit, internal antenna, 2 battery -Pit unit, plastic lid antenna, 2 battery

* Note: Australia EIRP was 122.2 dBuV/m / 27 dBm

Test Equipment					
Asset	Description	Manufacturer	Model	Cal Date	Cal Due
03741	Laser Data Interface	ETS Lindgren	HI-6113	9/1/2020	9/1/2022
03452	Field Probe	ETS-Lindgren	HI-6153	2/19/2020	2/19/2022

MPE Measurements for Static Fields (Free Space Configuration) (US)

For equipment where the fields are invariant in time, measurements are performed at a fixed height between 1.0m to 1.8m representing worst case measurements as determined by preliminary assessment.

Distance (m)	Height (m)	Measured Exposure mW/cm ²	Limit mW/cm ²	Result
0.2 (Remote Unit)	1	0.03	0.61	Pass
0.2 (Pit Unit antenna)	1	0.02	0.61	Pass

MPE Measurements for Static Fields (Free Space Configuration) (CAN)

For equipment where the fields are invariant in time, measurements are performed at a fixed height between 1.0m to 1.8m representing worst case measurements as determined by preliminary assessment.

Distance (m)	Height (m)	Measured Exposure W/m ²	Limit W/m ²	Result
0.2 (Remote Unit)	1	0.3	2.77	Pass
0.2 (Pit Unit antenna)	1	0.2	2.77	Pass

MPE Measurements for Static Fields (Free Space Configuration) (AUS)

For equipment where the fields are invariant in time, measurements are performed at a fixed height between 1.0m to 1.8m representing worst case measurements as determined by preliminary assessment.

Distance (m)	Height (m)	Measured Exposure W/m ²	Limit W/m ²	Result
0.2 (Remote Unit)	1	0.3	4.58	Pass
0.2 (Pit Unit antenna)	1	0.2	4.58	Pass

Summary:**MPE Measurement Results:**

Equipment demonstrating compliance with MPE measurement have been evaluated for use under mobile RF exposure configurations as identified herein. Additional configurations including collocation or simultaneous transmission with other transmitters (including necessary separation distances) are subject to further assessment. It is assumed that the manufacturer shall design the equipment such that the minimum separation distance of 20cm (or greater, as listed above) is met or that the manufacturer provides a protection guide (e.g. installation instructions) to the end user such that the antenna(s) may be installed in accordance with the manufacturer's instructions in such a manner to maintain the minimum separation distance.

General Comments:

The absorption and distribution of Electromagnetic energy in the body is a very complex phenomena that depends on the mass, shape and physiological condition of the body; the orientation of the body with respect to the fields; and, the electrical properties of the body and the environment. Variables that may play a substantial role in possible biological effects are those that characterize the environment (including but not limited to: ambient temperature, air velocity, relative humidity and body insulation); and those that characterize the individual (including but not limited to: age, gender, activity level and existing debilitation or disease). Because innumerable factors may interact to determine specific biological effects of exposure to electromagnetic fields, any protection guide should consider both intended and unintended operational environments and provide guidance for installation and use of the product such that proper separation distances can be maintained. (ANSI C95.1)

APPENDIX A - Assessment Procedure

TEST CONFIGURATION

The EUT antenna is placed in a configuration typical of normal installation. Where antenna mounting is required, non-conductive materials are used for support structures. In the special case of magnetically mounted vehicle antennas, a reference ground plane is used to simulate actual installation. In order to limit external interference effects, the test is performed in a semi-anechoic chamber. The EUT equipment is setup in a configuration representative of normal use. Support equipment for the measurement instruments are located outside of the testing area.

TEST PROCEDURE

Measurements are performed using a broadband detector with three orthogonal measurement axes. Values recorded are RMS based on the maximum measurements. To determine the direction of the maximum measurement, the detector is moved throughout the RF field generated by the transmit antenna. The detector is positioned at a minimum of 12 radials and at varying distances from the antenna along each radial. The area of maximum RF energy determined during preliminary investigation shall be used for the remainder of the tests. In the case where a transmitter may have multiple frequency bands, the preliminary investigation shall be repeated for each band.

For time varying fields, the appropriate averaging time is used. For spatially uniform fields, the measurement height is selected based on maximum preliminary measurements.

For spatially non-uniform fields (e.g. distances close to a magnetically mounted vehicle antenna), spatial averaging may be performed. The method for performing spatially averaged measurements is as follows:

1. Determine the direction of the maximum measurement.
2. At a specific distance measure vertically from the floor 5 points comprising a linear cross section of an adult human body, beginning at 0.2m and at each 40cm up to 1.8m.
3. Calculate the average of the measurements and compare with the established limit.

Since the applicable limits exist in several different measurement units, the following outlines the most common calculations used for determining the spatially averaged field.

Case 1: Where limits are applied in electric field strength (V/m), the spatially averaged electric field strength along a grid of n points is calculated using:

$$E = \left[\frac{1}{n} \sum_{i=1}^n E_i^2 \right]^{\frac{1}{2}}$$


Case 2: Where limits are applied in units of power density (mW/cm^2), assuming measurements are made in the far field, where the E and H vectors are mutually orthogonal, power density is first calculated using:

$$S = \frac{E^2}{3770}$$

And the spatially averaged power density along a grid of n points is calculated using:

$$S = \frac{1}{n} \sum_{i=1}^n S_i$$


The following diagram is an example of the grid used to perform local measurements for RF exposure evaluation over a whole-body spatial average.



The following diagram is an example of the setup used for most tests, excluding magnetically mounted vehicle antennas.

Setup Used for RF Evaluation Measurements

(excluding magnetically mounted vehicle antennas)




Top View

¹ Source: IC GL-01

The following diagram is an example of the setup used for vehicle-mounted antennas. In the case where vehicle glass mounted antennas are used, this setup shall not apply. The letter X represents the test distance used for RF exposure measurements. The distance X is measured from the phase center of the transmitting antenna to the volumetric center of the measurement instrument. In order to more accurately simulate normal installation, the antenna ground plane is not bonded to the ground reference plane. The transmitting antenna is placed in the center of the antenna ground plane.

Setup Used for Vehicle-Mounted Antennas



Top View

APPENDIX B - RF Exposure Limits

United States Compliance Requirements (1.1310):

RF Exposure Evaluation Limits Occupational / Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1	6
300-1500	---	---	f/300	6
1500-100,000	---	---	5.0	6

RF Exposure Evaluation Limits General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	---	---	f/1500	30
1500-100,000	---	---	1.0	30

* Plane wave equivalent power density

Limit is calculated based on the mid-band frequency used in the operating frequency range.

Stand-Alone Evaluation Exemption Levels:

In accordance with KDB 447498 D01 v05r02

Max Output Power at Exemption Limit (mW)		
Frequency (MHz)	$d \leq 50mm$	$50mm < d \leq 20cm$
<100	$\frac{1}{2} \cdot \left(\frac{R \cdot 50}{\sqrt{0.1}} \right) \cdot \left(1 + \text{LOG} \left(\frac{100}{f_{MHz}} \right) \right)$	$\left(\frac{R \cdot 50}{\sqrt{0.1}} + (d - 50) \frac{100}{150} \right) \cdot \left(1 + \text{LOG} \left(\frac{100}{f_{MHz}} \right) \right)$
100-1500	$\left(\frac{R \cdot d}{\sqrt{f_{GHz}}} \right)$	$\left(\frac{R \cdot 50}{\sqrt{f_{GHz}}} + (d - 50) \frac{f_{MHz}}{150} \right)$
1500-6000		$\left(\frac{R \cdot 50}{\sqrt{f_{GHz}}} + (d - 50) \cdot 10 \right)$

R is the allowed ratio: 3 for 1-g SAR and 7.5 for 10-g extremity SAR.

d is distance in mm, rounded to the nearest mm.

Canadian Compliance Requirements (RSS-102):

RF Exposure Evaluation Limits
Occupational / Controlled Exposure:

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m ²)	Averaging Time (minutes)
0.003-10	170	180	--	Instantaneous
0.1-10	--	1.6 / f	--	6
1.29-10	193 / f ^{0.5}	--	--	6
10-20	61.4	0.163	10	6
20-48	129.8 / f ^{0.5}	0.3444 / f ^{0.25}	44.72 / f ^{0.5}	6
48-100	49.33	0.1309	6.455	6
100-6000	15.60 f ^{0.25}	0.04138 f ^{0.25}	0.6455 f ^{0.5}	6
6000-15000	137	0.364	50	6
15000-150,000	137	0.364	50	616000 / f ^{1.2}
150,000-300,000	0.354 f ^{0.5}	9.40x10 ⁻⁴ f ^{0.5}	3.33x10 ⁻⁴ f	616000 / f ^{1.2}

RF Exposure Evaluation Limits
General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m ²)	Averaging Time (minutes)
0.003-10	83	90	--	Instantaneous
0.1-10	--	0.73 / f	--	6
1.1-10	87 / f ^{0.5}	--	--	6
10-20	27.46	0.0728	2	6
20-48	58.07 / f ^{0.25}	0.1540 / f ^{0.25}	8.944 / f ^{0.5}	6
48-300	22.06	0.05852	1.291	6
300-6000	3.142 f ^{0.3417}	0.008335 f ^{0.3417}	0.02619 f ^{0.6834}	6
6000-15000	61.4	0.163	10	6
15000-150,000	61.4	0.163	10	616000 / f ^{1.2}
150,000-300,000	0.158 f ^{0.5}	4.21x10 ⁻⁴ f ^{0.5}	6.67x10 ⁻⁵ f	616000 / f ^{1.2}


Stand-Alone Evaluation Exemption Levels:

Freq(MHz)	Exemption Limits (mW) at Separation Distance (mm)									
	≤5	10	15	20	25	30	35	40	45	≥50
≤300	71	101	132	162	193	223	254	284	315	345
450	52	70	88	106	123	141	159	177	195	213
835	17	30	42	55	67	80	92	105	117	130
1900	7	10	18	34	60	99	153	225	316	431
2450	4	7	15	30	52	83	123	173	235	309
3500	2	6	16	32	55	86	124	170	225	290
5800	1	6	15	27	41	56	71	85	97	106

Stand-Alone Evaluation Exemption Levels:

Frequency (MHz)	RF Exposure Exemption Limit (mW)
<20	1000
20-48	$22480 / f^{0.5}$
48-300	600
300-6000	$1310 f^{0.6834}$
≥6000	5000

General² Comparison of FCC and IC Exemption Limits



² Non-Exhaustive

Australian Radiation Protection and Nuclear Safety Agency Requirements (ARPANSA):

RF Exposure Evaluation Limits
Occupational / Controlled Exposure:

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m ²)	Averaging Time (minutes)
0.1 – 6.943	ES	4.9 / f _{MHz}	---	30
6.943-30	660 / f _{MHz}	4.9 / f _{MHz}	--	30
30-400	61	0.16	10	30
400-2000	3 * f _{MHz} ^{0.5}	0.008 * f _{MHz} ^{0.5}	f _{MHz} / 40	30
2000-300,000	--	--	50	30

RF Exposure Evaluation Limits
General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m ²)	Averaging Time (minutes)
0.1 - 6.27	ES	2.2 / f _{MHz}	---	30
6.27 – 30	300 / f _{MHz} ^{0.7}	2.2 / f _{MHz}	--	30
30-400	27.7	0.073	2	30
400-2000	1.375 f _{MHz} ^{0.5}	0.0037* f _{MHz} ^{0.5}	f _{MHz} / 200	30
2000-300,000	--	--	10	30

Stand-Alone Evaluation Exemption Levels:

Occupational Exposure: 100mW

Portable - General Public: 20mW

Mobile – General Public: Separation distance >20cm and power < 20mW or according to IEC 62479.

Or according to ARPANSA RPS S-1 Advisory Note

European Union Compliance Requirements (ICNIRP):

RF Exposure Evaluation Limits
Occupational / Controlled Exposure:

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m ²)	Averaging Time (minutes)
0.00082-0.065	610	24.4	---	6
0.065-1.0	610	1.6/f	---	
1.0-10	610/f	1.6/f	---	6
10-400	61	0.16	10	6
400-2000	3.0 * f ^{0.5}	0.008 * f ^{0.5}	f/40	6
2000-300,000	137	0.36	50	6

RF Exposure Evaluation Limits
General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (W/m ²)	Averaging Time (minutes)
0.003-0.150	87	5.0	---	6
0.150-1.0	87	0.73/f	--	6
1.0-10	87/f ^{0.5}	0.73/f	---	6
10-400	28	0.073	2	6
400-2000	1.375 f ^{0.5}	0.0037*f ^{0.5}	f/200	6
2000-300,000	61	0.16	10	6

*Power density limit applicable >100MHz

Stand-Alone Evaluation Exemption³ Levels:

Head / Body: 20mW

Extremity: 40mW

³ EN 62479 Annex A, General Public

APPENDIX C - References

1. ACMA Radiocommunications (Electromagnetic Radio – Human Exposure) Standard, 2014.
2. AS/NZS 2772.2, Radiofrequency fields – Principles and method of measurement and computation – 3 kHz to 300 GHz, 2011.
3. Australian Radiation Protection and Nuclear Safety Agency, ARPANSA RPS S-1, Standard for Limiting Exposure to Radiofrequency Fields 100 kHz to 300 GHz, 2021.
4. New Zealand Standard, NZS 2772.1, Radiofrequency Fields Part 1: Maximum Exposure Levels 3 kHz to 300 GHz, 2009.
5. Federal Communications Commission Knowledge Database (KDB) Publication 447498, "What are the RF exposure requirements and procedures for mobile and portable devices?" As in effect on the issue date of this report.
6. Title 47 Code of Federal Regulations, Part 1.1310, "Radiofrequency radiation exposure limits." As in effect on the issue date of this report.
7. Title 47 Code of Federal Regulations, Part 2.1091, "Radiofrequency radiation exposure evaluation: mobile devices." As in effect on the issue date of this report.
8. ANSI C95.1 (2005) IEEE Standard for Safety Level with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3kHz to 300 GHz, 2005.
9. Health Canada Safety Code 6 Limits of Human Exposure to Radiofrequency Electromagnetic Energy in the Frequency Range from 3 kHz to 300 GHz, 2015.
10. Industry Canada GL-01 Guidelines for the Measurement of Radio Frequency Fields at Frequencies From 3 kHz to 300 GHz, Issue 3, March 2015.
11. Industry Canada RSS-102 Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), Issue 5, March 2015.
12. EC Council Recommendation 1999/519/EC "On the limitation of exposure of the general public to electromagnetic fields (0Hz to 300GHz)," (1999).
13. European Committee for Electrotechnical Standardization. European Normative, EN 62311 Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0 Hz to 300 GHz), 2008.
14. European Committee for Electrotechnical Standardization. European Normative, EN 62479 Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz), 2010.
15. International Commission on Non-Ionizing Radiation Protection. Guidelines for Limiting Exposure to Time-Varying Electric, Magnetic, and Electromagnetic Fields (up to 300 GHz). *Health Physics* 74 (4): 494-522; 1998.
16. International Commission on Non-Ionizing Radiation Protection Statement on the "Guidelines for limiting exposure to time-varying electric, magnetic and electromagnetic fields (up to 300 GHz). *Health Physics* 97(3):257-259, 2009.